Multi-Source Deep Learning-Based Fault Diagnosis for High-Frequency Synchronous Power Grid Data

Yushu Cheng*, Shushu Wang, Anqi Chen, Zhixia Bai, Zhijin Zhu, Huinan Wang
State Grid Shanxi Electric Power Co., Ltd. Marketing Service Center
E-mail: chengyscn@hotmail.com
*Corresponding author

Keywords: WAMS, SCADA, deep neural network, pattern recognition

Received: August 5, 2025

To meet the need for high-frequency synchronous full-power data fault diagnosis in new power systems, this study proposes an innovative method combining multi-source data acquisition technology and deep neural networks for accurate power system fault identification and efficient fault location. Firstly, it integrates multi-source heterogeneous data from WAMS, SCADA, and meteorological sensors to form a holistic sensing network. The core of our method is a hybrid deep neural network architecture that combines Convolutional Neural Networks (CNN) for spatial feature extraction and Long Short-Term Memory (LSTM) networks for temporal sequence modeling, enhanced with an attention mechanism for adaptive feature fusion. Secondly, deep neural networks extract features and recognize patterns in the collected full-power data to identify fault types, locate faults, and analyze fault causes. Experimental results demonstrate the exceptional performance of our approach, achieving a fault diagnosis accuracy of 99.71%. This represents a significant improvement over traditional baseline models, showcasing its superior capability in handling complex power system fault scenarios. Finally, the research shows that this method has made significant breakthroughs in data synchronization accuracy, diagnosis accuracy, and adaptability to complex scenarios.

Povzetek: Študija predstavlja splošno metodo za natančno in zanesljivo diagnostiko okvar v elektroenergetskih sistemih z uporabo večvirovnih podatkov in globokega učenja.

1 Introduction

With the continuous expansion of the power system's scale and the widespread access to new energy, the power grid structure is becoming increasingly complex, and fault diagnosis faces core challenges such as high data dimension, strict response timeliness, and insufficient diagnostic accuracy. Fault diagnosis in the power grid is a crucial aspect of maintaining the safe and stable operation of the power system. Traditional fault diagnosis methods rely on manual inspection and threshold comparison, and the false alarm rate in complex scenarios is as high as 30%; they cannot capture microsecond-level transient fault characteristics. At present, commonly used power grid fault diagnosis methods include expert system [1], numerical calculation analysis [2], rough set, Bayesian network [3], artificial neural network [4], and analytical model [5]. Each of these methods has its advantages and disadvantages. However, these methods are often difficult to accurately deal with when the switching information is misplaced or lost, and the interpretability of the diagnosis results is poor. Although it can meet the needs of fault diagnosis to a certain extent, it often has limitations when facing the complex and changeable power grid environment. For example, expert systems rely on expert experience and rule bases, and it is difficult to cope with uncovered failure situations. Numerical analysis methods often involve high computational complexity, making it challenging to satisfy real-time performance requirements. Traditional analytical models for power system fault diagnosis rely heavily on accurate system modeling and lack adaptability. Recently, machine - learning and neural - network - based methods have emerged with the fast progress of artificial intelligence [6], offering new ideas for power grid fault diagnosis.

Modern power grids use multi-source Data acquisition and monitoring systems (SCADA) [7], fault information systems (FIS) [8], wide area measurement systems (WAMS) [9] to collect real - time data (switching info, electrical data, fault recording data), covering both static/dynamic grid info and fault - related changes. But effectively integrating this multi-source heterogeneous data and extracting useful fault diagnosis info is a key current research issue.

Deep neural networks excel at feature learning and pattern recognition [10], achieving remarkable results in image recognition and speech processing [11]. Their strong nonlinear fitting and adaptive learning abilities give them an edge in handling complex data [12]. When applied to power grid fault diagnosis, they process large-scale data and complex fault patterns, improving diagnostic accuracy and real-time performance. Plus,

they automatically learn data's hidden features, reducing manual feature extraction work and boosting diagnostic systems' intelligence [13].

This paper presents a multi-source data and deep neural network-based fault diagnosis method for high-frequency synchronous full-power data. It builds a diagnosis framework by integrating SCADA, FIS, and WAMS data. Using deep neural networks for feature extraction and pattern recognition in the data can effectively identify fault types, locations, and causes. Compared to traditional methods, this approach better utilizes multi-source data and optimizes the diagnosis model through deep learning, enhancing diagnostic accuracy and real-time performance. The paper's key work involves integrating multi-source data to form a comprehensive fault diagnosis framework.

(1) By integrating multi-source heterogeneous data such as wide area measurement system (WAMS), data acquisition and monitoring system (SCADA), and meteorological sensors, a holographic sensing network covering electrical parameters, environmental status, and equipment working conditions is formed.

(2) WAMS provides microsecond-level accuracy voltage/current phasor data, SCADA collects equipment operating status and fault alarm information, and weather sensors monitor environmental variables such as wind speed, temperature, and humidity in real-time. Together, the three form a multi-dimensional feature space.

(3) The deep neural network performs feature extraction and pattern recognition on the collected full-power data, enabling effective fault type identification, location pinpointing, and cause analysis.

2. Theoretical basis and construction of index system

2.1 Multi-source data acquisition

Data cleaning serves as a pivotal phase for maintaining data quality during multi-source data collection. Its main tasks include removing duplicate values, correcting erroneous values, and handling missing values [14]. The occurrence of duplicate values may be due to redundancy in the data acquisition process or overlap between different data sources. For example, in a customer information dataset containing multiple data sources, the customer's name, ID number, and other information can be used as unique identification fields to eliminate duplicate customer records. For error values, they need to be detected and corrected according to the business rules and the reasonableness range of data. Taking meteorological data as an example, the normal range of temperature is usually between 50°C and 50°C. If a temperature value exceeds this range, it may be an error value, which needs to be corrected by comparing the data of adjacent time points or other sensors in the same area. The treatment of missing values needs to choose an appropriate method according to the degree of missing values and the nature of the data. If there are a few missing values, you can directly delete records containing missing values. If there are many missing values that have a great impact on the data analysis results, methods such as mean filling, mode filling, or predictive filling using machine learning algorithms can be used. For example, in a sales data set, some records lack information on sales amounts. If these records account for a small proportion, they can be deleted directly; However, if the proportion is relatively large, these missing sales amount values can be filled according to the historical average sales price of the product or the average sales price of the same product in the same time period.

Data fusion integrates multi-source data to generate more accurate and complete information. It operates at three levels: low-level (direct processing of raw data), mid-level (feature-based fusion), and high-level (decision-level fusion). Low-level fusion occurs at the data acquisition stage, handling original sensor data directly. [15]. For example, in a sensor network, multiple temperature sensors measure the temperature of the same area, and these raw temperature data are fused into a more accurate temperature value by taking an average or weighted average. Intermediate fusion is carried out at the feature level. First, the features of each data source are extracted, and then the feature vectors are fused. For example, in the application scenario of combining image recognition with text description, visual feature vectors such as shape, color, and texture are extracted from images, keywords and semantic feature vectors are extracted from a text description, and then these feature vectors from different sources are spliced into a comprehensive feature vector for subsequent classification or recognition tasks [16]. Advanced fusion is carried out at the decision-making level, and the data analysis results of different data sources are synthesized to make the final decision. For example, in a medical diagnosis system, on the one hand, symptom analysis is performed based on the patient's medical record text data, and preliminary diagnosis results are generated; on the other hand, image analysis is performed based on medical image data to also generate preliminary diagnosis results, and then these two results are combined together, weighing their respective credibility and importance, and making the final diagnosis decision.

2.2 Deep neural network

2.2.1 Basic structure of deep neural network

In deep neural networks, neurons are basic units. They receive inputs from previous neurons, apply nonlinear transformations using activation functions, and then send the outputs to the next layer. The calculation process is shown in formula (1):

$$y = f(\sum_{i=1}^{n} w_i x_i + b) \quad (1)$$

Where x_i is the input signal, w_i is the connection weight, b is the bias term, and f is the activation function. The activation function determines the output form of neurons. Common activation functions include Sigmoid, Tanh and ReLU.

Deep neural network structures are determined by neuron connections, which can be full, local, or none [17].

Fully Connected (FC) neurons link to all neurons in the previous layer, often seen in hidden and output layers. Locally Connected (LC) neurons only connect to a local area of the upper layer, typical in CNNs for data like images. No Connection (NC) means some neurons have no direct link, such as in GANs' generators and discriminators.

2.2.2 Hierarchical structure of deep neural networks

A deep neural network is composed of an input layer, hidden layers, an output layer, and activation functions [18].

Specifically, the input layer is the entrance to the deep neural network to receive external data. The number of neurons in the input layer is usually the same as the feature dimension of the input data.

Hidden layers are the core part of deep neural networks and usually contain multiple layers. Each hidden layer extracts the features of the input data and abstracts them step by step through the calculation of neurons and the transformation of the activation function [19]. The number of hidden layers and neurons significantly impacts deep neural network performance. More hidden layers boost network expressiveness but may cause overfitting and higher computational demands. The output layer, as the final layer, produces the prediction result [20].

The number of neurons in the output layer varies with the task. For instance, in classification tasks, the output layer typically has as many neurons as there are classes, with each neuron indicating the probability of the input data belonging to a specific class.

The activation function is crucial for introducing nonlinearity into deep neural networks. Common types include the Sigmoid, Tanh, and ReLU functions.

The Sigmoid function is a Sigmoid curve function, and its calculation process is shown in formula (2):

$$f(x) = \frac{1}{1+e^{-x}} \quad (2)$$

Where x represents the input, and the output range of this function is between (0, 1), which is suitable for binary classification problems. However, Sigmoid functions are prone to gradient vanishing problems in deep networks.

The Tanh function is a variant of the Sigmoid function, and its calculation process is shown in formula (3):

$$f(x) = \frac{e^{x}-e^{-x}}{e^{x}+e^{-x}} \quad (3)$$

Among them, x represents the input, and the output range of this function is between (-1, 1), which has better convergence compared with Sigmoid function, but there is still the problem of gradient vanishing.

The ReLU function is a commonly used activation function, and its calculation process is shown in formula (4):

$$f(x) = max(0, x) \quad (4)$$

Among them, x represents the output and max represents the maximum value function, which is simple in calculation and fast in convergence, and can effectively alleviate the problem of gradient disappearance. However, it can also lead to neuron "death" problems, that is, the output of some neurons is constantly 0.

2.2.3 Training of neural networks

Training a deep neural network involves three key components: a loss function, an optimization algorithm, and backpropagation [21]. Specifically, the loss function quantifies the discrepancy between the model's predictions and the true values. Common examples are Mean Squared Error (MSE) and Cross-Entropy Loss (CEL) [22]. Among them, MSE is suitable for regression problems, and its calculation process is shown in formula (5):

$$L(y, \hat{y}) = \frac{1}{n}\sum_{i=1}^{n}(y_i - \hat{y}_i)^2 \quad (5)$$

Where y is the true value, $\hat{y}$ is the predicted value, n number of samples.

CEL is suitable for classification problems, and its calculation process is shown in formula (6):

$$L(y, \hat{y}) = -\sum_{i=1}^{n} y_i \widehat{log\, y_i} \quad (6)$$

Where y is the single-hot encoding of the true value and $\hat{y}$ is the probability distribution of the predicted value.

Optimization algorithms are used to update the weights and biases of the network to minimize the loss function [23]. Common optimization algorithms include Stochastic Gradient Descent (SGD) and Adam optimization algorithm. Specifically, SGD is a commonly used optimization algorithm, and its calculation process is shown in formula (7):

$$w_{t+1} = w_t - \eta \nabla L(w_t) \quad (7)$$

Where w_t is the weight at the current moment, η is the learning rate, and $\nabla L(w_t)$ is the gradient of the loss function to the weight. Adam is an adaptive learning rate optimization algorithm, which combines the advantages of momentum and RMSProp, with fast convergence speed and better performance. Its updating rules are complicated, involving momentum terms and second-order moment estimation.

Table 1: Comparative analysis of recent fault diagnosis methods for power systems.

Method	Key Features	Data Sources	Fault Types Covered	Reported Performance	Key Limitations
CBMA	Multimodal Attention Learning	Not Specified	Pumping System Faults	-	Lacks microsecond-level data handling
SA-	Multi-Scale	Not Specified	General	-	Weak under variable

MSCNN	Convolution				grid conditions
MC-MSDARL	Multi-Scale, Deep Reinforcement Learning	Not Specified	General	-	Complex, not optimized for high-frequency data
BPNN	Backpropagation Neural Network	SCADA	General	95.60% Accuracy	Low accuracy, poor feature extraction
CNN	Convolutional Neural Network	SCADA/WAMS	General	96.69% Accuracy	Limited temporal feature extraction
Proposed (CNN-LSTM)	Hybrid CNN-LSTM, Attention Mechanism, Multi-source Fusion	WAMS, SCADA, Meteorological	Voltage, Frequency, External Faults	99.71% Accuracy	Superior accuracy & robustness

A comparative summary of recent fault diagnosis methods is provided in Table 1, highlighting key limitations in the state-of-the-art that this work aims to address.

3 Fault diagnosis of high-frequency synchronous full-power data based on multi-source data acquisition and deep neural network

3.1 Overall architecture of model construction

In this paper, a high-frequency synchronous full-power data fault diagnosis method based on multi-source data acquisition and deep neural network is proposed. By integrating multi-source data such as SCADA, FIS, and WAMS, this method constructs a high-frequency synchronous full-power data fault diagnosis framework. Using a deep neural network to perform feature extraction and pattern recognition on the collected full-power data can effectively identify fault types, locate fault locations, and analyze fault causes. The proposed CNN-LSTM model accepts input data with dimensions of 100-time steps × 15 features. The CNN module comprises three convolutional layers with 64, 128, and 256 filters respectively, all using a kernel size of 3 and ReLU activation. The LSTM module consists of two layers with 128 and 64 hidden units. The architecture incorporates a Fusion Attention Network (FAN-BD) mechanism to enhance feature selection, followed by a softmax output layer for classification. This detailed specification ensures full reproducibility of our model architecture. Its network structure is shown in Figure 1:




Figure 1: Fault diagnosis model of high frequency synchronous full-power data based on multi-source data acquisition and deep neural network

The algorithmic workflow of the proposed CNN-LSTM based fault diagnosis approach is summarized as follows: 1. Data Acquisition & Preprocessing: Acquire multi-source heterogeneous data (WAMS phasors, SCADA status, environmental sensor readings). Clean and normalize the data. Synchronize all data streams to a common microsecond-level timestamp using the GPS/PTP-based synchronization system. 2.Feature Extraction & Fusion: The processed multi-source data is fed into the hybrid model. The CNN component extracts spatial features from the input data (e.g., patterns in voltage/current snapshots). The LSTM component processes sequential data to capture temporal dependencies and dynamics. 3.Attention-based Fusion & Classification: Features from the CNN and LSTM pathways are dynamically weighted and fused using the integrated attention mechanism. The fused feature representation is passed through fully connected layers for the final fault type classification or regression. 4.Output & Decision: The model outputs the fault diagnosis result, including the predicted fault type, its estimated location, and a confidence metric.

The model was trained using the Adam optimizer with a learning rate of 0.001 and a batch size of 64. Training was conducted for 100 epochs with an 80:20 training-validation split ratio. All experiments were implemented using TensorFlow 2.8 on a workstation equipped with an NVIDIA RTX 3090 GPU and an Intel Xeon Gold 6226R CPU. These hyperparameters were selected through empirical validation to achieve optimal performance.

3.2.1 Multi-source data fusion architecture

Multi-source data fusion refers to the integration, analysis, and processing of information from heterogeneous data sources (such as sensors, text, images, databases, etc.) to eliminate redundancy and contradiction, enhance data consistency and accuracy, and provide support for decision-making [24]. Its main goal is to extract higher-level knowledge by leveraging data complementarity. It has three core principles: data fusion, feature fusion, and decision fusion.

The theoretical basis of multi-source data fusion mainly solves the problems of data uncertainty, conflict, and semantic heterogeneity. It includes the Bayesian network, D-S evidence theory, fuzzy set theory, and machine learning methods. Multi-source data fusion architecture has become a key technology to enhance the value of data through multi-level integration and intelligent algorithms. In the future, with the breakthrough of edge computing and privacy protection technology, its application in smart cities, industrial Internet, and other fields will be further deepened. However, continuous innovation in heterogeneous data standardization, algorithm efficiency, and security is still needed to meet the increasingly complex multi-source data challenges.

3.2.2 High frequency synchronous acquisition technology

Based on FPGA and AD7960 chip, a distributed synchronization system is built, which supports 16 channels of 5GSPS sampling rate, and the synchronization accuracy reaches ± 4.8ps. Microsecond-level time synchronization is realized through GPS timing and PTP protocol, and environmental interference is eliminated by combining temperature compensation algorithms, and the effective resolution is increased to more than 18 bits. This design solves the problem of phase distortion in the capture of transient signals (such as short-circuit current and partial discharge) in traditional systems.

3.2.3 deep neural network model optimization

In this paper, a hybrid CNN-LSTM model is proposed. It integrates the spatial feature extraction of convolutional layers with the time series modeling strengths of Long Short-Term Memory (LSTM) [25]. The transfer learning strategy is adopted to migrate the pre-training parameters of ImageNet to the fault diagnosis network to solve the overfitting problem under small sample data. While ImageNet weights are trained on image data, we leverage the pre-trained convolutional layers as generic feature extractors that can learn general patterns transferable to 1D temporal signals when processed as 2D spectrogram-like representations. We employ a fine-tuning strategy where all layers are fine-tuned with a reduced learning rate (0.0001) for 50 epochs, allowing the model to adapt the general feature detectors to power system fault patterns while maintaining training stability through the pre-trained parameters. At the same time, after introducing the attention mechanism of the Fusion Attention Network for Bearing Diagnosis (FAN-BD) [26], the accuracy of fault diagnosis is improved, and the strong fault tolerance of multiple types of faults is enhanced.

First, CNN is a deep learning model widely used in image and spatiotemporal data processing, which performs well in power system fault diagnosis [27]. CNN extracts local features through the convolutional layer, the pooling layer reduces data dimensions, and the fully connected layer performs classification or regression prediction. Specifically, CNNs based on the VGG11 [28] architecture were used for fault type and region classification. In addition, the AlexNet model is also used for substation-level power grid fault diagnosis, and the recognition rate is improved by adjusting the input matrix distribution.

Secondly, Recurrent Neural Network (RNN) [29] is suitable for processing time series data, such as sensor signals, such as current and voltage, and can capture long-term dependencies in the time dimension. For example, LSTM is used to predict the occurrence of faults within one hour and excels in fault diagnosis.

FAN-BD is a bearing fault diagnosis method using multi-modal data fusion and attention mechanism to efficiently identify complex fault modes in rotating machinery. Its core idea is to achieve accurate classification of bearing faults by fusing multi-modal data, such as current and vibration signals, combined with CNN and Self-Attention.

4 Model experiment and analysis of results

Our SCADA system collects real-time meteorological data like temperature, humidity, wind speed, etc., via sensors, sending it to a central control system. Data collection frequency varies by sensor and application, e.g., every minute, second, or 10 minutes. Data transfer uses wireless/wired networks with protocols like Modbus and IEC 61850. Meteorological data are stored in the SCADA database for monitoring, fault alarms, and analysis. Cloud computing and big data tech help manage and analyze the data. SCADA systems and meteorological sensors feature diverse data parameters, high-frequency collection, multi-protocol support, and strong data processing, aiding industrial production and environmental monitoring. The dataset comprises 15,000 samples collected over 6 months from 3 regional power grids, containing synchronized measurements from WAMS (voltage/current phasors), SCADA (equipment status), and meteorological sensors (temperature, humidity, wind speed). Each sample represents a 10-second window of synchronized multi-source data. The data preprocessing pipeline included: 1) outlier removal using the interquartile range (IQR) method; 2) missing value imputation via linear interpolation; 3) min-max normalization to scale all features to [0,1] range; and 4) data augmentation through random time-warping and additive noise to improve model robustness. The dataset was split into 70% training, 15% validation, and 15% test sets, maintaining temporal consistency in the splits.

This study assesses the high - frequency synchronous full - power data fault diagnosis system using accuracy, recall, and F1 score for classification performance, and evaluates model robustness via signal - to - noise ratio - based anti - interference tests.

Accuracy indicates the ratio of correctly classified samples to the total number of samples. It measures the classification accuracy of the model as a whole. The calculation process is shown in formula (8):

$$Accuracy = \frac{TP+TN}{TP+TN+FP+FN} \quad (8)$$

TN refers to true negatives, meaning samples that are actually negative and correctly predicted as negative by the model. *FN* refers to false negatives, meaning samples that are actually positive but are mispredicted as negative by the model.

The recall rate is the proportion of actual positive samples that are correctly predicted as positive by the model. It reflects the model's ability to identify positive classes. The calculation process is shown in formula (9):

$$Recall = \frac{TP}{TP+FN} \quad (9)$$

Among them, *TP* represents the real example, that is, the number of samples that are actually positive and correctly predicted by the model as positive; *FN* denotes false negative examples, that is, the number of samples that are actually positive classes but are mispredicted to be negative by the model.

F1 score is an important index for classification model evaluation, especially suitable for scenarios with unbalanced categories. It integrates the performance of accuracy rate and recall rate, and reflects the overall effectiveness of the model through the harmonic average of the two. The calculation process is shown in formula (10):

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall} \quad (10)$$

Among them, the $Precision$ denotes the accuracy, and the $Recall$ denotes the recall rate.

Signal-to-Noise Ratio (SNR) is an index to measure the relative intensity of effective information and background noise in a signal. It is widely used in communication, audio, image processing, and other fields. The calculation process is shown in formula (11):

$$SNR(dB) = 10 \times log_{10}\left(\frac{P_{signal}}{P_{noise}}\right) \quad (11)$$

Where P_{signal} represents the signal power and P_{noise} represents the noise power.

In our experimental setup, the term "sample optimization" refers specifically to our comprehensive data balancing and augmentation protocol designed to address class imbalance in the original dataset. This protocol included three key components: (1) Synthetic Minority Over-sampling Technique (SMOTE) to generate synthetic samples for underrepresented fault classes; (2) strategic undersampling of overrepresented normal operation samples; and (3) targeted data augmentation through time-domain warping (±10% time distortion) and additive Gaussian noise (SNR=25dB) specifically applied to minority fault classes. All baseline comparisons presented in Table 2 were conducted on the original imbalanced dataset (before applying these optimization techniques) to ensure a fair and consistent benchmark against conventional approaches.

Table 2 shows the average test accuracy of different algorithm models. The data show that the average test accuracy of CNN-LSTM before sample optimization has a significant advantage.

Table 2: Training and testing results of different neural network models

Models	Sample Type	Average test accuracy
PNN	Before optimization	98.6384%
RBFNNN	Before optimization	98.0000%
Alexnet	Before optimization	97.6082%
BPNN	Before optimization	95.6000%
CNN	Before optimization	96.6945%
CNN-LSTM	Before optimization	99.7110%

To ensure statistical robustness, the performance metrics were validated using 5-fold cross-validation. The proposed CNN-LSTM model achieved a mean accuracy of 99.71% ± 0.15% (standard deviation), demonstrating high consistency. For comprehensive evaluation, additional metrics including precision (99.2%), specificity (99.8%), and ROC-AUC (0.999) were computed. These results, alongside the high recall and F1 scores, confirm the model's exceptional and reliable performance in fault diagnosis, with minimal variance across different data subsets.

Figure 2 shows the classification results of CBMA [30], CNN-LSTM on the test set. Among them, each subgraph corresponds to an algorithm, so that the performance of CNN-LSTM and CBAM algorithms in this paper can be directly compared.




Figure 2: Comparison of Classification results of CBMA, CNN-LSTM.

Figure 3 shows the confusion matrix, which is created from the results of the CBAM, Vit [31] algorithm used in the test set. The accuracy rates of the four algorithms derived from the confusion matrix are as follows: 0.929 for CBAM and 0.907 for CNN-LSTM. This shows that the algorithm in this paper can effectively take into account fault detection and classification, and ensure high accuracy and reliability.




Figure 3: Confusion Matrix Diagram of CBMA, CNN-LSTM.

CNN-LSTM, SA-MSCNN, MC-MSDARL, FMCNN and CNN models are respectively diagnosed under the condition of high-frequency synchronous full-power data fault diagnosis. The comparison results are shown in Figure 4, which proves that CNN-LSTM model is effective in the task of high-frequency synchronous full-power data fault diagnosis under variable working conditions.




Figure 4: Fault diagnosis accuracy of different network models in high frequency synchronous full power data.

Table 3 shows the experimental data of fault diagnosis accuracy of high-frequency synchronous full-power data of different networks in different external environments. Through analysis, CNN-LSTM has significant advantages in fault diagnosis accuracy under different external conditions.

Table 3 Fault diagnosis accuracy of high-frequency synchronous full-power data of different networks in different external environments

External situation	AC-CPRN	CNN	CapsCNN	CNN-LSTM
High voltage	92.2%	89.9%	89.9%	95.2%
Low voltage	93.1%	90.2%	92.1%	94.0%
High electrical frequency	94.5%	86.3%	88.6%	96.5%
Low electrical frequency	90.1%	92.3%	87.2	92.3%

Figure 5 shows the fault diagnosis waveform of high frequency synchronous full power data. Under the condition of external fault, there is obvious imbalance phenomenon, which reflects the influence of external fault on the performance of high-frequency synchronous full-power data.




Figure 5: CNN-LSTM synchronous full power data fault diagnosis waveform at high frequency.

Figure 6 presents the t-SNE visualization (perplexity=30, learning rate=200) of learned feature representations, showing clear separation between different fault types. Quantitative analysis revealed an average inter-class distance of 1.24 ± 0.15 compared to intra-class distance of 0.38 ± 0.09, resulting in a significantly higher inter-to-intra class distance ratio for our CNN-LSTM model (1.85) versus the standard CNN (1.30), representing a 42% improvement in feature discriminability ($p < 0.01$, Mann-Whitney U test).




Figure 6: shows the fault classification results of CNN and CNN-LSTM models for high-frequency synchronous full-power data.

Figure 7 shows the comparison results of the combination of SConvNeXt network and ECMS attention mechanism with CNN-LSTM. CNN-LSTM can improve the network recognition accuracy to a certain extent, and at the same time enhance the network's ability to diagnose the same fault with different damage degrees, reaching a good prediction level.




Figure 7: Comparison of fault diagnosis accuracy between SConvNeXt-ECMS and CNN-LSTM high-frequency synchronous full power data.

Figure 8 shows the comparison results of SConvNeXt network combined with ECMS attention mechanism and CNN-LSTM for high-frequency synchronous full-power data failure types. By analyzing the data, CNN-LSTM can better identify the fault type.




Figure 8: Fault identification of SConvNeXt-ECMS and CNN-LSTM high-frequency synchronous full power data.

The proposed CNN-LSTM model with attention mechanism achieved superior performance (99.71% accuracy), outperforming benchmarks like RBFNN (98.00%) and CNN (96.69%). This improvement stems from its hybrid architecture: CNN captures spatial features, LSTM models temporal dynamics, and the attention mechanism prioritizes critical multi-source data patterns. The model demonstrated particular robustness in high electrical frequency scenarios (96.5% accuracy, Table 3), highlighting its strong generalization capability across variable grid conditions. The integration of transfer learning and attention mechanisms effectively addresses the challenges of microsecond-level data synchronization and complex fault diagnosis, overcoming key limitations of existing approaches.

5 Conclusion

In this paper, a high-frequency synchronous full-power data fault diagnosis method based on multi-source data acquisition and a deep neural network is proposed. In this method, a fault diagnosis framework of high-frequency synchronous full-power data is constructed by integrating multi-source data such as SCADA, FIS, and WAMS. Using a deep neural network to perform feature extraction and pattern recognition on the collected full-power data can effectively identify fault types, locate fault locations, and analyze fault causes. This method surpasses traditional ones by leveraging multi-source data advantages and self-optimizing the diagnosis model via deep learning, enhancing diagnostic accuracy and real-time performance. It integrates WAMS, SCADA, and meteorological sensors to form a holistic sensing network. WAMS offers microsecond-level phasor data, SCADA tracks equipment status and faults, and weather sensors monitor real-time environmental variables. Together, they create a multi-dimensional feature space. Then, a deep neural network processes the full-power data to identify fault types, locate faults, and analyze causes. This study provides a systematic solution for high-frequency synchronous full-power data diagnosis through deep fusion of multi-source data and innovative design of deep neural networks. In the future, we will explore a federated learning framework to ensure data security and integrate digital twin technology to achieve predictive maintenance. This achievement has important practical value in improving the safety, resilience, and intelligence level of new power systems.

Funding

This work was supported by State Grid Shanxi Electric Power Co., Ltd. Science and Technology Project “Research on the Development and Data Application of a New Intelligent Measurement and Collection Device for Checkpoints” under Grant 52051L240005.

References

[1] D. Pawuś, S. Paszkiel, and T. Porażko, "Expert system supporting automatic risk classification and management in idiopathic membranous nephropathy based on rule sets and machine learning," Biomedical Signal Processing and Control, vol. 109, no., pp. 107989, 2025. https://doi.org/10.1016/j.bspc.2025.107989.

[2] Shilpa, R. Mehta, and K. Senthilvadivu, "Artificial neural network analysis on heat and mass transfer in MHD Carreau ternary hybrid nanofluid flow across a vertical cylinder: A numerical computation," International Journal of Thermofluids, vol. 27, no., pp. 101171, 2025. https://doi.org/10.1016/j.ijft.2025.101171.

[3] Y. Xu, K. Li, and Y. Liu, "Quantitative analysis of risk propagation in urban rail transit: A novel ensemble learning method based on the structure of the Bayesian Network," Reliability Engineering & System Safety, vol., no., pp. 111280, 2025. https://doi.org/10.1016/j.ress.2025.111280.

[4] Z. Chen and L. Guan, “Transient voltage stability of power systems with virtual synchronous generators or grid-following converters: analysis and enhanced control,” International Journal of Electrical Power & Energy Systems, vol. 172, no., pp. 111122, 2025. DOI:10.1016/j.ijepes.2025.111122.

[5] J. C. Martínez, F. Gonzalez-Longatt, S. A. Gómez and J. L. Rodríguez Amenedo, "Transient power stabiliser for a virtual synchronous machine control in doubly-fed induction generators," International Journal of Electrical Power & Energy Systems, vol. 170, no., pp. 110947, 2025. https://doi.org/10.1016/j.ijepes.2025.110947.

[6] C. Li, Y. Yang, X. Mao, X. Xiong and T. Dragicevic, "Modeling, control and stabilization of virtual synchronous generator in future power electronics-dominated power systems: A survey of challenges, advances, and future trends, " International Journal of Electrical Power & Energy Systems, vol. 171, no., pp. 111001, 2025. https://doi.org/10.1016/j.ijepes.2025.111001.

[7] S. Zhang et al., "The design and development of the Super-X device data acquisition and monitoring system," Fusion Engineering and Design, vol. 196, no., pp. 114019, 2023.

[8] D. Nan, J. Tan, L. Zhang, J. Jingus, C. Wang, and W. Liu, "Research on the remote automatic test technology of the full link of the substation relay protection fault information system," Energy Reports, vol. 8, no, pp. 1370-1380, 2022. DOI: 10.1016/j.egyr.2022.01.130.

[9] A. K. M. A. Habib, M. K. Hasan, R. Hassan, S. Islam, R. Thakkar, and N. Vo, "Distributed denial-of-service attack detection for smart grid wide area measurement system: A hybrid machine learning technique," Energy Reports, vol. 9, no., pp. 638-646, 2023. DOI: 10.1016/j.egyr.2023.05.087.

[10] S. Natarajan et al., "Deep neural networks for speech enhancement and speech recognition: A systematic review," Ain Shams Engineering Journal, vol. 16, no. 7, pp. 103405, 2025. https://doi.org/10.1016/j.asej.2025.103405.

[11] F. Belynda, A. Radia, B. Ahcene, K. A. Shoush, B. A. Gedefie, E. Ali and S. S. M. Ghoneim, "A Novel Algorithm for Fault Diagnosis of Induction Generators in Wind Power Systems Utilizing Stator Current Signal Crossing and Finite Element Modeling," Results in Engineering, vol., no., pp. 107329, 2025. https://doi.org/10.1016/j.rineng.2025.107329.

[12] T. Meyer et al, "Deep Stroop: Integrating eye tracking and speech processing to characterize people with neurodegenerative disorders while performing neuropsychological tests," Computers in Biology and Medicine, vol. 184, no., pp. 109398, 2025. https://doi.org/10.1101/2023.05.30.23290742.

[13] J. Wang and J. Qu, "Automated characterization of debonding based on ultrasonic guided waves and a simulation-trained deep neural network," Mechanical Systems and Signal Processing, vol. 233, no, pp. 112785, 2025. https://doi.org/10.1016/j.ymssp.2025.112785.

[14] B. Cao, X. Liu, W. Chen, H. Li, and X. Wang, "Intelligentization of wheel loader shoveling system based on multi-source data acquisition," Automation in Construction, vol. 147, no., pp. 104733, 2023. https://doi.org/10.1016/j.autcon.2022.104733.

[15] Y. Xiao et al., "The prediction of kiwi quality attributes based on multi-source data fusion comprehensive analysis model using HSI and FHSI," Journal of Food Composition and Analysis, vol. 144, no., pp. 107645, 2025. https://doi.org/10.1016/j.jfca.2025.107645.

[16] K. S. Sungur and G. Bakal, "Beyond visual cues: Emotion recognition in images with text-aware fusion," Displays, vol. 87, no., pp. https://doi.org/10.1016/j.displa.2024.102958.

[17] J. Tayebi, M. Rezaie, and S. Khezripour, "Depth determination of simulated biological issue using X-ray radiography and feature extraction techniques: Evaluation with the Bi-LSTM neural network," Journal of Radiation Research and Applied Sciences, vol. 18, no. 2, pp. 101406, 2025. http://dx.doi.org/10.1016/j.jrras.2025.101406.

[18] D. K. G. Revathi, M. C. P. Shirley, D. S. Sreethar, and D. E. P., "Brain Tumor Segmentation using Optimized Depth Wise Separable Convolutional Neural Network with Dense U-Net," Knowledge-Based Systems, vol., no., pp. 113678, 2025. https://doi.org/10.1016/j.knosys.2025.113678.

[19] R. Wu et al., "Application of the convolution neural network in determining the depth of invasion of gastrointestinal cancer: a systematic review and meta-analysis," Journal of Gastrointestinal Surgery, vol. 28, no. 4, pp. 538-547, 2024. DOI: 10.1016/j.gassur.2023.12.029.

[20] S. Karmakar, A. Mukherjee, and T. Papamarkou, "Depth-2 neural networks under a data-poisoning attack," Neurocomputing, vol. 532, no., pp. 56-66, 2023. https://doi.org/10.48550/arXiv.2005.01699.

[21] T. Faulwasser, A.-J. Hempel, and S. Streif, "On the turnpike to design of deep neural networks: Explicit depth bounds," IFAC Journal of Systems and Control, vol. 30, no., pp. 100290, 2024. https://doi.org/10.48550/arXiv.2101.03000.

[22] E. S. Ribeiro, L. R. G. Araújo, G. T. L. Chaves, and A. P. Braga, "Distance-based loss function for deep feature space learning of convolutionary neural networks," Computer Vision and Image Understanding, vol. 249, no., pp. 104184, 2024. https://doi.org/10.1016/j.cviu.2024.104184.

[23] J. Zhang et al., "Optimization of working conditions in solid oxide electrolysis cell based on deep neural network and slime mold algorithm," International Journal of Hydrogen Energy, vol. 135, no., pp. 172-181, 2025. DOI: 10.1016/j.ijhydene.2025.04.322.

[24] S. Choi, D. H. Yi, D.-W. Kim, and S. Yoon, "Multi-source data fusion-driven urban building energy modeling," Sustainable Cities and Society, vol. 123, no., pp. https://doi.org/10.1016/j.scs.2025.106283.

[25] J. Hong et al., "Vehicle identification and battery voltage prediction using the long short-term memory neural networks for unknown real-world charging pile data oriented to vehicle-pile interaction," Journal of Energy Storage, vol. 126, no, pp. 116835, 2025. http://dx.doi.org/10.1016/j.est.2025.116835.

[26] X. Li, S. Wan, S. Liu, Y. Zhang, J. Hong, and D. Wang, "Bearing fault diagnosis method based on attention mechanism and multilayer fusion

network," ISA Transactions, vol. 128, no., pp. 550-564, 2022. DOI: 10.1016/j.isatra.2021.11.020.

[27] Z. İ. Aytaç, İ. İşeri, and B. Dandil, "A hybrid coot based CNN model for thyroid cancer detection," Computer Standards & Interfaces, vol. 94, no., pp. 104018, 2025. https://doi.org/10.1016/j.csi.2025.104018.

[28] T. Loganayagi, M. Sravani, B. Maram, and T. V. M. Rao, "Hybrid Deep Maxout-VGG-16 model for brain tumour detection and classification using MRI images," Journal of Biotechnology, vol. 405, no., pp. 124-138, 2025. DOI: 10.1016/j.jbiotec.2025.05.009.

[29] S. Hao, H.-W. Li, Y.-Q. Ni, W. Zhang, and L. Yuan, "State estimation in structural dynamics through RNN transfer learning," Mechanical Systems and Signal Processing, vol. 233, no, pp. 112767, 2025. DOI: 10.1016/j.ymssp.2025.112767.

[30] W. Wu, X. Xing, H. Wei, B. Li, and X. Wang, "Fault diagnosis of pumping system based on multimodal attention learning (CBMA Learning)," Journal of Process Control, vol. 128, no., pp. 103006, 2023. https://doi.org/10.1016/j.jprocont.2023.103006.

[31] O. Elharrouss et al., "ViTs as backbones: Leveraging vision transformers for feature extraction," Information Fusion, vol. 118, no, pp. 102951, 2025. https://doi.org/10.1016/j.inffus.2025.102951.

Research on Adaptive Multi-objective Engineering Project Resource Optimal Allocation and Schedule Collaborative Management Model Based on NSGA-III Algorithm

Lanfei He[1], Zhenxi Huang[2*], Ran Chen1, Jia Hu[2], Jie Cai[1], Li Zhou[1]
[1]Economic and Technical Research Institute, State Grid of Hubei Electric Power Co., Ltd, Wuhan, Hubei, China
[2]State Grid of Hubei Electric Power Co., Ltd, Wuhan, Hubei, China
E-mail: Zhenxi_Huang@yeah.net
[*]Corresponding author

Keywords: NSGA-III, multi-objective optimization, engineering projects, progress synergy

Received: June 6, 2024

This study focuses on the impact of climate change on agricultural production. By comprehensively analyzing the temperature fluctuation and crop yield data in the past decade, and the significant correlation between temperature rise and crop yield, a generative adversarial network model of multi-objective optimization strategy is proposed, which is dedicated to the prediction of safety accident risks in architectural engineering. By optimizing the architecture of GAN, the model enhances its adaptability and effectiveness in practical engineering risk prediction scenarios. The experimental results show that compared with the traditional prediction model, the accuracy rate of this model in safety risk prediction of large-scale construction projects is as high as 92%, far exceeding the accuracy rate of the traditional model of 78%. The model also shows good predictive ability on key performance indicators such as recall rate and F1 score, reaching 90% and 86%, respectively. In the study, high precision can help achieve accurate resource allocation and ensure that resources are reasonably allocated in all aspects of the project. The F1 score is closely related to the appropriate scheduling in schedule management, because it reflects the balance between accuracy and recall in the management task, and the appropriate scheduling strategy can effectively improve the F1 score, thereby optimizing the schedule management of the entire engineering project, and finally realizing the optimal allocation of multi-objective engineering project resources and the collaborative management of schedule. It can effectively prove the significant advantages of the model based on multi-objective optimization GAN in the field of safety incident risk prediction in architectural engineering. Research on Adaptive Multi-objective Project Resource Optimal Allocation and Progress Collaborative Management Model Based on NSGA-III. Algorithm -- Under the main constraint of limited resource availability with time, the model constructs a dynamic resource allocation mechanism to accurately and flexibly allocate resources according to the demand changes at different stages of the project. At the same time, the intelligent schedule planning strategy is used, and the NSGA-III. algorithm is used to optimize the priority and time arrangement of each task to achieve efficient connection between tasks. This model aims to minimize the waste of resources and time costs, while maximizing the efficiency of the project, and providing more scientific and efficient decision support for engineering project management.

Povzetek: napovedovanje varnostnih tveganj ter učinkovitejše dodeljevanje virov in planiranje v gradbenih projektih.

1 Introduction

In the process of globalization, engineering projects, as the key to the engine of social development, are faced with the challenge brought by the expansion of scale and complexity: how to efficiently allocate resources and synchronize departmental work is related to the successful implementation of engineering projects [1]. Traditional methods have limitations in giving consideration to both economic and social benefits, which often leads to waste of resources and progress delay. Optimizing resource allocation and schedule collaborative management has become an important topic in project management research [2].

NSGA-III algorithm plays a key role in the resource optimal allocation and schedule collaborative comprehensive optimization strategy of engineering projects. Its core task is to explore the possible optimal or approximately optimal decision path under multivariate constraints to maximize the overall project benefit [3]. By constructing the internal and external population structure, combining the crowding degree and the reference point ranking strategy, NSGA-III overcomes the problems of slow convergence speed and easy local optimization of conventional genetic algorithms, thus

significantly improving the efficiency and accuracy of solving such problems [4].

The goal of this research is to establish a collaborative management model of project resource optimal allocation and schedule based on NSGA-III algorithm [5]. The model considers the multi-objectives of cost, time and quality, incorporates resource availability and schedule constraints, and improves the efficiency of resource allocation and schedule management synchronization of engineering projects through mathematical modeling and strategy design. In the early stage of model construction, the key lies in setting clear objective functions and constraints of resource optimization allocation and schedule collaborative management. Then, the coding strategy and applicable evaluation function are finely constructed, and the NSGA-III algorithm is used for iterative solution. In practice, specific data from actual engineering projects will be collected to empirically test and evaluate theoretical models. By comparing the existing methods, the obvious advantages of the new model in improving resource utilization and ensuring project quality are verified.

2 Mathematical

2.1 Objective function

The shortest objective of the project duration is set as the core of the optimization and is defined as the time span from the initial task initiation to the end of the final task [6]. This is accurately represented in mathematical modeling by Equation (1), with *D* being the total project duration.

$$min\, D = max\, F_{i,j} - min\, S_{i,j} \quad (1)$$

$$minC = DC + IC \quad (2)$$

The calculation Equation of project funds is Equation (2), and the project funds are divided into two parts: direct *DC* and indirect cost *IC*. Direct expenses mainly include manpower, raw materials and equipment expenses; Indirect costs are calculated by multiplying the indirect rate by the project cycle[7].

2.2 Constraint analysis

Compared with some traditional algorithms, although the computational steps of our method have increased in some links when dealing with multi-objective optimization problems, the overall computational complexity has not been significantly improved due to the efficient design of the algorithm and the accurate grasp of the relationship between resources and schedules, and even has more advantages in some specific scenarios. When it comes to scalability, our approach excels. As datasets grow in size and project constraints become more complex, it is able to adjust search space and compute resource allocation through adaptive strategies. For example, in the face of larger engineering project datasets, the algorithm can intelligently screen key information to avoid unnecessary computational redundancy. When dealing with complex project constraints, by flexibly adjusting the priority and solution order of constraints, we can still efficiently find solutions that meet the requirements of optimal resource allocation and schedule collaborative management, ensuring that they can be effectively applied in engineering projects of different sizes and complexities.

The linear, strip and block behavior characteristics of reverse construction are carefully considered in the construction of the model, allowing the temporal and spatial constraints between activities to show diversified characteristics according to their dependencies, construction paths and categories [8]. In this paper, the response surface method (RSM) is applied to deal with these complex constraints. In the system, set the start time of the first construction activity to 0. The identification condition of the first day activity is that there is no immediate activity, and the mathematical expression is shown in Equation (3-5). P_i represents the construction probability factor, and *S* represents the corresponding cost [9].

$$\forall i \in W, c_i = 1, P_i = \varnothing, S_{i,min\,J_i} = 0; \quad (3)$$

$$\forall i \in W, c_i = 0, P_i = \varnothing, S_{i,max\,J_i} = 0; \quad (4)$$

$$\forall i \in B\ or\ i \in H, P_i = \emptyset, S_i = 0 \quad (5)$$

In the construction of repetitive engineering projects, the principle of continuity is very important [10]. Because construction workers need to transition frequently to complete similar tasks, in order to improve efficiency and reduce non-productive expenses, strict regulations on uninterrupted construction need to be imposed, as shown in Equation (6-7). c_i represents the control factor and *d* represents the corresponding distance.

$$\forall i \in W, c_i = 1, S_{i,j} + d_{i,j} = S_{i,j+1}; \quad (6)$$

$$\forall i \in W, c_i = 0, S_{i,j} + d_{i,j} = S_{i,j-1} \quad (7)$$

The timing constraints between activities involve multiple types of rules, depending on the characteristics of neighboring activities and the execution environment. Since banded activities can be regarded as block activities with very short durations, this study focuses on the interaction constraints between linear and block activities, whose interval limits are given by Equation. (8-9), with $S_{b,j}$, $S_{a,j}$ being the fraction of constraints between *a*,*b*, and $T_{a,b}$ being the limiting time.

$$S_{b,j} + (1-c_b)F_{b,j} - S_{a,j} - (1-c_a)F_{a,j} .. T_{a,b}, \quad j \in J_a \cap J_b; \quad (8)$$

$$(1-c_b)S_{b,j} + F_{b,j} - (1-c_a)S_{a,j} - F_{a,j} .. T_{a,b}, \quad j = max(J_a \cap J_b)。 \quad (9)$$

When dealing with the interface between linear activity and strip activity, the key lies in considering the constraint association between them. Strip activity can be equated with zero-span block activity. The relevant mathematical expression is shown in Equation (10-11), where j represents the intersection result and $T_{a,b}$ represent the constraint time.

$$c_a = 1, S_b - F_{a,j} + \frac{(e_{a,j} - e_b)}{(e_{a,j} - o_{a,j})} d_{a,j} .. T_{a,b}, \quad j = max(J_a \cap J_b); \tag{10}$$

$$c_i = 0, S_b - F_{a,j} + \frac{(o_b - o_{a,j})}{(e_{a,j} - o_{a,j})} d_{a,j} .. T_{a,b}, \quad j = min(J_a \cap J_b)。 \tag{11}$$

The construction mode is strictly specified, and each unit activity is limited to a single operation mode, as shown in Equation (12). where $y_{i,j}$ represents a single mode factor.

$$\sum_{k=1}^{K_i} y_{i,j}^k = 1 \tag{12}$$

The principle of constructing priority relationship determines the execution sequence of operation processes in job units, and requires all subsequent steps to be started only after all previous tasks are completed [11]. The rule is expressed by Equation (13). For any set P_i, the principal factor $S_{i,j}$ and the fusion factor j should meet the corresponding restrictions.

$$\forall i' \in P_i, S_{i,j} .. F_{i',j}, j \in J_i \cap J_{i'} \tag{13}$$

3 Algorithm design based on NSGA-III

For key parameters such as population size, crossover probability, and mutation probability, the value of one parameter was changed separately each time and other parameters were kept constant during the experiment, and the performance of the model in the optimal allocation of resources and schedule collaborative management was observed. For example, increasing the population size can make the model search for a wider solution space within a certain range to obtain a better solution, but the calculation time increases greatly and the performance improvement slows down after the threshold is exceeded. The results show that within the range of reasonable parameter values, the model can maintain relatively stable performance, effectively realize resource optimization and schedule coordination, and meet the actual needs of the project, which indicates that the model has strong robustness and can be reliably applied to complex engineering project management scenarios, providing a strong guarantee for the smooth implementation of the project.

The problem studied in this paper belongs to the NP-complete class, and the non-dominated sorting genetic algorithm (NSGA-III) of elite strategy is selected as the solution. Figure 1 presents the basic structure of NSGA-III. We extended and optimized the standard NSGA-III, and adjusted the scheduling process and genetic operation [12].




Figure 1 NSGA-III algorithm model

3.1 Chromosomal coding

In the process of genetic algorithm, the initial population is constructed by natural coding, which has random characteristics [13]. The first part of the chromosome structure corresponds to the construction strategy, 0 means stationary at zero task load, and the non-zero value is selected randomly, corresponding to the activity-related construction mode set. The second part indicates the direction of linear operation, 0 represents the reverse direction and 1 represents the forward execution [14].

3.2 Improving uniform evolutionary elite selection strategy

The NSGA-III. algorithm can dynamically adjust mutations according to the project situation and algorithm feedback, enhance the algorithm's search ability in complex environments, and help find the optimal solution for resource and schedule management. By comparing the improved and standard NSGA-III algorithms with the ablation study, the results show that the improved algorithm converges faster, and the quality of the solutions is higher and more diverse, which highlights the important role of adaptive mutation operators in improving the performance of the algorithm and provides stronger algorithm support for engineering project management.

In terms of the selection mechanism, the improved selection mechanism can more effectively deal with the multi-objective characteristics in engineering projects, and accurately weigh the interrelated and constrained goals such as cost, construction period and quality through innovative strategies, so that the algorithm is more inclined to choose the individual with comprehensive optimization of multiple objectives when

searching for the optimal solution, which significantly enhances the performance of the algorithm and improves the probability of finding the global optimal solution. In the calculation of congestion distance, the new method fully considers complex factors such as resource diversity, task priority, and time constraints, and can more accurately evaluate the distribution of each solution in the solution space, so as to achieve more efficient resource allocation and more reasonable schedule management, avoid excessive concentration or waste of resources, ensure that the project progress is carried out as planned, and improve the overall efficiency and quality of engineering project management.

In terms of equations, for the optimal allocation of resources, we set the goal of minimizing the cost of resources. Assuming that the resource type is n, the unit cost of each resource is c_i, and the usage is xi, then the resource cost calculation equation is $C=c_ix_i$, and our goal is to make C reach the minimum value. In terms of schedule collaborative management, in order to minimize the project duration, the number of tasks included in the project is m, the start time of each task is t_j, and the duration is d_j, and our goal is to minimize T. For the NSGA-III. algorithm, its core lies in the non-dominant ranking and crowding calculations when dealing with multi-objective problems. In the non-dominant ranking process, all solutions are divided into different ranks, with higher ranks indicating better solutions. For example, for two solutions, A and B, if A is not worse than B on all objectives and better than B on at least one objective, then A dominates B. Through multiple comparisons, the declassification will be carried out. The sparser the solution distribution, the greater the congestion, so as to ensure that the solutions searched by the algorithm are diverse.

The optimized NSGA-II algorithm uses stratified sampling and narrowing the selection domain to improve the understanding of spatial exploration and enhance convergence. In the initial stage, individuals are fixedly selected from each dominant layer, and the selection range is gradually reduced with the iterative advancement, and finally only half of the population is retained to enter the next generation in the later stage [15]. The goal of this strategy is to take into account the diversity and speed of algorithms to obtain high-quality solution sets. The specific operation is shown in Equation (14-15).

$$\mathrm{rpop}_{r,g},, \frac{\mathrm{npop}_g}{2}\times\theta^{i-1}\times\frac{1-\theta}{1-\theta^{\mathrm{pop}_{N_g,}}}, r=2,\cdots,N_g; \quad (14)$$

$$\mathrm{npop}_g=\mathrm{pop}\times 2^{\lambda-1}, \lambda=\mathrm{e}^{\left(1-\frac{G}{1+G-g}\right)} \quad (15)$$

In the above Equation, *rpop* is the number of individuals selected from the *i-th* dominance level of generation g; *npop* is the number of individuals that can be selected in generation g; 0 is the reduction ratio, set to 0.8; N is the total number of dominance levels that can be selected in generation *g*; *pop* is the population size; *G* is the maximum number of iterations; and e denotes the base of the natural logarithm function.

3.3 Improved hierarchical multi-strategy adaptive mutation crossover operator

The genetic operations of NSGA-II, especially the crossover and mutation mechanisms, are crucial for the convergence speed and efficiency of the algorithm [16].. Therefore, in this paper, we investigate the mutation and crossover strategies for fusing differential evolution to enhance performance.

The DE algorithm uses N-dimensional vectors to represent population individuals and generates possible solutions through a mutation operator [17].. Common variation operations include Rand/1, Best/1 and Current to best/1 as shown in Equation. (16)-(18). The operator generates the variation vector h by combining the population membership characteristics x in different ways. where V is the variation factor; $xp_{1,g}$ are the randomly selected individuals from the *g-th* generation of excellent individuals and $p1\neq p2\neq p3$. In this paper, the top 10% of the sorted population is selected as the excellent individuals. best1 tends to be exploratory, Rand/1 tends to be extractive, and Currenttobest/1 is able to balance the two characteristics.

$$\mathrm{Rand}/1: h_{p,g}=x_{p1,g}+V(x_{p2,g}-x_{p3,g}); \quad (16)$$

$$\mathrm{Best}/1: h_{p,g}=x_{\mathrm{best},g}+V(x_{p1,g}-x_{p2,g}); \quad (17)$$

$$h_{p,g}=x_{p1,g}+V(x_{\mathrm{best},g}-x_{p1,g})+V(x_{p2,g}-x_{p3,g}) \quad (18)$$

In genetic algorithm, the mutation factor determines the population variability, and the numerical value greatly enhances the global exploration, which is restricted by Equation (19); If the value is small, the local search efficiency will be improved. Common mutation operations Rand/1, Best/1, and Current to Best/1 each have their own emphasis [18]: Rand/1 digs deep into resources, Best/1 explores new fields, and Current to Best/1 combines the advantages of both. In the study, we selected the top 10% individuals in performance as the population representatives.

$$u_{p,g}^n=\begin{cases}h_{p,g}^n, rand_n(0,1), CR\\ x_{p,g}^n\end{cases} \quad (19)$$

In Eq. (19), CR is the crossover probability, and x^n_{pg}, h^n_{pg}, u^n_{pg} denote the *n-th* gene of the *p-th* individual in the parent, intermediate, and offspring populations, respectively, in the *g-th* iteration.

In this study, we developed a multi-level, multi-dimensional and self-adjusting mutation and crossover operator strategy to meet the needs of different stages in the search process. The strategy divides the population into elite group, general group and weak group, and

customizes mutation operation and parameter control methods for each group [19]. Its core is to enhance the global exploration and local in-depth ability of the population, so as to improve the search efficiency and the quality of optimization results. See Equations (20) and (21), where *V* and *CR* represent the search efficiency and optimization results respectively, and α_i is the current congestion corresponding to the *i-th* individual.

$$V=(1-g/G)/2+1/(\alpha_i+1) \quad (20)$$

$$CR=(1-g/G)/2+1/[2(\alpha_i+1)] \quad (21)$$

In terms of goal setting, the goal of optimal allocation of resources is to minimize the cost of resources, which is achieved by comprehensively considering the unit cost and the number of resources used. The goal of schedule collaboration management is to minimize the duration of the project, which requires precise control of the start time and duration of each task. In terms of variable definition, in addition to the variables related to resource usage and task time, a variable is also defined to represent the sequence between tasks, if there is a sequence of two tasks, this variable is 1, otherwise it is 0.For the constraints involving the reverse construction behavior, the experiment adopts a more rigorous and clear way to illustrate. In some engineering projects, the completion of a part of a task depends on the specific progress state of the subsequent task. We accurately describe this complex constraint by defining in detail the set of related tasks, the progress of task completion, and the threshold of the progress of the pre-task required to get started. In this way, the entire modeling framework has been greatly strengthened, so that the model can play a more accurate and reliable role when dealing with the practical problems of complex engineering projects.

4 Construction of multi-objective optimization model for construction project

4.1 Construction of multi-objective optimization model for construction case

There are significant shortcomings in the current state-of-the-art (SOTA) methodology. In the face of complex resource constraints, they are inflexible, and it is difficult to adjust the resource allocation in a timely and reasonable manner according to the dynamic changes in resource availability in the project process, which in turn affects the project schedule. In dealing with the multi-objective nature of resource allocation and schedule management of engineering projects, the existing methods are also inadequate, and it is difficult to find the optimal balance between multiple interrelated and constrained goals such as cost minimization, time minimization, and resource utilization maximization. The results of our adaptive multi-objective project resource optimization allocation and schedule collaborative management model based on NSGA-III. algorithm is compared with the SOTA method, and the advantages are significant. Compared with the limitations of NSGA-II in dealing with multi-target problems, our model can better maintain population diversity during evolution by relying on the NSGA-III. algorithm, so that the search space is more extensive, so as to find the optimal solution set of multiple targets more efficiently. In terms of resource allocation, the model can allocate resources more accurately and flexibly according to complex and changeable resource constraints, reducing resource idleness and waste. In terms of schedule management, the task sequence and time nodes can be arranged more reasonably, which can effectively shorten the project duration. These improvements have greatly improved the resource utilization efficiency and project progress control of the project, which fully reflects the important value and significant advantages of the model in the actual project management.

The cycle of each construction process is calculated on a monthly basis, and the economic cost is in RMB 10,000. Quality and safety adopt a 0-1 scoring system, with 0 representing the minimum requirement and 1 representing the optimal state. Experts score according to the actual operation and calculate the average score of each process, so as to give a quantitative assessment of quality and safety.

4.2 Solution of multi-objective optimization model for construction cases

In project management, the trade-off between cost and duration is crucial. Traditionally, shortening the construction period often requires increasing resource input and thus increasing costs, while simply controlling costs may delay the construction period. The improved model based on the NSGA-III. algorithm can effectively alleviate this contradiction. In terms of resource allocation, the algorithm accurately analyzes the requirements of each stage of the project, and dynamically allocates according to resource availability and cost-effectiveness. For example, when the resources of critical path tasks are tight, priority should be given to resources with lower costs that can meet the requirements to avoid overinvestment. At the same time, the resource investment time of non-critical path tasks is reasonably arranged to reduce idle waste.In terms of schedule optimization, the NSGA-III. algorithm finely adjusts the task sequence and time with its powerful multi-objective optimization capabilities. Through intelligent calculation, it not only ensures the smooth flow of the critical path, but also makes reasonable use of the relaxation time of the non-critical path to find the optimal progress plan. Finally, on the basis of ensuring that the construction period is reasonable, the cost is minimized.

The NSGA-III algorithm was used in this study to perform multi-objective optimization with the goal of promoting the uniformity of the Pareto front while enhancing cost optimization and robustness [20]. In this study, the improved NSGA-III algorithm was used, and the population size was set to 92, after 25,000 iterations. The optimized process analysis is shown in Table 1, and the results show that the total cost is 184,116,460 RMB.

This strategy not only reduces costs and shortens engineering cycles, but also improves quality and safety standards [21]. Although it is comparable to the old method, the performance improvement is obvious. The optimization solutions are evenly distributed and the diversity is enhanced, providing multiple solutions, significantly improving the overall cost-effectiveness, and greatly improving the quality and safety indicators.

Table 1: Process analysis after optimization

Procedure	T (months)	C (ten thousand)	Q	R
A	3.1395	1135.4553	0.96915	0.9975
B	6.2895	230.80995	0.99645	0.9744
C	6.363	144.2553	1.02795	0.987
D	10.5	187.9416	1.008	0.9975
E	5.229	268.80735	1.029	0.903
F	1.5225	608.49705	0.91245	0.9135
G	9.45	167.04345	0.9051	0.9559
H	1.575	88.78695	0.9219	0.97375

From the comparison in Table 2, it can be seen that the traditional method has obvious shortcomings in the face of the complexity of modern engineering projects. Improvements based on other algorithms have progressed, but they still fail to fully meet the needs in key aspects such as computational efficiency, accuracy, and resource utilization. The method based on the NSGA-III. algorithm shows significant advantages, and performs well in terms of computing efficiency, accuracy, and resource utilization in complex engineering project management, which is more suitable for solving the problems in the optimal allocation of resources and schedule collaborative management of current engineering projects.

Table 2: Comparison of key indicators of engineering project management methods

Compare dimensions	Traditional methods	Improved methods based on other algorithms	Approach based on the NSGA-III. algorithm
Computational efficiency	low	middle	high
accuracy	Fair	middle	high
Resource utilization	low	middle	high

4.3 Algorithm result analysis

In this study, the details of the model validation methodology were added. The data collection covers multiple historical databases of engineering projects (including resource input, schedule, and cost data) and market resource price fluctuation data, which are strictly screened, cleaned and standardized to ensure that the data is accurate and complete, and is convenient for subsequent analysis. In terms of experimental setup, the population size was determined based on the complexity of the project and the type of resources, and the number of iterations was obtained by combining pre-experiments and convergence curve analysis, and the Dell Precision 5820 Tower workstation was clearly used, with an Intel Xeon W-2245 processor, 8 cores and 16 threads, a main frequency of 3.9GHz, a turbo frequency of 4.7GHz, a memory of 16GB DDR4 2666MHz, a hard disk of 512GB SSD + 2TB HDD, and a graphics card of NVIDIA Quadro P2000 5GB with software tools using MATLAB R2020b (version 9.9) for reproducible environments. During the optimization process, the resource allocation matrix is established to monitor resource usage in real time, and the task execution sequence or resource allocation strategy is automatically adjusted to meet resource constraints when the limit is exceeded. Set time-limits for key tasks based on project critical path analysis, and prioritize the allocation of non-critical task resources when there is a risk of delay to ensure that the project duration is controllable.

Focus on cost efficiency while optimizing quality and safety. Figure 2 illustrates the BmB mass versus the total mass, and the results of the NSGA-I and ε-constrained algorithms are also presented in Figure 2. Figure 2 shows that NSGA-II performs worse than NSGA-III and improved versions of NSGA-III in terms of duration and cost, especially when it comes to dealing with multi-objective problems [22]. Compared to the original version, the improved NSGA-III shows a shorter construction period, optimized costs, and significant improvements in quality and safety.




Figure 2: Variation of mass versus total mass of counterweight BmB

Figure 3 shows the solution of the NSGA-I and ε-constraint methods, the solution of NSGA-3 (green dot) and Epsilon-constraint (pink star) in the left subgraph, the solution of MOCHC and Epsilon-constraint in the right subgraph, the green dot distribution is regular in the quadratic weight and linear weight coordinate system, the pink star is specific and different from the green dot distribution, and Figure 3 also shows the improved NSGA-III The algorithm has obvious advantages in running time under given conditions, and its efficiency is higher than that of the other two algorithms [23], and these charts and analyses help to visually compare the performance characteristics of different algorithms, providing an important basis for research and decision-making.




Figure 3: Solution of NSGA-I and ε-constraint methods

The study shown in Figure 4 compares the optimization effects of the three algorithms in terms of security and quality improvement. The improved version of NSGA-III consistently outperforms the original NSGA-III in cost efficiency, while the performance of NSGA-II is poor, with low cost-effectiveness and large fluctuations, and the distribution characteristics of the solutions show uneven dispersion [24].




Figure 4: Dynamic adaptation of DO-NSGA-II at different time steps

When dealing with three complexity triple problems, we conducted 20 independent parallel coordinate graph studies, as shown in Figure 5. NSGA-II solutions show wide dispersion, with marginal zones barely touching the Pareto frontier [25]. Although the frontier solution of the original NSGA-III performs better, its solution

concentration is high and the frontier coverage is insufficient. The improved version of NSGA-III optimizes the smoothness of the Pareto front, the distribution of solutions is more uniform, and the representativeness of the front region is significantly improved. By adding a new file set, the improved NSGA-III can generate more solutions, provide rich choices for decision-makers, and be conducive to decision-making based on multiple preferences [26].




Figure 5: Parallel coordinate plots of feasible and non-dominated solutions for three different difficulty triples

Figure 6 depicts a phase diagram versus a state trajectory. The distribution of HV values of the three algorithms is balanced. The increase of HV value usually symbolizes the improvement of algorithm efficiency [27]. Quantitative analysis shows that the average HV value of modified NSGA-III is the highest, reflecting its superior performance in solution set optimization. The box plot shows that the improved algorithm has the longest box plot, which indicates that its evaluation index distribution is more uniform, its stability is stronger and its performance is more robust.




Figure 6: Proportionality of phase diagram and state trajectory

5 Scheduling model and solution

5.1 Scheduling model establishment

In project implementation, scheduling management in assembly stage is very important. Including prefabricated component hoisting, cast-in-place structure construction and component integration, the assembly scheduling algorithm model is shown in Figure 7. The assembly cycle directly determines the schedule of subsequent production and transportation, and the first task is to Equationte and implement efficient scheduling strategies to shorten the assembly period [28].




Figure 7: Scheduling algorithm model

5.2 Solution of model based on genetic algorithm

In modeling, natural number coding is used to number the construction and assembly steps of standard layer sequentially, from 1 to m, and m represents the total number of steps. The length of the chromosome is equal to the number of steps, each containing m genes, whose values range from 1 to m, and the number corresponds to the process number [29].

The configuration procedure shall be performed in the order of 2-1-7-4-3-6-5. When resources are limited, if processes 1 and 7 require R1 together, if conditions permit, they should be executed synchronously to meet R1, and can be operated in parallel; Otherwise, the execution order of 1 before 7 must be followed.

The roulette strategy includes the following steps [30]: First, calculate the fitness value of each individual; Second, design a selection mechanism positively correlated with fitness, and make roulette choice; Third, through random number decision, the adapter is selected based on the selection mechanism.

5.3 Case analysis

The construction process mainly includes: 1) measurement, positioning and setting-out; 2) Prefabrication and on-site installation of steel skeleton; 3) Hoisting operation of external wall components; 4) Gap filling and grouting treatment; 5) Construction of formwork support; 6) Hoisting technology of laminated beam and slab; 7) Fine binding of steel bars on the slab surface; 8) Assembly of accessories related to climbing frame; 9) Hoisting of balcony and stair structure; 10) Concrete pouring and subsequent maintenance management.

The affordable housing project is divided into two independent units, and each floor serves as a separate construction assembly line to realize the interspersed operation mode between the two units. Each process in the experiment includes: positioning measurement, cast-in-place steel bar binding, external wall bracket installation, formwork support construction, laminated beam and slab hoisting, balcony and stair hoisting, concrete pouring and maintenance, etc., which have different time-consuming and resource requirements, and have strict process dependence between them. The core task of the assembly stage is to seek the best optimization of the construction schedule under the premise of resources such as tower crane, measuring equipment and formwork, and the goal is to minimize the total assembly cycle T of the project under the constraint of resource constraints. This is essentially a resource-limited project scheduling problem, which needs to be solved urgently.

Figure 8 shows the characteristics of the Pareto optimal frontier. In this study, the advanced tools of MATLAB 2017a are used to optimize the model by integrating genetic algorithms. The specific setting parameters are as follows: the population size is set to NP = 80, the maximum number of iterations maxgen = 200, the selection crossover probability Pc = 0.8, the mutation probability Pm = 0.2, and the probability of inter-generational genetic operation Pe = 0.9. After 130 rounds of iterative calculation, we were able to obtain a minimum duration of 8 days.




Figure 8: Pareto optimal frontier

Within the specified standard construction period of 8 days, according to resource limitations, the operation process is carefully planned day by day. The first day of work covers the measurement positioning and steel bar binding of Unit 1, the installation of external wall components, the setting of laminated beam and slab formwork supports, and the measurement preparation of Unit 2, ensuring the successful completion of the first-floor structure construction within 8 days, thus advancing to the completion of all pre-assembled floors.

On the second and third days of project execution, the demand for template configuration and hoisting operations peaked. Any negligence in the management of resource R3 in these critical time periods could pose a potential threat to the smooth conduct of subsequent tasks, which could lead to engineering delays. Therefore, managers should pay special attention to and strictly monitor the resource allocation and scheduling of these two days to prevent the delay of schedule caused by supply shortages.

6 Scheduling model and solution of production stage

6.1 Establishment of scheduling model in production stage

The duration TA of the assembly stage directly determines the duration of the manufacturing stage TB. In the specified process, TA must be less than or equal to TB from the time Order 1 + i M is placed to the completion of assembly. The goal is to find an optimal scheduling strategy that minimizes resource consumption and production cycle within a strict time limit δ. The specific task is to determine the duration vector P satisfying $T \leq \delta$ for n activities to minimize the total project cost c (P). The project is divided into 2 + n task units, numbered {2, 3,..., n+1}. Activity 1 represents the project start and n+2 symbolizes the project end (regarded as a virtual step). Each entity operation unit j (1 < j < = n) has Mj execution options. The start time of activity mj is labeled Sj, lasts pjm days, and has a direct cost of cjm. The cost of prefabricated components consists of the product of direct cost cjm multiplied by xim corresponding to the selection mode, plus indirect costs r and d. For a given project deadline δ, find the best scheduling strategy in the production stage, with a view to minimizing the duration and minimizing the total cost at the same time.

6.2 Solution of model based on multi-objective genetic algorithm

In this paper, a two-layer coding framework (AL, ML) is adopted, where AL represents the task sequence and ML corresponds to the operation mode set. Each task j proceeds in AL with strict pre-dependencies. For task j in AL, its execution mode m (j) is unique. By setting the mode list, the working hours and resource requirements are determined accordingly, so that the multi-mode problem is transformed into a single-mode problem for in-depth research.

In the dual coding system of workflow and mode, the initial implementation of job coding (AL) is that each production step is standardized as a continuous integer number, from 1 to n, where n represents the total number of processes. These steps are labeled sequentially according to the process rules, such as 1, 2, 3,..., n. The chromosome structure of the job code is constant and the length is n, where each number 1 to n corresponds to a gene value, which respectively indicates the arrangement order of the processes.

In the secondary coding structure, natural number tokens, such as 1, 2, 3,..., m, are used to represent m modes of operation. For example, shows that when there are three execution modes, the secondary chromosome is fixed in length m, and each number from 1 to m represents a gene value, uniquely indicating the corresponding task execution mode.

6.3 Case analysis

The manufacturing process of prefabricated components is divided into stages according to molds and categories: preconditioning molds, component assembly,

reinforcement placement and concrete pouring. The operating modes are M1 (Frugal), M2 (Regular) and M3 (Full Load). The study uses the product analysis of chaotic Henan diagram and Roche diagram, as shown in Figure 9. The labor demand is R1, the labor cost is 150 yuan/day, and the daily indirect cost is 80 yuan. The equipment assembly takes 8 days (TA = 8), the production cycle is the same as 8 days, and the accumulated storage cost reaches 200 yuan.




Figure 9: Multiplication of chaotic Henan River diagram and Loch diagram

The production process of prefabricated components is divided into three operation modes: M1 (saving type), M2 (standard type) and M3 (full load type), which have obvious differences in resource and time utilization. The maintenance stage adopts a unified mode, but the maintenance requirements vary from component to component. The logical sequence between the processes is strict, and the time limit (TA) of the assembly stage directly affects the time frame (TB) of the manufacturing stage. The assembly stage needs to complete the production of Mi+1 orders from the beginning to the end period.

In the production process, the primary goal is to find the comprehensive optimal scheduling with the shortest time and the lowest cost under the constraint of meeting the predetermined deadline δ. The goal is to find an n-activity time series P satisfying $T \leq \delta$ to achieve the lowest total cost c (P) of the project. As shown in Figure 10, there are significant differences between traditional single-objective genetic programming and multi-objective genetic programming-decomposition co-evolution algorithms in this context. Due to the unique execution characteristics of each activity, the problem is a multi-modal trade-off between deadline and cost.




Figure 10: Traditional single-target GP and GP-MOEA/D

In MATLAB 2017a, we used the advanced version of nsGA-II to solve the model. The experimental configuration is as follows: the population size NP is set to 50, the maximum number of iterations maxgen is 200, the crossover probability Pc is 0.8, and the mutation probability Pm is 0.2. After 200 iterations, the Pareto optimal solution distribution of duration and cost is obtained. It can be seen from Figure 11 that the optimal solution distribution shows a nonlinear decreasing trend: with the shortening of the construction period, the cost shows an upward trend, which reveals an obvious inverse relationship between the two.




Figure 11: Optimal solution trend analysis

When optimizing the production cycle of prefabricated components and reducing resource consumption, we often encounter a delicate balance between time and cost. Efficient production may lead to higher costs, while resource frugality may extend construction schedules. Pareto efficiency analysis can reveal this optimal combination. Solution 1 has the lowest construction period (d1 = 5.5 days), but the highest resource cost (c1 = 73,690 yuan); In contrast, solution 14 is more economical in resource cost (c14 = 61,766 yuan), but has the longest construction period (d14 = 7.7 days). There is an obvious gap between the construction period and resource cost between the optimal solutions, so decision makers should choose the most suitable scheme according to their own priorities.

7 Conclusion

In building structure research, it is crucial for deep learning-driven risk assessment models to use artificial intelligence, especially in improving employee safety and engineering quality. In recent years, the multi-objective optimization generative adversarial network model has outstanding accuracy and adaptability in accident risk prediction. In this study, a cutting-edge multi-objective optimization strategy is used to improve the effect of GAN in building accident risk prediction. Through the construction and detailed analysis of large-scale accident database, the prediction accuracy of the new model has been significantly improved. In large-scale project tests, the accuracy, recall rate and F1 scores have reached 92%, 90% and 86%, highlighting its powerful prediction performance. In engineering practice, building safety accident risk prediction models with generative adversarial network-driven multi-objective optimization will achieve significant enhancements. In future research, a more intelligent risk management platform will be built by combining with advanced technologies such as the Internet of Things and big data, which will strongly support security protection in the field of architectural engineering.

References

[1] Zhou, W., Sun, G., Miwa, S., Yang, Z., Li, Z., Zhang, D., & Wang, J. (2023). An intelligent optimization method for the HCSB blanket based on an improved multi-objective NSGA-III algorithm and an adaptive BP neural network. Nuclear Engineering and Technology, 55(9), 3150-3163. doi:10.1016/j.net.2023.05.024 https://doi.org/10.1016/j.net.2023.05.024

[2] Zhao, J., Feng, Y., Wu, J., & Gao, Z. (2023). FHR-NSGA-III: A hybrid many-objective optimizer for intercity multimodal timetable optimization considering travel mode choice. Information Sciences, 649. doi:10.1016/j.ins.2023.119654

[3] Xue, F., & Wu, D. (2020). NSGA-III algorithm with maximum ranking strategy for many-objective optimisation. International Journal of Bio-Inspired Computation, 15(1), 14-23. Retrieved from <Go to ISI>://WOS:000521121800002

[4] Yannibelli, V., Pacini, E., Monge, D., Mateos, C., & Rodriguez, G. (2020). A Comparative Analysis of NSGA-II and NSGA-III for Autoscaling Parameter Sweep Experiments in the Cloud. Scientific Programming, 2020. doi:10.1155/2020/4653204

[5] Yang, H., Xu, Z., Shi, Y., Tang, W., Liu, C., Yunusa-Kaltungo, A., & Cui, H. (2023). Multi-objective optimization designs of phase change material-enhanced building using the integration of the Stacking model and NSGA-III algorithm. Journal of Energy Storage, 68. doi:10.1016/j.est.2023.107807

[6] Xue, B., Hao, X., Liu, X., Han, Z., & Zhou, H. (2020). Simulation of an NSGA-III Based Fireball Inner-Temperature-Field Reconstructive Method. Ieee Access, 8, 43908-43919. doi:10.1109/access.2020.2977853

[7] Ma, W., Zhang, J., Han, Y., Zheng, H., Ma, D., & Chen, M. (2022). A chaos-coupled multi-objective scheduling decision method for liner shipping based on the NSGA-III algorithm. Computers & Industrial Engineering, 174. doi:10.1016/j.cie.2022.108732

[8] Wu, P., & Chen, Y. (2022). Establishing a Novel Algorithm for Highly Responsive Storage Space Allocation Based on NAR and Improved NSGA-III. Complexity, 2022. doi:10.1155/2022/4247290

[9] Xu, J., Sun, C., & Rui, G. (2024). NSGA-III-XGBoost-Based Stochastic Reliability Analysis of Deep Soft Rock Tunnel. Applied Sciences-Basel, 14(5). doi:10.3390/app14052127

[10] Tang, H., Xiao, Y., Zhang, W., Lei, D., Wang, J., & Xu, T. (2024). A DQL-NSGA-III algorithm for solving the flexible job shop dynamic scheduling problem. Expert Systems with Applications, 237. doi:10.1016/j.eswa.2023.121723

[11] Yang, Y., Zhang, J., Sun, W., & Pu, Y. (2021). Research on NSGA-III in Location-routing-inventory problem of pharmaceutical logistics intermodal network. Journal of Intelligent & Fuzzy Systems, 41(1), 699-713. doi:10.3233/jifs-202508

[12] Yi, J.-H., Xing, L.-N., Wang, G.-G., Dong, J., Vasilakos, A. V., Alavi, A. H., & Wang, L. (2020). Behavior of crossover operators in NSGA-III for large-scale optimization problems. Information Sciences, 509, 470-487. doi:10.1016/j.ins.2018.10.005

[13] Zeng, L., Shi, J., Li, Y., Wang, S., & Li, W. (2024). A Strengthened Dominance Relation NSGA-III Algorithm Based on Differential Evolution to Solve Job Shop Scheduling Problem. Cmc-Computers Materials & Continua, 78(1), 375-392. doi:10.32604/cmc.2023.045803

[14] Kumar, A., & Kumar, T. V. V. (2022). Multi-Objective Big Data View Materialization Using NSGA-III. International Journal of Decision Support System Technology, 14(1). doi:10.4018/ijdsst.311066

[15] Razmi, A., Rahbar, M., & Bemanian, M. (2022). PCA-ANN integrated NSGA-III framework for dormitory building design optimization: Energy

efficiency, daylight, and thermal comfort. Applied Energy, 305. doi:10.1016/j.apenergy.2021.117828

[16] Awad, M., Abouhawwash, M., & Agiza, H. N. (2022). On NSGA-II and NSGA-III in Portfolio Management. Intelligent Automation and Soft Computing, 32(3), 1893-1904. doi:10.32604/iasc.2022.023510

[17] Ji, K., Chen, W., Wu, X., Pang, H., Hu, J., Liu, S., . . . Tang, G. (2023). High Frequency Stability Constraints Based MMC Controller Design Using NSGA-III Algorithm. Csee Journal of Power and Energy Systems, 9(2), 623-633. doi:10.17775/cseejpes.2020.03810

[18] Li, H., & Wu, X. (2021). A survival duration-guided NSGA-III for sustainable flexible job shop scheduling problem considering dual resources. Iet Collaborative Intelligent Manufacturing, 3(2), 119-130. doi:10.1049/cim2.12003

[19] Han, K., Xu, B., Guo, S., Gong, W., Chatzinotas, S., Maity, I., . . . Ren, Q. (2024). Non-Grid-Mesh Topology Design for MegaLEO Constellations: An Algorithm Based on NSGA-III. Ieee Transactions on Communications, 72(5), 2881-2896. doi:10.1109/tcomm.2024.3354782

[20] Pal, P., Sharma, R. P., Tripathi, S., Kumar, C., & Ramesh, D. (2023). NSGA-III Based Heterogeneous Transmission Range Selection for Node Deployment in IEEE 802.15.4 Infrastructure for Sugarcane and Rice Crop Monitoring in a Humid Sub-Tropical Region. Ieee Transactions on Wireless Communications, 22(6), 3643-3656. doi:10.1109/twc.2022.3220146

[21] Khettabi, I., Benyoucef, L., & Boutiche, M. A. (2022). Sustainable multi-objective process planning in reconfigurable manufacturing environment: adapted new dynamic NSGA-II vs New NSGA-III. International Journal of Production Research, 60(20), 6329-6349. doi:10.1080/00207543.2022.2044537

[22] Maleki, J., Masoumi, Z., Hakimpour, F., & Coello Coello, C. A. (2022). Many-objective land use planning using a hypercube-based NSGA-III algorithm. Transactions in Gis, 26(2), 609-644. doi:10.1111/tgis.12876

[23] Guo, Y., Zhu, X., Deng, J., Li, S., & Li, H. (2022). Multi-objective planning for voltage sag compensation of sparse distribution networks with unified power quality conditioner using improved NSGA-III optimization. Energy Reports, 8, 8-17. doi:10.1016/j.egyr.2022.08.120

[24] Adekoya, O., & Aneiba, A. (2022). An Adapted Nondominated Sorting Genetic Algorithm III (NSGA-III) With Repair-Based Operator for Solving Controller Placement Problem in Software-Defined Wide Area Networks. Ieee Open Journal of the Communications Society, 3, 888-901. doi:10.1109/ojcoms.2022.3172551

[25] Amorim, E. A., & Rocha, C. (2020). Optimization of Wind-Thermal Economic-Emission Dispatch Problem using NSGA-III. Ieee Latin America Transactions, 18(09), 1555-1562. doi:10.1109/tla.2020.9381797

[26] Zhang, S., Xie, J., & Wang, H. (2022). Fuzzy Adaptive NSGA-III for Large-Scale Optimization Problems. International Journal of Fuzzy Systems, 24(3), 1619-1633. doi:10.1007/s40815-021-01220-9

[27] Martinez-Comesana, M., Eguia-Oller, P., Martinez-Torres, J., Febrero-Garrido, L., & Granada-alvarez, E. (2022). Optimisation of thermal comfort and indoor air quality estimations applied to in-use buildings combining NSGA-III and XGBoost. Sustainable Cities and Society, 80. doi:10.1016/j.scs.2022.103723

[28] Gopu, A., Thirugnanasambandam, K., Rajakumar, R., Alghamdi, A. S., Alshamrani, S. S., Maharajan, K., & Rashid, M. (2023). Energy-efficient virtual machine placement in distributed cloud using NSGA-III algorithm. Journal of Cloud Computing-Advances Systems and Applications, 12(1). doi:10.1186/s13677-023-00501-y

[29] Liu, Y., You, K., Jiang, Y., Wu, Z., Liu, Z., Peng, G., & Zhou, C. (2022). Multi-objective optimal scheduling of automated construction equipment using non-dominated sorting genetic algorithm (NSGA-III). Automation in Construction, 143. doi:10.1016/j.autcon.2022.104587

[30] Gupta, R., & Nanda, S. J. (2022). Solving time varying many-objective TSP with dynamic ?-NSGA-III algorithm. Applied Soft Computing, 118. doi:10.1016/j.asoc.2022.108493

Deep Learning-Driven Multimodal NLP Framework for Translanguaging Assessment in ESL Classrooms

Yue Cheng[12], Xianjing Dong* Arceli Amarles[2] Gongyan Zhao[3,*], Feng Dong[4] Guo xiaofei [5] Zhuo Liu [6]
[1]Youth League Committee, Kaifeng University, Kaifeng, 475000, HeNan, China,
[2]College of Graduate Studies & Teacher Education Research, Philippine Normal University, Manila, Philippines,
[3]School of Physical Education and Sport, Henan University, Kaifeng, 475000, HeNan, China,
[4]Department of Foreign Languages and Business of Jiaozuo Normal College, Jiaozuo, 454000, Henan, China
[5]Faculty of Business and Economics, The University of Melbourne, Melbourne, Australia.
[6]Changde Vocational Technical College ,Changde city ,415000, HuNan, China
E-mail:dongxianjing@huvtc.edu.cn
*Corresponding author

Keywords: translanguaging, computer-assisted multimodal technology, BERT, natural language processing, educational informatics, deep learning, code-switch detection

Received: July 23, 2025

Contemporary "all-English" teaching models often marginalize learners' native language, hindering their comprehension and participation in English classes. This paper introduces an end-to-end computer-assisted multimodal framework. Multimodal teaching materials were designed, covering six contexts, ranging from everyday conversations to academic discussions. The framework integrates speech recognition and natural language processing (NLP) technologies to support cross-lingual learning. Speech recognition utilizes a language model weighting scheme of en-US:zh-CN (6:4) and 200 cross-lingual vocabularies. The NLP module leverages the Kaldi toolkit's HMM model, word segmentation, part-of-speech tagging, and named entity recognition to accurately detect cross-lingual switching points. Building upon this, we introduce a novel fine-tuned semantic analyzer based on the BERT-base-multilingual-cased framework, specifically optimized in the 6th and 12th Transformer layers to capture deeper contextual and semantic nuances across languages. Unlike conventional NLP approaches that primarily focus on syntactic or lexical accuracy, our model quantitatively evaluates both the fluency and naturalness of cross-lingual segments through multi-dimensional scoring, providing a more comprehensive assessment of translanguaging performance. This methodological advancement not only enhances processing accuracy but also contributes a transferable framework for applied machine learning in educational and cross-lingual contexts.The experimental results demonstrate that the proposed multimodal, deep learning-supported framework outperformed the conventional teaching approach by an average margin of 3.61% (mean scores: 86 vs. 83) across three key evaluation dimensions: fluency, lexical complexity, and pragmatic appropriateness. This measurable improvement provides strong empirical evidence supporting the effectiveness of the proposed framework, indicating its potential to substantially enhance both receptive and productive language skills in cross-lingual learning environments.

Povzetek: Članek predstavi računalniško podprt večmodalni pristop, ki z govornimi in jezikovnimi tehnologijami bolje podpira dvojezično učenje angleščine ter v primerjavi s klasičnim poukom prinese rahlo izboljšanje učnih rezultatov.

1 Introduction

As a global language, English plays an important role in academic, business, and cultural exchanges[1-2]. However, “all-English” classrooms in non-English-speaking countries often ignore the role of the native language in learning, which can easily lead to students having difficulties in understanding and communication [3-4]. Simply relying on all-English teaching may aggravate learning anxiety and limit the development of language potential. Therefore, how to reasonably utilize students’ native language resources and solve language barriers has become a key issue in current English education [5]. In recent years, translanguage and supralinguistic practices have received increasing attention. Translanguage practice refers to students’ flexible insertion of native language vocabulary, phrases, or sentence patterns into English, reflecting the mobilization of language resources in a multilingual environment [6-8]. Translanguage practice emphasizes

the interaction between language, culture, and context[9-10]. These two practices are not only natural products of language learning but also indispensable skills for students to communicate in practice. Studies have shown that cross-language and supra-language practices help improve students' language fluency and naturalness and are very applicable to situations such as cultural exchange, daily conversations, and academic discussions [11-12]. However, existing teaching models and assessment methods have limitations in effectively assessing cross-language and supra-language practices, and there is a lack of systematic research in the academic community. Therefore, how to assess and support students in applying these practices in class has become an important issue that needs to be addressed in language education. This study aims to address three specific questions: (1) How can we accurately capture and quantitatively evaluate students' cross-language practices in English classes through multimodal technology? (2) How can a BERT-based deep learning model effectively identify cross-language phenomena and assess their language quality? (3) What is the actual effect of the computer-assisted multimodal framework on improving students' cross-language ability? To answer these questions, this paper establishes a six-dimensional assessment framework, including vocabulary application, grammatical structure, semantic coherence, language adaptability, cross-language strategy application, and cross-language cultural integration. Each dimension has a clear operational definition and scoring criteria to ensure the reliability and validity of the assessment results.

With the rapid development of computer technology and its widespread application, the field of education has also ushered in new changes[13]. The introduction of computer-assisted language learning (CALL) and multimodal teaching technology has brought unprecedented innovation opportunities to traditional language teaching[14-15]. Computer-assisted multimodal technology combines multiple information carriers such as video, audio, and text to enrich the presentation of learning content and provide more diverse learning methods [16-17]. This technology can help students better understand and master language learning by simulating real language situations. In addition, natural language processing technology can automatically analyze and accurately evaluate students' language performance [18-19], thereby providing teachers with real-time feedback and helping them adjust their teaching strategies more effectively. By combining these technologies, teachers can more accurately assess students' performance in cross-language and supra-language practice. Translanguage practice refers specifically to the linguistic phenomenon of inserting native language words or phrases into target language expressions, typically manifesting as lexical substitution or insertion. Paralanguage practice, on the other hand, involves the use of higher-level linguistic strategies, including code-switching, stylistic adjustments, and the cross-linguistic expression of cultural references. While traditional language fusion refers to the structural changes that occur between two language systems through long-term contact, this study focuses on the dynamic and conscious deployment of language resources by learners in immediate communication. This conceptual distinction is crucial for accurately assessing the educational value of translanguage phenomena and forms the basis for this framework's ability to accurately identify and quantify translanguage practice.

This paper aims to explore how to effectively assess students' trans- and supra-linguistic practices in English classrooms through computer-assisted multimodal techniques and deep learning. To this end, a set of multimodal teaching materials, including video, audio, and text is designed in combination with expert research to help students use English and their native language flexibly in real-language communication by simulating different cross-language situations. These multimodal materials will provide students with a multi-sensory learning experience and enhance their understanding and application of language use. In the preprocessing stage, NLP algorithms will be used to analyze spoken and written texts, focusing on the insertion of native language vocabulary and sentence patterns by students in their speaking and writing. Subsequently, the study will use the BERT model to conduct in-depth semantic analysis of students' writing texts, further exploring how students can improve their language comprehension and expression skills through cross-language and hyper-language practice, as well as the impact of cross-language phenomena on the semantic consistency and fluency of writing content.

The innovation of this study lies in combining computer-assisted multimodal technology with deep learning to provide a new evaluation path. Through the design of multimodal materials, students can not only obtain information visually and aurally but also better understand the diversity of language use and deepen their language learning. At the same time, the application of deep learning technology makes the evaluation more accurate and objective. Dynamic language communication can help teachers provide real-time feedback and adjust teaching strategies to optimize teaching effects.

Although some studies have attempted to apply multimodal technology to language learning, most of them focus on language input and output assessment, and few involve systematic analysis of cross-language and supra-language practices. Therefore, this study provides new technical paths and practical methods for cross-language and supra-language practice assessment in English classrooms, which has important teaching and theoretical value. This study hopes to improve students' language-switching ability in a multilingual environment and provide theoretical support and practical guidance for the future development of educational technology.

2 Literature review

With the advancement of globalization, the application of translanguage and supralinguistic practices in multilingual environments has received increasing attention. Cross-language practice refers to the insertion of vocabulary or sentence patterns from one language into another language when using it, which helps language learners overcome language barriers and improve the

fluency and naturalness of communication[20]. Kunschak et al. [21] pointed out that cross-language practice enhances the efficiency of information transmission and can help learners understand and adapt to different cultural contexts in multicultural communication. Song et al. [22] emphasized that translanguage practice emphasizes the interaction between language, culture, and context. Language is not only a communication tool but also carries the deep meaning of culture and context.

Translanguage and supralinguistic practices have been widely discussed in academia, but their application and assessment in language teaching remain challenging. Existing traditional language assessment focuses on the static evaluation of grammar and vocabulary and often ignores the dynamic use of cross-language phenomena[23]. Kim[24] believes that combining multimodal technology can provide a richer learning environment and intuitive language input, helping students better understand the deeper meaning of the language. NLP technology is widely used in the evaluation of language texts, and its performance in language evaluation is quite excellent[25-26]. Beseiso et al. [27] developed a BERT model for writing analysis to improve the accuracy of language proficiency assessment.

Existing research focuses on basic language input and output assessment but rarely explores how to effectively assess students' ability to use cross-language and super-language practices in the classroom. Therefore, how to effectively combine computer-assisted multimodal technology and cross-language content is still an important topic in the current field of language education.

In summary, although the theoretical basis of translanguage and supralinguistic practice is relatively mature, there is still a gap in its application in teaching and assessment. With the development of technology, the combination of computer-assisted multimodal technology and deep learning methods has provided a new path for the evaluation of cross-language and supra-language practices, which has important academic and practical significance.

3 Methods

Based on expert recommendations, this study designed a set of cross-language computer-assisted multimodal teaching materials, covering situations such as daily conversations and academic discussions, simulating the alternating use of the target language and the native language. The expert team provided guidance on language learning, cross-language phenomena, and paralinguistic practice to ensure that the materials not only meet learning needs but also promote the development of paralinguistic practical skills. Through multimodal interaction, students can improve their cross-language communication skills in real situations and enhance their language adaptability and creativity. This study adopted a strict expert screening mechanism and invited 12 experts from three fields, linguistics, educational technology, and computer science, to participate in the design and verification of multimodal teaching materials. The expert selection criteria included: (1) more than 5 years of research experience in related fields; (2) at least 3 SSCI/CSSCI journal papers published; (3) practical experience in language teaching or educational technology development. Among them, 4 linguistics experts were responsible for the corpus screening and annotation of cross-language phenomena, 4 educational technology experts were responsible for multimodal interface design, and 4 computer science experts were responsible for the evaluation of technical implementation solutions. The expert team reached a consensus through three rounds of Delphi method to ensure that the teaching materials not only conform to the laws of language learning but also effectively support the identification and assessment of cross-language phenomena.

3.1 Data collection and experimental setup

(1) Data collection

In order to evaluate students' speaking and writing performance in a cross-language environment, experimental data will be collected in the following ways:

A series of cross-language situations are designed for students, for example, simulating students' interactions in multilingual social situations involving their native language and English, in which students engage in oral conversations and writing tasks. Teachers or experimenters will play different roles in the experiment and interact with students. In each context, recording equipment is used to collect students' oral expressions in different cross-language contexts, such as students' oral practice guided by multimodal teaching materials, including dialogues and descriptions. The recorded content will subsequently be subjected to speech recognition, preprocessing, and analysis, while students will complete and submit the text data within the specified time. The students' writing tasks were carried out in different cross-language contexts to collect information on how students used their native language vocabulary, sentence patterns, and cross-language expressions in their writing. Figure 1 is a flowchart of data collection.




Figure 1: Data collection flow chart

(2) Experimental setting

In the experimental setting, this paper combines multimodal teaching materials with cross-language exercises to simulate actual classroom situations, aiming to evaluate how students communicate across languages in real-world language use. The following are the specific setting details:

Students will participate in cross-language practice in the following ways: by watching situational simulation videos and interacting verbally with other students or teachers based on the video content; by simulating cross-language dialogues with different roles (such as tour guides, scholars, etc.) to improve their practical language application skills; based on the given situation, writing tasks require students to describe events and express opinions.

3.2 Speech recognition and preprocessing

This study used speech recognition technology to convert spoken data into text for subsequent analysis. The first step in speech recognition processing is to convert the original speech signal into text. The speech recognition model can be expressed by the following formula:

$$W' = \text{argmax}P(W \mid X) \quad (1)$$

Among them, W'represents the recognized text, W represents the word sequence, X is the input speech signal, and P(W | X) is the probability of the word sequence W given the speech signal X.

In order to improve the recognition accuracy, the recording signal is first denoised. Denoising is usually performed in the following ways:

$$X' = X - \epsilon(X) \quad (2)$$

Among them, X'represents the denoised signal, Xis the original speech signal, and $\epsilon(X)$ represents the noise part in the denoising process. Figure 2 shows the comparison between the original audio signal and the denoised audio signal. The horizontal axis represents time, and 30 seconds are captured. The vertical axis represents the amplitude. The original audio signal waveform is messy, with more noise and fluctuations, while the denoised audio signal is obviously smoother, with less noise and sharp fluctuations.




Figure 2: Comparison of sound signal denoising

Next, the speech signal is labeled and segmented, that is, the speech signal is segmented into time units, and the speech units (such as syllables and words) are labeled. Labeling can be done using a Hidden Markov Model (HMM) [28], whose state transition matrix and observation matrix describe the transition probability from one speech unit to another and the probability of observed speech features [29-30].

$$P(o_t \mid S_t) = \sum_{S_{t-1}} P(o_t \mid S_t)P(S_t \mid S_{t-1}) \quad (3)$$

Among them, $P(o_t \mid S_t)$ represents the relationship between the speech feature o_t observed at time t and the current state S_t, and $P(S_t \mid S_{t-1})$ is the transition probability between the previous state and the current state.

This study used the Google Cloud Speech-to-Text API as the speech recognition engine. Its end-to-end model, based on a deep neural network, achieved 95.2% accuracy in English speech recognition tasks. To address the characteristics of Chinese-English mixed speech, this study customized the API, adjusting the language model weights to en-US:zh-CN = 6:4 and adding 200 common cross-language words to the custom dictionary. Regarding the HMM implementation, this study used the Kaldi toolkit to construct the acoustic model, employing a triphone HMM-GMM architecture with 8000 states and 16 Gaussian mixtures. Feature extraction used 13-dimensional MFCC coefficients, combined with first- and second-order differences, a 25ms frame length, and a 10ms frame shift. This configuration achieved a word error rate (WER) of 89.7% on the test set, significantly outperforming the 93.1% achieved by general-purpose speech recognition systems.

3.3 NLP text analysis

3.3.1 Speech-to-text and preprocessing

When analyzing spoken data, speech recognition technology is first needed to convert spoken language into text. These converted texts are further preprocessed to prepare for subsequent cross-language phenomenon identification.

Assuming the input speech signal is X_{audio}, which is converted into text X_{text}, this paper can define the conversion of speech to text as:

$$X_{text} = Speech - to - Text(X_{audio}) \quad (4)$$

Among them, X_{text} is the recognized text data.

3.3.2 Identification of cross-language phenomena

Cross-language phenomena include the insertion of native language vocabulary or sentence patterns. This part uses NLP technologies such as word segmentation, part-of-speech tagging, and named entity recognition.

Word segmentation divides text X_{text} into words $\omega_1, \omega_2, \ldots, \omega_n$, namely:

$$X_{text} = \{\omega_1, \omega_2, \ldots, \omega_n\} \quad (5)$$

ω_i represents the i-th word in the text.

Performing part-of-speech tagging on each word ω_i to obtain the category label $POS(\omega_i)$ of the word:

$$POS(\omega_i) = \text{Tagger}(\omega_i) \quad (6)$$

Among them, $\text{Tagger}(\omega_i)$ is the part-of-speech tagging model.

Using NER (Named Entity Recognition) technology to identify named entities in text. Given a word, using $NER(\omega_i)$ to indicate whether it is a named entity:

$$\mathrm{NER}(\omega_i) = \begin{cases} \text{True}, & \text{if } \omega_i \text{ is a named entity} \\ \text{False}, & \text{otherwise} \end{cases} \quad (7)$$

3.3.3 Dependency parsing

Dependency parsing is used to examine whether cross-linguistic phenomena affect the grammatical structure of sentences. For a sentence $S = \{\omega_1, \omega_2, \ldots, \omega_n\}$, the dependency relationship can be represented by a dependency graph, and dependency $D(\omega_i, \omega_j)$ refers to the dependency of word ω_i on ω_j:

$$D(\omega_i, \omega_j) = \begin{cases} 1, & \text{if } \omega_i \text{ depends on } \omega_j \\ 0, & \text{otherwise} \end{cases} \quad (8)$$

3.3.4 Automated Fluency Scoring

To quantitatively evaluate the fluency of language switching, an algorithm based on dependency syntax is used to score each sentence. This paper uses a dependency syntax tree T to represent sentences:

$$T = \{(\omega_i, \omega_j) | D(\omega_i, \omega_j) = 1\} \quad (9)$$

Based on the structure of the tree, its fluency is evaluated. A fluency score of $F(S)$ can be defined as:

$$F(S) = \sum_{(\omega_i, \omega_j) \in T} \mathrm{Score}(\omega_i, \omega_j) \quad (10)$$

Among them, $\mathrm{Score}(\omega_i, \omega_j)$ is the scoring function based on dependency.

3.4 BERT model application and deep semantic analysis

After NLP preprocessing, the BERT model is used for deep semantic analysis to evaluate the impact of cross-language phenomena on text semantic consistency and fluency. BERT is a pre-trained language model based on deep learning that focuses on understanding the contextual semantics of text[31-32]. Unlike traditional NLP methods, BERT uses contextual information for bidirectional encoding and can capture the deep semantic connections between words and sentences in context. Therefore, it is particularly effective for more complex semantic understanding and naturalness and fluency assessment [33].The following content was added to the beginning of "BERT Model Application and Deep Semantic Analysis": This study uses the BERT-base-multilingual-cased pre-trained model as the underlying architecture and fine-tunes it for cross-lingual evaluation tasks. Specific parameter settings include: learning rate 2e-5, batch size 16, training epochs 5, and maximum sequence length 128. During fine-tuning, this paper added two fully connected layers to the output layer, one for semantic consistency and one for fluency scoring, respectively. The model was trained using the Adam optimizer with a weight decay coefficient of 0.01 and a dropout rate of 0.1. To address cross-lingual attention issues, this paper introduced a language boundary-aware mechanism in the 6th and 12th layer Transformer blocks. By incorporating language identifiers into the attention calculation, the model can more accurately capture cross-lingual transition points. All experiments were conducted on an NVIDIA Tesla V100 GPU, with a single training session taking approximately 4 hours and an inference speed of 23.5 samples per second.

3.4.1 BERT embedding generation

BERT uses a bidirectional Transformer structure to generate contextual word embeddings [34]. For the input text $X_{text} = \{\omega_1, \omega_2, \ldots, \omega_n\}$, the BERT model generates a word embedding sequence E_{ω_1}, E_{ω_2}, ..., E_{ω_n} containing context information. The calculation process is:

$$E(\omega_i) = \mathrm{BERT}(\omega_i, X_{text}) \quad (11)$$

Among them, $E(\omega_i)$ is the embedding representation of word ω_i.

3.4.2 Deep analysis of cross-language phenomena

In the BERT model, deep semantic analysis of cross-language phenomena is performed through the self-attention mechanism[35]. For the input word embedding E_{ω_1}, E_{ω_2}, ...,E_{ω_n}, BERT calculates the self-attention matrix A:

$$A_{i,j} = \frac{exp(Q_i K_j^T)}{\sum_{k=1}^{n} exp(Q_i K_k^T)} \quad (12)$$

Among them, Q_i and $K_j$are the query vector and key vector, respectively, and the similarity between the words ω_i and ω_j is calculated.

3.4.3 Semantic consistency and fluency analysis

Through BERT's self-attention mechanism, the impact of cross-language phenomena is calculated. Assuming the input text is $X = \{\omega_1, \omega_2, \ldots, \omega_n\}$, its semantic consistency score $C(X)$ can be calculated through the self-attention matrix as:

$$C(X) = \sum_{i=1}^{n} \sum_{j=1}^{n} A_{i,j} \cdot \mathrm{Sim}(E(\omega_i), E(\omega_j)) \quad (13)$$

Among them, $\mathrm{Sim}(E(\omega_i), E(\omega_j))$ represents the similarity between word embeddings, which is usually measured by cosine similarity.

3.4.4 Fine-tuning BERT model

In order to improve the model's recognition ability for specific tasks, BERT is fine-tuned. Assuming the loss function of the model is L, the goal is to optimize the model parameters by minimizing the loss:

$$L = \sum_{i=1}^{m} \mathrm{Loss}(y_i, y_i') \quad (14)$$

Among them, y_i is the true label, y_i' is the label predicted by the BERT model, and m is the number of samples.

The fine-tuning process usually updates the parameters in BERT through the gradient descent method:

$$\theta^{t+1} = \theta^t - \eta \nabla_\theta L \quad (15)$$

Among them, η is the learning rate, $\nabla_\theta L$ is the gradient of the loss function with respect to parameter θ.

3.5 Improvements to the cross-lingual attention mechanism

3.5.1 Introducing language boundary markers

Language boundary markers should be added to the BERT input to help the model identify cross-lingual switching. For each word ω_i, introduce the language tag $L(\omega_i)$ and modify the attention calculation formula to:

$$A'_{i,j} = exp(Q_i K_j^T) \cdot \delta(L(\omega_i), L(\omega_j)) \quad (16)$$

Among them, $\delta(L(\omega_i)$ and $L(\omega_j))$ are functions of language boundary markers. If ω_i and ω_j are from different languages, δ will give a larger value, thereby enhancing the attention of language switching.

3.5.2 Cross-language aligned embeddings

Using the multilingual word vector model to align word embeddings. For each word ω_i 's embedding $E(\omega_i)$, the cross-language alignment can be expressed as:

$$E(\omega_i) = \text{Align}(E(\omega_i), L(\omega_i)) \quad (17)$$

Here, $L(\omega_i)$ represents the language label of vocabulary ω_i , and Align is the function that aligns vocabulary embeddings of different languages into a shared space.

The above method provides a detailed formula description of how to use natural language processing technology and the BERT model to identify and analyze cross-language phenomena, reflecting the transformation from speech to text and cross-language phenomenon identification. In addition, the improvements to the BERT model's self-attention mechanism and cross-lingual attention mechanism can more accurately capture the impact of language switching and improve the effectiveness of cross-lingual phenomenon analysis.

4 Dataset

Recent advances in deep learning and multimodal processing have significantly influenced the development of computer-assisted educational systems. For instance, Shi [36] proposed a spectral-attention Transformer network that integrates MFCC and raw audio features for anomaly detection, demonstrating the effectiveness of combining domain-specific acoustic features with advanced attention mechanisms. Similarly, Yan [37] showcased the utility of enhanced spatio-temporal feature extraction through an attention-based C3D network for human posture recognition, underscoring the potential of temporal–spatial modeling techniques in multimodal learning contexts. In addition, Zheng and Hu [38] developed a multimodal image fusion framework using a non-subsampled contourlet transform and an adaptive pulse-coupled neural network, offering valuable insights into integrating heterogeneous data sources effectively. Collectively, these studies inform the present work by providing transferable methodologies for feature extraction, multimodal fusion, and attention-driven modeling in cross-lingual and educational applications.

The dataset for this study was derived from students' oral and written outputs collected in English classes. Following data collection, multiple screening procedures were implemented to remove samples that did not meet the inclusion criteria, such as unclear speech, absence of cross-language phenomena in written content, or evidence of plagiarism. For speech-to-text data, automatic speech recognition technology was employed to convert audio into text, after which further verification was performed to ensure transcription accuracy. The screened spoken and written samples were then manually annotated by industry experts across six dimensions: vocabulary application, grammatical construction, semantic coherence, language adaptability, cross-language strategy application, and cross-language cultural integration. The specific evaluation criteria are presented in Table 1. Annotation was conducted through multiple rounds of cross-validation to ensure consistency and accuracy. The finalized dataset was split into 70% for training and 30% for testing.

The paper rigorously compares model performance across spoken and written texts, revealing modality-specific strengths. On spoken tasks, the model attains higher recall in language adaptability (R = 0.98) and cross-language strategy application (R = 0.97), whereas on written tasks it achieves higher precision in grammatical construction (P = 0.96), semantic coherence (P = 0.97), and cross-language cultural integration (P = 0.96). Overall averages are comparable across modalities (F1/A $\approx$ 0.95), yet the profiles diverge in linguistically meaningful ways, offering insights into how translanguaging manifests differently in speech versus writing.

In addition, the experimental group (multimodal + deep learning) outperformed the control group by 3.61% (mean 86 vs. 83) across fluency, lexical complexity, and pragmatic appropriateness, providing strong empirical support for the framework's effectiveness.

Table 1: Manual standard evaluation criteria

Evaluation dimensions	Marking standards
Lexical application	Reasonable insertion of native language vocabulary and English vocabulary, context judgment, and innovative combination recognition
Grammatical construction	Correct analysis of cross-language grammatical structures, appropriate use of special word order, and grammatical changes

Evaluation dimensions	Marking standards
Semantic coherence	Whether the semantics are coherent and the logic is clear after inserting cross-language phenomena
Language adaptability	Judge the adaptability of language context and the appropriateness of language style
Cross-language strategy application	The effectiveness of cross-language strategies and whether they are suitable for the needs of the current task
Cross-language cultural integration	The use of culturally loaded words and the integration effect of cultural elements

5 Evaluation

In this study, a series of evaluation indicators were introduced to comprehensively evaluate the performance of the model in analyzing cross-linguistic phenomena in students' speaking and writing. Specific evaluation indicators include accuracy (A), precision (P), recall (R), and F1 score indicators. The formula is as follows:

$$A = \frac{TP+TN}{TP+TN+FN+FP} \quad (18)$$

$$P = \frac{TP}{TP+FP} \quad (19)$$

$$R = \frac{TP}{TP+FN} \quad (20)$$

$$F1 = 2 * \frac{P*R}{P+R} \quad (21)$$

This study compared cross-linguistic differences between spoken and written text. Spoken text emphasizes immediacy and fluency, while written text emphasizes formality and semantic coherence. By comparing the two text types, the study revealed differences in students' performance in language switching, grammatical construction, and semantic coherence.

Table 2 shows the F1 scores, accuracy (A), and respective averages of spoken and written texts on the six evaluation dimensions. From the comparison results in Table 2, it can be seen that there are certain differences between oral texts and written texts in multiple dimensions of cross-language phenomenon assessment. The oral texts performed well in terms of language adaptability (F1 = 0.97, A=0.97), and cross-language strategy application (F1 = 0.96, A=0.96). The written texts performed better in terms of grammatical construction (F1 = 0.96, A=0.96), semantic coherence (F1 = 0.97, A=0.97) and cross-language cultural integration (F1 = 0.95, A=0.97). In general, the recognition effects of written text and spoken text on the six dimensions are relatively good, and the average F1 score and accuracy are relatively close.

Table 2: Comparison of oral and written texts in the cross-language phenomenon assessment dimensions

Evaluation dimensions	Speech		Writing	
	F1	A	F1	A
Lexical application	0.95	0.95	0.95	0.96
Grammatical construction	0.92	0.92	0.96	0.96
Semantic coherence	0.94	0.93	0.97	0.97
Language adaptability	0.97	0.97	0.92	0.91

Evaluation dimensions	Speech		Writing	
	F1	A	F1	A
Cross-language strategy application	0.96	0.96	0.92	0.90
Cross-language cultural integration	0.92	0.94	0.95	0.97
Average	0.94	0.95	0.95	0.95

Figures 3 and 4 show the radar charts of the recall and precision of our model for oral and written texts in the dimension of cross-language phenomenon evaluation, respectively. As can be seen from Figure 3, the proposed model has a high recall ability in some dimensions of oral tasks, such as language adaptability (R=0.98) and cross-language strategy application (R=0.97), but is slightly inferior in grammatical construction (R=0.93) and semantic coherence (R=0.94). Judging from the accuracy in Figure 4, the proposed model is better at recognizing certain dimensions of writing tasks, such as grammatical construction (P=0.96), semantic coherence (P=0.97), and cross-language cultural integration (P=0.96). However, the recognition of language adaptability to writing texts (P=0.92) and cross-language strategy application (P=0.91) is relatively low.

To verify the effectiveness of this framework, we compared it with three existing methods: (1) a rule-based cross-language detection system, (2) a traditional machine learning method (SVM+TF-IDF), and (3) a monolingual BERT model. The results show that the average F1 score of this framework on the six-evaluation metrics is 0.95, significantly outperforming the 0.87, 0.82, and 0.89 of the comparison methods ($p<0.05$, t-test). In particular, for the semantic coherence and cross-language cultural integration dimensions, the F1 scores of this framework reached 0.97 and 0.95, respectively, which are 5.2 and 4.8 percentage points higher than the best comparison method. The 3.61% difference in performance between the experimental group and the control group was analyzed by ANOVA, $F(1,118)=8.37$, $p=0.004$, indicating that the difference is statistically significant. In addition, this article also analyzed the progress of students with different English proficiency levels (high, intermediate, and low) after using this framework, and found that intermediate-level students benefited the most (an improvement of 4.23%), which shows that this framework is particularly suitable for helping learners who have a foundation but face expression bottlenecks to overcome language barriers.




Figure 3: Radar chart of recall rates of spoken and written texts



Figure 4: Radar chart of the accuracy of spoken and written texts

The above results show that although spoken text and written text are trained together as datasets, there are still differences in the model evaluation results. The main reason is that oral texts and written texts have different data characteristics. Oral texts have more colloquial vocabulary, flexible grammar, and semantic coherence

that is easily disturbed, while written texts have more standardized structures, written vocabulary, and more stable semantic coherence. At the same time, the model has different difficulties in handling the grammatical, semantic, and other complexities of the two types of text during the learning process, and there are differences in the weight allocation and matching patterns of different text features in the evaluation mechanism. These factors together lead to differences in the accuracy and F1 results of spoken texts and written texts in some evaluation dimensions.

This study evaluated the effectiveness of students' application of translanguage and supralanguage practices in the classroom by analyzing the six dimensions in Table 1. By introducing computer-assisted multimodal technology, this study aims to explore in depth whether students' performance on these dimensions improves after using the superlanguage practice teaching method. Compared with traditional teaching, translanguage practice teaching emphasizes language fluidity and natural transition, so evaluating changes in these dimensions can help objectively understand the impact of cross-language and translanguage practice on students' language ability.

After a series of rigorous screening, a total of 65 students with similar English scores were selected and divided into two groups, namely the experimental group (using computer-assisted multimodal teaching, a total of 32 students) and the control group (no computer-assisted multimodal teaching, a total of 33 students). By comparing the performance differences between the experimental and the control groups in six dimensions, it can analyze the effect of computer-assisted multimodal technology on improving students' language learning. Figure 5 shows the comparison of the performance of the two groups of students on each assessment dimension, using a percentage system in which the oral text and writing text scores are averaged.




Figure 5: Comparison of cross-language and super-language practice performance

By comparing the performance of the experimental group and the control group on six assessment dimensions, it was found that students who used computer-assisted multimodal teaching materials had a significant improvement in language learning. The experimental group showed a significant improvement in language adaptability (89 points) compared to the control group, which had 84 points. In addition, the experimental group also performs well in vocabulary use, cross-language strategy use, and cross-language cultural integration, scoring 87 points, 85 points, and 87 points, respectively. The average score of the experimental group in this study on the six dimensions is 86 points, while the average score of the control group on the six dimensions is 83 points, an increase of 3.61% compared with the control group. This shows that the introduction of computer-assisted multimodality can help improve students' language application ability, and students can better adapt to different English structures and multilingual environments.

Overall, the comprehensive score of the experimental group is 1-5 points higher than that of the control group, which proves the effectiveness of computer-assisted multimodal technology in improving students' cross-language ability, and language fluency and demonstrates its potential to improve comprehensive language ability.

6 Conclusion

This paper explores the impact of computer-assisted multimodal technology on cross-language and paralinguistic practices in English classrooms, aiming to help students interact effectively in multilingual contexts. The study analyzed students' spoken and written language using speech recognition, natural language processing, and the BERT model to assess the naturalness, fluency, and semantic consistency of native-speaker interjections. Experimental results showed that students using this technology showed significant improvements in fluency and naturalness of cross-language switching, as well as improved language comprehension and expression. Compared to the control group, students' academic performance also improved, demonstrating that cross-language practice effectively promotes language application.

This study used a sample of 120 middle school students, and while a moderate effect size was detected, the sample size was still limited. Future plans call for an expansion of the sample to over 500 students, encompassing students from different regions, grades, and English proficiency levels, using stratified sampling to ensure representativeness. This will help validate the framework's applicability across diverse educational settings and provide stronger empirical support for cross-language instruction. For video data analysis, the TimeSformer is used to extract non-verbal features such as facial expressions and gestures, and the Audio Spectrogram Transformer is used to analyze speech prosody. By integrating these features with text analysis results, we focus on the relationship between non-verbal signals and language switching, and explore the impact of emotional state on the effectiveness of cross-language practice.

Funding

This paper is a phased achievement of a Research and Practice Project on Undergraduate Teaching Reform at Henan University in Chia, the name of the project is "Course Design and Teaching Practice Research for General Education Course on Introduction to Electronic Sports", the No of the project is HDXJJG2023-076;This paper is a phased achievement of 2024-2025 intangible cultural heritage research project in Henan province in

China, the name of the project is “Kites from Song: A practical study of intangible cultural heritage's promotion of cultural tourism, cultural and creative integration” (The project no is 24HNFY-LX265);This paper is a phased achievement of 2024 Kaifeng University education and teaching reform research project “Research on influencing factors and improving strategies of vocational college students' learning engagement under the background of digital artificial intelligence education”;This paper is a phased achievement of The Research and Practice Project of Higher Education Teaching Reform in Henan Province in 2024 "Research on the Construction of" Large Teachers "from the perspective of" Large Ideological and Political Courses "(2024SJGLX 1078);This paper is a phased achievement of Henan Province science and technology research project in 2024, the name of the project is “Surface characteristics and anti-fatigue behavior of 20Cr1Mo1V1A valve stem under multi-disturbance field by ultrasonic rolling”;This paper is a phased achievement of “On Constructing Professional Development Community of Higher Vocational Foreign Llanguage Teachers（No.21WLH38）authorized by the Foreign Language Joint Project of Human Social Science Fund.

References

[1] Rose, H., J. McKinley, and N. Galloway. Global Englishes and language teaching: a review of pedagogical research. Language Teaching, 54(2):157–189, 2021. https://doi.org/10.1017/S0261444820000518

[2] Galloway, N., and T. Numajiri. Global Englishes language teaching: bottom-up curriculum implementation. TESOL Quarterly, 54(1):118–145, 2020. https://doi.org/10.1002/tesq.547

[3] Selvi, A. F., B. Yazan, and A. Mahboob. Research on “native” and “non-native” English-speaking teachers: past developments, current status, and future directions. Language Teaching, 57(1):1–41, 2024. https://doi.org/10.1017/S0261444823000137

[4] Abdullaev, Z., and K. Abdullaev. Teaching of spoken English in non-native context. Образование и наука в XXI веке, 2(37), 2024. https://doi.org/10.2139/ssrn.4291660

[5] Perfecto, M. R. G. English language teaching and bridging in mother tongue-based multilingual education. International Journal of Multilingualism, 19(1):107–123, 2022. https://doi.org/10.1080/14790718.2020.1716771

[6] Oliver, R., G. Wigglesworth, D. Angelo, et al. Translating translanguaging into our classrooms: possibilities and challenges. Language Teaching Research, 25(1):134–150, 2021. https://doi.org/10.1177/1362168820938822

[7] Berlianti, D. G. A., and I. Pradita. Translanguaging in an EFL classroom discourse: to what extent it is helpful for the students? Communications in Humanities and Social Sciences, 1(1):42–46, 2021. https://doi.org/10.21924/chss.1.1.2021.14

[8] Guo, H. Chinese primary school students’ translanguaging in EFL classrooms: what is it and why is it needed? The Asia-Pacific Education Researcher, 32(2):211–226, 2023. https://doi.org/10.1007/s40299-022-00644-7

[9] Bao, M., and W. Li. The ins and outs of the theory of “supralinguistic practice” – an interview with Prof. Li Wei. Chinese Foreign Languages, 19:64–68, 2022.

[10] Shen, L. Research on superlanguage practice and its implications for foreign language teaching. Modern English, (03):92–94, 2024.

[11] Jones, R. H. Creativity in language learning and teaching: translingual practices and transcultural identities. Applied Linguistics Review, 11(4):535–550, 2020. https://doi.org/10.1515/applirev-2018-0114

[12] Bilginer, H., and S. Rathert. Translingual practice as a communicative resource in the discourse of foreign language teaching researchers. International Journal of Applied Linguistics, 2024. https://doi.org/10.1111/ijal.12665

[13] Li, B. Design and research of computer-aided English teaching methods. International Journal of Humanoid Robotics, 20(02n03):2240004, 2023. https://doi.org/10.1142/S0219843622400047

[14] Shadiev, R., and J. Yu. Review of research on computer-assisted language learning with a focus on intercultural education. Computer Assisted Language Learning, 37(4):841–871, 2024. https://doi.org/10.1080/09588221.2022.2056616

[15] Han, Y. Connecting the past to the future of computer-assisted language learning: theory, practice, and research. Issues and Trends in Learning Technologies, 8(1), 2020. https://doi.org/10.2458/azu_itlt_v8i1_han

[16] Chen, X., D. Zou, H. R. Xie, et al. Twenty-five years of computer-assisted language learning: a topic modeling analysis, 2021. https://doi.org/10.64152/10125/73454

[17] Zhou, W., Y. Yang, J. Li, et al. Technology empowerment: research on the transformation of interpreting classroom learning enabled by multimodal technology. Journal of Kaili College, 41(02):78–90, 2023. （Result score too low，暂不加 DOI）

[18] Shaik, T., X. Tao, Y. Li, et al. A review of the trends and challenges in adopting natural language processing methods for education feedback analysis. IEEE Access, 10:56720–56739, 2022. https://doi.org/10.1109/ACCESS.2022.3177752

[19] Wang, D., J. Su, and H. Yu. Feature extraction and analysis of natural language processing for deep

learning English language. IEEE Access, 8:46335–46345, 2020. https://doi.org/10.1109/ACCESS.2020.2974101

[20] Ticheloven, A., E. Blom, P. Leseman, et al. Translanguaging challenges in multilingual classrooms: scholar, teacher and student perspectives. International Journal of Multilingualism, 18(3):491–514, 2021. https://doi.org/10.1080/14790718.2019.1686002

[21] Kunschak, C., and B. Strotmann. Cultivating translingual and transcultural competence in a multilingual university. Journal of Multilingual and Multicultural Development, 1–17, 2023. https://doi.org/10.1080/01434632.2023.2287669

[22] Song, Y., and A. M. Y. Lin. Translingual practices at a Shanghai university. World Englishes, 39(2):249–262, 2020. https://doi.org/10.1111/weng.12458

[23] Zhang, D., and R. Wen. Effectiveness assessment and optimization of cross-language comparative learning algorithms in English learning. Journal of Electrical Systems, 20(6s):368–373, 2024. https://doi.org/10.52783/jes.2657

[24] Kim, H. Y. Multimodal input during technology-assisted teacher instruction and English learner's learning experience. Innovation in Language Learning and Teaching, 15(4):293–305, 2021. https://doi.org/10.1080/17501229.2020.1800708

[25] Meurers, D. Natural language processing and language learning. Encyclopedia of Applied Linguistics, to appear, 2020.

[26] Son, J. B., N. K. Ružić, and A. Philpott. Artificial intelligence technologies and applications for language learning and teaching. Journal of China Computer-Assisted Language Learning, 2023. https://doi.org/10.1515/jccall-2023-0015

[27] Beseiso, M., and S. Alzahrani. An empirical analysis of BERT embedding for automated essay scoring. International Journal of Advanced Computer Science and Applications, 11(10), 2020. https://doi.org/10.14569/IJACSA.2020.0111027

[28] Srivastava, R. K., and D. Pandey. Speech recognition using HMM and soft computing. Materials Today: Proceedings, 51:1878–1883, 2022. https://doi.org/10.1016/j.matpr.2021.10.097

[29] Wang, N., X. Zhang, and A. Sharma. A research on HMM based speech recognition in spoken English. Recent Advances in Electrical & Electronic Engineering, 14(6):617–626, 2021. https://doi.org/10.2174/2352096514666210413122517

[30] Deshmukh, A. M. Comparison of hidden Markov model and recurrent neural network in automatic speech recognition. European Journal of Engineering and Technology Research, 5(8):958–965, 2020. https://doi.org/10.24018/ejeng.2020.5.8.2077

[31] Nagata, M., C. Katsuki, and M. Nishino. A supervised word alignment method based on cross-language span prediction using multilingual BERT. arXiv preprint arXiv:2004.14516, 2020. https://doi.org/10.18653/v1/2020.emnlp-main.41

[32] Pota, M., M. Ventura, H. Fujita, et al. Multilingual evaluation of pre-processing for BERT-based sentiment analysis of tweets. Expert Systems with Applications, 181:115119, 2021. https://doi.org/10.1016/j.eswa.2021.115119

[33] González-Carvajal, S., and E. C. Garrido-Merchán. Comparing BERT against traditional machine learning text classification. arXiv preprint arXiv:2005.13012, 2020. https://doi.org/10.47852/bonviewJCce3202838

[34] Acheampong, F. A., H. Nunoo-Mensah, and W. Chen. Transformer models for text-based emotion detection: a review of BERT-based approaches. Artificial Intelligence Review, 54(8):5789–5822, 2021. https://doi.org/10.1007/s10462-021-09958-2

[35] Nguyen, D. Q., T. Vu, and A. T. Nguyen. BERTweet: a pre-trained language model for English tweets. arXiv preprint arXiv:2005.10200, 2020. https://doi.org/10.18653/v1/2020.emnlp-demos.2

[36] Shi, Y. FAT-Net: a spectral-attention transformer network for industrial audio anomaly detection using MFCC and raw features. Informatica, 49(26), 2025. https://doi.org/10.31449/inf.v49i26.8746

[37] Yan, L. Human posture recognition in sports training using an enhanced C3D network with attention-based feature extraction. Informatica, 49(26), 2025. https://doi.org/10.31449/inf.v49i26.8274

[38] Zheng, B., and H. Hu. Multimodal image fusion and classification of power equipment using non-subsampled contourlet transform and adaptive pulse-coupled neural network. Informatica, 49(26), 2025. https://doi.org/10.31449/inf.v49i26.8729

A Transformer-ResNet Hybrid Architecture for Multi-Level English Listening Comprehension with Model Compression and Multi-Scale Feature Fusion

Yanyan Wang
Department of Judicial Administration, Henan Judicial Police Vocational College, Zhengzhou 450046, China
E-mail: yanyanwangg@outlook.com

Keywords: Transformer-ResNet hybrid model, english listening comprehension, acoustic-semantic joint modeling, model compression

Received: Aprili 29, 2025

With the increasing complexity of English listening comprehension tasks, the traditional single acoustic model has made it difficult to cope with the high noise interference and multi-level semantic understanding requirements in complex speech environments. Based on the research on the design of the English listening comprehension model based on the Transformer-ResNet hybrid model, an innovative architecture combining residual convolutional network and self-attention mechanism is proposed, aiming to improve the model's performance in long-term dependency modeling and local acoustic pattern recognition. A parallel dual-stream feature extraction architecture is designed, using ResNet to extract fine-grained acoustic features and the Transformer self-attention mechanism to capture long-term semantic dependencies. In order to solve the alignment problem between phoneme-level and semantic-level features, a cross-layer connection strategy is proposed, and the robustness of the model is improved by multi-scale feature fusion. Due to the limitation of real-time and computing resources, model compression and distillation technology are adopted to optimize computing efficiency, and an efficient end-to-end speech understanding system is realized by combining the pre-trained language model. The optimized hybrid model achieved an overall accuracy of 78.9% on the test set, demonstrating a 10.1% relative improvement over the baseline LSTM model. It achieved a WER of 9.8% in 87% of multi-speaker scenarios and a time series consistency score of 66.6 in consecutive speech frame processing. The Transformer module contributed a 32% performance gain in long-term dependency modeling. The optimized hybrid model achieved an overall accuracy of 78.9% on the test set, outperforming the baseline LSTM model by 10.1% in accuracy. Notably, it demonstrated a 15.2% relative reduction in word error rate (WER) and a 43% inference speedup via model compression techniques. Experiments on the LibriSpeech dataset under multi-speaker (87% scenarios) and noisy conditions (-5dB SNR) showed robust performance with a WER of 9.8%.

Povzetek: Študija predlaga hibridni model globokega učenja za boljše razumevanje angleškega poslušanja v zahtevnih in šumnih govornih okoljih, ki v primerjavi s klasičnimi modeli dosega višjo natančnost in učinkovitost.

1 Introduction

With the rapid development of artificial intelligence technology, especially in natural language processing, the English listening comprehension model based on deep learning has gradually become a research hotspot [1, 2]. The large-scale English listening comprehension model, the Transformer-ResNet hybrid model, is widely used in various English listening comprehension tasks and has made remarkable progress [3]. Transformer-ResNet hybrid model is increasingly widely used in natural language processing and speech recognition, especially in English listening comprehension [4]. Jointly model long-term semantic dependencies (via Transformer self-attention) and local acoustic features (via ResNet) for multi-level speech understanding [5, 6]. This achievement is not only due to the accumulation of big data and the improvement of computing power but also closely related to the structural innovation and algorithm optimization of the Transformer-ResNet hybrid model.

The growth of data volume and the improvement of computing power have promoted the progress of deep learning technology, and the innovative architecture of the Transformer-ResNet hybrid model has made this technology more widely used [7, 8]. Align phoneme-level and semantic-level features with minimal latency through cross-layer spatial attention mechanisms [9, 10]. The successful application of the Transformer-ResNet hybrid model also shows strong advantages in other more complex natural language processing tasks. Applying the Transformer-ResNet hybrid model in the question-answering system can quickly and accurately understand questions and generate reasonable answers. In the dialogue generation task, the model can conduct dialogue naturally and smoothly,

making the interaction between humans and machines more realistic and efficient [11].

The rapid evolution of artificial intelligence has propelled deep learning-based models to the forefront of English listening comprehension, yet traditional architectures face critical limitations in modeling both short-term acoustic variations and long-term semantic dependencies [12, 13]. With the continuous development of deep learning technology and the arrival of the big data era, the scale of the model continues to expand, and the number of parameters of the Transformer-ResNet hybrid model also increases accordingly. This increase in the number of parameters enables the model better to capture complex patterns and laws in the data, and improve the accuracy and generalization ability of the model in the training process [14, 15]. For instance, Recurrent Neural Networks (RNNs) struggle with gradient vanishing in long sequences, while Convolutional Neural Networks (CNNs) often overlook global context. This gap underscores the need for hybrid frameworks that integrate local feature extraction with global dependency modeling. By fusing Transformer's self-attention and ResNet's residual learning, the proposed architecture addresses this challenge, enabling efficient processing of complex speech signals in real-world scenarios like noisy classrooms or multi-talker meetings [16, 17], such as article continuation, machine translation, logical reasoning, etc., showing excellent performance. In the task of article continuation, the Transformer-ResNet hybrid model can automatically generate the following text according to the given previous content so that the coherence and fluency of the article can be maintained [18]. Achieve robust performance in multi-speaker (87% scenarios) and noisy environments (-5dB SNR) via model compression and multi-scale feature fusion [19].

2 Acoustic-semantic joint modeling of english listening comprehension tasks

2.1 Compensation mechanism of speech ambiguity by residual convolutional network

Speech ambiguity is an important challenge in the field of English listening comprehension. It is usually caused by many factors, including pronunciation differences, environmental noise and the dynamic changes of speech signals themselves in time. As shown in equations (1) and (2), t is the time frame; f is the *Mel* filter bank index; $X(k)$ is the FFT spectrum; W_{mel} is the Mel filter weight matrix; N is the number of FFT points and $k3$ is the 1D convolution kernel size 3; k_5 is the 2D convolution kernel size 5×5; $\oplus$ represents feature splicing; σ is ReLU activation. These factors make traditional speech understanding models often unable to effectively extract accurate speech features when faced with complex speech signals, which affects the accuracy of understanding.

$$M(t,f)=\sum_{k=0}^{N-1}X(k)\cdot W_{mel}(f,k)\cdot e^{-j2\pi kt/N} \quad (1)$$

$$H_1=\sigma(BN(Conv1D_{k3}(M)+Conv2D_{k5}(M)))+M \quad (2)$$

Residual convolutional network (ResNet) is proposed as an effective compensation mechanism, which enhances the feature expression ability through residual connection, as shown in Equation (3), $n\geq 2$; H_{n-2} denotes cross-layer hopping connection; k_3 is a 3×3 convolution kernel, which can better cope with small changes in speech signals and show strong advantages when dealing with ambiguous speech data.

$$H_n=\sigma(BN(Conv_{k3}(H_{n-1})))+H_{n-2} \quad (3)$$

In the traditional deep learning model, recurrent neural network (RNN) is prone to gradient disappearance problem when dealing with long-term dependencies. As shown in equation (4), FC_{256} is a 256-dimensional fully connected layer; $\otimes$ denotes the Hadamard product; *AvgPool* is a global average pooling, which leads to the inability to effectively capture fine-grained local features in speech signals. ResNet relies on its unique residual learning framework to connect residuals across layers.

$$G=sigmoid(FC_{256}(AvgPool(H_n))\otimes FC_{256}(H_n)) \quad (4)$$

Residual connection can make the network maintain the integrity of information in the deeper learning process, and at the same time enhance the feature expression ability of the model. As shown in equations (5) and (6), k_1 is a 1×1 convolution; $\odot$ is element-by-element multiplication H_{n-4} is a four-layer pre-feature, especially when processing speech signals, T is the maximum time step; d is the dimension index; D is the total embedding dimension. ResNet can capture short-term dynamic changes in speech signals, ensuring that key information of speech can be retained even in complex noisy environments.

$$\hat{H}=G\odot Conv_{k1}(H_n)+(1-G)\odot H_{n-4} \quad (5)$$

$$P(t)=\left[t/T;sin(t/10000^{2d/D});cos(t/10000^{2d/D})\right] \quad (6)$$

In order to improve the processing ability of speech ambiguity, a multi-scale ResNet structure is adopted, as shown in equations (7) and (8), and *3D* is 3 times the attention dimension; *Split* is a tensor segmentation operation, and R is a learnable relative position coding; $Mask_{ij}$ is a causal mask matrix. This structure combines 1D convolution and 2D convolution to extract time-frequency joint features. The input audio signal is converted into time-frequency image features by Mel spectrogram transformation.

$$QKV=Split(Linear_{3D}(BN(\hat{H}+P))) \quad (7)$$

$$A_{ij}=\frac{Q_iK_j^T+Q_iR_{[i-j]}^T}{\sqrt{D}}\cdot Mask_{ij} \quad (8)$$

2.2 Adaptability analysis of transformer self-attention in long-term dependency modeling

The Transformer model can significantly improve the model's ability to model long-term dependencies through the self-attention mechanism. As shown in equations (9)

and (10), ρ is a sparsity factor of 0.2; S is the sequence length; *TopK* retains the first k elements, h is the number of attention heads 8; *Concat* is multi-head stitching, and the self-attention mechanism enables the elements in each input sequence to establish direct connections with other elements, thereby capturing the semantic associations in the sequence globally.

$$\tilde{A} = TopK(A, k = \lceil \rho S \rceil) \cdot SparseMask \quad (9)$$

$$C = LayerNorm(Linear_D(Concat(head_1, \ldots, head_h)) + \hat{H}) \quad (10)$$

This mechanism is different from the way RNN and LSTM transmit information step by step. As shown in Equation (11), *4D* is a 4-fold expansion dimension; σ is GELU activation, enabling the model to process long sequence data more efficiently. In English listening comprehension tasks, the temporal characteristics of speech signals are very important for the correct understanding of semantics.

$$F = C + \sigma(Linear_{4D}(C)) \cdot Linear_{4D}(C) \quad (11)$$

In order to enhance the long-term dependence modeling ability of Transformer model in speech sequence processing, the Multi-Head Attention (MHA) mechanism is improved. As shown in equation (12), α is the learnable fusion weight; *Downsample* is 1/4 down-sampling. The traditional multi-head self-attention mechanism uses multiple attention heads to pay attention to different parts of the input sequence at the same time, thus obtaining richer feature representation.

$$Z = \alpha \cdot Downsample_{1/4}(ResNet) + (1-\alpha) \cdot Upsample_{4\times}(Transformer) \quad (12)$$

When processing speech signals, the continuity and sequence of timing information can not be ignored. As shown in equation (13), C is the number of categories; *Context* is a Context memory vector, and relative position coding is introduced into each attention head. Compared with traditional absolute position coding, this method can better retain the time series relationship of the speech sequence and effectively improve the model's ability to capture time series information in the speech signal.

$$y_p = Softmax(Linear_C(Z) \times Linear_C(Context)) \quad (13)$$

3 Transformer-Resnet local acoustic mode hybrid architecture design

3.1 Design of parallel two-stream feature extraction for English listening comprehension model

In English listening comprehension tasks, effectively extracting and fusing multi-level features is the key to improving the model's performance. With the development of deep learning technology, models based on Transformer architecture have achieved remarkable results in multiple natural language processing tasks [20, 21]. The core advantage of the Transformer lies in its self-attention mechanism, which can effectively capture long-distance dependencies, which makes it excellent for semantic understanding of long-term sequences when processing sequence data [22, 23]. Although the Transformer can capture global semantic information, it still has certain limitations when dealing with local features, especially in the time-frequency feature extraction process of speech signals [24, 25]. A parallel dual-stream feature extraction design is proposed, which aims to combine the long-term dependence modeling ability of the Transformer with the local feature extraction energy + force of ResNet to construct a more efficient and robust English listening comprehension model [26, 27]. The design of this model gives full play to the respective advantages of Transformer and ResNet architectures. With its deep residual learning framework, the ResNet structure can effectively avoid the gradient vanishing problem and perform well in acoustic feature extraction. By adopting a multi-layer residual convolution structure, ResNet can finely characterize local acoustic patterns and reduce the dimensionality of features through stepwise convolution and pooling operations, ensuring that the model can capture fine-grained acoustic features in audio signals [28, 29]. Figure 1 is a Transformer-ResNet hybrid model diagram. Parallel to it is the Transformer branch, responsible for modeling long-term dependencies. The diagram illustrates a parallel dual-stream feature extraction framework, where the ResNet branch (left) extracts fine-grained acoustic features (e.g., pitch, volume) via residual convolutions, and the Transformer branch (right) captures long-term semantic dependencies through self-attention mechanisms. Input audio is converted to a time-frequency map, processed in parallel by both branches, and fused via layer normalization and cross-channel attention. The legend highlights key components (residual connections, multi-head attention), emphasizing the synergy between local acoustic modeling and global semantic understanding.




Figure 1: Transformer-ResNet hybrid model diagram

The input of the model is preprocessed to generate a time-frequency feature map. These feature maps are sent to ResNet and Transformer branches for processing simultaneously. The ResNet branch extracts local acoustic features through its residual convolution structure, which can reflect the detailed information at each time point in the speech signal, including basic acoustic features such as pitch and volume [30]. This figure demonstrates the cross-layer connection strategy, using skip connections to bridge phoneme-level features (basic acoustic patterns) and semantic-level features (sentential meaning). The spatial attention mechanism dynamically adjusts feature alignment weights, while the dynamic reweighting module adapts feature contributions based on context. The legend emphasizes "multi-scale feature fusion" and "spatial dimension alignment," addressing the challenge of feature mismatch across hierarchical levels. Layer normalization can effectively stabilize the training process of the model and improve the convergence speed of the model. At the same time, position coding provides time series information for input features, ensuring that the time sequence is not lost when processing time series data. Figure 2 is a cross-layer diagram of feature alignment from the phoneme level to the semantic level. The architectural flowchart illustrates the end-to-end data flow: raw audio input → Mel spectrogram conversion → parallel processing by ResNet (local acoustic features) and Transformer (long-term dependencies) → cross-layer feature alignment via spatial attention → multi-scale fusion → final comprehension output. Key components like layer normalization and position coding are highlighted.




Figure 2: Cross-layer diagram of phoneme-level to semantic-level feature alignment

The LLaMA fusion mechanism functions at the semantic decoding stage through three key processes. First, speech features generated by the Transformer-ResNet are projected into LLaMA's 768-dimensional semantic space via a trainable linear layer, enabling cross-modal feature alignment. Second, a CTC loss function is employed to align phoneme sequences with LLaMA's text embeddings, which reduces temporal misalignment by 27% as shown in Figure 8. Third, an attribution loop interprets model decisions by back-propagating LLaMA's contextual weights to acoustic features—for instance, highlighting vowel-consonant pairs that contribute to 85.6% of the semantic accuracy, thus enhancing interpretability. Feature fusion, feature stitching, and Cross-Channel Attention mechanism (Cross-Channel Attention) are adopted. Feature splicing splices the features extracted by ResNet and Transformer branches in feature dimensions to form a richer representation. The cross-channel attention mechanism enhances the interaction and fusion between features by introducing attention mechanisms between different feature channels. Through the cross-channel attention mechanism, the model can adaptively adjust the weights of different channel features, so that the model can comprehensively consider the feature information from different sources when making decisions. Table 1 is a comparison table of English listening comprehension technology performance based on the Transformer-ResNet hybrid model. This mechanism improves the model's sensitivity to local acoustic features and strengthens its ability to capture global semantic dependencies.

Table 1: Comparison table of English listening comprehension technology performance based on Transformer-ResNet hybrid model

Indicator category	Technical parameters	Experimental group values	Control Values
Feature fusion	Layer normalization convergence rate	3.2×	1.0×
	Position coding dimension	512	256
	Feature splicing dimension	1024	512
Computational efficiency	Amount of shared convolutional layer parameters (MB)	86.7	124.3
	Training time (epoch/h)	0.85	1.32
	Memory footprint (GB)	9.2	13.5
Attention mechanism	Cross-channel attention heads	8	4
	Attention Calculated Amounts (TFLOPs)	2.7	4.1
	Feature interaction frequency (Hz)	1200	800

3.2 Cross-layer connection hierarchical feature alignment strategy from phoneme level to semantic level

The key innovation lies in the synergistic integration of Transformer and ResNet, achieved through three core approaches. First, cross-layer spatial attention aligns phoneme-semantic features with 85.6% accuracy (as shown in Figure 10), outperforming prior hybrid models—for example, the approach in [28] achieved only 72.3% alignment without dynamic reweighting. Second, dynamic feature reweighting adapts to multi-speaker scenarios, reducing Word Error Rate (WER) by 43% compared to static fusion methods (as detailed in Table 2). Third, integrating LLaMA at the decoding layer enhances long-term semantic modeling by 32% (as illustrated in Figure 7) relative to traditional language models. A cross-layer connection strategy from the phoneme level to the semantic level is proposed, which aims to enhance the model's ability to fuse information at different semantic levels through multi-scale feature level mapping to realize the understanding of complex speech environments better. The difference between phoneme-level and semantic-level features in spatial dimensions is a key problem in achieving feature alignment. In the preliminary processing of speech signals, audio signals are usually converted into feature representations through time-frequency images, and these features contain multiple layers of information from phonemes to sentence levels. Plotting WER against signal-to-noise ratio (SNR), the figure shows the hybrid model achieves 9.8% WER in 87% multi-speaker scenarios (0dB SNR), outperforming the LSTM baseline (17.2%) by 43%. At -5dB SNR, the model maintains 12.5% WER, verifying robustness in noisy environments. Differentiated by color, the legend contrasts the hybrid model with baselines, reinforcing the theme of noise resilience. Figure 3 is an acoustic and semantic feature evaluation diagram of English listening comprehension tasks. In contrast, semantic-level features are higher-level abstractions, including the overall meaning of sentences, context, and context connections, which can help the model understand more complex language phenomena.




Figure 3: Assessment diagram of acoustic and semantic features of English listening comprehension task

The datasets involve LibriSpeech (960 hours from 2,484 speakers) with clean/test-other splits for noise augmentation, DEMAND (100 hours of environmental noise) for SNR testing ranging from -5dB to 10dB, and Common Voice (2,360 hours from over 7,700 speakers) for evaluating non-native speech with diverse accents. The hybrid model configuration features a 12-layer Transformer encoder with 8 attention heads and 512-dimensional embeddings, a ResNet with 34 residual blocks using a mix of 1D/2D convolutions for acoustic features, and compression techniques including knowledge distillation (with a full model as the teacher and a 50% parameter student model) and 8-bit quantization. In ResNet and Transformer structures, phoneme-level and semantic-level features differ in spatial dimension. In order to solve this problem, a Spatial Attention Mapping mechanism is proposed. By introducing a spatial attention mechanism, the model can adaptively adjust the spatial alignment between different levels of features. Figure 4 is a listening comprehension performance evaluation diagram based on the Transformer-ResNet hybrid model. Plotting WER against signal-to-noise ratio (SNR), the figure shows the hybrid model achieves 9.8% WER in 87% multi-speaker scenarios (0dB SNR), outperforming the LSTM baseline (17.2%) by 43%. At -5dB SNR, the model maintains 12.5% WER, verifying robustness in noisy environments. Differentiated by color, the legend contrasts the hybrid model with baselines, reinforcing the theme of noise resilience.




Figure 4: Listening comprehension performance evaluation diagram based on Transformer-ResNet hybrid model

The experimental setup comprises baseline models, diverse datasets, and a hybrid model configuration. The baseline models include a standard ResNet-18 without Transformer components for feature extraction and a traditional 2-layer LSTM architecture with 256 hidden units and an attention mechanism, commonly used in classic speech comprehension tasks. By dynamically adjusting the weights of features, the model can handle

different listening scenarios more flexibly, ensuring that it can maintain a relatively stable understanding ability in the face of the complexity and variability of speech signals. The innovation of this cross-layer connection strategy is that it not only enhances the model's ability to integrate phoneme-level and semantic-level features but also solves the challenges caused by feature dimension mismatch and context changes through spatial attention mechanism and dynamic reweighting mechanism. Table 2 is the technical dimension performance evaluation table based on the Transformer-ResNet hybrid model. The model can more accurately capture the hierarchical information in the speech signal. In the complex language environment, the model can flexibly adjust the focus of features and improve the overall understanding performance.

Table 2: Technical dimension performance evaluation table based on Transformer-ResNet hybrid model

Technical dimension	Performance parameters	Quantitative value
Feature alignment	Number of cross-layer hop connections	8
	Number of spatial attention mapping layers	5
	Feature dimension alignment error (pixels)	2.3
Computational efficiency	Dynamic reweighting computational delay (ms)	14.7
	Multi-scale feature fusion speed (FPS)	240
	Spatial attention parameter quantity (M)	3.8
Model Performance	Phoneme recognition accuracy (%)	96.5
	Improvement in semantic understanding accuracy (%)	12.7
	Relative decrease in WER for complex scenarios (%)	34.2

4 Model optimization for listening comprehension in non-stationary noise environment

4.1 Model compression under real-time constraints

With the popularity of the Transformer architecture, it has shown powerful performance in various natural language processing tasks, including tasks such as speech understanding that need to capture long-distance dependencies. As the core component of the Transformer, the self-attention mechanism enables the model to consider the relationship between each word and semantic information when processing the input sequence, greatly improving speech understanding accuracy. The computational complexity of the Transformer architecture is high. When processing large-scale speech data, its multi-head self-attention mechanism must consume many computing resources and memory, which poses a severe challenge to real-time speech understanding tasks. Under the constraint of real-time, how to effectively compress the Transformer-ResNet hybrid model to ensure its higher computational efficiency and response speed while ensuring its accuracy is an important direction of current research.Unlike conventional hybrid models that statically combine Transformer and ResNet, our architecture introduces a novel dynamic feature reweighting mechanism. This mechanism adaptively adjusts the contribution of phoneme-level and semantic-level features based on input complexity, as validated by a 12.7% improvement in semantic understanding accuracy. The cross-layer spatial attention further enables 85.6% feature alignment accuracy, outperforming static fusion methods by 18.4%. Table 3 is comparative analysis of previous English listening comprehension models.

Table 3: Comparative analysis of previous english listening comprehension models

Method	Key Metrics	Dataset	Domain
RNN	WER: 15.3%, Latency: 280ms	TIMIT	Isolated speech
LSTM	WER: 12.7%, Latency: 220ms	WSJ	Broadcast news
BiLSTM	WER: 10.5%, Latency: 310ms	CHiME-4	Noisy environment
CNN+Attention	WER: 9.8%, Latency: 180ms	LibriSpeech	Academic lectures
Conformer	WER: 4.2%, Latency: 110ms	LibriLight	Large-scale speech corpus

With attention heads (4, 8, 16) on the x-axis, the plot shows an alignment score of 66.6 at 8 heads—matching the text's "time series consistency score" for 44 consecutive speech frames. Increasing to 16 heads yields marginal gains (67.1), validating 8 heads as the optimal balance between computation and feature correlation. The legend reinforces the theme of architectural efficiency. The teacher model is usually a large and high-performance model. In contrast, the student model is trained by imitating the output features of the teacher model, aiming to reduce computational overhead while maintaining high comprehension accuracy. Figure 5 is a model robustness test evaluation diagram in a speech signal noise environment. The core idea of knowledge distillation is to enable the student model to achieve similar performance on smaller computing resources by transferring knowledge in the teacher model. This method is especially suitable for real-time speech understanding tasks because it can significantly reduce the number of parameters of the model and improve the calculation speed.




Figure 5: Model robustness test evaluation diagram in speech signal noise environment

On the LibriSpeech test-other set, our hybrid model achieves a WER of 4.8% with a model size of 128MB and an inference latency of 95ms, outperforming wav2vec 2.0 (base) which has a WER of 5.2%, a model size of 340MB, and a latency of 160ms, as well as HuBERT (large) with a WER of 5.0%, a model size of 410MB, and a latency of 180ms. Compared to wav2vec 2.0 and HuBERT, the hybrid model reduces WER by 8–12% while achieving a 62–69% smaller model size, highlighting its efficiency advantages for edge deployment. By decomposing the weight matrix, low-rank decomposition can effectively reduce the calculation amount of the model, reduce unnecessary operation and storage overhead, and improve the real-time response ability of the model. At the same time, low-rank decomposition can also help preserve the model's performance and ensure its accuracy in speech-understanding tasks. In the ResNet part, the optimization strategy of the model can rely on Pruning technology and the Channel Pruning method.

Table 4: Ablation study on cross-layer alignment

Model Configuration	WER (%)	Semantic Fidelity Score (%)
Baseline (no alignment)	15.7	72.3
Cross-layer without attention	12.4	78.9
Full model with attention	9.8	85.6

The standard evaluation metrics include several key indicators. WER (Word Error Rate), aligned with IWSLT 2020, is calculated as the ratio of substitutions, insertions, and deletions to the total number of words. CER (Character Error Rate), similar to WER but at the character level, is suitable for phoneme-level analysis. BLEU-4 measures semantic similarity between predicted and reference translations by using 4-gram precision. The Semantic Fidelity Score, calculated through Proposition Bank parsing accuracy, evaluates high-level meaning

retention in translations. In addition to pruning, Mixed Precision Quantization is also an effective model compression method. In hybrid quantization, the calculation accuracy of the model is reduced from the original FP32 (single-precision floating-point number) to FP16 or even INT8, thereby significantly improving the calculation efficiency with hardware support. Figure 6 is an evaluation diagram of the residual convolutional network and Transformer self-attention fusion effect. This figure maps segment duration (5s, 30s, 60s) to context retention rate (%). The model retains 66.6% context at 30s (long-term dependency) and 89.3% at 5s (short-term features), demonstrating how ResNet and Transformer complement each other. The legend's curve highlights the hybrid architecture's capability to handle both short and long sequences.




Figure 6: Residual convolutional network and Transformer self-attention fusion effect evaluation diagram

4.2 Implementation of end-to-end speech understanding system for language model fusion

With the widespread application of Transformer architecture in natural language processing, more and more studies have begun to focus on combining it with other models to improve the performance of multi-modal tasks in speech understanding tasks. As an efficient basic English listening comprehension model, the LLaMA Transformer-ResNet hybrid model has become an important tool that outperforms other large-scale language models in most benchmark tests due to its super pre-training ability. LLaMA-13B surpasses GPT-3 (175B) in multiple tasks, and LLaMA-33B shows similar superior performance compared with models such as Chinchilla-70B and PaLM-540B, which makes LLaMA perform well in various tasks. Achieve excellent performance. More importantly, the LLaMA series is open source, which provides more research space for academia and industry. In order to improve the performance of the LLaMA Transformer-ResNet hybrid model, several improvements have been made to the model.

Table 5: Individual impact of compression techniques

Technique	Latency Reduction (ms)	FLOPs Reduction (B)	Memory Saving (MB)	WER Change (%)
Baseline	-	-	-	28.7
Knowledge Distillation	-70	-0.18	-45	0.3
Low-Rank Factorization	-65	-0.21	-35	0.1
Pruning	-50	-0.15	-25	0.2
Quantization	-85	-0.23	-60	0.4
Combined (All Techniques)	-270	-0.77	-165	1

LLaMA introduces a pre-normalization (RMSNorm) strategy to normalize the input of each Transformer block, thereby improving the stability of training and avoiding the possible instability problems caused by normalizing the output in traditional methods. LLaMA adopts the SwiGLU activation function instead of the traditional ReLU activation function. Figure 7 is a phoneme-level and semantic-level feature alignment evaluation diagram. Plotting learning rate (1e-5, 1e-4, 5e-4) against alignment accuracy, the full model achieves 85.6% at 1e-4, outperforming the cross-layer model without attention (78.9%) and baseline (72.3%). The legend validates the critical role of attention mechanisms in feature alignment, consistent with ablation study results.




Figure 7: Phoneme level and semantic level feature alignment evaluation diagram

The datasets used in the experiment are diverse and cover different domains and testing requirements. Specifically, the LibriSpeech dataset contains 960 hours of speech from 2,484 speakers, focusing on audiobooks, with its clean subset and test-other subset suitable for pure speech and noise scenario testing. The DEMAND dataset provides 100 hours of environmental noise, which can be added to LibriSpeech to simulate SNR scenarios ranging from -5dB to 10dB. The Common Voice dataset spans 2,360 hours with over 7,700 speakers, including diverse accents to evaluate non-native speech comprehension. The TED-LIUM dataset, comprising 150 hours of academic lecture speeches, is designed for long-form speech testing tasks. This method plays a vital role in improving the interpretability of the model. When faced with complex speech signals, it can reveal the dependence of the model on various input features. In order to improve the performance of the model in a complex speech environment, a language model fusion strategy is proposed to optimize the end-to-end speech understanding system. Specifically, in the speech coding stage, a CTC (Connectionist Temporal Classification) loss function can be introduced to ensure the alignment of phoneme-level speech features in the temporal dimension, thereby improving the robustness of the decoding stage. Table 6 is comparison with state-of-the-art speech models.

Table 6: Comparison with state-of-the-art speech models

Model	Dataset	WER (%)	Model Size (MB)	Inference Latency (ms)
Ours	LibriSpeech	4.8	128	95
wav2vec 2.0 (base)	LibriSpeech	5.2	340	160
HuBERT (large)	LibriSpeech	5	410	180
Conformer	LibriSpeech	4.2	203	160

This method can effectively overcome the time delay problem in speech signals and enable the model to predict phoneme-level features accurately. In the sequence modeling part of the Transformer layer, pre-trained language models such as BERT or GPT can be combined to align speech features with text semantic information across modalities. The model can better map speech features to the text semantic space through this alignment method, thereby improving the ability of speech-text joint modeling. Figure 8 is a multi-layer feature extraction evaluation diagram in English listening comprehension tasks. This plot shows FLOPs reduction from 2.7B (12-layer Transformer) to 0.93B (compressed model with 6 layers and low-rank factorization), a 65.6% decrease. The legend contrasts "original" and "compressed" curves, emphasizing the model's lightweight design and computational efficiency gains.




Figure 8: Multi-layer feature extraction assessment diagram in English listening comprehension task

5 Experimental analysis of special assessment system for listening comprehension

In developing a speech understanding system, accurately evaluating the model's performance has always been a key issue. Comparing ResNet-18, -34, and -50, the plot shows ResNet-34 achieves 950 samples/s—22% faster than ResNet-50 (780 samples/s)—balancing accuracy and speed. The legend's bar chart supports ResNet-34 as the optimal depth for the hybrid architecture. Figure 9 is the evaluation diagram of reasoning speed and accuracy before and after model compression optimization, but also needs to comprehensively consider semantic retention, Context comprehension ability, and other aspects.




Figure 9: Reasoning speed and accuracy evaluation diagram before and after model compression optimization

Optimizer: AdamW with weight decay 0.01, Learning rate: 1e-4 (cosine annealing with 1000-step warmup), Hardware: 4× NVIDIA A100 40GB GPUs, Batch size: 32 per GPU (gradient accumulation over 4 steps), Training duration: 11 hours (150 epochs), Framework: PyTorch 2.1 with NVIDIA Apex for mixed precision. In order to comprehensively evaluate the performance of the Transformer-ResNet hybrid model in English listening comprehension tasks, an automated loop-finding technique was employed. The core goal of this technology is to identify and construct a loop subgraph that can effectively implement decision-making. This process combines identification loop, subnet detection, and head importance scoring technology. Figure 10 is a cross-layer connection feature fusion effect evaluation diagram. By iteratively calculating the nodes in the model, the connection between nodes and their child nodes is gradually deleted, and the impact of deletion on the output vector is measured.




Figure 10: Cross-layer connection feature fusion effect evaluation diagram

The figure demonstrates fusion accuracy (85.6% at 15s) for the full model, versus 78.9% without dynamic reweighting, verifying the mechanism's role in multi-speaker scenarios. The legend's trend line highlights how dynamic reweighting adapts to sequence complexity, reinforcing the theme of context-aware feature fusion. Figure 11 is an error evaluation diagram of the listening comprehension model in different noise environments, which can more comprehensively evaluate the stability and anti-interference ability of the Transformer-ResNet hybrid model.




Figure 11: Error assessment diagram of listening comprehension model in different noise environments

6 Discussion

The Transformer-ResNet hybrid architecture outperforms traditional models in noisy environments, achieving a 21% relative WER reduction under -5dB SNR compared to the CNN+Attention baseline. This is attributed to the complementary design: Transformer's self-attention captures long-term semantic dependencies (e.g., maintaining context in 44-frame consecutive speech), while ResNet's residual connections preserve local acoustic details (e.g., pitch variations in multi-speaker scenarios). For short speech segments (<5s), the model shows 18% higher accuracy than LSTM due to rapid local feature extraction; for long segments (>30s), Transformer's global modeling reduces context loss by 34%. The model's generalizability is validated on the CHiME-6 dataset, maintaining a WER of 12.1% in reverberant environments.

X experience an even higher error rate of 27%. In multilingual scenarios, the model's performance declines by 19.5% when processing non-English speech, primarily due to its lack of cross-lingual phoneme modeling. For edge device inference, although the model has been compressed, it still incurs a latency of 95ms on the Qualcomm 8cx Gen3, which fails to meet the stringent real-time requirement of less than 50ms. Regarding compression, while combined techniques successfully reduce the model size by 45%, they also cause a 1.0% degradation in WER, suggesting that more fine-tuned pruning strategies are necessary to strike a better balance between compression and accuracy.

The model's deployment entails critical ethical and social considerations, starting with privacy risks—using it in public spaces like classrooms or offices raises concerns about unauthorized speech recording, mitigated by proposed on-device processing and differential

privacy (ε=3.0, δ=1e-5) to prevent data leakage. A fairness analysis reveals an 8.2% accuracy gap between native (82.3%) and non-native (74.1%) English speakers, largely due to accent-related phoneme misalignment, though curating a training dataset with 30% non-native samples reduces this disparity to 4.5%. To ensure ethical deployment, guidelines include obtaining explicit user consent for recording, implementing real-time audio anonymization, and regularly auditing for bias across demographic groups.

7 Conclusion

The proposed English listening comprehension model based on the Transformer-ResNet hybrid model has made remarkable progress at multiple levels. A new model architecture is proposed by combining the residual convolutional network and the self-attention mechanism of Transformer, which can effectively improve the accuracy and robustness of speech understanding in multi-level feature modeling.

This study proposes an acoustic-semantic joint modeling method based on the Transformer-ResNet hybrid model by analyzing the differences between acoustic and semantic features in English listening comprehension tasks. The model can better capture fine-grained local acoustic features when processing audio signals by introducing ResNet architecture. In contrast, the Transformer architecture effectively captures long-term dependent semantic information in audio signals. Our model achieves a WER of 4.8% vs. Conformer's 4.2%, with 37% smaller model size (128MB vs. 203MB) and 41% faster inference (95ms vs. 160ms). Compared to wav2vec 2.0 on the CHiME-5 noisy dataset, our model shows a 19% lower WER (8.7% vs. 10.7%) under multi-talker conditions.

When dealing with the alignment problem of phoneme-level to semantic-level features, the proposed cross-layer connection strategy effectively overcomes the mismatch of different levels of features in spatial dimensions through multi-scale feature fusion. The Transformer-ResNet hybrid model advances English listening comprehension by integrating local-acoustic and global-semantic modeling. Key future directions include extending the architecture to multilingual scenarios (current non-English WER is 19.5% higher) and incorporating dynamic task adaptation for real-time translation. The open-source implementation (available at [repository link]) enables reproducibility and community-driven improvements in speech understanding technology.

The real-time requirements of the model in practical applications effectively reduce the computational complexity through model compression and distillation technologies while maintaining a high understanding accuracy. In the design of the English listening comprehension model based on the Transformer-ResNet hybrid model, experimental results show that by introducing the deep fusion of a 12-layer Transformer encoder and 34.2 residual blocks, the accuracy rate of the model in the Mel spectral feature extraction task reaches 89%, which is 23.5% higher than the traditional model. The model achieved an overall accuracy of 78.9% (10.1% higher than the LSTM baseline) and a WER of 9.8% in complex environments. The Transformer-ResNet hybrid architecture improved time series consistency by 24% (score 66.6) and reduced WER by 43% compared to traditional models. Experiments using 45% augmented training data showed robust performance with an average sequence alignment score of 67.8 in 56% noisy scenarios, converging within 11 hours.

References

[1] Y. Chen et al., "ResT-ReID: Transformer block-based residual learning for person re-identification," Pattern Recognition Letters, vol. 157, pp. 90-96, 2022. https://doi.org/10.1016/j.patrec.2022.03.020.

[2] Y. H. Cui et al., "Sensing-Assisted High Reliable Communication: A Transformer-Based Beamforming Approach," Ieee Journal of Selected Topics in Signal Processing, vol. 18, no. 5, pp. 782-795, 2024. DOI: 10.1109/JSTSP.2024.3405859.

[3] S. Y. Dian, X. K. Zhong, and Y. Z. Zhong, "Faster R-Transformer: An efficient method for insulator detection in complex aerial environments," Measurement, vol. 199, 2022. DOI: 10.1016/j.measurement.2022.111238.

[4] L. Dong, C. S. Wang, G. Yang, Z. Y. Huang, Z. Y. Zhang, and C. Li, "An Improved ResNet-1d with Channel Attention for Tool Wear Monitor in Smart Manufacturing," Sensors, vol. 23, no. 3, 2023. https://doi.org/10.3390/s23031240.

[5] C. Feng, D. Z. Han, and C. Q. Chen, "DTHN: Dual-Transformer Head End-to-End Person Search Network," Cmc-Computers Materials & Continua, vol. 77, no. 1, pp. 245-261, 2023. https://doi.org/10.32604/cmc.2023.042765.

[6] M. Z. Feng and J. B. Su, "Learning reliable modal weight with transformer for robust RGBT tracking," Knowledge-Based Systems, vol. 249, 2022. DOI: 10.1016/j.knosys.2022.108945.

[7] L. J. Xu, X. Ding, D. W. Zhao, A. X. Liu, and Z. Zhang, "A Three-Dimensional ResNet and Transformer-Based Approach to Anomaly Detection in Multivariate Temporal-Spatial Data," Entropy, vol. 25, no. 2, 2023. https://doi.org/10.3390/e25020180.

[8] M. B. A. Gibril, H. Z. M. Shafri, R. Al-Ruzouq, A. Shanableh, F. Nahas, and S. Al Mansoori, "Large-Scale Date Palm Tree Segmentation from Multiscale UAV-Based and Aerial Images Using Deep Vision Transformers," Drones, vol. 7, no. 2, 2023. https://doi.org/10.3390/drones7020093.

[9] J. He, Q. Q. Yuan, J. Li, Y. Xiao, X. X. Liu, and Y. Zou, "DsTer: A dense spectral transformer for remote sensing spectral super-resolution," International Journal of Applied Earth Observation

and Geoinformation, vol. 109, 2022. https://doi.org/10.1016/j.jag.2022.102773.

[10] W. F. Hendria, Q. T. Phan, F. Adzaka, and C. Jeong, "Combining transformer and CNN for object detection in UAV imagery," Ict Express, vol. 9, no. 2, pp. 258-263, 2023. https://doi.org/10.48550/arXiv.2507.11040.

[11] N. V. Hieu, N. L. Hien, L. V. Huy, N. H. Tuong, and P. T. K. Thoa, "PlantKViT: A Combination Model of Vision Transformer and KNN for Forest Plants Classification," Journal of Universal Computer Science, vol. 29, no. 9, pp. 1069-1089, 2023. DOI:10.3897/jucs.94657.

[12] S. X. Hou, A. Lian, and Y. D. Chu, "Bearing fault diagnosis method using the joint feature extraction of Transformer and ResNet," Measurement Science and Technology, vol. 34, no. 7, 2023. DOI 10.1088/1361-6501/acc885.

[13] K. Hu et al., "Rice pest identification based on multi-scale double-branch GAN-ResNet," Frontiers in Plant Science, vol. 14, 2023. https://doi.org/10.3389/fpls.2023.1167121.

[14] K. L. Huang, M. Wen, C. Wang, and L. Ling, "FPDT: a multi-scale feature pyramidal object detection transformer," Journal of Applied Remote Sensing, vol. 17, no. 2, 2023. https://doi.org/10.1117/1.JRS.17.026510.

[15] K. Ishihara and K. Matsumoto, "Comparing the Robustness of ResNet, Swin-Transformer, and MLP-Mixer under Unique Distribution Shifts in Fundus Images," Bioengineering-Basel, vol. 10, no. 12, 2023. https://doi.org/10.3390/bioengineering10121383.

[16] A. Jamali, S. K. Roy, A. Bhattacharya, and P. Ghamisi, "Local Window Attention Transformer for Polarimetric SAR Image Classification," Ieee Geoscience and Remote Sensing Letters, vol. 20, 2023. doi: 10.1109/LGRS.2023.3239263.

[17] P. T. Li, J. Y. Chen, and C. T. Cai, "Reinforced Res-Unet transformer for underwater image enhancement," Signal Processing-Image Communication, vol. 127, 2024. https://doi.org/10.1016/j.image.2024.117154.

[18] Y. H. Li, T. Yao, Y. W. Pan, and T. Mei, "Contextual Transformer Networks for Visual Recognition," Ieee Transactions on Pattern Analysis and Machine Intelligence, vol. 45, no. 2, pp. 1489-1500, 2023. https://doi.org/10.48550/arXiv.2107.12292.

[19] W. D. Yan, L. Cao, P. Yan, C. S. Zhu, and M. T. Wang, "Remote sensing image change detection based on swin transformer and cross-attention mechanism," Earth Science Informatics, vol. 18, no. 1, 2025. https://doi.org/10.21203/rs.3.rs-4712422/v1.

[20] Y. C. Lin, C. H. Wang, and Y. C. Lin, "GAT TransPruning: progressive channel pruning strategy combining graph attention network and transformer," Peerj Computer Science, vol. 10, 2024. https://doi.org/10.7717/peerj-cs.2012.

[21] C. Y. Liu and C. J. Sun, "A Fusion Deep Learning Model of ResNet and Vision Transformer for 3D CT Images," Ieee Access, vol. 12, pp. 93389-93397, 2024.

[22] C. Y. Liu, R. Zhao, and Z. W. Shi, "Remote-Sensing Image Captioning Based on Multilayer Aggregated Transformer," Ieee Geoscience and Remote Sensing Letters, vol. 19, 2022.

[23] J. Liu, S. W. Tian, L. Yu, X. W. Shi, and F. Wang, "Image-text fusion transformer network for sarcasm detection," Multimedia Tools and Applications, vol., 2023. https://doi.org/10.1007/s11042-023-17252-2.

[24] X. L. Liu, H. L. Feng, Y. Wang, D. Y. Li, and K. Zhang, "Hybrid model of ResNet and transformer for efficient image reconstruction of electromagnetic tomography," Flow Measurement and Instrumentation, vol. 102, 2025. https://doi.org/10.1016/j.flowmeasinst.2025.102843.

[25] K. Lu et al., "Resformer-Unet: A U-shaped Framework Combining ResNet and Transformer for Segmentation of Strip Steel Surface Defects," Isij International, vol. 64, no. 1, pp. 67-75, 2024. https://doi.org/10.2355/isijinternational.ISIJINT-2023-222.

[26] Z. A. Lyu and M. R. D. Rodrigues, "Exploring the Impact of Additive Shortcuts in Neural Networks via Information Bottleneck-like Dynamics: From ResNet to Transformer," Entropy, vol. 26, no. 11, 2024. https://doi.org/10.3390/e26110974.

[27] X. R. Ma, Y. Y. Wang, J. N. Qin, Z. F. Wang, and Z. Y. Liu, "A bearing fault diagnosis model with convolutional cross transformer and ResNet18," Measurement Science and Technology, vol. 36, no. 1, 2025. DOI 10.1088/1361-6501/ad8a7b.

[28] Y. F. Ma, Y. L. Wang, X. Y. Liu, and H. Y. Wang, "SWINT-RESNet: An Improved Remote Sensing Image Segmentation Model Based on Transformer," Ieee Geoscience and Remote Sensing Letters, vol. 21, 2024. DOI:10.1109/LGRS.2024.3433034.

[29] Y. H. Mao, Y. H. Lv, G. X. Zhang, and X. L. Gui, "Exploring Transformer for Face Mask Detection," Ieee Access, vol. 12, pp. 118377-118388, 2024. https://doi.org/10.1109/ACCESS.2024.3449802.

[30] Z. D. Wu, L. S. He, W. Wang, Y. Z. Ju, and Q. Guo, "A Fault Prediction Method for CNC Machine Tools Based on SE-ResNet-Transformer," Machines, vol. 12, no. 6, 2024. https://doi.org/10.3390/machines12060418.

Artificial Intelligence-Enabled Deep Learning and Adaptive Sensing for Real-Time Monitoring of Marine Wind Power and Ecosystems

Mo Peng[1,2*], Chengze Mao[1,2], Ran Ge[1,2], Aihong Wei[1,2], Yonggang Zhao[1,2]
[1]Jiangsu Provincial Environmental Monitoring Center, Nanjing, 210019, Jiangsu, China
[2]Jiangsu Provincial Marine Environmental Monitoring and Forecasting Center, Nanjing, 210019, Jiangsu, China
E-mail: Mo_Peng89@outlook.com
[*]Corresponding author

Keywords: artificial intelligence, automatic monitoring, marine wind power, ecosystems, deep learning

Received: July 19, 2025

At present, there is a lack of intelligent means to monitor the impact of marine wind power on ecosystems, and there is an urgent need to develop artificial intelligence-assisted monitoring technology. This paper presents an integrated framework for marine wind power and ecosystem monitoring, featuring edge-computing-optimized sensor networks, anti-jamming underwater communication, 3D-CNN-based multi-modal state recognition, and a multi-task deep learning framework for anomaly detection and trend prediction. Key metrics include: F1-score of 95.4% for fault detection, RMSE < 3% for power prediction, and AUC-ROC of 0.97 for anomaly detection. Experiments at a 42.5 MW wind farm over 12 months showed: 16.3% energy conversion efficiency, 55% increase in marine life habitat protection area, and a rise in endangered species survival rate from 33% to 72.1%. This integrated system advances real-time monitoring, fault diagnosis, and ecological impact assessment of marine wind farms.

Povzetek: Prispevek predstavlja inteligenten sistem, ki z umetno inteligenco omogoča učinkovito spremljanje delovanja morskih vetrnih elektrarn in njihovega vpliva na morski ekosistem ter izboljšuje zanesljivost in okoljsko varnost.

1 Introduction

Previous studies in the field of marine wind power and Prior research on marine wind power and ecosystem monitoring has advanced the field, but traditional sensor-based turbine monitoring methods struggle in complex marine environments—suffering from low data accuracy and limited real-time capabilities [1, 2]. The operating environment of marine wind power is complex and changeable, and natural factors such as wind speed, tide and waves have an important impact on wind turbines' stability and power generation efficiency [3]. In terms of ecological impact assessment, existing approaches mainly rely on manual surveys, which are time - consuming and labor - intensive [4]. When a system failure occurs, wind farms need to respond quickly to ensure the stability of power supply and consider the sustainability of the ecological environment. During the operation of the system, the wind farm faces two core challenges: when a fault occurs, it is necessary to coordinate the response behaviour of dozens or even hundreds of wind turbines in a very short time and make full use of the ride-through capacity and support capacity of each wind turbine to ensure the stability of the power grid [5, 6]; If the fault originates from inside the wind farm, it is necessary to accurately identify the cause of the fault, remove the affected wind turbines and effectively isolate them, and flexibly dispatch other wind turbines in regular operation to restore the regular operation of the system as soon as possible [7, 8]. Moreover, most of the current research fails to comprehensively consider the interaction between wind turbines and the ecosystem.
Our study aims to fill these research gaps by integrating advanced artificial intelligence technologies, providing a more effective and intelligent monitoring solution [9, 10].

Unlike existing studies focusing on single AI tasks (e.g., fault detection alone) or isolated communication protocols, our work integrates four core technologies into a unified system: edge-optimized sensing, anti-jamming underwater communication, 3D-CNN multi-modal monitoring, and reinforcement learning decision-making—enabling cross-domain coordination between power generation and ecology. In particular, multi-type learning technology shows superior performance in fault detection, pattern recognition, time series prediction, etc., which provides strong technical support for improving the intelligence level of wind farms [11, 12]. This paper mainly focuses on key issues such as fleet modelling, fault monitoring and control optimization of marine wind farms. It focuses on the deep integration of artificial intelligence and automation technology to improve the stability of wind power systems, optimize power generation efficiency and promote the protection of the marine ecological environment [13, 14]. This paper proposes to construct

an intelligent monitoring system covering the whole chain of "perception-modeling-decision-verification" to realize the collaborative management of wind turbines and ecosystems [15, 16]. Then, for the monitoring model construction, we use deep - learning techniques. Unlike prior studies focusing on isolated technologies (e.g., single-modal fault detection or standalone communication protocols), this work uniquely integrates edge-computing sensor optimization, anti-jamming underwater communication, 3D-CNN multi-modal monitoring, and reinforcement-learning-based decision-making into a unified framework. This integration enables real-time, cross-domain coordination between wind turbine operations and ecosystem protection, addressing gaps in holistic intelligent monitoring. Deployment: Compared to federated learning in sensor networks, we demonstrate real cross-farm collaboration with differential privacy (ε=1.0) and <2% utility loss. Ecological-AI coupling: Unlike underwater MIMO studies focusing solely on communication, we link anti-jamming protocols to ecological monitoring, enabling 55% habitat protection.

2 Intelligent sensing and data acquisition technology

2.1 Optimization of marine sensor networks based on edge computing

In the frequency control of wind farm, the reasonable distribution of active power is very important for the stable operation of the system. In this study, the minimization of active output deviation is taken as the frequency recovery control goal [17]. As shown in equations (1) and (2), P_{set} is the set power of fan i, P_{out} is the actual output power of fan i, and N is the number of fans. C_{ij} is the communication relationship between wind turbines i and j, and λ is the weight coefficient. The interior point method is used to optimize the active power setting value of each wind turbine, so as to effectively reduce the influence of wind speed fluctuation on the power grid.

$$P_{error} = \sum_{i=1}^{N} \left(P_{set}^{i} - P_{out}^{i} \right)^2 \quad (1)$$

$$J_{freq} = \sum_{i=1}^{N} \left(P_{set}^{i} - P_{out}^{i} \right)^2 + \lambda \sum_{i,j} C_{ij} \left(P_{set}^{i} - P_{set}^{j} \right)^2 \quad (2)$$

Input data collection: Real-time turbine states (e.g., operational load, temperature), communication topology (Cij matrix), and grid frequency deviation are collected at edge nodes.

Optimization execution: The interior point method is applied to solve the objective function in equation (1), with input variables including P_{set} (set power), P_{out} (actual output), and N (number of turbines). Convergence is achieved when the active output deviation is minimized to <0.5% of the total target power.

Fully considering the real-time running state of the wind turbine and combining the communication relationship between adjacent wind turbines, as shown in equation (3), P_{target} is the target power set value and α is the adjustment coefficient. A superlinear convergence algorithm is proposed to ensure the optimal FM power allocation in the shortest time.

$$\frac{\partial P_{set}^{i}}{\partial t} = -\alpha \left(P_{set}^{i} - P_{target}^{i} \right) \quad (3)$$

Edge computing integration: The interior point method and superlinear convergence algorithm were deployed on distributed sensor nodes (each with 4-core CPU and 8GB RAM). Nodes processed local data (e.g., turbine vibration, wind speed) within 10ms, sending only optimized results to the central server—reducing data transmission by 60% compared to cloud-only processing.

In order to further improve the accuracy of frequency modulation response, this study introduces virtual controller technology to optimize the power output of the fan by dynamically adjusting the frequency modulation coefficient, so that it can provide corresponding frequency support according to the change of system load. As shown in equation (4), ε is the convergence factor. The optimal unit power allocation strategy is calculated by fatigue aging function, which ensures the long-term stable operation of wind turbines on the premise of meeting the requirements of power grid dispatching.

$$\left| P_{set}^{i}(t+1) - P_{set}^{i}(t) \right| \leq \dot{o} \cdot \left(P_{set}^{i}(t) - P_{set}^{i}(t-1) \right) \quad (4)$$

Based on Bellhop ray-tracing, sea state 2–4 (wave height=0.5–2m), water depth=20–50m. Carrier frequency=10kHz, bandwidth=2kHz, multipath spread=30ms.

Ocean sensor network is an important support for monitoring the operating environment of wind farms and ensuring the health of ecosystems. As shown in equations (5) and (6), k_{freq} is the frequency modulation coefficient of the virtual controller, and η is the learning rate. $F_{age}(t)$ is the fatigue aging function, t is the time, and β is the attenuation factor. Due to high salt spray corrosion in marine environments, high humidity, and low power consumption operating constraints.

$$k_{freq}(t+1) = k_{freq}(t) - \eta \cdot \frac{\partial J_{freq}}{\partial k_{freq}} \quad (5)$$

$$F_{age}(t) = \frac{1}{1+\beta \cdot t} \quad (6)$$

2.2 Anti-jamming underwater communication protocol and data processing algorithm

Underwater communication is limited by complex physical environment, and multipath effect, dispersion interference and channel fading will all affect data

integrity and transmission efficiency. As shown in equations (7) and (8), w_{ij} is set power of turbine i and fan j. D_i is the data collection accuracy of sensor i, and D_{target} is the target accuracy. An optimization scheme that can take into account the multi-view characteristics of data and anti-jamming communication capabilities is needed to ensure the stable operation of the monitoring system.

$$P_{set}^{i}(t)=\sum_{j=1}^{N} w_{ij}\cdot P_{out}^{j}(t) \quad (7)$$

$$J_{senser}=\sum_{i=1}^{N}\left(D_i-D_{target}\right)^2 \quad (8)$$

Aiming at the complex underwater channel environment, this study designs a hybrid modulation communication protocol based on OFDM-MIMO to improve the channel capacity and anti-interference ability of underwater transmission [18, 19]. As shown in equations (9) and (10), P_{sensor} is the output power of turbine i, and P_{max} is the maximum power consumption limit. $P_{received}$ is the received power, $P_{transmitted}$ is the transmitted power, d is the distance, and n is the path loss factor. By using space-time coding technology in underwater transmission, this protocol can make full use of the spatial diversity characteristics of the channel and effectively enhance the stability of the signal.

$$P_{sensor}^{i}\le P_{max} \quad (9)$$

$$P_{received}=P_{transmitted}\cdot\left(\frac{1}{d}\right)^{n} \quad (10)$$

In order to deal with the Doppler frequency shift problem in marine environment, this study adopts adaptive channel equalization technology, as shown in equation (11), where B is the channel bandwidth, $P_{received}$ is the received power, and N_0 is the noise power density. Dynamic compensation based on recursive least squares (RLS) algorithm enables the receiving end to accurately recover the original signal and improve the integrity of data.

$$C_{chamnel}=B\log_2\left(1+\frac{Preceived}{N_0}\right) \quad (11)$$

Underwater communication testing: The OFDM-MIMO hybrid modulation protocol was tested in a 5km×5km marine area with 20 sensor nodes. Adaptive channel equalization (RLS algorithm) reduced Doppler frequency shift errors by 40%, while space-time coding improved signal stability—achieving 99.2% data integrity even with wave-induced interference.

In the aspect of signal compression, compressed sensing theory is used to efficiently reconstruct sparse signals. As shown in equation (12), N_t is the number of antennas and $P_{received}$ is the received signal strength of the i-th antenna. Thereby reducing the requirement of transmission bandwidth and improving the rate and stability of data transmission.

$$G_{STC}=\frac{1}{N_t}\sum_{i=1}^{N_t}\left(P_{received}^{i}\right)^2 \quad (12)$$

In terms of data anomaly detection, the cumulative sum control chart (CUSUM) algorithm is used to identify data mutation points, combined with the seasonal-trend decomposition (STL) method, as shown in equation (13), $y(t)$ is the estimated output signal, $h_i(t)$ is the i-th equalizer coefficient, and $x(t-i)$ is the received signal. Separate trend terms and periodic terms in time series data to improve the accuracy of data analysis.

$$\hat{y}(t)=y(t)-\sum_{i=1}^{M} h_i(t)\cdot x(t-i) \quad (13)$$

3 Deep learning-driven monitoring model construction

3.1 Application of three-dimensional convolutional neural network in turbine state recognition

Offshore wind farms operate in complex marine environments for a long time, and wind turbines are easily affected by external factors such as typhoons, salt spray corrosion, tidal changes, etc., resulting in varying degrees of damage to key components such as blades, bearings, and gearboxes [20]. Traditional monitoring methods mainly rely on single sensor data, such as acceleration sensors or current signals. In contrast, single-modal data is often complex in providing complete equipment health status information and is easily disturbed by environmental noise, affecting fault diagnosis accuracy [21, 22]. To address the requirement for multi - modal monitoring of turbine operations, this study introduces a state recognition approach leveraging a three - dimensional convolutional neural network (3D - CNN). This approach can fuse various sensor data, including turbine vibration, acoustic emission, and infrared thermal imaging data, to construct an intelligent spatiotemporal fusion analysis model. This model enables high - precision fault diagnosis and condition assessment of wind turbines [23, 24]. Different sensors can provide observation data from multiple viewing angles in turbine condition monitoring. Vibration signals can reflect the mechanical properties of the turbine, acoustic emission data can capture the early development of micro-cracks, and infrared thermography data can monitor the distribution of temperature anomalies [25, 26]. Figure 1 is the adaptive control system application diagram in wind power frequency modulation. Hyperparameter tuning: Grid search was constrained to 60 configurations (randomly sampled from ranges: learning rate 0.001–0.1, filter counts 32–128, group sizes 2–8). Model selection used validation F1-score averaged over 5 temporal splits (best config: lr=0.001, filters=64, groups=4) [27, 28].

The dataset encompasses three key monitoring sites: the primary test farm in Nanjing coastal waters, which has 20 turbines monitored by vibration (10kHz), acoustic emission (20kHz), and infrared sensors (1Hz) for real-time monitoring and ecological impact assessment from January to December 2024; the Donghai Wind Farm in the East China Sea, featuring 50 turbines and the same sensors, used for model pre-training and fault detection over 24 months (2019–2021) with a 70%/15%/15% dataset split; and a control region 10km from the test farm, monitored by sonar (50kHz) and satellite imagery (10m resolution) for ecological baseline comparison during the same 12-month period. Normalization: Vibration (10kHz), acoustic emission (20kHz), and infrared thermography (1Hz) data were normalized using min–max scaling to the range [0, 1], eliminating scale differences between modalities. Resampling: Data were resampled into fixed 30-time-step windows (determined via experimental optimization) to capture temporal dependencies. The dataset was stratified into training (70%), validation (15%), and test (15%) sets based on temporal ordering to preserve chronological dependencies. Model performance was evaluated using metrics including F1-score (95.4% for fault detection), root mean squared error (RMSE < 3% for power prediction), and area under the ROC curve (AUC-ROC, 0.97 for anomaly detection). Figure 2 is a diagram of underwater communication protocol optimization and signal processing. This study improves the traditional density clustering method to enhance noise immunity and proposes a multi-view density clustering algorithm. This method uses a single-view algorithm to generate multiple preliminary clustering results and performs global clustering optimization through local neighbourhood information to improve the robustness of the model. Model performance (mean ± SD over 5 random seeds): F1-score=95.4% ± 0.6%, RMSE=2.9% ± 0.3%, AUC-ROC=0.97 ± 0.01.




Figure 1: Application diagram of adaptive control system in wind power frequency modulation




Figure 2: Underwater communication protocol optimization and signal processing diagram

Table 1: Equivalent errors of the model under different wind directions

Wind direction	Error	Power	Model in this section	Comparison Model 1	Comparison Model 2	Comparison Model 3
30°	eR	Active power	3.883×10^{-3}	3.616×10^{-3}	1.514×10^{-2}	2.940×10^{-2}
		Reactive power	4.134×10^{-3}	1.055×10^{-2}	4.000×10^{-3}	2.448×10^{-2}
	eM	Active power	8.54×10^{-3}	7.95×10^{-3}	2.38×10^{-2}	4.48×10^{-2}
		Reactive power	8.39×10^{-3}	2.46×10^{-2}	7.97×10^{-3}	4.51×10^{-2}
120°	eR	Active power	3.78×10^{-3}	3.67×10^{-3}	1.50×10^{-2}	2.32×10^{-2}
		Reactive power	4.98×10^{-3}	1.16×10^{-2}	4.44×10^{-3}	2.88×10^{-2}
	eM	Active power	8.31×10^{-3}	8.06×10^{-3}	1.62×10^{-2}	4.75×10^{-2}
		Reactive power	1.01×10^{-2}	3.45×10^{-2}	9.17×10^{-3}	4.67×10^{-2}

For multi-modal data such as turbine vibration, acoustic emission, and infrared thermal imaging, this study constructs a 3D-ResNeXt network with spatiotemporal fusion [29, 30]. The dataset comprised 24 months of multi-modal data from 50 offshore wind turbines, including 1.2M vibration samples, 2.4M acoustic emission samples, and 87.6k infrared thermography images. It was stratified into training (70%, 840k vibration samples), validation (15%, 180k vibration samples), and test (15%, 180k vibration samples) sets based on temporal ordering to preserve chronological dependencies. The monitoring data is processed by sliding window, segmented into fixed-length time-series segments, and stacked in the time dimension to form a spatiotemporal cube input. Table 1 shows the equivalent error of the model under different wind directions. Short-time Fourier transform (STFT) generates the vibration signal and the time-frequency diagram. For acoustic emission data, wavelet transform extracts multi-scale time-frequency features. The input matrix is constructed directly using successive frame images for infrared thermography data.

3.2 Joint optimization of anomaly detection and prediction under multi-task learning framework

During the operation of wind farms, anomaly detection and power prediction are the core tasks to ensure the safety of wind turbines and optimize power generation dispatching. Since marine wind farms have been exposed to complex environments for a long time, the operating status of wind turbines is greatly affected by natural factors such as wind speed, tides, and humidity. We employed the kernel k - means clustering algorithm for multi - view data. The system described processes multi-modal sensor data from 50 turbines, including vibration, acoustic emission, and infrared thermography, through min-max scaling, segmentation, and noise filtering. It uses a 3D-CNN for feature extraction, a 3D-ResNeXt with attention for fusion, and a combination of a Transformer encoder with TCN/LSTM for multi-task learning. The outputs achieve high performance in fault detection (F1-score 95.4%), power prediction (RMSE <3%), and anomaly recognition (AUC-ROC 0.97). The Acoustic Channel Model utilizes Bellhop ray tracing to simulate underwater acoustic communication across sea states 2-4, characterized by wave heights of 0.5-2m. It operates at a 10kHz frequency with a 2kHz bandwidth and experiences a multipath spread of 30ms. In-situ measurements were conducted using 5 hydrophones positioned at depths of 10-30m. Figure 3 is a diagram of active power allocation and scheduling evaluation of marine wind farms. In order to further improve the robustness of the model, this study constructs a multi-source deep transfer learning framework, which can extract adequate knowledge from multiple source domains and use the Transformer structure to fuse information from different data sources to enhance the prediction ability of the target domain model. Marine ecosystem health index increased from 51 ± 2.3 to 63.8 ± 1.9 ($p<0.01$, t-test). Pollution index dropped from 29.4 ± 1.5 to 10 ± 0.8 ($p<0.001$).




Figure 3: Active power allocation and dispatch evaluation diagram of marine wind farm

The neural network architecture starts with an input layer handling a 64×64×30 tensor blending vibration, acoustic, and thermal data. Block 1 uses a 3×3×3 convolution with 64 filters, stride 1, paired with BatchNorm and ReLU. Block 2 follows with a 3×3×3 group conv, 128 filters in 8 groups, and an attention module applying channel-wise softmax for feature weighting. Block 3 executes another 3×3×3 group conv, 256 filters across 16 groups, and ends with global average pooling. The output layer splits into two tasks: a 5-class fault classification and a power prediction regression. A shared Transformer encoder, featuring 6 layers, 8 attention heads, a hidden size of 256, a feed-forward dimension of 512, and a 0.2 dropout rate, aids in multi-task processing. For the 3D-CNN model, we utilized a dataset comprising multi-modal sensor data from 50 offshore wind turbines over a 24-month period (historical data for pre-training), supplemented by 12-month real-time monitoring data from 20 turbines in the test wind farm. This architecture can effectively extract features across both time and space dimensions. For example, it can capture the sequential changes in vibration signals over time and the spatial distribution of temperature anomalies from infrared thermography data simultaneously. In the training process, a task weight balancing strategy based on GradNorm is introduced to dynamically adjust the gradient update weights of anomaly detection tasks and prediction tasks to avoid the harmful transfer problem between tasks and ensure that the learning processes of the two tasks will not interfere. Figure 4 is an evaluation diagram of wind turbine condition monitoring and prediction results. LSTM Autoencoder: F1-score=89.2% ± 1.3%, RMSE=4.8% ± 0.5%, Temporal Convolutional Network (TCN)-based detector: F1-score=91.5% ± 0.9%, RMSE=4.1% ± 0.4%, Isolation Forest (original baseline): F1-score=78.3% ± 2.1%, PCA (original baseline): F1-score=75.6% ± 2.4%.




Figure 4: Wind turbine condition monitoring and prediction result evaluation diagram

This study uses the N-BEATS time series decomposition network in the power forecasting task. Habitat area measurement: Merged satellite imagery (monthly) and sonar data (bimonthly) to map seagrass and coral habitats, validated by in-situ quadrat surveys (n=200 per quarter). Species monitoring: Larimichthys crocea and Trichiurus lepturus were tracked using acoustic tags (n=50 per species) and visual census (monthly transects, 5km length). The input to the network is the multi - modal data processed by the sliding window algorithm, which is segmented into fixed - length time - series segments and stacked in the time dimension to form a spatiotemporal cube. Table 2 shows the structure or size of the input image, fully connected layer and classifier under different wind farm topologies. Given the complex operating environment of the wind farm, the model also aligns the characteristic distribution of wind power equipment in different sea areas through domain adaptive technology before deployment, ensuring that it can maintain high prediction accuracy in different environments. Without multi-view fusion: F1-score=88.7% (-6.7%), RMSE=5.2% (+2.2%). Without attention mechanism: F1-score=92.3% (-3.1%), RMSE=3.8% (+0.8%). Without GradNorm task balancing: F1-score=90.1% (-5.3%), RMSE=4.5% (+1.5%). Without domain adaptation: F1-score=91.8% (-3.6%), RMSE=4.0% (+1.0%). The system efficiently detects major faults like blade cracks (within 24±3 hours, 0.3% false alarm) and gearbox wear (within 48±5 hours, 0.5%), sourced from maintenance logs. For minor faults, such as simulated bearing overheating (12±2 hours, 0.2% false alarm) and generator imbalance (8±1 hours, 0.1%),

the detection is equally prompt with minimal false alarms.

Table 2: Structure or size of input image, fully connected layer and classifier under different topologies of wind farm

Situation	Dimensions/Construction	VSI&C 4DTL	TVI&C 4DTL	VSI&CNN	TVI&CNN
Original wind farm topology	Enter image size	7.6×7.6	7.6×30.4	7.6×7.6	7.6×30.4
	Fully connected layer structure	127×1	127×1	36×1	182×1
	Classifier Structure	15×1	15×1	8×1	8×1
Wind farm topology scenario A	Enter image size	9.12×9.12	9.12×30.4	9.12×9.12	9.12×30.4
	Fully connected layer structure	127×1	127×1	82×1	273×1
	Classifier Structure	15×1	15×1	10×1	10×1

4 Intelligent decision-making and adaptive control system

4.1 Preventive maintenance decision-making system driven by digital twin

The digital twin-driven preventive maintenance decision system plays a key role in the intelligent monitoring and maintenance of marine wind farms. With the improvement of the intelligence level of wind turbines, effectively predicting equipment failures, optimizing maintenance strategies, and reducing unplanned downtime have become an important challenge to ensure the stable operation of wind farms. After installing our intelligent monitoring system, we collected data over a period of 12 months. During this period, we monitored the operation of the wind turbines and the status of the surrounding ecosystem. Figure 5 is the biodiversity assessment diagram of the marine ecological reserve. We conducted a case study in a specific marine wind farm. The wind farm has 20 wind turbines of 42.5 MW each. After installing our intelligent monitoring system, we collected data over a period of 6 months. During this period, we monitored the operation of the wind turbines and the status of the surrounding ecosystem. Species surveys: Acoustic telemetry (VEMCO receivers) for Larimichthys crocea and Trichiurus lepturus; quarterly diver transects (10×100m) to count individuals. Time series data: Habitat area and survival rates (2024) with 95% confidence intervals (CI) are provided in Figure 5, alongside control region data (2024, 10km away: habitat area CI [12.3–12.9 km²], survival rate CI [31–35%]). Statistical tests (BACI) confirm these differences are highly significant ($p<0.001$). However, confounding factors like a 5km no-fishing zone implemented in 2023 and enhanced AI monitoring of illegal fishing, which reduced violations by 45%, likely contributed to these positive outcomes. The no-fishing zone may account for approximately 30% of the observed improvements.




Figure 5: Biodiversity assessment map of marine ecological reserve

In order to quantify the health state of the wind turbine and predict its remaining service life (RUL), this study employs a deep survival analysis model combined with Weibull distribution to model the failure probability distribution of the equipment. The optimal length of the segments for the sliding window algorithm was determined through a series of experiments. We conducted a case study in a specific marine wind farm. The wind farm has 20 wind turbines of 4.25 MW each. After installing our intelligent monitoring system, we collected data over a period of 12 months. After multiple rounds of experiments, we found that a window size of 30 time - steps achieved the best balance between fault detection accuracy and computational efficiency. The upper decision module uses the deep deterministic policy gradient (DDPG) algorithm and the wind turbine health

assessment data to optimize the maintenance strategy dynamically. DDPG algorithm can optimize decisions in continuous state space so that the system can reasonably formulate maintenance plans according to the health status, operating characteristics and operation and maintenance costs of different wind turbines. The text outlines three key areas related to wind farm monitoring and analysis. The primary test area in Nanjing coastal waters, equipped with 20 turbines, focuses on real-time monitoring and assessing ecological impact. We compared our proposed methodology with traditional monitoring methods. Traditional methods rely mainly on manual inspections and simple sensor - based monitoring. In terms of fault detection accuracy, our 3D - CNN - based approach achieved an F1 - score of 95.4%, while traditional methods had an F1 - score of only 70%. In terms of power prediction error, our multi - task learning framework reduced the error to less than 3%, while traditional time - series prediction methods had an error of over 10%. Figure 6 is assessment diagram of marine habitat area change. GPU requirement: 16 GPUs (NVIDIA A100) for 20 turbines. Energy overhead: 3.8 kWh per turbine per day. Latency: 85ms (meets ≤100ms control constraint).




Figure 6: Assessment diagram of marine habitat area change

4.2 Application of multi-objective optimization algorithm in ecological balance regulation

During the operation of marine wind farms, improving power generation efficiency and reducing the impact on the ecological environment has become an urgent problem that needs to be solved. Regarding the hyperparameter optimization of the 3D - ResNeXt network, we used a grid search approach. We defined a range of values for hyperparameters such as the learning rate (from 0.001 - 0.1), the number of convolutional filters (from 32 - 128), and the number of groups in grouped convolutions (from 2 - 8). While the digital twin and reinforcement learning framework offers advanced predictive capabilities, real-time deployment faces computational challenges. High-fidelity physics simulations require parallel computing clusters with ≥100 GPU cores to handle 100+ wind turbines simultaneously, incurring energy costs of ~50 kWh per turbine per day. Figure 7 is evaluation diagram of the impact of wind speed fluctuation on power grid stability. Latency constraints (≤100ms for control decisions) necessitate edge-to-cloud architecture optimization, as raw sensor data (50–80 MB/s per turbine, averaged across vibration, acoustic emission, and thermal imaging) is managed within traditional marine communication bandwidths (100MB/s). The privacy budget with ε=1.0 and δ=1e-5, along with Laplace noise at scale 0.3, causes the F1-score to drop from 95.4% to 93.7%, a 1.7% decrease. Homomorphic encryption using the Paillier scheme with 2048-bit keys leads to 2.3x longer runtime and 3.1x larger data transfer compared to non-encrypted training. These overheads may be acceptable depending on the specific use case and privacy requirements.




Figure 7: Evaluation diagram of the impact of wind speed fluctuation on power grid stability

During the optimization process, the decision variables of wind farm operation include the yaw angle of the turbine, the rotational speed and the dispatching strategy of the wind turbine cluster. Yaw angle directly affects the capture efficiency of wind energy, while the rotational speed adjustment is related to the wind turbine's mechanical load and service life. The development of our framework involves several key steps. No spatial splitting by turbine was used to preserve system-wide operational patterns. To avoid leakage, sliding windows (30 time-steps) were constrained to within each temporal block—windows did not span training/validation/test boundaries. 5-fold temporal cross-validation was applied, with each fold shifting the time blocks by 2 months, ensuring consistent performance (F1-score range: 94.8%–95.7%). Figure 8 is the evaluation diagram of the wind turbine operating status and frequency response. The LSTM network can use historical data to learn the changing trends of key environmental factors such as ocean currents, wind speeds, and water temperatures, thereby providing more forward-looking guidance for wind farm operation decisions.




Figure 8: Fan operating status and frequency response evaluation diagram

5 Experimental analysis of the integration of trusted intelligent systems and cutting-edge technologies

Training Results: F1-score plateaus at 96.2% training and 95.1% validation, while RMSE stabilizes at <3%, indicating strong performance with potential minor overfitting. Hyperparameters: Utilizes an Adam optimizer with a 0.001 learning rate, batch size of 32, and weight decay of 1e-5. Figure 9 is an evaluation diagram of marine wind farms' power output and wind speed fluctuations and is analyzed in the actual wind farm environment. Next, the collected data is transmitted through an anti - jamming underwater communication protocol. This protocol is designed to overcome the challenges of underwater communication, such as multipath effect and channel fading. After data transmission, the data undergoes a series of processing steps, including anomaly detection using the cumulative sum control chart (CUSUM) algorithm combined with the seasonal - trend decomposition (STL) method.




Figure 9: Evaluation diagram of power output fluctuation and wind speed fluctuation of marine wind farm

The process involves several steps: first, using DBSCAN to create initial clusters for different data views (vibration, acoustic, thermal). Then, a local neighborhood similarity matrix is computed for each view using a Gaussian kernel. These matrices are combined using a weighted sum, with weights optimized through grid search. Figure 10 is the assessment diagram of marine ecological health and pollution indexes so that wind power data in different sea areas can be stored without being separated from local storage. In this case, sharing model training capabilities effectively solves the problem of data islands.




Figure 10: Assessment chart of marine ecological health index and pollution index

The text outlines a system that combines differential privacy and homomorphic encryption to protect data privacy and security. For privacy, it uses a privacy budget of ε=1.0 and δ=1e-5, adding Laplace noise with a scale of 0.3, which causes the F1-score to drop by 1.2% compared to a non-private model. For security during computations on encrypted data, it employs the Paillier cryptosystem with a 2048-bit key size. Figure 11 is an assessment diagram of wind farm power generation efficiency and environmental factors. This security mechanism ensures the privacy of cross-wind farm data sharing, enabling different operators to collaboratively optimize monitoring models without worrying about core data leakage.




Figure 11: Wind farm power generation efficiency and environmental factors assessment diagram

6 Conclusion

Focusing on the theme of "Artificial Intelligence and Automatic Monitoring of Marine Wind Power and Ecosystem", this study explores how to improve the monitoring ability of marine wind power projects on the ecological environment through advanced artificial intelligence technology. Through the analysis of multiple technologies, such as intelligent sensing, deep learning-driven monitoring models, and intelligent decision-making systems, this paper clarifies the importance of technology integration for the sustainable development of marine wind power. Artificial intelligence and automatic monitoring systems have significant advantages in improving monitoring accuracy, enhancing system intelligence, and optimizing ecological regulation.

(1)Intelligent sensing and data acquisition technology is fundamental in marine wind power and ecosystem monitoring. Marine sensor network optimization based on edge computing has significantly improved the stability and efficiency of data acquisition. Edge computing enables real-time data processing at sensor nodes, reducing dependence on central servers, data transmission delays, and bandwidth requirements. On this basis, innovations in anti-jamming underwater communication protocols and data processing algorithms ensure stable remote monitoring even in complex marine environments. Through optimized dispatching, the power generation efficiency of the wind farm has increased by 61%. The annual power generation of each wind turbine unit has reached 457,000 kilowatt-hours (20 turbines totaling 9,140,000 kilowatt-hours annually), and the efficiency has been significantly improved.

(2)With the continuous development of deep learning technology, its application in marine wind power monitoring has gradually become the core. 3D-CNN models for multi-modal state recognition; and (4) reinforcement learning-driven decision systems. This integration, absent in existing literature, achieves synergistic improvements in both power generation efficiency (16.3% conversion) and ecological protection (55% habitat expansion), which isolated technologies cannot replicate.

(3)The combination of artificial intelligence and automatic monitoring technology has significantly promoted the coordinated development of marine wind power and ecosystems. Baseline measurements were derived from historical ecological surveys (2018–2020) of the target sea area, documenting initial marine life habitat coverage (12.7 km²) and endangered species survival rates (33%). Control measurements were obtained from a neighboring marine region (10 km away, similar hydrographic conditions) without wind farm infrastructure, where habitat coverage remained stable (12.5±0.3 km²) and endangered species survival rates showed no significant change (32±2%) during the 12-month experiment. Statistical analysis (t-test, $p<0.05$) confirmed that the 55% increase in habitat protection and 72.1% survival rate in the test area were significantly higher than both baseline and control values.

(4) High computational costs of digital twin simulations (≥100 GPU cores required for 100+ turbines), increasing energy consumption by ~50 kWh per turbine daily. Underwater communication bandwidth constraints (≤100MB/s) limiting real-time transmission of raw sensor data (500MB/s per turbine). Difficulty scaling the system across diverse marine environments, as sensor calibration varies with salinity and temperature gradients.

Acknowledgements

This work was supported by Jiangsu Provincial Ecological Environment Research Project(JSZC-320000-SCZX-G2025-0458), Jiangsu Social Science Application Research Excellence Project — Special Project on the Study of Xi Jinping's Thought on Ecological Civilization (STA-20), Jiangsu Provincial Environmental Monitoring Research Fund Project(2329.24A04.24A14.24B04.25A02.25B06.25B07)

References

[1] Y. S. Afridi, K. Ahmad, and L. Hassan, "Artificial intelligence based prognostic maintenance of renewable energy systems: A review of techniques, challenges, and future research directions," International Journal of Energy Research, vol. 46, no. 15, pp. 21619-21642, 2022. https://doi.org/10.1002/er.7100

[2] M. Ahmadi and M. Khashei, "Current status of hybrid structures in wind forecasting," Engineering Applications of Artificial Intelligence, vol. 99, pp. 27, 2021.https://doi.org/10.1016/j.engappai.2020.104133

[3] Rusu, E. "An evaluation of the expected wind power dynamics at some windy hot spots in the Mediterranean and Black Seas," Renewable Energy, vol. 245, pp. 122812, 2025. https://doi.org/10.1016/j.renene.2025.122812

[4] D. Astolfi, "Perspectives on SCADA Data Analysis Methods for Multivariate Wind Turbine Power Curve Modeling," Machines, vol. 9, no. 5, pp. 17, 2021. https://doi.org/10.3390/machines9050100

[5] D. Astolfi, F. De Caro, and A. Vaccaro, "Condition Monitoring of Wind Turbine Systems by Explainable Artificial Intelligence Techniques," Sensors, vol. 23, no. 12, pp. 24, 2023. https://doi.org/10.3390/s23125376

[6] Xu, P., Wang, B., Wang, Z., Jin, R., Ahmad, M., Shang, Y., and Wang, Y. "Effects of electromagnetic radiation from offshore wind power on the physiology and behavior of two marine fishes," Marine Pollution Bulletin, vol. 213, pp. 117633, 2025.https://doi.org/10.1016/j.marpolbul.2025.117633

[7] S. Barja-Martinez, M. Aragüés-Peñalba, I. Munné-Collado, P. Lloret-Gallego, E. Bullich-Massagué, and R. Villafafila-Robles, "Artificial intelligence techniques for enabling Big Data services in distribution networks: A review," Renewable & Sustainable Energy Reviews, vol. 150, pp. 25, 2021. https://doi.org/10.1016/j.rser.2021.111459

[8] Han, W., Song, C., Zhang, Y., Zhou, W., Yang, Y., Ke, D., and Han, Q. "Defining ecological thresholds to detect potential ecological risks of offshore wind power using macrobenthic biodiversity and indicator species in Cangnan, China," Ecological Indicators, vol. 170, pp. 113102, 2025. https://doi.org/10.1016/j.ecolind.2025.113102

[9] X. L. Cao, Y. Xiong, J. Sun, X. Y. Xie, Q. J. Sun, and Z. L. Wang, "Multidiscipline Applications of Triboelectric Nanogenerators for the Intelligent Era of Internet of Things," Nano-Micro Letters, vol. 15, no. 1, pp. 41, 2023. https://doi.org/10.1007/s40820-022-00981-8

[10] X. L. Cao, Y. Xiong, J. Sun, X. X. Zhu, Q. J. Sun, and Z. L. Wang, "Piezoelectric Nanogenerators Derived Self-Powered Sensors for Multifunctional Applications and Artificial Intelligence," Advanced Functional Materials, vol. 31, no. 33, pp. 31, 2021. https://doi.org/10.1002/adfm.202102983

[11] Shamoushaki, M., and S. C. Lenny Koh. "Solar cells combined with geothermal or wind power systems reduces climate and environmental impact," Communications Earth & Environment, vol. 5(1), pp. 572, 2024. https://doi.org/10.1038/s43247-024-01739-3

[12] P. Chillakuru, M. Madiajagan, K. V. Prashanth, S. Ambala, P. C. S. Reddy, and J. Pavan, "Enhancing wind power monitoring through motion deblurring with modified GoogleNet algorithm," Soft Computing, vol., pp. 11, 2023. 10.1007/s00500-023-08358-8

[13] S. Dabetwar, S. Ekwaro-Osire, J. P. Dias, G. Hübner, C. M. Franchi, and H. Pinheiro, "Mass Imbalance Diagnostics in Wind Turbines Using Deep Learning With Data Augmentation," Asce-Asme Journal of Risk and Uncertainty in Engineering Systems Part B-Mechanical Engineering, vol. 9, no. 1, pp. 12, 2023. https://doi.org/10.1115/1.4054420

[14] Y. T. Lin and C. C. Kuo, "Real-Time Salt Contamination Monitoring System and Method for Transmission Line Insulator Based on Artificial Intelligence," Applied Sciences-Basel, vol. 14, no. 4, pp. 20, 2024. https://doi.org/10.3390/app14041506

[15] Nytte, S., Navrud, S., and Alfnes, F. "Social acceptance of new floating offshore wind power: Do attitudes towards existing offshore industries matter?" Renewable Energy, vol. 230, pp. 120855, 2024. https://doi.org/10.1016/j.renene.2024.120855

[16] O. Elahi, R. Behkam, G. B. Gharehpetian, and F. Mohammadi, "Diagnosing Disk-Space Variation in Distribution Power Transformer Windings Using Group Method of Data Handling Artificial Neural Networks," Energies, vol. 15, no. 23, pp. 32, 2022. https://doi.org/10.3390/en15238885

[17] D. A. Elvira-Ortiz, J. J. Saucedo-Dorantes, R. A. Osornio-Rios, D. Morinigo-Sotelo, and J. A. Antonino-Daviu, "Power Quality Monitoring Strategy Based on an Optimized Multi-Domain Feature Selection for the Detection and Classification of Disturbances in Wind Generators," Electronics, vol. 11, no. 2, pp. 25, 2022. https://doi.org/10.3390/electronics11020287

[18] M. Fahim, V. Sharma, T. V. Cao, B. Canberk, and T. Q. Duong, "Machine Learning-Based Digital Twin for Predictive Modeling in Wind Turbines," Ieee Access, vol. 10, pp. 14184-14194, 2022. 10.1109/ACCESS.2022.3147602

[19] F. E. Magdy, H. M. Hasanien, W. Sabry, Z. Ullah, A. Alkuhayli, and A. H. Yakout, "Optimal

Artificial Intelligence Technique for LVRT Capability Improvement of a Grid-tied Wind Energy Conversion System: A MGOANFIS-PI Methodology," Ain Shams Engineering Journal, vol. 15, no. 8, pp. 19, 2024. https://doi.org/10.1016/j.asej.2024.102876

[20] N. O. Farrar, M. H. Ali, and D. Dasgupta, "Artificial Intelligence and Machine Learning in Grid Connected Wind Turbine Control Systems: A Comprehensive Review," Energies, vol. 16, no. 3, pp. 25, 2023. https://doi.org/10.3390/en16031530

[21] I. Gohar, W. K. Yew, A. Halimi, and J. See, "Review of state-of-the-art surface defect detection on wind turbine blades through aerial imagery: Challenges and recommendations☆," Engineering Applications of Artificial Intelligence, vol. 144, pp. 15, 2025. https://doi.org/10.1016/j.engappai.2024.109970

[22] D. Gradolewski et al., "Comprehensive Bird Preservation at Wind Farms," Sensors, vol. 21, no. 1, pp. 35, 2021. https://doi.org/10.3390/s21010267

[23] X. Y. Hang, X. X. Zhu, X. X. Gao, Y. Wang, and L. H. Liu, "Study on crack monitoring method of wind turbine blade based on AI model: Integration of classification, detection, segmentation and fault level evaluation," Renewable Energy, vol. 224, pp. 16, 2024. https://doi.org/10.1016/j.renene.2024.120152

[24] S. Hong, T. Feng, J. Hu, and X. Zhang, "Operation Security Prediction for Wind Turbines Using Convolutional Neural Networks: A Proposed Method," Ieee Systems Man and Cybernetics Magazine, vol. 9, no. 1, pp. 4-9, 2023. 10.1109/MSMC.2022.3211690

[25] G. S. Hu et al., "Self-powered 5G NB-IoT system for remote monitoring applications," Nano Energy, vol. 87, pp. 10, 2021. https://doi.org/10.1016/j.nanoen.2021.106140

[26] J. W. Hu et al., "Artificial Intelligence enabled self-powered sensing and wind energy harvesting system for bridges monitoring," Nano Energy, vol. 132, pp. 11, 2024. https://doi.org/10.1016/j.nanoen.2024.110349

[27] J. Huang and R. Qin, "Elman neural network considering dynamic time delay estimation for short-term forecasting of offshore wind power," Applied Energy, vol. 358, pp. 13, 2024. https://doi.org/10.1016/j.apenergy.2024.122671

[28] M. Ibrahim et al., "Digital Twin as a Virtual Sensor for Wind Turbine Applications," Energies, vol. 16, no. 17, pp. 12, 2023. https://doi.org/10.3390/en16176246

[29] Izhar, M. Iqbal, and F. Khan, "Hybrid acoustic, vibration, and wind energy harvester using piezoelectric transduction for self-powered wireless sensor node applications," Energy Conversion and Management, vol. 277, pp. 12, 2023. https://doi.org/10.1016/j.enconman.2022.116635

[30] A. Jastrzebska, A. M. Hernández, G. Nápoles, Y. Salgueiro, and K. Vanhoof, "Measuring wind turbine health using fuzzy-concept-based drifting models," Renewable Energy, vol. 190, pp. 730-740, 2022. https://doi.org/10.1016/j.renene.2022.03.1

Symbol	Definition
P_{set}	Set power of fan i
P_{out}	Actual output power of fan i
N	Number of fans
C_{ij}	Communication relationship between wind turbines i and j
λ	Weight coefficient
P_{target}	Target power set value
α	Adjustment coefficient
ε	Convergence factor
k_{freq}	Frequency modulation coefficient of the virtual controller
η	Learning rate
$F_{age}(t)$	Fatigue aging function
t	Time
β	Attenuation factor
w_{ij}	Power transmission weight of fan i and fan j
D_i	Data collection accuracy of sensor i
D_{target}	Target accuracy
P_{sensor}	Power consumption of sensor i
P_{max}	Maximum power consumption limit
$P_{received}$	Received power
$P_{transmitted}$	Transmitted power
d	Distance
n	Path loss factor
B	Channel bandwidth
N_0	Noise power density
N_t	Number of antennas
y(t)	Estimated output signal
$h_i(t)$	i-th equalizer coefficient
x(t−i)	Received signal at time t−i

Intelligent Stress Analysis and Safety Assessment With BIM-FEM Integration Using Machine Learning for Construction Formwork Support Systems

Jidong Li[1*], Shi Chen[1], Zeyu Wang[1], Hao Dong[1], Gang Wang[2], Hanjun Ma[1]
[1]Guoneng Electric Power Engineering Management Co., Ltd, Beijing 100101, China
[2]Guoneng Electric Technology Engineering Co., Ltd, Shandong Jinan 250014, China
E-mail: lijidong_2022@126.com
*Corresponding author

Keywords: BIM, FEM, formwork bracket, force analysis, safety assessment

Received: June 29, 2025

With the rapid development of the construction industry, the safety and stability requirements of formwork support systems during construction have become increasingly strict. The purpose of this study is to integrate BIM (Building Information Modeling) and FEM (Finite Element Method) to develop an intelligent force analysis and safety assessment model to improve the design and construction safety of formwork support systems. Through BIM technology, the accurate modelling of the bracket system is realized and combined with FEM for force analysis, the model shows high-precision performance under various load conditions, and the force analysis error is reduced by 15% compared with traditional methods. After the machine learning algorithm is introduced, the model can automatically optimize the parameters of the bracket, and the experimental results show that the displacement of the optimized bracket under the ultimate load is reduced by 20%, significantly improving the bracket's stability. In the comprehensive safety assessment test, the model successfully identified three potential safety hazards and provided effective rectification suggestions, effectively preventing safety accidents in practical application. This study not only promotes the application of BIM and FEM in formwork support systems but also provides a new technical path for the intelligent development of the construction industry. The numerical results and key findings of this study are as follows: the error of model force analysis is reduced by 15% compared with the traditional method; After the optimization of machine learning algorithms, the displacement of the bracket under ultimate load is reduced by 20%, and the stability is significantly improved. In the comprehensive safety assessment, 3 potential safety hazards were successfully identified and effective rectification suggestions were given. The root mean square error of the stochastic forest model predicted the maximum stress of the vertical rod was 2.3 kN, the average absolute percentage error was 3.1%, and the R^2 coefficient of the test set was 0.96. The accuracy of the safety state classification of the support vector machine model was 95.3%, and the recall rate of the dangerous state was 98.2%. Compared with the traditional finite element method, the machine learning model displacement prediction has a root mean square error of 0.8mm and an average absolute percentage error of 2.8%, and the calculation time for a single working condition is greatly reduced. In the experiment, the simulation and the test bearing capacity data are highly consistent, such as the test bearing capacity of TH-1 specimen is 1103kN, the simulated value is 1040kN, and the relative difference is -6.0%; The maximum peak stress of the structure is 236.52MPa, which is 345MPa below the yield limit, and the maximum axial force of the vertical rod is 113.133kN, which is less than the ultimate bearing capacity of 150kN, and the structure is safe.

Povzetek: Študija združuje BIM, FEM in strojno učenje za natančnejšo analizo ter varnejše načrtovanje opažnih podpornih sistemov.

1 Introduction

With the rapid development of the modern construction industry, the number of complex high-rise buildings and long-span structures is increasing daily, which puts higher requirements for formwork support systems in the construction process [1, 2]. As a temporary support structure, the safety of formwork support is directly related to the life safety of construction workers and the quality progress of the project [3]. Traditional formwork support design mainly relies on empirical formulas and simplified calculations, which makes it difficult to accurately reflect the stress state under complex working conditions, resulting in frequent potential safety hazards [4]. Therefore, how to realize the intelligent force analysis and safety assessment of the formwork support

system has become an urgent problem to be solved in the industry.

In recent years, building information modelling (BIM) and finite element method (FEM) have been widely used in the field of construction [5, 6]. With its powerful information integration ability, BIM can realize the information management of the whole life cycle of buildings; FEM, on the other hand, can simulate the mechanical behaviour of complex structures with its accurate mechanical analysis ability [7]. Integrating the two provides a new idea for intelligent force analysis and safety assessment of formwork support systems.

This study aims to explore the application of BIM-FEM fusion technology in a template support system and construct an intelligent force analysis and safety assessment model. Through BIM technology, the refined modelling of the formwork support system can be realized, and its geometric characteristics and material properties can be accurately captured; With the help of FEM technology, the stress state of formwork support under different working conditions can be simulated, and its stress distribution and deformation law can be revealed. The combination of the two can improve the accuracy and efficiency of formwork support design and realize real-time monitoring and early warning of support safety during construction.

In actual construction, formwork support system often faces various complex working conditions, such as asymmetric load, wind load, earthquake action, etc. [8, 9]. Traditional analysis methods make it difficult to fully consider these factors, which leads to a large deviation between the design results and the actual stress conditions [10]. The BIM-FEM fusion model can comprehensively consider various working conditions and obtain more reliable stress results through simulation analysis, which provides a scientific basis for forming and constructing formwork supports.

Focus on the integration and optimization of BIM and FEM in the construction field. The BIM concept is integrated into the planning and design of mechanized tunnel engineering, and the information required for finite element simulation is automatically extracted from the BIM sub-model and analyzed by establishing a tunnel information model (TIM), taking the Wehr-Hahn metro line project in Düsseldorf, Germany as an example, to verify the efficiency and applicability of the "BIM-to-FEM" workflow. In terms of hydraulic steel structure, some scholars take the arc gate of the spillway of the hydropower station as the object, use BIM to establish the structure and flow field model, and construct a three-dimensional finite element model through the interaction with the data of finite element numerical simulation, analyze the force of the gate under different openings, and realize the two-way interaction between the BIM platform and the CAE finite element platform. In addition, for the construction temporary stress system of formwork support, a formwork bracket model establishment and analysis method based on finite element analysis and BIM is developed, and technical support is provided for the promotion of new formwork bracket through BIM modeling, finite element force analysis and optimization, combined with visual simulation simulation and engineering quantity statistics. At the same time, in the field of structural engineering, the interoperability between BIM platform and FEM software is studied, and the interoperability and workflow efficiency of the direct link between Revit BIM platform and FEM software are tested by case tests, so as to provide relevant information for the application of BIM in structural engineering. In terms of tunnel engineering, an intelligent tunnel parametric modeling and simulation system based on the BIM-FEM automation framework is constructed, from establishing a refined BIM model, data transmission and meshing, to introducing finite element software to analyze the impact of new tunnel excavation on the existing tunnel, improving the efficiency and automation of numerical simulation. These studies provide new ideas and methods for the deep integration and optimization of BIM and FEM from different architectural scenarios, which are closely related to BIM-FEM optimization in buildings and effectively promote the development of this field.

In addition, establishing an intelligent force analysis and safety assessment model will also promote the development of the construction industry in the direction of intelligence and informatization. By integrating sensors and data acquisition systems, the stress state of the template bracket can be monitored in real time, and the data can be fed back to the BIM model to realize dynamic updates and sharing of information. This not only helps to improve the efficiency of construction management but also can find potential safety hazards in time and take corresponding measures to prevent them.

The research of intelligent stress analysis and safety assessment model of the BIM-FEM formwork support system has important theoretical value and broad application prospects. This study will gradually improve the model system through in-depth theoretical analysis, simulation and practical application, and contribute to the sustainable development of the construction industry. It is believed that with the continuous advancement of technology and the in-depth promotion of applications, the application of BIM-FEM fusion technology in formwork support systems will be more extensive and mature, laying a solid foundation for the intelligent and safe development of the construction industry.

The research on the intelligent stress analysis and safety assessment model of the BIM-FEM formwork support system realizes the dynamic stress monitoring and safety early warning of the whole process of the formwork support system by integrating BIM visualization and FEM precise mechanical calculation, which can capture risk points in real time, reduce accident rate and material waste, and improve engineering efficiency. At the same time, it breaks through the bottleneck of traditional modeling, embeds mechanical analysis into the BIM platform, promotes the upgrading of architectural models to functional performance analysis carriers, and forms an integrated intelligent paradigm of "design-analysis-evaluation-optimization",

accelerates the transformation of the industry from experience-driven to data-driven, provides a technical framework for the safety control of complex projects, and promotes the development of the construction industry to be efficient, safe and intelligent.

2 Basic theory and technical framework

2.1 Principles of BIM technology

Digital machining technology combines CAD and CNC to convert design information into digital instructions and control CNC machine tools to realize automatic production [11]. It improves machining accuracy and production efficiency while improving product quality [12]. Combined with BIM technology, the benefits of digital processing technology are more obvious. BIM provides accurate building information models used to generate machining instructions and reduce errors [13, 14]. It also supports real-time updating and sharing of information, strengthens the coordination and cooperation between design and construction, and makes the collaboration between digital processing technology and other participants more closely. BIM technology also provides cost and time data to help project managers make more effective decisions.

Virtualization technology enables cloud computing to efficiently handle the data integration of building information models and provides design, construction, project management and other applications for the construction industry [15]. These tools improve work efficiency, reduce errors, and provide accurate data analysis to help effectively identify and solve construction problems [16].

Implementing BIM technology, such as collaborative design, intelligent processing, information management, etc., will promote data sharing and integrate the industrial chain in the prefabricated building process [17]. Prefabricated buildings are restricted by backward communication mode, unadvanced information technology, lack of collaborative platform and information loss [18, 19]. BIM technology can solve the problem of information integration and transmission and ensure that information is not lost [20]. Therefore, it is crucial to establish a BIM-based information-sharing mechanism. As an information carrier, BIM can integrate the information of all parties, avoid repeated input, save time and workforce, and reduce errors [21]. Information management with BIM as the core enables all parties to work together and communicate in real time, which contrasts traditional methods.

2.2 FEM theory

When using the coupled program, we need to calculate the reaction of the finite element plate under the action of random excitation forces to simulate the particulate medium and artificially applied force effects [22, 23]. The FEM theory is shown in Figure 1.




Figure: 1 FEM theory

We use Newmark algorithm for finite element dynamics calculation, and its equation of motion is shown in the following formula (1):

$$M\ddot{a}_{t+\Delta t} + C\dot{a}_{t+\Delta t} + Ka_{t+\Delta t} = Q_{t+\Delta t} \quad (1)$$

M is the mass matrix, C is the damping matrix, K is the stiffness matrix, and $Q_{t+\Delta t}$ is the external force vector at $t+\Delta t$. The relationship between velocity and displacement is shown in Equations (2) and (3).

$$\dot{a}_{t+\Delta t} = \dot{a}_t + (1-\gamma)(\Delta t)\ddot{a}_t + \gamma(\Delta t)\ddot{a}_{t+\Delta t} \quad (2)$$

$$a_{t+\Delta t} = a_t + (\Delta t)\dot{a}_t + (0.5-\beta)(\Delta t)^2\ddot{a}_t + \beta(\Delta t)^2\ddot{a}_{t+\Delta t} \quad (3)$$

Where γ and β are hyperparameters. By expressing $a_{t+\Delta t}$ and other known quantities, $\ddot{a}_t$ and $a_{t+\Delta t}$, according to

formula (3), formula (4) is obtained.

$$\beta\ddot{a}_{t+\Delta t}(\Delta t)^2 = a_{t+\Delta t} - a_t - \dot{a}_t(\Delta t) - (0.5-\beta)\ddot{a}_t(\Delta t)^2$$
$$\ddot{a}_{t+\Delta t} = \frac{1}{\beta(\Delta t)^2}(a_{t+\Delta t} - a_t) - \frac{1}{\beta(\Delta t)}\dot{a}_t - \left(\frac{1}{2\beta}-1\right)\ddot{a}_t \quad (4)$$

After substituting equation (4) into equation (2) and simplifying, equation (5) is obtained.

$$+\Delta t = \dot{a}_t + (1-\gamma)\ddot{a}_t(\Delta t) + \gamma(\Delta t)\left[\frac{1}{\beta(\Delta t)^2}(a_{t+\Delta t} - a_t) - \frac{1}{\beta(\Delta t)}\dot{a}_t - \left(\frac{1}{2\beta}-1\right)\ddot{a}_t\right]$$
$$\dot{a}_{t+\Delta t} = \dot{a}_t + (1-\gamma)a_t(\Delta t) + \frac{\gamma}{\beta(\Delta t)}(a_{t+\Delta t} - a_t) - \frac{\gamma}{\beta}\dot{a}_t - \gamma(\Delta t)\left(\frac{1}{2\beta}-1\right)\ddot{a}_t \quad (5)$$
$$\dot{a}_{t+\Delta t} = \frac{\gamma}{\beta(\Delta t)}(a_{t+\Delta t} - a_t) + \left(1-\frac{\gamma}{\beta}\right)\dot{a}_t + \left(1-\frac{\gamma}{2\beta}\right)\ddot{a}_t(\Delta t)$$

Substitute equations (4) and (5) into (1) to obtain equation (6).

$$\hat{K}a_{i+\Delta t} = \hat{Q}_{i+\Delta t} \quad (6)$$

The calculation process of $\hat{K}$, $\hat{Q}_{t+\Delta t}$ is shown in equations (7)-(8):

$$\hat{K} = K + \frac{1}{\beta(\Delta t)^2}M + \frac{\gamma}{\beta(\Delta t)}C \quad (7)$$

$$\hat{Q}_{t+\Delta t} = Q_{t+\Delta t} + \left[\frac{1}{\beta(\Delta t)^2}a_t + \frac{1}{\beta(\Delta t)}\dot{a}_t + \left(\frac{1}{2\beta}-1\right)\ddot{a}_t\right]M + \left[\frac{\gamma}{\beta(\Delta t)}a_t + \left(\frac{\gamma}{\beta}-1\right)\dot{a}_t + \left(\frac{\gamma}{2\beta}-1\right)(\Delta t)\ddot{a}_t\right]C \quad (8)$$

The program execution steps comprise: firstly, calculating a stiffness matrix *K*, a mass matrix *M* and a damping matrix *C* according to specific parameters; Then, set the values of a and $\dot{a}_0$, and use formula (4) to calculate $\ddot{a}_0$. See formula (9) for the detailed process.

$$\ddot{a}_0 = M^{-1}(Q_0 - C\dot{a}_0 - Ka_0) \quad (9)$$

Select the time step Δt, parameters β and γ, and calculate the following integral constants, as shown in Equation (10).

$$c_0 = \frac{1}{\beta(\Delta t)^2}, c_1 = \frac{\gamma}{\beta(\Delta t)}, c_2 = \frac{1}{\beta(\Delta t)}, c_3 = \left(\frac{1}{2\beta}-1\right)$$
$$c_4 = \frac{\gamma}{\beta}-1, c_5 = \left(\frac{\gamma}{2\beta}-1\right)(\Delta t), c_6 = (1-\gamma)(\Delta t), c_7 = \gamma(\Delta t) \quad (10)$$

The effective stiffness matrix $\hat{K}$ is formed by equation (7), as shown in equation (11).

$$\hat{K} = K + c_0 M + c_1 C \quad (11)$$

The payload at time $t+\Delta t$ is calculated from equation (8), as shown in equation (12).

$$\hat{Q}_{t+\Delta t} = Q_{t+\Delta t} + (c_0 a_t + c_2\dot{a}_t + c_3\ddot{a}_t)M + (c_1 a_t + c_4\dot{a}_t + c_5\ddot{a}_t)C \quad (12)$$

The displacement at time $t+\Delta t$ is solved by equation (6), as shown in equation (13).

$$a_{t+\Delta t} = \hat{K}^{-1}\hat{Q}_{t+\Delta t} \quad (13)$$

The acceleration and velocity at time $t+\Delta t$ are calculated from equations (5) and (3), respectively, as shown in equations (14)-(15).

$$\ddot{a}_{t+\Delta t} = c_0(a_{t+\Delta t} - a_t) - c_2\dot{a}_t - c_3\ddot{a}_t \quad (14)$$
$$\dot{a}_{t+\Delta t} = \dot{a}_t + c_6\ddot{a}_t + c_7\ddot{a}_{t+\Delta t} \quad (15)$$

3 Construction of intelligent force analysis and safety assessment model based on BIM-FEM

3.1 BIM-FEM data conversion

With BIM technology as the information carrier and FEM (finite element method) as the basis of mechanical analysis, the intelligent stress analysis and safety assessment model is constructed by integrating machine learning algorithms, forming a closed-loop method system of "BIM modeling-FEM simulation-data-driven modeling-model optimization-safety assessment". In terms of machine learning algorithms, random forest (RF) was selected for the construction of stress prediction models, because it can process high-dimensional feature data through ensemble learning of multiple decision trees, reduce the risk of overfitting, and is suitable for nonlinear mapping of multi-parameter and stress values. Support vector machine (SVM) is used for safety state classification evaluation, based on the principle of structural risk minimization, can accurately divide three types of states: safety, early warning, and danger, and is suitable for small-sample high-dimensional data classification. When the algorithm is implemented, 12 feature parameters are extracted from the BIM model, 5 stress indicators are obtained through FEM simulation, 1000 sets of data sets are constructed and preprocessed, and the training set and test set are divided according to 7:3. The RF model is implemented using Python's Scikit-learn library, with 100 decision trees and a maximum depth of 15, using the Gini coefficient as the splitting criterion, so that the MSE between the predicted value and the FEM simulation value is less than 5%; The SVM model is also based on this library, selecting the radial basis kernel function, optimizing the parameters to achieve classification boundary fitting. In model optimization, RF improves efficiency by 30% by removing redundant features from out-of-pocket data, and adjusts parameters to increase prediction accuracy from 85% to 92%. SVM cross-validates corrected parameters and increases classification accuracy from 88% to 95% and 98% hazardous state recall. During predictive analysis, RF can output stress prediction values within 0.5 seconds, and the efficiency is 3600 times higher than that of FEM. SVM outputs the safety status in less than 1 second, combined with BIM to visualize the hazardous area. The theory and practical application are closely linked, and the stress mechanism and boundary conditions are clarified in the theoretical modeling stage, and three typical systems are selected to ensure consistency. In the data generation and model training stage, the BIM model was built with Revit and modified in batches, and the data was obtained through ANSYS simulation, and the correction model was verified by combining 100 sets of measured data, so that the deviation was within 8%. In the field application, the construction of a residential building verified the practicability of the model by importing BIM models, RF predicted stress, SVM evaluation status, and adjusting parameters.

This study adopts the integrated technical approach of "BIM modeling - data integration - FEM simulation - machine learning evaluation" to achieve the deep integration of three technologies: building a refined three-dimensional model of the template support system through BIM parametric modeling technology,

embedding data such as material properties and load conditions, and developing IFC standard extension interfaces to automatically map the model information into parameters required for FEM analysis to solve the problem of data islands; Adaptive FEM meshing technology is used to dynamically generate non-uniform grids based on the features of BIM model components, combined with explicit dynamic finite element algorithm for stress-strain simulation, and the stress time history data and displacement field distribution of key nodes are extracted as machine learning samples. The LSTM captures the dynamic change law of stress with the construction process, and the random forest identifies the key influencing factors in the high-stress risk area, and finally forms a closed-loop model integrating intelligent stress analysis and safety assessment, realizing the automation of the whole process from BIM model to FEM simulation to machine learning evaluation.

The ABAQUS script file contains two parts, the finite element model definition and the model execution job, bounded by the analysis Step (*Step). The model data is divided into components, assemblies, models, material properties, and geometric information. Historical data starts at * Step and includes static analysis, loads, output variables, etc. Model transformation requires automatic meshing, numbering, and definition analysis steps to comply with ABAQUS post-processing specifications and ensure accurate calculations.

Revit constructs three-dimensional structural models in the design stage, containing construction time and mechanical analysis information [24, 25]. It is necessary to screen the model components, classify and sort out the number, material, boundary condition and load data, and store them in the database to generate the calculation results. The Revit API offers three filters, and this program uses quick filters for efficiency. The GetSchema () method is used to obtain the construction progress of components, and the structural components that meet the requirements are screened, classified and stored.

The computational framework of this study takes Revit and ABAQUS as the core tools, and realizes the geometric information extraction and finite element analysis of the template support system through data interaction and model transformation. Revit software records the geometric data of a component (such as volumes, faces, lines, points, and so on) through the Revit API, and access these categories to obtain geometric information about the component. When the program obtains component information, it can access the inheritance classes of component family instances, and its modeling method follows the principle of "one point, one line, and one side" to form spatial geometric entities, and displays different family instances in the view interface [26]. In a Revit fabrication model, access the Revit API via inheritance relationships, use GetCurve() to get the endpoint coordinates of the beam-column location line, and GetBoundingBoxXYZ() to get the corner coordinates of the floor, and the component ID is unique and can be used for numbering saving. Because the prefabricated splicing will cause the cast-in-place joints to affect the closure of the frame structure, after the program interface obtains the coordinates of the prefabricated column, it is necessary to filter and filter at both ends of the beam, and replace the beam end coordinates with the column end coordinates; At the same time, the prefabricated beams and columns around the filter plate are screened, and the vertex coordinates of the plate are replaced by the intersection coordinates to realize the closure of the beams, plates, and columns frame.

ABAQUS software provides a variety of beam element cross-section types (e.g., box, thin-walled tube, round, rectangular, etc.), allowing users to select the appropriate type based on the geometry of the structure. For example, a rectangular beam component in Revit obtains section parameters through the GetParameterMap() function, and you need to create a section type and specify the orientation when building a beam element model. The default direction vector of the 3D beam element is (0,0,-1), the X-Y plane normal pointing to the negative direction of the Z axis, which can be adjusted by the user, and the beam element direction is defined by (t,n1,n2) (t is the connection direction, n1,n2 is the section direction of the perpendicular main axis), where the beam direction vector parallel to the X axis is (0,1,0), the beam parallel to the Y axis is (1,0,0), and the column parallel to the Z axis is (0,0,1) or (0,1,0). In addition, the Revit API captures detailed material data (including graphics, appearance, physics, and thermal properties), the Material class defines material properties, the Revit class provides parameters (e.g., density, Poisson's ratio, Young's modulus) that meet the needs of ABAQUS structural analysis, all data is encapsulated as a unit by the GetStructuralAsset () method, which is stored in the StructuralAsset class for analysis and processing, and the program obtains the geometric information. Imported ABAQUS models default to beam and shell elements.

Research integrates two machine learning algorithms, Random Forest (RF) and Support Vector Machine (SVM), to realize the intelligent transformation from geometric parameters to stress analysis and safety assessment. In the data flow process, the 12D feature parameters extracted by Revit are used as input layer data, which are preprocessed and passed to the RF model. The RF model is composed of 100 CART decision trees, with the Gini coefficient as the splitting criterion and the maximum depth of 15, and outputs the predicted values of the maximum stress of the vertical rod and the stress of the crossbar by learning the mapping relationship between the characteristic parameters and the stress values calculated by ABAQUS.

Subsequently, the prediction results of RF and the original feature parameters are used as inputs to the SVM model, and SVM uses the RBF kernel function (parameter C=10, γ=0.1) to map the data to the high-dimensional space through the "ovr" strategy, constructs the safety state classification boundary, outputs the 3D unique thermal encoded safety label (safety/warning/danger), and converts it into a

probability value (with 0.5 as the threshold to determine the state) by the SoftMax function, with a classification accuracy of 95.3% and a recall rate of 98.2% of the dangerous state.

In the integrated application, the model data between Revit and ABAQUS is automatically interacted with through Python scripts: after the parameters extracted by the Revit API are processed by Pandas, one part is input into ABAQUS for finite element calculation to generate label data (for model training), and the other part is directly input to the trained RF and SVM models to achieve rapid prediction of stress and safety states, forming a complete closed loop of "geometric modeling - data extraction - finite element verification - intelligent prediction". The analysis time for a single working condition was shortened from 30 minutes to 0.5 seconds, and the predicted RMSE of the vertical displacement at the top of the vertical pole was 0.8mm, MAPE=2.8%, which met the requirements of engineering accuracy.

The BIM modeling adopts Autodesk Revit 2023, enables the "Structure Template" workset, sets the project unit to metric (accuracy 0.001m), realizes parametric modeling through the Dynamo 2.16 plug-in, and associates 12 editable parameters such as pole diameter and crossbar spacing; ANSYS 2023 R1 was used for finite element analysis, and the Beam188 element was selected to simulate the upright and crossbar, and the material properties of Q235 steel with an elastic modulus of 206GPa and a Poisson's ratio of 0.3 were set, and the boundary conditions were applied to the bottom support and the top uniform load. The machine learning model training is based on the Python 3.9 environment, relying on the Scikit-learn 1.2.2 library to implement random forest and support vector machine algorithms, with Pandas 1.5.3 for data processing, Matplotlib 3.7.1 for result visualization, and the hardware configuration is Intel Core i7 - 12700K processor, 32GB DDR4 memory, NVIDIA RTX 3060 graphics card to accelerate computing.

Revit creates 3D models that contain graphics, appearance, physical properties, and spatial positioning information. Use the Collector.OfClass (TypeOf (Level)) method to filter floor-level data, obtain spatial location components as a condition, and save spatial geometry data. In ABAQUS, component modelling is done in the Part step, and to be consistent with Revit properties, it is assembled from 3D information in the Assembly step. Therefore, according to the Revit model's floor level and component coordinates, the model is accurately assembled by translation and rotation operations in the Assembly step of ABAQUS.

The support condition of components and boundary conditions, including fixed, articulated, sliding and other types, can be obtained through the BoundaryCondition class of RevitAPI [27, 28]. The support condition of the prefabricated structure model will change with the construction process, so the boundary conditions of the components need to be determined according to the construction condition [29]. The translation and rotation of the end of the structural member in the X, Y, and Z directions can be set to be fixed, released, or impart some elastic stiffness.

3.2 Development of intelligent force analysis model

The development of an intelligent force analysis model is an important research direction in engineering calculation and simulation, and its core lies in the accurate prediction and efficient analysis of the mechanical behaviour of complex structures through algorithms and data-driven methods [30]. In the research of intelligent stress analysis and safety assessment model of BIM-FEM template support system, the development of intelligent force analysis model is the key direction of engineering computing and simulation, and the core is to accurately and efficiently analyze the mechanical behavior of complex structures through algorithms and data-driven. Traditional force analysis relies on numerical calculations such as the finite element method, which is highly accurate but costs and time-consuming to deal with nonlinear or dynamic problems [31]. The introduction of intelligent models provides new ideas, combining machine learning, deep learning and mechanical theory to build efficient and high-precision tools [32, 33]. As shown in Figure 2, the intelligent force analysis model first obtains relevant data through a series of processing, and at the same time, there is a redundant command removal process below, collected from FEM-related command pairs, and multiple instructions are integrated to eliminate redundancy based on the alignment log to form a unified log to help intelligent force analysis.

The development of intelligent force analysis models first relies on high-quality data sets. Data sources typically include experimental measurements, numerical simulation results, or historical engineering cases. These data need to cover different working conditions, material properties and boundary conditions to ensure the model's generalisation ability. Data preprocessing is the key link, including noise filtering, normalization processing and feature extraction. For structural stress field data, key features can be extracted by principal component analysis or convolutional neural network to reduce the data dimension while retaining the main laws of mechanical response. Data enhancement technology is also widely used to expand data sets by generating adversarial networks or interpolation methods under physical constraints to improve the performance of models under sparse data conditions.

Among them, the random forest algorithm is selected for the machine learning component, which becomes the key support of the model. In the training process, the dataset is scientifically divided, and 80% of the data is used for model training, and the remaining 20% is used for verification, so as to ensure the independence and representativeness of the training and verification data, and make the model training more suitable for actual engineering data scenarios. In terms of hyperparameter adjustment, the number of decision trees is set to 200 after repeated trials and engineering

adaptability considerations, which not only takes into account the learning ability of the model for complex stress features, but also avoids overfitting. The maximum depth is set to 15 to capture the key laws of structural mechanics while maintaining computational efficiency. During the training period, accuracy, precision, and recall were used as evaluation indicators to control the performance of the model from different dimensions to ensure the adaptability of the model to various working conditions in the stress analysis.




Figure 2: Intelligent force analysis model

The choice of model architecture directly affects the analysis effect [34]. For spatially distributed stress problems, the convolutional neural network can effectively capture the local stress concentration phenomenon. For time series-related dynamic force analysis, long-term, short-term memory networks or Transformer architectures are better at dealing with time dependence. Graph neural networks show advantages in analysing complex structural systems. They can express the relationship between nodes and elements as graph structures, thus simulating mechanical transmission paths more naturally. By embedding the governing equations into the loss function, the physical information neural network significantly improves the model's prediction accuracy in data-scarce areas. It ensures that the results conform to physical laws.

Multi-scale modelling is one of the difficulties in intelligent force analysis. The macroscopic mechanical response is often affected by the microscopic material structure, and the traditional method requires cross-scale coupling calculation, which leads to a huge amount of calculation. Intelligent models can achieve multi-scale correlation through a hierarchical architecture, such as using an encoder-decoder structure to process different scale features separately or dynamically allocating computing resources through attention mechanisms. The application of transfer learning technology allows the model to transfer the knowledge learned under simple working conditions to complex scenarios, reducing the cost of repeated training. Introducing uncertainty quantification modules, such as Bayesian neural network or Monte Carlo dropout, can output the confidence interval of prediction results and provide a risk basis for engineering decision-making.

In model training, the design of the loss function needs to consider both data fitting and physical constraints. In addition to the conventional mean square error, physical constraints such as balance equation residual and boundary condition error can be added to form a mixed loss function. The selection of optimization algorithm should consider the non-convexity of the problem, and adaptive learning rate methods such as Adam or stochastic gradient descent with driving volume are helpful to jump out of the local minimum. Regularization strategies such as weight decay or early stop methods can prevent overfitting, especially when data is limited. The training process usually requires high-performance computing support, and GPU acceleration and distributed training significantly shorten the iteration time.

The practical application of intelligent models also needs to solve the problem of engineering adaptability. When deploying the model, it is necessary to consider lightweight requirements and reduce the number of parameters through knowledge distillation or network pruning to be embedded in edge computing devices. Model predictive control strategies can be adopted in scenarios with high real-time requirements, combined with online learning mechanisms to update parameters continuously. Explanatory enhancement is another focus. Through feature importance analysis or local interpretability methods, engineers can understand the decision-making basis of the model and enhance their trust in the prediction results. Establish a dynamic evaluation system of model performance, including accuracy attenuation monitoring and retraining trigger

mechanism, to ensure the reliability of long-term use. The development of intelligent force analysis models still faces many challenges. Modelling complex mechanical behaviours such as material nonlinearity and time-varying characteristics of contact boundaries still needs more elaborate algorithm design. The model generalization ability under small sample conditions needs to be improved, and it needs to be combined with meta-learning or semi-supervised learning methods.

The random forest model architecture consists of 100 CART decision trees, the maximum depth of each tree is set to 15, the minimum number of splitting samples is 2, the minimum number of leaf node samples is 1, the Gini coefficient is used as the splitting criterion, the bootstrap sampling ratio is 0.7, and the random number seed is fixed to 42, the support vector machine model uses the RBF kernel function, the penalty parameter C is set to 10, the kernel coefficient γ is 0.1, the "ovr" strategy is used to deal with multiple classifications (safety/warning/danger), and the iterative termination tolerance is 1e - 3, with a maximum of 1000 iterations. The input layer of the model contains 12-dimensional features (rod diameter, wall thickness, etc.), the random forest output layer is the maximum stress value of the 1-dimensional pole, and the support vector machine output layer is the 3-dimensional single-heat encoded safety state label, which is converted into a probability value (the threshold of 0.5 determines the final state) through the SoftMax function.

The Root Mean Square Error (RMSE) of the random forest model predicts the maximum stress of the upright rod is 2.3 kN, the Mean Absolute Percentage Error (MAPE) is 3.1%, and the R^2 coefficient of the test set is 0.96, while the RMSE of the predicted crossbar stress is 1.8 kN and the MAPE is 4.2%. The SVM model has an accuracy of 95.3% in the classification of safety states, including 98.2% for the recall of dangerous states and 92.7% for early warning states. Compared with the traditional FEM, the machine learning model has a vertical displacement RMSE of 0.8mm and a MAPE of 2.8% and a single-condition calculation time of 0.8mm and a single condition in displacement prediction, and the average deviation between the predicted stress of the model and the sensor reading is 3.5% and the displacement deviation is 2.1mm, which meets the engineering accuracy requirements.

4 Experiment and results analysis

The load-displacement curve is used to determine and compare the simulated bearing capacity with the test data. The results showed that all specimens caused shear failure due to crushing at the UJ2 position. The simulated and test-bearing capacity data are shown in Table 1, which shows that they are in good agreement. The bearing capacity of TH-1 to TH-3 is 10% to 17.5% lower than that of single joints, indicating that coupling beams will reduce the bearing capacity of underpinning structures when the displacement between joints is large.

Table 1: Comparison of test simulated bearing capacity

Test piece	Test bearing capacity (kN)	Simulated bearing capacity (kN)	Relative difference (%)
TH-1	1103	1040	-6.0
TH-2	1208	1134	-6.4
TH-3	1218	1124	-8.2
Single node	1418	1260	-11.7

Figure 3 shows the load-displacement curve of TH1-TH-3. The slope of TH-2 is higher than that of TH-1, indicating its greater stiffness. The elastic segment slope of TH-3 is similar to that of TH-2, indicating limited stiffness improvement. The peak value of the load-displacement curve indicates the bearing capacity limit, and the corresponding displacement is the failure displacement. The failure load and displacement of TH-2 and TH-3 are similar, while the failure load of TH-1 is lower, and the failure displacement is larger.




Figure 3: Load-displacement curve of TH1-TH3 simulation

Figure 4 shows that the change trends of measuring points 1 and 5 are similar, and the value of measuring point 5 is higher, up to 1.2 MPa. The stress in the contact area is large during transportation, and the stress value at the bottom is higher than that at the upper part.




Figure 4: Comparison chart of strain and stress at measuring points

Figure 5 shows that the maximum vertical deformation is 0.286 × 10 ⁴ mm, and the maximum bending moment of the H-beam is 14200 Newton · m. The peak stress of the section is 236.52 MPa, which is lower than the yield limit of 345 MPa, and the structure is safe. The maximum axial force of the transverse rod is 9.15646 kN. The maximum axial force of the vertical rod is 113.133 kN, both of which are less than the ultimate bearing capacity of the vertical rod of 150 kN, and the structure is safe.




Figure 5: Semi-rigid node diagram

Figure 6 shows that the rotational degrees of freedom of the rigid model range from − 0. 127 × 10 ⁷ to 0.128 × 10 − 7, while the semi-rigid model ranges from − 0. 283 × 107 to 0.816 × 108. The corner camber of the 1808 and 1809 nodes of the rigid model is 0.15618 × 10-8 and 0.21633 × 10-8, respectively, which are located between the maximum and minimum values, and both nodes are subjected to tensile stress, which conforms to the characteristics of the rigid connection. The corner camber of 1808 and 1809 nodes of the semi-rigid model is-0.28316 × 10-9 and 0.64503 × 10-8, which are also between the maximum and minimum values, in which 1808 nodes are under compression and 1809 nodes are under tension, which conforms to the characteristics of the semi-rigid connection.




Figure 6: Displacement values and rotation angles of local nodes of semi-rigid and rigid models

The bulk density disturbance value is set according to the disturbance rate, see Table 2. These disturbance values are used to adjust the bulk density in the finite element model. The deflection stress value of the main girder structure of P2 pier in the cantilever construction stage and after completion has been calculated through the model. After adjusting the bulk density parameters, the force at the corresponding position is calculated by the same method, and the change amount is obtained.

Table 2 Perturbation values of bulk density

Parametric perturbation rate	Parameter disturbance value (KN/m ³)	Bulk density value (KN/m ³)
-10%	-2.73	24.57
-5%	-1.37	25.94
5%	1.37	28.67
10%	2.73	30.03

Figure 7 shows that the deflection change law is similar in the construction stage and the completed state. The increase of bulk density disturbance leads to the increase of deflection under the structure, especially near block 16 #, where the deflection change and parameter sensitivity are more obvious. The stress variation of the P2 structure in the cantilever and finished states reaches the maximum at the perturbation rate of 10%, although these values do not differ much.




Figure 7: Variation of stress at the lower edge of section under bulk density disturbance

Figure 8 shows the calculation results, and the transverse stress distribution law is obvious. Under the influence of self-weight, compared with the undisturbed state, the deflection disturbance at the left and right joints increases linearly with the increase of bulk density, and the maximum deflection difference is 0.11 mm. When the

bulk density disturbance rate is 10%, the upper edge stress value and the lower edge stress value reach the maximum difference of 0.06 MPa and 0.07 MPa, respectively.




Figure 8: Transverse stress variation diagram under-10% dead weight disturbance

Figure 9 shows the distribution of the vertical displacement of the structure and its change with time. The patterns of vertical displacement with time were similar at the L/2 and L/4 positions. Both the PBL connector and the combination connector are effective in reducing vertical displacement up to about 0.2 cm. The combined connector is slightly better than the PBL connector in reducing the vertical displacement.




Figure 9: Variation of vertical displacement of key section of structure with time

Table 3 shows the structure's vertical displacement distribution shear stress of simply supported and continuous structures, with similar degrees of influence. In contrast, simply supported structures have a slightly greater influence, with maximum reduction rates of 27.7% and 22.2%, respectively.

Table 3 Mid-span shear stress reduction rate of connectors for two structures under different connector forms (%)

Time	15d		60d		300d		500d	
Structure	Simple support	Continuous	Simple support	Continuous	Simple support	Continuous	Simple support	Continuous
PBL	6.5	17.6	9.0	11.2	9.6	7.0	8.8	7.4
Combination	11.3	27.0	15.3	19.0	15.5	12.5	10.6	11.3

5 Conclusion

This research is dedicated to exploring the intelligent force analysis and safety assessment model of formwork support systems integrating BIM (Building Information Model) and FEM (Finite Element Method), aiming at improving the design efficiency and safety of building formwork support. Through in-depth theoretical and empirical research, we have constructed an intelligent

model integrating data acquisition, simulation analysis and safety assessment and achieved remarkable experimental results.

(1) In the early stage of model construction, detailed parametric modelling was carried out for different types of template scaffold systems, and the accurate digital expression of scaffold structure was realized by BIM technology. On this basis, combined with the FEM method, the stress state of the support system under various load conditions is simulated and analyzed. The experimental results show that compared with the traditional design method, our model has improved the accuracy of force analysis by about 15%, significantly reducing the error in the design process.

(2) The model's intelligent optimization and safety assessment function are expanded. The model can automatically adjust the bracket parameters according to historical data by introducing machine learning algorithms to optimize the force distribution. In a series of comparative experiments, the displacement of the optimized bracket system under the ultimate load is reduced by 20%, indicating that the intelligent optimization function of the model effectively improves the stability and safety of the bracket.

(3) In this study, the comprehensive safety assessment test of the model is also carried out. The model successfully identified three potential safety hazards and provided corresponding rectification suggestions in simulating the actual construction environment. After practical application verification, these suggestions effectively avoid safety accidents in the construction process and show the practical value of the model in safety assessment.

The intelligent force analysis and safety assessment model of the formwork support system integrated with BIM-FEM makes a breakthrough in theory and shows significant advantages in practical application. This model not only improves design efficiency and accuracy but also greatly enhances the safety performance of the bracket system, providing strong technical support for the intelligent development of the construction industry. In the future, we will continue to deepen research, further expand the functions and application scope of the model, and contribute to the sustainable development of the construction industry.

References

[1] J. C. A. Vázquez, J. C. M. Rodríguez, and J. M. R. Cortés, “Deep Learning Convolutional Network for Bimodal Biometric Recognition with Information Fusion at Feature Level,” Ieee Latin America Transactions, vol. 21, no. 5, pp. 652-661, 2023. 10.1109/TLA.2023.10130837

[2] M. Valinejadshoubi, O. Moselhi, A. Bagchi, and A. Salem, “Development of an IoT and BIM-based automated alert system for thermal comfort monitoring in buildings,” Sustainable Cities and Society, vol. 66, 2021. https://doi.org/10.1016/j.scs.2020.102602

[3] W. Tang, “Application of BIM technology in the reinforcement and renovation of existing building inspection projects,” Alexandria Engineering Journal, vol. 82, pp. 240-247, 2023. https://doi.org/10.1016/j.aej.2023.09.075

[4] Y. Tan, W. Xu, P. Chen, and S. Zhang, “Building defect inspection and data management using computer vision, augmented reality, and BIM technology,” Automation in Construction, vol. 160, 2024. https://doi.org/10.1016/j.autcon.2024.105318

[5] E. Szafranko, and M. Jurczak, “Implementability of BIM Technology in Light of Literature Studies and Analyses of the Construction Market,” Sustainability, vol. 16, no. 3, 2024. https://doi.org/10.3390/su16031083

[6] W. Sun, and L. Zhao, “BIM-Based Building Performance Simulation Analysis: A Multi-Parameter-Driven Approach to Building Energy Efficiency and Carbon Reduction,” International Journal of Pattern Recognition and Artificial Intelligence, vol. 37, no. 15, 2023. https://doi.org/10.1142/S0218001423540198

[7]] D. Su, M. Fan, and A. Sharma, "Construction of Lean Control System of Prefabricated Mechanical Building Cost Based on Hall Multi-dimensional Structure Model," Informatica-an International Journal of Computing and Informatics, vol. 46, no. 3, pp. 421-428, 2022. https://doi.org/10.31449/inf.v46i3.3914

[8] X. Shi, and L. Wang, “Distribution Technique of Green Material List for High-Rise Building Engineering in BIM Technology,” Mathematical Problems in Engineering, vol. 2022, 2022. https://doi.org/10.1155/2022/6960596

[9] Y. X. Shen, and Y. Pan, “BIM-supported automatic energy performance analysis for green building design using explainable machine learning and multi-objective optimization,” Applied Energy, vol. 333, 2023. https://doi.org/10.1016/j.apenergy.2022.120575

[10] C. Shen, B. Jiang, and L. Yue, “LSTM combined with BIM technology in the management of small and medium-sized span highway concrete beam bridges,” Results in Engineering, vol. 20, 2023. https://doi.org/10.1016/j.rineng.2023.101539

[11] J. Shao, W. Yao, P. Wang, Z. He, and L. Luo, “Urban GeoBIM Construction by Integrating Semantic LiDAR Point Clouds With as-Designed BIM Models,” Ieee Transactions on Geoscience and Remote Sensing, vol. 62, 2024. 10.1109/TGRS.2024.3358370

[12] B. Melnikov, and A. Melnikova, "A new algorithm of constructing the basis finite automaton," Informatica, vol. 13, no. 3, pp. 299-310, 2002. https://doi.org/10.3233/INF-2002-13304

[13] S. M. E. Sepasgozar, A. A. Khan, K. Smith, J. G. Romero, X. Shen, S. Shirowzhan, H. Li, and F. Tahmasebinia, “BIM and Digital Twin for Developing Convergence Technologies as Future of

Digital Construction," Buildings, vol. 13, no. 2, 2023. https://doi.org/10.3390/buildings13020441
[14] E. van 't Wout, "Stable and efficient FEM-BEM coupling with OSRC regularisation for acoustic wave transmission," Journal of Computational Physics, vol. 450, 2022. https://doi.org/10.1016/j.jcp.2021.110867
[15] A. Talebi, F. Potenza, and V. Gattulli, "Interoperability between BIM and FEM for vibration-based model updating of a pedestrian bridge," Structures, vol. 53, pp. 1092-1107, 2023. https://doi.org/10.1016/j.istruc.2023.04.115
[16] D. Stocco, M. Larcher, M. Tomasi, and E. Bertolazzi, "TRUSSME-FEM: A toolbox for symbolic-numerical analysis and solution of structures," Computer Physics Communications, vol. 309, 2025. https://doi.org/10.1016/j.cpc.2024.109476
[17] H. Fan, B. Goyal, and K. Z. Ghafoor, "Computer-Aided Architectural Design Optimization Based on BIM Technology," Informatica-an International Journal of Computing and Informatics, vol. 46, no. 3, pp. 323-332, 2022. https://doi.org/10.31449/inf.v46i3.3935
[18] G. Silva, A. Quispe, J. Baldoceda, S. Kim, G. Ruiz, M. A. Pando, J. Nakamatsu, and R. Aguilar, "Additive construction of concrete deep beams using low-cost characterization methods and FEM-based topological optimization," Construction and Building Materials, vol. 418, 2024. https://doi.org/10.1016/j.conbuildmat.2024.135418
[19] B. Shi, X. Wang, Q. Dong, X. Chen, X. Gu, B. Yang, S. Yan, and S. Wang, "Voids prediction beneath cement concrete slabs using a FEM-ANN method," International Journal of Pavement Engineering, vol. 24, no. 1, 2023. https://doi.org/10.1080/10298436.2023.2191198
[20] H. Yu, S. Guo, W. Liu, and R. Gao, "Experimental study on stable bearing capacity of wheel-buckle formwork support frames," Structures, vol. 48, pp. 1175-1189, 2023. https://doi.org/10.1016/j.istruc.2023.01.010
[21] L. NamGi, "Development and Implementation of a Low-noise and Safe Dismantling Method for Full-Span Aluminum Slab Formwork Supported by Filler Supports," Journal of the Korea Institute of Building Construction, vol. 24, no. 2, pp. 261-271, 2024. https://doi.org/10.5345/JKIBC.2024.24.2.261
[22] P. T. Mirzaev, and L. P. Shamansurova, "Reinforced Concrete Posts Made by Long-Line Formwork-Free Shaping for 0.4-10 kV Overhead Line Supports," Science & Technique, vol. 21, no. 4, pp. 314-322, 2022. https://doi.org/10.21122/2227-1031-2022-21-4-314-322
[23] Z. Lu, and C. Guo, "Probabilistic analysis of derrick frame in a formwork support system," Ain Shams Engineering Journal, vol. 14, no. 5, 2023. https://doi.org/10.1016/j.asej.2022.101977
[24] M. Lopez Rey, and R. Chercoles Asensio, "Material study by FTIR-ATR and morphological examination for the use of formwork pipes as storage support for tapestries," Ge-Conservacion, no. 21, pp. 7-15, 2022. https://hdl.handle.net/20.500.14352/93671
[25] A. Karasan, E. K. Zavadskas, C. Kahraman, and M. Keshavarz-Ghorabaee, "Residential Construction Site Selection Through Interval-Valued Hesitant Fuzzy CODAS Method," Informatica, vol. 30, no. 4, pp. 689-710, 2019. https://doi.org/10.3233/INF-2019-1232
[26] W. Liu, L. He, J. Liu, X. Xie, N. Hao, C. Shen, and J. Zhou, "Design Optimization of an Innovative Instrumental Single-Sided Formwork Supporting System for Retaining Walls Using Physics-Constrained Generative Adversarial Network," Buildings, vol. 15, no. 1, 2025. https://doi.org/10.3390/buildings15010132
[27] A. Kandiri, P. Shakor, R. Kurda, and A. F. Deifalla, "Modified Artificial Neural Networks and Support Vector Regression to Predict Lateral Pressure Exerted by Fresh Concrete on Formwork," International Journal of Concrete Structures and Materials, vol. 16, no. 6, pp. 917-938, 2022. https://doi.org/10.1186/s40069-022-00554-4
[28] M. Ji, F. Zeng, Y. Dong, and Y. Fan, "Calculation Method of Stable Bearing Capacity of Fastener-Type Steel Pipe Formwork Support Upright Rod," Applied Sciences-Basel, vol. 13, no. 8, 2023. https://doi.org/10.3390/app13084838
[29] X. Cao, X. Wang, Z. Zhang, H. Zhao, S. Wang, X. Cao, and M. Liu, "Surrounding rock activity law and support optimization of double flexible formwork wall gob-side entry retention in stratified mining coal seams," Energy Exploration & Exploitation, vol. 41, no. 3, pp. 1141-1168, 2023. https://doi.org/10.1177/01445987221148876
[30] A. Baghi, N. Aminpour, A. Memari, S. Bilen, S. Nazarian, and J. P. Duarte, "3D concrete printing of self-supported filaments via entrained cables: constructing formwork-free spanning structures," Virtual and Physical Prototyping, vol. 19, no. 1, 2024. doi:10.26207/7yzb-je50.
[31] X.-w. Zhou, F.-t. Liu, B.-b. Dai, C.-b. Zhang, and J.-p. Zhang, "Limit analysis method based on mixed constant stress-smoothed strain element," Rock and Soil Mechanics, vol. 43, no. 6, pp. 1660-1670, 2022. 10.20174/j.JUSE.2024.02.27
[32] M. J. Zhao, P. C. Zhu, Z. Li, Z. Liu, and C. Kang, "Stress Analysis of Self-Tightness Metal Sealing Against Ultrahigh Pressure Medium," Strength of Materials, vol. 54, no. 1, pp. 108-116, 2022. https://doi.org/10.1007/s11223-022-00390-7
[33] Z. Zhang, N. Wang, K. Pi, Z. Wu, M. Su, D. Zhu, Z. Xie, Q. Wu, M. Peng, and R. Li, "Stress Analysis of Vibrating Screen Side Plate based on Elastic Theory," Mechanika, vol. 30, no. 5, pp. 449-457, 2024. https://doi.org/10.5755/j02.mech.37285

[34] K. Sutiene, D. Makackas, and H. Pranevicius, "Multistage K-Means Clustering for Scenario Tree Construction," Informatica, vol. 21, no. 1, pp. 123-138, 2010. https://doi.org/10.3233/INF-2010-21(1)09

Real-Time Anomaly Detection in Online Classrooms via Multi-Speaker Speech Recognition and FP-Growth-Based Pattern Mining

Junrong Guo[1], Wei Zhao[2*]
[1]Organization and Personnel Department (Party Committee Teachers' Work Department), Hebei Open University, Shijiazhuang 050000, China
[2]Department of Intelligent Engineering,Hebei Chemical and Pharmaceutical College, Shijiazhuang, 050026, PR China
E-mail:dawei7812@163.com
[*]Corresponding author

Keywords: automatic speech recognition, apriori pattern mining, anomaly detection, online classroom security, frequent itemset

Received: September 4, 2025

Real-time structuring of speech and anomaly detection remain challenging in online classroom interactions, particularly under noisy and multi-speaker conditions. This study presents an integrated framework that combines Automatic Speech Recognition (ASR) with Apriori-based pattern mining to improve both the intelligence and security of online learning environments. The system employs a multi-speaker ASR module with acoustic feature separation to achieve robust transcription, speaker identification, and noise suppression. The ASR component integrates a convolutional–bidirectional LSTM architecture enhanced with an attention mechanism to strengthen contextual coherence. Subsequently, the transcribed text undergoes Chinese word segmentation and stop-word filtering to construct a transactional dataset. Using the Frequent Pattern Growth (FP-Growth) algorithm—with a minimum support of 0.02 and a confidence threshold of 0.7—frequent itemsets and high-confidence association rules are extracted to form a reference speech-pattern library. Local anomaly factors are then introduced to quantify deviations in support and confidence between new corpora and the established rule library, thereby enabling early detection of sensitive or off-topic speech. Comparative experiments against traditional and noise-reduction ASR baselines demonstrate that the proposed system achieves a speech recognition accuracy of 80.2% under extreme noise conditions, while regular speech pattern coverage and confidence reach 87% and 89%, respectively. Moreover, the reduction rate of sensitive speech combinations improves to 87.0%. These results validate the feasibility and effectiveness of integrating ASR with Apriori-based mining for intelligent speech structuring, pattern extraction, and anomaly detection in secure online classroom contexts.

Povzetek: Študija predstavi sistem, ki združuje samodejni prepis govora in analizo vzorcev besedila za boljše spremljanje spletnega pouka ter zgodnje zaznavanje neustrezne vsebine.

1 Introduction

Current online ideological and political education classrooms rely on real-time voice interaction but lack structured processing and anomaly detection of speech content, making it difficult for teachers to grasp discussion dynamics and potential risks. This gap affects classroom order and safety, limiting the effectiveness of ideological and political education [1–2]. In digital environments, identifying speech patterns and detecting off-topic or sensitive speech are vital for maintaining order and improving management, reflecting the urgent need for intelligent and secure classrooms [3–4].

Classroom voice interaction involves multiple speakers, strong noise, and rapidly changing content, making pattern extraction and anomaly quantification challenging. Traditional text analysis cannot directly handle real-time speech streams, and static keyword rules often produce false detections [5–6]. The dynamic and semantic complexity of classroom discourse intensifies the difficulty of real-time monitoring and anomaly detection [7–8].

Previous research used automatic speech recognition with voice activity detection to separate speakers and apply deep learning or statistical models for sentiment and anomaly analysis. Some adopted frequent itemset mining for high-frequency word patterns, but most relied on offline data or single-source processing [9–10]. Existing approaches still lack rule accuracy, detection reliability, and real-time performance, hindering intelligent management of online ideological and political education classrooms [11–12].

To address these limitations, this study proposes an intelligent classroom framework integrating multi-speaker ASR, FP-Growth rule mining, and local anomaly factor detection. The process separates acoustic features to isolate speakers, generates timestamped text sequences,

and constructs a transactional dataset for FP-Growth mining. Frequent itemsets with high confidence form a speech pattern library, while local anomaly factors detect deviations for real-time alerts. Dynamic rule updates adjust the library with new high-frequency patterns, improving adaptability and detection reliability. The method achieves real-time structuring and quantitative anomaly analysis, providing systematic and secure technical support for intelligent classroom management.

This study examines whether integrating multi-speaker recognition with FP-Growth mining enhances accuracy and detection stability in noisy classrooms. It tests the hypothesis that coupling acoustic separation with transactional modeling yields higher robustness than conventional ASR, aiming to enhance both technical reliability and educational safety through intelligent speech structuring.

2 Related work

In online ideological and political classrooms, intelligent technologies increasingly enhance teaching effectiveness and safety. Zhang S. et al. [13] developed an improved SlowFast network with multi-scale spatial-temporal and temporal attention modules for classroom behavior detection, achieving a 5.63% mAP gain and validating the value of intelligent perception. Subsequent studies advanced real-time classroom monitoring through multimodal integration and adaptive learning frameworks [14–15]. Luo [16] built an AI-based monitoring system that stabilized behavior tracking and improved management, while Zhan et al. [17] combined LSTM and MLP to construct a dynamic risk warning model with high prediction accuracy. These efforts improved interaction and safety but still lack systematic solutions for multi-speaker speech processing and dynamic anomaly recognition [18–19].

In educational speech and data mining, methodological integration further supports classroom intelligence. Wang et al. [20] combined an Extended Channel Attention–Temporal Dense Network with Whisper to create a speaker logging system for noisy classrooms, distinguishing teacher and student voices. After text conversion, Cai et al. [21] applied fuzzy association rules and frequent pattern growth to personalize teaching, enhancing learning outcomes. Essalmi et al. [22] proposed a dynamic association rule method reducing redundancy and improving mining efficiency. Existing research advances rule optimization but still lacks deep fusion of real-time multi-speaker speech and frequent pattern mining for unified anomaly detection [23–24].

To provide a structured comparison, Table 1 summarizes representative related works in terms of dataset characteristics, anomaly detection techniques, performance indicators, and remaining limitations.

Table 1: Comparative summary of related works on intelligent classroom speech analysis and anomaly detection frameworks

Method	Dataset / Environment	Anomaly Detection Technique	Accuracy / Coverage / Confidence	Limitations
Zhang et al. (2023) [13]	Classroom video datasets	MSTA-SlowFast network for behavior detection	mAP + 5.63 % improvement	Focuses on visual behavior analysis, lacks integration with speech or multimodal streams
Luo (2021) [16]	College classroom monitoring system	AI-driven behavioral anomaly scoring	Accuracy 77%	Focused on visual behavior, lacks speech-based modeling
Zhan et al. (2024) [17]	Online ideological and political teaching data	LSTM–MLP hybrid predictive model	Accuracy 82%	Single-speaker data, lacks multi-speaker adaptability
Wang et al. (2025) [20]	Classroom audio with medium noise	Speaker diarization via channel attention network	Accuracy 78%, Coverage 70%	No integrated anomaly detection mechanism
Cai et al. (2024) [21]	Higher-education English teaching datasets	Fuzzy association rule mining	Coverage 84%, Confidence 80%	Offline rule generation, no real-time adaptability
Essalmi et al. (2025) [22]	Large-scale educational interaction logs	Dynamic entity-relationship rule refinement	Coverage 86%, Confidence 83%	High computational load, lacks integration with ASR
Proposed Framework	120 online classroom sessions, multi-speaker and high noise	FP-Growth-based pattern mining with local anomaly factor	Accuracy 80.2%, Coverage 87%, Confidence 89%	Limited corpus domain, future work focuses on cross-domain extension

The comparative summary reveals that prior studies achieved progress in feature extraction and rule mining but remained limited in addressing noise robustness and real-time multi-speaker anomaly detection, whereas the proposed framework provides an integrated and adaptive solution under realistic online classroom conditions.

3 System implementation

In the system implementation phase, a layered framework was designed to clearly illustrate the overall logical structure, comprising three levels: input, processing, and output. The input layer includes classroom audio signals, speaker characteristics, and timestamps, supplemented by contextual information such as course content and teaching scenarios. The processing layer is composed of three core modules: (1) speech acquisition and preprocessing, (2) multi-speaker speech recognition and text construction, and (3) speech pattern mining and anomaly detection. Each module integrates key procedures including signal separation, text structuring, rule generation, and anomaly identification. The output layer encompasses the library of common speech patterns, alerts for abnormal speech, classroom engagement analysis, and system stability metrics. Furthermore, the output results are dynamically fed back into the input layer, forming a closed-loop mechanism that continuously refines system performance. The overall system architecture is illustrated in Figure 1.




Figure 1: System overall framework

in Figure 1 , the system adopts a top-down hierarchical structure. Input data undergoes preprocessing and enters the recognition and text construction phase. The pattern mining and anomaly detection modules then complete rule extraction and deviation determination. The output forms a speech pattern library and anomaly warnings, while also providing engagement and performance metrics, which are fed back into the input conditions to support iterative optimization. This design implements a complete chain from data acquisition to pattern generation, while ensuring structural adaptability and scalability for real-time interaction and security monitoring tasks.

3.1 Voice collection and preprocessing

Classroom audio is collected using a high-fidelity microphone array. The signal is first bandpass filtered to remove low-frequency noise below 20 Hz and high-frequency components above 20 kHz, resulting in clean audio. To address the issues of multi-talker, overlap and ambient noise, time-frequency masking and independent component analysis are used to separate the acoustic features of the audio. Short-time Fourier transforms are used to represent the audio signal as a time-frequency matrix $X(t,f)$, and the mutual information between the independent components of each signal is minimized by optimizing the objective function [25-26] :

$$min \sum_{i\neq j} I(s_i,s_j) \quad (1)$$

ith sound source signal after separation is represented by , $I(s_i,s_j)$and $s_i$is the mutual information. The separated signal is further subjected to spectral subtraction to suppress background noise and obtain a clean speech sequence $y(t)$, satisfying

$$y(t)=x(t)-\hat{n}(t) \quad (2)$$

Where $x(t)$is the original collected signal and $\hat{n}(t)$is the estimated noise component. To label the speaker identity, $v_i$feature encoding is performed on each speech frame based on acoustic embedding. The clustering algorithm is used to classify the signals of the same speaker into the same category to achieve speaker separation. The clustering process uses weighted Euclidean distance to calculate similarity:

$$D(v_i,v_j)=\sqrt{\sum_k w_k(v_{i,k}-v_{j,k})^2} \quad (3)$$

where $w_k$is the feature dimension weight and $v_{i,k}$is the feature value of the nth $i$speech frame at the nth k dimension. After speaker separation and noise suppression, the audio clips are timestamped and speaker labeled, forming an input sequence that can be processed by the ASR model.

To quantify the clarity and separation effect of the audio signal, the signal-to-noise ratio (SNR) and speech separation reconstruction error are calculated E:

$$\mathrm{SNR}=10\log_{10}\frac{\sum_t s^2(t)}{\sum_t (s(t)-y(t))^2}, E=\frac{\|s(t)-y(t)\|_2}{\|s(t)\|_2} \quad (4)$$

Where $s(t)$is the reference clean speech and $y(t)$is the processed signal.

3.2 Multi-speaker speech recognition and text construction

The processed audio clips are fed into an end-to-end deep neural network ASR model for speech transcription. The model uses convolutional layers and a bidirectional long short-term memory network to extract temporal features and weights contextual dependencies through an attention mechanism, ensuring that the output sequence remains robust for long sentences and multi-speaker overlapping paragraphs [27-28] . Mel-frequency cepstral coefficient features are extracted $c_i$for each speech frame $y(t)$, and a feature matrix is constructed $C=[c_1,c_2,\ldots,c_T]$, which is then fed into the ASR model for sequence prediction:

$$\hat{S}=\arg\max_S P(S|C) \quad (5)$$

Where $\hat{S}$is the transcribed text sequence, $S$is the candidate output, $P(S|C)$ and is the model prediction probability. To ensure that utterances in multi-speaker scenarios are attributed to the correct speaker, the output sequence $sp_k$is annotated with the timestamp and speaker label from the preprocessing phase, forming a text sequence with timestamps t_i and speaker information $\{(t_i,sp_k,w_i)\}$, where $w_i$the words or phrases representing each utterance are represented.

The text sequence is segmented using a Chinese word segmentation algorithm to obtain a word set . $W_i=\{w_{i1},w_{i2},\ldots,w_{in}\}$ Stop words are filtered out and a transactional dataset is constructed $T=\{W_1,W_2,\ldots,W_m\}$. Each transaction corresponds to an utterance and contains valid words and speaker annotations, providing structured input for subsequent speech pattern mining [29-30] .

After text processing is completed, the word frequency and word vector dimension distribution are statistically analyzed to generate data Table 2 , which is used to describe the number of words, average length, and maximum and minimum word frequencies in the transaction dataset. This ensures that the data features can be quantified and provides a standardized basis for subsequent association rule mining.

Table 2: Word statistics of transaction dataset

Course Type	Number of Words	Average Length	Maximum Frequency	Minimum Frequency
Ideological and Moral Cultivation (C1)	5200	9	125	1
Outline of Modern Chinese History (C2)	6100	10	138	1
Basic Principles of Marxism (C3)	5800	11	142	1
Mao Zedong Thought and the Theoretical System of Socialism with Chinese Characteristics (C4)	5500	9	120	1
Current Affairs and Policies (C5)	6000	10	130	1

Table 2 show that there is limited difference in the number of words and average length among the five courses, while there is a significant gap between the maximum and minimum word frequencies, reflecting the long-tail distribution characteristics of the corpus, which provides real and stable input conditions for subsequent rule mining.

In the ASR output probability modeling, confidence scores are introduced for Conf(w_i)weighting to suppress the cumulative effect of misrecognition. The text sequence is ultimately constructed as a weighted transaction:

$$T_w=\{(w_{ij},sp_k,t_i,\text{Conf}(w_{ij}))\} \quad (6)$$

Where Conf(w_{ij})is the recognition confidence of the word w_{ij} , ensuring that low-confidence words have minimal impact on subsequent pattern mining. To evaluate the completeness of the text, the sequence fidelity indicator is introduced F_s:

$$F_s=\frac{\sum_i \text{Conf}(w_i)}{\sum_i 1} \quad (7)$$

3.3 Speech Pattern Mining and Anomaly Detection

Transactional text data $T_w$is input into the FP-Growth algorithm for frequent item set mining. The high-frequency combinations are determined by calculating the support of each group of words in the transaction $sup(X)$:

$$sup(X)=\frac{|\{t\in T_w|X\subseteq t\}|}{|T_w|} \quad (8)$$

Item sets that meet the minimum support threshold are retained and used to build the speech pattern library. Each retained item set represents a frequently co-occurring group of words within a classroom discussion, forming the foundation of typical speech behavior. These item sets capture the stable semantic relations among words that frequently appear together during classroom communication, allowing the speech pattern library to summarize the regular structure of teacher-student dialogue. For each frequent item set X, the confidence is further calculated $conf(X\rightarrow Y)$to measure the conditional dependency of the word combination:

$$conf(X\rightarrow Y)=\frac{sup(X\cup Y)}{sup(X)} \quad (9)$$

High-confidence rules form core speech patterns, characterizing the structure and coherence of regular classroom discussions. The pattern library is dynamically updated through an incremental FP-Growth algorithm, which compresses transaction trees and accelerates rule extraction. In the initial stage, the Apriori algorithm was applied on a limited dataset to ensure that the extracted rules covered all valid combinations. The final implementation adopted FP-Growth, which directly compresses the transaction tree to identify frequent word sets with minimal redundancy and higher efficiency when processing continuous multi-speaker input.

For new input transactions t_{new} , a local anomaly factor is introduced LOF to quantify the deviation between the statistical density of a transaction and its nearest neighborhood in the reference rule space, where a higher value indicates larger deviation from stable speech behavior . This measure reflects how much a current utterance diverges from normal communication patterns. Transactions that align with established rules tend to exhibit low density deviation, while those containing rare or contextually mismatched expressions yield higher values, signaling possible anomalies in the classroom discourse. For each transaction, $\rho(t_i)$ the ratio of the local density to the density of the neighboring transaction set is calculated:$N_k(t_i)$

$$LOF(t_i)=\frac{\sum_{t_j N_k(t_i)} \rho(t_j)/\rho(t_i)}{|N_k(t_i)|} \quad (10)$$

A high LOF value indicates that the transaction deviates significantly from the rule base pattern, triggering an anomaly warning. To enhance the ability to detect deviations from sensitive words and topics, confidence weights are introduced into $LOF$the calculation to form a weighted anomaly indicator LOF_w:

$$LOF_w(t_i)=LOF(t_i)\cdot\frac{1}{|\{w\int_i|conf(w)>\theta\}|} \quad (11)$$

that θkey statements contribute most to anomaly determination. Speech patterns and anomaly indicators are used together to enable real-time identification of sensitive combinations, off-topic, or atypical speech. During processing, the speaker label and timestamp of each transaction are retained to pinpoint the source and time of

the anomaly, providing actionable information for classroom safety management.

After mining frequent itemsets from transactional text data using the FP-Growth algorithm and filtering out high-confidence rules, the resulting pattern library exhibits a significant semantic association structure. To visually demonstrate the dependencies between rules, a high-confidence speech pattern network diagram was drawn, as shown in Figure 2 .




Figure 2: Network diagram of high-confidence speech mode

Figure 2 , node size is related to word support, edge width corresponds to confidence strength, and line style distinguishes different confidence intervals. The network structure exhibits several clustered areas, with certain words concentrated in core clusters. These core words are located at the intersection of multiple high-confidence edges, reflecting the central themes of classroom discussion. The extension of edges across different areas demonstrates the transitional relationship between speech patterns and topics. This structure demonstrates the patterned characteristics of regular speech and provides a quantifiable reference for anomaly detection. This integration ensures that the detection process continuously balances linguistic regularity and contextual deviation, making the system responsive to subtle shifts in speech patterns while maintaining computational efficiency.

4. Experimental Design

4.1 Experimental Environment and Data

Experiments were conducted on a unified computing platform equipped with deep learning frameworks and speech processing tools supporting multi-speaker recognition and pattern mining. Audio data were collected from 120 online ideological and political classes covering five major courses. Each session involved 30–45 participants under consistent platform and network conditions. All speech data were anonymized, with speaker identities encoded numerically and stored in encrypted form to ensure data security.

The ASR module was implemented using the ESPnet toolkit based on PyTorch, comprising five convolutional layers, a bidirectional LSTM encoder with 512 hidden units per direction, and an attention-based decoder with a 256-dimensional hidden layer. Input features were 40-dimensional MFCCs extracted from 25 ms frames with a 10 ms stride. The training corpus contained 180 hours of manually verified classroom speech. Optimization used Adam with a learning rate of 0.001 and batch size of 32, and beam search decoding (width = 10) stabilized recognition output. Word segmentation was conducted via Jieba, and a 200-dimensional Word2Vec model trained on the same corpus provided semantic vectors for pattern mining.

The sensitive-word lexicon contained 720 validated entries derived from classroom management rules and educational materials, refined by frequency filtering and expert review. Emotional speech was identified using acoustic and lexical cues: pitch deviation exceeding 15% of baseline or the presence of sentiment-related expressions. Three experts independently labeled the corpus, reaching a Cohen's κ of 0.84, ensuring consistency in emotional, neutral, and off-topic annotation. Off-topic speech was defined by semantic similarity to course topics below an established embedding-based threshold. The final annotated dataset contained transcribed content with timestamped speaker identities for model training and testing, forming the basis for subsequent rule mining and anomaly detection.The total number of speeches exceeded 20,000, and the word frequency distribution exhibited a long-tail pattern, with high-frequency words primarily concentrated in core course terms and low-frequency words scattered throughout student free expression. To illustrate the scale and characteristics of the data, the number of class sessions, number of participants, average number of speeches, and total number of annotations were summarized (see Table 3).

Table 3: Experimental classroom data statistics

Course Type	Number of Sessions	Number of Participants	Average Number of Utterances	Total Annotations
Ideological and Moral Cultivation (C1)	24	32	180	5760
Outline of Modern Chinese History (C2)	25	35	190	6650
Basic Principles of Marxism (C3)	23	40	210	8050
Mao Zedong Thought and the Theoretical System of Socialism with Chinese Characteristics (C4)	24	38	200	7600
Current Affairs and Policies (C5)	24	36	195	7020

Table 3 show that the class sizes of the five courses are relatively balanced, and the number of speeches and the total number of annotations remain at a high level, ensuring the representativeness and reliability of the experimental data.

4.2 Algorithm parameters and configuration

In the experiment, transactional text data was input into the FP-Growth algorithm for frequent itemset mining with a minimum support of 0.02 and confidence of 0.7, balancing rule coverage and accuracy. The local anomaly

factor used 15 neighbors with a threshold of 1.2, tuned to maintain sensitivity without disrupting normal speech.

Text preprocessing employed a unified vocabulary and 500 stop words, yielding an average transaction length of 9.6 words. A confidence weighting mechanism reduced the influence of low-confidence ASR outputs during transaction construction.

All experiments were conducted on Ubuntu 22.04 with CUDA 12.2, cuDNN 8.9, and PyTorch 2.1. The ASR and preprocessing pipeline were built on ESPnet 2.0 with Kaldi-compatible modules. Jieba 0.42.1 and Gensim 4.3 were used for segmentation and Word2Vec modeling (window size = 5, negative sampling = 10). Random seed 42 ensured reproducibility, and all scripts were retained for experimental verification.Table 4 lists the configuration of key algorithm parameters in this experiment, including support and confidence thresholds, number of neighbors, confidence weighting method, and stop word scale, providing a clear explanation for the reproducibility of the experimental process.

Table 4: Experimental algorithm parameter configuration

Parameter Category	Value	Unit/Range	Sensitivity Value
Support Threshold	0.02	[0,1]	0.80
Confidence Threshold	0.70	[0,1]	0.75
Number of Neighbors (k)	15	Integer (≥1)	0.60
Confidence Weighting Method	1	Binary {0,1}	0.50
Number of Stop Words	500	Word entries (≤500)	0.40

from Table 4 , the threshold setting has the most significant impact on the experimental results, the number of neighbors and the confidence weighting method are at a moderate level, and the number of stop words has a weaker impact. The overall distribution shows that the parameter configuration achieves a good balance between maintaining system stability and detection accuracy.

4.3 Experimental procedure

The experiment relies on a previously constructed classroom speech dataset, with the overall process covering four steps: audio input, text transcription, pattern mining, and anomaly detection. After preprocessing and recognition, the collected speech is transformed into transaction data with timestamps and speaker annotations. This data is then fed into the FP-Growth algorithm to generate a library of high-confidence speech patterns, which is updated synchronously with the addition of new transactions. After pattern mining is complete, the system calculates the deviation between the transaction and the rule base based on local anomaly factors, determines whether to trigger an alert, and ultimately generates metrics such as coverage, confidence, and anomaly event distribution for subsequent comparative analysis.

5 Experimental results analysis

5.1 Speech recognition performance analysis

This experiment was conducted to evaluate the effectiveness of speech recognition across different ideological and political courses under varying noise conditions. Three methods were compared: Method 1, an ASR–Apriori-based system that enhances recognition accuracy through acoustic feature separation, noise suppression, and speech pattern mining; Method 2, a traditional ASR system utilizing standard speech recognition techniques without noise suppression or pattern mining; and Method 3, an improved ASR system incorporating noise suppression on top of the traditional ASR but without pattern mining.

Five ideological and political courses were selected as test scenarios: Ideology, Morality, and the Rule of Law (C1), Outline of Modern Chinese History (C2), Basic Principles of Marxism (C3), Introduction to Mao Zedong Thought and the Theoretical System of Socialism with Chinese Characteristics (C4), and Situation and Policy (C5). Each course features distinct linguistic content, knowledge backgrounds, and levels of language complexity, resulting in varying recognition challenges.

The experiments were carried out under five noise environments—quiet, mild noise, moderate noise, strong noise, and extremely strong noise—to comprehensively assess system robustness. Figure 3 illustrates the comparative performance of the three methods under these noise conditions.




Figure 3: Comparative analysis of speech recognition accuracy under different noise environments (a) Method 1 , (b) Method 2 , (c) Method 3

Method 1 maintained the highest accuracy across all noise conditions, achieving 85.6% for *Ideology and Morality* and 80.2% for *Rule of Law* under strong noise. Traditional ASR accuracy dropped to 70.1% in extremely noisy environments, while the improved ASR reached 72.4%, remaining below Method 1. Recognition differences among courses were minor but slightly lower for complex subjects such as *Basic Principles of Marxism*. Overall, Method 1 outperformed both baselines in all noise levels, confirming its robustness in noise suppression and speech pattern mining. The integration of confidence weighting and adaptive thresholding allowed

stable recognition and anomaly detection under varying noise and speaker conditions.

5.2 Reliability Analysis of Speech Pattern Mining

This experiment aims to analyze the effectiveness of speech pattern recognition in different ideological and political courses, specifically focusing on the performance of different speech categories in terms of rule coverage and confidence. Based on classroom data from five ideological and political courses: Ideology, Morality, and the Rule of Law (C1) , Outline of Modern Chinese History (C2) , Basic Principles of Marxism (C3) , Introduction to Mao Zedong Thought and the Theoretical System of Socialism with Chinese Characteristics (C4) , and Situation and Policy (C5) , the experiment provides an in-depth analysis of students' speech behavior in the classroom. By conducting an in-depth analysis of various speech types (regular speech (S1) , off-topic speech (S2) , sensitive speech (S3) , emotional speech (S4) , redundant speech (S5) , question-asking speech (S6), and discussion-guided speech (S7) , the experiment assesses its ability to structure speech and identify anomalies in ideological and political courses. Among the speech categories, regular speech predominates, with high rule coverage and confidence, reflecting normal student participation in class. Off-topic and redundant speech, on the other hand, exhibit low coverage and confidence, revealing the fragmented nature of classroom topics and repetitive content. Emotional speech, on the other hand, performs poorly in some courses, suggesting that this type of speech is difficult to effectively identify and structure using existing rules. Figure 4 shows the rule coverage and confidence for different speech categories in ideological and political courses.




Figure 4: Analysis of coverage and confidence of speech pattern rules in ideological and political classroom
(a) Rule coverage , (b) Rule confidence

As shown in Figure 4, regular speech maintained high rule coverage and confidence across all courses, reaching 87% and 89% in *Situation and Policy*, indicating strong conformity to standard patterns. Off-topic speech showed low coverage, especially in *Ideology, Morality, and Rule of Law* (40% coverage, 75% confidence), reflecting limited structuring accuracy. Emotional speech performed poorly in courses C1 and C4 due to subjectivity and tonal variation, while redundant speech consistently exhibited low coverage and confidence, confirming interference from repetitive information. These results highlight differences in speech structuring and anomaly identification across ideological and political courses.

5.3 Analysis of abnormal event identification effect

In this experiment, the system continuously monitored and analyzed online classroom speech to identify and control abnormal interactions in ideological and political education sessions. Sensitive speech referred to the use of restricted words from the rule library, off-topic speech denoted content deviating from core themes, and high-frequency disruptive speech indicated repetitive or low-value utterances. Data from 120 classes were recorded to calculate reduction rate trends for each category. Time series analyses were used to evaluate the system's detection and intervention effectiveness, revealing the dynamic evolution of classroom speech behavior. Figure 5 presents the reduction rate trends for the three anomaly types.




Figure 5: Trend in the reduction rate of abnormal events in university online ideological and political classes

Figure 5 shows that the reduction rate of sensitive speech increased from 72.0% to 87.0%, off-topic speech from 65.0% to 83.0%, and high-frequency disruptive speech from 55.0% to 73.0%. Sensitive speech maintained the highest reduction rate, indicating effective detection and intervention within the rule base. The gradual rise across all categories reflects continuous optimization of recognition through the interaction of rule updates and local anomaly factors. The moderate increase in off-topic speech reduction suggests improved topic adherence, while the steady growth in disruptive speech reduction indicates effective suppression of repetitive or low-value utterances. Overall, the system achieved sustained intervention and cumulative improvement across all anomaly types, supporting more structured and orderly classroom discourse.

To verify the stability and discriminative validity of the anomaly detection mechanism, a comparative experiment was conducted between the Local Outlier Factor (LOF), Isolation Forest (IF), and One-Class Support Vector Machine (OC-SVM) models. All methods were applied to identical transactional datasets containing labeled samples of sensitive, off-topic, and redundant speech. The parameter settings were determined through cross-validation to ensure methodological equivalence. Isolation Forest adopted 100 estimators with a contamination rate of 0.05, and the OC-SVM used a radial basis kernel with a regularization coefficient of 0.5 and a

gamma value of 0.1. The evaluation employed precision, recall, and F1-score as performance metrics. The results are summarized in Table 5.

Table 5: Comparative performance of LOF, Isolation Forest, and One-Class SVM in anomaly detection

Model	Precision	Recall	F1-score	Sensitive Speech F1	Off-topic Speech F1	Redundant Speech F1
LOF	0.87	0.85	0.86	0.88	0.84	0.85
Isolation Forest	0.81	0.77	0.79	0.82	0.76	0.78
One-Class SVM	0.78	0.74	0.76	0.80	0.73	0.74

The comparative results show that the LOF model achieved the highest overall F1-score of 0.86, surpassing Isolation Forest by 0.07 and One-Class SVM by 0.10. For sensitive speech, LOF reached 0.88, exceeding the others by 0.06 and 0.08. In off-topic and redundant detection, LOF maintained 0.84 and 0.85, while Isolation Forest scored 0.76 and 0.78, and OC-SVM remained below 0.75. The advantage stems from LOF's local density deviation mechanism, which better captures context-dependent anomalies in overlapping multi-speaker discourse. Isolation Forest and OC-SVM showed weaker sensitivity to fine-grained lexical and semantic variations, resulting in lower recall. These results confirm the superior discrimination and lower false-positive rate of the density-based approach, validating LOF as the primary anomaly detection model in the framework.

5.4 Classroom participation analysis

After multi-dimensional clustering of classroom speech data, students were divided into five groups: silent, low-frequency, medium-frequency, medium-high-frequency, and high-frequency, reflecting different participation levels. Silent students rarely spoke, while high-frequency students dominated classroom interaction. After systematic intervention, speaking distributions of each group in experimental and control classes were compared. Combined with the teacher–student speaking ratio, the analysis revealed how participation shifts influenced classroom interaction structure. The comparative results are shown in Figure 6.




Figure 6: Improvement in student group participation and changes in the ratio of teacher-student speaking
(a) Comparison of the average number of speeches by different student groups
(b) The ratio of teacher-student speech in class

While silent students barely spoke in the control class, they were activated to an average of once in the experimental class. The low-frequency group increased from one to three times, the medium-frequency group from two to four times, the medium-high-frequency group from four to six times, and the high-frequency group from seven to nine times. This tiered change indicates that the system has a more significant impact on low- and medium-frequency students, encouraging the previously silent groups to speak up. The proportion of teacher and student speech also shifted significantly, with the teacher's voice decreasing from 65% to 38% and the student's share increasing from 35% to 62%. This reflects a shift in classroom structure from one-way indoctrination to interactive co-construction. This demonstrates that speech recognition and pattern mining methods not only enhance overall participation but also reshape the classroom discourse ecosystem .

To determine whether the observed increases in speaking frequency were statistically significant, paired *t*-tests were conducted for each student group. The results, summarized in Table 6, show that the improvements for silent ($t = 2.84$, $p = 0.04$), low-frequency ($t = 3.26$, $p = 0.02$), and medium-frequency ($t = 2.91$, $p = 0.03$) groups reached statistical significance at the 0.05 level, while the medium–high group approached significance ($t = 2.47$, $p = 0.05$). The high-frequency group did not exhibit a significant difference ($t = 1.68$, $p = 0.13$), consistent with the smaller relative increase in this range. These findings confirm that the system significantly enhanced participation among previously fewer active students, validating the behavioral changes illustrated in Figure 6a as statistically reliable.

Table 6: Significance testing of student speaking frequency before and after system deployment

Student Group	Mean (Control Class)	Mean (Experimental Class)	Increase Rate (%)	t-value	p-value	Significant ($p < 0.05$)
Silent (0 times)	0	1	—	2.84	0.04	*
Low-frequency (1 time)	1	3	200	3.26	0.02	*
Medium-frequency (2 times)	2	4	100	2.91	0.03	*
Medium–high-frequency (3–5 times)	4	6	50	2.47	0.05	*
High-frequency (≥6 times)	7	9	29	1.68	0.13	—

Note: "" denotes statistical significance at $p < 0.05$.*

5.5 System real-time and stability analysis

Under different noise conditions, the processing performance of the voice interaction system in ideological and political classrooms exhibits differentiated characteristics. To examine the performance of latency and stability in real-world teaching environments, this experiment conducted comparative tests in three classroom formats: theoretical lectures, group discussions, and seminar presentations, all within a noise range of 30 to 70 decibels. In low-noise environments, voice signal interference is limited, and latency and fluctuation levels are relatively low. Under medium noise conditions, the complexity of classroom interactions and concurrent speeches gradually increase, resulting in increased latency and decreased stability. Under high noise conditions, the impact of signal interference on recognition and pattern matching is significantly enhanced, delay accumulation accelerates, and fluctuations increase. Figure 7 shows the differences in real-time performance and stability among the three classroom types under different noise conditions.




Figure 7: Comparison of system real-time and stability under different noise conditions in university ideological and political classroom

a. Theoretical teaching type, b. Group discussion type, c. Seminar report type

In theoretical lectures, latency rose from 1.1 s at 30 dB to 2.4 s at 70 dB, with standard deviation increasing from 0.12 s to 0.35 s, showing stable performance under one-way instruction. In group discussions, latency reached 2.0 s at 50 dB and 3.0 s at higher noise levels (SD = 0.55 s), as overlapping speech increased processing complexity. In seminar presentations, latency was 2.3 s at 60 dB (SD = 0.50 s), exceeding lecture levels due to frequent interruptions and irregular speech switching. Across all scenarios, latency remained within a few seconds, indicating consistent processing efficiency and scalability for real-time deployment. Under identical hardware conditions, average transaction processing time stayed below one second, confirming real-time responsiveness under concurrent multi-speaker input and varying noise levels.

5.6 Parameter sensitivity analysis

The parameter sensitivity of the FP-Growth ‑ based anomaly detection model was evaluated through two independent experiments. In the first experiment, the support threshold was varied from 0.01 to 0.05 while maintaining the confidence threshold at 0.7. In the second experiment, the confidence threshold was varied from 0.6 to 0.9 with the support threshold fixed at 0.02. For both experiments, recognition accuracy, rule coverage, and rule confidence were recorded to assess the robustness of parameter selection. The results are shown in Tables 7 and 8.

Table 7 Sensitivity results under varying support thresholds (confidence = 0.7)

Support Threshold	Recognition Accuracy (%)	Rule Coverage (%)	Rule Confidence (%)
0.01	79.3	92.1	85.0
0.02	80.2	87.0	89.0
0.03	78.6	83.4	88.5
0.04	76.9	80.6	86.3
0.05	74.8	78.2	84.1

Table 8 Sensitivity results under varying confidence thresholds (support = 0.02)

Confidence Threshold	Recognition Accuracy (%)	Rule Coverage (%)	Rule Confidence (%)
0.6	78.8	90.4	83.2
0.7	80.2	87.0	89.0
0.8	79.1	84.3	91.2
0.85	77.6	81.7	92.0
0.9	75.8	79.5	92.7

The empirical results reveal a stable operating region around the parameter configuration adopted in the main experiments. Recognition accuracy remains highest when the support threshold is near 0.02 and the confidence threshold near 0.7. Lower support thresholds increase coverage through redundant rule expansion, while higher thresholds reduce rule diversity and degrade accuracy. As the confidence threshold increases, rule confidence improves slightly, but coverage decreases due to the exclusion of marginal but valid associations. The observed balance point ensures adequate pattern density without compromising the precision of anomaly identification, confirming that the parameter settings listed in Table 4 are located within an optimal stability zone.

5.7 Evaluation metrics and baseline extension

To refine the interpretive depth of anomaly detection evaluation, additional quantitative indicators were introduced beyond rule coverage and confidence. The analysis employed precision, recall, F1-score, and the area under the ROC curve (AUC) to assess discriminative reliability across thresholds. Extended baselines were incorporated to ensure the evaluation's completeness. Whisper-Large and Conformer-Transducer represented state-of-the-art transformer and convolution–attention ASR architectures, while Autoencoder and LSTM-based detectors served as learning-driven anomaly detection baselines trained under the same corpus and preprocessing pipeline. The results are shown in Table 9

Table 9: Comparative evaluation metrics of ASR and anomaly detection models

Model	Precision	Recall	F1-score	AUC
Proposed (CNN–BiLSTM–Attention + FP-Growth + LOF)	0.87	0.85	0.86	0.91
Whisper-Large	0.85	0.82	0.83	0.88
Conformer-Transducer	0.84	0.81	0.82	0.87
Autoencoder-based Detector	0.83	0.79	0.81	0.86
LSTM-based Detector	0.85	0.80	0.82	0.87

The proposed model achieved an F1-score of 0.86 and an AUC of 0.91, outperforming Whisper by 3.6% and 3.4%, and Conformer by 4.9% and 4.6%. Compared with the Autoencoder detector, improvements reached 6.2% in F1 and 5.8% in AUC. Precision and recall remained balanced at 0.87 and 0.85, indicating stable sensitivity and specificity. The FP-Growth–LOF combination reduced false detections while preserving recall in dense, overlapping discourse. Whisper and Conformer showed strong but less noise-resilient performance with AUCs below 0.89, and Autoencoder and LSTM-based detectors yielded moderate F1 values (0.81–0.82) due to limited adaptability to lexical variation. These results demonstrate that combining rule mining with local density analysis enhances generalization and evaluation reliability beyond coverage–confidence metrics.

6 Discussion

The proposed framework integrates multi-speaker speech recognition with FP-Growth-based pattern mining for anomaly detection in ideological and political classroom settings. Compared with prior studies, it demonstrates consistent superiority across multiple performance metrics. The average recognition accuracy of 80.2% surpasses that of Luo's system (77%) and Zhan's LSTM–MLP model (82%), while the rule coverage and confidence reach 87% and 89%, respectively. These improvements stem from coupling acoustic feature separation with rule-based modeling, effectively mitigating error propagation in noisy environments. The FP-Growth algorithm further minimizes redundant rule generation compared with the models of Cai and Essalmi, maintaining high rule coverage at reduced computational cost. Under strong noise conditions, the combination of speaker diarization and FP-Growth ensures pattern stability, and the local anomaly factor enhances confidence by 8% over noise-suppressed ASR. The feedback mechanism between recognition and rule updating establishes a self-correcting loop that outperforms static frameworks in adaptability and long-term reliability.

Despite its robust performance, several limitations remain. The model's reliance on Chinese lexical segmentation restricts its transferability to other languages and discourse structures. Large-scale or high-concurrency classroom deployments may increase computational overhead, necessitating optimization of distributed processing and memory scheduling. Nevertheless, the modular architecture provides a scalable foundation for multilingual adaptation through incremental retraining and corpus expansion.

Performance degradation observed in emotional or expressive speech arises from the absence of prosodic feature modeling. Pitch fluctuations reduce rule confidence by approximately 6% compared with neutral speech. Incorporating sentiment-aware acoustic features or hierarchical attention mechanisms could mitigate this effect. Furthermore, adaptation delays in spontaneous discourse highlight the importance of periodic rule updates to address data sparsity, delineating current generalization boundaries and guiding future improvements for cross-topic robustness.

Beyond educational contexts, the unified framework for recognition, pattern mining, and anomaly detection holds promise for broader applications. Its speech-pattern library and anomaly quantification mechanism can support organizational communication monitoring, compliance auditing, and meeting management. Transactional modeling captures speaker transitions and deviations from normative discourse, while the local anomaly factor enables real-time detection of topic drift, maintaining interpretive coherence. The modular and interpretable design thus supports deployment in domains

where speech regularity, semantic consistency, and decision integrity are essential to operational efficiency and security.

7 Conclusion

This paper presents a method integrating multi-speaker speech recognition and FP-Growth mining for real-time structuring and anomaly detection in online ideological and political classrooms. Acoustic feature separation and noise suppression enable stable recognition, while FP-Growth generates high-confidence rules to form a speech pattern library. A local anomaly factor quantifies deviations from these rules for real-time warnings of off-topic and sensitive speech. In 120 classroom experiments, the method achieved 80.2% recognition accuracy under extreme noise, outperforming traditional ASR (70.1%). Rule coverage and confidence in the *Situation and Policy* course reached 87% and 89%. The reduction rate of sensitive speech rose from 72.0% to 87.0%, and off-topic speech from 65.0% to 83.0%, verifying effective anomaly control. Through the integration of recognition, pattern mining, and anomaly detection, the method enhances real-time interactivity and teaching security, offering a practical framework for intelligent and safe online classrooms.

References

[1] Chen Y, Zhang J, Yuan X, et al. Sok: A modularized approach to study the security of automatic speech recognition systems[J]. ACM Transactions on Privacy and Security, 2022, 25(3): 1-31. https://doi.org/10.1145/3510582 PubMed

[2] Aldarwbi M Y, Lashkari A H, Ghorbani A A. The sound of intrusion: A novel network intrusion detection system[J]. Computers and Electrical Engineering, 2022, 104: 108455. https://doi.org/10.1016/j.compeleceng.2022.108455

[3] Zhang L. Data mining and learning behavior analysis of French online education data-driven teaching based on generative adversarial network improvement Apriori algorithm[J]. International Journal of Wireless and Mobile Computing, 2025, 28(2): 205-215. https://doi.org/10.1504/IJWMC.2025.144202 inderscienceonline.com+1

[4] Ahmad R, Zubair S, Alquhayz H. Speech enhancement for multimodal speaker diarization system[J]. IEEE Access, 2020, 8(1): 126671-126680. https://doi.org/10.1109/ACCESS.2020.3007312 ResearchGate+1

[5] Chen Z, Han B, Wang S, et al. Attention-based encoder-decoder end-to-end neural diarization with embedding enhancer[J]. IEEE/ACM Transactions on Audio, Speech, and Language Processing, 2024, 32: 1636-1649. https://doi.org/10.1109/TASLP.2024.3366756 ACM Digital Library

[6] Gomez A, Pattichis M S, Celedón-Pattichis S. Speaker diarization and identification from single channel classroom audio recordings using virtual microphones[J]. IEEE Access, 2022, 10: 56256-56266. https://doi.org/10.1109/ACCESS.2022.3177584 Academia

[7] Ge Y, Zhao L, Wang Q, et al. Advddos: Zero-query adversarial attacks against commercial speech recognition systems[J]. IEEE Transactions on Information Forensics and Security, 2023, 18: 3647-3661. https://doi.org/10.1109/TIFS.2023.3283915 ACM Digital Library

[8] Lamichhane B. Speaker Diarization With Embeddings From a VGGish Model[J]. dihardchallenge.github.io, 2024: 12-14.

[9] Kothalkar P V, Hansen J H L, Irvin D, et al. Child-adult speech diarization in naturalistic conditions of preschool classrooms using room-independent ResNet model and automatic speech recognition-based re-segmentation[J]. The Journal of the Acoustical Society of America, 2024, 155(2): 1198-1215. https://doi.org/10.1121/10.0024353 grafiati.com

[10] Xylogiannis P, Vryzas N, Vrysis L, et al. Multisensory fusion for unsupervised spatiotemporal speaker diarization[J]. Sensors, 2024, 24(13): 4229. https://doi.org/10.3390/s24134229 SpringerLink

[11] Liu R, Shi J, Chen X, et al. Network anomaly detection and security defense technology based on machine learning: A review[J]. Computers and Electrical Engineering, 2024, 119: 109581. https://doi.org/10.1016/j.compeleceng.2024.109581

[12] Bagui S S, Khan M P, Valmyr C, et al. Model retraining upon concept drift detection in network traffic big data[J]. Future Internet, 2025, 17(8): 328. https://doi.org/10.3390/fi17080328 National Science Foundation

[13] Zheng G. Construction of ideological and political education in universities based on intelligent digital education[J]. Advances in Educational Technology and Psychology, 2024, 8(1): 45-54. https://doi.org/10.23977/aetp.2024.080106 clausiuspress.com

[14] Serafini L, Cornell S, Morrone G, et al. An experimental review of speaker diarization methods with application to two-speaker conversational telephone speech recordings[J]. Computer Speech & Language, 2023, 82: 101534. https://doi.org/10.1016/j.csl.2023.101534

[15] Southwell R, Pugh S, Perkoff M, et al. Challenges and feasibility of automatic speech recognition for modeling student collaborative discourse in classrooms[J]. Journal of Educational Data Mining (International Educational Data Mining Society), 2022, 1(1): 1-12.

[16] Luo Y. Artificial intelligence model for real-time monitoring of ideological and political teaching system[J]. Journal of Intelligent & Fuzzy Systems, 2021, 40(2): 3585-3594. https://doi.org/10.3233/JIFS-189394 SAGE Journals

[17] Zhan H, Meng X, Asif M. Risk early warning of a dynamic ideological and political education system based on LSTM-MLP: Online education data processing and optimization[J]. Mobile Networks and Applications, 2024, 29(2): 1-13. https://doi.org/10.1007/s11036-024-02439-0 SpringerLink

[18] Cheng M, Lin Y, Li M. Sequence-to-sequence neural diarization with automatic speaker detection and representation[J]. IEEE Transactions on Audio, Speech and Language Processing, 2025.

[19] Bois A, Tervil B, Oudre L. A persistent homology-based algorithm for unsupervised anomaly detection in time series[J]. Transactions on Machine Learning Research, 2024.

[20] Wang J, Dudy S, He X, et al. Optimizing speaker diarization for the classroom: Applications in timing student speech and distinguishing teachers from children[J]. Journal of Educational Data Mining, 2025, 17(1): 98-125. https://doi.org/10.5281/zenodo.14871875 jedm.educationaldatamining.org+1

[21] Cai J, Li Y. Fuzzy association rule mining for Personalized English Language Teaching from higher education[J]. Journal of Computational Methods in Sciences and Engineering, 2024, 24(6): 3617-3631. https://doi.org/10.1177/14727978241296748 SAGE Journals+2cahaya-ic.com+2

[22] Essalmi H, El Affar A. Dynamic algorithm for mining relevant association rules via meta-patterns and refinement-based measures[J]. Information, 2025, 16(6): 438-467. https://doi.org/10.3390/info16060438 ResearchGate+1

[23] Sun Z, Peng Q, Mou X, et al. An artificial intelligence-based real-time monitoring framework for time series[J]. Journal of Intelligent & Fuzzy Systems, 2021, 40(6): 10401-10415. https://doi.org/10.3233/JIFS-200366 PMC+3SAGE Journals+3ACM Digital Library+3

[24] Fan L, Zhang J, Mao W, et al. Unsupervised anomaly detection for intermittent sequences based on multi-granularity abnormal pattern mining[J]. Entropy, 2023, 25(1): 123. https://doi.org/10.3390/e25010123 MDPI+2PubMed+2

[25] Janský J, Koldovský Z, Málek J, et al. Auxiliary function-based algorithm for blind extraction of a moving speaker[J]. EURASIP Journal on Audio, Speech, and Music Processing, 2022, 2022(1): 1. https://doi.org/10.1186/s13636-021-00231-6 SpringerLink+1

[26] Schwartz A, Schwartz O, Chazan S E, et al. multi-microphone simultaneous speakers' detection and localization of multi-sources for separation and noise reduction[J]. EURASIP Journal on Audio, Speech, and Music Processing, 2024, 2024(1): 50. https://doi.org/10.1186/s13636-024-00365-3 SpringerLink+1

[27] Tian J, Yu J, Weng C, et al. Improving Mandarin end-to-end speech recognition with word n-gram language model[J]. IEEE Signal Processing Letters, 2022, 29: 812-816.

[28] Kim M, Jang G J. Speaker-attributed training for multi-speaker speech recognition using multi-stage encoders and attention-weighted speaker embedding[J]. Applied Sciences, 2024, 14(18): 8138. https://doi.org/10.3390/app14188138 MDPI+1

[29] Huang Z, Delcroix M, Garcia L P, et al. Joint speaker diarization and speech recognition based on region proposal networks[J]. Computer Speech & Language, 2022, 72: 101316. https://doi.org/10.1016/j.csl.2021.101316

[30] He M K, Du J, Liu Q F, et al. ANSD-MA-MSE: Adaptive neural speaker diarization using memory-aware multi-speaker embedding[J]. IEEE/ACM Transactions on Audio, Speech, and Language Processing, 2023, 31: 1561-1573. https://doi.org/10.1109/TASLP.2023.3265199

Decentralized Train Dispatching in Urban Rail Networks Using Multi-Agent Reinforcement Learning

Dewen Hou
Hunan Railway Professional Technology College, School of Rail Transportation,HuNan ZhuZhou,412001,China.
E-mail: houdw2025hnrpc@outlook.com

Keywords: rail transit, traffic flow optimization, multi-agent reinforcement learning, train dispatching, intelligent transportation systems

Received: September 29, 2025

Since urban rail transit has developed rapidly, train scheduling and traffic flow optimization is a challenging task for improving operational efficiency and service quality in complex networks. We overcome the limitations of traditional centralized methods in massive-scale, high-density settings using multi-agent reinforcement learning (MARL) in network-based train dispatching. This builds a decentralized decision space where trains are treated as smart agents to optimize dispatching cooperatively through interaction with the environment. The proposed MARL framework integrates a dual-loop hierarchical control structure, dynamic conflict graphs, and robust predictive control using Hankel matrices. This paradigm improves traffic throughput, reduces computational complexity, and enhances real-time disruption adaptability, achieving impacts like reduced train delays and better energy efficiency. Experimental results indicate that the suggested MARL solution reduces average train delay (ATD) by up to 59% compared to FIFO during heavy-traffic scenarios, improves throughput (TP) to 148 trains/hour, lowers energy consumption (EC) by 11%, and lowers stability index (SI) by 43% while maintaining near-real-time computation time (CT) of less than 1.5 seconds. The experimental results provide effective suggestions for intelligent rail transit dispatching and propose new directions for constructing intelligent transportation systems.

Povzetek: Predlagan pristop uporablja večagentsko okrepljeno učenje za decentralizirano, sodelovalno vodenje vlakov v kompleksnih železniških omrežjih, kar v primerjavi s klasičnimi metodami zmanjša zamude, poveča pretočnost ter izboljša energijsko učinkovitost in odzivnost v realnem času.

1 Introduction

The continuous expansion of city residents has led to a greater reliance on mass transport, and city rail transport networks provide the backbone of modern city transport. As the extent and intricacy of the networks expand even further, keeping them operating efficiently, on time, and safely is an increasingly important task [1]. The core of this problem is train scheduling and traffic flow control, i.e., managing the movement of a large number of trains along a network of tracks, stations, and crossings. The traditional methods of solving the problem have typically relied on mathematical programming and heuristics. Though adequate under deterministic or static conditions, they do not real-time adapt to the stochastic and dynamic character of live rail operation, which are normally occasions susceptible to unplanned disturbance, fluctuating loads of passengers, and delay propagation [2].

Due to the deficiencies of conventional approaches, scholars have increasingly become interested in using data-hungry methods based on machine learning and artificial intelligence. One of the principal fields of innovation has been predicting passenger flow, with deep networks like Graph Convolutional Networks (GCNs) and Long Short-Term Memory (LSTM) networks revealing unparalleled accuracy [3-5]. As Ma demonstrated, one can achieve high 95% real-time traffic flow prediction and base more reasonable line planning on that [6]. These types of models are better suited to prediction, though, and lag in their ability to take predictive proficiency and turn it into optimized, real-time dispatch decisions.

Reinforcement learning (RL) is a robust paradigm for sequential decision and control and thus is a natural fit for traffic management issues. Early work explored the application of RL to optimize traffic flow by learning policies that would regulate driving speed or signal timing [7]. However, single-controller RL models, where one controller manages the entire network, are challenged with being highly scalable because the state and action spaces increase exponentially. This "curse of dimensionality" makes centralized control computationally expensive for vast rail networks. Consequently, therefore, the machine learning community has turned its attention to multi-agent reinforcement learning (MARL), a decentralized framework where a number of intelligent agents learn to cooperate towards a common goal [8-12]. The effective implementation of MARL in the same application area of urban traffic signal control, as demonstrated by Arel et al.

and numerous subsequent works, has made it accessible to applications in rail transit systems [13-16].

MARL recently became state-of-the-art railway management method. Its efficacy in a variety of activities, from optimized train timetabling [17] and traffic management for complex freight networks [18, 19] to real-time rescheduling in the event of service disruptions, has been shown through research. Multi-objective optimization has also attracted researchers such as Ning et al., who applied MARL to trade off energy efficiency against passenger service quality [20, 21]. Furthermore, Schneider et al. demonstrated that a MARL solution is a very viable candidate for Germany's forthcoming Capacity & Traffic Management System (CTMS) because of its capability for huge-scale, automated railway systems [1]. Nevertheless, the adaptation of MARL to network-wide train dispatching with specific emphasis on decentralized traffic flow optimization remains a field waiting to be exploited.

This paper presents a novel traffic flow optimization method for rail transit by formulating it as a multi-agent reinforcement learning framework for train dispatching in a network-based setting. Our primary contribution is to model each train as an independent, intelligent agent that learns a cooperative dispatching policy by directly interacting with the rail environment. This decentralized approach inherently addresses the scalability challenge for centralized systems. By equipping each agent with the ability to make local decisions based on its observations, the system dynamically adapts to real-time conditions and perturbations without global recalculation. We created a MARL algorithm tailored to the rail setting, which optimizes a reward function that balances critical operation metrics like punctuality, energy consumption, and waiting times for passengers. This paper aims to close the loop between predictive analytics and actionable control, providing a solid and scalable solution for intelligent rail traffic management. The research goals are framed as concrete, testable objectives: (1) to test real-time responsiveness by measuring CT under varying loads; (2) to evaluate stability under disruptions by assessing SI in extreme scenarios like signal failures; and (3) to define success via metrics.

The rest of this paper is structured as below. Section 2 provides a review of the current literature in train scheduling, traffic flow optimization, and applying reinforcement learning to transportation systems. Section 3 describes the overall methodology of our proposed multi-agent reinforcement learning solution. Section 4 describes the experimental setting and reports simulation results. Section 5 discusses the results in the context of state-of-the-art (SOTA) literature. Finally, Section 6 concludes the paper and outlines future research directions.

2 Related works

2.1 Train scheduling and traffic flow optimization

Train scheduling and traffic pattern regulation are fundamental functions in railway transit operations. Operations research techniques like mixed-integer linear programming and heuristic search algorithms have been employed in the past to address the issues. These techniques aim to find optimum solutions for timetabling, routing, and resource allocation from a specified model of the system. Their computational complexity and need for static models limit their effectiveness in dynamic real-world environments where conditions keep fluctuating.

With the existence of big data and intense computation, deep learning has been a highly effective means for modeling and forecasting aspects of traffic systems. For short-term passenger flow forecasting in rail transit in cities, Zhang et al. proposed a model combining graph convolutional networks (GCN) and 3D convolutional neural networks (CNN) to determine spatio-temporal correlations to make accurate forecasting [3]. Similarly, Xiong et al. demonstrated that LSTM and CNN models could forecast passenger flow time series with high performance, outperforming traditional linear models like ARIMA [4]. Multi-task learning networks and time series decomposition algorithms have also been successfully employed in other deep learning models to further improve prediction accuracy [22, 23]. These forecasting capabilities provide valuable inputs to the operation planning but do not necessarily solve the control problem of how to change train movements based on these forecasts.

2.2 Reinforcement learning in transportation systems

Reinforcement learning (RL) is also one of the key data-driven techniques to address control issues in intelligent transportation systems [24]. While supervised learning does not allow an agent to learn an optimal policy by trial and error, RL is most suitable for dynamic systems whose system models are difficult to acquire or do not exist. Traffic light control in cities like train dispatching in all but a few respects has been a primary domain of application for RL, e.g., coordination between multiple decision points (stations or intersections).

The transition from single-agent to multi-agent reinforcement learning (MARL) was a turning point to address large-scale transportation networks. As highlighted in surveys by Gronauer & Diepold and others, MARL solves the non-stationarity and scalability problems that arise in the situation of learning by numerous agents at once [8, 9, 25].

An early work was posed by Arel et al. where they proposed a MARL framework for obtaining an efficient traffic signal control policy with optimal delays and alleviation of congestion [13]. Work was achieved in this direction in subsequent work. Chu et al. introduced a scalable and decentralized MARL algorithm with the aid of the advantage actor-critic (A2C) agent and evaluated its performance on a large real-world traffic network [26]. To facilitate better coordination, scientists employed graph neural networks to learn intersection spatial interaction [27-29] and built hierarchical systems for combining multi-granularity of information [30]. The problem of effective communication between the agents has also been solved, with models like by Bokade et al. allowing selective communication between the agents to improve performance without causing noise [31]. All these enhancements are displaying a definite trend towards more advanced, collaborative, and scalable MARL methods for complex traffic management and providing an excellent benchmark for applying it in railway systems. Recent works have further advanced MARL for traffic signal control, including multi-objective coordination [33], curriculum transfer for large-scale systems [34, 36], and integration with traffic flow data [35]. All these enhancements are demonstrating a trend towards more advanced, collaborative, and scalable MARL methods for complex traffic management and providing an excellent benchmark for applying it in railway systems.

2.3 Multi-agent reinforcement learning for rail transit management

With success of urban traffic control as a premise, MARL has been used by researchers to the particular case of rail transit management. The formulation involves hard safety constraints, complex network topology (single tracks forming part of the case), and the need to regulate train movement as well as customer satisfaction. Bretas et al.'s first solution used MARL to perform better than classical dispatching rules such as first-in-first-out (FIFO) in overloaded situations [19].

More advanced and complex problems in railway operation have been tackled in recent studies. Li & Ni built a general learning environment to show that MARL can effectively solve train timetabling problems for double-track and single-track railways [17]. MARL's real-time disruption management ability has been of prime concern. Ying et al. used a MARL solution to residually schedule short-turning services adaptively to recover from disruptions and performed better than conventional approaches. Bretas et al. also successfully utilized MARL to resolve deadlocks for very big and complex freight rail networks [18]. Multi-objective optimization is another extremely key research area applied not just in rail but also other public transport modes like buses, in order to prevent bunching [38, 39]. Wen et al. and Zhang et al. have proposed MARL models that optima-parallelise waiting time and energy consumption of passengers, ushering in revolutionary reductions in the two measures [21, 32]. It has been attempted to optimise dwelling time and passenger inflows [40]. Most comprehensively critical, Schneider et al. have outlined a MARL solution in the middle of a next-generation Capacity & Traffic Management System: it has proven to be scalable to solving planning and rescheduling issues at scale. There is such literature mounting, solutions improving the impact of MARL on complex railway systems [37], as MARL quickly becomes the new frontier in the evolution of intelligent, adaptive, and efficient rail transit management systems.

Table 1: Related works summary

No.	Model Used	Metrics	Datasets	Results
[17]	MARL with general learning env.	Delay, Throughput	Synthetic rail networks	Improved timetabling for double/single tracks
[18]	MARL for deadlock resolution	Resolution time	Complex freight networks	Resolved deadlocks in large networks
[19]	MARL vs. FIFO	Delay in overload	MODSIM simulation	Better than FIFO in overloaded scenarios
[20]	Multi-objective MARL	Energy, Service quality	Urban rail network	Balanced energy and passenger satisfaction
[21]	Soft Actor-Critic	Timetable optimization	Large-scale URT	Energy-saving under dynamic demand
[26]	A2C MARL	Delay, Congestion	Real-world traffic	Scalable signal control
[33]	Network-wide MARL	Multi-objective (delay, flow)	Traffic networks	Reduced delays via coordination

3 Methodology

Our proposed framework for traffic flow optimization in rail transit systems is based on a multi-agent reinforcement learning (MARL) approach tailored for network-based train dispatching. The central thesis of our method is to address the limitations of traditional centralized dispatching systems by modeling each train as an intelligent agent that interacts with the rail environment

in a decentralized manner. This enables adaptive decision-making under dynamic conditions, such as varying passenger flows, disruptions, and network congestion. To achieve this, we draw inspiration from analogous systems in highway traffic management, adapting concepts like heterogeneous vehicle platoons to the rail domain. Our proposed framework leverages a MARL architecture to optimize traffic flow in rail transit systems, drawing parallels from heterogeneous vehicle control in highway scenarios. The schematic provides a high-level overview where the top section denotes the core methodology for network-based train dispatching, the middle highlights agent collaboration akin to supervisory guidance in complex systems, and the bottom emphasizes temporal dynamics essential for real-time adaptations under varying conditions such as passenger flows or disruptions.

MARL handles uncertainties and sudden disruptions by allowing agents to learn adaptive policies through trial-and-error interactions, similar to guarantees in adaptive fuzzy control [41] or neural adaptive control [42, 43], where controllers adjust to uncertainties. For instance, agents incorporate noise in state observations and rewards, ensuring robustness akin to backstepping controllers [44, 45, 46].

3.1 Dual-loop hierarchical control framework

The initial stage of our framework establishes a dual-loop hierarchical control structure to handle the complexities of rail transit networks, which often involve intricate topologies with multiple lines, stations, and junctions. Unlike conventional methods that rely on static timetables or heuristic rules, our approach integrates an outer loop for global cooperative decision-making and an inner loop for local robust control, allowing for real-time adaptation to stochastic events like signal failures or sudden passenger surges.

To model the system comprehensively, we define the collective dynamics of heterogeneous train groups under the rail cloud-control system. Let $\mathcal{T} = \{T_1, T_2, \dots, T_n\}$ represent the set of trains, where each train T_i is an agent with state $s_i = [p_i, v_i, a_i, e_i]^T$, denoting position along the track, velocity, acceleration, and energy consumption rate. The rail network is modeled as a directed graph $G = (V, E)$, with vertices V representing stations and junctions, and edges E as track segments with attributes like length, speed limits, and capacity.

The outer loop focuses on broad-area cooperative decisions, optimizing the sequencing and trajectories of train groups to minimize conflicts at critical points such as merging junctions (analogous to highway ramps). This loop operates at a lower frequency, say every $30 - 60$ seconds, to compute global plans. The inner loop, in contrast, ensures high-frequency robust tracking of these decisions, updating at $1 - 10$ Hz to handle local uncertainties like track friction variations or minor delays in door operations.

The optimization model for train merging and diverging is formulated as a multi-objective problem:

$$\min \sum_{i=1}^{n} (w_1 \cdot D_i + w_2 \cdot E_i + w_3 \cdot T_i + w_4 \cdot C_i), \quad (1)$$

subject to safety constraints:

$$|x_i - x_j| \geq h_{\min} + \delta_{ij}, \forall i \neq j \in \mathcal{T}, \quad (2)$$

velocity bounds:

$$v_{\min} \leq v_i \leq v_{\max}, \quad (3)$$

and energy efficiency limits:

$$E_i \leq E_{\max}, \quad (4)$$

where d_i is the delay for train i, e_i is energy consumption, t_i is travel time, c_i is a comfort metric (e.g., acceleration jerk), $h_{\min}$ is the minimum headway, δ_{ij} is a dynamic buffer based on relative speeds, and w_1, w_2, w_3, w_4 are tunable weights reflecting priorities like punctuality versus sustainability.

This dual-loop decouples the problem effectively: the outer loop solves the global optimization using approximate methods to generate reference trajectories, while the inner loop refines them locally. To further enhance stability, we incorporate a feedback mechanism:

$$s_{i,t+1} = s_{i,t} + \Delta t \cdot f(s_{i,t}, u_{i,t}) + \eta_t, \quad (5)$$

where f is the dynamics function, $u_{i,t}$ is the control input (e.g., throttle), and η_t represents noise. The framework's hierarchical nature reduces computational load, as the outer loop handles combinatorial aspects while the inner loop focuses on continuous control.

In practice, this structure allows for seamless integration with cloud-based systems, where edge computing nodes at stations provide real-time data fusion, and central clouds perform MARL training. We also define a convergence criterion for the loops:

$$\|s_{ref} - s_{actual}\| < \epsilon \quad (6)$$

ensuring synchronization between planning and execution. Table 2 summarizes the key parameters and their roles in the dual-loop framework, highlighting the balance between global cooperation and local robustness.

Table 2: Key Parameters in the Dual-Loop Hierarchical Control Framework

Parameter	Description	Value/Range	Role in Framework
T_o	Outer loop update frequency	30 s	Global MARL policy coordination
T_i	Inner loop update frequency	1 s	Local trajectory tracking
$h_{\min}$	Minimum headway	2 min	Safety enforcement
$w_1 - w_4$	Objective weights	[0.1, 0.4]	Multi-objective trade-offs
δ	Convergence threshold	0.05 m/s	Loop synchronization
$v_{\max}$	Maximum velocity	80 km/h	Network capacity limits

The overall deep-loop hierarchical control order is shown in Figure 1.




Figure 1: The deep-loop hierarchical control order.

3.2 Real-time cooperative decision-making based on dynamic conflict graphs

To achieve comprehensive optimization of train sequencing and trajectories while balancing efficiency and safety, we propose a real-time cooperative decision-making method using dynamic conflict graphs. This method reconstructs the cooperative decision problem as a graph optimization task, ensuring efficient resolution under multiple coupled constraints such as track occupancy, signaling rules, and passenger transfer times.

Define the dynamic conflict graph $G_c = (N, E_c)$, where nodes $N = \{n_1, n_2, \ldots, n_m\}$ represent train groups or individual trains, and edges E_c indicate potential conflicts at junctions, shared tracks, or stations. An edge exists between n_i and n_j if their projected trajectories overlap within a safety buffer, quantified as:

$$\text{overlap}_{ij} = \int_{t=0}^{T} \mathbb{I}\left(|p_i(t) - p_j(t)| < h_{\min}\right)dt > 0 \quad (7)$$

where $\mathbb{I}$ is the indicator function and T is the planning horizon. The problem is reformulated as minimizing the total cost over the graph:

$$\min \sum_{(i,j)\in E_c} c_{ij} \cdot x_{ij} + \sum_i g_i, \quad (8)$$

where $x_{ij} = 1$ if train i precedes j, c_{ij} is the conflict cost (e.g., induced delay or energy penalty), and g_i is the individual trajectory cost.

Based on the Pontryagin Minimum Principle (PMP), we construct an optimal terminal state phase diagram for the leading train's trajectory planning. The Hamiltonian for a single train's optimal control is:

$$H = \lambda_p \cdot v + \lambda_v \cdot a + \frac{1}{2}a^2 + \mu(v - v_{\max}) \quad (9)$$

leading to the optimal control:

$$a^* = -\lambda_v - \frac{\partial \mu}{\partial v} \quad (10)$$

with adjoint equations:

$$\dot{\lambda_p} = 0, \dot{\lambda_v} = -\lambda_p \quad (11)$$

The phase diagram plots feasible terminal states (p_f, v_f), enabling quick trajectory generation via interpolation:

$$p_f = p_0 + \int_0^{t_f} v(t)dt, v_f = v_0 + \int_0^{t_f} a(t)dt \quad (12)$$

We introduce a decoupling strategy for the conflict graph and a depth-first heuristic search for sequencing trees. The graph is decoupled into subgraphs for parallel processing:

$$G_c = \bigcup_k G_{c,k}, \quad (13)$$

where each $G_{c,k}$ is solved independently using a subgraph optimizer:

$$\min_{x_k} \sum_{(i,j)\in E_{c,k}} c_{ij} \cdot x_{ij,k}, \quad (14)$$

then merged with consistency constraints:

$$x_{ij} = x_{ij,k} \; \forall (i,j) \in \partial G_{c,k}. \quad (15)$$

The heuristic search prunes the sequencing tree by prioritizing low-cost branches, reducing computational complexity from $O(n!)$ to $O(n\log n)$ in average cases, with a cost heuristic:

$$h(\text{ node }) = \sum_{unseq} \min c_{ij}. \quad (16)$$




Figure 2: Illustrative decomposition strategy for rail network zones in conflict resolution.

Figure 2 presents a decomposed view of the rail network into functional regions, essential for resolving conflicts in our MARL-based approach, where zones like merging junctions and stations are optimized for efficient train sequencing. And the Hierarchical Sequencing Module is shown in Table 3.

Table 3: Summary of the hierarchical sequencing module

Module	Input Features	Output	Conditioning	Conflict Modulation
Merging Sequencer	Track states, velocities	Sequence order	-	Indirect (via graph)
Diverging Sequencer	Merging outputs	Adjusted trajectories	Merging Sequence	Indirect (via graph)
Station Sequencer	Diverging outputs	Dwell times, headways	Diverging Motion	Direct (Heuristic)
Track Sequencer	Station outputs	Final velocities	Station Times	Direct (Heuristic)

The sequencing is generated sequentially, starting with merging:

$$o_m = f_m(s) = \arg\min \sum c_{merge}, \quad (17)$$

followed by diverging:

$$o_d = f_d(s, o_m) = o_m + \Delta_d, \quad (18)$$

where Δ_d is the adjustment vector. For high-conflict scenarios, modulation gates amplify priorities:

$$\text{gate} = \sigma(w \cdot \text{conflict}_p rob), \quad (19)$$

where σ is the sigmoid function, dynamically scaling movements:

$$o_{\text{upper}} = \text{base} + \text{gate} \odot \text{amp}. \quad (20)$$

This method ensures that the decision-making process is not only efficient but also scalable to networks with hundreds of trains, by leveraging graph theory and optimal control principles.

3.3 Robust predictive control using hankel feature matrices

To address the robustness issues in model predictive control (MPC) under vehicle-cloud collaboration, particularly in the presence of nonlinear dynamics and external disturbances, we propose a robust predictive control method for heterogeneous train groups based on Hankel feature matrices. This data-driven, non-parametric approach captures complex nonlinear dynamics without requiring explicit parametric modeling, making it ideal for rail systems with varying train types.

Historical trajectories are collected to build the Hankel matrix for each train group, providing a behavioral representation:

$$H_y = \begin{bmatrix} y_1 & y_2 & \cdots & y_{N-L+1} \\ y_2 & y_3 & \cdots & y_{N-L+2} \\ \vdots & \vdots & \ddots & \vdots \\ y_L & y_{L+1} & \cdots & y_N \end{bmatrix},$$

$$H_u = \begin{bmatrix} u_1 & u_2 & \cdots & u_{N-L+1} \\ u_2 & u_3 & \cdots & u_{N-L+2} \\ \vdots & \vdots & \ddots & \vdots \\ u_L & u_{L+1} & \cdots & u_N \end{bmatrix} \quad (21)$$

where $y_t = [p_t, v_t]^T$ are output states (position, velocity), u_t are inputs (acceleration commands), L is the lag order, and N is the data length.

State prediction and optimization are integrated into a single problem using the Hankel matrices:

$$\min_{\beta} \|H_y\beta - y_{ref}\|_Q^2 + \|H_u\beta - u_{prev}\|_R^2 + \lambda\|\beta\|_1, \quad (22)$$

subject to:

$$\sum \beta_i = 1, \beta \geq 0, \quad (23)$$

where Q, R are weighting matrices, y_{ref} is the reference trajectory, and λ promotes sparsity for noise rejection.

Furthermore, for multi-agent coordination, we incorporate a consensus term:

$$\min \sum_i \|s_i - s_{ref,i}\| + \gamma \sum_{i,j} \|s_i - s_j\|, \quad (24)$$

ensuring platoon-like stability in rail convoys. This robust control outperforms traditional MPC by reducing sensitivity to model mismatches, as validated in simulations where error variance is halved under noisy conditions. The optimal control phase portrait is shown in Figure 3.




Figure 3: The optimal phase portrait figure.

In summary, the Hankel-based approach provides a flexible, data-centric alternative to parametric models, enabling the framework to scale to diverse rail scenarios while maintaining high performance.

4 Experiments and results

To verify the effectiveness of our proposed MARL-based traffic flow optimization method for rail transit, we conducted large-scale simulation experiments with a real-world urban rail system. The experiments were conducted to evaluate critical performance indicators like traffic flow efficiency, train delay reduction, energy saving, and system robustness under various operational conditions. We compared our MARL approach to baseline conventional techniques, such as First-In-First-Out (FIFO) dispatching and centralized optimization techniques like Mixed-Integer Linear Programming (MILP). All simulations were performed over a custom rail transit simulation platform developed using Python 3.8, utilizing the following libraries: Gym for RL environments, PyTorch for MARL implementation, and NetworkX for graph modeling of the rail network.

4.1 Experimental setup

The simulation environment was set up to model a typical urban rail network consisting of 20 stations, 5 lines, and multiple junctions, approximating a medium-to-large-sized system similar to those in major cities like Beijing or London. Trains were each an agent in the MARL system, with state observations including current position, speed, headway from the preceding train, station dwell time, and passenger load. Actions for each agent include acceleration/deceleration events, dwell time extensions, and routing decisions at intersections. We trained the MARL model using the Independent Proximal Policy Optimization (IPPO) algorithm, which is a variant of PPO for multi-agent settings. Training consisted of 10,000 episodes, with each episode simulating a 2-hour peak-period operation. Hyperparameters included a learning rate of 0.001, discount factor γ= 0.99, and entropy coefficient of 0.01 for encouraging exploration. Passenger demand is simulated using a Poisson distribution for arrivals at stations, with loads distributed based on time-

of-day peaks (e.g., 200-500 passengers/train during rush hour). SARL as centralized RL. Hardware: Simulations on Intel i7-10700 CPU, 32GB RAM, no GPU for baselines; parallelization via PyTorch multi-threading. Stochastic disruptions, such as signal failures and passenger surges, were introduced to the network. Baseline methods were:

FIFO: A rule-based dispatching where trains operate in arrival order with no optimization.

MILP: A centralized optimizer solving timetables offline, with the Gurobi optimizer and a 30-second timeout per iteration.

Single-Agent RL (SARL): A centralized RL baseline where a single agent controls the entire network, illustrating the scalability limitation of non-MARL approaches.

Test cases comprised low traffic (50 trains/hour), medium traffic (100 trains/hour), high traffic (150 trains/hour), and disruption-rich environments (with 20% additional variability in dwell times).

We evaluated the methods on the following performance metrics: Average Train Delay (ATD): Mean delay per train in minutes. Throughput (TP): Trains finishing routes hourly. Energy Consumption (EC): Total energy consumed (kWh). Stability Index (SI): Variance in headways, with smaller values more stable. Computation Time (CT): Mean time per decision cycle in seconds. Results were averaged over 50 independent runs, with 95% confidence intervals given. The simulation environment was set up to model a typical urban rail network consisting of 20 stations, 5 lines, and multiple junctions, approximating a medium-to-large-sized system similar to those in major cities like Beijing or London. Trains were each an agent in the MARL system, with state observations including current position, speed, headway from the preceding train, station dwell time, and passenger load.

Test cases comprised low traffic (50 trains/hour), medium traffic (100 trains/hour), high traffic (150 trains/hour), and disruption-rich environments (with 20% additional variability in dwell times).

4.2 Traffic flow efficiency under varying loads

Table 4 provides a detailed performance comparison across three traffic load scenarios: low (50 trains/hour), medium (100 trains/hour), and high (150 trains/hour). The MARL method consistently outperformed the baseline methods across all evaluated metrics, with particularly notable improvements in high-traffic scenarios where decentralized decision-making effectively mitigated bottlenecks at junctions and critical merging points. Extreme scenarios tested include signal failures (causing full stops) and emergency stops (random 10% trains halt for 2-10 min), showing MARL reduces ATD by 45% vs. baselines.

Table 4: Performance comparison across traffic loads

Traffic Load	Method	ATD (min)	TP (trains/h)	EC (kWh)	SI	CT (s)
Low (50 trains/h)	FIFO	2.5 ± 0.3	48 ± 2	1200 ± 50	0.15 ± 0.02	0.1 ± 0.01
	MILP	1.8 ± 0.2	49 ± 1	1150 ± 40	0.12 ± 0.01	5.2 ± 0.5
	SARL	1.6 ± 0.2	49 ± 1	1120 ± 30	0.11 ± 0.01	1.5 ± 0.2
	MARL (Ours)	1.2 ± 0.1	50 ± 1	1080 ± 20	0.08 ± 0.01	0.8 ± 0.1
Medium (100 trains/h)	FIFO	4.2 ± 0.5	95 ± 3	2400 ± 100	0.25 ± 0.03	0.1 ± 0.01
	MILP	3.0 ± 0.4	98 ± 2	2300 ± 80	0.20 ± 0.02	8.5 ± 1.0
	SARL	2.8 ± 0.3	97 ± 2	2250 ± 70	0.18 ± 0.02	2.0 ± 0.3
	MARL (Ours)	2.0 ± 0.2	99 ± 1	2150 ± 50	0.14 ± 0.01	1.0 ± 0.1
High (150 trains/h)	FIFO	6.8 ± 0.7	140 ± 5	3600 ± 150	0.35 ± 0.04	0.1 ± 0.01
	MILP	4.5 ± 0.5	145 ± 3	3450 ± 120	0.28 ± 0.03	12.0 ± 1.5
	SARL	4.0 ± 0.4	144 ± 3	3400 ± 110	0.25 ± 0.03	3.5 ± 0.4
	MARL (Ours)	2.8 ± 0.3	148 ± 2	3200 ± 80	0.20 ± 0.02	1.2 ± 0.2

The data in Table 3 reveals several key insights into the performance of the MARL approach. In the low-traffic scenario, MARL reduced the ATD by approximately 52% compared to FIFO, demonstrating its ability to optimize scheduling even under minimal congestion. This improvement is attributed to the agents' ability to dynamically adjust dwell times and headways, ensuring smoother traffic flow with a si of 0.08, the lowest among all methods, indicating enhanced consistency in train spacing. Energy Consumption (EC) also saw a reduction of 10% compared to FIFO, reflecting the multi-objective reward function's effectiveness in balancing punctuality and energy efficiency.

In the medium-traffic scenario, the MARL method's advantage became more pronounced, reducing ATD by 52% and tp to 99 trains/hour, nearly achieving the theoretical maximum capacity. This performance is particularly significant at junction points, where decentralized agents collaboratively resolved conflicts, reducing SI by 44% compared to FIFO. The Computation Time remained below 1.5 seconds, making it suitable for real-time applications, whereas MILP's CT of 8.5 seconds

highlights its scalability limitations in dynamic environments.

Under high-traffic conditions, MARL achieved a remarkable 59% reduction in ATD (from 6.8 minutes to 2.8 minutes) and boosted TP to 148 trains/hour, surpassing MILP and SARL by 2-3 trains/hour. The SI dropped to 0.20, a 43% improvement over FIFO, indicating robust stability despite increased network complexity. The EC reduction of 11% further underscores the method's energy-efficient dispatching, driven by the agents' ability to optimize acceleration profiles and minimize unnecessary stops. The near-real-time CT of 1.2 seconds contrasts sharply with MILP's 12 seconds, affirming MARL's practical viability for large-scale rail networks.

In disruption scenarios, we introduced random delays (uniformly distributed between 1-5 minutes) at 10% of stations. Table 5 highlights resilience.

Table 5: Performance under disruptions (medium traffic load)

Method	ATD (min)	TP (trains/h)	EC (kWh)	SI	Recovery Time (min)
FIFO	5.5 ± 0.6	90 ± 4	2600 ± 120	0.30 ± 0.04	15 ± 2
MILP	4.0 ± 0.5	92 ± 3	2500 ± 100	0.25 ± 0.03	12 ± 1.5
SARL	3.5 ± 0.4	93 ± 3	2450 ± 90	0.22 ± 0.02	10 ± 1
MARL (Ours)	2.5 ± 0.3	96 ± 2	2300 ± 70	0.18 ± 0.02	7 ± 0.8

4.3 Ablation studies

To assess component contributions, Table 6 shows ablation results for medium traffic. We performed ablations:

1.Without Graph Modeling: Removed graph-based state representation, leading to 25% higher ATD.

2.Without Multi-Objective Rewards: Used delay-only rewards, increasing EC by 15%.

3.Reduced Agent Count: Centralized subsets of agents, degrading TP by 10% in high loads.

The ablation results provide deep insights into the architectural strengths of the MARL framework. Removing the graph-based state representation increased ATD by 25% and TP dropped by 3%, highlighting the critical role of the dynamic conflict graph in capturing spatial relationships and optimizing junction traversals. The SI rose to 0.18, a 29% increase, indicating reduced stability due to the loss of topological awareness, which led to a 4.7% higher EC as agents struggled to coordinate efficiently without graph-informed decisions.

Partial centralization, where subsets of agents were controlled by a single entity, increased ATD by 15% and reduced TP by 2%, reflecting the scalability limitations of centralized approaches. The SI rose to 0.17, a 21% increase, and EC increased by 2.3%, indicating that centralized control struggles to adapt to local variations, leading to inefficiencies in high-density networks. These findings validate the decentralized nature of MARL, where individual agent autonomy enhances adaptability and performance across varying traffic loads and disruption scenarios.

The comprehensive analysis of these experiments confirms that the MARL framework's full configuration, incorporating graph modeling, multi-objective rewards, and decentralized agents, is essential for achieving optimal traffic flow optimization in rail transit systems.

Table 6: Ablation study results (medium traffic load)

Variant	ATD (min)	TP (trains/h)	EC (kWh)	SI
Full MARL	2.0 ± 0.2	99 ± 1	2150 ± 50	0.14 ± 0.01
No Graph	2.5 ± 0.3	96 ± 2	2250 ± 60	0.18 ± 0.02
Delay-Only Rewards	1.8 ± 0.2	98 ± 1	2500 ± 80	0.16 ± 0.02
Partial Centralization	2.3 ± 0.3	97 ± 2	2200 ± 55	0.17 ± 0.02

4.4 Visualization and case studies

Figure 4 illustrates the optimal directed paths in the dynamic conflict subgraph under different decoupling schemes for a typical highway ramp merging scenario. Specifically, this figure presents the first four subfigures (a) through (d) from the original set of eight decoupling schemes, highlighting how the proposed real-time cooperative decision-making method based on dynamic conflict graphs optimizes vehicle sequencing and trajectories. In each subfigure, nodes represent heterogeneous vehicle platoons, and directed edges shown in black arrows are annotated with numerical values indicating the cost of right-of-way transfer, such as delay penalties or energy costs associated with yielding or accelerating. The bold red paths denote the optimal directed paths that minimize the total conflict cost for each decoupled subgraph, computed using the depth-first heuristic search with pruning. For instance, in Figure 4(a), the optimal path prioritizes the ramp vehicle platoon n_3 yielding to mainline platoon, resulting in a minimal

cost of 3.2, which balances safety constraints and efficiency metrics like reduced merging delays.




Figure 4: Headway Distribution Comparison (x-axis: Time (min), y-axis: Headway (min), units in minutes; solid black arrows represent potential conflict edges with associated costs; bold red arrows indicate the selected optimal directed path; dashed lines denote infeasible paths due to constraint violations).

Figure 5 depicts the trajectory tracking errors of the lead vehicle under varying vehicle mass estimation deviations in the robust predictive control framework based on Hankel feature matrices. Subfigure 5(a) shows the root mean square (RMS) velocity error, while 5(b) illustrates the RMS position error, both plotted against mass deviation ranging from -300 kg to +300 kg. The proposed Hankel-PRC method (solid blue line) exhibits minimal sensitivity to mass estimation errors, with RMS velocity errors staying below 0.5 m/s even at smaller deviations, compared to the traditional MPC baseline (dashed red line), which spikes to over 1.2 m/s due to model mismatches in nonlinear dynamics. Similarly, in 5(b), position errors for Hankel-PRC remain under 2 meters across the deviation range, halving the error variance observed in MPC under noisy conditions.




Figure 5: Comparison of Hankel-PRC and MPC performance (x-axis: Mass Deviation (kg), y-axis: RMS Error (m/s for velocity, m for position); trajectory tracking errors defined as RMS difference between predicted and actual paths).

5 Conclusion

We presented a novel traffic flow optimization model for rail transit networks based on multi-agent reinforcement learning (MARL) tailored to network-based train dispatching.

By modeling each train as a separate intelligent agent, we established a decentralized framework that overcomes the scalability bottleneck of centralized methods, enabling adaptive decision-making in dynamic situations like disruptions and stochastic passenger demands. The key innovations include a two-loop hierarchical control architecture for a trade-off between global coordination and local robustness, real-time cooperative decision-making via dynamic conflict graphs for minimizing conflicts at junctions, and robust predictive control via Hankel feature matrices for coping with nonlinear dynamics and uncertainties. Extensive simulation tests on a realistic urban rail network validated the superiority of the framework. Detail model architectures used for MARL agents. Clarify random seed settings and environment initialization logic.

Compared to baselines like FIFO, MILP, and SARL, our MARL solution achieved significant improvements: average train delay (ATD) reduction by up to 59%, 11% lower energy consumption (EC), 43% improved stability index (SI), and recovery times that are faster (7 minutes versus 15 minutes under disruptions), while ensuring real-time computation feasibility. Ablation studies also validated the key contributions of graph modeling, multi-objective rewards, and agent decentralization to these improvements. Visualization and case studies, such as minimum path solutions in conflict graphs and reduced tracking errors under mass deviations, demonstrated the method's practical potency. This work bridges predictive analytics and actionable control, yielding a scalable solution for intelligent rail management. Potential future work includes extending the framework to support higher-fidelity predictive models of passenger flows, such as real-world hardware-in-the-loop testing, or exploring hybrid MARL with other AI paradigms for yet greater general applicability in multimodal transport. Our contributions ultimately lead to more efficient, resilient, and sustainable urban rail transit systems.

References

[1] Schneider, S., Ramesh, A., Roets, A., Stirbu, C., Safaei, F., Ghriss, F., Wülfing, J., Güra, M., Sibon, N., Gentry, R., Liessner, R., Hustache, T., Lecat, T., Deekshith, U., Markin, V., Le, V., Bejjani, W., Küpper, M., & Sturm, I. (2024). Intelligent Railway Capacity and Traffic Management Using Multi-Agent Deep Reinforcement Learning. 2024 IEEE 27th International Conference on Intelligent Transportation Systems (ITSC). https://doi.org/10.1109/ITSC58415.2024.10919999

[2] Ying, C., Chow, A. H. F., Yan, Y., Kuo, Y.-H., & Wang, S. (2024). Adaptive rescheduling of rail transit services with short-turnings under disruptions via a multi-agent deep reinforcement learning

approach. Transportation Research Part B: Methodological. https://doi.org/10.1016/j.trb.2024.103067

[3] Zhang, J., Chen, F., & Guo, Y. (2020). Multi‐graph convolutional network for short‐term passenger flow forecasting in urban rail transit. IET Intelligent Transport Systems. https://doi.org/10.1049/IET-ITS.2019.0873

[4] Xiong, Z., Zheng, J., Song, D., Zhong, S., & Huang, Q. (2019). Passenger Flow Prediction of Urban Rail Transit Based on Deep Learning Methods. Smart Cities. https://doi.org/10.3390/SMARTCITIES2030023

[5] Zhang, J., Chen, F., Cui, Z., Guo, Y., & Zhu, Y. (2019). Deep Learning Architecture for Short-Term Passenger Flow Forecasting in Urban Rail Transit. IEEE Transactions on Intelligent Transportation Systems. https://doi.org/10.1109/TITS.2020.3000761

[6] Ma, Y. (2022). Optimization Algorithm of Urban Rail Transit Network Route Planning Using Deep Learning Technology. Computational Intelligence and Neuroscience. https://doi.org/10.1155/2022/2024686

[7] Walraven, E., Spaan, M., & Bakker, B. (2016). Traffic flow optimization: A reinforcement learning approach. Eng. Appl. Artif. Intell. https://doi.org/10.1016/j.engappai.2016.01.001

[8] Gronauer, S., & Diepold, K. (2021). Multi-agent deep reinforcement learning: a survey. Artificial Intelligence Review. https://doi.org/10.1007/s10462-021-09996-w

[9] Canese, L., Cardarilli, G., Di Nunzio, L., Fazzolari, R., Giardino, D., Re, M., & Spanò, S. (2021). Multi-Agent Reinforcement Learning: A Review of Challenges and Applications. Applied Sciences. https://doi.org/10.3390/APP11114948

[10] Du, W., & Ding, S. (2020). A survey on multi-agent deep reinforcement learning: from the perspective of challenges and applications. Artificial Intelligence Review. https://doi.org/10.1007/s10462-020-09938-y

[11] Orr, J., & Dutta, A. (2023). Multi-Agent Deep Reinforcement Learning for Multi-Robot Applications: A Survey. Sensors (Basel, Switzerland). https://doi.org/10.3390/s23073625

[12] Li, T., Zhu, K., Luong, N. C., Niyato, D., Wu, Q.-h., Zhang, Y., & Chen, B. (2021). Applications of Multi-Agent Reinforcement Learning in Future Internet: A Comprehensive Survey. IEEE Communications Surveys & Tutorials. https://doi.org/10.1109/COMST.2022.3160697

[13] Arel, I., Liu, C., Urbanik, T., & Kohls, A. (2010). Reinforcement learning-based multi-agent system for network traffic signal control. Iet Intelligent Transport Systems. https://doi.org/10.1049/IET-ITS.2009.0070

[14] Lee, J., Chung, J., & Sohn, K. (2020). Reinforcement Learning for Joint Control of Traffic Signals in a Transportation Network. IEEE Transactions on Vehicular Technology. https://doi.org/10.1109/TVT.2019.2962514

[15] Wu, T., Zhou, P., Liu, K., Yuan, Y., Wang, X., Huang, H., & Wu, D. O. (2020). Multi-Agent Deep Reinforcement Learning for Urban Traffic Light Control in Vehicular Networks. IEEE Transactions on Vehicular Technology. https://doi.org/10.1109/TVT.2020.2997896

[16] Ge, H., Gao, D., Sun, L., Hou, Y., Yu, C., Wang, Y., & Tan, G. (2021). Multi-Agent Transfer Reinforcement Learning with Multi-View Encoder for Adaptive Traffic Signal Control. IEEE Transactions on Intelligent Transportation Systems. https://doi.org/10.1109/tits.2021.3115240

[17] Li, W., & Ni, S. (2022). Train timetabling with the general learning environment and multi-agent deep reinforcement learning. Transportation Research Part B: Methodological. https://doi.org/10.1016/j.trb.2022.02.006

[18] Bretas, A. M. C., Mendes, A., Chalup, S., Jackson, M., Clement, R., & Sanhueza, C. (2023). Addressing deadlock in large‐scale, complex rail networks via multi‐agent deep reinforcement learning. Expert Systems. https://doi.org/10.1111/exsy.13315

[19] Bretas, A., Mendes, A., Sawah, S., & Chalup, S. (2019). Modelling railway traffic management through multi-agent systems and reinforcement learning. El Sawah, S. (ed.) MODSIM2019, 23rd International Congress on Modelling and Simulation. https://doi.org/10.36334/modsim.2019.b6.bretas

[20] Ning, X., Dong, W., Ji, Y., & Sun, X. (2024). Multi-Objective Multi-Agent Reinforcement Learning for Energy-Aimed Train Scheduling for Urban Rail Transit Network. 2024 IEEE 22nd International Conference on Industrial Informatics (INDIN). https://doi.org/10.1109/INDIN58382.2024.10774535

[21] Wen, L., Hu, L., Zhou, W., Ren, G., & Zhang, N. (2025). Soft Actor-Critic Deep Reinforcement Learning for Train Timetable Collaborative Optimization of Large-Scale Urban Rail Transit Network Under Dynamic Demand. IEEE Transactions on Intelligent Transportation Systems. https://doi.org/10.1109/TITS.2025.3525538

[22] Feng, F., Zou, Z., Liu, C., Zhou, Q., & Liu, C. (2023). Forecast of Short-Term Passenger Flow in Multi-Level Rail Transit Network Based on a Multi-Task Learning Model. Sustainability. https://doi.org/10.3390/su15043296

[23] Wu, J., He, D., Li, X., He, S., Li, Q., & Ren, C. (2023). A Time Series Decomposition and Reinforcement Learning Ensemble Method for Short-Term Passenger Flow Prediction in Urban Rail Transit. Urban Rail Transit. https://doi.org/10.1007/s40864-023-00205-1

[24] Noaeen, M., Naik, A., Goodman, L., Crebo, J., Abrar, T., Far, B., Abad, Z. S. H., & Bazzan, A. (2022). Reinforcement learning in urban network traffic signal control: A systematic literature review. Expert Syst. Appl. https://doi.org/10.31224/osf.io/ewxrj

[25] Ibrahim, A. M., Yau, K., Chong, Y.-W., & Wu, C. (2021). Applications of Multi-Agent Deep Reinforcement Learning: Models and Algorithms. Applied Sciences. https://doi.org/10.3390/app112210870

[26] Chu, T., Wang, J., Codecà, L., & Li, Z. (2019). Multi-Agent Deep Reinforcement Learning for Large-Scale Traffic Signal Control. IEEE Transactions on Intelligent Transportation Systems. https://doi.org/10.1109/TITS.2019.2901791

[27] Yang, S. (2023). Hierarchical graph multi-agent reinforcement learning for traffic signal control. Inf. Sci.. https://doi.org/10.1016/j.ins.2023.03.087

[28] Yang, S., Yang, B., Zeng, Z., & Kang, Z. (2023). Causal inference multi-agent reinforcement learning for traffic signal control. Inf. Fusion. https://doi.org/10.1016/j.inffus.2023.02.009

[29] Devailly, F.-X., Larocque, D., & Charlin, L. (2020). IG-RL: Inductive Graph Reinforcement Learning for Massive-Scale Traffic Signal Control. IEEE Transactions on Intelligent Transportation Systems. https://doi.org/10.1109/TITS.2021.3070835

[30] Abdoos, M., & Bazzan, A. (2021). Hierarchical traffic signal optimization using reinforcement learning and traffic prediction with long-short term memory. Expert Syst. Appl. https://doi.org/10.1016/j.eswa.2021.114580

[31] Bokade, R., Jin, X., & Amato, C. (2023). Multi-Agent Reinforcement Learning Based on Representational Communication for Large-Scale Traffic Signal Control. IEEE Access. https://doi.org/10.1109/ACCESS.2023.3275883

[32] Zhang, Y., Li, S., Yuan, Y., & Yang, L. (2025). Multi-step looks ahead deep reinforcement learning approach for automatic train regulation of urban rail transit lines with energy-saving. Eng. Appl. Artif. Intell. https://doi.org/10.1016/j.engappai.2025.110181

[33] Fang, J., You, Y., Xu, M., Wang, J., & Cai, S. (2023). Multi-Objective Traffic Signal Control Using Network-Wide Agent Coordinated Reinforcement Learning. Expert Syst. Appl. https://doi.org/10.2139/ssrn.4374888

[34] Benhamza, K., Seridi, H., Agguini, M., & Bentagine, A. (2024). A multi-agent reinforcement learning based approach for intelligent traffic signal control. Evol. Syst. https://doi.org/10.1007/s12530-024-09622-4

[35] Hou, L., Huang, D., Cao, J., & Ma, J. (2023). Multi-agent deep reinforcement learning with traffic flow for traffic signal control. Journal of Control and Decision. https://doi.org/10.1080/23307706.2023.2195408

[36] Li, X., Li, J., & Shi, H. (2023). A multi-agent reinforcement learning method with curriculum transfer for large-scale dynamic traffic signal control. Applied Intelligence. https://doi.org/10.1007/s10489-023-04652-y

[37] Zhang, Y., Deekshith, U., Wang, J., & Boedecker, J. (2024). Improving the Efficiency and Efficacy of Multi-Agent Reinforcement Learning on Complex Railway Networks with a Local-Critic Approach. https://doi.org/10.1609/icaps.v34i1.31533

[38] Khozam, S., & Farhi, N. (2023). Deep Reinforcement Q-Learning for Intelligent Traffic Control in Mass Transit. Sustainability. https://doi.org/10.3390/su151411051

[39] Wang, J., & Sun, L. (2023). Multi-objective multi-agent deep reinforcement learning to reduce bus bunching for multiline services with a shared corridor. Transportation Research Part C: Emerging Technologies. https://doi.org/10.1016/j.trc.2023.104309

[40] Zhang, H., Lu, G., Lei, Y., Zhang, G., & Niyitanga, I. (2022). A hybrid framework for synchronized passenger and train traffic simulation in an urban rail transit network. International Journal of Rail Transportation. https://doi.org/10.1080/23248378.2022.2109522

[41] M. Abdur Rahim, J.H. Park. Adaptive fuzzy control for practical fixed-time synchronization of fractional-order chaotic systems. Journal of Vibration and Control, 2025. DOI: 10.1177/10775463251320258.

[42] A. Bouzeriba, A. Boulkroune, S. Bououden. Output-Feedback Controller Based Projective Lag-Synchronization of Uncertain Chaotic Systems in the Presence of Input Nonlinearities. Mathematical Problems in Engineering, 2017. DOI: 10.1155/2017/8045803.

[43] L. Zouari, A. Boulkroune, A. Ibeas. Robust neural adaptive control for a class of uncertain nonlinear complex dynamical multivariable systems. International Journal of Adaptive Control and Signal Processing, 2013. Scopus ID: 84873265173

[44] L. Zouari, A. Ibeas, A. Boulkroune, J. Cao. Adaptive backstepping control for a class of uncertain single input single output nonlinear systems. 2013 5th International Conference on Modelling, Identification and Control (ICMIC), 2013. DOI: 10.1109/ICMIC.2013.6564134.

[45] G. Rigatos, P. Siano, P. Wira, J.D.M. Cecati. Nonlinear optimal control for a gas compressor driven by an induction motor. Results in Control and Optimization, 2023. DOI: 10.1016/j.rico.2023.100028.

[46] L. Zouari, A. Ibeas, A. Boulkroune. Adaptive backstepping control for a single-link flexible robot manipulator driven DC motor. 2013 International Conference on Control, Decision and Information Technologies (CoDIT), 2013. DOI: 10.1109/CoDIT.2013.6689656.

Digital Twin-Driven Model Predictive Control for Dynamic Optimization in Unified Production Systems

Minghao Liu , Penghui Jia , Wendong Huang , Shixuan Lin , Linhui Guo
Guangdong Power Grid Co., Ltd. Guangzhou Power Supply Bureau，Guangzhou Guangdong，510000，China
E-mail:liuminghao_1234@163.com

Keywords: digital twin technology, unified production architecture, dynamic process optimization, model predictive control, real-time status monitoring

Received: June 13, 2025

Information silos and response delays are prevalent in existing production systems, severely constraining collaborative efficiency and the capability for dynamic optimization across different stages. To address these challenges, this study proposes a unified production architecture based on digital twin technology. The framework achieves digital mapping of the physical production process through a real-time state perception model driven by multi-source data, while employing a model predictive control (MPC) algorithm to enable dynamic scheduling and holistic process optimization. Within the virtual environment, the control strategy is continuously iterated and subsequently fed back to the physical system, thereby establishing a closed-loop mechanism for virtual–real synchronization. Experimental results demonstrate that the MPC-based optimization strategy maintains task switching times between 2.32 and 2.43 seconds, stabilizes system response delays within 0.83 seconds, and improves the process response stability score from 0.72 to 0.94. The proposed approach effectively bridges virtual–physical integration across production links, realizing real-time optimization and intelligent decision-making throughout the process, and offering a feasible pathway toward collaborative control in intelligent manufacturing systems.

Povzetek: Študija predlaga enotno proizvodno arhitekturo z digitalnim dvojčkom in napovednim vodenjem (MPC), ki poveže virtualni in fizični proces v zaprto zanko za sprotno usklajevanje, hitrejše odzive ter stabilnejšo in učinkovitejšo optimizacijo proizvodnje.

1 Introduction

With the continuous advancement of intelligent manufacturing, achieving efficient coordination and real-time optimization of production processes has become a central objective for modern manufacturing systems. As the core foundation for cross-level and cross-system data integration and process coordination, the structural integrity and dynamic adaptability of a unified production architecture directly determine the system's response efficiency and the quality of resource allocation [1–2]. Yet most current manufacturing systems still exhibit pronounced architectural fragmentation: information and control flows across hierarchical levels are weakly coupled, leading to pervasive data silos and the absence of unified logical associations among production links [3–4]. Traditional scheduling methods—largely grounded in static rules or preset strategies—depend on predetermined models and offline parameter configurations; they lack the capacity to perceive and respond to environmental changes in real time and therefore struggle to support resource reconfiguration and task reassignment in complex settings [5–6]. Although some studies have introduced the industrial Internet of Things and edge computing to form information closed loops, their limited fidelity in perceiving physical processes constrains continuous process mapping and end-to-end linkage control [7–8]. Meanwhile, mainstream production optimization approaches built on centralized control or multi-objective linear programming encounter bottlenecks when facing high-dimensional, multivariable dynamics, including heavy real-time computational loads, weak model generalization, and lagging control feedback—making high-frequency, full-link dynamic adjustment difficult to sustain [9–10]. Establishing a full-process closed-loop optimization mechanism under a unified architecture thus remains a critical challenge. The key is to develop a pathway that is both real-time and decision-optimal, enabling efficient virtual–physical integration and dynamic control supported by a unified data model [11–12].

As manufacturing moves toward higher intelligence and tighter integration, digital twin technology has emerged as a core enabler. Onaji et al. examined the evolution of digital twin concepts in manufacturing, proposing a conceptual framework for integrated product-process twins and, through three case studies, demonstrated their potential to enhance flexibility, integration, and collaboration [13]. To strengthen adaptability and cross-level collaboration in manufacturing processes, research has progressed from conceptual frameworks to more structured models [14–

15]. Liu Shimin et al. proposed a new reference model for digital-twin-based manufacturing systems (DTMS), analyzing DTMS characteristics and operating mechanisms across hierarchy, dimension, and scale to offer methodological guidance and practical reference models [16]. As model systems mature, systematic syntheses of implementation pathways and mechanisms have become essential to technology transfer [17–18]. Lattanzi et al. reviewed digital twin concepts, technical solutions, and industrial cases in intelligent manufacturing, identifying key implementation elements and challenges and outlining future directions to inform deployment in practice [19]. Despite advances in modeling, frameworks, and applications, notable gaps remain in dynamic model evolution, full-process linkage mechanisms, and cross-domain integration practices [20–21].

In parallel, the literature on unified production architectures and whole-link dynamic optimization has increasingly leveraged digital twins and reinforcement learning to boost responsiveness and overall efficiency in complex systems. Liu Qiang et al. proposed a "configuration–motion–control–optimization" methodology grounded in digital twins, formulating corresponding models for flow-type intelligent manufacturing and validating feasibility and efficiency in an insulating-glass case study [22]. With rising scenario complexity, requirements for real-time response and multi-agent collaboration continue to intensify [23–24]. Zhang et al. developed a digital-twin-driven intelligent workshop community model integrated with hierarchical reinforcement learning to optimize human–machine collaboration ratios, markedly improving adaptability to demand fluctuations and line reconfiguration [25]. Such approaches have expanded from micro-level human–machine coordination to macro-level production organization and resource allocation, underscoring the breadth and flexibility of reinforcement learning in multi-scale manufacturing decision-making [26–27]. Choi et al. employed reinforcement learning coupled with production simulation to optimize factory layouts and processes, reducing logistics costs and AGV requirements within a multilayer optimization framework [28]. Nonetheless, limitations persist—including insufficient algorithm generalization and weak coupling between data-driven optimization and physical systems—hindering full compliance with the stringent demands of end-to-end linkage and dynamic regulation in complex manufacturing scenarios [29–30].

To summarize current progress and gaps, a structured comparison of representative studies related to digital twin-based production optimization is provided in Table 1. Existing works often lack tight coupling between MPC and digital twin frameworks, and they struggle to maintain high-frequency control under multi-stage dynamic conditions.

Table 1: Comparison of existing studies

Reference	Architecture Type	Optimization Method	Digital Twin Integration	Reported Metric (Response / Stability)	Limitation
Liu et al. (2021) [22]	Flow-type Manufacturing	Rule-based + RL	Partial Process Twin	3.4 s / 0.75	No full-chain coordination
Zhang et al. (2023) [25]	Human–Machine Collaboration	Hierarchical RL	Virtual layer only	3.2 s / 0.81	Lack of real-time feedback
Choi et al. (2024) [28]	Factory Layout Optimization	RL-based	Simulation-level	3.0 s / 0.84	No closed-loop control
Proposed Method	Unified Production System	MPC + Digital Twin	Full-link Integration	2.38 s / 0.94	Computational overhead

To overcome the aforementioned challenges, this paper proposes a dynamic optimization method for the entire production process within a unified architecture based on digital twin technology. The method establishes a one-to-one correspondence between physical entities and their virtual counterparts. Real-time production states are captured through sensor data acquisition and time-series synchronization, while a multidimensional feature fusion model dynamically correlates key process parameters to construct a high-fidelity digital twin system. A closed-loop control framework, driven by a virtual controller and the Model Predictive Control (MPC) algorithm, generates dynamic scheduling strategies based on current system states and short-term predictions, transmitting control commands to the physical system in real time. Supported by a unified data platform, the proposed approach integrates data modeling, state perception, prediction, and control, enabling continuous responsiveness and adaptive adjustment under multi-source disturbances. This framework achieves significant advances in unified modeling, control, and architecture, realizing dynamic optimal control of multivariable coupled systems and providing a scalable theoretical and methodological foundation for intelligent industrial deployment.

This research is guided by three key questions. First, can an MPC controller integrated with a digital twin maintain system response delays below 0.85 seconds in multi-stage production scenarios? Second, does the unified production architecture enhance interlink coordination and system stability compared with localized optimization strategies? Third, can the proposed virtual–real closed-loop mechanism achieves dynamic synchronization and process consistency under task variations and external disturbances? The study ultimately aims to enable real-time coordination and adaptive optimization across all production links under varying operating conditions, establishing a unified pathway toward intelligent manufacturing control.

2 Construction of dynamic optimization system driven by digital twins

2.1 Model design principles for unified production architecture

The unified production architecture is designed to eliminate information silos across production links by establishing a clear hierarchical logic, stable data communication, and a virtual–real collaborative framework, thereby enabling dynamic mapping and closed-loop control of the entire process. Built upon digital twin technology, the architecture consists of four functional layers: information perception, data transmission, model computation, and decision execution. The perception layer acquires real-time physical states through multi-dimensional sensor data; the transmission layer ensures low-latency and high-stability communication between physical and virtual systems; the computation layer performs digital twin modeling, state prediction, and optimization through multi-model fusion and adaptive parameter adjustment; and the execution layer applies optimized control strategies to physical entities with real-time feedback correction.

All layers are coordinated under unified scheduling by the platform center, which guarantees time synchronization, data consistency, and iterative optimization of control strategies. It also handles anomaly detection and manages coordination among multi-objective tasks. The overall architecture—together with its information, instruction, and feedback flows—is illustrated in Figure 1, highlighting the central role of the platform in data integration, control transmission, and state correction.

The unified production architecture requires a robust data communication mechanism to integrate multiple protocols and heterogeneous interfaces, ensuring reliable bidirectional transmission of control signals and feedback. Unified parameters, timestamps, and version control maintain consistent status and task alignment across modules. The platform hub incorporates abnormal data detection, redundancy elimination, and parameter alignment to prevent logic interruption and misjudgments from short-term fluctuations. This mechanism enables dynamic response to multi-source information and efficient distribution of control instructions, supporting practical and stable operation. By integrating logical hierarchy, structural modules, and communication protocols, the architecture provides the foundation for real-time perception, predictive control, and closed-loop strategy, ensuring continuous synchronization and consistent virtual–real feedback for digital twin–based dynamic optimization.

2.2 Digital twin modeling and state mapping method

The construction of the digital twin model is founded on high-frequency acquisition of physical system states and deep fusion of multimodal data. To ensure model fidelity, precise correspondence between the virtual and physical entities must be achieved across the data, structural, and behavioral layers. The system continuously samples key operational parameters of the physical process through the deployment of multi-source perception nodes and reconstructs asynchronous data via a time-synchronization module, forming a high-dimensional input vector set suitable for twin-driven computation. Different data sources adopt distinct configurations in sampling frequency, feature extraction strategy, and mapping objectives. The main perception sources and modeling parameter settings are summarized in Table 2.




Figure 1: Unified production architecture model

Table 2: Multi-source data acquisition and feature fusion parameter table

Data Source Type	Perception Node Form	Sampling Frequency	Mapping Target
Industrial Sensors	Temperature, pressure, vibration sensors	10–50 Hz	Construct system physical state vector
Image Capture Unit	Industrial vision cameras	25–30 fps	Assist in operating status recognition and modeling
Control Instruction Stream	PLC (Programmable Logic Controller) or embedded controller interface	Real-time	Behavioral sequence state modeling
Equipment Logs	Industrial control system logging module	1 Hz	Describe evolution trends and prediction input

Table 2 shows the correspondence between the type of sensing node, data collection method, sampling period and its mapping target, reflecting the functional positioning and accuracy requirements of the system for different information channels during the modeling process. Industrial sensors are mainly used to construct the underlying physical state vector, the image acquisition unit focuses on supplementing the spatial information of the operating state, the control instruction stream participates in the behavior layer modeling in the form of encoding, and the equipment log provides time evolution feature support for the prediction model. The collaborative input of multi-source data ensures the comprehensive characterization of the physical entity state by the twin system, and provides a highly consistent modeling basis for subsequent virtual-real synchronous control.

Assuming that the physical entity state is $x_p(t)\in\mathbb{R}^n$ and the perception data set is $D(t)=\{d_1(t),d_2(t),\ldots,d_m(t)\}$, then the state mapping function $f_m(\cdot)$ converts it into a virtual state vector $x_v(t)\in\mathbb{R}^n$, as shown in formula (1):

$$x_v(t)=f_m(D(t))=W\cdot\phi(D(t))+b_1 \quad (1)$$

$W\in\mathbb{R}^{n\times m}$ is the feature mapping weight matrix; $\phi(\cdot)$ represents the nonlinear feature extraction function; $b_1\in\mathbb{R}^n$ is the bias term. The feature extraction function is constructed based on the stacked autoencoder, and its training goal is to minimize the reconstruction error to ensure that the mapping of high-dimensional perception data to low-dimensional state space has sufficient expressive power. Its loss function $\mathscr{L}_{SAE}$ is defined as formula (2):

$$\mathscr{L}_{SAE}=\frac{1}{T}\sum_{t=1}^{T}\|D(t)-\psi(\phi(D(t)))\|^2 \quad (2)$$

$\psi(\cdot)$ is the decoding function and T is the sampling time. After completing the state modeling, the system extracts the dynamic change characteristics of the state sequence through the sliding window mechanism to characterize the evolution law of the physical entity in the time domain. The sliding window length is l; the step length is δ; the state trajectory matrix $X_v^{(t)}=[x_v(t-l+1),\ldots,x_v(t)]\in\mathbb{R}^{n\times l}$ is formed; and the differential operator is introduced to obtain the state change rate, as shown in formula (3):

$$\Delta x_v(t)=x_v(t)-x_v(t-\delta) \quad (3)$$

The update cycle of the state parameters is consistent with the control cycle of the physical system. The system uses the message queue middleware to complete the real-time transmission of state synchronization, and uses the hash verification mechanism to ensure data consistency during the transmission process. In order to maintain the synchronization of the virtual and physical systems at the operation layer, the virtual model feedback control instructions need to be compared for state consistency. The control instructions with differences exceeding the threshold will be marked as mismatched. The system adjusts the prediction weight matrix W and model parameters according to the error correction mechanism. The error correction rules are shown in formulas (4) and (5):

$$W^{(k+1)}=W^{(k)}-\eta\cdot\nabla_W\mathscr{L}_{err} \quad (4)$$

$$\mathscr{L}_{err}=\left\|x_p(t)-x_v(t)\right\|^2 \quad (5)$$

η is the learning rate; $\mathscr{L}_{err}$ is the state error loss function; and $W^{(k)}$ is the weight parameter of the k-th iteration. The error correction mechanism is used to achieve adaptive adjustment of the virtual model, improve the accuracy and stability of the state mapping, and provide an accurate system state basis for subsequent optimization control.

2.3 Design of process dynamic optimization algorithm based on MPC

The dynamic scheduling and optimization of various processes in the unified production architecture rely on the integrated implementation of the model predictive control algorithm. MPC establishes a dynamic model of the controlled system and combines the system state prediction in the future to perform rolling optimization on the control quantity to achieve optimal control of the entire full-link process. The construction of the system optimization objective function is based on multi-dimensional performance indicators such as production process resource allocation, time cost and response accuracy, and introduces prediction error and control quantity change rate as regular terms for adjustment. The objective function form is shown in formula (6):

$$J=\sum_{k=0}^{N_p-1}\|\hat{y}(k|t)-y_{\text{ref}}(k)\|_Q^2+\sum_{k=0}^{N_c-1}\|\Delta u(k|t)\|_R^2 \quad (6)$$

$\hat{y}(k|t)$ is the predicted value of the system output at the k-th step at the prediction time t; $y_{ref}(k)$ is the target reference value at the corresponding time; $\Delta u(k|t)$ is the change in the control quantity at the k-th step; N_p and N_c are the prediction step length and control step length, respectively; Q and R are the weight matrices used to

adjust the relative influence of the state error and the control behavior. The state prediction is modeled in the form of a discrete linear state space model. The system state update equation and output equation are expressed by formulas (7) and (8), respectively:

$$x(t+1)=Ax(t)+Bu(t) \quad (7)$$

$$y(t)=Cx(t)+Du(t) \quad (8)$$

$x(t)$ is the system state vector at time t; $u(t)$ is the input control vector; $y(t)$ is the output vector; A, B, C, and D are the system state transfer matrix, input control matrix, output mapping matrix, and direct transfer matrix, respectively, all of which are obtained by system identification of the physical system process data. In order to ensure that the system meets physical constraints and resource limitations in actual operation, hard constraints such as those shown in formulas (9) and (10) are introduced for boundary control:

$$u_{\min}\le u(t)\le u_{\max} \quad (9)$$

$$y_{\min}\le y(t)\le y_{\max} \quad (10)$$

In formula 9-10, $u_{\min}$ and $u_{\max}$ are the upper and lower limits of the control variables. $y_{\min}$ and $y_{\max}$ are the limit ranges of the output variables, and all constraints are derived from the process requirements of each process segment in the unified production architecture and the safety boundaries of equipment operation. On the basis of hard constraints, the system also introduces a soft constraint mitigation strategy, setting penalty function terms for some variables. When the control variable breaks through the boundary in the short term but the overall operation is still within the tolerance range, the objective function value is adjusted through the Lagrange multiplier mechanism to maintain a balance between optimization convergence and response flexibility.

During system operation, abnormal disturbances and model deviations are inevitable. To enhance the stability and robustness of the MPC controller, a disturbance detection mechanism is embedded in the platform center to identify persistent prediction errors, adjust model weights through feedback, and perform adaptive correction. The real-time deviation between virtual and physical states guides iterative updates of the weight matrix and controller parameters, ensuring control convergence under dynamic disturbances.

To mitigate the high computational complexity of MPC in multivariable scenarios, the optimization module employs a fast interior-point algorithm for constrained quadratic programming while restricting iteration counts within each control cycle. For scenarios with stringent real-time requirements, the system dynamically switches to approximate or reduced-order solutions to guarantee timely responses. Furthermore, a multi-step rolling prediction mechanism continuously updates system states and re-optimizes control sequences, forming a high-frequency closed-loop interaction between the virtual and physical systems.

This integrated optimization framework significantly enhances resource utilization, scheduling responsiveness, and operational stability throughout the entire production process.

2.4 Integrated implementation of virtual-real closed-loop control mechanism

The implementation of the virtual-real closed-loop control mechanism relies on multi-level system integration and standardized communication protocol support under a unified production architecture. The digital twin system and the physical production system realize two-way interaction of data and instructions through industrial protocols such as OPC UA (Open Platform Communications Unified Architecture) and MQTT (Message Queuing Telemetry Transport), forming an integrated control channel. The perception layer in the physical system collects various state parameters in real time, including equipment operation status, production process parameters and environmental variables, and transmits them to the data access module through the data bus, and uploads them to the digital twin platform after preprocessing. Based on a unified data model, the digital twin platform maps the collected state parameters to entity nodes in the virtual environment, generates state snapshots equivalent to the physical system, and dynamically updates them in the form of time series.

In the virtual space, the decision module generates an instruction stream $\mathbf{C_t}=\{c_{t,1},c_{t,2},...,c_{t,m}\}$ based on the current system state and the preset global scheduling strategy, where $c_{t,i}$ represents the control instruction sent to the i-th unit of the physical system at time t. The instruction stream is encapsulated as a standard message through the communication scheduling module of the interface layer, and is sent to the physical system after being sorted by priority and timestamp. After the physical system receives the control instruction, it parses it through the field controller and drives the actuator to complete the action, such as adjusting the drive shaft speed, opening and closing the fixture, and modifying the process parameters. Each execution unit immediately generates a feedback signal $\mathbf{F_t}=\{f_{t,1}f_{t,2},...,f_{t,m}\}$ after the action is completed. The feedback signal contains the execution status identifier, the action completion timestamp and the error report. The feedback link is uploaded to the digital twin platform through the same communication protocol to update the system status.

After receiving feedback, the virtual-real closed-loop scheduling engine compares the real-time state $\mathbf{S}_t$ with the predicted state $\hat{\mathbf{S}}_t$, and the error term $\mathbf{E}_t=\mathbf{S}_t-\hat{\mathbf{S}}_t$ is sent to the deviation compensation module of the scheduling engine. If $\|\mathbf{E_t}\|$ exceeds the set threshold, the system will trigger the error adaptive adjustment logic to make subsequent predictions more consistent with actual feedback by correcting the control instruction weight matrix or adjusting the virtual model parameters.

The system status update and instruction issuance process runs in a fixed cycle to form a closed-loop control flow of continuous iteration. The iterative optimization strategy in the virtual model takes real-time feedback as input, adjusts the prediction results through the historical data sliding window $W_t=\{\mathbf{S}_{t-n},...,\mathbf{S}_t\}$, generates the control instructions for the next cycle and sends them to the physical system. The overall operation logic of the virtual-

real closed-loop system is managed by the scheduling main control module, realizing the full-link closed-loop control process from data perception, virtual mapping, decision generation, control issuance to feedback transmission, ensuring the real-time consistency and response accuracy of the virtual model and the physical system in various links such as state mapping, instruction execution, and feedback update, and providing support for the dynamic optimization and adaptive scheduling of the system.

3 Experimental system and verification environment construction

3.1 Experimental platform architecture and software and hardware configuration

The construction of the experimental system relies on high-performance hardware support and multi-level software system collaboration. The overall architecture covers modules such as data acquisition, transmission, processing and control to ensure dynamic optimization and real-time response capabilities of the entire production process. The components of the system are connected through high-speed communication links to achieve efficient interaction between the physical system and the virtual twin platform. In order to further clarify the composition and functions of the experimental platform, the core hardware and software configurations are listed.

Table 3: Hardware and software configuration of the experimental platform

Module Category	Specifications	Hardware/Software	Functional Description
Sensor Unit	0.01 mm resolution	Industrial sensor	Real-time acquisition of physical state data
Communication Module	100 Mbps	Industrial Ethernet	High-speed data transmission and interaction
Control Platform	Multi-core processor	MATLAB/Simulink	Runs MPC algorithm and decision logic
Data Processing Module	32 GB memory	Python environment	Multi-source data fusion and feature extraction
Digital Twin Engine	3D modeling engine	Unity3D	Digital mapping of the physical system

Table 3 shows the functional division and configuration parameters of each module in the experimental platform, covering the sensor unit, communication module, control platform, data processing module and virtual twin engine. It clarifies the specifications, operating environment and core functions adopted by each module, providing basic support for subsequent experimental verification and results analysis.

3.2 Construction process of digital twin system

The digital twin system is built around multi-dimensional state mapping and real-time interaction with the physical production system. A virtual model is first constructed, defining node structure, attribute variables, and state transfer logic to match the spatial, functional, and dynamic characteristics of the physical system. Multi-source sensing nodes collect real-time data on equipment status, production flow, environmental variables, and energy consumption at 100 Hz, with timestamp-based synchronization. TSN protocol ensures low-latency, high-reliability transmission, while edge preprocessing performs format conversion, anomaly detection, and noise filtering, standardizing data in JSON format for the data center. The twin system interfaces with the physical system via OPC UA, issuing control instructions and receiving status updates. State updates occur every second, with millisecond-level WebSocket communication. Object-oriented modeling integrates geometry, kinematics, and dynamics in Unity3D with a real-time physics engine. Kalman filtering smooths data and compensates anomalies, keeping virtual and physical states within 1% error. MPC-based predictive optimization generates control instructions sent via the industrial bus, completing closed-loop control. Docker-based deployment enables module decoupling, hot-swapping, model updates, and flexible maintenance.

3.3 Definition and implementation of the full-link path of the production process

The full-link process ensures continuity and synchronization across modules in the unified production architecture. By defining process nodes in both physical and virtual environments, cross-level and cross-device control links maintain consistent data and control logic transmission. The process is divided into five stages—raw material delivery, primary processing, quality inspection, finished product assembly, and packaging—each with state acquisition, control execution, and feedback analysis modules. The main control unit monitors state variables and releases scheduling instructions, while the process state transfer matrix and control strategy library define logical relationships. Inputs and outputs are standardized for rapid parsing, and MPC-based scheduling allows real-time adaptive adjustment to task changes or resource conflicts. Key-node control strategies are transmitted via the twin model interface to ensure virtual–real consistency, forming a stable, efficient, low-latency closed-loop

system that coordinates task switching, state transfer, and command execution throughout the entire production path. Table 4 shows the configuration of each link and the corresponding core control variables.

Table 4: Configuration parameter table of the full-link production path control structure

Link ID	Production Stage	State Acquisition Parameters	Control Command Variables	Feedback Mechanism Delay (s)
P01	Raw Material Feeding	Sensor Weight, Silo Capacity	Feeding Speed, Start-End Time	0.61
P02	Primary Processing	Spindle Speed, Processing Temperature	Tool Feed Rate, Cooling Frequency	0.74
P03	Quality Inspection	Image Recognition Result, Dimensional Deviation	Inspection Frequency, Movement Path	0.69
P04	Final Assembly	Component Position, Assembly Torque	Assembly Sequence, Fixture Pressure	0.85
P05	Packaging and Dispatch	Barcode Recognition, Inventory Status	Packaging Mode, Dispatch Rhythm	0.76

Table 4 shows the state perception parameters, applied control variables and time delay of feedback mechanism required for each process node in actual operation based on five major production links. Each link is bound to a specific set of sensor data and execution instructions, and the logical mapping relationship between them is maintained and updated in real time by the system main control unit. The feedback delay reflects the time deviation between the physical system response and the twin model regulation in virtual-real collaboration.




Figure 2 State perception accuracy diagram

Figure 2 (a) Comparison of multi-source data perception errors

Figure 2 (b) State parameter error distribution statistics

4 Results analysis

4.1 State perception accuracy analysis

In order to verify the perception accuracy of the digital twin system for key state parameters, the experimental design introduces five core physical variables, namely temperature, pressure, speed, liquid level, and flow rate, as analysis objects, selects three types of sensors for multi-source information collection, and generates a unified state expression model through the data fusion module. Sensor A is based on the principle of thermal resistance and piezoelectric sensitivity, with fast response speed but large signal fluctuations; sensor B adopts MEMS (Micro-Electro-Mechanical Systems) structure and performs stably in the medium and low frequency bands; sensor C is an industrial-grade precision equipment with high accuracy but is more sensitive to environmental interference. The fusion model realizes multi-source feature collaborative modeling through a weighted residual mechanism to improve the recognition accuracy and fluctuation suppression ability of state parameters. Through the two-part analysis of perception error comparison and state modeling error distribution, the performance of various data sources and fusion models under different state parameters is systematically revealed, as shown in Figure 2.

From Figure 2 (a), we can see that the recognition error of the fusion model on all state parameters is significantly lower than that of a single sensor. The temperature perception error is reduced from 3.2% of sensor A to 1.4%, which is mainly due to the enhanced compression ability of random noise after data fusion. The error control effect of flow is relatively weak, and it remains at 2.0% after fusion. The reason is that the flow sensor has a delayed response under boundary conditions, which affects the data alignment accuracy. Figure 2 (b) shows that the maximum errors of pressure and flow are 2.5% and 2.7%, respectively. The main reason is that such variables are more sensitive to transient disturbances, and some original data have large fluctuations, which is not conducive to stable modeling. The median errors of temperature and speed are controlled within 1.5%, showing the robustness of fusion modeling for periodic variable recognition. The overall results show that multi-source information fusion significantly improves parameter accuracy in the state perception stage and effectively suppresses error fluctuations in single-source measurement.

4.2 Analysis of dynamic scheduling response capability

In order to verify the performance of the proposed MPC optimization strategy in dynamic task scheduling and system response, the experiment designed multiple rounds of scheduling control tests, running the MPC strategy and the traditional scheduling strategy respectively through a unified platform, and recording the two key indicators of system response delay and task switching time in real time. In each round of task switching, the scheduling control system needs to reallocate production resources and drive the physical execution unit to complete the switching operation, thereby forming a complete data closed loop. Traditional methods rely on static rules and predefined paths, lacking the ability to dynamically perceive and roll forward the system state, while the MPC strategy dynamically generates a control sequence based on the current state and predicted trajectory, thus forming a comparison group. After completing 10 consecutive rounds of scheduling under unified experimental conditions, the above two performance indicators are collected and summarized, and the results are shown in Figure 3.




Figure 3: Dynamic scheduling performance comparison
Figure 3 (a): System response delay change trend
Figure 3 (b): Task switching time change trend

The overall system response delay under the MPC strategy remains stable at approximately 0.8 seconds, with the maximum not exceeding 0.83 seconds. In contrast, the traditional control strategy exhibits a response delay exceeding 1.2 seconds in most cycles, with peak values reaching 1.31 seconds. This improvement arises from the MPC's ability to dynamically adjust control instructions based on real-time state feedback, thereby minimizing system waiting time and reducing conflicts in resource allocation to enhance response efficiency.

Regarding task switching, the MPC-controlled system maintains switching durations between 2.32 and 2.43 seconds, exhibiting minimal fluctuation, whereas the traditional method averages around 3.6 seconds, indicating a clear disparity. The traditional approach lacks a rolling planning mechanism when handling task continuity, resulting in redundant waiting periods between successive control instructions and producing discontinuities in switching processes.

In summary, the MPC-based strategy markedly enhances response stability, resource reconfiguration efficiency, and overall adaptability in dynamic task scheduling scenarios.

4.3 Virtual-real mapping consistency verification

In the control link of the unified production architecture, the accuracy and timeliness of the virtual model directly affect the execution effect of the physical system. In order to verify the effectiveness of the digital twin system in generating control instructions and analyze the dynamic response differences between it and the actual physical execution, this experiment selected three key control variables: speed, temperature, and flow rate, and compared the predicted control values generated by the MPC algorithm in the virtual system with the response values sent back by the physical system sensors in time series. By collecting bidirectional control signals under a unified operating cycle and drawing synchronous curves, the mapping consistency verification diagram between the virtual and real systems shown in Figure 4 is constructed.




Figure 4: Virtual and real system command and response comparison curve
Figure 4 (a): Virtual and real speed comparison
Figure 4 (b):. Virtual and real temperature comparison
Figure 4 (c): Virtual and real flow comparison

Figure 4 shows that the virtual system closely tracks the physical response with minor deviations. At time of 6 s, a 1270 RPM command corresponds to a 1252 RPM physical response, with an 18 RPM lag due to motor regulation delay and inertial load. Temperature control at the same moment shows a 1.0 ℃ difference (72.1 ℃ virtual vs. 71.1 ℃ physical) caused by uneven heat capacity and delayed local heat exchange. At time of 8 s, flow reaches 90 L/min virtually and 88 L/min physically, with the 2 L/min difference attributed to servo valve hysteresis and pressure rebound. These deviations result from the internal dynamics and external coupling of the physical system rather than model prediction errors, demonstrating that the current digital twin modeling method provides stable, real-time system-level reflection.

4.4 Process optimization stability and convergence performance

To validate the process stability of the proposed digital twin–MPC fusion method in actual control scenarios, an experimental process system was constructed encompassing multiple representative operating conditions, including task switching, resource scheduling, and state regression. By comparing process response data before and after the implementation of the optimized control strategy, key performance indicators—such as task delay, control error, state recovery time, and system throughput under varying operating conditions—

were collected and quantitatively evaluated. These metrics were used to comprehensively assess the system's operational stability under dynamic disturbance conditions from multiple dimensions.

During the experiment, a unified data acquisition interface was employed to continuously record process control logs throughout the entire operation cycle. A structured data processing method was then applied to extract numerical features related to stability performance. The comparative results are illustrated in Figure 5, demonstrating the stability improvements achieved through the proposed optimization control framework.




Figure 5: Comparison of process control stability

Figure 5 illustrates that, after applying the optimized control strategy, the process system's response delay stability increased to 0.94 (an improvement of 0.22), reflecting the predictive scheduling capability of the MPC framework. The instruction execution consistency between the virtual model and the physical system improved from 0.68 to 0.92, attributed to accurate multi-source data fusion and synchronization. The state regression index rose from 0.65 to 0.90, indicating that the closed-loop control rapidly corrected process disturbances. Meanwhile, control error stability improved from 0.70 to 0.93, demonstrating reduced parameter drift under MPC constraints. Throughput stability increased from 0.74 to 0.96, driven by coordinated scheduling that enhanced inter-unit linkage and output uniformity. Collectively, these improvements highlight the multi-dimensional advantages of precise modeling, predictive control, and collaborative feedback within the proposed optimization strategy.

When compared with reinforcement-learning-based optimization methods reported in [22], [25], and [28], which exhibit average task switching times of 3.1–3.4 seconds and stability indices of 0.80–0.84, the proposed approach achieves a switching time range of 2.32–2.43 seconds and a stability index of 0.94 under comparable task intensities. The performance gains are primarily attributed to the direct integration of the digital twin model with the MPC framework, enabling predictive scheduling and continuous correction of control commands. Overall, the full-link MPC–digital twin strategy demonstrates approximately 28% faster response and 12% higher stability compared with state-of-the-art reinforcement-learning-based approaches.

4.5 Robustness verification under disturbance conditions

To validate the robustness of the proposed system under complex disturbances, tests were conducted by introducing three scenarios: variable load fluctuations, sensor noise interference, and actuator failure recovery. The load fluctuation amplitude was set at ±15% of nominal torque, Gaussian white noise with 0.02 variance was added to the sensor signal, and a 3-second actuator disconnection was simulated to represent temporary equipment fault. The performance metrics included average response delay, control output deviation, and recovery time after disturbance. Table 5 presents the test results.

Table 5: Robustness test results under different disturbance conditions

Disturbance Scenario	Average Response Delay (s)	Output Deviation (%)	Recovery Time (s)
Baseline (No Disturbance)	0.83	0.0	0.0
Load Fluctuation ±15%	0.87	3.1	1.8
Sensor Noise 0.02 Var	0.89	2.4	1.3
Actuator Failure (3 s)	0.94	4.2	3.2

Under all disturbance scenarios, the system maintained stable operation without oscillation or divergence. The maximum delay increase did not exceed 0.11 seconds, and the system recovered normal response within 3.2 seconds. These results demonstrate that the proposed full-link control mechanism maintains effective dynamic correction and control convergence under multi-source interference and temporary component faults.

4.6 Comparative analysis with existing methods

To demonstrate the improvement of the proposed full-link production optimization over conventional localized optimization strategies, comparative experiments were conducted between the unified digital twin–MPC method and three representative approaches: traditional rule-based scheduling, subsystem-level MPC control, and hierarchical optimization. All experiments were performed under the same hardware and control configurations described in Section 3.1. Each method

executed ten rounds of dynamic task switching, and the key metrics included response delay, task switching time, stability index, and interlink coordination performance. Table 6 shows the comparative results.

Table 6: Comparative performance between the proposed full-link optimization and existing methods

Control Method	Average Response Delay (s)	Task Switching Time (s)	Stability Index	Interlink Coordination Index
Rule-based Scheduling	1.27	3.62	0.72	0.70
Local MPC Control	0.96	3.05	0.81	0.83
Hierarchical Scheduling	0.89	2.84	0.86	0.87
Proposed Full-link MPC-DT	0.83	2.38	0.94	0.95

The results indicate that the proposed method achieves faster overall response and stronger cross-link coordination than existing approaches. The stability index improves by 16% on average compared with hierarchical scheduling, and the response delay is reduced by 12%. The improvement stems from the unified data modeling and the closed-loop control mechanism that synchronizes process-level prediction and physical execution.

To further validate the effectiveness of the proposed unified digital twin–MPC strategy, additional simulations were performed against several advanced control approaches commonly used in nonlinear and uncertain systems, namely adaptive fuzzy control, neural adaptive control, and nonlinear optimal control. All algorithms were implemented under identical plant models and boundary constraints, and the evaluation indicators included steady-state error, convergence time, and collaborative control index. Table 7 shows the results of comparative simulations.

Table 7: Comparison with advanced control methods

Control Method	Steady-state Error (%)	Convergence Time (s)	Collaborative Control Index
Adaptive Fuzzy Control	3.2	3.54	0.83
Neural Adaptive Control	2.7	3.22	0.85
Nonlinear Optimal Control	2.4	3.10	0.86
Proposed MPC-Digital Twin	1.8	2.38	0.95

The results show that the proposed approach reduces steady-state error by 25%–40% and shortens convergence time by approximately 30% compared with the other advanced control methods. The improvement arises from the integration of multi-source perception data and the closed-loop virtual-real feedback, which enhances global coordination and real-time optimization across the production chain.

5 Discussion

The experimental results indicate that integrating the digital twin with MPC yields superior dynamic performance through multi-source data fusion and real-time, closed-loop correction. Under the proposed strategy, response delay remains ~0.8 s (max 0.83 s) versus >1.2 s for the traditional baseline (max 1.31 s), and task switching time concentrates tightly within 2.32–2.43 s rather than ~3.6 s. Stability metrics also improve markedly (e.g., response-delay stability to 0.94, execution consistency to 0.92, state-regression index to 0.90, and throughput stability to 0.96). These gains arise from rolling-horizon prediction and synchronized virtual–physical feedback that continuously refines control commands, thereby shortening waiting times, reducing resource-conflict arbitration, and preserving coherent switching trajectories.

Relative to adaptive fuzzy and neural adaptive controls, the proposed framework benefits from explicit predictive modeling and online optimization rather than post-hoc rule or parameter adaptation. Compared with reinforcement-learning-based methods in comparable settings, which report 3.1–3.4 s average switching and 0.80–0.84 stability, the proposed approach achieves 2.32–2.43 s switching and 0.94 stability—about 28% faster with ~12% higher stability. Mechanistically, MPC's constraint-aware predictions, coupled with the twin's high-fidelity state representation and multi-modal synchronization, enable proactive schedule updates and rapid correction of incipient deviations, whereas policy-based methods can suffer from distribution shift and delayed recovery outside their training manifold.

Scalability is chiefly constrained by computational burden as the number of coupled variables grows: dense matrix factorizations and constrained QP solves within tight cycles can challenge real-time guarantees beyond ~20 units. Mitigations include (i) hierarchical/distributed MPC to localize solves, (ii) reduced-order or surrogate models to compress dynamics for faster predictions, (iii) move-blocking, warm-starts, and limited-iteration interior-point updates to bound solve time, and (iv) parallelization or hardware acceleration for the optimization kernel. These measures preserve the closed-loop benefits while extending the operating envelope to

larger lines or multi-cell plants.

The framework assumes reliable communications and sensor synchronization; under severe packet loss, drift, or actuator faults, the platform's recovery logic sustains stability but may degrade optimality. Future work will target robustness and adaptability on three fronts: (1) robust/tube MPC to explicitly hedge model and measurement uncertainty, (2) adaptive neural predictors (e.g., twin-consistent, online-updated surrogates) to capture nonlinearities and aging effects without sacrificing solve time, and (3) anomaly-aware scheduling that co-optimizes control performance with data quality, enabling graceful degradation and rapid re-synchronization after faults.

Overall, the evidence supports the twin-coupled MPC as a practical route to full-link dynamic optimization: it improves response stability and resource reconfiguration efficiency while maintaining process consistency under disturbances. With the proposed scalability and robustness enhancements, the architecture offers a credible, extensible pathway for industrial deployment across heterogeneous manufacturing scenarios.

6 Conclusion

This paper proposes a dynamic optimization method for full-link production processes within a unified architecture leveraging digital twin technology. Integrating perception modeling, rolling control, and closed-loop scheduling, the method employs a model predictive control (MPC) algorithm to generate multi-process scheduling strategies and feedback execution, achieving full-chain coordination of control logic and state information through multi-source perception and virtual–real mapping. Experimental results demonstrate significant advantages over traditional strategies: task switching times are maintained between 2.32–2.43 s, system response delays remain below 0.83 s, process stability improves from 0.72 to 0.94, and virtual–physical instruction consistency increases from 0.68 to 0.92. The proposed approach effectively addresses delayed responses in high-frequency, multivariable scenarios.

Future work will focus on incorporating dynamic parameter updates and disturbance-adaptive models to enhance fault tolerance and generalizable scheduling across large-scale, heterogeneous systems. Comparative experiments further confirm the method's superiority in response speed, stability, and collaborative coordination relative to localized or subsystem-level control strategies.

References

[1] Latsou, Christina, Dedy Ariansyah, Louis Salome, John Ahmet Erkoyuncu, Jim Sibson, and John Dunville. A unified framework for digital twin development in manufacturing. Advanced Engineering Informatics, 62:102567, 2024. https://doi.org/10.1016/j.aei.2024.102567

[2] Fu, Yang, Gang Zhu, Mingliang Zhu, and Fuzhen Xuan. Digital twin for integration of design-manufacturing-maintenance: an overview. Chinese Journal of Mechanical Engineering, 35(1):80, 2022. https://doi.org/10.1186/s10033-022-00760-x

[3] Van Dyck, Marc, Dirk Luttgens, Frank T. Piller, and Sebastian Brenk. Interconnected digital twins and the future of digital manufacturing: insights from a Delphi study. Journal of Product Innovation Management, 40(4):475–505, 2023. https://doi.org/10.1111/jpim.12685

[4] Cheng, Xun, Feihong Huang, Qiming Yang, and Linqiong Qiu. A digital twin data management and process traceability method for the complex product assembly process. Journal of the Brazilian Society of Mechanical Sciences and Engineering, 47(3):151, 2025. https://doi.org/10.1007/s40430-025-05466-4

[5] Chang, Xiao, Xiaoliang Jia, Shifeng Fu, Hao Hu, and Kuo Liu. Digital twin and deep reinforcement learning enabled real-time scheduling for complex product flexible shop-floor. Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture, 237(8):1254–1268, 2023. https://doi.org/10.1177/09544054221121934

[6] Corsini, Roberto Rosario, Antonio Costa, Sergio Fichera, and Jose M. Framinan. Digital twin model with machine learning and optimization for resilient production–distribution systems under disruptions. Computers & Industrial Engineering, 191:110145, 2024. https://doi.org/10.1016/j.cie.2024.110145

[7] Kang, Min-Su, Dong-Hee Lee, Mahdi Sadeqi Bajestani, Duck Bong Kim, and Sang Do Noh. Edge computing-based digital twin framework based on ISO 23247 for enhancing data processing capabilities. Machines, 13(1):19, 2024. https://doi.org/10.3390/machines13010019

[8] Li, Yajun, Wei Liu, Yang Zhang, Wenlong Zhang, Changyong Gao, and Qihang Chen. Interactive real-time monitoring and information traceability for complex aircraft assembly field based on digital twin. IEEE Transactions on Industrial Informatics, 19(9):9745–9756, 2023. https://doi.org/10.1109/TII.2023.3234618

[9] Karkaria, Vispi, Anthony Goeckner, Rujing Zha, Jie Chen, Jianjing Zhang, Qi Zhu, et al. Towards a digital twin framework in additive manufacturing: machine learning and Bayesian optimization for time series process optimization. Journal of Manufacturing Systems, 75:322–332, 2024. https://doi.org/10.1016/j.jmsy.2024.04.023

[10] Liu, Chao, Leopold Le Roux, Carolin Korner, Olivier Tabaste, Franck Lacan, and Samuel Bigot. Digital twin-enabled collaborative data management

for metal additive manufacturing systems. Journal of Manufacturing Systems, 62:857–874, 2022. https://doi.org/10.1016/j.jmsy.2020.05.010

[11] Xie, Jieyu, and Jiafu Wan. Digital twin four-dimension fusion modeling method design and application to the discrete manufacturing line. Big Data and Cognitive Computing, 7(2):89, 2023. https://doi.org/10.3390/bdcc7020089

[12] Ye, Xun, Wenjun Xu, Jiayi Liu, Yi Zhong, Quan Liu, Zude Zhou, et al. Implementing digital twin and asset administration shell models for a simulated sorting production system. IFAC-PapersOnLine, 56(2):11880–11887, 2023. https://doi.org/10.1016/j.ifacol.2023.10.600

[13] Onaji, Igiri, Divya Tiwari, Payam Soulatiantork, Boyang Song, and Ashutosh Tiwari. Digital twin in manufacturing: conceptual framework and case studies. International Journal of Computer Integrated Manufacturing, 35(8):831–858, 2022. https://doi.org/10.1080/0951192X.2022.2027014

[14] Yao, Jun-Feng, Yong Yang, Xue-Cheng Wang, and Xiao-Peng Zhang. Systematic review of digital twin technology and applications. Visual Computing for Industry, Biomedicine, and Art, 6(1):10, 2023. https://doi.org/10.1186/s42492-023-00137-4

[15] Attaran, Mohsen, Sharmin Attaran, and Bilge Gokhan Celik. The impact of digital twins on the evolution of intelligent manufacturing and Industry 4.0. Advances in Computational Intelligence, 3(3):11, 2023. https://doi.org/10.1007/s43674-023-00058-y

[16] Liu, Shimin, Pai Zheng, and Jinsong Bao. Digital twin-based manufacturing system: a survey based on a novel reference model. Journal of Intelligent Manufacturing, 35(6):2517–2546, 2024. https://doi.org/10.1007/s10845-023-02172-7

[17] Karkaria, Vispi, Ying-Kuan Tsai, Yi-Ping Chen, and Wei Chen. An optimization-centric review on integrating artificial intelligence and digital twin technologies in manufacturing. Engineering Optimization, 57(1):161–207, 2025. https://doi.org/10.1080/0305215X.2024.2434201

[18] Wang, Yuchen, Xinheng Wang, Ang Liu, Junqing Zhang, and Jinhua Zhang. Ontology of 3D virtual modeling in digital twin: a review, analysis and thinking. Journal of Intelligent Manufacturing, 36(1):95–145, 2025. https://doi.org/10.1007/s10845-023-02246-6

[19] Lattanzi, Luca, Roberto Raffaeli, Margherita Peruzzini, and Marcello Pellicciari. Digital twin for smart manufacturing: a review of concepts towards a practical industrial implementation. International Journal of Computer Integrated Manufacturing, 34(6):567–597, 2021. https://doi.org/10.1080/0951192X.2021.1911003

[20] Elgebaly, Hamdy, Basma Elhariry, Amr Noureldin, and Doaa Stohy. Digital twin for maintenance and smart manufacturing: the mediating role of replacement maintenance in the Saudi industrial sector. Journal of Lifestyle and SDGs Review, 5(4):06107–06107, 2025. https://doi.org/10.47172/2965-730X.SDGSREVIEW.V5.N04.PE06107

[21] Alfaro-Viquez, David, Mauricio Zamora-Hernandez, Michael Fernandez-Vega, Jose Garcia-Rodriguez, and Jorge Azorin-Lopez. A comprehensive review of AI-based digital twin applications in manufacturing: integration across operator, product, and process dimensions. Electronics, 14(4):646, 2025. https://doi.org/10.3390/electronics14040646

[22] Liu, Qiang, Jiewu Leng, Douxi Yan, Ding Zhang, Lijun Wei, Ailin Yu, et al. Digital twin-based designing of the configuration, motion, control, and optimization model of a flow-type smart manufacturing system. Journal of Manufacturing Systems, 58:52–64, 2021. https://doi.org/10.1016/j.jmsy.2020.04.012

[23] Wang, Likun, Zi Wang, Kevin Gumma, Alison Turner, and Svetan Ratchev. Multi-agent cooperative swarm learning for dynamic layout optimisation of reconfigurable robotic assembly cells based on digital twin. Journal of Intelligent Manufacturing, 1–24, 2024. https://doi.org/10.1007/s10845-023-02229-7

[24] Marah, Hussein, and Moharram Challenger. Adaptive hybrid reasoning for agent-based digital twins of distributed multi-robot systems. Simulation, 100(9):931–957, 2024. https://doi.org/10.1177/00375497231226436

[25] Zhang, Rong, Jianhao Lv, Jinsong Bao, and Yu Zheng. A digital twin-driven flexible scheduling method in a human–machine collaborative workshop based on hierarchical reinforcement learning. Flexible Services and Manufacturing Journal, 35(4):1116–1138, 2023. https://doi.org/10.1007/s10696-023-09498-7

[26] Kalyani, Yogeswaranathan, and Rem Collier. The role of multi-agents in digital twin implementation: short survey. ACM Computing Surveys, 57(3):1–15, 2024. https://doi.org/10.1145/3697350

[27] Nie, Qingwei, Dunbing Tang, Haihua Zhu, and Hongwei Sun. A multi-agent and Internet of Things framework of digital twin for optimized manufacturing control. International Journal of Computer Integrated Manufacturing, 35(10–

11):1205–1226, 2022. https://doi.org/10.1080/0951192X.2021.2004619

[28] Choi, Hyekyung, Seokhwan Yu, DongHyun Lee, Sang Do Noh, Sanghoon Ji, Horim Kim, et al. Optimization of the factory layout and production flow using production-simulation-based reinforcement learning. Machines, 12(6):390, 2024. https://doi.org/10.3390/machines12060390

[29] Li, Yibing, Zhiyu Tao, Lei Wang, Baigang Du, Jun Guo, and Shibao Pang. Digital twin-based job shop anomaly detection and dynamic scheduling. Robotics and Computer-Integrated Manufacturing, 79:102443, 2023. https://doi.org/10.1016/j.rcim.2022.102443

[30] Liu, Lilan, Kai Guo, Zenggui Gao, Jiaying Li, and Jiachen Sun. Digital twin-driven adaptive scheduling for flexible job shops. Sustainability, 14(9):5340, 2022. https://doi.org/10.3390/su14095340

Fuzzy Cluster Analysis-Based Methodology for Software and Hardware Selection in Cloud Infrastructure with Unified Information Space

Yulii Kondratenko, Yurii Kirpichnikov, Andrii Romaniuk, Ivan Kryvoruchko, Oleh Onofriichuk
Centre for Military and Strategic Studies, National Defence University of Ukraine, 03049, 28 Povitryaflotskiy Ave., Kyiv, Ukraine
E-mail: yuliikondratenko@gmail.com, y.kirpichnikov@outlook.com, an_romaniuk@hotmail.com, i-kryvoruchko@outlook.com, oleh.onofriichuk@hotmail.com

Keywords: choice optimisation, data uncertainty, resource optimisation, mathematical modelling, adaptive algorithms, performance criteria.

Received: March 23, 2025

The research established a methodological framework for assessing and choosing software and hardware configurations for cloud infrastructure within a cohesive information space, employing the fuzzy c-means clustering algorithm. The principal obstacle tackled was the complexity of decision-making among ambiguity, a common occurrence in intricate IT system planning. The methodology incorporated a multi-criteria evaluation framework, encompassing performance, cost, scalability, reliability, and security, utilising fuzzy logic to address data ambiguity and expert subjectivity. A comparative analysis was performed utilising conventional approaches including AHP, TOPSIS, and Mamdani fuzzy inference. Empirical testing was conducted utilising configuration files from five prominent cloud service providers, analysing 60 distinct setups. The methodology enhanced evaluation precision by 23% and diminished expert subjectivity by 31% relative to traditional methods. The fuzzy clustering technique discerned three ideal configurations (high-performance, balanced, and cost-effective) that enhanced computer resource utilisation by 18% and diminished cloud infrastructure setup and maintenance expenses by 22%. These findings highlight the efficacy of fuzzy cluster analysis in facilitating dependable, adaptive, and resource-efficient decision-making for the design and optimisation of cloud ecosystems.

Povzetek: Raziskava predstavi metodo na osnovi mehke logike in gručenja za bolj zanesljivo in učinkovito izbiro konfiguracij oblačne infrastrukture, ki zmanjša subjektivnost odločanja ter izboljša izrabo virov in stroškovno učinkovitost.

1 Introduction

The development of information technology and the rapid growth of data volumes are creating new challenges for organisations seeking to effectively manage their information technology resources. Cloud computing has become a primary method for solving these problems, providing access to computing resources and data from anywhere and at any time. However, the selection of the optimal set of software and hardware tools to create a cloud environment with a single information space remains a complex task. Existing methods often fail to address the complexity of the interaction of various factors and the dynamic nature of cloud environments. They also struggle to effectively integrate quantitative and qualitative evaluation criteria, accommodate input data uncertainty, and ensure adaptive resource planning in a single information space.

This problem is particularly relevant in the context of deploying information infrastructure in critical industries such as defence. The experience of the Ministry of Defence of Ukraine in creating a private cloud demonstrates the importance of choosing an integration platform that allows for efficient data exchange between distributed information systems and managing complex business processes. The private cloud enables unified and standardised service delivery, providing the necessary flexibility and cost savings for deploying information systems, fast resource allocation and reliable access to application services.

Y.A. Kirpichnikov et al. [1] substantiated the use of a data-centric approach to create a single information space for the defence forces. The authors proposed a model that can describe a set of interacting processes in a single information space and can be used to determine the requirements for information systems when building a defence information infrastructure. This approach aims to increase the speed, accuracy and quality of decision-making, which are critical for strategic decisions and the success of operations and combat operations.

The issue of optimal solutions for cloud infrastructure has been extensively explored by researchers, focusing on the integration of cloud, fog, and edge computing to create a unified information space. R. Buyya and S.N. Srirama [2] highlighted the necessity of developing new evaluation and selection methods for software and hardware that specifically address the unique challenges of distributed computing environments. They argue that such integration

can enhance data processing efficiency and reduce latency by leveraging the proximity of edge devices to data sources. Similarly, S.S. Gill et al. [3] examined the impact of emerging technologies on cloud computing and stressed the importance of adaptive evaluation methods for cloud environments. Their findings suggest that adaptive methods can dynamically adjust to varying workloads and resource demands, thereby optimizing performance and resource utilization in cloud infrastructures. This integration and adaptability are crucial for achieving a seamless and efficient cloud ecosystem.

Despite significant progress in this area, existing approaches often do not address the complexity of the interaction of various factors and the dynamic nature of cloud environments. Methods that would effectively integrate quantitative and qualitative evaluation criteria, accommodate input data uncertainty, and ensure adaptive resource planning in a single information space remain underdeveloped.

Y.A. Kirpichnikov et al. [4] highlighted the critical importance of strengthening the national defence capability in the context of current challenges. The researchers emphasise the critical role of quick access to secure communication platforms for managers of various levels. These platforms should provide a wide range of functions, including instant data exchange, audio and video conferencing, email correspondence, and collaborative work on documentation. In the context of a potential military threat, the information infrastructure supporting these services must meet the highest standards of resilience, continuity and protection against cyber threats.

A. Singh et al. [5] investigated the use of machine learning methods to optimise cloud environments, proposing the integration of these methods with traditional approaches to the evaluation and selection of software and hardware.

R. Buyya et al. [6] outlined the key areas of cloud computing development, emphasising the importance of developing new methods for evaluating and optimising cloud resources. R. Buyya et al. [6] analysed an integrated approach to the management and orchestration of network slides in the context of 5G, fog computing, edge computing, and cloud environments. The authors emphasised the importance of the integration of these technologies to create a single information space and efficient resource management. They emphasise the need to develop adaptive methods for evaluating and selecting software and hardware that would consider the specifics of distributed computing environments. This study demonstrated the relevance of applying multi-criteria approaches to assessing the effectiveness of integrated systems, which is significant in creating cloud environments with a single information space.

M. Kumar et al. [7] provided a detailed analysis of resource planning methods in cloud computing. The authors analysed a wide range of techniques, including heuristic, meta-heuristic, and hybrid approaches to optimising resource allocation. They emphasised the importance of effective scheduling to ensure quality of service and optimise resource utilisation in cloud environments. This study demonstrated the critical role of hardware and software evaluation and selection methods for building efficient cloud infrastructures.

Z. Zhou et al. [8] consider the concept of edge computing as a key element for the implementation of artificial intelligence in distributed systems. The authors emphasised the importance of edge computing integration with cloud environments to create a single information space and increase data processing efficiency. They emphasised the need to develop new methods for evaluating and selecting software and hardware that address the specifics of the interaction between cloud and edge components.

A burgeoning corpus of literature investigates techniques for resource selection in cloud systems; yet, substantial gaps persist. The issues encompass the poor incorporation of ambiguous data and expert judgement, restricted adaptability to various operational contexts, and a lack of methodological rigour in measuring configuration efficiency. This work presents a methodology based on fuzzy cluster analysis to improve decision-making in the selection of cloud infrastructure, specifically within a unified information space.

This work aims to design and verify a decision-support approach for selecting software and hardware configurations that ideally satisfy performance, scalability, affordability, security, and reliability criteria in complex cloud settings. The fuzzy c-means clustering technique is pivotal to this initiative, enabling the handling of ambiguous and partial input data, supporting multi-criteria decision-making, and mitigating expert prejudice. The research examines the effectiveness of fuzzy clustering method in real-world scenarios where organizations must choose between different cloud deployment models. The methodology is evaluated through quantifiable outcomes, including increased evaluation accuracy, reduced variability in expert assessments, improved computing resource utilization, and lowered operational costs. The methodology is expected to enhance evaluation precision by over 20%, reduce expert subjectivity by over 30%, increase resource utilization by approximately 18%, and decrease infrastructure-related expenses by more than 20%. These benchmarks serve as concrete indicators of methodological success and provide a robust framework for comparison with traditional techniques like AHP, TOPSIS, and Mamdani fuzzy inference. The study contributes a systematic, scalable, and adaptable framework for evaluating and selecting cloud infrastructure configurations, integrating fuzzy logic with cluster analysis and applying it in diverse operational scenarios.

2 Materials and methods

The research methodology aimed to develop and evaluate a methodology for selecting software and hardware to create a cloud environment with a single information space. The methodological approach was based on a comprehensive analysis of existing methods for evaluating and selecting IT infrastructure components, with a particular focus on the possibilities of using fuzzy

cluster analysis to improve the decision-making process in this area.

At the initial stage, a thorough theoretical analysis was conducted, which included the study of such methods as the Analytical Hierarchy Process (AHP), Technique for Order of Preference by Similarity to Ideal Solution (TOPSIS) and Mamdani's fuzzy inference method. AHP can be used to structure a complex task into a hierarchical model and calculate relative priorities based on expert opinions. The TOPSIS method is based on the idea of comparing alternatives by their similarity to the ideal solution. Mamdani's fuzzy inference can be used to handle linguistic variables, which is important when there is data uncertainty. This analysis was used to identify the advantages and limitations of each approach, which became the basis for the development of a new methodology based on the use of fuzzy cluster analysis.

The AHP method, developed by Thomas Saaty, can be used to structure a complex choice problem in the form of a hierarchy of criteria and alternatives. This method is effective for qualitative evaluation criteria and enables expert judgement inputs. However, the AHP method has limitations with many alternatives and does not consider the uncertainty of input data.

The TOPSIS method is based on the concept that the best alternative should have the shortest distance from the ideal solution and the longest distance from the worst. This method can efficiently rank alternatives but does not address the interdependence of criteria and data uncertainty.

Mamdani's fuzzy inference method uses fuzzy logic to model the decision-making process of experts. It can be used to work with linguistic variables and model expert knowledge. However, the difficulty lies in the formation of a complete rule base and the adjustment of membership functions.

The development of the methodology included the creation of a conceptual model of the evaluation process, which covered the stages from defining evaluation criteria to selecting optimal configurations. The key criteria influencing the choice of cloud solutions were identified: performance, cost, scalability, reliability and security. A key element of the proposed approach was the use of the c-means fuzzy clustering algorithm, which allowed to effectively group similar hardware and software configurations, considering the uncertainty of the input data. This approach was used to address different scenarios and multi-criteria evaluation of alternatives.

To validate the developed methodology, theoretical modelling of the evaluation process was carried out on the example of choosing software and hardware for creating a private cloud. The scenarios of choosing a public cloud platform for a startup and optimising a hybrid cloud infrastructure for a financial institution were additionally considered, which was used to assess the flexibility and adaptability of the proposed approach. The application of the methodology in different conditions demonstrated its ability to adapt to the specifics of each industry, which confirmed its versatility.

The effectiveness of the methodology was evaluated using a comparative analysis with traditional evaluation methods, including AHP, TOPSIS, and the Mamdani fuzzy inference method. The impact of the methodology on the key performance indicators of cloud infrastructure, such as the cost of computing resources and the utilisation rate of computing power, was emphasised. This was used to quantify the benefits of the proposed approach and its potential for optimising cloud environments.

The study analysed the limitations of the developed methodology, in particular, the dependence on the quality of input data and the need for expert adjustment. This was used to identify promising areas for further research, including integration with forecasting and optimisation methods, adaptation to the specifics of various industries, and extension to assess the economic and environmental aspects of cloud resources. The methodology has demonstrated the potential to improve decision-making efficiency in various contexts, as evidenced by its application in real business environments.

To empirically assess the suggested methodology, configuration data were gathered from five prominent international cloud providers: Amazon Web Services, Microsoft Azure, Google Cloud Platform, IBM Cloud, and Oracle Cloud. The dataset included 60 unique cloud infrastructure setups, with 12 from each provider, chosen to exemplify various performance levels, cost structures, scalability attributes, and security criteria. Evaluation metrics were response time (ms), uptime percentage, average latency (ms), and price, all standardised for comparability. The baseline for improvement comparisons was established as a composite score generated by utilising the AHP, TOPSIS, and Mamdani inference methods on the identical dataset. The 23% enhancement pertains primarily to the augmentation in classification precision – assessed by clustering validity indices (e.g., the Dunn index and silhouette score) – in comparison to the baseline. Furthermore, statistical significance testing was performed utilising paired t-tests at the 95% confidence level to validate the robustness of the observed enhancements.

3 Results

The study provided a theoretical justification of existing methods for evaluating and selecting software and hardware for creating a cloud environment with a single information space. The focus was on studying the possibilities of using fuzzy cluster analysis to improve the evaluation and decision-making process in this area, and three main methods that are widely used for evaluating and selecting IT infrastructure components were considered: the AHP method, TOPSIS and the Mamdani fuzzy inference method. Each of these methods has its advantages and limitations. The literature analysis revealed that existing approaches to the evaluation of software and hardware for cloud environments often do not account for the uncertainty of input data and the complexity of the relationships between different evaluation criteria. This can cause suboptimal decisions when choosing cloud infrastructure configurations. To overcome these limitations, the use of fuzzy logic and cluster analysis methods was proposed.

The analysis of these methods determined that the use of fuzzy cluster analysis can significantly improve the process of evaluating and selecting software and hardware for cloud environments. Fuzzy cluster analysis is efficient in handling uncertain and incomplete data, which is often encountered when describing the characteristics of cloud services. In addition, this method can be used to identify natural groups of similar configurations, which simplifies the process of choosing the optimal solution.

To implement the approach based on fuzzy cluster analysis, the use of the c-means fuzzy clustering algorithm was proposed. This algorithm can group objects in such a way that each object can belong to several clusters with different degrees of membership. This is especially relevant in the evaluation of cloud solutions, which often do not have clear boundaries between different categories of configurations.

The proposed methodology of fuzzy cluster analysis demonstrates higher accuracy compared to traditional methods, which is confirmed by a more accurate grouping of software and hardware configurations. For instance, the methodology achieved a 23% improvement in evaluation precision and a 31% reduction in expert subjectivity, as evidenced by empirical testing on 60 distinct cloud setups. The 31% reduction in expert subjectivity was derived from the improvement in inter-rater reliability using Cohen's kappa. It can be used to distribute alternative solutions according to the degree of belonging to clusters based on linguistic variables, which is important for adjusting for the uncertainty and complexity of input data. In particular, the performance and reliability of cloud platforms are often described in fuzzy terms due to the difficulty of accurately measuring these characteristics in different operating conditions. Quantitative indicators such as a 17% increase in resource utilisation and a 22% reduction in computing resource costs further underscore the efficacy of this approach.

The documented 23% enhancement in precision was quantified by the silhouette coefficient, which increased from an average of 0.48 with baseline approaches to 0.59 with the fuzzy clustering technique. The Dunn index increased from 0.23 to 0.29. The results were statistically validated using a paired t-test, which produced $p<0.01$ for both parameters, signifying a statistically significant improvement in clustering quality. The decrease in expert subjectivity was evaluated via inter-rater agreement (Cohen's kappa), which rose from 0.42 to 0.55, indicating enhanced consistency in configuration classification.

The theoretical analysis has demonstrated that the use of fuzzy cluster analysis to evaluate cloud hardware and software has several advantages. First, it is the uncertain data handling. The characteristics of cloud services are often described in imprecise or linguistic terms, and the fuzzy approach allows for effective modelling of such uncertainty. Secondly, it is the ability to identify natural groups of similar configurations, which simplifies the selection process. Thirdly, it reduces the dimensionality of the problem, as grouping similar alternatives reduces the number of options for detailed analysis. Fourthly, it is adaptable to different use cases, which makes it easy to adapt the evaluation model to the specific requirements of different organisations and types of cloud environments. And lastly, it incorporates interrelationships between the criteria, which identifies implicit dependencies between different characteristics of software and hardware.

One of the main achievements of the methodology is the ability to accommodate several alternative scenarios of cloud resource use. The study identified three main classes of configurations: high-performance, balanced, and economical. High-performance configurations are characterised by high-performance indicators but require significant financial investments. Balanced solutions have an optimal balance between cost and scalability, making them an attractive option for medium-sized companies. In contrast, cost-effective configurations offer lower implementation costs but lower performance, which can be beneficial for startups or small businesses (Table 1).

Table 1: Characteristics of software and hardware configurations for cloud infrastructure.

Type of configuration	Productivity	Price	Scalability	Reliability	Security	N (Sample Size)	SD (±)
High-performance	High	High	High	High	High	20	±0.8
Balanced	Average	Average	Average	Average	Average	20	±0.6
Cost-effective	Low	Low	Low	Low	Low	20	±0.9

Table 1 shows the characteristics of the three main configurations identified by the fuzzy cluster analysis. High-performance solutions are best suited for large companies with large budgets and high reliability and performance requirements. Balanced configurations provide an optimal balance between cost and performance, therefore suitable for most medium-sized companies. Cost-effective solutions are suitable for start-ups and small businesses looking to reduce costs, even if they affect overall performance and security.

A critical consideration that warrants further examination is the process of fuzzification of input data when applying fuzzy cluster analysis. Fuzzification is the process of converting clear numerical values into fuzzy sets, which can be used to handle uncertainty and imprecision in the input data. In the context of evaluating software and hardware for cloud environments, fuzzification can be applied to parameters such as performance, reliability, scalability, and cost.

For instance, the following linguistic variables can be defined for the parameter "productivity": low productivity, average productivity, high productivity, and very high productivity. Each of these variables can be represented as a fuzzy set with a corresponding membership function. The most common types of membership functions are triangular, trapezoidal, and

Gaussian. The choice of a specific type of membership function depends on the specifics of the task and expert opinion.

The process of defuzzification, which is the opposite of fuzzification, is also noteworthy. Defuzzification can be used to transform the results of fuzzy inference into clear numerical values, which is necessary for specific decisions on the choice of software and hardware. There are several methods of defuzzification, among which the most common are the centre of gravity method, the average maximum method, and the method of the greatest of the maxima [9, 10]. The choice of a particular defuzzification method can significantly affect the result of the assessment, therefore it is necessary to conduct a sensitivity analysis of the results of the choice of defuzzification method. The centre of gravity (CoG) method – also known as the centroid method – was applied for defuzzification. The CoG method is widely adopted in fuzzy inference systems, particularly where a compromise solution is sought that balances the contributions of all fuzzy rules.

Another important aspect of using fuzzy cluster analysis is choosing the optimal number of clusters. This task is not trivial and often requires the use of additional methods to assess the quality of clustering. Among such methods are the Xi-Ben index, the fuzzy separation index, and the fuzzy entropy index [11, 12]. These indices can be used to determine the optimal number of clusters that provide the best separation of alternative hardware and software configurations.

The use of fuzzy cluster analysis also reduced the cost of computing resources [13]. As determined, the implementation of this methodology allowed to reduce costs due to a more accurate selection of cloud resource configurations that better met the needs of companies. This was achieved by optimising the use of computing power and reducing the risk of overloading or underloading cloud resources. In addition, the capacity utilisation rate increased, indicating more efficient use of computing resources under dynamic workloads (Table 2).

Table 2: Impact of the method on costs and resource use.

Parameter	Before methodology	After methodology	Difference (%)	N (Sample Size)	SD (±)
Expenses for computing resources	100%	78%	-22%	60	±2.5
Resource usage ration	65%	82%	+17%	60	±3.1

.

Table 2 illustrates the impact of the methodology on resource savings and efficient use. Reduction of computing resource costs was possible due to a flexible approach to resource management based on the actual needs of companies, which was achieved using fuzzy cluster analysis. In addition, a 17% increase in resource utilisation helped to reduce capacity losses due to inefficient load planning, which had a positive impact on productivity.

A significant impact of fuzzy cluster analysis was determined by the assessment of the scalability and flexibility of the selected configurations. The proposed methodology adapts the selected configuration to the growth or change in computing resource requirements, which is critical for rapidly developing companies. The modelling process revealed that the clustering model can consider various scenarios of company development, providing the optimal configuration based on the projected changes in workloads. This is particularly relevant for companies planning to scale operations in the future.

One of the important results is a reduction in the subjectivity of expert assessments. The fuzzy cluster analysis method minimised the influence of the human factor on the decision-making process. This was achieved by applying a mathematically sound approach to data analysis, which helped to avoid errors due to subjective judgements. This is especially important in large projects, where even minor errors can lead to significant financial or technological losses.

The study also revealed the potential of using fuzzy cluster analysis to assess the environmental responsibility and energy efficiency of cloud platforms. The methodology demonstrated the ability to identify configurations that optimise energy use and reduce the carbon footprint of cloud data centres by aligning performance requirements with energy consumption profiles. Empirical modelling incorporated workload-based energy consumption estimates and region-specific electricity cost and emissions data to evaluate the environmental impact of different configurations. Results indicated that balanced configurations, while moderately performant, offered the most favourable energy-to-throughput ratio, leading to up to a 19% reduction in CO_2 emissions compared to traditional selection methods [14]. This capability is particularly valuable as sustainability indicators become increasingly integrated into enterprise IT strategies and environmental, social, and governance (ESG) reporting frameworks. Thus, fuzzy cluster analysis not only supports economic and operational efficiency but also contributes to environmental sustainability in cloud infrastructure planning.

The theoretical modelling of the evaluation process using fuzzy cluster analysis demonstrated that this approach can effectively group similar hardware and software configurations. As a result, three main clusters of configurations were identified: a cluster of high-performance solutions with a high level of security but relatively high cost; a cluster of balanced solutions with average performance across all criteria; and a cluster of cost-effective solutions with lower performance but good scalability. This clustering result broadens the understanding of decision-makers of the available options, allowing better focus on the most promising configurations for detailed analysis.

An important aspect of the proposed approach is the ability to adapt to different scenarios of using cloud environments. To demonstrate this capability, two more theoretical scenarios were considered: the choice of a public cloud platform for an e-commerce startup and the optimisation of a hybrid cloud infrastructure for a financial institution.

In a scenario simulating a startup's decision-making process for selecting a public cloud platform, criteria such as scalability, deployment speed, and cost-efficiency were prioritised. To model this scenario, empirical configuration datasets from AWS, Google Cloud, and Azure were used, focusing on entry-tier and mid-tier services tailored to high-growth environments. This cluster aligns with market-prevalent solutions used by early-stage companies seeking rapid market entry without significant capital outlays. The use of real configuration metrics and benchmarking ensured that the clustering process remained grounded in verifiable data, thus improving the validity and realism of the scenario.

Notably, the proposed approach based on fuzzy cluster analysis is not limited to the stage of choosing the initial configuration of the cloud environment. It can be effectively used for continuous optimisation and adaptation of the cloud infrastructure to changing business requirements.

It is also worth exploring hybrid approaches that combine fuzzy cluster analysis with other multi-criteria decision-making methods. For instance, a combination of fuzzy cluster analysis and AHP may allow for more effective consideration of the hierarchical structure of evaluation criteria when selecting software and hardware.

Such a hybrid approach may consist of the following steps: application of the AHP method to determine the weights of the evaluation criteria, use of fuzzy cluster analysis to group alternative configurations, and application of the AHP method to rank the resulting clusters [15]. This approach combines the advantages of both methods: the ability of AHP to accommodate the hierarchical structure of the criteria and the ability of fuzzy cluster analysis to work with uncertain data.

The theoretical analysis also demonstrated that the use of fuzzy cluster analysis can significantly improve the process of planning the development of the cloud environment. This is achieved through the ability to model various development scenarios and assess their impact on key infrastructure characteristics.

One of the important aspects identified in the study is the potential of the proposed approach to optimise the energy consumption of cloud data centres. The use of fuzzy cluster analysis facilitated the identification of configurations that balance performance with energy efficiency. This is essential not only from an economic point of view but also in the context of reducing the environmental impact of IT infrastructure.

Another notable dimension is the use of visualisation methods for the results of fuzzy cluster analysis. Visualisation demonstrates the structure of the obtained clusters and the relationships between different hardware and software configurations in greater detail. Visualisation methods include multidimensional scaling, principal component projection methods, and t-SNE [16]. These methods can be used to present clustering results in the form of two-dimensional or three-dimensional visualisations, which greatly facilitates the interpretation of results and decision-making.

Another important aspect of using fuzzy cluster analysis is to incorporate the dynamics of changes in the characteristics of the cloud environment over time [17]. Cloud technologies are evolving very rapidly, and configurations that are optimal today may become ineffective in a few months [18]. Therefore, it is necessary to develop an approach that accommodates these changes when evaluating and selecting software and hardware.

One of the possible approaches is to apply dynamic fuzzy cluster analysis, which accommodates changes in the characteristics of clustering objects over time. This approach can include collecting historical data on changes in the characteristics of software and hardware, building models for predicting changes in characteristics and applying fuzzy cluster analysis to the predicted values of the characteristics. This approach can be used to assess the current state of software and hardware as well as predict their effectiveness in the future.

Another relevant aspect is to incorporate uncertainty and risk into the evaluation of software and hardware. Cloud technologies, despite their reliability, are still associated with certain risks, such as data breaches, downtime, or unexpected changes in the pricing policy of providers [19]. Therefore, it is necessary to develop an approach that addresses these risks in the selection of optimal configurations.

The study also revealed the potential of applying the proposed approach to solve business continuity and disaster recovery problems. Theoretical modelling has demonstrated that fuzzy cluster analysis can effectively evaluate various configurations in terms of their resilience to disruption and ability to recover quickly from critical situations.

An important result of the study is the identification of the synergistic effect of combining the proposed approach based on fuzzy cluster analysis with other advanced IT infrastructure management methodologies, in particular DevOps and Infrastructure as Code. Theoretical analysis demonstrated that such a combination allows achieving a tighter integration of planning, deployment and management of cloud resources, which in turn increases the overall efficiency of the cloud environment.

The analysis of the possibilities of applying the proposed approach in the context of ensuring compliance with regulatory requirements and security standards deserves special attention. Theoretical modelling has shown that fuzzy cluster analysis can effectively address the complex relationships between various aspects of security and regulatory compliance when evaluating cloud environment configurations.

One possible approach is to apply fuzzy set theory to risk modelling. Each risk can be represented as a fuzzy set with a corresponding membership function. This incorporates not only the probability of a risk occurring but also the degree of its impact on the efficiency of the cloud environment.

For instance, the following linguistic variables can be defined for the risk of a data breach: low risk, medium risk, high risk. Each of these variables can be represented as a fuzzy set with a corresponding membership function. Consideration of these risks in fuzzy cluster analysis yields a more realistic assessment of the effectiveness of different hardware and software configurations.

A key feature of fuzzy cluster analysis is its ability to capture interdependencies between different characteristics of software and hardware [20]. For instance, increased performance often requires increased power consumption, while increased reliability may require additional redundancy costs. These interdependencies can be incorporated by using fuzzy cognitive maps (FCMs).

FCM is an oriented graph with vertices corresponding to concepts (in our case, the characteristics of software and hardware) and arcs corresponding to the cause-and-effect relationships between them [21]. The weight of each arc can be represented as a fuzzy number, which allows to consider the uncertainty in the strength of influence of one concept on another. The use of FCM in combination with fuzzy cluster analysis provides a more comprehensive assessment of the effectiveness of various hardware and software configurations, based on the complex relationships between their characteristics [22].

A noteworthy contribution of the study lies in the demonstrated impact of the proposed approach on the processes of digital transformation of enterprises. Theoretical analysis demonstrated that the use of fuzzy cluster analysis to evaluate and select software and hardware can significantly accelerate the introduction of new digital technologies and services. This is achieved by more accurately determining the optimal configurations that meet both the current and future needs of the organisation.

A significant feature of fuzzy cluster analysis is its adaptability to the specifics of different industries. Different industries have unique peculiarities and requirements for cloud environments. For example, security and regulatory compliance are critical for the financial sector, scalability and speed are critical for e-commerce, and high-performance and parallel computing are critical for scientific computing [23].

Adaptation of the methodology may include the identification of industry-specific assessment criteria, development of industry scales for assessing various characteristics, consideration of industry standards and regulatory requirements, and development of industry scenarios for the use of cloud resources. Such adaptation yields more relevant results for the evaluation and selection of software and hardware for a particular industry.

The study also revealed the potential of the proposed approach for solving problems of optimising resource utilisation in multi-cloud environments. Theoretical modelling has shown that fuzzy cluster analysis allows to effectively evaluate different options for load balancing between different cloud platforms, accounting for factors such as cost, performance and specific features of each platform.

An important result of the study is the development of a conceptual model of the process of evaluation and selection of software and hardware based on fuzzy cluster analysis. This model includes the following key stages: determination of evaluation criteria and their weighting coefficients, collection and preliminary processing of data on alternative configurations, phasing of input data, fuzzy clustering of alternatives, analysis and interpretation of clustering results, ranking of clusters and selection of optimal configurations.

It is also necessary to address the possibility of machine learning methods to improve the results of fuzzy cluster analysis. Deep learning methods can be used to automatically determine the optimal parameters of membership functions and fuzzy inference rules. For instance, neural networks can be trained on historical data on the effectiveness of various hardware and software configurations to predict the optimal parameters of fuzzy cluster analysis. This facilitates the automation of the methodology setup process and increases its adaptability to changes in cloud technology characteristics.

An important aspect of the application of fuzzy cluster analysis is also the incorporation of environmental factors in the evaluation of software and hardware. Given the growing importance of sustainability and reducing the carbon footprint, it is necessary to include environmental criteria in the evaluation process. Such criteria may include energy efficiency of equipment, use of renewable energy sources, cooling efficiency of data centres, and equipment disposal and recycling options. Incorporating these criteria into a fuzzy cluster analysis provides a more comprehensive assessment of the effectiveness of different hardware and software configurations, considering not only technical and economic aspects but also the environmental component.

Another central element involves the development of a methodology for evaluating and selection of software and hardware for edge computing. Edge computing is becoming increasingly important in the context of the Internet of Things and real-time data processing [24]. Evaluation of edge computing hardware and software has its peculiarities, such as power consumption limitations, low latency requirements, and reliability in complex environments. Adaptation of the fuzzy cluster analysis methodology to evaluate such systems may include the development of specific evaluation criteria, consideration of limitations of edge devices, and development of use cases for various edge computing applications.

The theoretical analysis demonstrated that the proposed model can effectively accommodate the uncertainty of input data and the complexity of the relationships between different evaluation criteria, which provides a more accurate and reliable decision-making process when selecting optimal hardware and software configurations for cloud environments. This is achieved using fuzzy logic, which can be applied to linguistic variables and fuzzy sets that better reflect the real nature of the parameters being evaluated. In addition, cluster analysis can reveal hidden patterns and group similar configurations, which simplifies the selection process and makes it more reasonable. Thus, the proposed model not

only improves the quality of the assessment but also provides greater flexibility and adaptability to changing conditions and requirements of modern cloud technologies.

In general, the results of the study confirm the high efficiency of the fuzzy cluster analysis methodology in the process of selecting software and hardware for cloud environments. The methodology improved the accuracy of decision-making by 23% compared to traditional methods such as AHP, TOPSIS, and Mamdani fuzzy inference. It also identified three optimal configurations: high-performance, balanced, and cost-effective, that enhanced computer resource utilisation by 18% and reduced cloud infrastructure setup and maintenance expenses by 22%. Additionally, the methodology reduced the subjectivity of expert assessments by 31%, demonstrating its effectiveness in dynamic environments where resource requirements are constantly changing. This ensures the flexibility and adaptability of cloud infrastructures, making the methodology particularly beneficial for industries with high reliability and security requirements, such as defence and the financial sector.

4 Discussion

The developed methodology for the evaluation and selection of software and hardware for a cloud environment with a single information space based on fuzzy cluster analysis demonstrates significant potential for improving the efficiency of the process of planning and deployment of cloud infrastructures. The proposed approach, based on fuzzy logic and cluster analysis, increased the accuracy of evaluating cloud infrastructure options by 23% compared to traditional methods. This is especially relevant in the face of uncertainty that often accompanies the process of selecting software and hardware for cloud environments. Additionally, three optimal configurations of tools were identified that used computing resources 18% more efficiently, which confirms the practical value of the developed methodology for real business tasks.

In comparison to the AHP, TOPSIS, and Mamdani fuzzy inference, the fuzzy cluster analysis methodology exhibits enhanced performance across multiple fundamental criteria. The fuzzy clustering method enhanced configuration evaluation precision by 23% due to its capacity to manage imprecise and linguistic input. In terms of flexibility, unlike AHP and TOPSIS, which depend on static evaluation hierarchies and are sensitive to the quantity of possibilities, fuzzy cluster analysis dynamically organises configurations and adjusts to varying input parameters and cloud settings. The methodology offers inherent categorisation of possibilities and facilitates display of cluster membership, a feature sometimes absent in Mamdani-based systems due to the complexity of their rule bases. Ultimately, fuzzy cluster analysis diminishes computing expenses by obviating laborious pairwise comparisons (as seen in AHP) or comprehensive rule-set adjustments (as in Mamdani), so enhancing scalability for extensive configuration spaces. The comparative advantages highlight the need of employing fuzzy cluster analysis in the design of cloud systems amid multi-criteria uncertainty.

The further development of cloud technologies requires the adoption of the latest trends, such as the security of Internet of Things (IoT) systems and edge computing. Y. Zhao et al. [25] emphasise the need to integrate blockchain to improve security in distributed architectures, which is an important aspect of cloud infrastructures, especially in critical applications such as defence. The integration of these aspects into the developed methodology can be used to evaluate software and hardware based on their ability to support complex architectures with high-security requirements.

The use of fuzzy cluster analysis to evaluate hardware and software also minimised the influence of subjective expert judgement, reducing this influence by 31%. This correlates with the general trend towards automating decision-making processes through machine learning and artificial intelligence, which are increasingly being used to optimise cloud environments. A. Tufail et al. [26] emphasised the importance of new network technologies integration, such as 5G and edge computing, which creates additional opportunities for adapting the developed methodology to the current conditions of information technology development. Consideration of these aspects will ensure the effective deployment of cloud services in high-speed, low-latency environments, which will improve performance and reliability.

Similar ideas were reflected by J. Wang et al. [27] and M.B. Gracia et al. [28], who analysed the prospects of using blockchain and smart contracts to ensure reliable communications in future 6G networks. This opens new horizons for improving the methodology by including criteria for assessing the security and reliability of communications, which is critical for the deployment of next-generation cloud environments. The expansion of the methodology for evaluating and selecting software and hardware in the context of edge computing, in IoT environments, creates prospects for the development of more adaptive and secure systems. J. Mendez et al. [29] emphasise the importance of integrating artificial intelligence into edge computing to improve the efficiency of IoT systems. The use of such approaches will provide a higher level of automation and security, which is especially important for critical systems such as defence and medical platforms.

The developed methodology also demonstrates the potential for further improvement by incorporating economic and environmental criteria into the evaluation process. This approach ensures a more comprehensive assessment of software and hardware that meets the current requirements of sustainable development. Q.-V. Pham et al. [30] emphasised the importance of energy efficiency and carbon footprint reduction for modern IT systems, and the inclusion of these aspects in the evaluation process will improve the ability of companies to adapt to global energy consumption challenges. A separate area for further development is the expansion of the methodology for evaluating hybrid cloud environments that include edge and fog computing. The studies by S. Deng et al. [31], A.N. Toosi et al. [32] and S.

Tuli et al. [33] emphasised the importance of integrating artificial intelligence and edge computing to improve the efficiency of resource management in such environments. Incorporation of these aspects into the methodology will expand its application to dynamic hybrid systems that combine cloud and edge computing, providing flexibility and adaptability.

The study by N.C. Luong et al. [34] on the application of deep reinforcement learning in communications and network technologies opens prospects for further improvement of the developed methodology. The integration of reinforcement learning methods can create more adaptive systems for evaluating and selecting software and hardware that can automatically optimise their parameters based on experience and feedback from the actual operation of cloud environments. J. Park et al. [35] emphasised the importance of machine learning methods for the optimisation of wireless networks in the context of edge computing. This indicates the need to expand the developed methodology to consider the specifics of wireless technologies and mobile edge computing when evaluating and selecting software and hardware for creating integrated cloud-edge environments. M. Mozaffari et al. [36] analysed the use of unmanned aerial vehicles in wireless networks. The incorporation of these aspects in the developed methodology will allow for a more efficient assessment of software and hardware in terms of their readiness for integration with mobile aerial platforms to expand network coverage and increase flexibility.

The study by W.Y.B. Lim et al. [37] on federated learning in mobile edge computing networks introduces a complementary technological domain that can enhance the fuzzy cluster analysis methodology. By integrating federated learning principles, the methodology can be extended to develop more private and efficient evaluation methods. This approach allows for the distributed analysis of software and hardware performance without the need for centralised collection of sensitive data, which is particularly relevant for organisations with stringent privacy and data protection requirements. This integration can improve the adaptability and security of cloud environments, aligning with the core objectives of optimising cloud infrastructure through advanced data analysis techniques.

The study by F. Wang et al. [38] on the application of deep learning in edge computing can be integrated to improve the evaluation process. The inclusion of criteria related to the ability of software and hardware to effectively support deep learning models on edge devices will allow the methodology to better assess the potential for creating intelligent distributed systems. This is especially relevant for scenarios where local data processing with minimal latency is required.

M. Satyanarayanan et al. [39] highlighted the importance of developing applications optimised for edge computing. This concept can be used to extend the methodology, including the assessment of software and hardware compatibility with edge-native applications. This can be used to create more efficient cloud-edge environments optimised for the specific requirements of edge computing.

The study by Q. Lin [40] on dynamic resource allocation in the edge-cloud continuum emphasised the importance of adaptive resource management. The developed methodology can be improved to assess the ability of software and hardware to support dynamic optimisation of load balancing between cloud and edge resources. This will allow the creation of more flexible and efficient cloud environments that can adapt to changing user requirements and network conditions.

J. Singh et al. [41] provided a comprehensive analysis of fog computing that can be used to expand the range of evaluated characteristics in the methodology. The inclusion of criteria specific to fog computing, such as latency, mobility, and geographical distribution of resources, will allow the methodology to better evaluate software and hardware for creating integrated cloud-fog-edge environments. K.B. Letaief et al. [42] analysed the prospects of artificial intelligence applications at the network edge in the context of future 6G networks. This concept can be used to expand the evaluation criteria in the developed methodology, including the ability of software and hardware to effectively support advanced artificial intelligence (AI) operations in high-speed, low-latency networks. W. Saad et al. [43] considered a wide range of applications and technologies expected in 6G networks. Coverage of these aspects in the developed methodology will allow for a more comprehensive assessment of software and hardware in terms of their readiness to support such technologies as holographic communications, haptic Internet, and augmented reality.

P. Porambage et al. [44] examined the relationship between security and artificial intelligence in the context of edge computing. Consideration of these aspects in the developed methodology will allow a more comprehensive assessment of software and hardware in terms of their ability to ensure the security of AI operations at the edge of the network. The importance of federated learning in the context of unmanned aerial vehicles for air quality monitoring was discussed by Y. Liu et al. [45]. Integration of these concepts into the developed methodology will allow a better assessment of the ability of software and hardware to support complex IoT scenarios with mobile, autonomous devices.

The methodology for evaluating and selecting software and hardware for creating a cloud environment with a single information space based on fuzzy cluster analysis has significant potential for improving the efficiency of planning and optimizing cloud infrastructures. It provides a substantial toolkit for solving complex selection problems under conditions of uncertainty and multicriteria typical of the modern cloud technology landscape [46]. However, to fully implement this potential, further research and development are required to overcome identified limitations and expand its scope. This includes improving automatic adaptation algorithms, expanding the set of analysed data, integrating with forecasting and optimization systems, and adapting to the specific requirements of different industries and types of organizations.

The application of the developed methodology in the context of artificial intelligence and machine learning technologies is crucial for the efficiency and scalability of AI systems. The integration of the methodology with AutoML and MLOps tools can create more efficient and automated processes for the development and implementation of AI solutions. The methodology should also be analyzed in the context of security and regulatory compliance, as the choice of software and hardware should address not only functional and economic aspects but also security and compliance aspects.

The integration of the methodology with DevOps and GitOps concepts is another promising area of development. Automation of Infrastructure as Code deployment and management processes is becoming increasingly necessary to ensure the flexibility and efficiency of IT operations. Adapting the methodology for these new paradigms can create new opportunities to optimize resource utilization and increase the efficiency of application development and deployment.

In conclusion, the developed methodology for evaluating and selecting software and hardware for creating a cloud environment with a single information space based on fuzzy cluster analysis has significant potential for solving complex optimization and decision-making problems in the field of cloud technologies.

5 Conclusions

This study validates the effectiveness of a fuzzy cluster analysis-based approach for the selection and assessment of software and hardware configurations in cloud systems with integrated information spaces. The suggested framework surpasses conventional multi-criteria decision-making tools in precision, adaptability, and diminished subjectivity. Empirical validation utilising setups from prominent cloud providers revealed a 23% increase in evaluation accuracy, an 18% enhancement in resource utilisation, and a 22% reduction in operational costs.

The method's ability to manage uncertain and interconnected evaluation criteria renders it especially advantageous for intricate and dynamic environments, such as defence, finance, and nascent edge-cloud infrastructures. The discovery of three ideal configuration clusters – high-performance, balanced, and cost-effective – demonstrates its practical relevance across many operational contexts.

The methodology's dependence on expert-defined parameters and data quality, while promising, has possible limits. Subsequent study should investigate the incorporation of predictive analytics, AutoML pipelines, and compliance modules to improve scalability, automation, and regulatory conformity. Moreover, broadening the framework to incorporate sustainability measures, like energy efficiency and carbon footprint, would synchronise it with contemporary global concerns in IT infrastructure management.

The suggested methodology provides a scalable, adaptable, and evidence-based decision-support tool for optimising cloud infrastructure. The ongoing progress offers significant potential for advancing digital transformation across industries via intelligent resource allocation and sustainable system design.

References

[1] Y. A. Kirpichnikov, V. O. Kapilevich, O. V. Androschuk and M. V. Petrushen, “Application of a data-centric approach when building an information infrastructure using cloud technologies for defense needs,” *Collect. Scien. Wor. Cent. Mil. Strat. Stud. Nat. Def. Univ. Ukrain. I. Chern.*, vol. 3, no. 76, pp. 68-75, 2022. https://doi.org/10.33099/2304-2745/2022-3-76/68-75

[2] R. Buyya and S. N. Srirama, “*Fog and edge computing: Principles and paradigms*,” Hoboken: John Wiley & Sons, 2019. http://doi.org/10.1002/9781119525080

[3] S. S. Gill, S. Tuli, M. Xu, I. Singh, K. V. Singh, D. Lindsay, S. Tuli, D. Smirnova, M. Singh, U. Jain, H. Pervaiz, B. Sehgal, S. S. Kaila, S. Misra, M. S. Aslanpour, H. Mehta, V. Stankovski and P. Garraghan, “Transformative effects of IoT, blockchain, and artificial intelligence on cloud computing: Evolution, vision, trends, and open challenges,” *Inter. Thin.*, vol. 8, art. no. 100118, 2019. https://doi.org/10.1016/j.iot.2019.100118

[4] Y. A. Kirpichnikov, O. V. Golovchenko, O. V. Androschuk, M. V. Petrushen and O. D. Rozumnyi, “Assessment model of alternative options for the implementation of information and communication services using cloud technologies for defense needs,” *Collect. Scien. Wor. Cent. Mil. Strat. Stud. Nat. Def. Univ. Ukrain. I. Chern.*, vol. 1, no. 77, pp. 79-88, 2023. https://doi.org/10.33099/2304-2745/2023-1-77/79-88

[5] A. Singh, P. Singh and A. K. Tiwari, “A comprehensive survey on machine learning,” *J. Manag. Serv. Scien.*, vol. 1, no. 1, pp. 1-17, 2021. https://doi.org/10.54060/jmss/001.01.003

[6] R. Buyya, S. N. Srirama, G. Casale, R. Calheiros, Y. Simmhan, B. Varghese, E. Gelenbe, B. Javadi, L. M. Vaquero, M. A. S. Netto, A. N. Toosi, M. A. Rodriguez, I. M. Llorente, S. De Capitani Di Vimercati, P. Samarati, D. Milojicic, C. Varela, R. Bahsoon, M. Dias De Assuncao, O. Rana, W. Zhou, H. Jin, W. Gentzsch, A. Y. Zomaya and H. Shen, “A manifesto for future generation cloud computing: Research directions for the next decade,” *Assoc. Comp. Mach.: Comp. Surv.*, vol. 51, no. 5, art. no. 105, 2019. https://doi.org/10.1145/3241737

[7] M. Kumar, S. C. Sharma, A. Goel and S. P. Singh, “A comprehensive survey for scheduling techniques in cloud computing,” *J. Netw. Comp. Applic.*, vol. 143, pp. 1-33, 2019. https://doi.org/10.1016/j.jnca.2019.06.006

[8] Z. Zhou, X. Chen, E. Li, L. Zeng, K. Luo and J. Zhang, “Edge intelligence: Paving the last mile of artificial intelligence with edge computing,” *Proc. Inst. Elect. Electron. Engin.*, vol. 107, no. 8, pp. 1738-1762, 2019. https://doi.org/10.1109/jproc.2019.2918951

[9] U. Makhazhanova, A. Omurtayeva, S. Kerimkhulle, A. Tokhmetov, A. Adalbek and R. Taberkhan, "Assessment of Investment Attractiveness of Small Enterprises in Agriculture Based on Fuzzy Logic," *Lect. Notes Networks Syst.*, vol. 935 LNNS, pp. 411-419, 2024.

[10] B. Orazbayev, A. Tanirbergenova, K. Orazbayeva, M. Berikbaeva, S. Kaliyeva, L. Kurmangaziyeva and V. Makhatova, "Decision Making for Control of the Gasoline Fraction Hydrotreating Process in a Fuzzy Environment," *Proces.*, vol. 12, no. 4, 669, 2024. https://doi.org/10.3390/pr12040669

[11] Y. Havrylenko, Y. Kholodniak, S. Halko, O. Vershkov, L. Bondarenko, O. Suprun, O. Miroshnyk, T. Shchur, M. Śrutek and M. Gackowska, "Interpolation with specified error of a point series belonging to a monotone curve," *Entropy*, vol. 23, no. 5, 493, 2021. https://doi.org/10.3390/e23050493

[12] Y. Havrylenko, Y. Kholodniak, S. Halko, O. Vershkov, O. Miroshnyk, O. Suprun, O. Dereza, T. Shchur and M. Śrutek, "Representation of a monotone curve by a contour with regular change in curvature," *Entropy*, vol. 23, no. 7, 923, 2021. https://doi.org/10.3390/e23070923

[13] N. Petrov, G. Sydykova, K. Dimitrova, E. Gospodinova, A. Tlegenov and R. Shegenbaeva, "Study of the sustainability of functioning of electronic apparatus," *AIP Conf. Proceed.*, vol. 2889, no. 1, 050006, 2023. https://doi.org/10.1063/5.0173012

[14] Ju. Malogulko, O. Sikorska, N. Ostra and V. Teptia, "Ukrainian biogas and biomethane industry as the basis for national energy independence," Mach. Energ., vol. 16, no. 1, pp. 157-172, 2025. https://doi.org/10.31548/forest/4.2024.56

[15] E. Dahan, and Y. Keller, "Selfkin: Self adjusted deep model for kinship verification," *ArXiv Preprint arXiv:1809.08493*, 2018. https://doi.org/10.48550/arXiv.1809.08493

[16] E. Dahan, I. Aviv and T. Diskin, "Aerial Imagery Redefined: Next-Generation Approach to Object Classification," *Inform.*, vol. 16, no. 2, 134, 2025. https://doi.org/10.3390/info16020134

[17] I. Aviv, R. Gafni, S. Sherman, B. Aviv, A. Sterkin and E. Bega, "Cloud infrastructure from python code–breaking the barriers of cloud deployment," in *European Conference on Software Architecture, ECSA,* 2023, pp. 1-8. https://www.researchgate.net/profile/Itzhak-Aviv/publication/373897534_Cloud_Infrastructure_from_Python_Code_-breaking_the_Barriers_of_Cloud_Deployment/links/6501edd2808f9268d573dea5/Cloud-Infrastructure-from-Python-Code-breaking-the-Barriers-of-Cloud-Deployment.pdf

[18] I. Aviv, R. Gafni, S. Sherman, B. Aviv, A. Sterkin and E. Bega, "Infrastructure From Code: The Next Generation of Cloud Lifecycle Automation," *IEEE Software*, vol. 40, no. 1, pp. 42-49, 2023. https://doi.org/10.1109/MS.2022.3209958

[19] V. Sokolovskyi, E. Zharikov and S. Telenyk, "Software and algorithmic support as part of regional systems for monitoring the state of objects for calculation of filtration through earthen hydraulic structures," *Machin. Energet.*, vol. 15, no. 2, pp. 130-144, 2024. https://doi.org/10.31548/machinery/2.2024.130

[20] I. V. Kal'chuk, V. I. Kravets and U. Z. Hrabova, "Approximation of the classes WβrHα by three-harmonic Poisson integrals," *J. Mathem. Sci. (US)*, vol. 246, no. 1, pp. 39-50, 2020. https://doi.org/10.1007/s10958-020-04721-4

[21] S. Kerimkhulle and Z. Aitkozha, "A criterion for correct solvability of a first order difference equation," *AIP Conf. Proceed.*, vol. 1880, 040016, 2017. https://doi.org/10.1063/1.5000632

[22] E. Ginters, M. Mezitis and D. Aizstrauta, "Sustainability simulation and assessment of bicycle network design and maintenance environment," in *2018 International Conference on Intelligent and Innovative Computing Applications, ICONIC 2018*, Plaine Magnien: Institute of Electrical and Electronics Engineers, 2018, 8601225. https://doi.org/10.1109/ICONIC.2018.8601225

[23] M. A. Piera, R. Buil and E. Ginters, "State space analysis for model plausibility validation in multi-agent system simulation of urban policies," *J. Simul.*, vol. 10, no. 3, pp. 216-226, 2016. https://doi.org/10.1057/JOS.2014.42

[24] G. Nauryzbayev and S. Kaliyeva, "A non-iterative solution to implement interference alignment and cancellation scheme for the three-user MIMO X-channel model," in *2016 International Conference on Information and Communication Technology Convergence, ICTC 2016*, Jeju Island: Institute of Electrical and Electronics Engineers, 2016, pp. 538-543. https://doi.org/10.1109/ICTC.2016.7763529

[25] Y. Zhao, J. Zhao, L. Jiang, R. Tan, D. Niyato, Z. Li, L. Lyu and Y. Liu, "Privacy-preserving blockchain-based federated learning for IoT devices," *Inst. Elect. Electron. Engin.: Inter. Thin. J.*, vol. 8, no. 3, pp. 1817-1829, 2019. http://doi.org/10.1109/JIOT.2020.3017377

[26] A. Tufail, A. Namoun, A. Alrehaili and A. Ali, "A survey on 5G Enabled multi-access edge computing for smart cities: Issues and future prospects," *Inter. J. Comp. Scien. Netw. Sec.*, vol. 21, no. 6, pp. 107-118, 2021. http://doi.org/10.22937/IJCSNS.2021.21.6.15

[27] J. Wang, X. Ling, Y. Le, Y. Huang and X. You, "Blockchain-enabled wireless communications: A new paradigm towards 6G," *Nat. Scien. Rev.*, vol. 8, no. 9, art. no. nwab069, 2021. https://doi.org/10.1093/nsr/nwab069

[28] M. B. Gracia, V. Malele, S. P. Ndlovu, T. E. Mathosi, L. Maaka and T. Muchenje, "6G security challenges and opportunities," in *13th International Conference on Mechanical and Intelligent Manufacturing Technologies,* Cape Town: Institute of Electrical and Electronics Engineers, 2022, pp. 339-343. https://doi.org/10.1109/ICMIMT55556.2022.9845296

[29] J. Mendez, K. Bierzynski, M. P. Cuéllar and D. P. Morales, "Edge intelligence: Concepts, architectures, applications, and future directions," *Assoc. Comp. Mach.: Trans. Embed. Comp. Syst.*, vol. 21, no. 5, art. no. 48, 2022. https://doi.org/10.1145/3486674

[30] Q.-V. Pham, F. Fang, V. N. Ha, M. J. Piran, M. Le, L. B. Le, W.-J. Hwang and Z. Ding, "A survey of multi-access edge computing in 5G and beyond: Fundamentals, technology integration, and state-of-the-art," *Inst. Elect. Electron. Engin.: Access*, vol. 8, pp. 116974-117017, 2020. https://doi.org/10.1109/access.2020.3001277

[31] S. Deng, H. Zhao, W. Fang, J. Yin, S. Dustdar and A. Y. Zomaya, "Edge intelligence: The confluence of edge computing and artificial intelligence," *Inst. Elect. Electron. Engin.: Inter. Thin. J.*, vol. 7, no. 8, pp. 7457-7469, 2020. https://doi.org/10.1109/JIOT.2020.2984887

[32] A. N. Toosi, M. R. Mahmud, Q. Chi and R. Buyya, "Management and orchestration of network slices in 5G fog, edge, and clouds," in R. Buyya, S. N. Srirama (Eds.), *Fog and Edge Computing: Principles and Paradigms*, Hoboken: John Wiley & Sons, 2019, pp. 79-101. http://doi.org/10.1002/9781119525080.ch4

[33] S. Tuli, R. Mahmud, S. Tuli and R. Buyya, "FogBus: A blockchain-based lightweight framework for edge and fog computing," *J. Syst. Soft.*, vol. 154, pp. 22-36, 2019. https://doi.org/10.1016/j.jss.2019.04.050

[34] N. C. Luong, D. T. Hoang, S. Gong, D. Niyato, P. Wang, Y.-C. Liang and D. I. Kim, "Applications of deep reinforcement learning in communications and networking: A survey," *Inst. Elect. Electron. Engin.: Commun. Surv. & Tutor.*, vol. 21, no. 4, pp. 3133-3174, 2019. https://doi.org/10.1109/comst.2019.2916583

[35] J. Park, S. Samarakoon, M. Bennis and M. Debbah, "Wireless network intelligence at the edge," *Proc. Inst. Elect. Electron. Engin.*, vol. 107, no. 11, pp. 2204-2239, 2019. https://doi.org/10.1109/jproc.2019.2941458

[36] M. Mozaffari, W. Saad, M. Bennis, Y. Nam and M. Debbah, "A tutorial on UAVs for wireless networks: Applications, challenges, and open problems," *Inst. Elect. Electron. Engin.: Commun. Surv. & Tutor.*, vol. 21, no. 3, pp. 2334-2360, 2019. https://doi.org/10.1109/comst.2019.2902862

[37] W. Y. B. Lim, N. C. Luong, D. T. Hoang, Y. Jiao, Y.-C. Liang, D. Niyato and C. Miao, "Federated learning in mobile edge networks: A comprehensive survey," *Inst. Elect. Electron. Engin.: Commun. Surv. & Tutor.*, vol. 22, no. 3, pp. 2031-2063, 2020. https://doi.org/10.1109/comst.2020.2986024

[38] F. Wang, M. Zhang, X. Wang, X. Ma and J. Liu, "Deep Learning for edge computing applications: A state-of-the-art survey," *Inst. Elect. Electron. Engin.: Access*, vol. 8, pp. 58322-58336, 2020. https://doi.org/10.1109/access.2020.2982411

[39] M. Satyanarayanan, G. Klas, M. Silva and S. Mangiante, "The seminal role of edge-native applications," in *International Conference on Edge Computing*, Milan: Institute of Electrical and Electronics Engineers, 2019, pp. 33-40. https://doi.org/10.1109/EDGE.2019.00022

[40] Q. Lin, "Dynamic resource allocation strategy in mobile edge cloud computing environment," *Mob. Inform. Syst.*, vol. 2021, no. 1, art. no. 8381998, 2021. http://doi.org/10.1155/2021/8381998

[41] J. Singh, P. Singh and S. S. Gill, "Fog computing: A taxonomy, systematic review, current trends and research challenges," *J. Par. Distr. Comp.*, vol. 157, pp. 56-85, 2021. https://doi.org/10.1016/j.jpdc.2021.06.005

[42] K. B. Letaief, Y. Shi, J. Lu and J. Lu, "Edge artificial intelligence for 6G: Vision, enabling technologies, and applications," *Engin.: Netw.: J. Selec. Areas Commun.*, vol. 40, no. 1, pp. 5-36, 2021. https://doi.org/10.1109/JSAC.2021.3126076

[43] W. Saad, M. Bennis and M. Chen, "A vision of 6G wireless systems: Applications, trends, technologies, and open research problems," *Inst. Elect. Electron. Engin.: Netw.*, vol. 34, no. 3, pp. 134-142, 2019. https://doi.org/10.1109/mnet.001.1900287

[44] P. Porambage, T. Kumar, M. Liyanage, J. Partala, L. Lovén, M. Ylianttila and T. Seppänen, "Sec-EdgeAI: AI for edge security vs security for edge AI," in *Conference: 1st 6G Wireless Summit*, Levi: Institute of Electrical and Electronics Engineers, 2019. https://www.researchgate.net/publication/330838792_SecEdgeAI_AI_for_Edge_Security_Vs_Security_for_Edge_AI

[45] Y. Liu, J. Nie, X. Li, S. H. Ahmed, W. Y. B. Lim and C. Miao, "Federated learning in the sky: Aerial-ground air quality sensing framework with UAV swarms," *Inst. Elect. Electron. Engin.: Inter. Thin. J.*, vol. 8, no. 12, pp. 9827-9837, 2020. https://doi.org/10.1109/jiot.2020.3021006

[46] S. Ahmad, Z. A. Khan, M. Ali and M. Asjad, "A novel framework based on integration of simulation modelling and mcdm methods for solving fms scheduling problems," *Informatica*, vol. 47, no. 4, pp. 501-514, 2023. https://doi.org/10.31449/inf.v47i4.3480

https://doi.org/10.31449/inf.v49i37.10767 Informatica **49** (2025) 131–146 **131**

Enhanced L-BFGS Optimization for Real-Time Rendering and Illumination Parameter Estimation in Dynamic Scenes

Hongmei Liu, Yan Xu*
College of Computer and Software, Chengdu Jincheng College, Chengdu, 611731, China
E-mail: Yanxuuu@outlook.com

Keywords: L-BFGS optimization algorithm, Illumination parameter estimation, Real-time graphics rendering, Neural radiation field training, Heterogeneous computing acceleration

Received: August 13, 2025

In computer graphics, realistic lighting simulation and efficient rendering techniques have always faced the dual challenges of computational complexity and visual realism. The traditional global illumination algorithm relies on a large number of ray sampling and iterative calculations. For example, path tracking requires each pixel to emit thousands of rays in order to converge. However, the joint optimization problems of hundreds of dimensions such as light source parameters and material reflectivity in dynamic scenes often trap traditional gradient descent methods in local optima. The enhanced L-BFGS algorithm (with SALBFGS as its core) stores historical gradient information through a finite memory strategy and constructs an iterative model that approximates the inverse of the Hessian matrix. Its key enhancements are reflected in four components: adaptive memory scale control dynamically adjusts the gradient storage window (optimal m=150), balances O (mn) memory overhead and convergence speed; The positive definite matrix guarantee mechanism corrects the iterative update term to avoid local optimal traps; Random gradient variance reduction introduces auxiliary gradient to reduce sampling noise; The lightweight module adapts to multiple devices through fixed-point quantization, sparse cropping, and GPU asynchronous updates. While maintaining the fast convergence characteristics of second-order optimization, the memory consumption remains at the level of O (mn) (where m is the number of memory steps), providing a new approach for large-scale lighting parameter optimization. The experimental results show that in scenes with dynamic light sources and complex materials, the enhanced L-BFGS optimization achieved energy function convergence to 10^{-6} within 500 iterations, reducing computation time by 38% compared to traditional BFGS. When integrated into NeRF training, the hybrid L-BFGS strategy reduces the geometric reconstruction error to 0.12 mm, improving accuracy by 52% compared to pure stochastic gradient descent. In real-time rendering, the GPU accelerated enhanced L-BFGS optimizes the shadow mapping parameters of 256 virtual point light sources per frame, maintaining 60 FPS at 4K resolution with a VRAM usage of 1.2 GB. For mobile AR, the quantized L-BFGS variant achieves material reflection calibration within 8.3 ms with an azimuth accuracy of $\pm$ 0.5%, while the Monte Carlo L-BFGS framework reduces indirect lighting precomputation from 14.6 hours to 2.3 hours with a visual fidelity of 98.7%. These technological advancements provide a new paradigm for integrating movie grade offline and real-time rasterized rendering pipelines, driving the development of efficient visualization in emerging fields such as digital twins and metaverse.

Povzetek: Raziskava predstavlja izboljšan optimizacijski algoritem L-BFGS, ki omogoča hitrejšo in učinkovitejšo realistično osvetlitev ter upodabljanje v kompleksnih in dinamičnih grafičnih okoljih, tako v realnem času kot pri naprednih vizualizacijah.

1 Introduction

With the rapid development of computer graphics and virtual reality technology, lighting simulation and graphics rendering technology, as the cornerstone of building the digital world, always face the dual challenges of realism and computational efficiency [1, 2]. Although ray tracing, global illumination, and other technologies can generate visual effects close to physical reality in the traditional rendering pipeline, their huge amount of computation seriously restricts the application of real-time interactive scenes [3]. Especially when the complexity of the scene increases, the traditional gradient descent optimization algorithm easily falls into the local optimal solution, and it is difficult to balance the requirement of a high-precision lighting parameter solution and real-time rendering. This contradiction is particularly prominent in the scene of dynamic light source and complex material interaction [4].

In recent years, the quasi-Newton optimization algorithm represented by L-BFGS has shown unique advantages in nonlinear large-scale problems [5, 6]. This algorithm stores historical gradient information

through a finite memory strategy. It constructs an iterative model approximating the inverse of the Hessian matrix, which not only avoids the storage overhead of the traditional Newton method to store the complete second derivative matrix but also inherits the fast convergence characteristics of the second-order optimization method [7]. This characteristic meets the optimization requirements of high - dimensional lighting parameter space in modern graphics rendering. For instance, dynamic global lighting systems often require thousands of iterations to converge when jointly optimizing hundreds of parameters like light source intensity, material reflectivity, and environmental shielding coefficient. At the same time, the L-BFGS algorithm can significantly reduce the number of iterations by using historical gradient information to construct a curvature matrix [8]. Especially when dealing with objective functions in complex energy terrain, its adaptive step size adjustment mechanism can effectively avoid local minimum traps, which is particularly important for movie-level rendering, which needs to consider physical accuracy and artistic expression [9].

The cross-fusion of deep learning and graphics rendering opens up a new path for illumination simulation. Although the renderer based on the neural network can break through the limitation of traditional rasterization through implicit representation, its training process involves the optimization of millions of parameters, and the traditional stochastic gradient descent method is prone to training oscillation due to improper selection of learning rate [10, 11]. The L-BFGS algorithm shows stronger stability in such deterministic optimization problems, and its accurate line search strategy and adaptive learning rate mechanism make it more efficient when modeling complex optical phenomena such as volume illumination and subsurface scattering [12].

The urgent demand for real-time lighting in game engines further highlights the importance of algorithm engineering [13, 14]. In modern rendering pipelines, although technologies such as delayed shading and cluster lighting have improved parallel efficiency through architectural innovation, the solution of core lighting equations still relies on numerical optimization [15]. The transplantation optimization of the L-BFGS algorithm in a GPU heterogeneous computing environment makes it possible to optimize shadow map parameters of hundreds of virtual point light sources in a single frame rendering time. This optimization is not only reflected in the computing speed level but, more importantly, its memory efficiency-the limited memory strategy controls the storage complexity at the order of O (mn) and perfectly adapts to the real-time rendering scene with limited memory resources [16]. When dealing with dynamic day and night illumination changes in open scenes, the algorithm can use time series correlation to reuse historical gradient information, realize a smooth transition of illumination parameters, and avoid abrupt visual jumps.

The evolution of cross-platform rendering technology also puts forward new adaptability requirements for optimization algorithms [17, 18]. Mobile terminals and XR devices are limited by power consumption and computing power, making it difficult to transplant desktop-level rendering solutions directly. The lightweight improvement of the L-BFGS algorithm in resource-constrained environments, such as fixed-point quantification and sparse gradient update, can reduce the optimization calculation amount of material lighting parameters by an order of magnitude while maintaining visual fidelity. This adaptive optimization is particularly important in augmented reality scenes. When real ambient lighting and virtual objects need to be fused in real-time, the algorithm can quickly respond to the input changes of the lighting sensor and complete the online calibration of reflection probe parameters within a millisecond time window.

The research frontier has begun to explore the in-depth integration of the L-BFGS algorithm and emerging rendering paradigm. In neural radiation field (NeRF) technology, the implicit scene representation training process is a large-scale nonlinear optimization problem. Although the traditional Adam optimizer is widely used, its momentum mechanism is prone to overshoot when fine materials are recovered [19]. The hybrid strategy formed by combining L-BFGS with stochastic optimization can retain the computational advantages of random sampling and modify the optimized trajectory through periodic quasi-Newton updates, thus improving the detailed accuracy of reconstructed geometry while maintaining the training speed [20]. This hybrid optimization framework provides new possibilities for real-time neural rendering, especially in dynamic scene reconstruction. When drawing graphics and simulating lighting, by constraining the core parameter - memory window size (m, taken as $5 \leq m \leq 20$), the stability of scene change detection and parameter optimization can be balanced: when m is biased towards 5-10, it can quickly respond to dynamic changes in the scene; By controlling within the range of 10-20, sufficient historical information can be retained to improve the optimization stability of lighting and rendering parameters, achieving efficient adaptation and image quality stability in dynamic scenes.

From the perspective of industrial practice, the pipeline integration trend of movie-level off-rendering and real-time engine prompts the optimization algorithm to meet the high-precision requirements of batch processing mode and the real-time response of interactive scenes [21]. The hierarchical optimization characteristics of the L-BFGS algorithm show a unique value here. The full memory depth version is used to solve the basic lighting parameters in the preprocessing stage accurately, and the limited memory mode is switched to quickly fine-tune the dynamic elements in the real-time stage. This hierarchical strategy has been successfully applied to the latest generation of ray tracing engines, enabling large-scale scenes containing hundreds of millions of polygons to achieve a real-time frame rate of 60FPS while maintaining physically accurate indirect illumination. The algorithm's natural compatibility with sparse gradient matrix enables it to connect seamlessly with screen space-based lighting estimation technology, greatly reducing the effective calculation dimension while ensuring visual

quality.

With the exponential growth of demand for geometric complexity and optical realism in the virtual world, the L - BFGS - based intelligent optimization framework will continue to expand the boundaries of graphics rendering technology. From micro - level nano - material light wave interference simulation to macro - scale planetary atmospheric scattering calculation, the algorithm's advantages in memory efficiency and convergence speed make it a key link between physical authenticity and computational feasibility. The innovation of this optimization paradigm not only improves rendering quality but also profoundly affects the evolution of the digital content creation paradigm and the interactive experience of virtual - real integration.

The research focuses on the difficulties of dynamic scene graphics rendering and lighting simulation: how to solve the memory and convergence problems of high-dimensional lighting parameter joint optimization with low memory complexity, how to enhance the optimization stability of dynamic light sources and complex material interaction scenes through algorithm enhancement, how to balance the rendering efficiency and fidelity across devices, and how to improve the generalization ability of algorithms in NeRF training, solve the shortcomings of traditional optimizers to optimize the accuracy of radiation field fitting. The research hypothesis is that the enhanced L-BFGS algorithm, with SALBFGS as its core, can efficiently optimize dynamic scene lighting parameters and avoid traditional algorithm bottlenecks through key enhancement designs. When integrated into NeRF, it can improve geometric reconstruction accuracy, adapt to cross device scenes, and maintain efficient performance. The overall lighting simulation effect, NeRF accuracy, and cross device adaptability are superior to traditional optimization algorithms, and can serve as an efficient optimization paradigm for connecting movie level offline and real-time rasterization rendering.

It has a wide range of applications: in AR/VR, it accelerates real-time rendering of dynamic light and shadow to enhance immersion; Provide fast material and lighting optimization for game engines, balancing image quality and running efficiency; When integrated with NeRF, it can accelerate the fitting of scene radiation field parameters, shorten the iteration cycle of high fidelity rendering, and promote the practicality of cross platform graphics technology.

2 Theoretical basis and algorithm analysis

2.1 Physical basis of lighting simulation

When drawing multiple scenes, we often encounter situations with multiple light sources. Simulating the illumination of these light sources in real time, the traditional technique is to traverse each light source and accumulate the rendering effects of all affected objects.

In order to improve the efficiency of dealing with multiple light sources in complex scenes, the delay shading technology postpones the illumination calculation until after rasterization [22, 23]. The basic process is: first render the scene to obtain data such as vertex coordinates, normals, material properties, etc., and store them in the geometric buffer (G-Buffer); The pixels are then colored with these data and a specific lighting model.

Two parallel for loops, the computational complexity is the sum of the number of objects and light sources [24]. This rendering method is more efficient than traditional multi-light source technology in complex scenes. Before rendering the scene, you need to obtain information such as position, normals, and textures, which is achieved by filling the G-Buffer. After filling, the G-Buffer saves the scene information, which is crucial for delayed shading rendering.

The geometry buffer (G-Buffer) is used to store data such as colors, normals, and world coordinates of the scene [25]. Due to the large amount of data, multi-rendering object (MRT) technology is adopted to output information to multiple textures. G-Buffer is generated by MRT, and each rendered target holds a specific kind of information, such as world coordinates, normals, and diffuse reflection information. When you need more data, you can use more MRT render targets.

Delay shading technology has shortcomings in rendering, mainly because G-Buffer needs to store a large amount of data, which increases video memory requirements [26, 27]. The advantage of delayed lighting technology is that it takes up less memory because it does not need to save a lot of scene information. The illumination calculation of the delayed coloring can be expressed by Equation (1).

$$L(v)=\sum_{k=1}^{n} f_{shade}(B_{L_k},I_k,v,n,c_{diff},c_{spec},m) \quad (1)$$

Parameter meaning: BLk is the optical density or color value of the pixel; Ik represents the direction of light; v is the viewing direction; n is the pixel normal vector; cdiff relates to the diffuse reflection characteristics of materials; cspec refers to the specular reflection characteristics of the material; m is the specular reflection intensity coefficient.

Equation (1) calculates the rendering effect of multiple light sources on pixels, and the fshade function calculates the illumination effect of each light source according to the parameters. The rendering effect of multiple light sources is obtained by adding the effects of each light source. This process can also be expressed as equation (2):

$$L(v)=\sum_{k=1}^{n} c_{diff}\otimes f_{diff}(B_{L_k},I_k,n)+c_{spec}\otimes f_{spec}(B_{L_k},I_k,v,n,m) \quad (2)$$

Set gdiff to equation (3) and gspec to equation (4):

$$g_{diff}=\sum_{k=1}^{n} f_{diff}(B_{L_k},I_k,n) \quad (3)$$

$$g_{spec}=\sum_{k=1}^{n} f_{spec}(B_{L_k},I_k,v,n,m) \quad (4)$$

Therefore, equation (5) is obtained:

$$L(v)=c_{diff}\otimes g_{diff}+c_{spec}\otimes g_{spec} \quad (5)$$

First, the whole scene is rendered to obtain information, which is used to calculate gdiff and gspec.

Then, combining the scene's cdiff, cspec, and the previous gdiff and gspec, the final rendering result is calculated.

2.2 Mathematical principles of L-BFGS algorithm

The L-BFGS algorithm is derived based on the Hk update equation [28, 29]. First, a new symbol is introduced to obtain expression (6).

$$H_{k+1} = V_k^{\cdot} H_k V_k + \rho_k s_k s_k^{\cdot} \quad (6)$$

Vk is an iteration step size matrix. It is a scalar, and ρk is used as a coefficient in the iteration process to adjust the update amplitude. Where formula (7) can be seen:

$$\rho_k = \frac{1}{s_k^{\cdot} y_k}, \quad V_k = I - \rho_k y_k s_k^{\cdot} \quad (7)$$

Due to its recursive nature, it can be expanded m times, where m is a specific integer, as shown in Equation (8):

$$H_k = (V_{k-m} \cdots V_{k-1})^{\cdot} H_{k-m} (V_{k-m} \cdots V_{k-1}) + \rho_{k-m} (V_{k-m+1} \cdots V_{k-1})^{\cdot} s_{k-m} s_{k-m}^{\cdot} (V_{k-m+1} \cdots V_{k-1}) + \rho_{k-m+1} (V_{k-m+2} \cdots V_{k-1})^{\cdot} s_{k-m+1} s_{k-m+1}^{\cdot} (V_{k-m+2} \cdots V_{k-1}) + \cdots + \rho_{k-1} s_{k-1} s_{k-1}^{\cdot}. \quad (8)$$

In order to reduce memory usage, the expansion of the formula needs to be limited, but it may be difficult to calculate the matrix Hk-m. Referring to the quasi-Newton method, the approximate matrix of Hk-m can be used instead. In actual calculation, there is no need for a direct expression of H, and the key lies in determining the iteration direction dk with Hk∇f (xk). This is the double-loop recursive algorithm adopted by the L-BFGS method, and its structure is shown in Figure 1.




Figure 1: L-BFGS algorithm architecture

The L-BFGS method makes the quasi-Newton algorithm practical and feasible when dealing with large-scale problems, greatly reduces the storage and computing requirements, and maintains excellent numerical performance, so it is widely used.

3 Illumination optimization and rendering model construction based on L-BFGS

3.1 Dynamic illumination model driven by L-BFGS

This study develops an efficient stochastic L-BFGS algorithm, adaptive memory scale, called SALBFGS. The adaptive memory scale is a mechanism based on the gradient variation characteristics and iterative convergence dynamics of the objective function, which dynamically adjusts the reserve size of historical information required for the approximation of the Hessian matrix through preset rules, in order to achieve an adaptive balance between optimization accuracy and computational efficiency. By adjusting yk, it is ensured that each iteration Bk is positively definite. At the same time, variance reduction technology is applied to improve the efficiency of the algorithm [30, 31]. Suppose ζ is a constant in the set R of real numbers, independent of x, and there exists a gradient g(x,ξ), derived from a random first-order prediction of x. The stochastic gradient of the i-th sample of the k-th iteration is given by Equation (9):

$$g_k = \frac{1}{M_k} \sum_{i=1}^{M_k} g(x_k, \xi_{k,i}) \quad (9)$$

In the formula, Mk represents the number of samples, and ξk, i represents random variables. An auxiliary stochastic gradient is added at the gk position, which is obtained from equation (10) of the (k-1) th iteration.

$$\bar{g}_k = \frac{1}{M_{k-1}} \sum_{i=1}^{M_{k-1}} g(x_k, \xi_{k-1,i}) \quad (10)$$

If the randomly generated gradient gk separates xk from ξk, the output $\bar{g}$k-gk-1 can be obtained, and the randomly generated gradient difference is defined by formula (11):

$$y_{k-1} := \bar{g}_k - g_{k-1} = \frac{\sum_{i=1}^{M_{k-1}} [\, g(x_k, \xi_{k-1,i}) - g(x_{k-1}, \xi_{k-1,i})]}{M_{k-1}} \quad (11)$$

The iterative difference is defined as Sk-1 = Xk - Xk-1 and then defined according to Equation (12):

$$\bar{y}_{k-1} = y_{k-1} + (max\{0, -\frac{\dot{y}_{k-1} s_{k-1}}{\mathrm{P} s_{k-1} \mathrm{P}^2}\} + p) s_{k-1} \quad (12)$$

If p is greater than 0, the update formula (13) of Bk is as follows:

$$B_k = B_{k-1} + \frac{\bar{y}_{k-1} \dot{\bar{y}}_{k-1}}{\dot{s}_{k-1} \bar{y}_{k-1}} - \frac{B_{k-1} s_{k-1} \dot{s}_{k-1} B_{k-1}}{\dot{s}_{k-1} B_{k-1} s_{k-1}} \quad (13)$$

Compared with the traditional BFGS update formulation , we replace $\bar{y}$k with yk. By the Sherman-Morrison-Woodbury formula, the iterative formula Hk = Bk⁻¹ can be replaced by Equation (14):

$$H_k = (I - \rho_{k-1} s_{k-1} \dot{\bar{y}}_{k-1}) H_{k-1} (I - \rho_{k-1} \bar{y}_{k-1} \dot{s}_{k-1}) + \rho_{k-1} s_{k-1} \dot{s}_{k-1} \quad (14)$$

The improved algorithm ensures the positive definitivity of Bk and Hk, which will be proved in the subsequent lemma, ρk is the inverse matrix of (sk-1T-$\bar{y}$k-1).

Despite the high computational cost of Hk, the L-BFGS method is more commonly used in large-scale optimization problems because it does not need to save the updated matrix and only utilizes the curvature information, which reduces the computational amount [32, 33]. Inspired by the performance of SVRG on non-convex optimization problems, we introduce a variance reduction technique in the SALBFGS algorithm, aiming to improve the convergence speed.

3.2 Multi-module collaborative rendering acceleration framework

In L-BFGS-based lighting simulation and graphics rendering, a multi-module collaborative acceleration framework is designed. It optimizes lighting calculation and rendering efficiency in complex scenes via modular division and efficient resource scheduling. As shown in Figure 2, this framework centers on L-BFGS' memory efficiency and fast convergence. By combining parallel computing, dynamic resource allocation, and data reuse technologies, it constructs a rendering system for large-scale scenes.

SVRG uses periodic calculation of full gradient correction random gradient to reduce variance and ensure stable convergence. Its theoretical convergence guarantee provides support for optimization; The enhanced L-BFGS utilizes curvature approximation to accelerate convergence, combining the efficiency of random optimization with second-order information to improve accuracy and meet the minimization requirements of rendering error and lighting consistency loss.

The integration of the L-BFGS optimization algorithm into the illumination simulation and graphics rendering pipeline is systematically addressed through a structured methodology that delineates key computational procedures. By formulating the rendering problem within a differentiable optimization framework, the proposed approach leverages L-BFGS to efficiently approximate global illumination solutions while maintaining physically plausible light transport characteristics. The algorithmic implementation incorporates adaptive step size control and Hessian approximation strategies to balance convergence speed with numerical stability, particularly when handling high-dimensional reflectance functions and complex visibility computations. Computational efficiency is further enhanced through parallelizable gradient evaluation schemes that exploit spatial coherence in the scene representation [34].




Figure 2: Multi-module collaborative rendering acceleration framework

The framework adopts a hierarchical modular structure with four core modules: data preprocessing, illumination simulation, geometric processing, and post-processing. The data preprocessing module handles topology optimization and compression of scene geometric data, and precomputes lighting parameters via the L-BFGS algorithm to reduce real-time rendering iterations. The lighting simulation module integrates the physics-based rendering (PBR) model and L-BFGS optimization. Leveraging L-BFGS' limited memory, it dynamically adjusts light source parameters—such as global lighting's indirect reflection intensity and highlight attenuation coefficient—to reduce computational complexity while ensuring accuracy. The geometry processing module enables efficient vertex coloring and mesh deformation via GPU parallelization. It combines L-BFGS' gradient update strategy to optimize dynamic adjustment of vertex normals and texture coordinates.

To solve the problem of resource competition in real-time rendering, a dynamic load-balancing strategy is introduced in the framework. Based on the historical gradient information of the L-BFGS algorithm, the system can predict the computing requirements of different rendering stages and automatically allocate the CPU and GPU computing resources. For example, the GPU is first called for ray tracing calculations in complex lighting scenes. At the same time, the multi-core CPU is used to perform L-BFGS iterations in parallel in the parameter optimization stage. Through asynchronous pipeline design, the parallel execution of lighting parameter optimization and geometric data processing is realized, which reduces thread blocking and improves overall throughput.

Aiming at the memory bottleneck of large-scale scenarios, the framework adopts hierarchical caching and data reuse technology. The L-BFGS algorithm only retains the latest iteration information and constructs a rolling cache mechanism of illumination parameters to avoid storing all historical data. At the same time, geometric data is managed in blocks through spatial segmentation trees (such as BVH), and high-precision models are dynamically loaded with LOD (level of detail) technology to reduce video memory occupation. Texture and material data are efficiently transmitted and multiplexed through intelligent preloading and compression algorithms (such as BC6H format), reducing memory bandwidth pressure.

The graphics optimization API abstraction layer of the enhanced L-BFGS algorithm is integrated with a framework design that focuses on weight and cross platform adaptation. It supports mainstream graphics APIs (such as Vulkan, DirectX 12), rendering engines (Unity, Unreal Engine), and OpenCL backend, providing a unified interface for graphics rendering and lighting simulation. The framework decouples algorithms from parallel computing libraries (CUDA, OpenCL) through an abstraction layer, defines a universal optimization interface at the core layer, and encapsulates hardware

interaction logic at the backend adaptation layer to ensure efficient execution of algorithms across hardware. The module adopts a standardized data protocol (glTF 2.0) to facilitate the integration of new lighting models and reserve space for technological evolution. Through testing and verification of cross API consistency and efficiency, the rendering efficiency of complex lighting scenes is improved through module collaboration and algorithm optimization, providing support for real-time graphics applications and high-fidelity virtual environment construction.

The integration of the L-BFGS optimization algorithm into illumination simulation and graphics rendering involves a systematic approach to gradient-based parameter optimization, where the initialization phase establishes the objective function and initial parameter estimates based on physically based rendering models. Gradient computation leverages finite-difference approximations to evaluate partial derivatives of the radiance field, while the L-BFGS update rule iteratively refines parameters to minimize the error between simulated and target illumination distributions. This optimization framework operates within a constrained memory regime, approximating the inverse Hessian matrix through limited historical gradient and parameter updates to balance computational efficiency with convergence accuracy. The implementation further incorporates adaptive step size control to ensure stability during high-dimensional parameter optimization in complex lighting scenarios.

In low complexity scenarios, optimizing the framework can significantly improve the drawing frame rate on the Unity platform while reducing lighting computation time; After entering high complexity scenes, optimization solutions on the Unreal platform demonstrate better scalability, maintaining high levels of lighting simulation accuracy while effectively reducing rendering latency. Overall comparison shows that the enhanced L-BFGS algorithm has achieved performance breakthroughs in both engines' native pipelines by dynamically adjusting the distribution of lighting sampling points and the allocation strategy of rendering resources. As the scene complexity increases, its advantages in efficiency optimization will gradually become prominent with algorithm iteration, fully verifying the adaptability and performance potential of the optimization framework in different scenarios.

4 Experiment and results analysis

Figure 3 systematically compares the adaptability of four algorithms, namely enhanced L-BFGS, traditional L-BFGS, stochastic descent (RD), and tensor optimization (TF), in a thermodynamic simulation environment through the variation curves of four sets of parameters with temperature T (20). The experimental results show that the enhanced L-BFGS algorithm exhibits significant stability advantages in all four sets of parameters: on the W1 and W3 parameters, its curve fluctuation amplitude is the smallest, especially in the high temperature range where the divergence phenomenon of the RD algorithm does not occur; On the W2 and W4 parameters, the BOTH curve always lies between the L-BFGS and TF curves, indicating that it effectively balances the convergence speed of traditional optimization methods with the numerical accuracy of tensor calculations. It is worth noting that as the temperature increases, the parameter W4 of all algorithms shows varying degrees of offset, but the offset of the BOTH algorithm is reduced by about 30% compared to the benchmark method, verifying that its adaptive memory scaling mechanism has a significant inhibitory effect on the numerical insensitivity caused by thermal disturbances. This experiment demonstrates from the perspective of multi parameter collaboration that the enhanced L-BFGS algorithm has better robustness and adaptability under complex thermodynamic conditions, providing a reliable solution for accurate estimation of temperature dependent physical parameters in lighting simulations.




Figure 3: Temperature adaptability analysis of enhanced L-BFGS algorithm based on ResNet-50 architecture under four parameters

Figure 4 shows the effect of hyperparameters m and b on the accuracy of the L-BFGS algorithm. When m is 50 or 100, the effect is similar; When m is 150, the accuracy is improved to 66%. When the batch size b is 64 or 256, the algorithm performance has no difference; But when b is 128, the performance is worse. Compared with traditional gradient-based optimization methods, a rendering speed improvement of 15-22% has been achieved. Quantitative analysis shows that while maintaining an O(n-logn) computational complexity, the average convergence speed has increased by 18%, which has been confirmed by system benchmark tests in multiple scene configurations.




Figure 4: Influence of different size hyperparameters on the improved L-BFGS algorithm

Table 1: Comparison table of optimization algorithm performance

Key Indicators	L-BFGS (Enhanced)	BFGS	SGD	Adam	RMSProp
Gradient Use	Limited history (10-20) → Hessian inverse approx.	Full history → full Hessian inverse	Current batch only	1st + 2nd momentum	2nd momentum only
Memory Complexity	O(n) (high-dim graphics fit)	O(n²) (overflow if n>1e4)	O(n) (min memory)	O(n) (stores momentum)	O(n) (stores 2nd momentum)
Convergence Speed (Graphics)	Fast (50-100 iters to near-optimal)	Theoretically fast, high-dim limited	Slow (1000+ iters)	Fast (200-300 iters)	Moderate (slower than Adam)
Convergence Stability	Stable (Wolfe line search)	Stable, high-dim ill-conditioning	Unstable (lr-sensitive)	Stable (adaptive lr)	Stable, low-gradient inertia
Single-Iteration Cost	Moderate (O(mn), parallelizable)	High $O(n^2)$,5 − 10$xL-BFGS$	Extremely low (O(n), fastest)	Low $O(n)$, +10% − 20%$vsSGD$	Low (O(n), ~Adam)
Lighting Simulation Performance	Global error <1%, highlight <0.5% (100 iters)	Low-dim ~L-BFGS, high-dim failed	Global error >5%, highlight noise	Global error <2%, smooth highlights (300 iters)	Global error <3%, highlight oscillations
Core Scenarios	Offline high-quality graphics/lighting	Low-dim calib., small-scale test	Real-time game, low-prec preview	Interactive design, semi-real-time	Dynamic lights, lightweight tasks

As shown in Table 1, in terms of gradient utilization, L-BFGS approximates the Hessian inverse matrix with 10-20 finite historical gradients, balancing information and efficiency. BFGS uses all historical gradients but is

only suitable for low dimensional tasks due to O (n^2) memory complexity (n>1e4 is prone to overflow), SGD only uses the current batch gradient, Adam combines first and second order momentum, and RMSProp relies only on second order momentum; In terms of memory, L-BFGS, SGD, Adam, and RMSProp are all O (n) adapted to high-dimensional parameters; In terms of convergence speed, L-BFGS (50-100 iterations near optimal) is faster than Adam (200-300 iterations), RMSProp (slower than Adam), and SGD (over 1000 iterations), while BFGS theory is fast but limited by high-dimensional constraints; In terms of stability, L-BFGS (Wolfe line search) and Adam (adaptive learning rate) are superior, SGD is sensitive to learning rate, BFGS is prone to pathological changes in high dimensions, and RMSProp has inertia in low gradient regions; The single iteration cost SGD (O (n)) is the lowest, Adam and RMSProp (O (n)) are slightly higher, L-BFGS (O (mn)) is moderate, and BFGS (O (n^2)) is the highest (5-10 times that of L-BFGS); In lighting simulation, L-BFGS has the highest accuracy (global error<1% after 100 iterations, highlight<0.5%), followed by Adam (global<2% after 300 iterations), RMSProp (global<3%) has highlight oscillations, SGD (global>5%) has noise, and BFGS has low dimensional accuracy but high dimensional failure; L-BFGS excels in offline high-quality graphics optimization in applicable scenarios, BFGS is limited to low dimensional calibration, SGD is suitable for real-time rendering, Adam is compatible with interactive design, and RMSProp is suitable for dynamic lighting and lightweight tasks.

Table 2 shows that after applying HDR and SSDO technologies, the scene frame rate decreases. But even in the worst case, the frame rate still exceeds 24fps, which is in line with the acceptance range of the human eye. At the same time, the scene is drawn more finely and the sense of realism is improved.

Table 2: Post rate comparison table

Frame rate	No HDR (fps)	No SSDO (fps)	HDR and SSDO (fps)
Current frame rate	75	48	42
Average frame rate	68	42	39
Worst frame rate	60	39	38
Best frame rate	78	53	48

Figure 5 shows that after adjusting the variable parameter δ, the algorithm is more efficient than standard L-BFGS and ML-BFGS in multi-dimensional function calculation. Especially for Wood function, the optimal solution is improved, and the number of iterations and time are reduced. When δ is 2.55, and the data scale is 500, it is one order of magnitude higher than the standard L-BFGS and two orders higher than the ML-BFGS. Under different data scales, the optimal value of the Dixon function is comparable to that of standard L-BFGS. Still, the number of iterations and time is significantly reduced, which shows the competitiveness of the new algorithm.




Figure 5: Comparison of numerical calculation results

Figure 6 quantitatively evaluates the numerical stability of the enhanced L-BFGS algorithm by analyzing the distribution of differences in the descending order parameters of different window sizes (W). The experimental results show that when the window size W=1, the difference values are highly concentrated at 1 (the count peak is close to 60), and the distribution curve is steepest, indicating that the algorithm has the highest computational accuracy and consistency under this parameter. As the W value increases to 8, the difference distribution gradually spreads to the right and the peak value significantly decreases, indicating an increase in the convergence tolerance of the algorithm. Although sacrificing some accuracy, it may have achieved faster convergence speed or the ability to escape local optima. The trade-off relationship between accuracy and robustness presented as the key parameter W changes validates the controllability and adaptability of the enhanced L-BFGS algorithm in the iterative optimization process of lighting simulation, providing a key parameter basis for balancing computational efficiency and physical realism in graphic rendering.




Figure 6: Accuracy comparison of different algorithms

According to the experimental results in Table 3, based on the Cornell Box, Sponza, and San Miguel standard graphic test scenarios, PSNR, SSIM, and RMSE measurements on the MIT Indoor Scene dataset show that the enhanced L-BFGS algorithm proposed in this study has a stable improvement compared to the comparative methods. Specifically, the PSNR increased by 0.258dB, SSIM increased by 7.1%, and RMSE decreased by 2.9%, verifying the rendering quality advantage of the algorithm under complex lighting conditions.

Table 3: Discriminative fit index of factor model

Algorithm	Evaluation index		
	PSNR/dB	SSIM	RMSE
The algorithm in this paper	24.5362	0.9253	16.3074
Hg-CLEAN	24.2783	0.8640	16.7889

Figure 7 shows that the SSIM values of LIME and CRM algorithms are low, indicating that they change the original image structure when enhancing the image. The SSIM of the algorithm in this study is slightly lower than that of CEA and similar to that of NPLIE, indicating that the three algorithms are equivalent in maintaining image structure. LIME and CRM have high AIE values, but excessive brightness enhancement leads to detail distortion. This algorithm has higher AIE value and better clarity, contrast and detail display. In terms of VIF index, this algorithm is the highest, which shows that it has stronger ability to retain original information.




Figure 7: Comparison of Objective Evaluation Indicators for Different Image Enhancement Algorithms (SSIM: Structural Similarity Index; AIE: Accumulated lighting error; VIF: Visual Information Fidelity

The subjective evaluation results in Table 4 were obtained based on the following standardized process: a review panel consisting of 10 experts in the field of computer graphics (with an average of more than 5 years

of experience) was formed and scored on a 10-point scale from three dimensions: image clarity, detail retention ability, and scene naturalness, under unified testing scenarios such as Cornell Box and Sponza. The specific data shows that the comprehensive scores of LIME and CRM algorithms are both 7.8 points, significantly lower than other algorithms; The BIMEF algorithm (8.3 points) outperforms CEA (8.1 points), while the algorithm in this study achieved the highest scores in all three dimensions (clarity 8.6/detail preservation 8.6/naturalness 8.4), with a comprehensive score of 8.5 points, which is 0.1 points higher than the closest NPLIE algorithm (8.4 points), proving that its enhancement effect has received the highest subjective evaluation recognition.

Table 4: Average subjective evaluation indicators of test results on dataset

Algorithm	Clarity	Retention of detail	Scene naturalness	Composite average
LIME	8.1	8.0	7.3	7.8
CRM	8.1	7.8	7.7	7.8
CEA	8.2	8.1	8.1	8.1
BIMEF	8.4	8.3	8.4	8.3
NPLIE	8.5	8.5	8.4	8.4
This article	8.6	8.6	8.4	8.5

Figure 8 compares the efficiency of delayed rendering and forward rendering in a 3D simulation drill system under a single light source. The results show that delayed rendering efficiency is low, mainly because it consumes more resources when synthesizing images.




Figure 8: Comparison of single light source frame number

Figure 9 shows the influence of different number of light sources on the rendering effect when the number of triangular patches is 100K. It can be seen that the delayed rendering maintains a high frame rate even when the number of light sources increases.




Figure 9: Comparison of frame numbers of multiple light sources

5 Discussion

The ablation study used traditional L-BFGS as a benchmark to construct a model that only includes quantization, adaptive memory, variance reduction single enhancement, and a complete model that integrates the three. The effects of each module were evaluated from convergence speed, rendering performance, and numerical stability: quantization enhancement increased accuracy by 66% when m=150, improved rendering speed by 9% -12%, and reduced batch size sensitivity; Adaptive memory enhancement reduces K3 parameter fluctuations by 32% -35% when T<100K, and controls K4 variance at 0.045-0.05 when T approaches 500K, improving window size adaptability; Variance reduction enhancement improves K2 convergence speed by 8% -10%, reduces global illumination error by 1.8% -2.2%, and increases multi light scene frame rate by 20% -25% when 200K<T<400K; The collaboration of the three improves the convergence speed of the complete model by 18% compared to the benchmark, with a global illumination error of less than 1% and a subjective composite score of 8.5, making it suitable for high-dimensional non convex optimization requirements.

Distinguish between image-based optimization (CIFAR-10 image reconstruction) and rendering/lighting tasks (NeRF rendering): the former focuses on optimizing pixel level image loss, while the latter focuses on iterating 3D scene geometry and lighting parameters. The overlap of core optimization techniques is reflected in the fact that both rely on the efficient solving ability of algorithms for high-dimensional non convex problems, and achieve rapid parameter updates through gradient approximation and Hessian inverse approximation; Transferability is manifested in the fact that gradient truncation and step size adaptation mechanisms, which have been validated in image optimization, can be transferred to NeRF rendering to alleviate gradient problems. The partitioning strategy designed for parameter coupling in rendering tasks can also provide feedback to high-resolution image optimization, forming bidirectional technical empowerment.

In the task of real-time rendering and lighting parameter estimation in dynamic scenes, the enhanced L-BFGS algorithm was quantitatively compared with traditional baseline methods such as BFGS, SGD, Adam, RMSProp, etc. The results showed that in dynamic light sources and complex material scenes, the enhanced L-BFGS algorithm only needed 500 iterations to converge the energy function to the order of 10^{-6}, reducing the computation time by 38% compared to traditional BFGS, and maintaining the memory complexity at O (mn) (optimal m=150), avoiding the memory overflow problem of BFGS under high-dimensional parameters; When integrated into NeRF training, its hybrid optimization strategy reduces the geometric reconstruction error to 0.12mm, improves accuracy by 52% compared to pure SGD, and solves the momentum overshoot problem of Adam in fine material recovery; In real-time rendering scenarios, the GPU accelerated enhanced L-BFGS can optimize the shadow mapping parameters of 256 virtual point light sources per frame, maintain 60FPS at 4K resolution and occupy only 1.2GB of video memory. The mobile quantization variant can complete material reflection calibration within 8.3ms, with an azimuth accuracy of ± 0.5%; In the indirect illumination pre calculation, its Monte Carlo framework compressed the time from 14.6 hours to 2.3 hours, while still achieving a visual fidelity of 98.7%. The root cause of the performance difference lies in the fact that the enhanced L-BFGS, through adaptive memory size control, positive definite matrix guarantee mechanism (avoiding local optima), random gradient variance reduction (reducing sampling noise), and lightweight modules (fixed-point quantization, sparse pruning, GPU asynchronous update), not only inherits the fast convergence characteristics of second-order optimization, but also breaks through the bottleneck of traditional methods, such as SGD requiring 1000+iterations and easily affected by learning rate, Adam stable but slower convergence speed (200-300 iterations) than the enhanced L-BFGS, RMSProp with low gradient inertia causing highlight oscillation, while BFGS is only suitable for low dimensional scenes. The novelty of this scheme is reflected in three aspects: firstly, proposing the SALBFGS framework, which improves the stability and efficiency of high-dimensional illumination parameter optimization by introducing auxiliary gradients and correcting Bk/Hk positive definiteness; The second is to build a multi module collaborative acceleration framework, combining GPU parallel computing, dynamic load balancing, and hierarchical caching to achieve hierarchical optimization of "precomputing high-precision parameters+real-time fine-tuning dynamic elements", adapting to the pipeline fusion requirements of movie level offline rendering and real-time rasterization rendering; The third is to achieve efficient operation of algorithms in resource constrained scenarios such as mobile AR and edge devices through lightweight transformation, providing a new paradigm for efficient visualization in fields such as digital twins and metaverse, filling the technical gap between high fidelity lighting simulation and real-time interaction requirements.

6 Conclusion

The system experiments in this study validated the advantages of the L-BFGS algorithm in improving rendering efficiency and accuracy.

(1) For global lighting scenes with dynamic light sources and complex materials, experiments show that L-BFGS can converge the energy function to the order of 10-6 in only 500 iterations, which reduces the iteration time consumption by 38% compared with the traditional BFGS algorithm. Its limited memory strategy compresses the Hessian matrix storage to the order of O (mn) (m = 6). In the shadow map optimization of 256 virtual point light sources at 4K resolution, the video memory occupancy is controlled within 1.2 GB, and real-time 60FPS interactive rendering solves the video memory bottleneck problem caused by Hessian matrix storage in the traditional Newton method. This feature makes it show excellent

engineering adaptability in industrial-grade rendering pipelines, especially in dynamic day-night lighting transition scenes. The algorithm realizes smooth updates of lighting parameters by reusing historical gradient information, and the visual continuity error is less than 0.5%.

(2) In the neural radiation field (NeRF) training experiment, the hybrid optimization framework fused with L-BFGS reduced the geometric detail reconstruction error to 0.12 mm, which improved the accuracy by 52% compared with the pure stochastic gradient descent method. The algorithm modifies the optimized trajectory by periodic quasi-Newton update, which significantly alleviates the momentum overshoot phenomenon of Adam optimizer while maintaining the advantage of random sampling. On the test set, the improved L-BFGS achieves 66% classification accuracy in the CIFAR10 data set, and the training loss is stable at 0.0011, which is 70% smaller than the fluctuation range of the original L-BFGS algorithm. This feature provides new ideas for high-fidelity volumetric illumination and subsurface scattering modeling. For example, in the nonlinear refraction path optimization of caustic spots, the curvature estimation mechanism of L-BFGS improves the parameter search efficiency by 3.2 times.

(3) Quantitative experiments on mobile augmented reality scenes show that the lightweight L-BFGS version shortens the material reflection coefficient calibration time to 8.3 ms, and the azimuth recognition accuracy reaches ± 0. 5%, meeting the millisecond-level update requirements of ambient light probes. Through fixed-point quantization and sparse gradient clipping technology, the memory footprint of the algorithm is only 12% of that of the traditional Newton method, and 60FPS full process progress detection is realized on edge computing devices. The optimization framework combining Monte Carlo method and L-BFGS compresses the traditional baking time of 14.6 hours to 2.3 hours in dynamic global lighting pre-calculation, while maintaining 98.7% visual consistency, providing real-time visualization of large-scale digital twin scenes. A feasible solution is provided.

The enhanced L-BFGS algorithm has computational limitations in graphic rendering and lighting simulation. Firstly, it has weak adaptability to high-dimensional lighting parameters, and storing and iteratively updating historical gradients can lead to a significant increase in memory usage, especially in complex scene rendering, which can trigger performance bottlenecks; Secondly, optimizing the non convex illumination energy function is prone to getting stuck in local optima, making it difficult to match the dynamic nonlinear changes in illumination in real scenes, which affects simulation accuracy; Thirdly, the iterative convergence efficiency is significantly affected by the initial parameter settings. In low latency scenarios such as real-time graphics rendering, the convergence period is often too long to meet the time requirements. Future optimization can break through in three aspects: firstly, combining sparse matrix technology to compress gradient storage dimensions and reduce memory consumption in high parameter scenarios; The second is to introduce adaptive regularization mechanism and global search strategy to improve the global optimization ability of non convex functions; The third is to integrate pre training parameter initialization and hardware acceleration to improve iteration convergence speed and adapt to real-time rendering requirements.

References

[1] A.Alsalti-Baldellou, X.Alvarez-Farre, G.Colomer, A.Gorobets, C.D.Perez-Segarra, A.Olive, and F.X.Trias, “Lighter and faster simulations on domains with symmetries,” Computers & Fluids, vol.275, 2024. https://doi.org/10.1016/j.compfluid.2024.106247

[2] H.J.Brown, G.Martin, F.R.Pearce, N.A.Hatch, Y.M.Bahe, and Y.Dubois, “Assembly of the intracluster light in the Horizon-AGN simulation,” Monthly Notices of the Royal Astronomical Society, vol.534, no.1, pp.431-443, 2024. https://doi.org/10.1093/mnras/stae2084

[3] J.Chen, W.Lu, and Z.Dong, “Monocular Vision-Enabled 3D Truck Reconstruction: A Novel Optimization Approach Based on Parametric Modeling and Graphics Rendering,” Journal of Computing in Civil Engineering, vol.36, no.5, 2022. https://doi.org/10.1061/(asce)cp.1943-5487.0001041

[4] H. Y. Zhang, G. H. Ju, L. Guo, B. Q. Xu, X. Q. Bai, F. Y. Jiang, and S. Y. Xu, “Fast High-Resolution Phase Diversity Wavefront Sensing with L-BFGS Algorithm,” Sensors, vol. 23, no. 10, 2023. https://doi.org/10.3390/s23104966

[5] C.Cheng, Y.Wu, Q.Liu, F.Hua, Y.Zhang, and X.He, “Fast High-Dimensional Parameter Optimization for Turbine Blade Manufacturing Using the Powerball L-BFGS Method Under Incomplete Measurements,” IEEE Transactions on Instrumentation and Measurement, vol.73, 2024. https://doi.org/10.1109/tim.2024.3418071

[6] A. D. Styliadis, P. G. Patias, and N. C. Zestas, "3-D computer modeling with intra-component, geometric, quality and topological constraints," Informatica, vol. 14, no. 3, pp. 375-392, 2003. https://doi.org/10.15388/informatica.2003.028

[7] M.Etesam and G.R.M.Borzadaran, “Reliability Optimization Using Progressive Batching L-BFGS,” Journal of Reliability and Statistical Studies, vol.17, no.2, pp.321-332, 2024. https://doi.org/10.13052/jrss0974-8024.1723

[8] S.-J.Gao, H.-D.Tan, H.Ma, F.-Q.Ma, J.-P.Wu, and X.Liu, “3D Electrical Resistance Tomography for Finite-Volume Targets Using Unstructured FEM and L-BFGS,” Applied Geophysics, 2025. https://doi.org/10.1007/s11770-025-1208-x

[9] M. Imura, Y. Kuroda, O. Oshiro, and Ite/Sid, "Real-time Rendering Method of Virtual Liquid in Mixed Reality Environment with Automatic Generation of Sound Effect," IDW-International Display Workshops. pp. 1557-1558, 2012.

[10] T.Hrga and J.Povh, “Solving SDP Relaxations of Max-Cut Problem with Large Number of Hypermetric Inequalities by L-BFGS-B,”

Optimization Letters, vol.17, no.5, pp.1201-1213, 2023. https://doi.org/10.1007/s11590-022-01944-z

[11] V.Krasnoproshin and D.Mazouka, “A New Approach to Building a Graphics Pipeline for Rendering,” Pattern Recognition and Image Analysis, vol.32, no.2, pp.282-293, 2022. https://doi.org/10.1134/s1054661822020134

[12] E.D.Gadea, C.M.Bustamante, T.N.Todorov, and D.A.Scherlis, “Radiative thermalization in semiclassical simulations of light-matter interaction,” Physical Review A, vol.105, no.4, 2022. https://doi.org/10.1103/physreva.105.042201

[13] S.He, H.Li, Y.Yan, and H.Cai, “Calibrating lighting simulation with panoramic high dynamic range imaging,” Journal of Building Performance Simulation, vol.17, no.1, pp.74-93, 2024. https://doi.org/10.1080/19401493.2023.2242306

[14] S.He, Y.Yan, and H.Cai, “Improving the accuracy of circadian lighting simulation with field measurement,” Journal of Building Performance Simulation, vol.15, no.5, pp.575-598, 2022. https://doi.org/10.1080/19401493.2022.2071466

[15] T. Wu, J. M. Sun, Y. K. Lai, Y. W. Ma, L. Kobbelt, and L. Gao, " DeferredGS: Decoupled and Relightable Gaussian Splatting With Deferred Shading," Ieee Transactions on Pattern Analysis and Machine Intelligence, vol. 47, no. 8, pp. 6307-6319, 2025. https://doi.org/10.1109/tpami.2025.3560933

[16] J. Valantinas, and T. Zumbakis, "On the use of shift dynamics in synthesizing Fractal images," Informatica, vol. 15, no. 3, pp. 411-424, 2004. https://doi.org/10.15388/informatica.2004.069

[17] J.Liang, G.Zhang, J.Zhang, W.Chong, D.Xu, J.Sun, and Z.Yun, “Spectral Simulation Method for Calibration Light Source of Transmissometers,” Acta Optica Sinica, vol.42, no.6, 2022. https://doi.org/10.3788/aos202242.0601005

[18] S.Liu, G.Wu, X.Wang, X.Tian, and X.Ren, “Simulation of window parameters and orientation on teaching building lighting,” Architectural Engineering and Design Management, 2025. https://doi.org/10.1080/17452007.2025.2464598

[19] D.A.Loomis, V.Cianciolo, and E.Leggett, “Simulations of the nEDM@SNS light collection system efficiency,” Journal of Instrumentation, vol.17, no.4, 2022. https://doi.org/10.1088/1748-0221/17/04/t04007

[20] M.C.N.Martinez, D.Kreft, M.Grzegorczyk, S.Mahlik, M.Narajczyk, A.Zaleska-Medynska, D.P.Morales, J.A.Hollingsworth, and J.H.Werner, “Numerical Simulation of Light to Heat Conversion by Plasmonic Nanoheaters,” Nano Letters, vol.25, no.1, pp.230-235, 2024. https://doi.org/10.1021/acs.nanolett.4c04872

[21] J.Regimbal, J.R.Blum, C.Kuo, and J.R.Cooperstock, “IMAGE: An Open-Source, Extensible Framework for Deploying Accessible Audio and Haptic Renderings of Web Graphics,” ACM Transactions on Accessible Computing, vol.17, no.2, 2024. https://doi.org/10.1145/3665223

[22] P. Han, H. B. Hua, H. Wang, and J. D. Shang, "A graphic partition method based on nodes learning for energy pipelines network simulation," Energy, vol. 282, 2023. https://doi.org/10.1016/j.energy.2023.128179

[23] Y. W. Jang, J. W. Kim, H. B. Lee, and Y. H. Seo, " Generative AI-driven Graphic Pipeline for Web-based Editing of 4D Volumetric Data," Journal of Web Engineering, vol. 24, no. 1, pp. 135-162, 2025. https://doi.org/10.13052/jwe1540-9589.2416

[24] L.Li and J.Hu, “Fast-Converging and Low-Complexity Linear Massive MIMO Detection With L-BFGS Method,” IEEE Transactions on Vehicular Technology, vol.71, no.10, pp.10656-10665, 2022. https://doi.org/10.1109/tvt.2022.3185967

[25] B. Moon, J. A. Iglesias-Guitian, S. McDonagh, and K. Mitchell, "Noise Reduction on G-Buffers for Monte Carlo Filtering," Computer Graphics Forum, vol. 36, no. 8, pp. 600-612, 2017. https://doi.org/10.1111/cgf.13155

[26] X. C. Chen, Y. Nie, J. W. Chen, Y. L. Liu, and Y. C. Zhang, "Efficiently reconstruct light field probes from light-G-buffers," Computers & Graphics-Uk, vol. 94, pp. 144-151, 2021. https://doi.org/10.1016/j.cag.2020.12.003

[27] S. Y. Wu, D. Vembar, A. Sochenov, S. Panneer, S. Kim, A. Kaplanyan, and L. Q. Yan, "GFFE: G-buffer Free Frame Extrapolation for Low-latency Real-time Rendering, " Acm Transactions on Graphics, vol. 43, no. 6, 2024. https://doi.org/10.1145/3687923

[28] F.Mannel and H.O.Aggrawal, “A Structured L-BFGS Method with Diagonal Scaling and Its Application to Image Registration,” Journal of Mathematical Imaging and Vision, vol.67, no.1, 2025. https://doi.org/10.1007/s10851-024-01215-9

[29] F.Mannel, H.O.Aggrawal, and J.Modersitzki, “A Structured L-BFGS Method and Its Application to Inverse Problems,” Inverse Problems, vol.40, no.4, 2024. https://doi.org/10.1088/1361-6420/ad2c31

[30] D.A.Pratama, R.R.Abo-Alsabeh, M.A.Bakar, A.Salhi, and N.F.Ibrahim, “Solving Partial Differential Equations with Hybridized Physic-Informed Neural Network and Optimization Approach: Incorporating Genetic Algorithms and L-BFGS for Improved Accuracy,” Alexandria Engineering Journal, vol.77, pp.205-226, 2023. https://doi.org/10.1016/j.aej.2023.06.047

[31] J.Sha, A.Kadis, F.Yang, Y.Wang, and T.D.Wilkinson, “Multi-Depth Phase-Only Hologram Optimization Using the L-BFGS Algorithm with Sequential Slicing,” Journal of the Optical Society of America A-Optics Image Science and Vision, vol.40, no.4, pp.B25-B32, 2023. https://doi.org/10.1364/josaa.478430

[32] Y.Su, K.Song, Z.Du, K.Yu, Z.Hu, and H.Jin, “Quantitative Study of Predicting the Effect of the Initial Gap on Mechanical Behavior in Resistance Spot Welding Based on L-BFGS-B,” Materials, vol.17, no.19, 2024. https://doi.org/10.3390/ma17194746

[33] R.Taksana, N.Janjamraj, S.Romphochai, K.Bhumkittipich, and N.Mithiulananthan, “Design of Power Transformer Fault Detection of SCADA

Alarm Using Fault Tree Analysis, Smooth Holtz-Winters, and L-BFGS for Smart Utility Control Centers," IEEE Access, vol.12, pp.116302-116324, 2024. https://doi.org/10.1109/access.2024.3446804

[34] M. Zhao, H. Sheng, R. Chen, R. Cong, T. Wang, Z. Cui, D. Yang, S. Wang, and W. Ke, "A GPU-Enabled Framework for Light Field Efficient Compression and Real-Time Rendering," Ieee Transactions on Computers, vol. 74, no. 4, pp. 1168-1181, 2025. https://doi.org/10.1109/tc.2024.3517743

Energy-Efficient Data Center Cooling Using AGTO-CDQN: A Hybrid Reinforcement Learning and Metaheuristic Optimization Approach

Nan Lin, Rui Feng* Weihe Bu, Pengfei Zhu, Jie Song
State Grid Information&Telecommunication Branch, Beijing 100000, China
E-mail: fengri0315@126.com
*Corresponding author

Keywords: data center cooling, cold source group control, energy efficiency, temperature stability, cooling system, artificial gorilla troops optimizer-driven controlled deep Q-Network (AGTO-CDQN)

Received: June 7, 2025

Cooling systems in data centers signify a major share of overall energy consumption, making their effectual control essential for lowering costs and reducing environmental effect. Existing Deep Reinforcement Learning (DRL) approaches, such as Deep Deterministic Policy Gradient (DDPG), show restrictions in flexibility under dynamic workloads and lack the capability to organize multiple cold source units, which restricts their efficiency. The research aims to develop a hybrid optimization framework that reduces energy consumption while preserving thermal stability in data center operations. The framework gathers a cold source control dataset from Kaggle, which contains 3,498 hourly time-series records covering server workload, temperature parameters, cooling power consumption, chiller and Air Handling Unit (AHU) usage, energy cost, and temperature deviation. The proposed Artificial Gorilla Troops Optimizer-driven Controlled Deep Q-Network (AGTO-CDQN) integrates an attention-enhanced CDQN with the Artificial Gorilla Troops Optimization (AGTO) to strengthen feature prioritization, exploration, and multi-unit coordination. Experimental outcomes illustrates that a target temperature of 24 °C, AGTO-CDQN achieved 77 kW IT power consumption (24% saving vs. 23% with DDPG), 45.1 kW cooling power (15% saving vs. 10% with DDPG), and 125 kW total power (23% saving vs. 20% with DDPG), while maintaining an average zone air temperature of 23.0 °C compared to 23.5 °C with DDPG. The results confirm that AGTO-CDQN dependably distributes efficacy developments above 15% across all metrics, representing higher flexibility and coordination, and highlighting its potential for practical application in energy-efficient data center cooling management.

Povzetek: Raziskava predstavi hibridni pristop z globokim okrepljenim učenjem in metaoptimizacijo za usklajeno vodenje več hladilnih enot v podatkovnih centrih, ki ob ohranjanju temperaturne stabilnosti dodatno zmanjša porabo energije v primerjavi z obstoječimi DRL metodami.

1 Introduction

Cloud computing's (CC) explosive expansion has enabled a variety of uses, such as web search, scientific computing, and bioinformatics. Data centers (DCs) allow effective large-scale resource management that is accessible over the internet by centralizing computing resources and using virtualization to create multiple virtual machines [1]. DCs are a major source of energy consumption and carbon emissions worldwide. Lowering power consumption and reducing environmental impact requires optimization of cooling and information technology (IT) systems [2]. Large DCs' cooling systems use between 30 and 40 percent of their energy. That is more cost-effective to reduce cooling energy than server-side energy use. An important, challenging industrial problem is effectively managing air conditioners and chillers to preserve thermal safety while conserving energy [3]. DCs can use less energy by switching from mechanical refrigeration to natural cooling methods like direct or indirect evaporative cooling. The viability of the method, which has been proven to be effective over 5500 cooling hours a year, is dependent on humidification expenses and is less appropriate for areas with low dew point temperatures [4]. Complex cyber-physical systems with high power densities, such as cloud DCs, produce enormous amounts of heat, making effective energy management difficult. Despite possible efficiency gains, manual tuning is impractical because of the billions of configuration options, which complicates resource management and affects cost savings and carbon footprint reduction [5].

Existing Deep Reinforcement Learning (DRL) methods, such as Deep Deterministic Policy Gradient (DDPG), struggle to adapt effectively to highly dynamic server workloads, limiting their responsiveness under fluctuating operational conditions.

It is also ineffective at coordinating between more than two cooling units, lowering the overall potential of energy savings. Also, the prioritization of features is inadequate and prevents the model from concentrating on factors that are the most important in controlling the cooling, which limits performance further. The proposed Artificial Gorilla Troops Optimizer-driven Controlled Deep Q-Network (AGTO-CDQN) overcomes these limitations by incorporating attention mechanisms and the Artificial Gorilla Troops Optimization (AGTO) allows prioritizing features, better exploring, and coordinating the control of numerous cooling units. This combination provides greater flexibility, increased thermal management, and major energy savings to data center operations.

The aim of this research is to create an energy-efficient cooling control approach for DCs that uses a proposed AGTO-CDQN model to optimize cold source unit operations. The intention is to reduce energy costs while preserving temperature stability by using real-time and historical sensor data to make dynamic decisions.

The research paper is organized as follows: Section 1 deals with the introduction of research. Section 2 describes the related work. Section 3 displays a complete methodology. Section 4 concentrates on the experimental results and discussions, while Section 5 concludes.

Research question

1. Can the proposed AGTO-CDQN framework achieve higher energy efficiency than conventional DRL approaches such as DDPG while ensuring stable thermal conditions in data centers?
2. Does the integration of the AGTO with an attention-enhanced CDQN improve exploration dynamics and adaptability under variable workloads and environmental conditions?
3. Can AGTO-CDQN effectively coordinate multiple cold source units simultaneously to optimize system-wide cooling performance and energy savings?

2 Related work

Zhu et al. optimized DCs' chillers and cold-water storage systems to maximize cooling energy efficiency while lowering expenses and electricity usage. Utilizing mixed-integer linear programming (MILP), a sophisticated model predictive control (MPC) was created to control chillers and cold-water storage; that was verified through yearly simulations and field testing. The MPC approach decreased cooling energy by 5.8%, decreased power usage effectiveness (PUE) by 0.013, increased coefficient of performance (COP) by 1.96, and decreased annual power expenses by 21%; however, the result was sensitive to partial load variations and model mismatches [6]. Lee et al. created a thermal management plan that makes use of overhead cooling and cold aisle confinement; verify that using computational fluid dynamics (CFD) and airflow measurements; and assess cooling effectiveness for energy-efficient container DCs in tropical and subtropical areas. Achieved a low average PUE of 1.38, surpassing industry standards; showed efficient thermal and airflow control; however, model reliance on precise CFD inputs and site-specific environmental variables were limitations [7]. Table 1 shows the summary of the literature review.

Table 1: Comparative overview of optimization approaches for data center management

Reference	Objective	Dataset	Method	Results	Limitations
Dakić et al. [8]	Improve performance and energy efficiency of HPC workload placement	High-Performance Computing (HPC) workload traces	Machine Learning (ML)-based dynamic scheduling, automatic Kubernetes setup	Increased workload scheduling speed and cluster placement accuracy;	Hardware integration complexity; need for additional ML model tuning
Liu et al. [9]	Solve cold-start recommendation in tourist cities	Tourist city recommendation datasets	Meta-learning, attention-based feature mining, dynamically weighted collaborative filtering	Outperforms Content-Based Recommendation (CBR), Collaborative Filtering (CF),	High complexity; requires careful tuning; computationally intensive
Mehor et al. [10]	Minimize virtualized cloud data centre energy consumption and reduce Service Level Agreement (SLA) breaches	Simulated cloud DC workloads with SLA metrics	Adaptive Genetic Algorithm (GA) and threshold-based preprocessing;	Reduced execution time, energy consumption, SLA breach, and cooling energy requirement	Simulation-only validation; practical scalability and heterogeneity issues with real cooling system integration

Al-Najari et al. [11]	Optimize pH regulation in cooling towers with improved transient response and accuracy	Cooling tower experimental/simulated data	Adaptive Neuro-Fuzzy Inference System (ANFIS) with Particle Swarm Optimization (PSO)	Achieved RMSE = 0.0081; rise time = 0.5863 s; settling time = 1.4867 s; overshoot = 2.7958%; peak = 7.6548	Based on analytical/simulation studies; requires validation in real-world cooling towers; dependent on data quality
Li et al. [12]	Evaluate adoption of energy-saving technologies in data centers	Tropical-region data center environmental and workload data	Hybrid DC model with Deep Reinforcement Learning (DRL)	Effective cooling setpoint optimization; green technology adoption beneficial	Inconsistent implementation; lack of long-term performance statistics
Mahbod et al. [13]	Reduce energy expenses with dynamic cooling	Data center workload traces with cooling energy measurements	Model-free RL with adaptive cooling setpoints	Achieved 3–5.5% energy savings, mainly via reduced server fan usage	Limited generalization; dependency on specific hybrid model
Lin et al. [14]	Predict temperature in steady and transient data center settings	CFD (Computational Fluid Dynamics) simulation data for DC thermal profiles	Compared six ML-based thermal models: Process Regression (GPR), Extreme Gradient Boosting (XGBoost),	XGBoost and LightGBM achieved robust predictions with RMSE < 1 °C	Not designed for multi-unit coordination; evaluation limited to CFD simulations
Wang et al. [15]	Enhance efficiency of data-center cooling and thermal safety in the process of exploring reinforcement learning.	Operating history trace and data center trace of chilled water and direct expansion-cooled systems with two climate conditions.	Deep reinforcement learning (DRL) architecture that is safety conscious, which combines offline imitation learning	Enhanced total power savings up to 18-26.6% relative to traditional control; cut safety violations by 94.5-99% relative to reward shaping; enhanced 14% more than Proportional-Integral-Derivative (PID) control under non-uniform temperatures.	Leverages correct thermal transition modelling; additional computational cost is associated with rectification;

2.1 Research gap

Previous researches, such as Li et al. [12] did not provide uniform execution and long-term statistics of the performance of the hybrid DRL-based cooling optimization. Mahbod et al. [13] were uncertain in generalization and relied on a particular hybrid model. Lin et al. [14] concentrated on single-unit temperature prediction without coordinate action and the evaluation using CFD simulations only. Wang et al. [15] framework is very reliant on the quality and accessibility of the safe historical operation data which might not be available in all data centers. Comprehensively, this research is incomplete to cover flexible, multi-unit cold source control under dynamic workloads. This research fails to provide dynamic workload multi-unit DRL framework flexibility. Therefore, this research addresses these gaps by introducing the AGTO-CDQN approach that provides coordinated control of multiple cold source units and able to flexibly respond to changing workloads.

3 Methodology

This section gives a detailed description of data collection consisting of time-series temperature readings from multiple zones of the DC site, where cooling source unit power consumption and server workload data with CPU utilization are also recorded. There are two cooling systems with separate cooling units, a chiller system (C2) and a direct expansion (DX) system (C1), both of which use a cooling tower. Similar to most energy optimization problem formulations, the focus is essentially to minimize energy usage while ensuring thermal stability is maintained within DC constraints. The AGTO-CDQN model proposed in this research addresses cold source and thermal control using dynamic optimization techniques, with a specific emphasis on DRL and AGTO to achieve energy savings and stabilized temperature. Figure 1 shows the overall structure of the suggested approach.




Figure 1: Architecture of suggested method

3.1 Data collection

The data center cold source control dataset obtained from Kaggle (https://www.kaggle.com/datasets/programmer3/data-center-cold-source-control-dataset), shows the operational environment of a modern data center's cooling system. It focuses on cold source group control, which includes chillers and air handling units (AHUs), with the goal of maximizing energy usage while preserving temperature stability. The collection includes 3,498 time-series data points, each representing one hour of operation, with attributes such as server workload (%), inlet and outlet temperatures (°C), ambient temperature (°C), cooling unit power consumption (kW), chiller and AHU usage percentages, energy cost ($), and temperature deviation (°C).

3.2 Cooling system

Action Space: C1 and C2 in the target simulation model include separate cooling systems: a chilled water (chiller) for C2 and a DX for C1. The cooling tower provides cool water to both cooling systems, although they use it differently. The airflow in the DX system over the coils is cooled by the cool water that flows through them. The chiller system's cool water is initially utilized to cool a second stream of water, which cools the airflow that is provided to the DC. Two different kinds of evaporative coolers (EC): directive EC (DEC) and indirect EC (IEC) cool the intake ambient airflow in the DX cooling system before it overtakes the DX cooling coils and is sent to the DC.

3.3 Problem formulation

Strict temperature (T) stability restrictions are applied to the control problem of the cooling system (C1 and C2), which is presented as an energy (E) cost minimization assignment. The objective is to lower the cooling units' overall E usage while maintaining the DC environment within the specified thermal range required for optimal server performance and hardware dependability. The dynamic and complex nature of the DC workloads and environmental conditions means that traditional static or rule-based control systems frequently fall short in terms of efficiency and adaptability. This research suggests a DRL based AGTO-CDQN approach to overcome this difficulty. Using historical and real-time sensor data to learn optimal actions, this method allows for intelligent, real-time control of cold source groups, reducing energy costs without sacrificing temperature regulation.

3.4 Controlled using Artificial Gorilla Troops Optimizer-driven Controlled Deep Q-Network (AGTO-CDQN)

The control strategy is based on an AGTO-CDQN, which adds the AGTO to the CDQN, which integrates with DQN and a revised action space output layer (discrete to continuous). The hybrid approach also included the attention mechanism in DQN, which helps the DQN focus on the various relevant features of the states. The AGTO can optimize coordination between all the cold source units, while the attention-enhanced CDQN will maximize control of power-saving cooling in a data center application.

3.5 Controlled Deep Q-Network (CDQN)

The provided DC cooling control framework models cold source group regulation as a Markov Decision Process (MDP), defined by ⟨r, b, Q, q, γ⟩. r indicates system parameters (e.g., temperature, stress), b is the control action set, Q reflects transition probability, q is the reward (energy savings and temperature stability), and γ is the discount factor. The action space b often includes the list of activities that the agent can perform, such as altering cooling units, turning on/off certain chillers, or changing fan speeds. Improvement: By allowing the agent to select between more discrete or continuous actions, the granularity of actions could be increased. Instead of simply turning on or off a cooling unit, could make room for temperature and fan speed modifications. Using continuous action spaces, which allow the agent to make finer adjustments to the cooling settings, potentially leading to a more effective control technique. A CDQN represents the optimal action-value operating $P(r, b)$ by applying Deep Learning (DL) to high-dimensional state spaces according to the Bellman Eq. (1).

$$P(r,b) = F[q + \gamma\, Q(r,r') \max_{b'} P(r',s')] \quad (1)$$

The agent chooses behaviors that maximize $P(r,b)$ to conserve energy while maintaining thermal thresholds efficiently. Where r' is the working state, b' is the next action, and the expected outcome is calculated using the transition probabilities, q is reward and s is next state, F represents function approximator, Q produces Probability of state transition, r defines system parameters. Traditional Q-learning has scalability concerns in significant state-action spaces, which are characteristic of DC contexts. The solution integrates deep learning into the Q-learning framework, resulting in a parameterized approximation$P(r,b \mid \theta)$, where θ represents the neural network parameters. The architecture of CDQN is a multi-layer neural network with the input layer encoding the current condition, including real-time heat, workload, and energy statistics. Hidden Layers extract nonlinear features from complex state-action mappings. The output layer provides P-values for all conceivable control actions, with a dimensionality equal to the action space. The agent selects the action that yields the highest P-value in Eq. (2).

$$b_t = arg \max_b P(r_t, b|\theta) \quad (2)$$

Here r_t represents current state, b_t stands action set, and θ are network weights. To train the network, implement the following loss function O in Eq. (3).

$$O_{CDQN}(\theta_j) = F[(x_j^{DDQN} - P(r,b|\theta_j))^2] \quad (3)$$

Where O_{CDQN} loss minimizes the squared difference between target x_j^{DDQN} and predicted value, P_r giving loss, guiding parameter updates for accurate Q-value approximation, θ_j is set of trainable parameters.

Attention layer: The CDQN framework uses an attention mechanism to dynamically prioritize essential features like temperature deviations, workload increases, and cooling unit performance. This is achieved by providing attention weights, which represent the significance of each input in control decisions. These weights are learned during training and applied to input data before further processing. A common technique computes attention as follows in Eq. (4).

$$Attention(P,J,U) = softmax\left(\frac{PJ^t}{\sqrt{c_j}}\right)U \quad (4)$$

Where P is the query vector, J is the set of key vectors, U is the set of value

vectors, and c_J: the key vector dimension. PJ^t presents the transformed interaction between the input feature matrix P and the learned weight matrix J, producing attention scores before normalization. The technique improves the CDQN's ability to focus on context-relevant inputs, resulting in higher control precision and energy efficiency in DC cooling. AGTO-CDQN optimizes cold source group control by merging deep Q-learning, attention, and AGTO, resulting in adaptive, energy-efficient decisions based on a dynamic DC environment.

Artificial Gorilla Troops Optimizer (AGTO)

AGTO is used to optimize exploration and feature priorities, allowing successful coordination of a variety of cooling units. It achieves the optimal use of energy and helps to sustain the thermal stability, enhancing the efficiency and reliability of data center cooling in general. The proposed intelligent control method combines DLR and AGTO to reduce energy usage in DC cooling systems. AGTO, inspired by gorillas' social behavior, encourages exploration and exploitation. The actor-critic architecture dynamically regulates cold source units, such as chillers and air handling systems to maintain consistent thermal stability.

Exploration: In the AGTO, each gorilla represents a possible cooling unit control method. The best-performing solution serves as the silverback. During exploration, potential solutions (gorillas) adapt by migrating to new or recognized regions or merging with others, increasing search diversity. The position of a gorilla is changed $HY(t+1)$ using the following rule in Eq. (5).

$$HY(t+1) = \begin{cases} (VA - OA) \times s_1 + OA. & if rand < P \\ (s_2 - D) \times Y_s(t) + O \times G, & if rand \geq 0.5 \\ Y(t) - O \times \left(O \times \left(Y(t) - HY_s(t)\right) + s_3 \times \left(Y(t) - HY_s(t)\right)\right), & if rand < 0.5 \end{cases} \quad (5)$$

Where: $HY(t+1)$: Updated position vector.$Y(t)$: Current location.VA, OA: Upper and lower boundaries.$Y_s(t), HY_s(t)$: Locations of randomly selected gorillas,$s_1, s_2 s_3$ rand [0, 1]: Random values, D, O, and G are calculated as Eqs. (6-7).

$$D = L \times \left(1 - \frac{It}{maxIt}\right), G = \cos(2s_4) + 1 \quad (6)$$

$$O = D \times o, G = X \times Y(t), X \epsilon [-D, D], o \epsilon [-1,1] \quad (7)$$

D: control Parameter, L: fluctuating factor calculated from a cosine function and influenced by the random variable $s_4 \epsilon [0,1]$. It: Current iteration of the optimization process. $MaxIt$: Total current number of iterations. O: Direction and magnitude adjustment term from D, G: Applying a perturbation factor to position $Y(t)$ could help diversify search pathways.o: A randomly determined scalar is used to compute O. while X scales the movement of the current solution$Y(t)$. This phase ensures a wide range of control options for optimal energy-saving cooling arrangements.

Exploitation: The AGTO-CDQN for DC Cooling Control in the AGTO exploitation phase, two strategies are used to fine-tune control actions for cold source units: following the silverback (best current solution) and competing for leadership (intensified search). The coefficient D affects the actions of gorilla groups and can be calculated as follows in Eq. (10). If $C \geq Z$, gorilla agents (control candidates) follow the silverback (current optimal control policy) in Eq. (8).

$$HY(t+1) = O.N.(Y(t) - Y_{silverback}) + Y(t) \quad (8)$$

$Y_{silverback}$: The best-performing control policy. $O = D.o$, $\text{with} o \epsilon [-1,1]. N = \frac{1}{n}\sum_{j=1}^{n} HY_j(t)$: The average influence of all control agents.$C < Z$, competition arises to question the best strategy and investigate alternatives in Eq. (9).

$$HY(j) = Y_{silverback} - (Y_{silverback}.P - Y_t.P).B, P = 2s_5 - 1, B = \varepsilon.F \quad (9)$$

In Equation (9), $HY(j)$ is the updated position of a candidate solution relative to the best solution $Y_{silverback}$, adjusted by the difference in positions and scaled by factor B. Here, $P = 2s_5 - 1$ introduces randomness s_5 , and $B = \varepsilon.F$ represents a scaling term with ε as a random coefficient and F as the control factor guiding exploration.

The proposed AGTO-CDQN hybrid model integrates a CDQN with AGTO to enhance energy-efficient cooling control in DC. CDQN uses DQN and attention mechanisms to make precise control decisions, while AGTO optimizes exploration and hyperparameters. This hybrid approach dynamically manages cooling units, significantly reducing energy consumption and ensuring temperature stability under varying workloads for improved DC performance. Algorithm 1 represents the working procedure of proposed AGTO-CDQN model. Table 2 defines the hyperparameters of the AGTO-CDQN method.

Table 2: Configuration of hyperparameters

Hyperparameters	**Typical values**
Hidden units per dense layer	128, 256, 512
Epochs	100, 200
Dropout rate	0.3, 0.5
Optimizer	Adam, AGTO
Batch size	32, 64, 128
Learning rate	0.001, 0.0005, 0.0001
Discount factor (γ)	0.95, 0.99
Exploration rate (ε)	0.1 → 0.01 (decay)
Number of convolutional filters	32, 64
Activation function	ReLU, Leaky ReLU
Number of convolutional layers	2, 3
Attention heads	4, 8
Population size (AGTO)	20, 30, 50
Maximum iterations (AGTO)	50, 100

Algorithm 1: AGTO-CDQN

Step 1: Initialize Environment
Load DC simulator
Normalize inputs to [0,1].
Step 2: Define Action Space
Discrete: {chiller on/off, fan states}.
Continuous: {fan speed, temperature setpoints}.
Step 3: Initialize CDQN and AGTO
Initialize Q-network $P(r, b|\theta_j))$, target network, replay buffer B.
Define hyperparameters $\alpha, \gamma, \varepsilon$.
Initialize gorilla population, silverback = best candidate.
Step 4: Training Loop
For each episode:
Observe state r
If rand $< \varepsilon$: choose random action
Else: choose $b_t = arg\max_b P(r_t, b|\theta)$
Execute action, get reward
CDQN Update
Compute target: $P(r,b) = F[q + \gamma\, Q(r,r') \max_{b'} P(r',s')]$
Update loss: $O_{CDQN}(\theta_j) = F[(x_j^{DDQN} - P(r,b|\theta_j))^2]$
Apply attention weighting: $Attention(P,J,U) = softmax\left(\frac{PJ^t}{\sqrt{c_j}}\right)U$
AGTO Update
If $rand < 0.5$: update $HY(t+1)$
$D = L \times \left(1 - \frac{It}{maxIt}\right), G = \cos(2s_4) + 1$

Else:
If $HY(t+1) = O.N.(Y(t) - Y_{silverback}) + Y(t)$
Update silverback = best-performing solution.
Step 5: Termination
Stop when loss converges or $MaxIt$ reached.
Return optimized control policy for real-time deployment.

4 Result and discussion

Compare the results with existing methods vs proposed methods to optimize important parameters IT Power consumption**,** cooling power consumption, total power consumption, average Zone air Temperature and savings, while maintaining acceptable temperature restrictions and efficient operation throughout the monitoring period.

4.1 Experimental setup

The AGTO-CDQN framework was developed effectively that optimizing cold source control for energy-efficient, thermally stable data centers and the framework is implemented in Python 3.11. All experiments were performed on a work station with the NVIDIA RTX 3090 GPU, 64 GB of RAM, and an Intel Core i9-12900K processor. To reproducibly and reliably obtain performance evaluation, the model training and evaluation had been conducted under various conditions.

4.2 Comparative performance evaluation

The performance of the AGTO-CDQN model was compared with the deep deterministic policy gradient (DDPG) [15] algorithm based on four performance indicators. Utilized together, these performance indicators assess the AGTO-CDQN model's ability to minimize energy consumption while working to maintain thermal stability within the data center. The results of this comparison indicate that the proposed AGTO-CDQN model improves energy efficiency and successfully controls data center temperatures. In Figure (1-4), the proposed AGTO-CDQN method is represented as blue, and the DDPG represents green. Triangles with lines represent the saving percentages.

Table 3 shows the amount of electricity used by IT at various target temperatures (TC). At TC = 24°C, the AGTO-CDQN uses 77 kW and saves 24% of the energy, whereas DDPG uses 79 kW and saves 23%. All temperature settings reveal that the suggested approach is consistently marginally more efficient, demonstrating its capacity to lower server-side energy use without sacrificing performance. These comparisons were graphically illustrated in Figure 2.




Figure 2: IT power consumption and savings comparison of models

Table 3: IT power consumption and savings

TC (°C)	DDPG[15] (kW)	AGTO-CDQN [Proposed] (kW)	DDPG[15] Saving (%)	AGTO-CDQN [Proposed] Saving (%)
20	76	74	25	28.5
21	74	70	26.5	25.5
22	75	73	27	25
23	77	75	26	24.5
24	79	77	23	24

AGTO-CDQN performs better than DDPG in terms of cooling power consumption (Table 2). In contrast to DDPG, which uses 47.1 kW and saves 10%, the suggested model uses 45.1 kW of cooling electricity at TC = 24°C, saving 15%. This illustrates how well the model works to dynamically control the cold source units for the best possible energy use. Figure 3 and table 4 give the comparison of the models for these metrics.




Figure 3: Cooling Power consumption and savings comparison of models

Table 4: Cooling Power consumption and savings

TC (°C)	DDPG[15] (kW)	AGTO-CDQN [Proposed] (kW)	DDPG[15] Saving (%)	AGTO-CDQN [Proposed] Saving (%)
20	48	46	24.5	30
21	47	45	20.1	25
22	46.5	44.5	10.8	15.8
23	46.8	44.8	10.3	15.5
24	47.1	45.1	10	15

When combining cooling and IT energy (Total power consumption), the AGTO-CDQN uses 125 kW of power at 24°C, saving 23%, more than DDPG, which uses 130 kW and saves 20%. The overall reduction is consistent, demonstrating the AGTO-CDQN's comprehensive strategy for system-wide energy optimization (Table 4). Figure 4 and table 5 provide the comparison of the model with these metrics.




Figure 4: Total power consumption and savings comparison of models

Table 5: Total power consumption and savings

TC (°C)	DDPG [15] (kW)	AGTO-CDQN [Proposed] (kW)	DDPG [15] Saving (%)	AGTO-CDQN [Proposed] Saving (%)
20	123	120	23	25
21	120	115	25	30
22	121	118	23	25
23	128	120	21.1	24
24	130	125	20	23

AGTO-CDQN maintains an average zone air temperature of 23.0°C, which is closer to the objective than DDPG's 23.5°C, demonstrating the thermal regulation capability at TC = 24°C (Table 4). This suggests better temperature stability and more accurate environmental condition control in the data center. The comparison was graphically illustrated in Figure 5 and Table 6.




Figure 5: Average zone air temperature between models

Table 6: Average zone air temperature

TC (°C)	DDPG[15] (°C)	AGTO-CDQN [Proposed] (°C)
20	19.8	19.5
21	21.2	20.0
22	21.8	21.5
23	23.2	22.8
24	23.5	23.0

4.3 Dataset comparison

The AGTO-CDQN framework was tested on the Data Center Cold Source Control dataset and the Chiller Energy Data dataset [16], which tests the generalization between various cooling environments. Both datasets have been divided into 20% testing and 80% training sets to support robustness. The utilized metrics are IT power, the cooling power, the total power, and the average zone temperature. Table 7 provides the comparative dataset performance.

Table 7: Performance comparison of AGTO-CDQN across two datasets

Metrics	**Cold Source Control Dataset [Proposed]**	**Chiller Energy Data Dataset [16]**
IT Power Consumption (kW)	70	90
Cooling Power (kW)	50	75
Total Power (kW)	110	160
Average Zone Temperature (°C)	23.0	23.5

Table 7 reveals that Data Center Cold Source Control dataset has an IT power consumption of 70 kW and cooling power of 50 kW on the Cold Source Control dataset, which is against 90 kW and 75 kW respectively, on the Chiller Energy Data dataset [16]. The Cold Source Control dataset and Chiller Energy Data dataset [16] have a total power usage of 110 and 160 kW. The average zone temperature provides 23.0 °C and 23.5 °C. Therefore, the proposed Data Center Cold Source Control dataset performance is significantly lowered in all metrics compared to the Chiller Energy Data dataset [16].

4.4 Training stability

It is the convergence of this model among several runs without significant variation in loss or reward. It guarantees healthy energy optimization and consistent cooling in the data centers. The model converges stable with reducing residual error and increases stability with an increase in iteration, as seen in Figure 6.




Figure 6: Convergence behavior of AGTO-CDQN across training episodes.

The convergence plot shows that the AGTO-CDQN model continuously reduces loss and gradually increases the average reward and remaining stable across various random seeds. This indicates stable learning and strong performance throughout the training episodes.

Training the AGTO-CDQN model is computationally intensive and require more time to converge when performed offline. However, once trained, the inference pipeline is light-weight, as only forward passes through the neural network are required to choose actions. This makes the model suitable for real-time in the data center environment.

4.5 Statistical analysis

The research additionally provides the statistical analysis that concentrates on the comparison between the effectiveness of the AGTO-CDQN framework and the baseline DDPG technique. A paired-sample t-test was implemented to test the same workload and temperature condition.

4.6 Paired sample t-test

The paired sample t-test compares the average of two related groups with the same conditions to test whether there is significant variation. It compares AGTO-CDQN with DDPG to directly support the goal of optimizing data center cooling directly. The mathematical representation of paired sample t-test is represented in equation (1).

$$t = \frac{\bar{D}}{S_D/\sqrt{n}} \quad (1)$$

Where $\bar{D}$ = mean of the differences between paired values, SD= standard deviation of the differences, n = number of paired samples. The results of the comparative statistics of AGTO-CDQN and DDPG are presented in Table 8.

Table 8: Comparative performance with statistical significance testing

Metric	Mean	Std. Dev.	95% CI	Mean	Std. Dev.	95% CI	p-value
IT Power Consumption (kW)	80.2	6.1	[78.0, 82.4]	104.7	7.5	[101.8, 107.6]	<0.001
Cooling Power (kW)	47.5	4.2	[46.0, 49.0]	52.8	5.0	[50.8, 54.8]	0.002
Total Power (kW)	128.5	6.9	[126.0, 131.0]	159.6	8.7	[156.3, 162.9]	<0.001
Avg. Zone Temperature (°C)	22.9	0.6	[22.7, 23.1]	23.6	0.9	[23.3, 23.9]	0.003

As seen in the table 8, AGTO-CDQN can significantly decrease both IT power, cooling power and the total power consumption relative to the baseline and all p-values are less than 0.05. The confidence intervals show that there are uninterrupted enhancements of energy metrics. Furthermore, AGTO-CDQN has a reduced and more constant average zone temperature, which guarantees thermal security as well as energy efficiency.

4.7 Ablation study

The ablation study is performed to show the performance of the data, CDQN and AGTO. The accuracy of the methods in the ablation study is presented in Table 9. The combination of AGTO-CDQN has the best accuracy, which proves the complementary power of both elements.

Table 9: Ablation study showing accuracy improvements across methods

Method	Accuracy (%)
Data Center Cold Source Control dataset	85.0
Data Center Cold Source Control dataset + CDQN	87.5
Data Center Cold Source Control dataset + CDQN + attention mechanism	88.2
Data Center Cold Source Control dataset + CDQN + attention mechanism + AGTO [Proposed]	**91.5**

The outcomes indicate that the accuracy is increased from 85.0% to 91.5%, and the highest accuracy is 91.5% attained for a combined whole approach. This shows that the combined proposed AGTO-CDQN provides the best performance.

5 Discussion

The research developed a hybrid AGTO-CDQN framework that reduces the energy usage in cooling data centers and maintains constant thermal conditions. DDPG [15] has some drawbacks, such as limited exploration power resulting in early convergence, non-hierarchical weights on input features, prerecorded priority on key variables such as workload peaks or temperature variations, limited scalability to highly dynamic workloads, and limited co-ordination of multiple cold source units. The proposed AGTO-CDQN approach solves these gaps with the improvement of exploration via AGTO, an attention mechanism dedicated to prioritizing important features, and coordination of several cold sources to control the system-wide performance. The AGTO-CDQN was always able to perform better than DDPG because it was more adaptive, and more accurate temperature control, along with consumes less energy. In practical considerations, the framework gives data center operators a rational method to reduce the cost of operation and environmental impact; it offers deployment in a variety of workloads and environmental circumstances and offers a scaling entry to sustainable and energy efficient data center management.

6 Conclusion

The proposed AGTO-CDQN method intends to reduce energy consumption in DC cooling systems by dynamically optimizing control actions while maintaining temperature restrictions through DRL. The results show that AGTO-CDQN considerably increases the power saving above 15% for IT power consumption, cooling power consumption, total power consumption, and average zone air temperature. The AGTO-CDQN approach includes disadvantages, such as high processing needs, susceptibility to noisy or missing data, difficulties with real-time deployment, and potential performance degradation in highly dynamic or previously unplanned DC operating circumstances. Future directions for AGTO-CDQN include generalizing the approach to a multi-objective optimization framework, aimed not only at maximizing energy efficiency, but also at minimizing cooling latency, component wear, and carbon footprint. Trade-offs among those can be explored systematically by use of the Pareto front analysis. This will increase the strength and practical applicability of the model to real world data centers. It has potential applications in future work to optimize training efficiency and to lower the cost of computation to increase scalability.

References

[1] Feng H, Deng Y, Li J (2021). A global-energy-aware virtual machine placement strategy for cloud data centers. *Journal of Systems Architecture*, 116, 102048. https://doi.org/10.1016/j.sysarc.2021.102048

[2] Chi C, Ji K, Song P, Marahatta A, Zhang S, Zhang F, Qiu D, Liu Z (2021). Cooperatively improving data center energy efficiency based on multi-agent deep reinforcement learning. *Energies*, 14(8), 2071. https://doi.org/10.3390/en14082071

[3] Wan J, Duan Y, Gui X, Liu C, Li L, Ma Z (2023). SafeCool: Safe and energy-efficient cooling management in data centers with model-based reinforcement learning. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 7(6), 1621–1635. https://doi.org/10.1109/TETCI.2023.3234545

[4] Chen X, Tu R, Yang X (2023). Parameter prediction optimization of data center's heat dissipation system using machine learning algorithms. *Applied Thermal Engineering*, 232, 121047. https://doi.org/10.1016/j.applthermaleng.2023.121047

[5] Agostinelli S, Cumo F, Guidi G, Tomazzoli C (2021). Cyber-physical systems improving building energy management: Digital twin and artificial intelligence. *Energies*, 14(8), 2338. https://doi.org/10.3390/en14082338

[6] Zhu Y, Zhang Q, Zeng L, Wang J, Zou S, Zheng H (2023). An advanced control strategy for optimizing the operation state of chillers with cold storage technology in the data center. *Energy and Buildings*, 301, 113684. https://doi.org/10.1016/j.enbuild.2023.113684

[7] Lee YT, Wen CY, Shih YC, Li Z, Yang AS (2022). Numerical and experimental investigations on thermal management for the data center with cold aisle containment configuration. *Applied Energy*, 307, 118213. https://doi.org/10.1016/j.apenergy.2021.118213

[8] Dakić V, Kovač M, Slovinac J (2024). Evolving high-performance computing data centers with Kubernetes, performance analysis, and dynamic workload placement based on machine learning scheduling. *Electronics*, 13(13), 2651. https://doi.org/10.3390/electronics13132651

[9] Liu T, Deng F, Zhang H (2025). Meta-learning enhanced recommendation for cold-start tourist cities: A multi-component adaptive framework. *Informatica*, 49(32). https://doi.org/10.31449/inf.v49i32.9336

[10] Mehor Y, Rebbah M, Smail O (2024). Energy-aware scheduling of tasks in cloud computing. *Informatica*, 48(16). https://doi.org/10.31449/inf.v48i16.5741

[11] Al-Najari BMA, Hen CK, Paw JKS, Marhoon AF (2025). ANFIS controller design using PSO-tuned PID data for pH regulation in industrial cooling towers. *Informatica*, 49(32). https://doi.org/10.31449/inf.v49i32.8586

[12] Li G, Sun Z, Wang Q, Wang S, Huang K, Zhao N, Di Y, Zhao X, Zhu Z (2023). China's green data center development: Policies and carbon reduction technology path. *Environmental Research*, 231, 116248. https://doi.org/10.1016/j.envres.2023.116248

[13] Mahbod MHB, Chng CB, Lee PS, Chui CK (2022). Energy saving evaluation of an energy-efficient data center using model-free reinforcement learning approach. *Applied Energy*, 322, 119392. https://doi.org/10.1016/j.apenergy.2022.119392

[14] Lin J, Lin W, Lin W, Wang J, Jiang H (2022). Thermal prediction for air-cooled data center using data-driven model. *Applied Thermal Engineering*, 217, 119207. https://doi.org/10.1016/j.applthermaleng.2022.119207

[15] Wang R, Cao Z, Zhou X, Wen Y, Tan R (2024). Green data center cooling control via physics-guided safe reinforcement learning. *ACM Transactions on Cyber-Physical Systems*, 8(2), 1–26. https://doi.org/10.1145/3582577

[16] Comparison dataset: https://www.kaggle.com/datasets/chillerenergy/chiller-energy-data/data

MDQN: An Enhanced Deep Q-Network Approach for Wireless Resource Management in Industrial IoT

Long Yu, Na Yin*
Applied Technology College of Dalian Ocean University, Dalian 116300, China
E-mail: yulong1972@126.com, 15941162715@163.com
*Corresponding author

Keywords: Deep Q-network, wireless network, resource management, industrial internet of things, channel rate

Received: February 21, 2025

With the rapid growth of access devices, traditional resource management algorithms fall short in meeting practical needs. To address issues like poor coordination of wireless network resources and quality of service in conventional wireless resource management, this study starts from the actual Industrial Internet of Things (IIoT) network structure. Firstly, a more practical IIoT wireless network framework is proposed. Then, combining the Markov decision process, the depth Q - network algorithm is improved, and a novel wireless network resource management algorithm (MDQN) is put forward. The results show that after training, the performance of the proposed algorithm significantly improves, surpassing the Slotted Aloha Algorithm (SAA) and Randomized Algorithm (RA). It achieves high channel utilization and system sum - rate, and converges faster than the traditional depth Q - network algorithm. When the arrival rate exceeds 1.0, the channel utilization and average sum - rate of the proposed algorithm reach over 94% and 25 bits/s/Hz respectively, which are more than twice those of the SAA and RA. As the system bandwidth increases, the latency of all algorithms decreases, and the proposed algorithm has the lowest system waiting latency and computational cost among them. These results demonstrate the algorithm's ability to achieve dynamic wireless resource management in IIoT and promote efficient utilization of wireless network resources.

Povzetek: Predlagani algoritem MDQN omogoča učinkovitejše in hitrejše dinamično upravljanje brezžičnih virov v IIoT kot obstoječe metode.

1 Introduction

With the swift advancement of commercial 5G networks and wireless communication technology, the number of devices accessing the network has increased sharply. The Internet of Things (IoT) is driving the development of traditional industries and accelerating the consumption of network resources. As a core resource in wireless networks, the static allocation mode of spectrum resources is inadequate to fulfill the escalating communication requirements [1-3]. Meanwhile, the development of the information and communication industry has led to a surge in demand for energy and computing resources, and researchers around the world have also carried out research on this. In wireless communication networks such as the IoT, Industrial Internet of Things (IIoT), and wireless sensor networks, communication devices are widely distributed and numerous, and usually rely on battery power. The battery capacity is limited and needs to be replaced regularly, resulting in high costs [4-6].Therefore, many scholars are dedicated to studying the related fields of wireless network resource management (RSMG), in order to optimize resource allocation (RSAL), improve resource utilization efficiency, and thus address the challenges of resource consumption. The research efforts focused on wireless resource management, such as those optimizing resource allocation and improving resource utilization efficiency, are of paramount significance in driving the sustainable development of wireless communication technology and ushering in the era of comprehensive intelligent interconnection [7].

Several studies have advanced wireless network resource management: Naderalizadeh et al. utilized multi-agent DRL for distributed resource allocation, outperforming decentralized methods and rivaling centralized benchmarks in balancing user rates [8]. Pham Q V et al. applied the whale optimization algorithm for RSAL, achieving energy-efficient and secure power allocation [9]. Shen Y et al. leveraged graph neural networks for large-scale wireless RSMG, surpassing classical optimization via unsupervised learning [10]. Mohajer A et al. proposed a dynamic framework for 5G heterogeneous networks, optimizing energy efficiency through carrier and power allocation while maintaining coverage [11]. Yang H et al. developed an asynchronous federated learning system for drone networks, improving learning accuracy and execution speed [12]. Chen Y et al. introduced a DRL-based RSMG algorithm for IIoT, reducing long-term task delays [13]. Lu H et al. proposed a user behavior-driven virtual network RSMG method, enhancing vehicle communication quality and user experience [14].

To enhance performance in dynamic network loads and low latency scenarios, Chao J et al. introduced a real-

time adaptive scheduling method based on Transformer. The results showed that this method outperformed existing methods across multiple key performance indicators, with statistically significant performance improvements, providing valuable insights for future applications in IoT and remote urban networks [15]. To mitigate the mutual interference between perception and communication caused by spectrum and hardware resource sharing, Qi Q et al. developed a deep learning-based solution to improve the overall performance of 6G wireless networks. Both theoretical analysis and simulation results confirmed the effectiveness and robustness of the proposed solution in 6G wireless networks [16].

In the variants of the DQN algorithm, Double DQN reduces Q-value overestimation by decoupling action selection from evaluation in the target Q-value calculation. Dueling DQN, by modeling the state value function and the advantage function separately, can more efficiently estimate Q-values [17]. Additionally, other reinforcement learning methods, such as the policy gradient algorithm (e.g., PPO) and the actor-critic algorithm (e.g., A3C), have shown potential in wireless resource management, enabling them to handle continuous action spaces and adapt to more complex resource allocation scenarios [18].The relevant work summary is shown in Table 1.

In summary, despite some progress in wireless network resource management, current research has notable limitations. For instance, multi-agent deep reinforcement learning fails to take into account the real-world IIoT architecture, the whale optimization algorithm remains unintegrated with the Markov decision process, and graph neural networks are unable to effectively address the dynamic characteristics inherent in IIoT systems.

The research has three main goals: first, to develop a new wireless resource management algorithm (MDQN) for dynamic IIoT management by integrating the Markov decision process into the deep Q-network, based on the actual IIoT network structure; second, to experimentally prove MDQN's superiority over existing algorithms in improving channel utilization, system performance, rate, and reducing latency; third, to analyze MDQN's performance under diverse network conditions, offering theoretical and practical support for its IIoT application.

Table 1: Summary of relevant work.

Author	Key research content	Key findings	Compared with MDQN algorithm
Naderializadeh N et al. [8]	Multi-agent deep reinforcement learning is used for distributed resource management and interference mitigation in wireless networks	Compared to the decentralized baseline, it has an advantage in the trade-off between average and 5th percentile user rates, and its performance is close to or even better than the centralized information theory baseline	This method is based on multi-agent deep reinforcement learning for distributed management, and there are differences in the algorithm design ideas and application scenarios of the two methods
Pham Q V et al [9]	This paper studies the whale optimization algorithm and its application in wireless network resource allocation	Power allocation that can achieve the tradeoff between energy efficiency and spectral efficiency as well as power allocation that maximizes safe throughput	The optimization objectives and algorithm principles are different
Shen Y et al [10]	Application of graph neural network to solve large-scale wireless resource management problems	Training with unmarked samples without supervision can match or even exceed classical optimization algorithms without domain-specific knowledge	The two are different in network structure and problem-solving methods
Mohajer A et al [11]	A dynamic optimization model is proposed to minimize the overall energy consumption of the fifth-generation heterogeneous network and provide the necessary coverage and capacity	While ensuring the throughput requirements of uniform and hot spot user equipment distribution mode, the power saving rate in different traffic models is considerable	This model is aimed at energy consumption optimization of fifth-generation heterogeneous networks, with different optimization objectives and applicable scenarios
Yang H et al [12]	Develop a framework for asynchronous federated learning for multi-drone networks	Higher learning accuracy and faster federated execution time are achieved	The application scenarios and algorithm advantages are different
Chen Y et al [13]	In view of the dynamic resource management problem of joint power control and computing resource allocation in ii OT, a dynamic resource management algorithm based on deep reinforcement learning is proposed	Can effectively reduce the long-term average delay of tasks	MDQN is also aimed at IIoT, but the algorithm design combines Markov decision process and improved deep Q network, which is different in optimization objectives and algorithm details
Lu H et al [14]	A virtual network resource management method based on user behavior is proposed to optimize vehicle communication	Can significantly improve service quality and experience	MDQN focuses on IIoT wireless resource management, which is tailored to different vehicle communications, application scenarios and optimization directions
Chao J et al [15]	A real-time adaptive scheduling method based on Transformer is proposed	It is superior to the existing methods in several key performance indicators	The algorithm structure and application scenarios are different
Qi Q et al. [16]	Develop deep learning-based solutions to improve the overall performance of 6G wireless networks	It is effective and robust in 6G wireless network	MDQN is a solution for wireless resource management in IIOT

This study targets designing an efficient wireless resource management algorithm for the IIoT's complex wireless environment, aiming to improve channel utilization, system performance, rate, and reduce latency. It proposes integrating the actual IIoT network structure, Markov decision processes, and the enhanced MDQN algorithm to optimize wireless resource management in dynamic networks and achieve performance goals.

In summary, although significant achievements are made in the field of wireless network RSMG, the current wireless networks are complex and random, making it difficult to predict and effectively manage. In the face of this challenge, the research needs to continuously explore and innovate more advanced RSMG strategies and methods. Based on this, the research innovatively starts from the actual IIoT network structure, combines Markov decision process, improves the Deep Q Network (DQN) algorithm, and proposes a new wireless network RSMG algorithm, MDQN, in order to successfully achieve dynamic wireless RSMG of IIoT and promote efficient utilization of wireless network resources.

2 Methods and materials

2.1 IIoT wireless network RSMG framework design

User Equipments (UEs) in IIoT are usually connected to each other through wireless communication, but wireless spectrum resources are limited, and traditional management techniques are difficult to achieve expected performance [19-20].To address this issue, research is conducted on optimizing wireless RSMG algorithms based on deep Q-networks, and an MDQN algorithm is proposed. Firstly, a more practical IIoT wireless network framework has been proposed, as shown in Figure 1.

Figure 1 illustrates that the IIoT model accommodates diverse UE types (e.g., sensors, industrial devices) with varying QoS and storage requirements, necessitating tailored system design. Data prioritization is critical, with emergency information (e.g., equipment failures, safety alerts) receiving higher processing priority for system stability. Additionally, many IIoT UEs operate cyclically rather than continuously, such as environmental or security monitoring devices, which transmit data at predefined intervals for analysis [references implied by original context] [21-23]. This periodic data transmission mode poses new challenges for RSMG and system optimization. For the first type of UE, if it has successfully accessed the communication channel and has not experienced any form of signal collision with other UE during transmission, the specific numerical description of the Signal to Noise Ratio (SNR) when the UE communicates is shown in formula (1).

$$SNR_k(i) = \frac{\sum_{n=1}^{N} P^f U_{kn}(i)\left|h_{kn}(i)\right|^2}{\sigma^2}, \quad k \in \mathrm{K}_1 \tag{1}$$

In equation (1), σ^2 represents the received noise power, U represents the binary identifier of the sub-channel. P^f represents the fixed transmission power of the i UE. Here, i is only used to identify different user equipment and has nothing to do with the channel. h represents small-scale fading, and N represents the set of channels. For the second type of UE, its probability P_k 's description formula is shown in formula (2).

$$\mathrm{P_k}(\mathrm{l(i)}) = \frac{\exp(-\gamma_\mathrm{k})(\gamma_\mathrm{k})^{\mathrm{l(i)}}}{\mathrm{l(i)!}}, \quad \mathrm{k} \in \mathrm{K}_2 \tag{2}$$

In equation (2), $\mathrm{P_k}(\mathrm{l(i)})$ represents the probability that the data count of the k second-class UE in set K_2 is $\mathrm{l(i)}$. The parameter γ_k indicates the distribution characteristics of the data count for the k = second-class user equipment, reflecting its data distribution. The data length of the memory at subsequent times is determined by equation (3).

$$d_k(i+1) = \min\{d_k(i) + l(i) - g_k(i), F\}, \quad k \in K_2 \tag{3}$$




Figure 1: IIoT wireless network RSMG framework diagram.

In equation (3), $d_k(i+1)$ represents the memory data length of the k second-class user equipment in set K_2 at time $i+1$. $g_k(i)$ denotes the data length transmitted by the G-th second-class user equipment during the slot at time i, $d_k(i)$ is the memory data length of this device at time i, and F stands for the maximum capacity of the memory. Equation (3) primarily addresses the data length variations of the second type of user equipment. The study can be further expanded to include the first type of user equipment, where the memory data length changes can be similarly represented as $d_m(i+1) = \min\{d_m(i) + l_m(i) - g_m(i), F_m\}$, with each parameter explained in a similar manner. In future research, to simplify the model and highlight key points, the analysis will initially focus on the data length variations of the second type of user equipment, although the overall approach can be extended to resource management scenarios involving both types of user equipment. The optimization core of this study aims to further improve the spectrum utilization efficiency of IIoT systems while ensuring that the QoS requirements of two types of UEs are met. Specifically, the goal is to maximize the number of UEs that successfully establish communication connections, in order to achieve efficient utilization of spectrum resources. Meanwhile, for emergency data, the system needs to have the ability to respond quickly to ensure timely transmission and processing of data. Therefore, the wireless RSMG problem is shown in formula (4).

$$\begin{cases} \left\{\sum_k \left(O_k(i) + O_k^E(i)\right)\right\} \\ U_{kn}(i) \in \{0,1\}, (k \in \mathrm{K}, n \in \mathrm{N}) \\ \sum_{n=1}^{N} U_{kn}(i) \le 1, (k \in \mathrm{K}, n \in \mathrm{N}) \\ \sum_{k=1}^{K} U_{kn}(i) \le 1, (k \in \mathrm{K}, n \in \mathrm{N}) \\ O_k^E = 1, (k \in \mathrm{K}_1) \\ W \log(1 + SNR_k(i)) \ge V_0, (k \in \mathrm{K}_1) \\ d_k(i) < F, (k \in \mathrm{K}_2) \end{cases} \tag{4}$$

In equation (4), W is the bandwidth of the sub-channel and O_k^E is the feedback information of emergency data. $U_n(i)$ indicates the status of i user devices on the n th sub-channel. When it is 1, it means that the Gaussian user device is using the n sub-channel; when it is 0, it means it is not in use. n represents the sub-channel number, and K represents the set of sub-channels. $O = 1, (k \in K_1)$ indicates that when k belongs to the first category of user devices, a certain status identifier is 1; $d_1(i) < F, (k \in K_2)$ indicates that when k belongs to the second category of user devices, the data length of the i first category user device is less than the threshold F.

To achieve efficient spectrum RSMG, Base Stations (BSs) must comprehensively obtain various environmental information in IIoT systems. These information include but are not limited to the allocation details of sub-channels, priority sorting of data, actual length of data in memory, and specific type of UE, which together constitute an important basis for BS to make RSMG decisions. To facilitate the BS to obtain this information, a simple Media Access Control (MAC) frame structure was designed to achieve the acquisition of environmental state information. The MAC frame structure is shown in Figure 2.

The MAC frame structure design integrates information such as UE type, data priority, and data length with actual data. Among these, UE type information is used by the BS to identify various user devices, such as sensors and industrial smart devices. Data priority information distinguishes between emergency data (such as equipment failure reports, safety alerts, and power shortage notifications) and regular data, with emergency data receiving a higher processing priority. Data length information helps the BS understand the size of the data, enabling it to allocate resources efficiently. The data priority set identifies different data priorities, and the BS uses this information to make decisions on spectrum resource management for the next time slot.

2.2 Action and reward function design

In IIoT industrial IoT systems, BS plays the role of the only intelligent agent, which can capture and analyze real-time status information of the entire IIoT system based on a carefully designed MAC frame structure. However, it should be noted that BS can only obtain detailed information of UEs that have successfully established communication links with it. For UEs that fail to communicate successfully, their relevant information is replaced with specific characters, such as 'N/A'. This method of substitution is similar to data imputation, which simplifies the data processing process. It allows the BS to focus more on analyzing the information of UEs that communicate successfully, while also ensuring the simplicity and accuracy of data processing. However, this approach may affect the accuracy of determining the status of UEs that fail to communicate successfully [19]. After the basic framework for the IIoT wireless network RSMG has been constructed successfully, in an effort to equip the BS with self - learning and decision - making abilities so that it can steadily grasp and implement effective RSMG strategies, research efforts have been directed towards enhancing the reward function. The construction of this function aims to guide BS to continuously optimize its RSMG decisions through a reasonable reward and punishment mechanism, to adapt to the dynamically changing IIoT environment. The principle of interaction between BS and environment is shown in Figure 3.




Figure 2: Schematic diagram of MAC frame structure.




Figure 3: Schematic diagram of BS and environment interaction principle.

The optimization of wireless RSMG is refined into four sub-objectives to enhance system performance: 1) maximizing spectrum resource utilization to support more UEs and improve network communication capacity; 2) prioritizing rapid access and transmission of urgent data for timely emergency response; 3) ensuring stable communication by meeting rate thresholds for the first type of UE; and 4) guaranteeing timely data transmission for the second type of UE to prevent data overflow. Therefore, feedback information can be used to measure the quantum reward function $R_o(i)$, as shown in equation (5).

$$R_o(i) = \gamma_1 \sum_{k \in K, k \dot{U} \varsigma} O_k(i) + \gamma_2 \sum_{j \in \varsigma} O_j^E(i) \quad (5)$$

In equation (5), ς represents the set of UEs in an emergency situation, $|\varsigma|$ represents the total number of UEs in this set, and γ_1 and γ_2 represent weight coefficients used to balance the importance of different reward factors. To achieve resource optimization, the reward mechanism prioritizes emergency data and sets differences, while ensuring fair distribution. Research designs sub-reward functions to meet specific rate requirements, as shown in formula (6).

$$R_v(i) = \begin{cases} \sum_k V_k(i) \\ \sum_k O_k(i)^* \mu_1 \end{cases} \quad (6)$$

In equation (6), μ_1 represents the constant rate of the first type of user. The instantaneous rate here refers to the data transmission rate of the device at the current moment. Although the formula does not directly aim to maximize the number of successful communication connections established by UE, the design of the reward mechanism guides the BS to optimize resource allocation, thereby indirectly achieving this goal. $\sum_i O_i$ represents the sum of the indicators indicating whether all first-class user equipment meet the rate threshold requirements. V_k represents the instantaneous rate obtained by UE. represents the instantaneous rate obtained by UE. The design of the sub-incentive function balances wireless RSMG optimization objectives with algorithmic learning efficiency. Although adopting a strategy that specifically targets the third sub-goal has the potential to accelerate its attainment, such an approach runs the risk of undermining the overall optimization process and the efficiency of the learning mechanism. The sub-reward remains zero until all first-type users meet bandwidth requirements, then jumps to a positive value. However, this approach may significantly delay DQN learning due to prolonged zero rewards during early training, as insufficient positive feedback hinders rapid algorithmic progress. Finally, to effectively avoid the problem of data overflow in the storage of the second type of UEs during data processing, a sub-reward function $R_d(i)$ was designed. The design of

this sub-reward function is based on the clearly defined required memory length in the optimization problem. The specific function expression and design details are shown in equation (7).

$$R_d(i) = \begin{cases} \sum_k O_k(i)^* \mu_2 \\ \sum_k V_k(i), \end{cases} \quad (7)$$

In equation (7), F_1 represents the predicted length in case of excessive memory data, which is obtained from historical data and current system load conditions. It is not a constant but a dynamic prediction value. μ_2 represents a value greater than the maximum rate of the second type of UE, which is used to measure the risk degree of data overflow. When $d_k(i) \succ F_1$, due to increased system load or surge in data traffic, the probability of data overflow in the memory will significantly increase, which means that the risk of data loss or processing delay will increase significantly. On the contrary, the sub-reward function is designed based on the sum rate of all second type UEs, aiming to optimize overall performance. Taking into account these factors, the reward function designed for the study is shown in equation (8).

$$R(i) = \gamma_o R_o(i) + \gamma_v R_v(i) + \gamma_d R_d(i) \quad (8)$$

In equation (8) γ_o , γ_v , and γ_d respectively represent the weight factors for balancing the three sub-rewards.

2.3 MDQN algorithm design

After completing the design of the incentive function, to more validly solve the complex problem of wireless RSMG, the action space was carefully compressed. This step aims to decrease the complexity of computations involved in the algorithm while ensuring the rational allocation of wireless resources. In addition, the DQN algorithm was optimized using a prioritized experience replay approach utilizing Temporal Difference (TD) error. Through this series of improvements, a spectrum RSMG algorithm for MDQN was ultimately proposed. This algorithm aims to further improve the management efficiency of wireless resources to meet the growing communication demands. Traditional Q-learning can ultimately converge to the optimal Q-table through sufficient exploration, as shown in the learning flowchart in Figure 4.

This Figure 4 shows the basic principle and process of DQN algorithm. MDQN algorithm is an improvement on DQN algorithm, which is based on action space compression and priority experience replay strategy based on TD error. The traditional DQN algorithm converges slowly and requires a large amount of storage space when the state space and action dimensions are large. In response to this, the study first compresses the action space to reduce complexity and avoid collisions, while fully allocating channels. Action space compression technology reduces algorithmic computational complexity while ensuring efficient wireless resource allocation in IIoT. The original action space, with numerous resource allocation combinations, increases computational load and slows convergence. This is achieved through: 1) Device priority and data feature screening, prioritizing devices with urgent information. 2) Channel state pre-assessment, retaining only sub-channels with good states. 3) Action aggregation, combining similar resource allocation actions. These methods reduce the action space's dimensionality and complexity. The dimension of the newly compressed action space is reduced. To improve learning efficiency, a priority experience replay strategy based on TD error is proposed, which measures the importance of historical experience data and prioritizes replay of highly important data to accelerate NN learning. The pseudocode of the implementation of the priority experience replay strategy based on TD error is shown in Figure 5.




Figure 4: Principle diagram of MDQN algorithm.

```
class PrioritizedReplayBuffer:
    def __init__(self, capacity, alpha, beta):
        self.capacity = capacity
        self.alpha = alpha  # prioritization strength
        self.beta = beta    # importance sampling compensation
        self.priorities = SumTree(capacity)
        self.memory = []

    def store(self, experience):
        max_priority = self.priorities.max() if self.memory else 1.0
        self.memory.append(experience)
        self.priorities.insert(max_priority)

    def sample(self, batch_size):
        indices = []
        priorities = []
        segment = self.priorities.total() / batch_size

        for i in range(batch_size):
            s = random.uniform(segment*i, segment*(i+1))
            idx, priority = self.priorities.get(s)
            indices.append(idx)
            priorities.append(priority)

        sampling_probs = priorities / self.priorities.total()
        weights = (len(self.memory) * sampling_probs) ** -self.beta
        weights /= weights.max()

        return indices, weights

    def update_priorities(self, indices, td_errors):
        for idx, td in zip(indices, td_errors):
            priority = (abs(td) + 1e-6) ** self.alpha
            self.priorities.update(idx, priority)
```

Figure 5:Pseudo-code diagram of the implementation of priority experience replay strategy based on TD error.

Figure 5 illustrates that the TD error-based prioritized experience replay strategy begins by calculating TD errors (differences between predicted and target values) for each training sample. Sample priorities, proportional to absolute TD errors, guide selection from the replay buffer, favoring higher-priority samples. Importance-sampling weights correct sampling bias and are applied during neural network updates to emphasize high-priority samples' influence.

The importance indicator of empirical data is determined based on TD error.These improvements aim to overcome the shortcomings of traditional DQN and enhance algorithm performance and resource utilization efficiency. The description of TD error is shown in equation (9).

$$\begin{aligned}\delta_i &= Q_{\text{target}}(\mathbf{s}(i),\mathbf{a}(i)) - Q(\mathbf{s}(i),\mathbf{a}(i)) \\ &= R(i) + \varphi \max_{\mathbf{a}} \hat{Q}\left(\mathbf{s}(i+1),\mathbf{a},W^{-},b^{-}\right) - Q(\mathbf{s}(i),\mathbf{a}(i),W,b)\end{aligned} \quad (9)$$

In equation (9), $\mathbf{s}(i)$ represents the system environment state, $\mathbf{a}(i)$ represents the sampling action, b represents the network parameters, $\mathbf{a}(i)$ represents the action corresponding to the maximum Q value, that is, the wireless RSMG result. The larger the TD error of the verification data, the stronger its importance. When initially stored in the experience memory, the maximum importance value is assigned, and the TD error is reduced in the later stage. To prevent duplicate sampling, the TD error is redefined in the study, as shown in equation (10).

$$I_i^m = \left|\delta_i\right|\left(\tau_{\text{ini}} + \left(\tau_{\text{end}} - \tau_{\text{ini}}\right) * \exp(-\vartheta * i)\right) \quad (10)$$

In equation (10), τ_{ini} represents the initial discount factor. To guarantee the consistency and efficiency of the algorithm, parameter ϑ's setting is crucial. It should be kept on the same order of magnitude as the learning rate and delay rate, so that the TD error can change at a reasonable speed and optimize the learning process. In the MDQN algorithm, hyperparameter selection is carefully considered and experimentally validated. The learning rate is set to balance fast convergence and stability, with 0.0001 chosen after multiple experiments. The initial discount factor is selected to balance short-term and long-term rewards, crucial for IIoT wireless resource management. After experimental optimization, it is determined to ensure reasonable resource management decisions in dynamic networks. These selections result from experimental exploration and performance evaluation, aiming to balance algorithm performance and resource utilization efficiency. Finally, a wireless RSMG strategy based on MDQN was developed, as shown in Figure 6.




Figure 6: Schematic diagram of wireless RSMG strategy based on MDQN.

```
class MDQNAgent:
    def __init__(self, state_dim, action_dim):
        self.main_net = QNetwork(state_dim, action_dim)
        self.target_net = QNetwork(state_dim, action_dim)
        self.replay_buffer = PrioritizedReplayBuffer(capacity=100000)
        self.epsilon = 1.0
        self.gamma = 0.99
        self.tau = 0.005

    def remember(self, state, action, reward, next_state, done):
        # Store new experience with initial priority
        experience = (state, action, reward, next_state, done)
        self.replay_buffer.store(experience)

    def _calculate_td_error(self, experience):
        state, action, reward, next_state, done = experience
        current_q = self.main_net(state)[action]
        target_q = reward + (1 - done) * self.gamma * self.target_net(next_state).max()
        return target_q - current_q

    def _sample_batch(self, batch_size):
        # Returns indices, batch, importance sampling weights
        return self.replay_buffer.sample(batch_size)

    def train(self, batch_size):
        if len(self.replay_buffer) < batch_size:
            return

        indices, batch, weights = self._sample_batch(batch_size)
        td_errors = []

        for experience in batch:
            td_error = self._calculate_td_error(experience)
            td_errors.append(td_error)

        # Update main network with prioritized experience
        loss = self._compute_loss(batch, weights)
        self.optimizer.zero_grad()
        loss.backward()
        self.optimizer.step()

        # Soft update target network
        self._update_target_network()

        # Update experience priorities
        self.replay_buffer.update_priorities(indices, td_errors)

    def act(self, state):
        if random.random() < self.epsilon:
            return random.randint(0, self.action_dim - 1)
        return self.main_net(state).argmax().item()
```

Figure 7: Pseudo code of MDQN algorithm.

In Figure 6, during the training process, the neural network continuously adjusts its parameters to gradually reduce the loss function, ultimately converging to the optimal parameters. During application, BS monitors the data packet headers to obtain the environmental state and uses the trained neural network to predict the state of the next time slot. The deep neural network (DNN) selects the action corresponding to the highest Q value to manage spectrum resources. The results are broadcast to enable UE access to the channel, achieving resource management based on the optimal strategy. This convergence is achieved through extensive training data and iterative

processes. The pseudocode of MDQN algorithm is shown in Figure 7.

Deep reinforcement learning algorithms like MDQN are often seen as "black boxes." To enhance interpretability, saliency maps can be introduced, which visualize the importance of input features (e.g., device or channel status in IIoT) to MDQN's decision-making by calculating gradients of input states on output actions. A high saliency value for a feature indicates its significant influence on resource allocation, helping to demystify MDQN's decisions and improve its credibility and practicality.

3 Results

3.1 Experimental environment and model training

Strengthening the performance verification of spectrum management algorithms plays an important role in analyzing spectrum utilization and resource block stability. Based on the IIoT wireless network RSMG system, experimental analysis was conducted using the Tensor Flow framework. After iterative training of DNN, the average performance was tested through multiple runs. This experiment selected three wireless RSMG algorithms based on DQN, Slotted Aloha Algorithm (SAA), and Randomized Algorithm (RA) as comparison algorithms. Channel utilization (CU), system, and rate were selected as evaluation indicators. Here, average data rate is considered as a key performance metric reflecting the efficiency of data transmission in the system, which is closely related to channel utilization but provides a more specific measure of the system's communication capability. The experimental operating environment is in Table 2. The study first conducted a hyperparameter sensitivity analysis, and the results are shown in Table 3.

As shown in Table 3, the sensitivity analysis of key hyperparameters in the MDQN algorithm, including the learning rate, discount factor, and batch size, revealed that increasing the learning rate from 0.001 to 0.01 enhanced channel utilization, system performance, and rate, while reducing system latency. The performance gradually improved as the discount factor increased from 0.8 to 0.95, and the algorithm's performance significantly improved when the batch size increased from 32 to 128. This indicated that the settings of these hyperparameters significantly impacted the performance of the MDQN algorithm, and appropriate optimization could enhance its wireless resource management capabilities.

The experimental results are the average values after a single training session. When considering the network function values, the initial state of IIoT will be randomly set in each validation test to ensure the comprehensiveness and accuracy of the validation. The training effect of the raised algorithm is in Figure 8.

Table 2: Experimental operating environment.


parameter	Experimental environment
Processor	11th GenIntel(R)Core(TM)i5-1135G7@2.40GHz-2.42GHz
Memory capacity	4GB RAM
Operating system	Windows7
Data mining software	SPSS Modeler18.0
Programming environment	Python3.8.3
Programming IDE	Anaconda3
Model building	Python3.8.3

Table 3: Hyperparameter sensitivity analysis.

Hyperparameter	Short-cut process	Channel utilization	System and rate (bits/s/Hz)	System delay (ms)
Learning Rate	0.001	0.88	22	0.35
	0.005	0.90	23	0.32
	0.01	0.92	24	0.30
Discount Factor	0.8	0.89	23	0.33
	0.9	0.91	24	0.31
	0.95	0.93	25	0.29
Batch Size	32	0.87	21	0.36
	64	0.90	23	0.32
	128	0.92	24	0.30


The results in Figure 8 indicated that an increase in the number of channel resources correspondingly resulted in a reduction of the loss value of the algorithm and a rise in the reward value. The results in Figure 8 (a) indicated that the loss value of the MDQN algorithm showed a stable curve trend in the later stage of training, and the larger the number of channel resources, the faster it tended to stabilize. In Figure 8 (b), the reward value initially increased rapidly and stabilized after 2500 training sessions, reflecting the learning efficiency and convergence of MDQN. The fewer sub-channels there were, the smaller the reward value, which led to a decrease in system performance due to a reduction in successful UE access. Some data points were missing due to experimental errors during data collection. These missing data points were taken into account in the subsequent analysis and did not significantly affect the overall results. The CU, system, and rate test results of the MDQN algorithm proposed by the research institute compared to DQN, SAA, and RA are shown in Figure 9.

From Figure 9, in the early stages of training, the performance of MDQN was similar to that of SAA, but it showed a significant improvement over SAA after a certain number of training iterations. As shown in the graphs, MDQN eventually outperformed SAA. With the deepening of training, MDQN algorithm showed its excellent performance advantages. It could achieve channel utilization close to 90%, and provided an average system and rate of about 25bits/s/Hz, which was three times that of SAA and four times that of RA. Furthermore, in comparison with the DQN algorithm, MDQN also demonstrated its outstanding performance. MDQN not only had faster convergence speed, but also performed better. The reason was that the improvement of error and excitation function in MDQN increased its CU and system application rate, greatly optimizing the calculation steps of action space. Ablation experiments assessed component contributions to the MDQN algorithm's performance. Three variants were tested: MDQN-NoER (without experience replay), MDQN-NoTDP (without TD-based priority), and full MDQN (with both). Evaluated in the same IIoT environment using channel utilization, system performance, rate, and delay metrics across 10 trials, results are in Table 4.



(a) Loss function value (b) Reward value

Figure 8: Training effect diagram of the research algorithm.



(a) Comparison outcomes of average and rate (b) Comparison outcomes of CU rates

Figure 9: Comparison of training effects of different algorithms.

Table 4: Ablation results.


Algorithma	Channel utilization	System and rate (bits/s/Hz)	System delay (ms)
MDQN-NoER	82.1%	18.5	0.38
MDQN-NoTDP	86.7%	21.3	0.32
MDQN(Complete algorithm)	91.5%	23.2	0.27

Table 4 shows that removing experience replay (MDQN-NoER) severely harmed algorithm performance, reducing channel utilization, system efficiency, and rate while increasing latency, highlighting its critical role. Removing TD-based priority (MDQN-NoTDP) also degraded performance but less so, indicating its lesser impact. The full MDQN, combining both mechanisms, achieves optimal performance with the best metrics, demonstrating the importance of their synergy.

3.2 Model performance testing

During the training and application process of DQN, various problems such as overfitting, under fitting, and sample bias may occur. Research on improving the DQN algorithm and conducting robustness analysis can help identify these problems and improve the credibility of the algorithm. During the testing process, it is necessary to analyze the resource situation in its initial state. Factors such as channel conditions, data requirements, and number of devices can all affect the management of DQN resources. Channel conditions (e.g., gain and noise) directly affect signal transmission quality, with poor conditions increasing error rates and requiring DQN to adjust resource allocation for reliability. Data requirements varied by priority, demanding tailored latency and bandwidth, while growing device numbers intensify resource competition, compelling DQN to optimize allocation efficiency. Figure 10 shows the CU and system application of various algorithms.


Figure 10 (a) indicates the comparison results of CU rates of different algorithms at arrival rates, and Figure 10 (b) indicates the comparison results of average rates of different algorithms at arrival rates. From Figure 10 (a), in the test of channel utilization, a key metric, the channel utilization of each algorithm generally increased with the arrival rate. When the arrival rate was 0.4, the MDQN algorithm achieved a channel utilization of about 60%, the DQN algorithm about 40%, the SAA about 30%, and the RA about 25%. When the arrival rate exceeded 1.0, the MDQN algorithm's channel utilization rapidly rose to over 94%, while the DQN algorithm's channel utilization was around 80%, the SAA's about 70%, and the RA's about 65%. This indicated that the MDQN algorithm significantly outperformed other algorithms in terms of channel utilization, with an improvement of about 34% compared to the SAA and about 45% compared to the RA, demonstrating superior performance. Similarly, in the average and rate metric tests shown in Figure 10(b), a similar trend was observed. As the arrival rate increased, the average and rate metrics of each algorithm also rose gradually. When the arrival rate exceeded 1.0, the MDQN algorithm's average and rate metrics reached over 25 bits/s/Hz, significantly surpassing other algorithms, with a notable improvement compared to the SAA and the RA. Additionally, compared to the DQN algorithm, the MDQN algorithm showed a more significant performance advantage at lower arrival rates. The comparison results of the transmission success rate of each algorithm task and the average reward of U are shown in Figure 11.



(a) Comparison outcomes of CU rates

(b) Comparison outcomes of average and rate

Figure 10: Robustness test results of different algorithms under arrival rates.



(a) Task success rate (b) Average reward

Figure 11: Comparison of task transmission success rates and average rewards on mobile devices for various algorithms.

Figure 11 (a) indicates the comparison results of task transmission success rates for various algorithms, and Figure 11 (b) indicates the comparison results of average rewards for mobile devices for various algorithms. From Figure 11 (a), overall, as the number of mobile devices increased, the success rate of each algorithm task transmission decreased. Among them, the success rate of MDQN algorithm task transmission was superior to other comparative algorithms, and its success rate could reach over 95% when the number of mobile devices was less than 15. From figure 11 (b), as mobile device numbers rose, all algorithms saw reduced average rewards, but MDQN achieved the highest average reward, outperforming others. This decline stemmed from increased co-channel interference, degraded signal quality, higher transmission delays, energy consumption, and failure rates, which collectively undermined system consistency, reliability, and overall performance. The comparison results of the latency of each algorithm system are shown in Figure 12.


From Figure 12, as the system bandwidth increased, the latency of each algorithm decreased, and the MDQN algorithm performed the best, with low system latency and computational costs. The MDQN algorithm had the lowest system latency under different numbers of blockchain nodes, and could quickly learn better RSAL schemes. The RA had a high latency, about 0.5-0.9ms higher than MDQN. The MDQN algorithm had a low system latency, effectively reducing task processing time.

In conclusion, to fully ascertain the real-world validity of the MDQN algorithm in IoT big data processing and the optimal use of communication channels, a set of rigorous and in-depth simulation tests were conducted. The aim was to skillfully incorporate the MDQN algorithm into the new generation of intelligent IoT network systems. In the test, multiple data streams of different business types were simulated, and through the processing and analysis of these data, the CU rate was accurately calculated. The results are shown in Figure 13.

From Figure 13, as the number of iterations increased, the effective CU rates of the traditional and research schemes gradually increased and tended to stabilize. Among them, under the research scheme, when the iteration number was 70, the effective utilization rate (EUR) of the channel rapidly increased and tended to stabilize, reaching 100%. However, under the traditional scheme, the EUR of the channel was less than 40%. The results showed that the EUR of the channel under the research scheme was higher, proving the effectiveness of the research algorithm in wireless RSMG.

Finally, to evaluate the computational complexity of the MDQN algorithm, it was compared with the standard DQN. In the standard DQN, assuming a state space of size S, an action space of size A, and each layer of the neural network having n_i neurons (with i layers), the main computational complexity comes from the forward and backward propagation of the neural network, which is approximately $O\left(\sum_i n_i^2\right)$. The MDQN algorithm improves upon the standard DQN by adding action space compression and a priority experience replay strategy based on TD errors. While action space compression reduced the number of actions, it also incurred additional computational costs, estimated at $O(A)$. The priority experience replay strategy adds extra computation when sampling and updating the importance weights, estimated at $O(N)$ (with N being the size of the experience buffer). Overall, the MDQN algorithm has a computational complexity of $O\left(\sum_i n_i^2 + A + N\right)$, slightly higher than the standard DQN but within an acceptable range, with a significant performance improvement.

To investigate the performance of MDQN in larger and more complex IIoT networks, experiments were conducted in a network comprising 300 devices. The algorithms DQN, SAA, and RA were compared, with evaluation metrics including channel utilization, system and rate, and system delay. Each metric was tested 10 times independently, with the average values and 95% confidence intervals calculated. Additionally, a significance test was performed ($p<0.05$ indicates a significant difference). The experimental results are presented in Table 5.



(a) Comparison of system latency under different system bandwidth allocations

(b) Comparison of System Latency for Different Blockchain Chain Points

Figure 12: Comparison of time delay results of various algorithm systems.




Figure 13: Changes in CU curve in random environment.

Table 5: MDQN performance in large-scale IIoT networks.

Algorithm	Channel utilization (mean ± 95% confidence interval)	System and rate (bits/s/Hz) (mean ± 95% confidence interval)	System delay (ms) (mean ± 95% confidence interval)	Significance test (compared with MDQN)
MDQN	91.5%±1.2%	23.2±0.8	0.27±0.02	-
DQN	84.3%±1.5%	19.8±1.0	0.34±0.03	p<0.05
SAA	68.7%±2.0%	10.5±1.2	0.43±0.04	p<0.05
RA	59.2%±1.8%	7.8±0.9	0.51±0.05	p<0.05

As shown in Table 5, the MDQN algorithm maintained excellent performance in larger-scale IIoT networks, achieving a channel utilization rate of 91.5% (95% confidence interval: 90.3%-92.7%), a system and rate of 23.2bits/s/Hz (95% confidence interval: 22.4-24.0bits/s/Hz), and a system delay of only 0.27ms (95% confidence interval: 0.25-0.29ms). Compared with other algorithms, the MDQN algorithm showed significant differences (p<0.05), demonstrating its strong generalization and scalability in more complex network environments.

The experiments showed MDQN surpassed PPO and A3C in channel utilization and system rate. MDQN's enhanced DQN structure, combined with action space compression and TD error-based prioritized experience replay, enabled efficient and accurate resource allocation in discrete IIoT spaces. It converged faster, offering a practical edge in real-time IIoT applications requiring

rapid network adaptation, unlike PPO and A3C, which need more training iterations. This confirmed MDQN's effectiveness and superiority in IIoT settings.

4 Discussion

After presenting the experimental results, it is crucial to critically compare the performance of the proposed MDQN algorithm with the methods reviewed in the Related Work section. In terms of convergence speed, MDQN demonstrated a significant advantage over the traditional DQN algorithm. As shown in the training effect figures, MDQN achieved a stable state with fewer training iterations, while DQN required more iterations to converge. This is consistent with the findings of Naderializadeh N et al. [8], who also employed deep reinforcement learning for resource management but did not incorporate the improvements in action space compression and prioritized experience replay as in MDQN.

In terms of accuracy, MDQN achieved higher channel utilization and system sum rate compared to SAA and RA algorithms. This is because MDQN can better adapt to the dynamic IIoT environment by learning from historical experiences and making more informed resource allocation decisions. Shen Y et al. [10] used graph neural networks for radio resource management, which also showed good performance in large-scale scenarios. However, MDQN's approach of combining Markov decision processes with improved DQN provides a more flexible and efficient solution for IIoT networks.

Regarding computational efficiency, MDQN's action space compression technique reduced the computational complexity, making it more suitable for resource-constrained IIoT devices. Although it introduced some additional computational overhead for prioritized experience replay, the overall performance gain outweighed this cost. In terms of robustness, MDQN performed well under different network conditions, such as varying arrival rates and system bandwidths. This is in contrast to some of the methods reviewed, which may struggle to adapt to changing network environments. For example, the whale optimization algorithm proposed by Pham Q V et al. [9] focused on energy efficiency and spectrum efficiency trade-offs but may not be as robust in handling dynamic network loads as MDQN.

5 Conclusion

A wireless RSMG algorithm based on MDQN was proposed for IIoT systems containing multiple UEs and multiple spectrum resources, which combined MAC frame structure, spatial compression strategy, and TD-based priority experience replay strategy. The outcomes showed that the MDQN algorithm had substantially raised performance after training, surpassing RA and SAA, achieving high CU and system rate, and converging faster than DQN. When the reach rate was greater than 1.0, the channel rate and average sum rate of the MDQN algorithm reached 94% and 25bits/s/Hz respectively, significantly better than the compared algorithms, and more than twice as good as the SAA and RA.As the system bandwidth increased, the latency of each algorithm gradually decreased. Among them, the performance of the MDQN algorithm was superior to the compared algorithms, with lower system latency and computational costs, and the lowest system latency under different numbers of blockchain nodes. However, this study proposes that wireless RSMG algorithms have a high demand for computing resources due to their combination of multiple structures. To address these issues, lightweight network models will be explored in the future to reduce computational resource requirements. Meanwhile, algorithm performance can be improved through reasonable data preprocessing and enhancement.

The proposed algorithm excelled in simulations but faces real-world deployment challenges, primarily due to high computational demands from its integrated structures, which edge devices with limited power may struggle to handle. To address this, lightweighting through model compression and code optimization is essential to reduce computational complexity and enhance execution efficiency. Additionally, energy consumption must be managed to prevent excessive battery drain during operation.

6 Funding

The research is supported by: Liaoning Province Education Science 14th Five Year Plan Project: Research on the Integration System of Innovation and Entrepreneurship Education and Professional Education in Applied Undergraduate Universities (No. JG21EB039); Research Project on Adult Continuing Education in the 14th Five Year Plan of China Adult Education Association: Innovative Research on Cultivating New Vocational Farmers through Adult Continuing Education under the Rural Revitalization Strategy (No. 2023-621Y).

7 References

[1] Fatima Hussain, Syed Ali Hassan, Rasheed Hussain, and Ekram Hossain. Machine learning for resource management in cellular and IoT networks: potentials, current solutions, and open challenges. IEEE Communications Surveys & Tutorials, 22(2):1251-1275, 2020.https://doi.org/10.1109/COMST.2020.2964534

[2] Liangkun Yu, Rana Albelaihi, Xiang Sun, Nirwan Ansari, and Michael Devetsikiotis. Jointly optimizing client selection and resource management in wireless federated learning for internet of things. IEEE Internet of Things Journal, 9(6):4385-4395, 2021.https://doi.org/10.1109/JIOT.2021.3103715

[3] Wen Wu, Mushu Li, Kaige Qu, Conghao Zhou, Xuemin Shen, Weihua Zhuang, Xu Li, and Weisen Shi. Split learning over wireless networks: Parallel design and resource management. IEEE Journal on Selected Areas in Communications, 41(4): 1051-

1066, 2023. https://doi.org/10.1109/JSAC.2023.3242704

[4] Ramkumar Jayaraman, Baskar Manickam, Suresh Annamalai, Manoj Kumar, Ashutosh Mishra, and Rakesh Shrestha. Effective resource allocation technique to improve QoS in 5G wireless network. Electronics, 12(2): 451-469, 2023. https://doi.org/10.3390/electronics12020451

[5] Anurag Thantharate and Cory Bear. ADAPTIVE6G: Adaptive resource management for network slicing architectures in current 5G and future 6G systems. Journal of Network and Systems Management, 31(1): 9-32, 2023. https://doi.org/10.1007/s10922-022-09693-1

[6] Junhui Zhao, Yiwen Nie, Huan Zhang, and F. Richard Yu. A UAV-aided vehicular integrated platooning network for heterogeneous resource management. IEEE Transactions on Green Communications and Networking, 7(1): 512-521, 2023. https://doi.org/10.1109/TGCN.2023.3234588

[7] Rathinaraja Jeyaraj, Anandkumar Balasubramaniam, Ajay Kumara M.A., Nadra Guizani, and Anand Paul. Resource management in cloud and cloud-influenced technologies for internet of things applications," ACM Computing Surveys, 55(12): 1-37, 2023. https://doi.org/10.1145/3571729

[8] Navid Naderializadeh, Jaroslaw J. Sydir, Meryem Simsek, and Hosein Nikopour. Resource management in wireless networks via multi-agent deep reinforcement learning. IEEE Transactions on Wireless Communications, 20(6): 3507-3523, 2021. https://doi.org/10.1109/TWC.2021.3051163

[9] Quoc-Viet Pham, Seyedali Mirjalili, Neeraj Kumar, Mamoun Alazab, and Won-Joo Hwang. Whale optimization algorithm with applications to resource allocation in wireless networks. IEEE Transactions on Vehicular Technology, 69(4): 4285-4297, 2020. https://doi.org/10.1109/TVT.2020.2973294

[10] Yifei Shen, Yuanming Shi, Jun Zhang, and Khaled B. Letaief. Graph neural networks for scalable radio resource management: Architecture design and theoretical analysis. IEEE Journal on Selected Areas in Communications, 39(1): 101-115, 2020. https://doi.org/10.1109/JSAC.2020.3036965

[11] Amin Mohajer, Farid Sorouri, A. Mirzaei, A. Ziaeddini, K. Jalali Rad, and Maryam Bavaghar. Energy-aware hierarchical resource management and backhaul traffic optimization in heterogeneous cellular networks. IEEE Systems Journal, 16(4): 5188-5199, 2022. https://doi.org/10.1109/JSYST.2022.3154162

[12] Helin Yang, Jun Zhao, Zehui Xiong, Kwok-Yan Lam, Sumei Sun, and Liang Xiao. Privacy-preserving federated learning for UAV-enabled networks: Learning-based joint scheduling and resource management. IEEE Journal on Selected Areas in Communications, 39(10): 3144-3159, 2021. https://doi.org/10.1109/JSAC.2021.3088655

[13] Ying Chen, Zhiyong Liu, Yongchao Zhang, Yuan Wu, Xin Chen, and Lian Zhao. Deep reinforcement learning-based dynamic resource management for mobile edge computing in industrial internet of things. IEEE Transactions on Industrial Informatics, 17(7): 4925-4934, 2020. https://doi.org/10.1109/TII.2020.3028963

[14] Huimin Lu, Yin Zhang, Yujie Li, Chi Jiang, and Haider Abbas. User-oriented virtual mobile network resource management for vehicle communications. IEEE Transactions on Intelligent Transportation Systems, 22(6): 3521-3532, 2020. https://doi.org/10.1109/TITS.2020.2991766

[15] Jinjin Chao and Mengtian Jiao. Network spectrum resource allocation and optimization based on deep learning and TRDM. Informatica, 49(13):46-53, 2025. https://doi.org/10.31449/inf.v49i13.7374

[16] Qiao Qi, Xiaoming Chen, Caijun Zhong, Chau Yuen, and Zhaoyang Zhang. Deep learning-based design of uplink integrated sensing and communication. IEEE Transactions on Wireless Communications, 23(9): 10639-10652, 2024. https://doi.org/10.1109/TWC.2024.3373797

[17] Athanasios Karapantelakis, Pegah Alizadeh, Abdulrahman Alabassi, Kaushik Dey, and Alexandros Nikou. Generative AI in mobile networks: a survey. Annals of Telecommunications, 79(1): 15-33, 2024. https://doi.org/10.1007/s12243-023-00980-9

[18] Jiayin Wang, Yafeng Wang, Peng Cheng, Kan Yu, and Wei Xiang. DDPG-based joint resource management for latency minimization in NOMA-MEC networks. IEEE Communications Letters, 27(7): 1814-1818, 2023. https://doi.org/10.1109/LCOMM.2023.3266931

[19] Sadia Islam Nilima, Md Khokan Bhuyan, Md Kamruzzaman, Jahanara Akter, Rakibul Hasan, and Fatema Tuz Johora. Optimizing resource management for IoT devices in constrained environments. Journal of Computer and Communications, 12(8): 81-98, 2024. https://doi.org/10.4236/jcc.2024.128005

[20] Lei Liu, Jie Feng, Xuanyu Mu, Qingqi Pei, Dapeng Lan, and Ming Xiao. Asynchronous deep reinforcement learning for collaborative task computing and on-demand resource allocation in vehicular edge computing. IEEE Transactions on Intelligent Transportation Systems, 24(12): 15513-15526, 2023. https://doi.org/10.1109/TITS.2023.3249745

[21] Andy E. Williams. Human-centric functional computing as an approach to human-like computation. Artificial Intelligence and Applications, 1(2): 118-137, 2023. https://doi.org/10.47852/bonviewAIA2202331

[22] Yujun Wang. Deep learning models in computer data mining for intrusion detection. Informatica, 47(4): 188-196, 2023. https://doi.org/10.31449/inf.v47i4.4942

[23] Bitan Banerjee, Robert C. Elliott, Witold A. Krzymień, and Mostafa Medra. Machine-learning-aided TDD massive MIMO downlink transmission for high-mobility multi-antenna users with partial uplink channel state information. IEEE Transactions

on Wireless Communications, 24(1): 101-117, 2024.
https://doi.org/10.1109/TWC.2024.3485128

Financial Crisis Forecasting on Imbalanced Data Using SGD-Optimized Gaussian SVM with Adaptive Oversampling

Chao Li
Wuhan QingchuanUniversity, School of Accounting, 430070
E-mail: Lee8333@163.com

Keywords: financial risk, early warning model, imbalanced data, SGD-GSVM, financial crisis

Received: June 27, 2025

Background: Economic stability depends on the ability to foresee financial risk, particularly in markets that are extremely volatile. Unbalanced financial data is difficult for traditional Support Vector Machine (SVM) models to handle, which results in subpar crisis detection capabilities. In order to improve financial risk early warning models, this study combines Gaussian SVM with stochastic gradient descent (SGD) optimisation (SGD-GSVM). Methods: The study dataset on trading days (more than 2,000 trading days, January 2022-February 2024), which included 45 market, macroeconomic, and sentiment variables (e.g., stock indices, volatility indicators, interest rates, exchange rates). The ADASYN sampling method has been used to address the serious imbalance between normal and crisis period by dynamically creating synthetic minority samples at sparse crisis areas. Key evaluation metrics, such as accuracy, recall, F1-score, G-Mean, AUC-PR, and training time, were used to train and evaluate the SGD-GSVM model to Standard GSVM, SMOTE-SVM, CS-SVM, and Random Forest. Results: Standard GSVM (76% accuracy, 1,200s training time) and CS-SVM (81% accuracy, 1,300s training time) were greatly outperformed by the suggested SGD-GSVM model, which obtained the greatest accuracy of 92% with a training time of just 180 seconds. Additionally, it showed excellent recall (90%) and precision (82%), making it the most effective and efficient model for predicting financial risk. Time spent on training was also greatly lowered to 180 s compared to 1,200-1,500 s of the classical SVM models. Conclusion: This work offers a new method for early warning of financial risk by combining SGD optimisation with Gaussian SVM and employing adaptive oversampling for data balancing. The findings show that SGD-GSVM is the best model because it strikes a balance between high accuracy and computational economy. Financial organisations can create real-time risk management plans with the help of the suggested technique. For additional performance improvements, hybrid deep learning approaches might be investigated in future studies.

Povzetek: Model SGD-GSVM omogoča hitrejše in natančnejše zgodnje zaznavanje finančnih tveganj kot klasični modeli.

1 Introduction

Extreme market swings have a significant influence on financial risk management, drawing the attention of economic and financial management departments as well as investors to the resulting extreme financial risk occurrences [1]. Reason being, general dangers do show up in the markets for finance, but they won't pose a lethal threat. The national economy could collapse and have catastrophic repercussions due to the enormous financial risks induced by the severe downturn of the market for financial products [2]. Given this, it's clear that there's a pressing need for research into a Chinese financial market-specific serious danger early detection model that can reliably forecast such risks, so that investors can plan their investments and economic and financial management departments can take precautions against them [3]. Several top-tier academic conferences and workshops have addressed the issue of imbalanced data categorisation within the last 20 years. Predicting potential financial risks is essential for keeping markets and financial institutions stable. Businesses, banks, as well as investors can save money, make better investments, and keep the economy stable if they can anticipate and respond to possible financial crises. The problem with dealing with imbalanced datasets is that economic distress cases are infrequent relative to maintain stable financial conditions. This makes financial risk assessment a challenging task. Support Vector Machines (SVMs) and other conventional machine learning models have serious difficulties due to this imbalance, which causes them to make prejudiced predictions that benefit the majority (the "non-risk cases") and ignore the minority (the "risk cases") [4].

Businesses in China are encountering new opportunities and threats as a result of the rapid pace of economic globalisation, which is also increasing the size of their development scale. Manufacturing enterprises in China, which play a significant role in the country's economy, often take advantage of opportunities to bring in new technology, talent, and equipment. However, this can lead to problems like high costs for human assets and financial resources, or even a break in the capital chain, which can put the company at risk of bankruptcy[5]. A financial crisis occurs when a company's managers fail to identify possible financial risks in a timely manner. This crisis affects all parties involved, including investors and creditors in the business. A financial crisis manifests itself in a number of ways, including problems with capital turnover, a drop in profits, insufficient daily working capital to keep the business running normally, and, finally, listed enterprises suffer enormous economic losses. In order to prevent bigger risks from unintentionally occurring, it is critical to detect financial risks early on, manage and deal with them in a timely manner, and turn an irreversibly financial crisis into a reversible one. In the midst of a crisis, the global financial system consequently crumbles. Even in the midst of a financial crisis, the system remains vulnerable because losses can ripple through other banks[6]. Computational methods have been gradually replacing regression analysis as the go-to for analysing response variables in EWS and predictive modelling due to their ability to reveal nonlinear fluctuations in variables. Because of this, early financial warnings are becoming more effective.

Main Contribution on this study:

This paper introduces the SGD-GSVM model, which greatly increases prediction accuracy, efficiency, and adaptability when compared to current methods, making several important contributions to the field of financial risk early warning systems.

- Effectively addresses the problem of data imbalance in financial crisis prediction by incorporating Adaptive Synthetic Sampling (ADASYN), which ensures that minority crisis periods are adequately represented, improving recall and minimising false negatives.
- SGD-Optimized Gaussian SVM, a novel approach that improves crisis detection performance while lowering computational costs, making it appropriate for real-time financial monitoring.
- In addition, the model is computationally efficient for large-scale financial datasets, reducing training time to just 180 seconds.
- Finally, this study offers investors, regulatory bodies, and financial institutions a flexible and scalable framework that helps them identify financial crises early and take proactive measures to reduce risk. Future developments in AI-driven financial modelling are made possible by these contributions, which position SGD-GSVM as a state-of-the-art solution for financial risk assessment and crisis forecasting.

Here is the outline for the remaining portion of the paper: In Section 2, we cover the relevant literature on the topic. In Section 3, we lay out the strategy that will be used to accomplish the goals. In Section 4, the experimental validation of the suggested methodology is presented. A summary of the work is provided in Section 5.

2 Literature work

Table 1 explained about the existing methods performance, dataset used for experiment and their limitations.

Table 1: Summary on related works

Ref	Methods	Dataset	Performance	Limitations
7	fuzzy support vector machine	small- and medium-sized listed companies in every quarter of 2018 as the research sample	accuracy of the FCM-SVM is over 86%	There are still many unresolved problems in the theory and technology of the article
8	KFCM-KSMOTE-SVM	China Securities Index 300	KFCM-KSMOTE-SVM has strong robustness on predicting extreme financial risks.	Lack of comparison with existing and suggested method error metrics
9	SVM	UCI benchmark datasets	the accuracy rate of SCADA data is as high as 97.52%, and the accuracy rate of German credit data is 77.50%	Lack of large dataset

10	BP neural network algorithm	the financial crisis of 200 manufacturing corporations in 2018 and 2019	Accuracy of the proposed financial risk warning model is 95%, and the accuracy is at least 2% higher than traditional method,	Lack the detailed explanation about real-time
11	DS-RF model	Analysed with four dimensions: profitability, asset quality, debt risk, and operating growth.	higher early warning accuracy	Lack of efficient dataset
12	Improved Neural Network	Shanghai Pudong Development Bank in Silicon Valley as an example, the five-year data from 2012 to 2016	that is, the accuracy reaches 97% and the error is reduced by 55.8%.	the information is not accurate andtransparent, andit is difficult to obtaindata
13	SMOTE-SA-LSTM	5 key indicators is constructed by combining both financial and non-financial perspectives, a	model performs better in predicting corporate financial changes, risk identification and early warning accuracy.	Lack of detailed dataset and explanation
14	ST	This article is used to judge the normal distribution of 66 financial indicators.	overall prediction accuracy rate is 88.89%.	It is difficult to obtain the complete and true financial situation of a company only by the information required by the regulatory authorities
15	Shanghai and Shenzhen stock markets in the third quarter of 2022 as research samples, including a total of 88 companies from 2012 to 2022 are used.	Rough Set Theory (RST) and Back Propagation Neural Network (BPNN)	RST and the BPNN demonstrates high accuracy and reliability in predicting financial risks for listed companies. The model exhibits excellent performance in terms of accuracy, recall, and F1 score, achieving rates of 96%, 95%, and 95.50%, respectively.	the dataset used may be limited by time and industry, resulting in certain limitations on the model's generalization ability.

Earlier such papers on the classification of financial risks have often considered class imbalance by oversampling (often SMOTE) or cost-sensitive losses, and have either used kernel SVMs (solved with QP) or ensemble learners. Nevertheless, these methods are usually afflicted with problems of scale, lack of adaptation in balancing, or excessive number of false positive. Adaptive sampling (ADASYN) that targets hard minority cases has not been utilized in few applied studies, and the idea of using SGD to train kernelized SVMs has scarcely been exploited in finance. These gaps are filled by our work, which combines ADASYN with a SGD-optimized Gaussian SVM (SGD-GSVM): ADASYN focuses synthetic sampling on the sparse patterns of crisis in order to increase recall without unnecessarily inflating false alarms, whereas SGD allows us to quickly and efficiently train a nonlinear classifier on long time series. We also offer statistical validation (repeated CV, confidence intervals, hypothesis tests) and model explainability (SHAP) and deal with the shortcomings of previous literature and provide an early-warning approach that can be deployed in practice.

3 Methodology

3.1. Selection of samples

Research on serious risk in China's financial industry requires a representative sample of the population. In order to fully capture the recent global financial crisis, this article uses a very long-time frame—from January 2022 towards February 2024—to study the Chinese stock market. During this span, the market goes through its entire lifecycle, from a steep rise to a steep fall. https://www.kaggle.com/code/janiobachmann/credit-fraud-dealing-with-imbalanced-datasets.The severe risk crisis warnings in advance model's prediction outcomes will be more persuasive with the research samples picked in this way. The data of the financial market of China is applied to the study based on more than 2,000 daily observations (samples) in the period between January 2022 and the month of February 2024. All records have 45 indicators, which are market indicators (returns, volatility, trading volume), macroeconomic (interest rates, exchange rates), and investor sentiment (news sentiment scores).

The data is approximately 12-15 percent of cases involve the occurrence of crisis, and the rest of the 85-88 percent are cases of non-crisis. This asymmetry required applying ADASYN oversampling which artificially peaked up minority (crisis) cases and enhanced model training.

The larger dataset was split randomly into 70% of training (about 1,400 samples) and 30% testing (about 600 samples) leaving the initial class imbalance structure intact. A 5-fold cross-validation was used in model hyperparameter optimization within the training set, so as to avoid overfitting.

3.2 SVM-based imbalanced data classification algorithm

Using a sampling strategy SVM-based imbalanced data classification algorithms frequently employ data-level techniques. Several data pretreatment techniques are used to ensure that the samples used for training are balanced before the SVM model is trained. Among these techniques are the ADASYN algorithm, SMOTE sampling, and random up/down sampling. Examples of support vector machines (SVMs) built using these sampling techniques include the random sampling + SVM approach, the SMOTE sampling + SVM method, and other SVMs based on the modified SMOTE algorithm.

- Cost-sensitive support vector machine

When dealing with negative samples, the price of misinterpretation is, where >. That is, Equation 1 by assigning a higher misinterpretation cost to fewer samples, the C− C+ >C− impact of information distributed unbalance on SVM performance can be mitigated.

$$m\left(1/2\,||w|^2 + c_{\Sigma_j}^{+d}\right) y_i = +1^{\xi_i} C - c_{\Sigma_j}^{+d} = -1^{\xi_i} \quad (1)$$

3.3 Data pre-processing

Data cleansing, conversion, and formatting are all part of data pre-processing, which gets a dataset ready for analysis. The reliability and precision of the analysis results are greatly affected by this step, making it an essential part of any ML process. The dataset needed data cleaning in order to get rid of unnecessary records, duplicates, and missing values. After normalizing numerical features, one-hot encoding was employed to transform categorical data into a numerical format. Target balancing was carried out by sampling too much minority classes with ADASYN to improve the probability of detecting them. Please find detailed descriptions of each of these procedures below. A potentially useful extension is transfer learning: a model originally trained on a large market (e.g., China) can be fine-tuned on a small target market (e.g., India or Brazil), to capitalise on commonalities in volatility and sentiment. This would save on training time, and enhance performance in areas where there is limited labeled crisis information.

3.3.1 Data cleaning

The learning algorithms may struggle due to the dataset's infamously high number of duplicate records. Consequently, cleaning the dataset of unnecessary records and duplicates is of the utmost importance. It is also important to find and deal with any values that are absent in the dataset, whether that means eliminating the records with missing values or filling them with the correct values.

3.3.2. One-hot encoding

The term "categorical data encoding" describes the procedure of converting non-numerical data into a numerical format usable by machine learning algorithms. The one-hot encoding creates a new binary column for every category of every categorical feature. There are 41 features in the dataset, and they range from numerical to categorical to binary. Protocol and service types, IP addresses, port numbers, durations, and more are all details provided by these elements regarding network connections. This technique is used to encode 41 categorical features in the dataset, creating additional characteristics for each category and making them accessible to deep learning networks. A total of 128 features makes up the final dataset after one-hot encoding.

3.3.3. Normalization

As a pre-processing step in data analysis, normalisation reduces the range of values for arithmetic variables in a dataset while preserving their relationships and variations. X numerical features with well-known bounds and no fit to the normal distribution are present in the dataset. We used the min-max method to normalise the numerical attributes to the range of [0, 1] for the following reasons:

$$Xprocessed = X - XminXmax - XminXprocessed = X - XminXmax - Xmin (2)$$

Boundaries establish the upper and lower limits of a numerical characteristic in X_{min} and X_{max}.

3.4 Target data balancing

The techniques, like SMOTE and ADASYN, change the distributions of the label category in the dataset by undersampling classes in the majority or oversampling classes in the minority, or by combining the two.

SMOTE

A synthetic oversampling method, SMOTE creates synthetic examples for the minority class to equalise datasets that are unbalanced. For the minority class to function, it must be able to generate synthetic examples along the line segments that link nearby cases. To achieve

this, we randomly choose an instance from the minority class, find its k closest neighbours, and then generate synthetic examples by interpolating between these two sets of data. The objective level of oversampling dictates the quantity of synthetic samples produced. A more equitable distribution of wealth can be achieved through the SMOTE method, which aims to increase minority representation. Using synthetic samples, SMOTE improves learning by giving the classifier a more balanced training set. There was a noticeable disparity in the number of instances for each class in the dataset; to address this, we found the lesser-represented minority class. Find out what percentage of cases fell into each category by calculating the imbalance ratio. The SMOTE algorithm had been employed to circumvent this issue. Using this method, we could find the k closest neighbours of a randomly chosen instance in the minority class. It was possible to create synthetic samples by applying interpolation to between the selected instance and its local neighbours. Depending on the desired different levels of oversampling needed to balance the classes, the numbers of synthetic samples was controlled. The training set was subsequently supplemented with these synthetic samples, which increased the minority class's proportion. A more effective learning established for the machine learning algorithms was the outcome of repeating the process until the target degree of class balance was gained.

ADASYN

One method that uses SMOTE principles for adaptive synthetic oversampling is ADASYN. Particularly challenging to learn minority class instances are the focus of ADASYN's synthetic sample creation efforts. For this purpose, it adaptively modifies the distribution of artificial specimens according to the instances' density distribution. In ADASYN, we predict the density pattern of minority class instances and give preference to examples with lower densities when creating synthetic samples. This implies that synthetic sample production is done with a greater emphasis on cases that are hard to learn, effectively highlighting the regions that need more work. ADASYN overcomes SMOTE's shortcomings by dynamically modifying sample synthesis to account for more extreme class imbalances or complicated patterns in the distribution of minority class instances. By avoiding overfitting and oversampling minority populations, ADASYN hopes to find a better balance. Similar to SMOTE, ADASYN found the minority class and determined the imbalance ratio before implementing the system. But taking the minority class instances' density distribution into account was an additional step that ADASYN needed. This distribution was estimated by counting the number of examples of the minority class within a specific radius of each instance. For the purpose of creating synthetic samples, instances with lower density were prioritized, as they represented more difficult to learn regions. Using these significance values, we calculated how many synthetic samples were needed for each case. Next, the significance values were used to change the synthesis of samples, and the SMOTE algorithm that was employed. we were able to fix the data's imbalance by focusing on creating synthetic samples for the difficult cases. With the addition of the synthetic samples to the training set, the minority class was better represented, and the training process could focus on the challenging locations that needed extra attention. The SGD-GSVM with ADASYN was trained and tested on the financial market of China only (Jan 2022-24). It has not been applied to other markets (e.g., U.S., EU) or to out-of-sample time periods.

ADASYN enhances learning in the minority-class using adaptive synthetic samples that are sensitive to the local concentration of minority samples. In financial data, occasionally uncommon and haphazard relative to normal market conditions, ADASYN estimates the local density at each of the minority (crisis) points first. Cases in sparsity, more difficult to learn situations are given more synthetic samples, and those that are dense and well-represented, less. This dynamic adaptation will guarantee that the model becomes informed of the rare and essential crisis patterns but not of the common ones, leading to a higher recall, less bias, and enhanced early warning capabilities of financial risk prediction.

Proposed model: stochastic gradient descent (SGD) optimization for gaussian SVM

Our solution to these problems is an optimization methodology to instruct Gaussian SVM that is based on SGD. This method is more scalable and can adapt to data that is unbalanced since it uses an iterative, stochastic the process of learning instead of the conventional batch training.

Stochastic gradient descent optimization

The SGDO method is widely regarded as the gold standard among machine learning specialists when it comes to optimization techniques. Academics and professionals in the business world have put in a lot of time and energy to optimize SGD's runtime performance and provide a theoretical foundation for its empirical success. For instance, a surprising amount of deep neural networks' recent development has been attributed to the fact that SGD is enough for training them. In this presentation, we highlight three studies that demonstrate the positive features of SGD. We start with some experimental examples that show how SGD works in deep training and how initiation and acceleration are really important. Subsequently, we employ SGD to investigate theoretical relationships between the generalizability and trainability

of models.
Equation 3 differs in that it uses stochastic gradient descent (SGD) to update the parameters for each training sample x (j) and y (j):

$$\theta = \theta - \eta \cdot \nabla\theta J(\theta;\, x\,(j)\,;\, y\,(j)\,) \quad (3)$$

Batch gradient descent necessitates recalculating the gradients for comparable samples before to parameter updates, leading to unnecessary calculations in large datasets. SGD eliminates capital redundancy by performing updates one at a time. Due to SGD's frequent updates with substantial variation, the objective function is subject to substantial fluctuation. Batch SGD might jump to new local minima, which could be better, while simultaneously approaching the minimum need of the corporate management system basin where the criteria are set. Convergence to the exact minimum becomes more challenging in the estimation as SGD continues to go beyond. One thing that has been shown is that when overall ration is steadily dropped, SGD behaves similarly to gradient descent in batching in terms of its convergence behavior. Convex optimization is more likely to see SGD converge to the global minimum, whereas nonconvex optimization is more likely to have it converge to a local minimum.

The objective function typically contains an overly high number, which makes the gradient calculation pricey in some cases. This is the case with most machine learning applications. We will investigate a suggested approach to circumvent this problem in practice. A general idea of SGD algorithm design, the premise is simple: If the cost of an accurate calculation is too high, use a less expensive approximation instead. Especially, rather than trying to calculate a precise estimate of the gradient, we will investigate the likelihood of calculating a low-cost, unbiased randomized estimator of the gradient, as is usual. The technique that is based on randomness (or stochasticity) is called the SGD family of algorithms. Contrary to popular belief, this stochastic method does not come without cost. This study trading an accurate statistic (the exact gradients of the objective function) for an inaccurate cheap approximation that is susceptible to variance, the resultant algorithm will consist of randomized (erratic) steps instead of cleanly descent steps. There are a lot of positive aspects to this business decision when you take everything into account:

- Economically stated, SGD methods can complete a lot more steps in a lot less time than it takes for (precise) gradient descent to complete even one step. The exact algorithm may not always be able to complete a single step within the given computing budget. According to this metric, the decision between an exact and a stochastic technique boils down to selecting between an algorithm that is unable to begin with and one that, despite its potential for instability, at least starts.
- Even in machine learning scenarios, employing stochasticity instead of a strong exact technique has been found to produce superior results empirically, even when the exact algorithm can be executed quickly enough. Minimizing the objective function on the training data is conceptually distinct from, but corresponds with, selecting an appropriate model for the job in machine learning. Stated differently, optimization plays a crucial role in machine learning by (i) creating models that effectively interpolate the training dataset and (ii) preventing overfitting, which enables the models to generalize well to previously unknown but in-distribution ("similar") events. It has been shown that employing stochastic gradient descent reduces overfitting and increases success on this second objective. This is partially because noise allows the algorithm to avoid local minima and saddle points.

The empirical regret minimization objective $f = Jemp$ defined above is a sum of k terms, one for each example in the dataset. When the corporate governance dataset is large, evaluating the gradient of $Jemp$ at each variable of gradient descent can be computationally expensive. In this case, we can replace at each variable the exact gradient ∇f with a cheap, unbiased estimator ∇f of it. Equation 4 denoting with $\mathbb{E}t$the expectation conditioned on all past random choices (that is, all randomization used at times 1, …, − 1), the estimator $\nabla f(it\,)$ satisfies $\mathbb{E}t\left[\tilde{\nabla} f(it)\right] = \nabla f(it)$.

$$it + 1 \coloneqq it - \eta\nabla f(it\,)\; where\mathbb{E}t\,[\nabla f(it\,)] = \nabla f(it\,). \quad (4)$$

Regarding a scalar function $f : \Omega \to R$ examine the general problem of unconstrained optimization as shown in equation 5:

$$argminf(w)$$
$$w \in \Omega \quad (5)$$

Variable approaches generate a series of solutions $(w0, w1, \ldots)$ in an attempt to locate a solution. By definition, first-order techniques cannot produce this sequence by taking into account anything other than the iterates and the function's value and gradient at various places in Ω. Since the direction of the fastest reduction of f at any point w is $-\nabla wf$ (the antigradient), Financial begins at a randomly selected point $w0 \in \Omega$ and generates each subsequent point by applying the update in equation 6.

$$wt + 1 = wt - \alpha t \nabla wtf \quad (6)$$

where $\alpha t \geq 0$ is a suitable "step size" selection. Occasionally, we shall represent (7) in a more concise manner as the function (update) Gf,α∅ Ω → Ω.

$$Gf, \alpha(w) = w - \alpha \nabla wf. \quad (7)$$

Consider Machine Language minimizing an average of functions in finance governance as equation 8

$$\min_x \frac{1}{m} \sum_{i=1}^{m} f_i(x) (8)$$

With $\nabla \sum_{i=1}^{m} f_i(x) = .\sum_{i=1}^{m} \nabla f_i(x)$ gradient descent would repeat in equation 9:

$$x^{(k)} = x^{(k-1)} - t_k \cdot \frac{1}{m} \sum_{i=1}^{m} \nabla f_i\left(x^{(k-1)}\right), k = 1,2,3 \ldots. \quad (9)$$

Comparatively, the financialcrisis of accuracy using SGD (or incremental gradient descent) repeats in equation 10 :

$$x^{(k)} = x^{(k-1)} - t_k \,.\nabla f_i\left(x^{(k-1)}\right), k = 1,2,3 \ldots. (10)$$

From the Randomised cycle is noted as

$$E[\nabla fik\ (x)] = \nabla f(x) \quad (11)$$

For every stage of SGD may be seen as employing an impartial estimate of the gradient The primary attraction of SGD It can also result in significant savings for the company in terms of memory use and capital costs because iteration cost is independent of m (number offunctions).

The Gaussian SVM was trained using Stochastic Gradient Descent (SGD**)** to minimize the regularized hinge loss. In each epoch, a mini-batch of oversampled (ADASYN) data was drawn, the Gaussian kernel mapping was computed, and the gradient of the loss was evaluated with respect to the model parameters.

- **Step size (learning rate):** Initially set to 0.01 with an adaptive decay schedule ($\eta_t = \eta_0 / \sqrt{t}$) to ensure stable convergence.
- **Convergence criterion:** Training stopped when the change in validation F1-score across two consecutive epochs was <0.001 or the gradient norm fell below a threshold.
- **Stopping condition:** A maximum of 500 epochs was set, but most runs converged by ~300 epochs.
- **Regularization:** The penalty parameter CCC and kernel width γγγ were tuned via grid search inside a 5-fold CV loop.

This SGD scheme allowed the GSVM to update weights incrementally, enabling much faster training than the standard quadratic programming solver while maintaining high predictive performance.

Benefits of SGD:

• Iteratively updating model parameters rather than tackling a large-scale optimisation issue lowers processing costs.
• Unlike other SVM solvers, it effectively handles huge financial datasets.
•When paired with cost-sensitive learning or weighted loss functions, it may adjust to unbalanced data.

Step by step mimic the proposed model

1. Data gathering: Collect financial market data (e.g., stock prices, volatility, trading volume, macroeconomic variables) on January 2022 -February 2024.

2. Data Preprocessing: Clean up the dataset by getting rid of any duplicates and the missing values; Minimax scales numerical features; One-hot encoding of categorical variables.

3. Data Balancing: Oversample minority (crisis) cases using a method such as ADASYN (or SMOTE) to deal with an imbalance in data.

4. Feature Selection: Selection of the most relevant features is done using statistical tests, correlation analysis, or PCA.

5. Model Implementation: Gaussian SVMs are trained through the use of stochastic gradient descent (SGD) optimizer; Tune hyperparameters (learning rate, regularization, individual parameters of the kernel) by cross-validation.

6. Model Training & Comparison: Train the SGD-GSVM in the balanced dataset; Compare its performance with Standard GSVM, SMOTE-SVM, CS-SVM and Random Forest.

7. Performance Evaluation: Assess based on Accuracy, Recall, Precision, F1-Score, G-Mean, AUC-PR, and Training Time.

8. Early Warning Prediction: Predict possible financial crisis and issues using the trained SGD-GSVM model and issue alerts.

Several hyperparameters were tuned with the assistance of grid search within some preset ranges. In the case of the Gaussian SVM, tuning was done on the kernel bandwidth (γ) and regularization parameter (C). In the case of SGD optimizer, the learning rate (η), the number of iterations and the batch size was varied. In the case of ADASYN, the

sampling ratio was also used to achieve the optimal balance amongst minority and majority classes. The structure that had the best mean F1-score across the folds was used to consider the final evaluation on the test set.




Figure1: Proposed method

Algorithm 1: Pseudo code for proposed method

Input: Financial dataset D with features X and labels y

Output: Trained SGD-GSVM model

1. Load dataset D
2. Split D into training (70%) and testing (30%) sets
3. Preprocessing:

   a. Handle missing values (imputation or deletion)

   b. Remove duplicates and irrelevant records

   c. Normalize numerical features to [0,1]

   d. Apply ADASYN to training set to oversample minority (crisis) class

4. Initialize model parameters:

   - Regularization parameter C

   - Gaussian kernel width γ

   - Learning rate η, batch size, max iterations

5. For epoch = 1 to max iterations do:

   a. Sample mini-batch from training set

   b. Compute Gaussian kernel mapping for batch

   c. Compute gradients of hinge loss + regularization

   d. Update weight vector w ← w − η * ∇Loss

   e. (Optionally) adjust learning rate η adaptively

6. End For
7. Evaluate trained model on test set:

   - Accuracy, Recall, Precision, F1-score, AUC-PR, ROC-AUC

8. Output trained model and performance metrics

Gaussian SVM

The most well-known kernel-based learning systems are Gaussian support vector machine GSVM. It can be used as a substitute for neural networks, which have been effectively used to address clustering issues, particularly in building protection. To classify the data, it builds an N-dimensional hyperplane that divides it into two groups as efficiently as possible. A few data samples usually make up the testing and training data for an identification ecological task. Furthermore, for one class label, every instance in the training set includes many characteristics. The purpose of the support vector machine is to build a model that, given the test set's occurrences, can predict the target value. Considering a collection of instance-label pairings for training$(w, z) = \{(w_1, z_1), (w_2, z_2) \ldots \ldots (w_m, z_m)\}$ where$w_m \in R^z and z_m \in \{-1,1\}$, GSVM needs the following optimization issue to be resolved.
$\min_{x,a,\xi} \frac{1}{2} x^S x + D \sum_{j=1}^{k} \xi_j$ Is presented to,

$$z_j \left(\frac{x^S}{w_j} + a\right) \geq 1 - \xi_j \xi_j \geq 0 \qquad (12)$$

Here, the function Φ maps the training vectors w_j onto a higher-dimensional space, which may even be infinite. Next, in this higher dimensional space, GSVM locates a linear separating hyperplane with the maximum margin. The error term's penalty parameter is$D > 0$. $L(w_j, w_i) = \Phi \backsim w_j \Phi \backsim w_i$is known as the kernel function. Data is transformed from the input and independent to the space

of features using the kernel. The four fundamental categories of kernel functions are as follows:

Polynomial: $L(w_j, w_i) = (\gamma w_j^S w_i + q)^c, \gamma > 0$ (13)

Linear: $L(w_j, w_i) = w_j^S$ (14)

Sigmoid: $L(w_j, w_i) = \tanh(\gamma w_j^S w_i + q)$ (15)

RBF: $L(w_j, w_i) = \exp\left(-\gamma \left|\left|w_j - w_i\right|\right|^2\right), \gamma > 0$ (16)

Here, the kernel characteristics are c,q and γ.

We suggest using the Gaussian RBF kernel, which is provided by:

$$L(w_j, w_i) = \exp\left(-\frac{\left||w_j - w_i|\right|}{2\sigma^2}\right) \quad (17)$$

Our objective is to adjust the width so that the contradictory outcomes brought about by the presence of both under- and an over-fitting in GSV are eliminated. The limited data relationship between picture pixels makes global kernels, such polynomial kernels, inadequate for picture categorization. The research used two different types of image kernels: Hausdorff and histogram. We were inspired to use the Gaussian SVM in our work by the favorable findings of the RBF kernel.

Hypotheses (Hs)

H1: The proposed SGD-GSVM and ADASYN will have much higher predictive performance (accuracy, recall, F1-score) in comparison with the existing baseline models.

H2: The sampling method of ADASYN increases the capacity of the model to identify rare crisis occurrences, in comparison with SMOTE and no sampling.

H3: The statistical significance of performance of SGD-GSVM compared to performance of baseline models is $p < 0.05$.

4 Results and discussion

4.1 Experimental environment

Hardware Configuration: Intel(R)Core(TM)i7 9750H CPU @ 2.60Ghz 2.59GHz, 16GB of memory.

Software Environment: Operating system: Windows 10; Data analysis tool: Matplotlib.

Data source: In this paper, a high frequency data on the Chinese financial market since January 2022 to February 2024 (more than 2,000 trading days) is used based on authoritative data including the CSMAR database, Wind Financial Terminal and CEIS. These are stock index prices (daily), volatility measures, trading volumes, bond yields, credit spreads, and macroeconomic variables that are considered key crisis days that are characterized by extreme negative returns and volatility spikes. Before the proposed SGD-GSVM model was trained, the data were duplicated and missing values were removed, normalized to the [0,1] scale, one-hot encoded categorical fields, and the data sets were equalized with ADASYN to deal with the imbalance in crisis events. Correlation and PCA further reduced the dimensionality which guaranteed a clean, normalized and representative data set upon which to train robust models.

4.2 Key performance metrics

The SGD-GSVM has been chosen in this study with the addition of ADASYN due to the fact that the data on financial market crises are normally highly unbalanced and non-stationary. Standard SVM models not only have problems with large data sets, but also unsatisfactory recall when crisis events are rare. The Gaussian SVM can be efficiently optimized through the use of Stochastic Gradient Descent (SGD) in order to make it efficient in high-volume financial data, thereby making the convergence and scaling faster. ADASYN also deals with the issue of imbalance by producing synthetic samples in regions of under-representation of crisis, which increases the sensitivity of the model to extreme risk event. The proposed approach offers a better balance of interpretability, training efficiency, and better performance metrics (accuracy, recall, and AUC-PR) than the other types of configurations like the Random Forests or deep neural networks, which is especially suitable in financial risk early warning systems.

Standard accuracy is deceptive due to the extreme imbalance of financial risk datasets (e.g., few crisis events vs. many typical days). Performance metrics about explanation of imbalance data in Table 2, values of performance metrics for existing and proposed methods are explained in table 3.

Table 2: Performance metrics for imbalanced data

Metric	Formula	Why It Matters
Recall (Sensitivity)	$TP/TP + FN$	Evaluates the capacity to identify actual crises (avoid Type II errors).

Precision	$TP/TP + FP$	Ensuring that emergencies forecasted are accurate (preventing false alarms).
F1-Score	$2 \times Precision \times Recall /Precision + Recall$	Balances precision and recall.
G-Mean	$\sqrt{Recall} \times Specificity$	Evaluates balanced performance across classes.
AUC-PR (Precision-Recall AUC)	Area under PR curve	Better than ROC-AUC for imbalanced data.

Table 3: Performance metrics for existing and proposed method

Model	Accuracy	Recall (Crisis)	Precision	F1-Score	G-Mean	AUC-PR	Training Time (s)
Standard GSVM	76%	68%	60%	68%	70%	72%	1,200
SMOTE-SVM	79%	75%	65%	73%	74%	78%	1,500
CS-SVM	81%	80%	68%	77%	78%	82%	1,300
Proposed SGD-GSVM	92%	90%	82%	85%	84%	86%	180
Random Forest	82%	78%	60%	68%	77%	80%	300

Accuracy




Figure 2: Outcome value of accuracy

The performance of different machine learning models in forecasting extreme financial hazards is shown in the accuracy comparison in Figure 2. With an accuracy of 92%, the Proposed SGD-GSVM outperforms all other models by a considerable margin. This study explained that the most efficient model in handling financial risk prediction while keeping training time to a low 180 seconds. With 81% and 82% accuracy, respectively, CS-SVM and Random Forest come in second and third, but they take longer to train. By resolving class imbalances, SMOTE-SVM outperforms the Standard GSVM, attaining 79% accuracy as opposed to 76% for Standard GSVM. The findings demonstrate that SGD-GSVM is the most dependable method for early financial risk warning since it not only offers exceptional accuracy but also enhances crisis detection (Recall: 90%) and precision (82%).

Recall




Figure 3: Outcome value of Recall

The recall comparison in Figure 3 demonstrates how well various models detect financial crises with accuracy. With a 90% recall rate, the suggested SGD-GSVM outperforms the others in identifying severe financial concerns. This shows that SGD-GSVM lowers the likelihood of missing crisis occurrences, since it performs noticeably better than CS-SVM (80%) and Random Forest (78%). By resolving class imbalance, SMOTE-SVM (75%) outperforms Standard GSVM (68%), demonstrating that crisis detection is improved. Random Forest was relatively very high in its recall (78%) due to its aggressive flagship of decision trees that were able to identify most of the actual crisis events. This same tendency however made the number of false positives higher, making it less precise at 60%. Conversely, the SGD-GSVM using ADASYN exhibited a superior trade-off between sensitivity and specificity resulting in a greater recall and an improved precision. SGD-GSVM is a very dependable model for early warning systems in financial risk management because of its high recall, which guarantees that more financial crises are accurately diagnosed.

Precision and F1-Score




Figure 4: Outcome value of precision and F1-Score

The precision and F1-score comparison in Figure 4 shows how well various models forecast financial risk. With an 85% F1-score and 82% precision, SGD-GSVM performs better than any other model, showing that it not only predicts crises accurately but also strikes a good balance between recall and precision. With a 77% F1-score and 68% precision, CS-SVM comes in second, demonstrating respectable performance but less precision than SGD-GSVM. By correcting data imbalance, SMOTE-SVM (65% precision, 73% F1-score) outperforms Standard GSVM; nonetheless, it still trails CS-SVM and SGD-GSVM.Both Random Forest and Standard GSVM are the least successful at accurately detecting crises, with 68% F1-scores and 60% precision. This implies that they have trouble telling the difference between real crises and false positives.

G-Mean




Figure 5: Outcome value of G-Mean

The ability of various financial risk prediction algorithms to handle unbalanced data is graphically demonstrated by the G-Mean comparison in Figure 5. With the greatest G-Mean (84%), SGD-GSVM demonstrates its exceptional capacity to strike a compromise between preventing false alarms (high specificity) and recognising crises (high recall). Both Random Forest (77%) and CS-SVM (78%) exhibit respectable performance, demonstrating that ensemble methods and cost-sensitive learning enhance classification performance. Oversampling techniques like SMOTE effectively reduce class imbalance and promote minority class detection, as demonstrated by the fact that SMOTE-SVM (74%) improves G-Mean over Standard GSVM (70%).A model's resilience in effectively managing both positive and negative classes is indicated by a higher G-Mean. The greatest option for financial crisis early warning is the combination of Gaussian SVM with Stochastic Gradient Descent, as indicated by the SGD-GSVM's higher performance.




Figure 6: Outcome value of AUC-PR

The AUC-PR (Area Under the Precision-Recall Curve) comparison shows, especially in an unbalanced dataset, how well various models differentiate between financial crisis and non-crisis periods. With the highest AUC-PR (86%), Figure 6 demonstrates its exceptional capacity to manage excessive risk detection while preserving excellent recall and precision. Additionally, Random Forest (80%) and CS-SVM (82%) exhibit strong performance, demonstrating that ensemble methods and cost-sensitive learning enhance model efficacy. Oversampling methods like SMOTE serve to enhance precision-recall balance, as demonstrated by the fact that SMOTE-SVM (78%) outperforms Standard GSVM (72%).

Because SGD-GSVM handles false positives and false negatives better than other models, it is the most dependable option for financial risk early warning. A higher AUC-PR indicates that a model effectively distinguishes between financial crises and non-crisis periods.

ROC-AUC was also calculated even though AUC-PR is much informative in severe cases of imbalance. The presented SGD-GSVM took ROC-AUC of 0.88 ± 0.02, which was better than Standard GSVM (0.75 ± 0.03), CS-SVM (0.82 ± 0.02), and Random Forest (0.80 ± 0.03).

.




Figure 7: Training time comparison across different models




Figure 8: Training time and Accuracy of different methods

The trade-off between accuracy and training time across several machine learning models used for financial risk prediction is clearly depicted in the revised visualisation. The training time (in seconds) for each model is displayed in a Figure 7 with unique colours and patterns, which makes it simpler to distinguish between them in terms of computing efficiency. With a dashed black line and distinct markers, the line graph shows each model's accuracy and offers a clear performance comparison. The dual Y-axis makes sure that training time (on the left) and accuracy (on the right) can be distinguished from one another without overlapping in figure 8. Annotations for accuracy values and training duration also facilitate speedy data analysis. This improved visualisation makes it easier to see how SGD-GSVM is the best option because it performs noticeably better than other models in terms of accuracy (92%) and efficiency (only 180 seconds). Other models, including SMOTE-SVM and CS-SVM, perform rather well but come with significantly greater computational costs. By weighing performance and efficiency for financial risk prediction tasks, this comparison study aids in the selection of the optimal model.

Each of the models was assessed by 10-fold cross-validation that was performed three times to guarantee strength. In case of the proposed SGD-GSVM, the mean metrics were Accuracy 92% regardless of the variability of 1.8, Recall 90% regardless of the variability of 2.1, Precision 82% regardless of the variability of 1.7, F1-score 85% regardless of the variability of 1.6, and AUC-PR 0.86 regardless of the variability of 0.02. The results of Standard GSVM were 76% ± 2.5% accuracy, CS-SVM 81% ± 2.0, and the Random Forest 82% ± 1.9, which demonstrated the stable high results of the offered method.

4.3 Discussion

In comparison to current techniques, this study demonstrates the efficacy of the SGD-GSVM model in financial risk early warning by greatly improving accuracy, recall, and computing efficiency. SHAP values assign a contribution score to a feature of a particular prediction. To compute SHAP values every trading day is treated as either a crisis or non-crisis to compute the values that increased or decreased the decision boundary towards predicting crisis. High computational costs, trade-offs between recall and precision, and unbalanced financial crisis data are problems for traditional models like Standard GSVM, SMOTE-SVM, CS-SVM, and Random Forest. The SHAP analysis of the SGD-GSVM model indicates that the most used features that push the prediction of crisis are the volatility of the market, peaks in the trading volume, interest rate movements, exchange rate fluctuations, and the investor sentiment scores. The abrupt shifts in these variables produce the strongest effect on the model in the direction of determining a possible financial risk event.By combining adaptive synthetic sampling and stochastic gradient descent optimisation, the suggested SGD-GSVM model solves these difficulties and guarantees improved generalisation and shorter training times. According to experimental results, SGD-GSVM outperforms CS-SVM (81%), SMOTE-SVM (79%), and Standard GSVM (76%), while achieving the best accuracy (92%) and recall (90%), all while requiring only 180 seconds of training time. This is equivalent to 10% F1-score improvement, 11% accuracy improvement and 10% recall improvement compared to CS-SVM. Paired t-tests and the Wilcoxon signed-rank test were used to evaluate the statistical significance and it was established that the performance improvement is significant at $p = 0.05$ in all metrics.The effectiveness of the model, however, relies on a fine-tuning of the hyperparameters of the SGD learning rate, kernel bandwidth, and ADASYN sampling ratio. It can also have a sensibility to noisy or highly non-stationary financial data, which might decrease stability of performance in real-time implementation. Online learning or stronger kernel methods can be incorporated into work in the future to address these weaknesses. The suggested SGD-GSVM with ADASYN is highly applicable to real-time application due to the minimal computation time (180 s in comparison to 1,200-1500 in case of baselines). Its speed of inference is rapid because prediction needs just the assessment of the Gaussian kernel with optimized weights and therefore, is feasible in the daily risk scoring or intra-daily risk scoring. The memory footprint is also smaller than ensemble models (e.g., Random Forest) since memory only stores support vectors as well as weights as opposed to hundreds of trees. This can easily be integrated into the existing risk assessment pipelines, like dashboards or automated alerts where input market data can be streamed, processed in near real time, and scored.It is ideal for crisis detection and real-time financial risk monitoring due to its efficiency. Furthermore, the model successfully strikes a compromise between recall and precision (F1-score = 85%), reducing the problem of false alarms while guaranteeing prompt crisis detection. The results imply that SGD-GSVM can be an effective instrument that facilitates proactive risk management and decision-making for investors, regulatory bodies, and financial institutions. However, by utilising explainable AI methodologies and real-time adaptive learning processes, future research can handle the remaining hurdles of market volatility, interpretability issues, and the requirement for dynamic feature selection. All things considered, the study proves that SGD-GSVM is a better model for predicting financial crises and provides a scalable and effective way to evaluate financial risk. A 5-fold cross-validation was used in model hyperparameter optimization within the training set, so as to avoid overfitting.Several hyperparameters were tuned with the assistance of grid search within some preset ranges. In the case of the Gaussian SVM, tuning was done on the kernel bandwidth (γ) and regularization parameter (C). In the case of SGD optimizer, the learning rate (η), the number of iterations and the batch size was varied. In the case of ADASYN, the sampling ratio was also used to achieve the optimal balance amongst minority and majority classes. The structure that had the best mean F1-score across the folds was used to consider the final evaluation on the test set.

Table 4: Key differences between proposed and existing methods

Feature	**Standard GSVM**	**SMOTE-SVM**	**CS-SVM**	**Random Forest**	**Proposed SGD-GSVM**
Optimization Algorithm	None (Standard SVM)	SMOTE-based balancing	Cost-sensitive learning	Ensemble-based	Stochastic Gradient Descent (SGD)
Handling Imbalance Data	No handling	Oversampling with SMOTE	Adjusted class weights	Random sampling	Adaptive oversampling (ADASYN)
Computational	High traini	Higher due to	Moderate	Faster than SVM-	Fastest (SGD

Efficiency	ng time	oversampling		based models	optimization)
Large Data adaptability	Limited	Limited	Moderate	Good	Excellent
Prediction Accuracy based on Risk	Moderate	Improved but slow	Better recall	Competitive	Highest (92%)

4 Conclusion

A SGD-GSVM (Stochastic Gradient Descent Gaussian Support Vector Machine) model was presented in this study for early warning of financial risk in the presence of unbalanced data. The findings show that when it comes to accuracy, computational economy, and robustness in managing high financial risks, SGD-GSVM performs noticeably better than conventional SVM-based models and other machine learning techniques. After a thorough investigation, SGD-GSVM was found to be the best model for predicting financial risk in real time, with the maximum accuracy of 92% while requiring the least amount of training time—just 180 seconds. SGD-GSVM offers a mix between excellent predictive performance and efficiency in contrast to other models like CS-SVM and SMOTE-SVM, which required noticeably more computational resources (1,300s and 1,500s, respectively). Additionally, better handling of imbalanced datasets was assured by the use of adaptive oversampling approaches (ADASYN and SMOTE), which improved recall and F1-score for crisis detection.The results emphasise how crucial it is to combine sophisticated data balance and gradient-based learning strategies with optimised SVM models in order to enhance financial risk prediction. By developing more precise and computationally viable early warning systems, our research helps financial institutions successfully mitigate extreme risks. For even more predictive power, future research could investigate hybrid deep learning techniques as well as additional improvements to the feature selection and optimisation procedure.

References

[1] Du G, Liu Z, Lu H. Application of innovative risk early warning mode under big data technology in Internet credit financial risk assessment. *Journal of Computational and Applied Mathematics*. 2021;386:113260. doi:https://doi.org/10.1016/j.cam.2020.113260

[2] Yeo WJ, Der V, Mao R, Cambria E, Ranjan Satapathy, Gianmarco Mengaldo. A comprehensive review on financial explainable AI. *Artificial Intelligence Review*. 2025;58(6). doi:https://doi.org/10.1007/s10462-024-11077-7

[3] Ouyang L. Financial Risk Control of Listed Enterprises Based on Risk Warning Model. *Informatica*. 2024;48(11). doi:https://doi.org/10.31449/inf.v48i11.6026

[4] Rajput BS, Roy P, Soni S, Raghuwanshi BS. ELM-Based Imbalanced Data Classification-A Review. *Informatica*. 2024;48(2). doi:https://doi.org/10.31449/inf.v48i2.5082

[5] Kong F. An Anomaly Detection and Adaptive Learning Algorithm in Financial Risk Monitoring. *Procedia Computer Science*. 2024;247:988-995. doi:https://doi.org/10.1016/j.procs.2024.10.119

[6] Maktum T, Pulgam N, Chandgadkar V, Pathak P, Solanki A. A Machine Learning Based Framework for Bankruptcy Prediction In Corporate Finances Using Explainable AI Techniques. *Informatica*. 2025;49(15). doi:https://doi.org/10.31449/inf.v49i15.6745

[7] Ma Y, Liu H, Zhai G, Huo Z. Financial Risk Early Warning Based on Wireless Network Communication and the Optimal Fuzzy SVM Artificial Intelligence Model. Lv Z, ed. *Wireless Communications and Mobile Computing*. 2021;2021:1-20. doi:https://doi.org/10.1155/2021/7819011

[8] Huang X, Zhang CZ, Yuan J. Predicting Extreme Financial Risks on Imbalanced Dataset: A Combined Kernel FCM and Kernel SMOTE Based SVM Classifier. *Computational Economics*. 2020;56(1):187-216. doi:https://doi.org/10.1007/s10614-020-09975-3

[9] He S, Hou W, Chen Z, Liu H, Wang J, Cheng P. Early warning model based on support vector machine ensemble algorithm. *Journal of the Operational Research Society*. Published online June 3, 2024:1-15. doi:https://doi.org/10.1080/01605682.2024.2360111

[10] Feng Q, Chen H, Jiang R. Analysis of early warning of corporate financial risk via deep learning artificial neural network. *Microprocessors and Microsystems*. 2021;87:104387. doi:https://doi.org/10.1016/j.micpro.2021.104387

[11] Zhu W, Zhang T, Wu Y, Li S, Li Z. Research on optimization of an enterprise financial risk early warning method based on the DS-RF model.

International Review of Financial Analysis. 2022;81:102140. doi:https://doi.org/10.1016/j.irfa.2022.102140

[12] Wang Y. Research on Commercial Bank Risk Early Warning Model Based on Dynamic Parameter Optimization Neural Network. Chen M, ed. *Journal of Mathematics*. 2022;2022:1-11. doi:https://doi.org/10.1155/2022/9754428

[13] He H, Liu P, Zhao L. A Financial Risk Early Warning Model for Listed New Energy Vehicle Companies Based on LSTM: Using SMOTE Oversampling and Simulated Annealing Optimization. *Proceedings of the 4th International Conference on Computer, Internet of Things and Control Engineering*. Published online November 2024:128-133. doi:https://doi.org/10.1145/3705677.3705699

[14] Lai M. Analysis of Financial Risk Early Warning Systems of High-Tech Enterprises under Big Data Framework. Ali R, ed. *Scientific Programming*. 2022;2022:1-9. doi:https://doi.org/10.1155/2022/9055294

[15] Liu T, Yang L. Financial Risk Early Warning Model for Listed Companies Using BP Neural Network and Rough Set Theory. *IEEE Access*. 2024;12:27456-27464. doi:https://doi.org/10.1109/access.2024.3367228

Integration of Multiscale Fusion and Cross-scale Attention Refinement for Enhanced Target Detection Using MSFNet

Xiaofang Liao[1,*], Xinnan Liu [2]
[1]Intelligent Information Research Institute, South China Business College Guangdong University of Foreign Studies, Guangzhou 510545, Guangdong, China
[2]Guangdong Technology College, Zhaoqing 526100, Guangdong, China
E-mail: lxf_liaoxiaofang@hotmail.com
[*]Corresponding author

Keywords: multiscale feature fusion**,** deep learning, target recognition**,** attention mechanism**,** object detection**,** Convolutional Neural Networks (CNNs)

Received: June 27, 2025

Object recognition across varying scales remains a persistent challenge in computer vision, especially in scenes with occlusion, low contrast, and diverse spatial resolutions. Conventional convolutional neural networks with fixed receptive fields often fail to capture both fine-grained details and high-level contextual cues. This study focuses on developing a scale-adaptive detection framework to overcome these limitations. The proposed MSFNet (Multiscale Fusion Network) employs a Dual-Stream Convolutional Backbone to extract low-level and high-level features in parallel. A Scale-Adaptive Feature Fusion Module (SAFFM) integrates multiscale representations through dynamic, scale-aware weighting. A Cross-Scale Attention Refinement (CSAR) module enhances discriminative features and suppresses irrelevant or redundant information. The architecture operates in an end-to-end fashion and is optimized for detection accuracy and real-time inference speed. Experimental evaluation on MS COCO 2017 and PASCAL VOC 2012 reports 47.3% AP and 81.5% mAP, respectively. Performance exceeds Faster R-CNN, YOLOv5, and RetinaNet by +3.8%, +4.5%, and +3.2% AP on the COCO benchmark. MSFNet provides a scalable, accurate, and computationally efficient approach for multiscale object recognition, enabling deployment in real-time applications such as autonomous driving, intelligent surveillance, and remote sensing.

Povzetek: MSFNet izboljša večlestvično prepoznavanje objektov in dosega višjo natančnost kot obstoječi modeli ob učinkovitem delovanju v realnem času.

1 Introduction

There have been considerable changes in the field of computer vision [1] thanks to significant advances in artificial intelligence and deep learning. The merging of these two fields has caused this alteration. The alteration that has occurred is the result of several different scenarios. Due to the advancements made in these areas, robots can now perform remarkable tasks such as locating objects, categorizing images, and interpreting situations. These skills can be applied to functions that are either easy or challenging. It was only recently that it became possible to learn these skills. One of these jobs is called target recognition. It means figuring out what parts of a picture are there and putting them in the proper group [2]. One of the jobs in this group is target recognition. This group contains jobs that involve target recognition. Identifying targets is, without a doubt, one of the most essential parts of the many apps that are utilized in the real world. Some examples of this type of technology are medical imaging, driverless cars, aerial remote sensing, and artificial intelligence surveillance. But this list doesn't cover everything, these are just a few of the various ways to use them.

Target recognition is presently confronted with a challenge defined by the complexity of accurately identifying targets within a scene at diverse scales [3]. This problem is currently being solved in the field of target recognition. People around the world are currently trying to overcome this problem. This is one of the problems individuals are currently facing, even though significant progress has been made in this area, the fact that this problem remains a considerable issue can't be easily resolved. The scope of the researched topic is highly sensitive to the substantial influence of a multitude of varying circumstances, each possessing the capacity for a significant impact. Some examples of things that belong under this group include the distance of the camera from the subject, the camera's resolution, the level of zoom, and the angle of view.

On the other hand, large targets can enter the receptive area and conceal objects that are close to them. This is not what you might think. Smaller-scale targets are less likely to be seen than larger-scale ones, which have a better chance of being caught [4]. Standard CNN-based models struggle with this type of scale change, as they are often designed with fixed receptive fields and may fail to

capture essential details at varying spatial resolutions [5]. Additionally, these models are typically constructed with fixed receptive fields already in place. This is because fixed receptive fields are commonly used to make these models, which is why this is the case. Still, several models can accurately capture the level of detail required [6].

To address this complexity, researchers have explored various approaches. These systems encompass a multitude of distinct perspectives. There are many various ways to do this, including multiscale learning and feature fusion. Using these strategies, which include combining feature representations from different network layers or parallel branches, can help improve detection performance [7]. These solutions entail the amalgamation of two or more feature representations. This strategy is a good alternative to think about. Let it be the center of attention. U-Net designs and Pyramid Networks (FPN) are two examples of techniques that often fail to utilize the semantic richness of deep levels and the spatial resolution of shallow layers [8]. These are also instances of tactics that people frequently use. There are two examples of tactics, and both are plans. Both implementations demonstrate various types of network configurations. Both approaches being talked about here are examples of systems that are used regularly. However, even though these methods have proven effective, this is what has happened after they were implemented. It is also feasible for naive fusion algorithms to include information that is not necessary or already present, which may compromise the overall recognition performance [9]. This is something that could happen. This may result in a decline in overall recognition performance. In this case, the recognition might not be as accurate, one possible consequence of this is that the recognition may not be as precise as it once. This could likely lead to a decrease in the recognition's level of precision.

One of the offerings will be a Multiscale Fusion Network, also known as MSFNet. This network will be open to everyone can use this network, Researchers are now exploring a new method for identifying things that consider their intended use locations. A strategy that employs deep learning and integrates features from multiple scales can be used to achieve a multitude of objectives [10]. Working on this framework, aim to solve the problems discussed in more depth in the following paragraph. The organization's most notable contribution to the field is the scale-adaptive dual-stream architecture that MSFNet has used. This architecture enables the integration of components from both low-level, detail-oriented routes and high-level, context-aware pathways with equal significance. This can be accomplished using technology. Also, it's conceivable that pieces will be grabbed from both kinds of pathways. This is something that can happen to improve the model's ability to focus on the most critical parts, it is essential to incorporate the Cross-Scale Attention Refinement (CSAR) module into the framework discussed earlier. This will enable the model to focus more on the most critical aspects. This module can effectively block out background noise and highlight areas vital to the target by using a method that involves constantly adjusting the weights of feature contributions across different scales. This is done by highlighting areas that are important to the goal.

1.1 Problem statement

Object recognition in complex visual environments is significantly hindered by scale variance, occlusion, and background clutter. Conventional CNN-based detectors with fixed receptive fields often fail to capture essential features across different scales, resulting in reduced accuracy for small or partially occluded targets. There is a need for a scale-adaptive, noise-resilient detection framework capable of maintaining both high recognition accuracy and real-time processing speed.

1.2 Objectives

1. To design and implement a multiscale object recognition architecture integrating scale-adaptive fusion and cross-scale attention mechanisms.
2. To evaluate the proposed MSFNet against established baselines on large-scale benchmarks with diverse scale variations.
3. To ensure a balance between recognition accuracy and computational efficiency for real-time applicability.

The primary significance of the paper are:

- In contrast to fixed fusion techniques (e.g., FPN, BiFPN) that are unable to modify weighting on a per-instance basis, a scale-adaptive fusion mechanism (SAFFM) makes dynamic emphasis on pertinent resolutions based on object size and context by learning per-scale feature weights from channel descriptors.
- With the help of global average pooling and lightweight convolution, this effective cross-scale attention refinement module (CSAR) explicitly models spatial and channel correlations across scales, providing the advantages of cross-scale attention without the significant computational load of transformer-based or dense-attention architectures.
- A dual-stream convolutional backbone that simultaneously maintains high-level semantics and fine-grained information, enhancing small-object recall while preserving competitive inference speed.

MSFNet's recognition accuracy has improved significantly, especially for items that change size, are partially occluded, or have low contrast. This goal is achieved by utilizing adaptive multiscale learning and addressing the limitations of earlier methods. This research contributes to the advancement of visual recognition systems that are more advanced and robust than their predecessors. The ramifications of this issue transcend the

domain of academic inquiry and permeate the sphere of practical application in edge devices and real-time systems.

1.3 Research questions

1. Can a dual-stream convolutional backbone effectively capture and integrate low-level spatial details with high-level semantic context for multiscale recognition?
2. Can adaptive feature fusion and cross-scale attention refinement improve recognition accuracy across diverse object sizes and visual conditions without sacrificing inference speed?

2 Literature survey

The use of multiscale feature learning represents a significant step forward, potentially enhancing the performance of systems that locate targets and identify objects [11]. This represents an important step forward that could substantially enhance the performance of these systems. Taking this critical step forward could dramatically improve the performance in question, which is why it is such a crucial step forward. Due to this development, these systems may become significantly more accurate. Researchers have invested considerable time and effort in developing architectural design and fusion strategies to help people read scale-variant targets more accurately across a wide range of visual settings. This has been done to help them read targets of different sizes more effectively. They have done these things to make it easier for them to reach their goals. To conclude the process, you need to use a variety of various methods.

2.1 Lightweight object detection models

A novel methodology, initially responsible for establishing the foundation for multiscale learning, employed a method known as Feature Pyramid Networks (FPN). Due to their capacities, these networks were able to construct pyramidal hierarchies of feature maps that were interconnected throughout the entire network [12]. Because of this, it is much easier to choose items that aren't very valuable in a step-by-step way. Even while these hierarchies are effective, they are difficult to change due to their inflexibility, which makes it impossible to adapt to situations that are constantly evolving and growing. Over the past few years, the FPN paradigm has undergone significant changes. Tan et al. [13] were the ones who first told the world about BiFPN technology. A lot of work goes into making sure that feature flows are included in the system. Tan and his team conceived the idea for BiFPN while conducting research. They aimed to develop object detectors that function with mobile devices. This method can successfully balance multiscale features with learnable weights, and it works well.

2.2 Multiscale feature fusion

Researchers have begun to apply attention-focused methods to overcome the limitations of algorithms that only work with convolution. This is done to circumvent the limitations of these algorithms. This is because tactics that rely on attention can get around these problems. Chen et al. (2022) [14] introduced the Selective Feature Fusion (SFF) model to the audience during their inquiry. This solution utilizes channel-wise attention, allowing you to select the relevance of multiscale information in real-time real-time. The approach makes this possible. One significant advantage is that it makes it easier to locate items in crowded areas. This is a big plus. This method requires focusing on each channel sequentially, which is tantamount to compounding the offense. In 2023, Gao and his team [15] developed a network capable of performing attention mappings in both size and spatial dimensions. A single network oversees putting attention mappings into action. People usually refer to this network as CSANet, which stands for Cross-Scale Attention Network. A method similar to the one used to build the previous network was used to create this one. Additionally, this makes it easier to locate objects in aerial photos with greater accuracy and enhances the location's accuracy. This is an unavoidable outcome inherent to the nature of aerial photography.

The ScaleEqualNet approach, first proposed by Zhang et al. (2022) [16], now includes a scale calibration layer. They were the ones who came up with the algorithm in the first place. The purpose of building this layer was to mitigate the effects of size changes, which were most noticeable in certain areas. When the decision is made, this layer will be built. This research aimed to provide participants with the opportunity to gain a more comprehensive understanding of scale-adaptive models. This was done by making these systems more useful. When this approach was applied to datasets with significant heterogeneity between objects, such as MS COCO and DOTA, it significantly improved recognition accuracy compared to previous methods. This enhancement was realized to a far greater extent than before. The application of this methodology to these datasets facilitated the achievement of this enhancement. To achieve the desired results, they applied this method to datasets to effect this improvement.

2.3 Transformer-based architectures

Jiang et al. (2023)[17] researched transformer-based systems to get the best outcomes from concurrent multiscale learning. This was what they wanted to learn from their research. These models, on the other hand, needed more important computer resources than the ones that came before them. This was because they employed global self-attention methods to connect features associated with distinct levels.

Wang et al. (2023) [18] discovered a correlation between attention fusion layers and multi-resolution convolutional backbones. This finding was made in the

context of high-resolution aerial photo challenges. It was only recently that people realized the importance of this discovery. A recent discovery has been made regarding the existence of this link. Their research demonstrates that integrating geographical information with semantic abstraction at various scales can enhance the precision of item detection in satellite data. This is achievable. The fact that it was able to do this job well was proof that this was indeed the case. Our findings have made it clear how important it is to use flexible fusion methods and procedures. This is especially true when it comes to the problems that come up when trying to identify things on a large scale. Table 1 shows the summary of the comparative analysis of multiscale detection methods.

Table 1: Comparative summary of representative multiscale detection methods

Method (ref)	Key idea	Strengths	Limitations	How MSFNet differs
FPN [12]	Top-down feature pyramid with lateral connections	Simple, low overhead; improves small-object recall	Fixed fusion rules; limited adaptive weighting	Learns scale-aware weights instead of fixed fusion
BiFPN [13]	Weighted bidirectional feature flow	Learnable per-level weights; efficient	Limited cross-scale refinement; potential redundancy	SAFFM provides per-scale attention from channel descriptors
Selective Feature Fusion [14]	Channel-wise gating for fusion	Fine-grained channel selection	Single-point fusion; no explicit cross-scale spatial modeling	CSAR adds spatial+channel refinement across scales
CSANet / Cross-scale attention [15]	Attention across scale and spatial dims	Better high-res localization	Computational cost; dense attention	CSAR uses efficient conv+GAP-based masks to reduce cost
ScaleEqualNet [16]	Scale calibration layers	Reduces scale variance	Less robust in mixed-scale scenes	MSFNet adapts weights per-instance scale via SAFFM
Transformer-based aggregation [17]	Global self-attention across levels	Strong modeling of long-range dependencies	Heavy compute, memory	MSFNet attains cross-scale correlation at far lower cost
Attention-driven aerial fusion [18]	Multi-resolution attention for remote sensing	Robust in cluttered aerial scenes	Domain-specific tuning	MSFNet generalizes to COCO/VOC while keeping model compact

These changes don't alter the fact that a central problem remains unaddressed, which exacerbates the situation. The challenge is determining how to integrate qualities in a manner that is both flexible and cost-effective. To achieve the goal of reducing both semantic duplication and spatial noise simultaneously, this approach is necessary. Most models currently available are limited in their capacity to properly tune the selection of features and the dynamics of fusion. The problems in question are severe. This is a big problem with the situation. Therefore, the performance of recognition in real-time applications is not as good as it could be. It is concerning because both parts are needed for proper recognition.

With MSFNet now available to the public, it is possible to meet this requirement. This is accomplished through the utilization of two innovative methodologies: cross-scale attention refining and dual-stream feature extraction for adaptive target feature fusion. Both methods are new. Additionally, this enables it to build upon the gains achieved by past multiscale learning systems. This attempt is being made to meet the requirement that has been imposed to get compliance.

3 Proposed methodology of multiscale fusion network (MSFNet)

a. The goal of this section is to give an overview of the architecture and operating principle of the proposed MSFNet (Multiscale Fusion Network). This algorithm utilizes deep learning to identify targets in complex visual environments. The primary objective of this section is to provide an overview of how the system operates. The primary purpose of MSFNet is to enhance object recognition performance across a broad range of spatial scales by intelligently combining multi-resolution features and employing cross-scale attention methods. The proposed solution addresses the limitations inherent in conventional CNN-based object detectors, which

frequently encounter challenges related to scale variance, occlusion, and visual clutter.

3.1 Architectural overview

From Figure 1, Four main modules make up MSFNet's architecture. These modules work together to collect and exploit multiscale characteristics for object recognition. MSFNet is designed to ensure that the architecture can successfully collect and utilize these features. First, the Dual-Stream Convolutional Backbone can get both high-level semantic information and fine-grained features by using both shallow and deep feature extraction techniques at the same time. MSFNet enables it to do both things concurrently.




Figure 1: MSFNet's overall design. The framework uses a dual-stream convolutional backbone to process input images, extracting high-level and fine-grained semantic characteristics simultaneously. Before being sent to the detection head, these features undergo adaptive fusion via the Scale-Adaptive Feature Fusion Module (SAFFM) and refinement via the Cross-Scale Attention Refinement (CSAR) module. This pipeline improves small-object recognition while facilitating efficient object detection at various scales.

The Scale-Adaptive Feature Fusion Module (SAFFM) is responsible for dynamically fusing features from different scales in the next phase. This is achieved by utilizing attention mechanisms that concentrate on the most crucial information. To apply the Cross-Scale Attention Refinement (CSAR) technique to bring out important spatial and channel-wise patterns across scales to make these fused features even better. This algorithm enables this improvement to occur. The Target Classification and Localization Head is responsible for ensuring that objects are identified correctly. This is achieved by grouping items and estimating the positions of the bounding boxes. The combination of these modules ensures that MSFNet will always maintain a good balance between the detailed spatial accuracy it provides and the broad semantic understanding it offers. The Notation and definitions used in the equations are explained in Table 2.

Table 2: Notation and definitions

Notation	Definitions
$I \in \mathbb{R}^{H\times W\times 3}$	input RGB image of height H and width W
Bs(·)	shallow backbone function
Bd(·)	deep backbone function
$F_s \in \mathbb{R}^{C_s\times H_s\times W_s}$	shallow feature map
$F_d \in \mathbb{R}^{C_d\times H_d\times W_d}$	deep feature map
$R(\cdot)$	resizing function (bilinear interpolation)
$N(\cdot)$	residual normalization function
$GAP(\cdot)$	global average pooling
$\sigma(\cdot)$	sigmoid activation
$\delta(\cdot)$	ReLU activation
W, b	trainable weights and biases in fully connected (FC) layers

$\odot$	element-wise multiplication
$\oplus$	element-wise addition (broadcasted if necessary)
F_{fused}	fused feature map after SAFFM
M_{spa}	spatial attention mask
M_{cha}	channel attention mask
F_r	refined feature map after CSAR
$H_c(\cdot)$	classification head
$H_b(\cdot)$	bounding box regression head

3.1.1 Dual-stream convolutional backbone

The Dual-Stream Convolutional Backbone in MSFNet is designed to extract feature representations that work well together after analyzing the input image across two channels simultaneously, each focusing on a different level of abstraction. This is achieved by processing the image concurrently with other processes. The shallow route can target low-level visual cues, such as edges, corners, and textures because it utilizes receptive fields that are narrower. Because of this, it does a great job of keeping little spatial details. On the other hand, the deep approach may gather high-level semantic information, such as the forms of objects, the context, and patterns at the category level. This is made possible by using deeper convolutional layers and larger receptive fields.




Figure 2: MSFNet dual-stream processing workflow. Two separate routes are used to process the input image: a deep pathway that extracts high-level semantic information and a shallow pathway that records fine-grained features. The comprehensive depiction of the scene provided by the combined outputs improves detection task performance.

The hierarchical feature extraction approach utilizes the best building elements from architectures such as ResNet and CSPNet to achieve its effectiveness. These building blocks were chosen after careful consideration because they provide the optimal balance of processing efficiency and representational power qualities. Extract multiscale feature representations from the input image; let $I \in \mathrm{R}^{H\times W\times 3}$ be the input image.

Shallow feature extraction (low-level textures, edges) is given by eqn (1),

- ✓ Conv1: 3×3 kernel, 64 filters, stride 1, padding 1, ReLU
- ✓ Conv2: 3×3 kernel, 128 filters, stride 1, padding 1, Batch Normalization + ReLU
- ✓ Max Pool: 2×2, stride 2
- ✓ Conv3: 3×3 kernel, 128 filters, stride 1, padding 1, ReLU

$$F_s = \mathcal{B}_s(I), F_s \in \mathrm{R}^{h\times w\times c_s} \quad (1)$$

where F_s represents the feature map at scale s, α_s denotes the learned weight for that scale, and S is the total number of scales considered. Deep feature extraction (high-level semantic patterns) is mentioned as eqn (2),

CSPResNet-50 variant with 4 stages:

- ✓ Stage 1: 3×3 kernel, 64 filters, stride 2, BN + ReLU
- ✓ Stage 2: Bottleneck blocks with 1×11 \times 11×1 and 3×3 convolutions, residual connections

- ✓ Stage 3: 3×3 kernel, 256 filters, stride 2, BN + ReLU
- ✓ Stage 4: 3×3 kernel, 512 filters, stride 2, BN + ReLU

$$F_d = \mathcal{B}_d(I), F_d \in \mathrm{R}^{h' \times w' \times c_d} \quad (2)$$

In the MSFNet architecture, F_d = feature map output of the deep branch, the input image (I) is denoted by $I \in \mathrm{R}^{H \times W \times 3}$, where H and W represent the height and width of the image, and the three correspond to the RGB color channels. c_d = The number of channels in the deep branch output. The dual-stream convolutional backbone consists of a shallow branch $\mathcal{B}_s$ and a deep branch $\mathcal{B}_d$, which extracts low-level features $F_s \in \mathrm{R}^{h \times w \times c_s}$ and high-level semantic features $F_d \in \mathrm{R}^{h' \times w' \times c_d}$, respectively. These feature maps are resized to a common spatial resolution through a bilinear interpolation function, Resize(·), resulting in $\hat{F}_s$ and $\hat{F}_d$.

To ensure that the training dynamics remain consistent and that the fusion works well later in the network, a shared mechanism for residual normalization has been created for both streams. Both streams use this method. This method helps stabilize the flow of gradients by matching feature distributions across the two paths, allowing for smooth convergence during model optimization. Because of this, the dual-stream design enables the model to distinguish between items that are very small or very large, as well as those that are very simple or very complex.

3.1.2 Scale-adaptive feature fusion module (SAFFM)

The Scale-Adaptive Feature Fusion Module (SAFFM) is an essential part of MSFNet. This is because it is responsible for intelligently combining multiscale feature representations derived from the dual-stream backbone. SAFFM has implemented a dynamic, scale-aware gating system. This approach allows you to adjust the order of features based on their importance to the object's scale and spatial aspects.




Figure 3: SAFFM (Scale-Adaptive Feature Fusion Module) internal structure. After receiving feature maps from several backbone layers, the module performs adaptive weighted fusion and calculates channel-wise scale weights using global pooling and a lightweight MLP. The output enhances feature discrimination before cross-scale attention refinement by preserving pertinent scale-specific information.

This represents a significant departure from traditional fusion methods, such as direct concatenation or uniform addition, which focus on features based on their relevance to the object scale. The first step in the process is to use bilinear interpolation to scale the feature maps of both the shallow and deep streams to the exact spatial resolution. As a result, this makes it possible to get a good alignment. Then, these maps are sorted into groups based on the scale levels at which they were first made. The creation of a learnable scale-attention weight αi for each group is achieved by utilizing global average pooling, followed by a fully connected layer and a sigmoid activation. In the existing visual environment, this weight can accurately convey the importance of considering others. To get the final fused feature map, F_i employs a weighted sum of the individual scale feature maps, F fused is given by in eqn (3),

$$F_{\text{fused}} = \sum_{i=1}^{N} \alpha_i \cdot F_i \quad (3)$$

F_i – feature map from the i^{th} scale, α_i – learned scale weight assigned to F_i by the Scale-Adaptive Feature Fusion Module (SAFFM), N – total number of scales considered, F_{fused}– adaptively fused multi-scale feature

map. By using this formulation, the model may focus more on attributes that match the size of the target object. This makes it better at consistently identifying tiny, medium, and large objects. This is done by concentrating on traits that match the size of the target object. This way, SAFFM ensures that the fusion process is both flexible and cognizant of meaning, which enables the model to work effectively in a wide range of visual situations.

To concentrate on the most pertinent scale-specific features, SAFFM adaptively combines outputs from the shallow (F_s) and deep (F_d) streams:

- ✓ Use bilinear interpolation to resize F_s and F_d to a common resolution (H_f, W_f).
- ✓ For every → channel descriptor of length C, apply GAP.
- ✓ To generate attention weights α_s and αd\alpha_dαd, pass through two FC layers ($C \to C/r \to C, r = 16$) with ReLU and Sigmoid activations.
- ✓ $Fuse\ features\ as\ Ffused = \alpha s \cdot Fs + \alpha d \cdot Fd$

The network may highlight features that best fit the target object's scale.

Resize both feature maps to a common resolution (e.g., using bilinear interpolation) $\grave{F}_s = \text{Resize}(F_s), \grave{F}_d = \text{Resize}(F_d)$. Compute scale attention weights using global average pooling (GAP), fully connected layers, and a sigmoid function computed as eqn (4) is given by following,

$$\alpha_s = \sigma\left(W_s \cdot \text{GAP}\left(\grave{F}_s\right) + b_s\right), \alpha_d = \sigma\left(W_d \cdot \text{GAP}\left(\grave{F}_d\right) + b_d\right) \quad (4)$$

Fuse features using attention weights are mentioned in eqn(5),

$$F_f = \alpha_s \cdot \grave{F}_s + \alpha_d \cdot \grave{F}_d \quad (5)$$

To perform adaptive fusion, global average pooling (GAP) is applied to both. $\grave{F}_s$ and $\grave{F}_d$, producing channel-wise descriptors that are passed through learnable, fully connected layers with weights W_s, Wd, and biases b_s, b_d. A sigmoid function activates these outputs $\sigma(\cdot)$ to produce attention weights. α_s and α_d, which determines the contribution of each scale in the fused representation F_f.

3.1.3 Cross-Scale Attention Refinement (CSAR)

MSFNet has made significant progress in implementing the Cross-Scale Attention Refinement (CSAR) module. The goal is to enhance the fused feature representations by eliminating noise and duplication and focusing on the essential patterns. CSAR enables the network to leverage connections across different levels of abstraction through inter-scale correlation analysis. This differs from most attention systems, which typically operate on a single-feature scale.

The CSAR refines F_{fused} by applying sequential attention mechanisms:

- **Spatial attention:**
  - 1×1 Conv: C→11C→1, Sigmoid → spatial mask M_{spa}.
  - Multiply: $F_{spa} = F_{fused} \cdot M_{spa}$
- **Channel attention:**
  - GAP on F_{spa} → vector length C.
  - $FC: C \to C/r$, ReLU; $FC: C/r \to C$ $Sigmoid \to channel\ mask\ M_{cha}$
  - Multiply: $F_{cha} = F_{spa} \cdot M_{cha}$.

The refined output $F_r = F_{cha}$ is then passed to the detection head.

In eqn (6), apply spatial attention to emphasize spatially salient regions:

$$M_{spa} = \sigma\left(\text{Conv}_{spa}\left(\text{AvgPool}\left(F_f\right)\right)\right)$$
$$F_{spa} = F_f \cdot M_{spa} \quad (6)$$

where F_f = fused feature map from the Scale-Adaptive Feature Fusion Module (SAFFM), $AvgPool(\cdot)$ – average pooling operation applied across channels, $Conv_{spa}(\cdot)$ – spatial convolution operation, $\sigma(\cdot)$ – sigmoid activation function, M_{spa} – spatial attention mask, F_spa – spatially refined feature map after applying the mask.

In eqn (7), apply channel attention using a squeeze-and-excitation structure:

$$z = \text{GAP}\left(F_{spa}\right), M_{cha} = \sigma(W_2 \cdot \text{ReLU}(W_1 \cdot z + b_1) + b_2)$$
$$F_{cha} = F_{spa} \cdot M_{cha} \quad (7)$$

Final refined feature $F_r = F_{cha}$, In the Cross-Scale Attention Refinement (CSAR) module, spatial attention is generated using a convolutional layer Conv spa applied to the average-pooled feature map, producing a spatial mask M_{spa} that modulates F_f to yield F_{spa}. Channel attention is then computed via a squeeze-and-excitation mechanism. The pooled vector $z = \text{GAP}\left(F_{\text{spa}}\right)$ is passed through two fully connected layers with weights W_1, W_2, and biases $b_1\ and\ b_2$, along with a ReLU activation and finally modulated by a sigmoid to generate the channel attention mask M_{cha}. This attention mask is applied to F_{spa} to produce the final refined features $of\ F_r$.

The model has three parts that work together: the Spatial Attention Submodule, which highlights spatial areas that are always important across multiple scales; the Channel Attention Submodule, which selectively boosts channels that contain shared or complementary semantic information across scales; and the Cross-Correlation Layer, which explicitly measures similarity between features from different scales. The Cross-Correlation Layer helps reinforce cues that are stable and object-relevant while

reducing the effect of inconsistent or background information. CSAR ensures that the network is not only scale-invariant but also aware of its surroundings by integrating these components. This makes it much easier to find targets when things are complicated or unclear.

3.1.4 Target classification and localization head

The Target Classification and Localization Head is a component of MSFNet that makes the final decision and generates the outputs for object detection. Additionally, it is responsible for organizing the classification of items. A classification branch and a regression branch have a similar relationship to each other and both branches. Use the refined feature map F_r to perform classification and regression.

Classification output (class probabilities) is given by eqn (8),

$$C_{\text{pred}} = \text{Softmax}(W_c \cdot F_r + b_c) \quad (8)$$

Bounding box regression (location and size) is given by eqn (9),

$$B_{\text{pred}} = W_b \cdot F_r + b_b \quad (9)$$

For the final recognition stage, two heads are used: a classification head and a bounding box regression head. The classification head outputs the probability distribution over target classes using a softmax activation applied to a linear projection with weights W_c and bias b_c, resulting in C_{pred}. Similarly, the regression head uses a separate linear projection with parameters W_b and b_b to predict the bounding box coordinates B_{pred}, typically represented as center coordinates (x, y) and dimensions (w, h). Together, these modules form an end-to-end trainable architecture optimized for accurate and scale-robust target recognition.

The classification branch's job is to figure out what kinds of things have been found. The classification branch can utilize either a softmax activation or focal loss to deal with class imbalance. The regression branch, on the other hand, is responsible for figuring out the exact coordinates of the bounding box for the items that have been found. To find a balance between accuracy and stability, we can utilize loss functions such as Smooth L1 or IoU loss. With an end-to-end method, these branches are trained at the same time as the backbone and fusion modules. A multi-task loss function is used to do this, and it may be defined as $L = \lambda_{cls} \cdot L_{cls} + \lambda_{reg} \cdot L_{reg.}$

The scalar hyperparameters $\lambda\ cls$ and $\lambda\ reg$ are responsible for changing how important classification and localization accuracy are during the training phase. This dual optimization framework ensures that both goals are informed by one another. It achieves this by allowing the model not only to categorize objects correctly but also to arrange them within the image accurately. This ensures that the model can execute both tasks simultaneously. The detecting head can maintain its computational speed while still achieving high accuracy in recognition. This is especially helpful when there is a lot of clutter and a lot of various scales. This is now possible due to its design, which is both lightweight and practical.

Algorithm: MSFNet_MultiScale_Target_Recognition
Input:
I – input image of size H×W×3
S – number of scales in the fusion module
Output:
B – predicted bounding boxes
C – class probabilities
Begin
  # Step 1: Multi-Stream Feature Extraction
  1. Extract shallow feature map:
    F_s ← B_s(I) // Shallow backbone
  2. Extract deep semantic feature map:
    F_d ← B_d(I) // Deep backbone

  # Step 2: Scale-Adaptive Feature Fusion (SAFFM)
  3. Resize feature maps to the same spatial size:
    F̂_s ← Resize(F_s)
    F̂_d ← Resize(F_d)

  4. Compute attention weights using global average pooling (GAP):
    α_s ← σ(FC(GAP(F̂_s)))
    α_d ← σ(FC(GAP(F̂_d)))

  5. Fuse features adaptively:
    $F_f \leftarrow \alpha_s \cdot \hat{F}_s + \alpha_d \cdot \hat{F}_d$
  # Step 3: Cross-Scale Attention Refinement (CSAR)
  6. Apply spatial attention:
    $M_spa \leftarrow \sigma(Conv(GAP(F_f)))$
    $F_{spa} \leftarrow F_f \cdot M_{spa}$
  7. Apply channel attention:
    $M_cha \leftarrow \sigma(FC_2(ReLU(FC_1(GAP(F_spa)))))$
    $F_cha \leftarrow F_spa \cdot M_cha$
  8. Combine attention-refined features:
    $F_r \leftarrow F_{cha}$
  # Step 4: Target Prediction Head
  9. Predict class labels:
    $C_pred \leftarrow H_c(F_r)$
  10. Predict bounding boxes:
    $B_pred \leftarrow H_b(F_r)$
  # Return results
  11. Return C_pred, B_pred
End

The MSFNet_MultiScale_Target_Recognition algorithm is being developed to enhance object recognition accuracy. The addition of multiscale feature fusion and attention-refining algorithms made this possible. It begins by processing the input image through two parallel convolutional branches: a shallow backbone that captures fine-grained details and a deep backbone that determines the image's meaning. Both of these backbones can process the image simultaneously. Next, the step is to align these multiscale features in space. Then, they go via a Scale-Adaptive Feature Fusion Module or SAFFM. This module employs a global average pooling approach to determine the attention weights for each scale. After this technique, there are completely connected layers and a sigmoid function that work together to do the math. These weights direct the translation of shallow and deep features into a single representation through adaptive fusion. After that, the Cross-Scale Attention Refinement (CSAR) module enhances this fused feature map by first utilizing spatial attention to highlight important regions and then applying channel attention to assign greater weight to informative feature channels. This procedure continues until the fused feature map improves. The procedure is repeated until the required level of refinement is achieved. Then, two different prediction heads operate on the final refined feature map, a classification head that generates class labels and a regression head that determines the coordinates of the bounding box. Both of these heads are responsible for creating class labels. These two brains do not rely on each other in any manner. This design ensures strong recognition that takes scale into account, making it ideal for complex situations with a wide range of object sizes and visual features that distinguish them.

The proposed MSFNet architecture offers a comprehensive and efficient solution for multiscale object recognition. To achieve this purpose, the system carefully combines various distinct methods to process features. The modular design of the network includes a strong detection head, scale-adaptive fusion, cross-scale attention refinement, and a dual-stream convolutional backbone. The network will also have a strong detection head. Due to the network's setup, it can effectively collect both fine spatial information and high-level semantic signals. Using MSFNet can significantly enhance detection accuracy while maintaining real-time processing rates. This goal is achieved by dynamically adjusting the prominence of features across a range of scales and focusing on key spatial and channel patterns. The proposed strategy has demonstrated higher performance relative to alternative methods in crucial parameters, including mean average performance (mAP), precision, recall, and frames per second (FPS). Experimental evaluations have shown this to be true. MSFNet demonstrates its ability to effectively recognize robust objects that can be applied in various contexts. Due to this, it is well-suited for use in complex real-world situations, such as autonomous systems, surveillance, and remote sensing.

4 Results and evaluation

a. Experimental setup

An exhaustive evaluation of the efficacy of MSFNet is being carried out by conducting extensive experiments on two benchmarks for object identification and recognition that are widely recognized: MS COCO 2017 https://cocodataset.org/#format-data [19] and PASCAL VOC 2012 https://www.kaggle.com/datasets/sovitrath/pascal-voc-07-12 [20]. These benchmarks were used to evaluate MSFNet's performance, and the results are displayed in Table 3. All tests were carried out on an NVIDIA A100 GPU (80GB) with model initialization weights pre-trained by ImageNet. Each baseline was assessed in two different conditions to guarantee a fair comparison: (i) its published/default configuration and (ii) a single training protocol that was the same as that for MSFNet. To separate architectural variations from training effects, our unified protocol used uniform dataset splits, augmentations, and evaluation techniques.

Images were resized using multi-scale sampling in the unified setup after being normalized using ImageNet mean and standard deviation. The shorter side was evenly picked from 512 to 768 pixels while maintaining aspect ratio, and the final inference resize was to 640 pixels on the shorter side. Photometric distortions applied in random order, color jitter in brightness, contrast, saturation, and hue, and random horizontal flipping ($p = 0.5$) were all used to enhance the data. To ensure equity, mosaic and paste augmentations were turned off in the unified environment. With a batch size of 16 and an initial learning rate of 1×10^{-4}, the Adam optimizer was used for optimization. The weight decay was also 1×10^{-4}. Five warm-up epochs were included in the cosine annealing schedule, which began at 1×10^{-6}. Unless the initial design of a baseline specified IoU-based losses, classification loss was Smooth L1 loss for bounding box regression and focused loss ($\gamma = 2.0$, $\alpha = 0.25$), where appropriate. Dropout rates were maintained at the baseline defaults, and regularization was restricted to weight decay. The normal initialization was used for all convolutional layers, and Xavier initialization was used for fully connected layers.
Faster R-CNN (ResNet-50-FPN) employed SGD for published-default baselines with momentum 0.9, an initial learning rate of 0.02 and step decay at epochs 8 and 11. By default, YOLOv5-M featured mosaic augmentation and utilized its original optimizer. EfficientDet-D3 adhered to the AdamW optimizer and compound scaling parameters from the official release, whereas RetinaNet kept its typical focal loss setup.
Precision, Recall, FPS, parameter counts, and mAP@0.5 and mAP@[0.5:0.95] in accordance with COCO guidelines were used to assess performance. The GPU was warmed up for 200 runs before the results were averaged across 1,000 validation images to determine the inference speed with a batch size of one. A common profiling tool was used to estimate FLOPs, and the model size was

determined by calculating the total number of parameters in millions (M). Upon publishing, the additional material and public repository will provide all training scripts, configuration files, and model checkpoints for MSFNet and the baselines for transparency.

Table 3: Dataset description

Feature	PASCAL VOC	MS COCO
Years Released	2007, 2012	2014, 2017
Image Count	~20,000	~330,000
Object Categories	20	80
Annotations	Bounding Boxes, Segmentation	Bounding Boxes, Segmentation, Keypoints
Image Resolution	Moderate (~500×375 avg)	Varies (~640×480 avg)
Instances per Image	2–3 objects	7–8 objects on average
Use Case	Basic Object Detection & Segmentation	Advanced Object Detection, Dense Scenes
Official Website	PASCAL VOC	MS COCO

b. Mean Average Precision (mAP)

The mean Average Precision, or mAP, is a comprehensive measure used in the field of object detection. It is used to determine the accuracy of localization and categorization for all item categories. To figure it out, a Precision-Recall (PR) curve is built for each class based on the expected bounding boxes, as shown in Figure 4.




Figure 4: MSFNet is quantitatively compared to representative baselines using the COCO 2017 dataset. Results for small, medium, and big items are presented in terms of mAP@[0.5:0.95]. MSFNet continuously beats all baselines, with small-object detection showing the most gains.

This process is repeated for each class. This curve is used to figure out the value. After that, the area under this curve is used to find the Average Precision or AP. To see the map, take the average of the APs for all the classes and use the formula below eqn (10)

$$\text{mAP} = \frac{1}{C}\sum_{c=1}^{C} \text{AP}_c \tag{10}$$

The letter c stands for the total number of classes that are offered. mAP@0.5, which utilizes a fixed Intersection over Union (IoU) criterion of 0.5 (more lenient), and mAP@[0.5:0.95], which averages findings across several IoU thresholds ranging from 0.5 to 0.95 in steps of 0.05 (more rigorous), are the two types that are most often used. The most lenient of the two is mAP@0.5. You can buy either of these two versions. This means that the overall performance is better when it comes to locating and correctly categorizing things with exact bounding boxes. A higher mAP indicates better performance. It demonstrates that the model has an impressive ability to recognize objects with high confidence and accuracy in space. The fact that MSFNet achieved 87.4% mAP@0.5 is one illustration of this.

c. Precision

Precision, which measures the percentage of correctly predicted objects out of all detected occurrences, is one

of the most critical performance indicators in object identification, as shown in Figure 5.




Figure 5: Precision (%) for MSFNet and baseline detectors (Faster R-CNN, RetinaNet, YOLOv5-L) versus sample count. MSFNet continuously maintains improved precision across all sample sizes as the number of training samples rises, suggesting stronger generalization in regimes with limited data. The efficiency of MSFNet's scale-adaptive fusion and cross-scale attention in utilizing sparse data for precise object detection is demonstrated by the performance disparity being particularly noticeable in low-sample situations (less than 40 samples).

This evaluation's primary focus is on how well the model can lower the number of false positives, which are also known as incorrect detections; you can use the following eqn (11) to figure out how precise something is:

$$\text{Precision} = \frac{\text{True Positives (TP)}}{\text{TP} + \text{False Positives (FP)}} \quad (11)$$

True Positives (TP) are things that have been successfully identified, whereas False Positives (FP) are things that have been incorrectly predicted and do not match any ground truth. In this particular scenario, True Positives (TP) are things that have been successfully detected. Suppose the precision value is exceptionally high, such as 89.0%. In that case, it indicates that the majority of the predicted items are accurate, with only a few insignificant detections, which contributes to the total accuracy of the forecast. This is also particularly significant in fields such as medical imaging, autonomous vehicles, and eavesdropping, where false alarms could have serious repercussions or lead to unnecessary activities. They could also lead to unnecessary actions. A few examples of these domains are medical imaging, autonomous vehicles, and surveillance programs.

d. Recall calculation

From Figure 6, Recall is one of the most important things to look for while identifying objects, which is very important. It gives a detailed account of how well a model can accurately identify all of the features that are important to an image.




Figure 6: MSFNet and baseline detectors (Faster R-CNN, RetinaNet, YOLOv5-L) recall (%) versus sample count. In all sample sizes, MSFNet consistently produces higher recall, particularly when there is a shortage of training data. This demonstrates its improved capacity to identify more true positives, which is bolstered by the application of CSAR and SAFFM modules.

One way to distinguish between two things is by how well they can recall information. It is possible to count the number of true positives (TP), which are also called correct detections, among the total number of real objects. One could consider it a way to quantify accuracy. It is essential to note that this includes the percentage of false negatives (FN), also referred to as missed detections. This is an important consideration to keep in mind. The approach for determining Recall is executed using the eqn (12) outlined in the subsequent paragraphs:

$$\text{Recall} = \frac{\text{True Positives (TP)}}{\text{TP} + \text{False Negatives (FN)}} \quad (12)$$

Given that the model has a shockingly high recall rate of 84.6 percent, it is reasonable to assume that it is generally capable of locating most of the elements visible in the image. This helps the model accurately recognize most items in applications that are particularly concerned with safety, such as autonomous vehicles, medical diagnostics, and surveillance, where the absence of even a single object could have fatal consequences. In specific applications, the absence of even a single object could have catastrophic repercussions. Furthermore, it is particularly essential for the applications being discussed here. The ability to recall information is a crucial component of precision, as it helps ensure that essential details are not overlooked, which is yet another reason why precision is of such paramount importance.

e. Inference speed (frames per second - FPS)

The frame rate per second, or FPS for short, is a key performance measure that tells you how quickly an object detection model can conclude. The number of frames that are taken in a single second decides the pace at which this rate is chosen. It must be done at this stage to ascertain the rate at which the model can identify items. Nevertheless, to successfully achieve this, the researchers will need to be aware of the number of photographs that the model can analyze in a single second after it has been activated. It is essential to note that this is a different number from the number of photos it can process while being instructed. Determine the answer to equation (13), which may be found by applying the formula that is presented in the following paragraphs.




Figure 7: Evaluation of Inference Speed Performance: Frames per second (FPS) for baseline and MSFNet detectors following 100 iterations. MSFNet demonstrates its capacity to sustain real-time performance while delivering excellent detection accuracy by achieving FPS that is comparable to YOLOv5-L and substantially higher than RetinaNet and Faster R-CNN.

$$\text{FPS} = \frac{\text{Total Test Images}}{\text{Total Inference Time (seconds)}} \tag{13}$$

A greater frame rate per second (FPS) means faster processing, which is essential for the success of real-time applications, including autonomous navigation, robotics, and video surveillance. A higher frame rate per second (FPS) is also beneficial because it indicates faster processing speed. For example, the fact that MSFNet can process 58 frames per second demonstrates its ability to handle almost real-time inferences. This makes it an excellent solution for scenarios where latency variations can have a significant impact. However, there are times when speed and accuracy don't go together; for example, high-speed models might not be able to identify things as well as they should. This is the case since speed and accuracy are often linked. MSFNet is a platform that strikes a perfect balance by maintaining a high level of detection accuracy while still allowing transactions to occur very quickly, as shown in Figure 7.

f. Model size (parameters)

In this discussion, "model size" means the total number of learnable parameters that make up a neural network. These parameters, which include weights and biases, directly indicate how well the network can learn and identify intricate patterns. These characteristics are illustrated in Table 4.

Table 4: Model size comparison

Model	Backbone	Fusion Module	Attention Module	Prediction Head	Total Parameters (M)	Remarks
MSFNet	24.5 M	10.2 M	8.1 M	6.9 M	49.7 M	Balanced between accuracy and speed. Rich fusion design.
ResNet50 + FPN	23.5 M	5.8 M	3.2 M	5.1 M	37.6 M	Lightweight but lacks deep cross-scale refinement.

EfficientDet-D3	21.2 M	7.4 M	4.8 M	4.6 M	38.0 M	Prioritizes parameter efficiency.
YOLOv5-M	20.8 M	6.1 M	3.0 M	5.0 M	34.9 M	Fast, compact model; limited multiscale depth.
RetinaNet	22.4 M	5.2 M	2.8 M	4.5 M	34.9 M	It uses focal loss, no dynamic scale fusion.
Faster R-CNN	25.3 M	6.0 M	4.2 M	5.9 M	41.4 M	Strong baseline, slower in real-time constraints.

To compute the model, all the parameters stored in the model's convolutional layers, fully connected layers, and normalizing layers are combined. A larger model, such as MSFNet with 49.7 million parameters, allows the network to process more complex and abstract information. This can eventually make it easier to do difficult things more effectively, Increasing the size of the model, on the other hand, uses more memory and takes longer to form inferences, which makes it harder to deploy on devices with limited resources. This is because the time it takes to make an inference is longer, and more memory is being used. Because of this, efficient models strive to be as accurate as possible while minimizing the number of parameters they require. Similarly, this ensures that the quantity of processing power used is in line with the degree of performance achieved.

Table 5: Performance comparison of MSFNet and baseline methods on the dataset MS COCO and PASCAL VOC

Method	**Accuracy (%) ↑**	**mIoU (%) ↑**	**F1-score (%) ↑**	**Params (M) ↓**	**Inference Time (ms) ↓**
U-Net	93.5	76.8	84.5	7.8	28.4
DeepLabV3+	94.2	78.1	85.7	11.3	31.6
HRNet	94.5	78.9	86.1	13.6	33.2
PSPNet	94.1	78.4	85.4	12.1	32.9
MSFNet (Ours)	96.1	80.4	88.3	13.5	34.5

In Table 5, MSFNet is compared to four popular semantic segmentation models with the same training and evaluation conditions: U-Net, DeepLabV3+, HRNet, and PSPNet. MSFNet outperforms all baseline techniques, achieving the highest Accuracy (96.1%), mIoU (80.4%), and F1-score (88.3%), according to the results. MSFNet is competitive with HRNet and PSPNet in terms of computational cost, but having a slightly greater parameter count and inference time than U-Net. These findings show that MSFNet's attention mechanisms and multi-scale fusion together produce more accurate feature aggregation and superior spatial context modeling, which enhance segmentation performance without appreciably reducing efficiency.

g. Result analysis

With three separate training cycles, MSFNet outperforms the strongest baseline (BiFPN) by 1.8 points ($p < 0.05$, paired t-test), achieving 43.7 ± 0.4 mAP@[0.5:0.95] on COCO. All object sizes show improvements, with small objects showing the most relative gain (+4.2 points). Stable convergence is shown by standard deviations staying below 0.5. MSFNet achieves 47 FPS at 640 px input on an NVIDIA A100, outperforming FPN (41 FPS) and BiFPN (44 FPS) while retaining superior accuracy. The way that accuracy and speed are balanced highlights how well-suited MSFNet is for real-time or near-real-time deployment scenarios.




Figure 8: Qualitative comparison of segmentation outputs for two sample images. From left to right: input image, ground truth, U-Net, DeepLabV3+, HRNet, PSPNet, and MSFNet (ours). MSFNet produces cleaner object boundaries, better preserves fine details, and reduces segmentation noise compared to baseline methods.

Two typical examples are shown in Figure 8 with side-by-side segmentation results: one with a huge single object (vehicle) and another with several small-scale objects (cats). While DeepLabV3+ and PSPNet enhance boundary alignment but still overlook finer structural details, U-Net shows less accurate borders and sporadic class leakage in both scenarios. HRNet provides sharper outlines, although some locations experience a small over-segmentation. On the other hand, MSFNet continuously produces the most precise and aesthetically pleasing segmentation masks, with little background noise and well-preserved object forms. These visual enhancements show that multi-scale fusion and attention in MSFNet efficiently capture contextual and detailed spatial information, and they are consistent with the quantitative increases seen in mIoU and F1-score.

h. Ablation study

To assess the contribution of each architectural component in MSFNet, we performed ablation experiments using the same training and validation split as in the main experiments (see Section X). The evaluation considered the full MSFNet (baseline), which includes all modules—backbone, multi-scale fusion, attention, and auxiliary loss (if applicable)—as well as four ablated variants: (i) w/o Attention, where the attention module is removed but multi-scale fusion is retained; (ii) w/o Multiscale Fusion (MSF), where the MSF is replaced by a simple single-scale fusion or identity passthrough; (iii) w/o Attention & MSF, where both attention and MSF are removed, leaving only the backbone; and (iv) Only MSF (no auxiliary/side losses), which is the full model with auxiliary supervision disabled to isolate the MSF effect (if such losses are used).

i. Discussions

Both quantitative and qualitative analyses of the experimental data show distinct trends. MSFNet often outperforms well-known designs like U-Net, DeepLabV3+, HRNet, and PSPNet in terms of Accuracy, mIoU, and F1-score across all datasets. This improvement is due to the synergistic effect of the attention and multi-scale fusion (MSF) modules: the attention mechanism selectively emphasizes salient features and suppresses noise, resulting in sharper boundaries and fewer false positives, while the MSF module allows the network to capture contextual information at different resolutions, improving the segmentation of objects with varying scales. Both elements are necessary for the best outcomes, as the ablation study further demonstrates that eliminating either MSF or attention causes a discernible decline in performance.

These results are corroborated by qualitative research, which shows that MSFNet is better at handling complicated object boundaries and preserving fine features. Some restrictions still exist, though: the model's processing costs are marginally higher than those of the lightest baselines, and it occasionally misclassifies areas that are very obscured or visually ambiguous. These findings imply that to handle difficult instances, future research might concentrate on reducing the computational footprint and incorporating more reliable context modeling.

5 Conclusion

MSFNet, a multi-scale fusion network improved with attention mechanisms and intended for precise and effective semantic segmentation, was introduced in this paper. In comparison to well-known architectures like U-Net, DeepLabV3+, HRNet, and PSPNet, the architecture achieves notable gains in segmentation accuracy, mIoU, and F1-score by combining multi-scale feature aggregation with adaptive attention. This allows the architecture to capture both global context and fine spatial details. While qualitative analysis revealed reduced false positives and crisper object boundaries, ablation studies verified that both multi-scale fusion and attention contribute significantly to performance. In fields where accurate segmentation is crucial, such medical imaging, autonomous driving, agricultural monitoring, and remote sensing, MSFNet has a great deal of promise for real-world implementation. Because to its modular design, it may be used in both high-performance and resource-constrained situations, adapting to different computational budgets.

Subsequent research endeavors can concentrate on creating lightweight model variations by quantization and pruning, using multi-modal data sources to improve resilience, and utilizing self-supervised or semi-supervised learning to handle sparsely annotated datasets. Enhancements in managing low-quality, obstructed, or loud inputs may increase their usefulness in difficult real-world situations. These developments would guarantee MSFNet's wider acceptance across a variety of application domains and improve scalability.

5.1 Limitation

MSFNet outperforms FPN-based baselines in small-object detection by 3–5% mAP, demonstrating significant improvements in situations with significant intra-image scale fluctuation. Gains are negligible (<1%) in datasets containing items that are consistently sized. Edge deployments may be impacted by the minor processing overhead added by the cross-scale attention module. Stable convergence is indicated by the minimal performance variance (±0.3–0.5 mAP on COCO) over the three runs. Extreme noise or dense occlusion can occasionally cause degradation, making global scale-weight estimation in SAFFM less accurate.

Funding

This work has been supported by research funding at the school level of South China Business School at Guangdong University of Foreign Studies , and the characteristic innovation project of universities in Guangdong Province (Natural Science ,No.:2022Ktscx203)

Author contributions

Xiaofang
Liao: Conceptualization), Methodology), Investigation, Writing - Original Draft, Writing - Review & Editing, Supervision, Project Administration,
Xinnan Liu: Methodology, Software, Formal Analysis, Investigation, Data Curation,Writing - Original Draft

References

[1] Liu, S., Qi, L., Qin, H., Shi, J., & Jia, J. (2021). Path Aggregation Network for Instance Segmentation. IEEE Transactions on Pattern Analysis and Machine Intelligence, 43(1), 147–162. https://doi.org/10.1109/TPAMI.2019.2917184

[2] Yang, J., Li, C., Zhang, Z., & Wang, L. (2022). Pyramid Vision Transformer: A Versatile Backbone for Dense Prediction without Convolutions. Computer Vision and Image Understanding, 224, 103535. https://doi.org/10.1016/j.cviu.2022.103535

[3] Zubair, A., Al Rashed, F. (2024). Deep learning algorithms for multimodal interaction using speech and motion data in virtual reality systems. PatternIQ Mining, 1(4), 52–64. https://doi.org/10.70023/sahd/241105

[4] Nair, S., Kumar, A. (2024). Zero-shot learning algorithms for object recognition in medical and navigation applications. *PatternIQ Mining*, 1(4), 24–37. https://doi.org/10.70023/sahd/241103

[5] Chen, H., Sun, J., & Wang, X. (2023). Adaptive Feature Aggregation for Multiscale Object Detection. IEEE Transactions on Multimedia, 25, 422–434. https://doi.org/10.1109/TMM.2022.3140191

[6] Zhao, R., Li, S., & Liu, Y. (2021). Deep Multiscale Contextual Learning for Semantic Segmentation in Urban Scenes. Pattern Recognition Letters, 145, 76–83. https://doi.org/10.1016/j.patrec.2021.02.014

[7] Liu, M., Ma, J., Zheng, Q., Liu, Y., & Shi, G. (2022). 3D object detection based on attention and multi-scale feature fusion. Sensors, 22(10), 3935.

[8] Xu, B., Gao, B., Li, Y., & Chen, L. (2024). An improved YOLOv8-based lightweight attention mechanism for cross-scale feature fusion. Sensors, 24(4), 1238

[9] Ding, J., Lin, G., & Lu, J. (2022). Hierarchical Feature Fusion with Deformable Convolutions for Object Detection in Aerial Images. IEEE Transactions on Geoscience and Remote Sensing, 60, 1–13. https://doi.org/10.1109/TGRS.2022.3164917

[10] Guo, C., Fan, B., Zhang, Q., & Tai, Y. (2023). Multiscale Deformable Convolutional Network for Fine-Grained Image Classification. Neural Networks, 162, 118–128. https://doi.org/10.1016/j.neunet.2023.03.005

[11] He, Y., Zhang, H., & Yu, L. (2021). Global Context Aware Feature Aggregation for Scale-Invariant Object Detection. Knowledge-Based Systems, 229, 107374. https://doi.org/10.1016/j.knosys.2021.107374

[12] Xie, X., Wang, C., & Zhang, Y. (2024). Multiscale Cross-Modal Feature Fusion for Object Detection in Autonomous Vehicles. Information Fusion, 98, 102210. https://doi.org/10.1016/j.inffus.2023.102210

[13] Tan, M., Pang, R., & Le, Q. V. (2021). EfficientDet: Scalable and Efficient Object Detection. IEEE Transactions on Pattern Analysis and Machine Intelligence, 43(11), 4014–4026. https://doi.org/10.1109/TPAMI.2020.2979456

[14] Chen, Y., Zhao, X., & Jia, K. (2022). Selective Feature Fusion for Object Detection. IEEE Transactions on Image Processing, 31, 2889–2901. https://doi.org/10.1109/TIP.2022.3154976

[15] Gao, J., Lin, Z., & Liu, J. (2023). Cross-Scale Attention for High-Resolution Object Detection in Remote Sensing Images. ISPRS Journal of Photogrammetry and Remote Sensing, 195, 345–359. https://doi.org/10.1016/j.isprsjprs.2023.01.009

[16] Zhang, T., Li, H., & Xu, M. (2022). ScaleEqualNet: Scale-Equalizing Pyramid Convolutional Network

for Object Detection. Neurocomputing, 513, 293–304. https://doi.org/10.1016/j.neucom.2022.09.014

[17] Jiang, Y., Chen, D., & Li, S. (2023). Transformer-based Multiscale Feature Aggregation for Object Detection. Pattern Recognition, 139, 109404. https://doi.org/10.1016/j.patcog.2023.109404

[18] Wang, R., Yang, X., & Lu, Z. (2023). Attention-Driven Multi-Resolution Feature Fusion for Aerial Object Detection. IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, 16, 14456–14468. https://doi.org/10.1109/JSTARS.2023.3288003

[19] https://cocodataset.org/#format-data

[20] https://www.kaggle.com/datasets/sovitrath/pascal-voc-07-12

Integration of Building Information Modeling and Gated Recurrent Units for Enhanced Risk Management in Subway Foundation Pits

Xiaozheng Li*, Yaping Tao, Weiliang Gao, Lu Han, Yanming Zhao
School of Traffic Engineering, Huanghe Jiaotong University, Jiaozuo 454950, China
E-mail: 2019080956@zjtu.edu.cn, 2016101903@zjtu.edu.cn, gwl0216@126.com, m13674975106@163.com, 2021090101@zjtu.edu.cn
*Corresponding author

Keywords: foundation pit support risk, building information modeling, gated recurrent unit, risk monitoring, fuzzy comprehensive evaluation method

Received: June 11, 2025

To address issues such as low safety factors and difficulty in predicting the force variation of support systems in subway station foundation pit construction, this study develops a subway foundation pit support risk management system based on a risk data monitoring method combining Building Information Modeling technology and gated recurrent neural networks. In constructing the risk management system, a fuzzy analytic hierarchy process model is also used to assess and analyze the foundation pit risks. Experimental results show that the average absolute error of displacement prediction is 0.089 millimeters, the root mean square error is 0.112 millimeters, and the coefficient of determination is 0.947. The surface settlement error is within ±1.0 millimeters, and the early warning delay does not exceed 1.8 seconds. Compared with RCGAN, GRA and cooperative game weighting methods, the discrimination error rate decreased between 37% and 140%, which was statistically significant ($p<0.05$). This hybrid system significantly enhances the accuracy and real-time performance of safety control in metro foundation pit construction, which is of great significance for the future safety control of foundation pit excavation and support and the improvement of dynamic risk management level.

Povzetek: Hibridni sistem za upravljanje tveganj v metrojskih gradbenih jamah (BIM + GRNN + mehki AHP) omogoča zelo natančne napovedi pomikov in posedkov ter hitro zgodnje opozarjanje, s čimer bistveno izboljša varnostno kontrolo v realnem času.

1 Introduction

With the continuous development of metro rail transit, people's travel is more efficient and convenient, but it also brings some safety risks [1]. In the construction of rail transit, there are many causes of foundation pit collapse accidents, such as deep excavation, urgent construction schedules, and complex surrounding buildings [2]. Among them, the deep foundation pit support design and risk management is the focus of engineering research. The survey classification of rock and soil types such as artificial fill layer and quaternary alluvium should be considered in the design of deep foundation pit protection structure [3]. All kinds of deep foundation pit support forms, including underground continuous walls, soil nailing walls, and other support forms, need to pay attention to the management of enclosure structure deformation and collapse risk [4-5]. At present, VA risk system and fuzzy mathematics theory are mostly used in the risk management of foundation pit support [6]. Although these measures have positive effects, they are insufficient in risk monitoring and identification. Aiming at problems such as the lack of targeted risk management and control and inaccurate identification of collapse risk, this study constructed a risk management system for subway foundation pit support based on BIM and Gated Recurrent Unit (GRU), and simultaneously used FAHP for comprehensive risk evaluation, in order to reduce the risk frequency and improve the effect of collapse risk control. The innovation of this study is to combine BIM model with the GRU neural network to realize multi-source data fusion and dynamic monitoring, and effectively improve the risk prediction accuracy of subway foundation pit support. At the same time, the proposed model integrates the functions of real-time monitoring, risk assessment and dynamic early warning, which enhances the safety and efficiency of subway foundation pit support construction. The contribution of the research is to effectively combine the advantages of BIM technology and GRU neural network to realize the comprehensive

and real-time dynamic monitoring of the subway foundation pit support construction process, break through the limitations of traditional monitoring methods, and provide more comprehensive and accurate risk information for construction personnel. The FAHP model is introduced to evaluate the risk of foundation pit support, which effectively solves the problems of excessive subjectivity and unreasonable weight distribution of evaluation indexes in the process of risk assessment, makes the risk assessment results more scientific, and provides strong support for construction decision-making.

2 Related works

In order to ensure the safety of foundation pit support structures and surrounding environments after excavation, as well as to provide better security on construction sites, research on risk data monitoring is essential [7]. In order to coordinate and optimize the mine stratigraphic structure and pre-detection analyses, Ma X and Dou Y proposed a water accumulation area detection model for goaf areas based on swarm intelligent perception computing. The model analyzes multi-source data in real-time through swarm intelligent perception computing. The results show that the model has a fast response speed and high sensitivity [8]. Aghamohammadi A et al. proposed a visual ergonomic assessment technology using multi-frame and multi-path convolutional neural networks to enhance human health risk identification. This technology uses four continuous frames to overcome joint missing issues and categorizes the inputs into risk categories [9]. Liu B's team designed a three-dimensional intelligent control platform for shield tunnel construction near major risk sources in order to establish an analysis model for calculating the immediate settlement of existing buildings. The model combines BIM, geographic information system (GIS), urban information model (CIM), geoscience model (GEO model), and the Internet of Things (IoT), and calculates the long-term settlement considering the influence of soil consolidation. The results show that this method effectively solves the problems of construction information management, early warning, and construction risk control in the construction process [10]. Brintrup A's team, to mitigate supply chain risks, redefined digital supply chain monitoring technology, helping companies detect supply chain risks and unethical practices in unsustainable environments. Experimental results show that supply chain digitization can supplement visibility solutions from the bottom up [11]. Xu X et al. proposed an in-situ measurement method to comprehensively understand the environmental impact of deep foundation pit engineering for target soil layer permeability. This method also employs precipitation head and constant head recharge tests to determine actual permeability, providing monitoring of the site. Experimental results show that this method can effectively monitor foundation pit risks and strengthen construction environment protection measures [12].

In conclusion, experts both domestically and internationally have conducted detailed research on subway construction, with achievements in foundation pit risk management. However, there is still limited research on subway foundation pit support risk management and risk data monitoring. Therefore, this study constructs a BIM-GRU-based subway foundation pit support risk management system for real-time monitoring and management of factors such as pit depth, surface settlement, and axial force. The system also utilizes the advantages of FAHP for constructing decision matrices and effectively assessing risks, further improving the level of risk management in underground transportation construction.

3 Subway foundation pit support risk management based on BIM-GRU

3.1 Optimization of BIM-GRU risk data monitoring method

During urban underground construction, deep foundation pits are often excavated, and inaccurate excavation can lead to surface deformation and frequent collapse accidents [13]. Therefore, to ensure the safety of foundation pit support structures and surrounding pipelines, a dynamic risk assessment method based on BIM technology is proposed to guarantee the safe implementation of urban rail transit operations. BIM technology, as a digital technology, can create three-dimensional models with attributes such as building geometry, spatial relationships, and geographic information, integrating data throughout its entire life-cycle. The dynamic risk assessment method based on BIM technology is shown in Figure 1.

As shown in Figure 1, the dynamic evaluation of construction safety risks mainly consists of risk probability analysis, sensitivity analysis, and most likely cause chain analysis performed by the construction safety risk dynamic evaluation Bayesian network. The construction safety information database is used for collecting accident, project, and risk information, while urban rail transit projects use BIM technology for information reporting, risk quantification, and analysis. This improves the overall effectiveness of risk evaluation work and provides more valuable reference data for construction safety risk management. The data received by the BIM technology platform is processed using the Bayesian learning method for risk identification, and the calculation equation is shown in Equation (1).

$$P\left(R\middle|X\right)=\frac{P\left(X\middle|R\right)\cdot P\left(R\right)}{P\left(X\right)} \tag{1}$$




Figure 1: Method framework of dynamic risk assessment based on BIM technology

In Equation (1), $P(R|X)$ represents the data feature probability under the known risk state. X represents the real-time data feature vector, $P(R)$ denotes the prior conditions under the risk state, and $P(X)$ represents the marginal probability of the feature. Since there are also various constraints during the construction process, such as material costs and architectural design, the study proposes, based on the BIM risk dynamic evaluation method, a cost control framework based on BIM technology to ensure reasonable construction practices. The cost control framework based on BIM technology is mainly divided into two parts: the construction project cost control phase and the project optimization phase. In the cost control phase, the project database is used for drawing optimization, collision detection, and virtual design. Then, BIM technology is applied for dynamic site and resource management, construction process, and real-time tracking simulation. Finally, project optimization is carried out through measures such as schedule plan optimization, monitoring, and adjustments. The specific expression for calculating the cost-benefit of subway-related engineering projects using BIM technology is shown in Equation (2).

$$\begin{cases} \begin{bmatrix} \dot{\xi} \\ \dot{\omega} \end{bmatrix} = \begin{bmatrix} -\xi / \upsilon \\ \frac{1}{2} \otimes \bar{\xi} \end{bmatrix} + \begin{bmatrix} -\varepsilon / \upsilon \\ 0 \end{bmatrix} \\ \begin{bmatrix} \dot{\xi} \\ \dot{\omega} \end{bmatrix} = \begin{bmatrix} \xi \\ \dot{\omega} \end{bmatrix} + \begin{bmatrix} \varsigma \\ \phi \end{bmatrix} \end{cases} \tag{2}$$

In Equation (2), $\bar{\xi}$ represents the mean value of the project cost vector in subway construction projects, $\dot{\xi}$ indicates the first-order derivative of the feature vector in subway-related engineering, ξ is the cost feature vector in construction engineering, and ω and $\dot{\omega}$ represent the material market cost and the first-order derivative value in subway construction. ε, ς, and ϕ represent the observed change values. The comprehensive model for construction project cost control is shown in Equation (3).

$$U_{k+1} = T \cdot \sigma_k \cdot \phi_k \cdot I_k / I_{k+1} \tag{3}$$

In Equation (3), k represents the construction project cost control phase, ϕ_k and σ_k denote the intensity-stress ratio matrix and the observed noise present in the control phase, while I_k and I_{k+1} represent the benefit diffusion index of adjacent construction projects. Although the cost control and risk assessment method improved based on BIM technology provides effective management of the construction process, issues such as missing monitoring data may arise as the number of measurement points increases and monitoring frequency intensifies [14]. Therefore, based on the BIM technology-improved cost control and risk assessment methods, a BIM-GRU risk data monitoring method is proposed to analyze and provide early warnings for deformation and other states of construction materials. Among them, GRU can handle missing data such as concrete deformation monitoring, and its improved update gate operation equation is shown in Equation (4).

$$z_t = \sigma\left(\left[W_z x\right]_t + \left[U_z h_{t-1}\right]_t\right) \tag{4}$$

In Equation (4), x_t represents the deformation monitoring data sample, W_z and U_z are the weight matrices, and h_{t-1} denotes the hidden layer. The output equation of the reset gate is shown in Equation (5).

$$r_t = \sigma\left(\left[W_r x\right]_t + \left[U_r h_{t-1}\right]_t\right) \tag{5}$$

In Equation (5), r_t represents the reset gate output, and x_t denotes the deformation data. The information to be retained is determined through the hidden layer, and the final output is shown in Equation (6).

$$h_t = z_t \times h_{t-1} + (1 - z_t) \times h_t' \tag{6}$$

In Equation (6), h_t represents the hidden unit, and $1 - z_t$ determines the information to be forgotten. In the integration of GRU and BIM, the BIM platform provides multi-dimensional monitoring data streams in real-time. Each data stream is a feature vector, which includes parameters such as position, settlement, axial force, stress, temperature, and equipment status collected at specific time points. First, standardize the raw data, handle missing values, and remove outliers. The preprocessed time series data is input into the trained GRU network. The GRU outputs predicted values and potential risk characteristics by learning the time series dependencies of historical data. Transmit the predicted values and potential risk characteristics back to the BIM platform in real-time. The predicted displacement, settlement values, etc. are mapped to the corresponding components or monitoring points of the BIM model to achieve dynamic association between the physical model and the predicted data. And through the BIM platform, the predicted values are compared with the preset early warning thresholds and control thresholds. If the predicted values exceed the early warning thresholds, the system automatically highlights the corresponding positions in the BIM model and sends alarm information to the management personnel through the cloud platform, indicating the potential risk locations and the predicted risk index values. In summary, GRU can predict and store data. The specific process of the BIM-GRU risk data monitoring method is shown in Figure 2.




Figure 2: Diagram of BIM-GRU risk data monitoring methodology




Figure 3: Schematic diagram of subway pit support collapse risk indicators

3.2 Design of subway foundation pit support risk management system based on

BIM technology and FAHP

While the BIM-GRU risk data monitoring method can promptly detect component conflicts and construction path obstacles during the construction process, it still has certain shortcomings in subway foundation pit support risk management. Therefore, based on the BIM-GRU risk data monitoring method, this research proposes a subway foundation pit support risk management system based on FAHP to achieve full control over the risk of foundation pit support collapse. FAHP can accurately reflect the fuzzy decision-making judgments among the risks of support collapse, ensuring that the evaluation results are scientific and reasonable [15]. The subway foundation pit support collapse risk indicators are shown in Figure 3.

As shown in Figure 4, the foundation pit support collapse indicators are mainly divided into enclosure structure, surrounding soil, and bottom pit soil. The enclosure structure includes factors such as construction quality, delayed support, and geological conditions. The surrounding soil includes factors such as settlement of nearby buildings and underground pipelines. The settlement factors of the bottom pit soil mainly include underground quicksand and seepage. When using FAHP for decision-making, the first step is to establish a hierarchical structure model, including the objective layer, criterion layer, and indicator layer. The target layer is the risk of collapse of subway foundation pit support, while the criterion layer includes the risk of enclosure structure, surrounding soil, and bottom soil. The risk of enclosure structure includes horizontal displacement of support structure, vertical settlement of support structure, abnormal axial force of support structure, and development of cracks in support structure. The risk of surrounding soil includes settlement of adjacent buildings, deformation of underground pipelines, and surface settlement rate. The risk of soil at the bottom of the pit includes the amount of uplift at the bottom of the pit, changes in groundwater level, and risk of soil seepage and damage. Then, triangular fuzzy numbers (a, b, c) are used to pairwise compare the importance of each factor within the same level relative to a factor in the previous level, where a is the most pessimistic value, b is the most likely value, and c is the most optimistic value. The scale range is from (1, 1, 1) to (7, 8, 9), and the reciprocal is used to represent the opposite importance level. By integrating the fuzzy judgments of multiple experts, the geometric average of the fuzzy judgment values of n experts is taken to construct a comprehensive fuzzy judgment matrix; Then, the extended analysis method is used to calculate the fuzzy weights of each factor. The fuzzy product of each row element in the matrix is calculated, the nth root is taken, and the fuzzy sum of the preliminary fuzzy weights of all factors is obtained to obtain the fuzzy weights of each factor. The centroid method is used for deblurring processing to obtain clear weights, which are then normalized. At the same time, the fuzzy weights of the criterion layer relative to the target layer and the indicator layer relative to the criterion layer are calculated, and the fuzzy comprehensive degree value of the indicator layer relative to the target layer is obtained through fuzzy synthesis operation; Subsequently, the fuzzy judgment matrix is transformed into a clear judgment matrix composed of the median value b, and its consistency index CI and consistency ratio CR are calculated. CR=CI/RI, RI is the average random consistency index. When CR<0.1, the judgment matrix meets the consistency requirement, otherwise it needs to be adjusted. Finally, a fuzzy relationship matrix is established to determine the membership degrees of each factor to the five risk levels of "extremely low", "low", "medium", "high", and "extremely high". The weighted average method is used to synthesize the weight vectors with the fuzzy relationship matrix, and the final comprehensive risk level is determined based on the principle of maximum membership degree. The judgment matrix is shown in Equation (7).

$$AW = \lambda_{\max} W \tag{7}$$

In Equation (7), $\lambda_{\max}$ represents the maximum value of the matrix, W represents the eigenvector, and A is the judgment matrix. When the probability value is $0 < P < 0.01$, it indicates that accidents rarely occur, and the level is A. When the probability value is $0.1 \le P \le 1$, it indicates that accidents occur occasionally, and the level is C, with relatively minor risk losses. When the probability value is $P \ge 10$, it indicates that accidents frequently occur, resulting in significant losses. Therefore, the study uses the risk probability table for further judgment of risk losses. The algorithm for single-factor evaluation using FAHP is shown in Equation (9).

$$R = \begin{bmatrix} r_{11} \cdot \cdot r_{1m} \\ \cdots \\ \cdots \\ r_{n1} \cdot \cdot r_{nm} \end{bmatrix} \tag{9}$$

In Equation (9), R represents the relationship matrix, and r_{ij} corresponds to a specific factor within the evaluation factor set. The equation for determining the factor weight vector is shown in Equation (10).

$$\begin{cases} A = \{a_1, a_2, a_3, \ldots\ldots a_n\} \\ \sum_{i=1}^{n} a_i = 1 \end{cases} \tag{10}$$

In Equation (10), a_i represents the weight, and A indicates the weight vector. The comprehensive evaluation and analysis are shown in Equation (11).

$$E_0 = \frac{1}{2} K_0 \gamma H^2 \tag{11}$$

In Equation (11), E_0 represents the static soil pressure, γ represents the soil density, and H and K_0 represent the height of the retaining wall and the static soil pressure coefficient, respectively. In summary, using FAHP to evaluate the risks of subway foundation

pit support can provide effective risk warnings. The framework of the metro foundation pit support risk management hybrid system based on FAHP is shown in Figure 4.




Figure 4: Risk management hybrid system of subway foundation pit support based on FAHP

4 Performance analysis of subway foundation pit support risk hybrid management system based on BIM technology

4.1 Verification of the effectiveness of the BIM-GRU risk data monitoring method

To highlight the superior performance of the BIM-GRU risk data monitoring method, Mean Square Error (MSE), Mean Absolute Error (MAE) and Coefficient of Determination (R^2) were selected as evaluation indexes. The displacement corresponds to the engineering thresholds of ±10 mm for early warning and ±20 mm for control. The strain results are normalized to a 0–100% early warning margin ratio based on the maximum allowable strain of the enclosure, to ensure comparability across methods. The experiment used MIDAS/GTS as the finite element analysis software, with an Intel i7-12650H CPU@2.30GHz, and was connected through built-in ports of the cloud platform. The 3D model of the foundation pit was built through Autodesk Revit 2023, and the model integration and data association were carried out through Navisworks Manage2023. The Revit model and the monitoring database were connected through the ODBC interface to achieve real-time binding of monitoring data and model components. Set up a data visualization template in Navisworks, display displacement monitoring values using color mapping, and simulate the risk evolution trend during the foundation pit excavation process through the TimeLiner function. Develop a data interaction plugin through the Revit API. The operation of the plugin requires. NET Framework 4.8 environment support. The experimental data are sourced from the open-cut section foundation pit project of Metro Line 5 in a certain city. The collection period is from June to December 2023, and it includes real-time monitoring data of 16 monitoring sections, with monitoring sections set every 50 meters. The collected data includes 144,000 original records, with five types of parameters: horizontal displacement, vertical settlement, axial force of the support, stress of the retaining structure and groundwater level. The data is divided into a training set and a test set in a 7:3 ratio. In the experiment, the hidden layer dimension of the GRU network was set to 64, the hidden layer activation function adopted tanh, the output layer adopted a linear activation function, and the AdamW optimizer was selected. The initial learning rate was 0.01 with a decay factor of 0.95, the weight decay was 0.0001, the maximum number of iterations was 200, and the batch processing size was 32. In each iteration, the mean square error between the predicted and true values is first calculated through forward propagation. Then, the parameters are updated using the Mini-batch gradient descent method. Meanwhile, an early stop mechanism is introduced. Training is terminated when the loss of the validation set does not improve after 10 consecutive rounds to avoid overfitting. During the training process, the data needs to be preprocessed. The Lida criterion is adopted to identify outliers, and the cubic spline interpolation method is used for filling. The interpolation interval is set at 5 to 15 minutes, and the maximum interpolation error is ≤0.08mm. Normalize the data to the range [-1, 1] using min-max scaling. The sliding window method is adopted to extract temporal features and generate a feature matrix, where the window size is set to 30 and the step size is set to 5. To ensure the feasibility of the experiment, a subway station foundation pit with dimensions of 198×20.1×17m was selected, and

the calculation range for the experiment extended 2-3 times the side wall of the pit. In this study, SPSS 26.0 was used for statistical analysis. All monitoring data were tested by Shapiro-Wilk normality test to determine whether they conformed to the normal distribution. One-way analysis of variance (ANOVA) was used to compare the significance of the differences among the four methods, with a significance level of 0.05. If $p<0.05$, the differences between groups were significant. In order to verify the reliability of bim-gru risk data monitoring method for displacement monitoring, the displacement prediction results were compared with cooperative game empowerment, relative conditional generation countermeasure network (rcgan) and grey correlation analysis (GRA), and the comparison results are shown in Figure 5.





Figure 5: Comparison of measuring point displacement prediction and real value

As shown in Figure 5(a), the BIM-GRU risk data monitoring method's displacement predictions for test data points 4, 5, 8, and 9 were nearly identical to the actual values, with relatively small errors. In Figure 5(b), Cooperative Game Empowerment's prediction for test data point 4 showed a small error, while predictions for test data points 5 and 10 exhibited significant discrepancies from the actual values. In Figure 5(c), the RCGAN risk data monitoring method predicted -0.18mm for test data point 4, with a difference of 0.48mm from the actual value. In Figure 5(d), the GRA risk data monitoring method's overall prediction curve fluctuated significantly, with predictions for test data points 5 and 6 showing discrepancies of 0.68mm and 0.54mm from the actual values, respectively. In summary, the BIM-GRU risk data monitoring method was better at fitting data trends and offered higher prediction accuracy. To further highlight the strain measurement capability of the BIM-GRU risk data monitoring method, its strain limit testing results were compared with those of Cooperative Game Empowerment, RCGAN, and GRA. The testing results are shown in Figure 6.



(a) Comparison of strain limits of BIM-GRU risk monitoring data methods

(b) Comparison of strain limits of weighted methods in cooperative game

(c) Comparison of strain limits of RCGAN risk data monitoring methods

(d) Comparison of strain limits of GRA risk data monitoring methods

Figure 6: Strain limit test results comparison chart

As shown in Figure 6(a), when the BIM-GRU risk data monitoring method was tested with warning values of +10mm and control values of +20mm for 12 measurement points, the average strain values were 699.48 $\mu\varepsilon$ and 899.98 $\mu\varepsilon$, respectively. In Figure 6(b), for Cooperative Game Empowerment, when the 12 measurement points were tested with a warning value of -10mm, the average strain value was 412.33 $\mu\varepsilon$. In Figure 6(c), for the RCGAN risk data monitoring method, the average strain value was 218.39 $\mu\varepsilon$ when tested with a control value of -20mm for the 12 measurement points. In Figure 6(d), the GRA risk data monitoring method produced an average strain value of 207.39 $\mu\varepsilon$ when tested with a control value of -20mm for the 12 measurement points. In summary, the BIM-GRU risk data monitoring method provided a preliminary assessment of the internal structure of the subway foundation pit. To further demonstrate the predictive capability of the BIM-GRU risk data monitoring method for risk data, comparisons were made between the predicted and actual values using the Cooperative Game Empowerment method, the RCGAN risk data monitoring method, the GRA risk data monitoring method, and additional comparisons with the Vehicle Driving State-GAN (VDS-GAN) based on dynamic traffic change feature sequence data generation, as well as the WaveGAN, an audio generation model based on deep learning. The comparison results are shown in Table 1.

Table 1: Comparison of discriminant and predicted values

Different risk data monitoring methods	Discriminant value	The t value of the discrimination value compared with BIM-GRU	The P-value of the discrimination value compared with BIM-GRU	Predicted value	The t value of the predicted value compared with BIM-GRU	The p value of the predicted value compared with BIM-GRU
BIM-GRU	0.196±0.012	/	/	0.213±0.004	/	/
Cooperative	0.312±0.019	6.932	<0.05	0.294±0.005	8.256	<0.05

game empowerment method						
RCGAN	0.403±0.013	10.247	<0.05	0.375±0.008	9.873	<0.05
GRA	0.412±0.014	11.568	<0.05	0.312±0.007	7.635	<0.05
VDS-GAN	0.288±0.004	5.896	<0.05	0.301±0.007	6.427	<0.05
WaveGAN	0.472±0.010	14.329	<0.05	0.461±0.006	12.758	<0.05

As shown in Table 1, the sample error rate generated by the BIM-GRU risk data monitoring method is 0.196±0.012. Statistical analysis shows that the discrimination error rates of RCGAN, GRA, cooperative game weighting method, VDS-GAN and WaveGAN are all significantly higher than those of BIM-GRU, and the differences among the methods are statistically significant (p<0.05). The sample error rate of the RCGAN risk data monitoring method was 0.312±0.019, and the predicted value was 0.294±0.005, which was 37.1% higher than the error rate of the BIM-GRU risk data monitoring method. The sample error rate of the GRA risk data monitoring method was 0.403±0.013, and the predicted value was 0.375±0.008, which was 51.3% higher than that of the BIM-GRU risk data monitoring method. Moreover, the predicted values of RCGAN, GRA, cooperative game weighting method, VDS-GAN and WaveGAN were significantly different from those of BIM-GRU (p<0.05). In conclusion, the BIM-GRU risk data monitoring method performs better in terms of data correlation within the same frame.

4.2 Evaluation of the BIM-GRU-based subway foundation pit support risk management system

To verify the superior performance of the subway foundation pit support risk management system based on the BIM-GRU risk monitoring data method, the study compared it with three other subway foundation pit support risk management systems: Cooperative Game Empowerment, RCGAN, and GRA. Risk events can be classified into three types: retaining structure risks, geological and hydrological risks, and construction operation risks. Among them, retaining structure risks include excessive displacement of underground continuous walls, which can lead to soil collapse behind the walls and rupture of adjacent pipelines. Geological and hydrological risks can cause water accumulation in the foundation pit and delay the excavation process. Construction operation risks include deviations in support installation and damage to monitoring points, which can distort data collection, delay risk warning responses, and increase the risk of instability of the support structure. Since the materials used in the subway foundation pit support structure can limit soil deformation and surface settlement, the study selected surface settlement monitoring points DBC3294-Z1Z4 and DBC32493-Y1Y4 as representative monitoring points for the experiment. The four risk management systems—Cooperative Game Empowerment, RCGAN, GRA, and BIM-GRU—were compared for surface settlement analysis, with the results shown in Figure 7.





Figure 7: Comparative analysis of surface settlement map




Temperature equipment monitoring of different systems

Figure 8: Comparison of temperature monitoring in different risk management systems of subway foundation pit support

As shown in Figure 7(a), when the distance from the edge of the foundation pit was approximately 100mm, the measured settlement value was -12.12mm, the BIM-GRU subway foundation pit support risk management system recorded a settlement value of -10.83mm, and the RCGAN subway foundation pit support risk management system recorded a maximum settlement value of -10.11mm. As shown in Figure 7(b), when the distance from the edge of the foundation pit was approximately 100mm, the measured settlement value was -12.88mm, and the BIM-GRU subway foundation pit support risk management system recorded a settlement value of -11.83mm, which was close to the measured value. In summary, as the distance from the foundation pit edge increased, the settlement value monitored by the BIM-GRU subway foundation pit support risk management system decreased. To demonstrate the monitoring accuracy of the BIM-GRU subway foundation pit support risk management system, its results were compared with those of the Cooperative Game Empowerment, GRA, and RCGAN subway foundation pit support risk management systems for subway equipment temperature monitoring. The monitoring results are shown in Figure 8.

As shown in Figure 8, the BIM-GRU subway foundation pit support risk management system measured a temperature of 55.21°C after the equipment had been running for 20s, with an error of -0.05°C. The GRA subway foundation pit support risk management system measured a temperature of 58.21°C after the equipment had been running for 40s, with an error of -0.13°C. The RCGAN subway foundation pit support risk management system measured a temperature of 61.01°C after the equipment had been running for 60s, with an error of -0.12°C. In summary, the BIM-GRU subway foundation pit support risk management system was able to effectively monitor equipment operating temperature and demonstrated certain practical feasibility. To further highlight the risk avoidance capability of the BIM-GRU subway foundation pit support risk management system, its performance was compared with the Cooperative Game Empowerment, GRA, and RCGAN subway foundation pit support risk management systems in terms of risk event failure effects. The comparison results are shown in Figure 9.



(a) Foundation pit support risk test 1 (b) Foundation pit support risk test 2

Figure 9: Comparison of failure effects of risk events results plot

As shown in Figure 9(a), The BIM-GRU subway foundation pit support risk management system successfully avoided Risk Event 1 a total of 9 times, while the RCGAN subway foundation pit support risk management system managed to avoid Risk Event 1 a total of 7 times. The Cooperative Game Empowerment subway foundation pit support risk management system failed to avoid Risk Event 3. As shown in Figure 9(b), the BIM-GRU subway foundation pit support risk management system successfully avoided Risk Event 16 a total of 9 times. In summary, the BIM-GRU subway foundation pit support risk management system was able to effectively avoid different risks, with a high avoidance efficiency.

5 Conclusion

In order to improve the safety of subway construction, a risk management system for subway foundation pit support is constructed based on the BIM-GRU risk data monitoring method. In the process of building the system, the advantages of the FAHP multi-objective comprehensive evaluation are used to evaluate and analyze the risk of foundation pit support in real time. The experimental results show that the displacement of the BIM-GRU method at monitoring point 4 is 0.31 mm, and the accuracy is higher than that of the cooperative game empowerment method, GRA, and RCGAN. The system successfully avoided risks 19 times, which was better than the other three systems. The measured temperature was 55.21 ℃ and the deviation was -0.05 ℃ after the subway equipment operated for 20s. The overall performance was excellent. To sum up, the BIM-GRU metro foundation pit support risk management system can effectively manage the metro foundation pit support structure. Although the BIM-GRU system has high monitoring accuracy and risk control ability, it is highly dependent on data. If there are errors or incompleteness in the data collection process, it may affect the final monitoring and analysis results. Therefore, in future research, the data acquisition and processing program will be further optimized, and more advanced sensor technology and data cleaning algorithms will be introduced to improve data quality, thus enhancing the system's performance.

Acknowledgment

This study is supported by Henan Provincial Key Discipline of Transportation Engineering and Funded Program of Key Scientific Research Projects in Higher Education Institutions of Henan Province (No. 25A580010).

References

[1] Han X, Ye F, Han X, Ren C, Song J, Zhao R. Mechanical responses of underground carriageway structures due to construction of metro tunnels beneath the existing structure: A case study. Deep Underground Science and Engineering, 2024, 3(2):231-246.

[2] Liu K, Liu Y, Kou Y, Yang X, Hu G. Efficiency of risk management for tunnel security of megaprojects construction in China based on system dynamics. Journal of Asian Architecture and Building Engineering, 2024, 23(2):712-724.

[3] Xu N, Guo C, Wang L, Zhou X, Xie Y. A three-stage dynamic risk model for metro shield tunnel construction KSCE Journal of Civil Engineering, 2024, 28(2):503-516.

[4] Li X, Yuan J, Zhang L, Yang D. Risk assessment of subway station fire by using a Bayesian network-based scenario evolution model. Journal of Civil Engineering and Management, 2024, 30(3): 279–294.

[5] Chen D, Zhou J, Duan P, Zhang J. Integrating knowledge management and BIM for safety risk identification of deep foundation pit construction. Engineering, construction and architectural management, 2022, 30(8):3242-3258.

[6] Jiang M. Construction Technology and Safety Risk Control Measures of Deep Foundation Pit Excavation. Journal of World Architecture, 2023, 7(2):24-29.

[7] Li D, Ma J, Wang C, Gao X, Fang M. A new method for piping risk evaluation on unconfined aquifers under dewatering of deep foundation pits. KSCE Journal of Civil Engineering, 2022, 26(8):3275-3286.

[8] Ma X, Dou Y. Water Accumulation Area Detection Model Based on Multi-Source Data Fusion and Swarm Intelligence Perception. Informatica, 2024, 48(23): 33-45.

[9] Aghamohammadi A, Beheshti Shirazi S A, Banihashem S Y, Shishechi S, Ranjbarzadeh R, Jafarzadeh Ghoushchi S, Bendechache M. A deep learning model for ergonomics risk assessment and sports and health monitoring in self-occluded images. Signal, Image and Video Processing, 2024, 18(2):1161-1173.

[10] Liu B, Han Q, Fu C, Zhang G, He Y, Li W. Development and engineering application of intelligent management and control platform for the shield tunneling construction close to risk sources. Journal of Intelligent Construction, 2024, 2(2): 1-12.

[11] Brintrup A, Kosasih E, Schaffer P, Zheng G, Demirel G, MacCarthy B L. Digital supply chain surveillance using artificial intelligence: definitions, opportunities and risks. International Journal of Production Research, 2024, 62(13):4674-4695.

[12] Xu X, Zheng Y, Lan X, Pan J, Wen Y. Numerical simulation analysis of controlling settlement by water-resisting curtain combined with recharge in deep foundation pit. Journal of Civil Engineering and Management, 2024, 30(7):566–580.

[13] Luo Z, Guo J, Han J, Wang Y. Research on the construction safety risk assessment of prefabricated subway stations in China. Engineering, Construction and Architectural Management, 2024, 31(4):1751-1787.

[14] Li W, Lu X, Wu M. Safety risk assessment model of a subway tunnel collapse system based on improved DOW-FFTA method. International Journal of Low-Carbon Technologies, 2024, 19(2):171-184.

[15] Deng Y, Liu Z, Song L, Ni G, Xu N. Exploring the metro construction accidents and causations for improving safety management based on data mining and network theory. Engineering, construction and architectural management, 2024, 31(9):3508-3532.

Electricity Market Price Forecasting Using a Hybrid Least Squares Support Vector–Adaptive Random Forest Model with Economic Indicators

Shiming Zhang*, Yingjin Ye, Yaru Han, Qifan Wu, Chengsheng Zhang
State Grid Fujian Economic Research Institute State Grid Fujian Electric Power Company Fuzhou, China
E-mail: zsm1016@126.com
*Corresponding author

Keywords: electricity, market price prediction, economic factors, energy market, short-term fluctuations, least squares support vector-fused adaptive random forest (LSSV-ARF)

Received: May 30, 2025

Electricity market price forecasting is an increasingly important aspect of modern energy systems, as it aids grid operators and market developers and informs pricing decisions. Forecasting electricity prices is challenging due to the significant fluctuations in electricity prices, unpredictable demand for electricity, and dynamic economic conditions. Also, traditional models cannot leverage multiple economic indicators, and they cannot adjust to changing conditions in the electricity market. In this research, a hybrid forecasting method was proposed based on machine learning (ML) models and energy macroeconomic indicators to provide a short-term and long-term analysis of factors affecting electricity price, depression, and inflation trends. The dataset, gathered from Kaggle, it consists of electricity prices, inflation rates, currency exchange rates, indices of production, and ratios of electricity supply and demand at time period January 2020 to July 2023. The method employed z-score normalization to provide uniformity across features, and utilized Principal Components Analysis (PCA) to successfully reduce dimensionality. The proposed method comprises a Least Squares Support Vector (LSSV) algorithm to capture declaratively non-linear relationships, and an Adaptive Random Forest (ARF) algorithm to examine more linear relationships based on a composite node-splitting condition applying two frequently used criteria. The LSSV–ARF model is executed in Python, validated with real-world and real-time marketplace data, and produces a MAPE (30.90±1.12), RMSE (3.53±0.21), MSE (12.50±0.87), and MAE (2.55±0.15), indicating strong predictive performance and real-world applicability. These results confirm the effectiveness of integrating economic energy indicators with ML algorithms for electricity price forecasting in managing energy pricing strategies.

Povzetek: Raziskava predstavlja hibridni pristop strojnega učenja, ki z makroekonomskimi kazalniki izboljša napovedovanje cen električne energije in podpira odločanje na energetskem trgu.

1 Introduction

The early 1990s, when competitive markets and deregulation procedures were introduced, the monopolistic and government-controlled nature of the power industry has been evolving. Electricity was exchanged differently under free-competitive market regulations because it is a non-storable commodity, and its production and use rely on the stability of the power grid [1]. The stability of modern energy systems depends on the operational role of the electricity market. Even so, the high level of electricity price volatility continues to be a major problem for energy producers, consumers, traders, and policymakers [2]. The nature of electricity markets is volatile, mainly because of the way supply works, fuel prices, rules, climate, and national economic conditions all impact them. Because electricity cannot be stored, the balance between production and consumption needs to be very precise [3]. The movement toward cleaner and autonomous energy systems renders it critical to accurately estimate electricity market rates for reliable, effective, and informed grid management [4]. In many countries, freely setting energy prices has moved the job of forecasting prices from the government to organizations that buy and sell electricity and manage the grid [5]. It was important for a variety of people to have accurate information on electricity prices. Energy producers can use it to optimize bidding strategies and generation planning. Consumers and industrial users can leverage forecasts to manage consumption and reduce costs [6]. The model depends on high-quality data, has computational difficulty during real-time adaptive

ensemble learning, and may have limits when it comes to generalizing to unknown economic shocks.

This research intends to develop a hybrid forecasting method that is a combination of two ML methods the new method called as Least Squares Support Vector and Adaptive Random Forest (LSSV-ARF) to forecast electricity market prices with a estimate that relies on electricity data and principal economic variables to model both short-term non-linear tendencies and adapt to long-term economic fluctuations.

- To propose a new hybrid model (LSSV-ARF) that combines nonlinear short-term modelling with adaptive economic learning, enabling better electricity price forecasts.
- To collect historical real-world electricity market and economic data from January 2020 to July 2023, which included fuel prices, inflation, demand, and supply-related indicators.
- To utilize z-score normalization on features to control their scales, and LSSV outputs were inserted into ARF inputs as further enriched features.
- To provide better predictive accuracy and better stability, reflecting price volatility with long-term trends in the baseline economic fundamentals.

Research covers background of the research, related work, and methodology, introduces the proposed LSSV-ARF model, explains the experiment setup, and analyses the findings with economic indicators. The research finishes by highlighting how its findings can be applied, listing the main shortcomings, and suggesting future research paths to improve electricity price forecasting in changing markets and economies.

2 Related works

An ML model was implemented to lower MAPE in smart grid residential load forecasting [7]. Using the ANFIS. An overall 17% improvement was observed in the accuracy of the model when comparing its MAPE values across the seasons. The prediction models were improved to help with daily electricity load forecasting for energy planning [8]. The performance of each model, such as AdaBoost, Bagging, SVR, and DT, was assessed by using error metrics, and features were reduced with both PCA and LDA. To suggest a EWS to keep market fluctuations under control and reduce expenses [9]. ML models use uncertainty indices to make predictions about energy equity prices. Nonlinear Autoregressive with Exogenous Inputs of NN for an economics project produced superior results for decision-makers and investors. Compared the LSTMs and SVM models for predicting short-term electricity load in terms of both speed and accuracy [10]. LSTM showed an advantage when there was a large data capacity, while SVM performed better for speed and accuracy with less data. The model was developed using an attention-based LSTM model and utilized load, price, wind, and solar data, as well as wavelet transform, addressing irregularities of using renewable energies [11]. Evolving the parameters in the model with crisscross optimization led to better generalization. When tested with a high-renewable dataset, the model was more accurate than other hybrid methods.

A new hybrid model was formed by combining SVR, GC (1,1), and RF to improve short-term load forecasting accuracy [12]. SVR was used for predicting GC (1,1) minimized long-term variability, and RF improved the results. Using actual data, the model reached MAPE values of 6.35% and 6.21%, showing that it forecasts more accurately. To assess electric vehicle energy use, advanced models XGBoost and LightGBM were compared with linear regression and neural networks [13]. Performance was measured using R^2, RMSE, and MAE. Forecasting energy consumption reliably, LightGBM showed superior accuracy compared to XGBoost and traditional methods. A DRNN approach was suggested in [14] for precise electricity price prediction in deregulated markets. The approach outperformed current approaches by learning the indirect relationship between price and external factors. The DRNN performed better than single SVM and hybrid SVM networks, according to data from the New England electricity market. To forecast electricity prices by incorporating market coupling, [15] suggested integrating feature selection techniques with an LSTM-based DL model. It effectively handled nonlinear time series data and demonstrated high accuracy in the Nordic market. However, the model's limitations reside in its dependence on the availability and quality of cross-market data.

LSTM-DNN and feature selection algorithms were used in [16] to examine how market interconnections affect the prediction of power prices. It demonstrated how integrated market features affect prediction and how feature selection was essential for precise forecasting. The analysis found that Nord Pool's pricing was significantly influenced by the German market. The hybrid forecast model for short-term power load and price prediction presented in [17] combined a DL algorithm, feature selection, and wavelet transform. To provide effective and sustainable electricity distribution networks, the model has been tested using load and pricing data from PJM, Spain, and Iran. The data-driven approach for long-term electricity market price prediction using Fourier analysis was presented in [18]. By predicting base evolution and significant price volatility, the model captured underlying market dynamics. The approach validated data-driven, finely-grained predictions. To improve real-time electricity price prediction, a decision-level LSTM fusion model was suggested as an alternative to traditional ML and data fusion solutions [19]. Using the method, IoT data can be processed asynchronously, requiring less bandwidth and computation. Experiments showed that when it involved

tracking nonlinear electricity prices, LSTM performed better than linear regression. By using correlated features in a Gradient Boosting–LSTM model, more accurate smart city load forecasting was achieved [20]. Adding correlated features increased accuracy, and RMSE and loss functions were used to assess performance. SHAP provided details on factors contributing to household energy consumption. With the approach, it was possible to make accurate forecasts and useful insights for sustainable city planning. To employ a model using deep learning (DL) [21] to obtain power cost data characteristics while forecasting profit and future trends. The model employed a variational autoencoder for the extraction of features and economic analysis methodologies. The model generated an annual profit of 5.36 million yuan and has an accuracy rate of 93.5%, indicating good generalization ability. The deep neural networks (DNN) [22] were used to reliably predict long-term electricity prices in Hungary. The method evaluated various network structures and considered the influence of environmental variables such as meteorological data and date/time. The results were particularly for short-term forecasts, while utilizing a DNN with a single convolutional long-short term memory (ConvLSTM) encoder. The research emphasized the significance of accurate permanent electricity price estimates because of their considerable variability. Cloud computing was revolutionizing the IT sector, yet energy-intensive data centres necessitate effective data placement as well as scheduling. An Extreme Gradient Boosting (XGBoost) model is used to forecast electricity prices, lowering energy consumption expenses in data centres. The model's efficacy was evaluated on an operational dataset, which resulted in a 2532% cost decrease.

Table 1 gives a comparative summary of ML and DL based models used for electricity load and price forecasting, comprising datasets, methods used, results, and limitations that indicate the history and pitfalls of energy forecasting research.

Table 1: Summary of related studies on electricity load and price forecasting methods

References	Dataset	Method	Result
Yousaf et al., [7]	Smart grid residential load	ANFIS	17% improvement in MAPE across seasons
Nooruldeen et al., [8]	Daily electricity load	AdaBoost, Bagging, SVR, DT with PCA and LDA	Enhanced energy planning forecasts
Alshater et al., [9]	Market equity data	ML with uncertainty indices	Suggested EWS to control fluctuations and expenses
Pallonetto et al., [10]	Electricity load	LSTM vs. SVM	LSTM is better with large data, and SVM is faster with small data
Meng et al., [11]	Load, price, wind, solar	Attention-based LSTM with wavelet transform	Accurate with high-renewable datasets
Fan et al., [12]	Actual load and price data	SVR + GC(1,1) + RF hybrid	MAPE: 6.35% and 6.21%
Ullah et al., [13]	Electric vehicle consumption	XGBoost, LightGBM, Linear regression, NN	LightGBM outperformed others in R^2, MAE, RMSE
Zhang et al., [14]	New England electricity market	Deep Recurrent Neural Network (DRNN)	Outperformed SVM and hybrid models
Li and Becker, [15]	Nordic market	LSTM + Feature Selection (Market coupling)	High accuracy in cross-market forecasting
Kim et al., [16]	Nord Pool + Germany	LSTM-DNN + Feature selection	Found intermarket influence on prices
Memarzadeh and Keynia, [17]	PJM, Spain, Iran	DL + Wavelet + Feature Selection	Sustainable, effective load/price prediction
Gabrielli et al., [18]	Long-term market price	Fourier analysis (data-driven approach)	Captured base evolution and volatility
Xie et al., [19]	IoT-based smart grid data	LSTM fusion model	Better than traditional ML for real-time predictions
Janjua et al., [20]	Smart city load	Gradient Boosting + LSTM + SHAP	High accuracy and interpretable features
Fu, [21]	Power cost & economic data	DL with Variational Auto Encoder + economic analysis	93.5% accuracy; 5.36M yuan profit/year
Dombi and Dulai, [22]	Hungarian electricity prices	DNN + ConvLSTM with environmental data	Effective short-term forecasting

Albahli et al., [23]	Cloud data center energy prices	Extreme Gradient Boosting (XGBoost)	25.32% reduction in electricity costs in data centers via forecasting and offloading

1.1. Research gap

The existing methods have shown important progress in electricity price and load forecasting with identifiable limitations. Many of the models are highly data-specific, like renewable energy data, market coupling data, and EV data, which reduces their generalizability. Several models, such as LSTM, DNN, and DRNN, require high computational costs and have limited interpretability. Several also rely on feature selection accuracy, thus resulting in poor performance if economic data is missing or noisy. Furthermore, most approaches only provide an analysis of either short-term fluctuations or long-term changes. Overall, the proposed LSSV–ARF method offer the solutions these weaknesses by combining economic data and historical price data to reveal short-term nonlinearities, applying LSSV, and using adaptive random forests for long-term economic changes. The proposed LSSV–ARF reveals an accurate, interpretable, and adaptable model with a low computational cost and reasonable forecasting performance.

3 Methodology

Figure 1 provides a visualization of the procedures for electricity price prediction using the LSSV–ARF method. The various steps in Figure 1 start with collecting data from economic indicators, followed by data preprocessing using Z-score normalization to scale the input data. After the preprocessing stage, Principal Component Analysis (PCA) is used to extract the predictive features. The prediction model parameterizes the model by combining Least Squares Support Vector (LSSV) and Adaptive Random Forest (ARF). Finally, the performance of the modeling process is evaluated using measures of prediction accuracy and reliability.




Figure 1: Overall process for predicting electricity price.

1.2. Dataset

The dataset, which combines historical data and macroeconomic indices, is a tool for predicting electricity market prices. It includes 1,344 daily records from a market scenario, such as the Industrial Production Index, inflation rate, currency exchange rate, economic energy parameters, and power market variables. A demand-supply ratio is also included in the dataset. This dataset utilizes data from January 2020 to July 2023, as shown in Table 2. The data was split into training (80%), testing (10%), and validation (10%) to ensure balanced model development, efficient hyperparameter tuning, and an unbiased assessment of forecasting performance.

Source:
https://www.kaggle.com/datasets/ziya07/economic-indicators-price-forecasting/data

Table 2: Input features

Feature Name	Category	Unit / Description
Day-ahead electricity price	Electricity Market Variable	USD/MWh
Electricity demand		MWh
Electricity supply		MWh
Demand–supply ratio		Ratio
Crude oil price	Macroeconomic Indicator	USD/barrel
Natural gas price		USD/MMBtu
Coal price		USD/ton
Inflation rate		Percentage (%)

Currency exchange rate		Local currency per USD
Industrial production index		Index value (base year normalized)

1.3. Data preprocessing using Z-score normalization

Z-score normalization is used as an important data preprocessing technique to standardize the different sets of input features for electricity market price forecasting. The dataset contains variables with different scales/units, for example, the electricity price ($\$/MWh$), fuel costs with different currency units, inflation rate (percentage), and industrial index. In this way, Z-score normalization improves model convergence, numerical stability, and forecasting performance.

A statistical method for scaling numerical characteristics based on the mean and standard deviation is called Z-score normalization. Without altering the variations in the ranges of values, it normalizes various data formats to a single scale. The Z-score normalized value y_j for the j^{th} data point w_j is calculated using Equation (1).

$$y_j = \frac{w_j - \mu}{\sigma} \tag{1}$$

The initial feature value is denoted by w_j, the meaning of μ, the standard deviation by σ, and the normalized output by y_j.

1.4. Feature extraction using Principal Component Analysis (PCA)

PCA was used to derive the most important features from high-dimensional electricity and economic datasets efficiently in a way that provides improved forecasting accuracy while reducing the complexity of the models. PCA converts the original feature space into a lower-dimensional space and picks out only the components that retain the most variance in the data. This reduces redundancy, allows the model to generalize better, and reduces the overall chance of overfitting in the LSSV–ARF model. The transformed features are formed using the top components from the eigenvectors of the covariance matrix, in the following Equation (2).

$$X_{PCA} = X_{centred} \cdot W \tag{2}$$

Where $X_{centred}$ is the centred input data and W is the matrix of selected eigenvectors.

1.5. Prediction model for least squares support vector fused adaptive random forest (LSSV-ARF)

The hybrid LSSV–ARF forecasting model combines two forms of machine learning with different forecasting capabilities to improve the forecasting of electricity prices. The LSSV method was used to model nonlinear short-term price variations. LSSV can satisfy the optimization of non-linear equations using an LSSV approach, and regressions can be computed rapidly with accuracy because LSSV accommodates fewer hyper parameters. The ARF algorithm models long-term economic patterns in electricity prices and climatic dynamic market behavior. The ARF provides additional flexibility to traditional random forests by applying adaptive node-splitting strategies based on a weighted combination of Gini index and information gain, allowing for flexibility to learn to adapt to electricity prices and trends in economic data.

Table 3 depicts that the LSSV-ARF hybrid model utilizes LSSV with an RBF kernel and ARF with adaptive split as a hybrid model. The LSSV makes short-term forecasts from normalized data, which is then added as features in the training data, permitting ARF to create short-term forecasts. This hybridization combines the nonlinear pattern identification of LSSV and the economic adaptability of ARF for long-term forecasting to improve electricity price forecasting.

Table 3: Hyper parameter of proposed LSSV–ARF

Hyperparameter	**Typical Range/Value**
γ (Regularization)	0.01 – 100
σ^2 (RBF Kernel Width)	0.1 – 10
ε (Loss Insensitivity)	0.001 – 0.1
n_estimators	100 – 500
max_features	‘sqrt’, ‘log2’, or fixed value
α, β (Split Weights)	$0 \leq \alpha, \beta \leq 1$ and $\alpha + \beta = 1$

Least Squares Support Vector (LSSV): The LSSV model is applied to model the nonlinear and short-term changes in electricity market prices; it takes input data, maps it to some high-dimensional feature space using kernel function(s), which enables its nonlinear dependencies to be captured for a more fitted regression. A variation of standard SVM, the LSSV replaces the inequality constraints with equality constraints and minimizes the least squares loss such that the problem can be solved using a linear equation system. This reformulates the computational complexity of a standard SVM (quadratic programming) into a simpler form. LSSV for regression with the RBF kernel has only two hyper

parameters, while LSSV for regression includes the bias term in the solution. Let the dataset be shown in Equation (3).

$$\begin{bmatrix} \underset{x,a,f}{min}\, I_o(x,f) = \frac{1}{2}x^S x + \gamma\frac{1}{2}\sum_{l=1}^{M} f_l^2 \\ such\ that\ f_l = z_l - [x^S\phi(w_l) + a], l = 1,..,M \end{bmatrix} \tag{3}$$

Here, $\xi = [\xi 1,\ldots,\xi M]^s$ is the error vector, $w \in R^{\,f}$ is the weight vector in feature space, and $\phi: f\ m \to f^a$ is the nonlinear mapping function. The dual formulation is developed as shown in Equation (4).

$$\begin{bmatrix} Solve\ in\ b,a: \\ \begin{bmatrix} 0 & J^S \\ 1_u\ \Omega + \gamma^{-1}J_M \end{bmatrix}\begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} 0 \\ z \end{bmatrix} \end{bmatrix} \tag{4}$$

Where $z = [z_1, \ldots, z_M]^S$ 1_u is an M-dimensional vector $= [1, \ldots,1]^2, \alpha = [\alpha_1,..,\alpha_M]^S$, J_M is an M-dimensional identity matrix, and $\gamma \in Q$ is a variable for regularity. The following Equation (5) is how the kernel technique is used.

$$\Omega_{l,k} = \varphi(w_l)^S\varphi(w_k) - L(w_l,w_k)\ l = k = 1,..,M \tag{5}$$

Where the kernel function L is specified. Equation (6) contains the resultant LSSV model for function estimation.

$$z = N(w) = \sum_{l=1}^{M} \alpha_l\varphi(w_l)^2\ \varphi(w) + a \tag{6}$$

Where w_l is the training data, $l = 1,2 \ldots, M, w$ is the latest input case, $b_l, a \in Q$ are the results and RBF is selected as the kernel function l.

Adaptive Random Forest (ARF): Random Forest (RF) is a standard ensemble learning method that creates many decision trees that are trained with bootstrapped data subsets and combines the outputs of the trees, hoping that pooling the individual outputs will provide a more accurate and robust outcome. Each tree in the forest is trained on random sets of features; this randomness reduces overfitting and increases generalization to unseen data. For regression, the predicted final output is the average of each tree's output in Equation (7).

$$\hat{y} = \frac{1}{T}\sum_{T=1}^{t} h_t(x) \tag{7}$$

Here $h_t(x)$ is the prediction from t^{th} tree, and T is the total number of trees.

The ARF was used to improve electricity price prediction by employing an ARF model for feature selection, interpretation, and prediction in existing energy forecasting systems. The ARF is a step in defining the feature space to optimize electricity market modeling. The ARF removes the less related features, defines a collection of decision trees, performs adequate learning, followed by the performance monitoring of each decision tree, identifying the most efficient trees. The ARF is capable of operating in a binary or a multi-class classification task, such as price fluctuation level identification or peak-demand scenario categorization. The random forest models combine the predictions of each decision tree in the training, generating a stronger prediction through an ensemble of decision trees as expressed in Equation (8).

$$Gini_{impurity} = \sum_{l=0}^{m} RP(j_{PC})\big(1 - RP(j_{PC})\big) \tag{8}$$

In Equation (8), $RP(j_{PC})$ is the probability of selecting an element of class j_{PC} at node l, where m is the number of classes considered in the Gini impurity calculation, when employing ARF within the dynamic pricing model, it gave this system the ability to target the high impacts of features like fuel price or demand ratios which enabled more accurate, interpretable and adaptable price forecasts for different market conditions. The ARF consists of numerous simple decision trees to create an ensemble model to assist in minimizing the prediction error in electricity price forecasting. The ARF has computational simplicity and allows for the development of many inexpensive decision trees based on subsets of market features, patterns over time, economic indicators, and demand trends, which can then be consolidated using a majority vote or simple average of the predictions to provide one consolidated and robust prediction. The ensemble-learning method reduces computational effort and cost while improving reliability in electricity market price forecasting. ARF provides computational advantage, scalability, and interpretability for real-time energy forecasting. Collaborative construction of market features advances fine-grained decision-making, improving forecasting performance outcomes.

The hybrid approach utilizes the advantages of different ML models in a combined state to use the complementary benefits from these models to improve the accuracy in predictions. By using different models, it can capture complex patterns and dynamic variations in a variety of electricity market prices and economic variables, as shown in Algorithm 1.

Algorithm 1: Hybrid LSSV–ARF

Input: Dataset D = {X, Y}

Output: Predicted prices Y_pred

1. Preprocess Data:

- Normalize features with Z-score

- Apply PCA to reduce dimensionality

- Split D into training and testing sets

2. Train LSSV Model:

- Compute RBF kernel matrix K

*- Solve: [0 1^T; 1 K + γ^{-1}I] * [b; α] = [0; Y_train]*

*- Predict: z_LSSV(x) = Σ α_i * K(x_i, x) + b*

3. Train Adaptive Random Forest (ARF):

- Build T trees using bootstrapped samples and adaptive splitting

- Predict: y_ARF(x) = Average(tree_t.predict(x)) over all T trees

4. Fuse Predictions:

*- Final prediction: Y_pred = λ * z_LSSV + (1 - λ) * y_ARF*

Return Y_pred

2 Results and discussion

The findings showed that the LSSV–ARF model greatly improved the accuracy of electricity price forecasting. The results of comparative analysis indicated lower error metrics for LSSV–ARF than traditional models, which indicated the LSSV–ARF model was able to identify and capture short-term variability in the price signals while also adhering to long-term economic trends under a dynamic and evolving market.

2.1. System configuration

The experiments were conducted in a high-performance computing facility utilizing Python 3.10. We used a multi-core processor and a GPU, and there was sufficient RAM in the workstation that was able to manage the data provided and perform all training and testing of the models. Training the model on the full dataset (1,344 daily records) required approximately 142 seconds, and prediction on the test set required 6 seconds, as shown in Table 4.

Table 4: Experimental Setup

Specification	Details
Programming Language	Python
Python Version	3.10
CPU	Intel Core i7-11700 @ 2.50GHz
GPU	NVIDIA GeForce RTX 3060 (6GB VRAM)
Operating System	Windows 11 Pro 64-bit
RAM	32 GB DDR4 @ 3200 MHz

2.2. Research output

The correlation heat map shows some weak correlations between electricity price and individual variables, including demand (-0.01), supply (-0.03), and demand-supply ratio (0.01) in Figure 2. However, there are strong correlations between features like demand vs demand-supply ratio: 0.75, and weak correlations between features and price, which are related to feature interdependencies with the dataset and not electricity price prediction.




Figure 2: Correlation heat map for economic indicators feature.

The time series of natural gas, crude oil, and coal fuel prices from January 2020 to July 2023 is displayed in Figure 3. While the Natural Gas price remains relatively stable and low, with minor fluctuations, the Crude Oil and Coal prices are highly volatile and frequently spike, particularly in the latter part of the time series. The proposed LSSV-ARF prediction method was used to predict the fuel price trend. This suggests that the Crude Oil and Coal market conditions are more susceptible to fluctuations, likely due to global demand, geopolitical events, and supply disruptions, while Natural Gas market conditions remain comparatively stable.




Figure 3: Fuel prices from January 2020 to July 2023 used in the LSSV-ARF method.

The fluctuations in electricity prices, expressed in USD/MWh, between January 2020 and July 2023 are displayed in Figure 4. Many fluctuations reveal significant volatility, indicating that electricity prices are highly volatile based on demand, supply, fuel prices, and market dynamics. While there are fluctuations from day to day, over time the trend is relatively stable, with some significant sharp peaks and dips. These consistent oscillations demonstrate the impact of external economic factors, seasonal factors, and geopolitical factors on electricity pricing. The proposed hybrid optimization-based prediction method was used to predict the electricity prices.




Figure 4: Fluctuations in electricity prices prediction for LSSV-ARF.

In Figure 5, the time series for the Industrial Production Index (IPI) is one of the economic input features that is used to provide contextual input for electricity price predictions. The proposed model does not predict this feature but uses it as input for electricity price predictions.




Figure 5: Financial growth trend prediction using LSSV-ARF.

A feature importance analysis utilizing the ARF component. Results showed electricity demand (34%) and demand–supply ratio (26%) as the most important predictors of electricity demand. Macroeconomic indicators, such as crude oil price and inflation rate, were useful for long-run trend modelling and confirmed the model's interpretability and robustness, as shown in Figure 6.




Figure 6: Feature Importance in LSSV-ARF Model

2.3. Comparative analysis

This subsection provides the evaluation criteria utilized to measure the performance of the suggested LSSV-ARF model for forecasting electricity prices, including

XGBoost [23], RF [23], and SVR [23]. The outcome illustrates that the suggested hybrid model immensely outperforms conventional methods in precision and stability.

- MAE considers the average size of errors among predicted and actual electricity prices, without considering their direction. Lower MAE indicates better prediction accuracy and overall model performance.
- MAPE gives model prediction error as a percentage, indicating how much the prediction deviates from actual average prices; lower MAPE means more accurate and reliable forecasting of electricity prices.
- RMSE calculates the square root of the average squared differences of predicted and actual values, repeatedly indicated in future work to suggest RMSE also depicts the standard deviation of prediction errors.
- MSE computes the average of the squared differences of predicted and actual values, while giving an overall indication of prediction accuracy, but it is especially sensitive to large errors.

Table 5: Evaluation of predictive accuracy across different algorithms

Model	MAPE	RMSE	MSE	MAE
XGBoost	40.90	9.25	15.66	3.74
RF	71.54	11.25	98.36	7.98
SVR	44.91	12.11	99.2	7.67
LSSV-ARF [Proposed]	30.90 $\pm$ 1.12	3.53 $\pm$ 0.21	12.50 $\pm$ 0.87	2.55 $\pm$ 0.15

Table 5 and Figure 7 illustrate the evaluation of predictive accuracy of the four algorithms, XGBoost, RF, SVR, and the LSSV–ARF model, which was proposed, using the standard error metrics. The LSSV–ARF obtained the best performance, as compared to the others, as it provided the lowest MAPE (30.90), RMSE (3.53), MSE (12.50), and MAE (2.55). The other models had a higher error, and the accuracy of prediction decreased. These results demonstrate that the LSSV–ARF is a superior predictive model, when compared with the conventional models, in terms of the level of prediction precision.

To ensure a comprehensive appraisal of performance, we monitored RMSE and MSE alongside MAE and MAPE. For evaluative purposes, ten independent runs were used to assess variability of results, and a paired t-test was used to verify statistical significance. The LSSV–ARF model reported statistically significantly better results than all benchmarks with significance ($p < 0.01$) on every improvement, demonstrating more accurate, robust, and reliable performance across all measures.




Figure 7: Performance of electricity price prediction methods

The proposed model LSSV–ARF predicts electricity prices one day ahead, relying on 1,344 daily records from January 2020 to July 2023. 1,000 bootstrap resamples were constructed to ensure effect sizes were statistically reliable to report 95% confidence intervals for analyses. To further examine performance related to volatility, particularly low, medium, and high volatility levels were segmented for analysis, as shown in Table 6.

Table 6: Performance evaluation by volatility regime

Volatility Regime	MAE	MAPE
Low Volatility	0.65	4.12
Medium Volatility	0.81	5.39
High Volatility	0.94	6.21

The LSSV-ARF model employs regularization (C = 1.2) and has been tuned to prevent overfitting by ensemble averaging with adaptive node-splitting. Hyper parameters were tuned using 5-fold cross-validation. Ten independent runs of cross-validation showed minimal variation in fitted error, indicating that the model was stable and robust, and demonstrated strong generalization to unseen data, as shown in Table 7.

Table 7: 5-fold cross-validation results

Model	MAPE	RMSE	MSE	MAE
LSSV-ARF [Proposed]	30.90 $\pm$ 1.12	3.53 $\pm$ 0.21	12.50 $\pm$ 0.87	2.55 $\pm$ 0.15

2.4. Discussion

Despite their high accuracy, XGBoost [23] can be resource-intensive and exposed to overfitting of noisy data, and RF [23] models can exhibit high variance on large datasets and lack interpretability. SVR [23] has a difficult time scaling for large datasets, and can be sensitive to the kernel and parameters selected. All three models can have additional preprocessing to complete, as well as challenges due to non-linear fluctuations of electricity prices, which have the potential to greatly influence performance and accuracy.

The LSSV-ARF model addresses the drawbacks of the by XGBoost [23], RF [23], and SVM [23] utilizing LSSV and ARF together, while providing a more interpretable and computationally efficient approach. There is a more optimization from linear equations, as opposed to complicated quadratic programming, which saves on training time and cost; the ARF selects the splitting attributes when splitting nodes automatically, which allows the ARF to better track changing patterns without overfitting; and it has fewer hyper parameters. Overall, this combination enhances forecasting performance while interpreting the model, provides scale for larger datasets, and robustness for complex environments with limited data in dynamically data-limited environments such as the electricity market.

2.5. Real-world implications

In real electricity markets, price forecasting is critical for energy suppliers, system operators, and policy makers. The LSSV-ARF model suggested here is suitable for day-ahead electricity price forecasting using historical demand, climate data, and economic factors. An example would be to enable a utility company to reduce operational costs by managing energy procurement with accurate price forecasts, providing the most productive avenues for action during those periods when operational costs create volatility, enabling them to make more profit or less loss and deliver power at a lower cost to consumers.

3 Conclusion

The new electricity market price forecasting model presented in this research effectively combines advanced machine learning techniques with significant economic energy indicators. By including such variables as fuel prices, inflation, exchange rates, industrial production indexes, and demand-supply ratios in addition to historical price and load data, the model captures short-term variability as well as long-term economic patterns. The Z-score normalization method was applied during preprocessing to normalize input features, maintaining uniform scale and improving model stability. The suggested LSSV-ARF ensemble model, integration of Least Squares Support Vector and Adaptive Random Forest for predicting electricity prices, was implemented using the Python platform and tested with actual data. Achieving an MAPE (30.90 ± 1.12), RMSE (3.53 ± 0.21), MSE (12.50 ± 0.87), and MAE (2.55 ± 0.15), indicating its forecasting accuracy. The model is dependent on having quality and accessible historical and economic data. Further, when deployed in a real-time situation, the model may present complications. It requires significant computational resources to train. Further, it requires even more computational resources depending on the hyperparameter tuning. Future work could focus on reducing the computational complexity of the model to facilitate faster real-time predictions. Integrating additional data sources, such as renewable energy generation forecasts and weather conditions, may further improve accuracy.

References

[1] Acaroğlu H, García Márquez FP (2021) A comprehensive review of the electricity market price and load forecasting based on wind energy. *Energies* 14(22):7473. https://doi.org/10.3390/en14227473

[2] Cheng L, Huang P, Zhang M, Yang R, Wang Y (2025) Optimizing electricity markets through game-theoretical methods: strategic and policy implications for power purchasing and generation enterprises. *Mathematics* 13(3):373. https://doi.org/10.3390/math13030373

[3] Agbede OO, Akhigbe EE, Ajayi AJ, Stanley N (2024) Financial modeling for global energy market impacts of geopolitical events and economic regulations. *Magna Scientia Adv Res Rev* 10(2):272–296. https://doi.org/10.30574/msarr.2024.10.2.0049

[4] Cui S, Tian J (2024) Analysis and calculation of the marginal electricity price of nodes with network loss from the perspective of an intelligent robot considering digital signal processing technology. *Informatica* 48(14). https://doi.org/10.3390/app14114528

[5] Bojnec Š, Križaj A (2021) Electricity markets during the liberalization: the case of a European Union country. *Energies* 14(14):4317. https://doi.org/10.3390/en14144317

[6] Nebey AH (2024) Recent advancements in demand-side energy management systems for optimal energy utilization. *Energy* Rep 11:5422–5435.

[7] Yousaf A, Asif RM, Shakir M, Rehman AU, Adrees MS (2021) An improved residential electricity load forecasting using a machine-learning-based feature selection approach and a proposed integration strategy. *Sustainability* 13(11):6199. https://doi.org/10.3390/su13116199

[8] Nooruldeen O, Baker MR, Aleesa AM, Ghareeb A, Shaker EH (2023) Strategies for predictive power: machine learning models in city-scale load

forecasting. *E-Prime Adv Electr Eng Electr Energy* 6:100392. https://doi.org/10.1016/j.prime.2023.100392

[9] Alshater MM, Kampouris I, Marashdeh H, Atayah OF, Banna H (2025) Early warning system to predict energy prices: the role of artificial intelligence and machine learning. *Ann Oper Res* 345(2):1297–1333. https://doi.org/10.1007/s10479-022-04908-9

[10] Pallonetto F, Jin C, Mangina E (2022) Forecast electricity demand in commercial buildings with machine learning models to enable demand response programs. *Energy AI* 7:100121. https://doi.org/10.1016/j.egyai.2021.100121

[11] Meng A, Wang P, Zhai G, Zeng C, Chen S, Yang X, Yin H (2022) Electricity price forecasting with high penetration of renewable energy using an attention-based LSTM network trained by crisscross optimization. *Energy* 254:124212. https://doi.org/10.1016/j.energy.2022.124212

[12] Fan GF, Yu M, Dong SQ, Yeh YH, Hong WC (2021) Forecasting short-term electricity load using hybrid support vector regression with grey catastrophe and random forest modeling. *Util Policy* 73:101294. https://doi.org/10.1016/j.jup.2021.101294

[13] Ullah I, Liu K, Yamamoto T, Al Mamlook RE, Jamal A (2022) A comparative performance of machine learning algorithms to predict electric vehicles' energy consumption: a path towards sustainability. *Energy Environ* 33(8):1583–1612. https://doi.org/10.1177/0958305X211044998

[14] Zhang C, Li R, Shi H, Li F (2020) Deep learning for day-ahead electricity price forecasting. *IET Smart Grid* 3(4):462–469. https://doi.org/10.1049/iet-stg.2019.0258

[15] Li W, Becker DM (2021) Day-ahead electricity price prediction applying hybrid models of LSTM-based deep learning methods and feature selection algorithms under consideration of market coupling. *Energy* 237:121543. https://doi.org/10.1016/j.energy.2021.121543

[16] Kim J, Oh S, Kim H, Choi W (2023) Tutorial on time series prediction using 1D-CNN and BiLSTM: a case example of peak electricity demand and system marginal price prediction. *Eng Appl Artif Intell* 126:106817. https://doi.org/10.1016/j.engappai.2023.106817

[17] Memarzadeh G, Keynia F (2021) Short-term electricity load and price forecasting by a new optimal LSTM-NN based prediction algorithm. *Electr Power Syst Res* 192:106995. https://doi.org/10.1016/j.epsr.2020.106995

[18] Gabrielli P, Wüthrich M, Blume S, Sansavini G (2022) Data-driven modeling for long-term electricity price forecasting. *Energy* 244(Part B):123107. https://doi.org/10.1016/j.energy.2022.123107

[19] Xie K, Luo Y, Li W, Chen Z, Zhang N, Liu C (2022) Deep learning with multisource data fusion in electricity internet of things for electricity price forecast. *Wirel Commun Mob Comput* 2022(1):3622559. https://doi.org/10.1155/2022/3622559

[20] Janjua JI, Ahmad R, Abbas S, Mohammed AS, Khan MS, Daud A, Abbas T, Khan MA (2024) Enhancing smart grid electricity prediction with the fusion of intelligent modeling and XAI integration. *Int J Adv Appl Sci* 11(5):230–248. https://doi.org/10.21833/ijaas.2024.05.025

[21] Fu B (2025) Variational Autoencoder-based high-dimensional feature extraction for economic analysis of power cost data. *Informatica* 49(25). DOI:10.31449/inf.v49i25.8012

[22] Dombi G, Dulai T (2022) Hourly electricity price forecast for short-and long-term, using deep neural networks. *Acta Univ Sapientiae Inform* 14(2):208–222. DOI:10.2478/ausi-2022-0013

[23] Albahli S, Shiraz M, Ayub N (2020) Electricity price forecasting for cloud computing using an enhanced machine learning model. *IEEE Access* 8:200971–200981.https://doi.org/10.1109/ACCESS.2020.3035328

APPENDIX

$machine\ learning = ML$	$Neural\ Networks = NN$
$Mean\ Absolute\ Percentage\ E$ $= MAPE$	$Long\ Short - term\ Memory\ Network$ $= LSTMs$
$adaptive - network - based\ fuzzy\ inference\ sys$ $= ANFIS$	$Support\ vector\ machine = SVM$
$Support\ Vector\ Regression = SVR$	$grey\ catastrophe = GC$
$Decision\ Tree = DT$	$random\ forest = RF$
$Principal\ Component\ Analys$ $= PCA$	$least\ squares\ support\ ve$ $= LSSV$
$Linear\ Discriminant\ Analysis$ $= LDA$	$quadratic\ programs = QP$
$Early\ Warning\ System = EWS$	$Radial\ Basis\ Function = RBF$
$Mean\ Absolute\ Error = MAE$	$deep\ neural\ networks = DNN$
$Extreme\ Gradient\ Boosting = XGBoost$	$Information\ Technology = IT$

Exploration of the Development Path of Rural Smart Agriculture Driven by Artificial Intelligence

Qiang Zhou
Henan Finance University, Zhengzhou 450046, China
E-mail: Zq26551399@163.com

Keywords: quantum neural network, smart agriculture, soil moisture prediction, precise irrigation, development path

Received: June 27, 2025

Against the backdrop of global climate change and increasing constraints on agricultural resources, developing smart agricultural technologies is a key path to achieving food security and sustainable development. This study aims to investigate the development path of rural smart agriculture driven by artificial intelligence, with a focus on addressing the bottlenecks in traditional agricultural prediction models in terms of accuracy, efficiency, and resource consumption. This study focuses on winter wheat and summer corn rotation farmland, and collects environmental data through a Pico W+ESP32-CAM sensor network. After wavelet denoising, outlier detection, and Kalman smoothing interpolation preprocessing, the soil moisture prediction effects of various models are compared. Based on the predicted fruit, rule-based irrigation control is implemented. The core indicators include crop yield, protein and vitamin content, water and fertilizer usage, and model performance (response time, error, trainable parameters, etc.). Quantum Neural Network-Back Propagation model is constructed by combining an IoT multi-sensor data acquisition system. This study innovatively integrates quantum bits and parameterized quantum gates into the prediction module. The results showed that in terms of prediction, the accuracy of the soil moisture prediction model reached 97.48%, which was 10.29% higher than that of the traditional Back Propagation Neural Network (87.19%). The model response time was only 1.27 seconds, and the computational resource utilization rate has been reduced to 23.18%, meeting the real-time decision-making needs of farmland. The irrigation strategy based on the predicted results increased water resource utilization efficiency by 47.57%, reduced fertilizer usage by 19.41%, and increased economic benefits per unit area by 28.30%. The research method has achieved high-precision dynamic prediction of soil moisture. This research verified the feasibility of artificial intelligence algorithms in agricultural edge computing scenarios, provided a closed-loop solution of "perception decision execution" for rural smart agriculture, and promoted the transformation of agricultural production to precision and low-carbon.

Povzetek: Raziskava predstavlja pametno kmetijstvo, ki z IoT-senzorji in napovednim modelom (kvantna nevronska mreža) omogoča natančno napoved talne vlage ter avtomatizirano namakanje, kar izboljša pridelke in kakovost ter hkrati zmanjša porabo vode, gnojil in računske vire.

1 Introduction

In the process of globalization, climate change and agricultural resource constraints have become increasingly prominent, posing a serious threat to food security and sustainable development [1, 2]. Traditional agriculture relies heavily on human and material resources, with a relatively extensive production method and low resource utilization efficiency, making it difficult to adapt to the current complex and ever-changing environment [3]. At the same time, population growth has led to a continuous growth in the requirement for food and agricultural products, and agriculture urgently needs transformation [4]. In this context, Smart Agriculture (SA) combined with Artificial Intelligence (AI) has emerged. SA, with the help of modern information technology, is expected to achieve a leapfrog improvement in agricultural production efficiency and become a key breakthrough in solving agricultural difficulties [5, 6]. Numerous scholars have conducted extensive research on SA. In terms of data collection, Internet of Things (IoT) technology has been widely applied. Pincheira et al. proposed the use of sensor-based unmanned vehicles to collect accurate agricultural data. Practical application showed that this method could collect accurate dynamic data [7]. Ahmed et al. designed a blockchain-based "cluster head sleep scheduling" data aggregation method to address multi-sensor data redundancy and energy consumption in intelligent agriculture. This method could reduce energy consumption, extend network lifespan, and achieve efficient data collection and pest attack prevention and control [8]. Mohapatra et al. developed an intelligent agriculture model to improve the communication efficiency of IoT devices and soil monitoring level in agriculture. This model could optimize agricultural communication and soil monitoring [9].

In terms of decision support, Akhter and Sofi proposed an apple disease prediction model to improve orchard yield. Introducing this model into traditional agricultural production has improved the quality and yield of orchards [10]. Ali et al. used the IoT, Wireless Sensor Networks (WSN), and Sensor Cloud (SC) to collect and analyze agricultural data to provide digital solutions for agriculture. The experimental results indicated that this method could provide more agricultural development plans [11]. Sharma et al. proposed an unmanned weed control technology to integrate AI with agricultural technology. This method reduced manpower and could also be applied in unmanned spraying [12].

The current traditional agricultural prediction models are prone to local optima, slow convergence, and limited accuracy, making it difficult to meet real-time and accurate decision-making needs. Most studies focus on single technology applications and lack systematic solutions, making it difficult to achieve intelligent transformation of the entire agricultural production chain. To accurately predict agricultural data and explore the development path of rural SA driven by AI, a QNN-BP model that integrates Quantum Neural Network (QNN) and Back Propagation (BP) neural network is proposed. Combined with multiple sensors in the IoT, a "perception prediction decision execution" loop is formed to address the above issues. The research innovations are as follows: (1) Key input features such as soil temperature and humidity, meteorological data, etc. are transformed into quantum state representations, and the model's search for the global optimal solution is accelerated by the superposition characteristics of quantum bits; (2) By parameterizing quantum gates, a shallow quantum network structure is constructed, which reduces hardware resource requirements while retaining the advantages of quantum computing; (3) The quantum annealing technique is used to optimize the initial weights of the model, and the classical BP algorithm is combined to fine tune the parameters, avoiding gradient vanishing and balancing the convergence speed and prediction accuracy of the model. Summary Table of Review and Methods of This Study as shown in Table 1.

Table 1: Summary table of review and methods of this study

Technology Domain	Researcher	Method	Key Application Outcomes
IoT Data Collection	Pincheira et al. [7]	Sensor-based Unmanned Ground Vehicle (UGV) Data Collection Method	Precise dynamic data collection
	Ahmed et al. [8]	Blockchain-enabled Cluster Head Sleep Scheduling	Reduces energy use; extends network life; aids pest control
	Mohapatra et al. [9]	IoT-Based Agricultural Intelligent Monitoring Model	Improves communication efficiency; enhances soil monitoring
Agricultural Decision Support	Akhter and Sofi [10]	Apple Disease Prediction Model	Improves orchard yield/quality; aids disease control
	Ali et al. [11]	IoT, WSN, SC	Reveals data correlations; improves digital plans
	Sharma et al. [12]	AI-Integrated Unmanned Weed Control Technology	Reduces labor input; adapts to unmanned spraying
Data Collection - Prediction - Decision Loop	This Study	QNN-BP + IoT Data Acquisition System (DAS)	Realize high-precision prediction of soil moisture, optimize agricultural resource utilization efficiency and unit area economic benefits

2 Methods

2.1 Rural smart agriculture data collection

Rural Smart Agriculture (RSA) is a modern agricultural model that relies on digital technologies, including AI, big data, the IoT, and blockchain, to achieve efficient resource allocation and coordinated industrial development through intelligent transformation of the entire agricultural production, operation, management, and service chain [13-15]. Agricultural IoT, through sensing, transmitting, and processing agricultural production data, helps achieve intelligent monitoring and precise management, improving production efficiency and resource utilization. The architecture of agricultural IoT is shown in Figure 1.




Figure 1: Architecture of agricultural IoT

In Figure 1, the IoT architecture typically consists of the layers of perception, transport, service, and application. As the bottom layer, the perception layer is responsible for sensing and collecting various data in the

environment through sensors and other devices, and is the data source of the entire IoT. The transport layer mainly transmits the data collected by the perception layer to ensure a stable flow of data between nodes within the system. The service layer is the core part of the IoT, responsible for processing large amounts of transmitted data, conducting deep mining, and intelligent management of the data. The application layer directly faces users and integrates IoT technology into SA through interaction with the service layer, providing specific application scenarios and services, and bringing an intelligent experience and value to users. To explore the development path of RSA, data analysis is indispensable. Before analyzing agricultural data, it is necessary to first collect the data. To effectively collect agricultural data, this study combined multiple sensors to establish a DAS. Figure 2 shows the framework of the hardware structure.




Figure 2: Hardware structure of DAS

In Figure 2, the system hardware structure adopts a modular design, including a core control module, a Data Acquisition Module (DAM), a communication module, a display module, an Irrigation Control Module (ICM), and a power module. The DAM integrates multiple sensors, such as temperature and humidity sensors, soil temperature sensors, soil humidity sensors, etc., for real-time monitoring of key environmental parameters, including soil and air's temperature and humidity, and light intensity. These sensors are connected to the core controller through communication protocols including, Inter Integrated Circuit (I2C) and Universal Asynchronous Receiver/Transmitter (UART), to ensure stable data transmission [16]. The communication module adopts Wi Fi technology to achieve wireless transmission of data to the data management platform. The display module utilizes a screen to display real-time environmental information, enabling farmers to intuitively understand the growth environment of crops. The ICM achieves an automatic irrigation function based on soil moisture data through a relay control circuit. The entire system adopts a low-power design, suitable for long-term operation in agricultural environments. The hardware shell design focuses on protection, preventing adverse weather and human damage, and ensuring stable system operation. This system can provide reliable data support for agricultural intelligent management, promoting the development of agricultural production towards precision and intelligence. The hardware settings of the DAS are listed in Table 2.

Table 2: Hardware module parameters of DAS

Module Name	Model	Measuring Accuracy
Core Control Module	Raspberry Pi Pico W	264 KB memory, 2 MB flash memory
DAM	/	/
Air Temperature and Humidity Sensor	DHT22	Temperature accuracy ±0.5°C, humidity accuracy ±3% RH
Soil Temperature Sensor	TempDS18B20 - Soil Type	±0.5°C
Soil Moisture Sensor	FDR - Soil Moisture Sensor	±2% VWC (Volumetric Water Content)
Light Intensity Sensor	TSL2591	±10% (within the range of 0.1lx-88,000lx)
Carbon Dioxide Concentration Sensor	MG811	±50 ppm (within the range of 0-5000 ppm)
Communication Module	ESP32 - CAM - Wi-Fi / Bluetooth Module	Supports Wi-Fi and Bluetooth dual-mode communication
Display Module	Pimoroni Hyper - OLED Display	1.3-inch OLED display screen with a resolution of 128 × 64 pixels
ICM	JQC - 3F(T73) - 5V	Rated voltage 5 V, rated current 10 A
Electromagnetic Valve	2W025 - 15	Rated voltage 24 VDC, diameter DN15
Power Module	LM2596S - ADJ	Input voltage 4.5 V-35 V, adjustable output voltage 1.23 V-32 V, maximum output current 3 A

The hardware module of DAS can effectively detect various environmental data. To achieve automatic data collection, this study designs software for DAS. Figure 3 shows the software architecture of DAS.




Figure 3: Software structure of DAS

In Figure 3, the software part of DAS is developed on the open-source Arduino IDE platform, using C/C++ language to program and control various functional modules [17]. In the main loop, the system is in charge of collecting sensor data, uploading data to the cloud platform, and receiving remote control commands. The specific operation includes real-time collection and reading of sensor data such as air temperature and humidity, soil temperature and humidity, light intensity, CO_2 concentration, etc., and converting the data into a standard format through preprocessing. The system utilizes the message queue telemetry transmission protocol to stably transmit data to the cloud platform through a Wi-Fi module, achieving remote monitoring and management. At the same time, the software supports automatic control of irrigation equipment based on soil moisture data, accurately adjusting the irrigation amount. The interface design is user-friendly, making it easy for

users to intuitively understand the system's operating status and configure parameters.

2.2 Agricultural data preprocessing and soil prediction model

This study establishes RSA-DAS by combining multiple sensors and using the open-source Arduino IDE as the development platform, laying the foundation for the analysis and application of agricultural data. However, agricultural environmental data collected using sensors may have issues such as noise, missing values, and outliers, thus requiring preprocessing. The data preprocessing program is shown in Figure 4.




Figure 4: Data cleaning process

In Figure 4, this study first cleans the data by using data filtering algorithms to remove obvious errors and duplicate data, ensuring the accuracy of the data from the source. Then, to address the issue of missing values, a combination of time series analysis and spatial interpolation methods is used for filling. In the prediction of missing values in time series, a Kalman smoother is used to fit the trend and periodicity of historical data to fill in missing values. The standard formula is shown in equation (1) [18].

$$x_{t|T} = x_{t|t} + P_{t|t} A^T(t) P_{t+1|t}^{-1} (x_{t+1|T} - x_{t+1|t}) \quad (1)$$

In equation (1), $x_{t|T}$ is the smoothed estimation value of the t time state based on the total observation data (up to the upper limit of time T) (corresponding to the prediction result of missing values in the original equation). $x_{t|t}$ is the estimated value of state filtering at time t. $P_{t|t}$ is the covariance matrix of the state filtering estimation at time t. $A^T(t)$ is the transition matrix of time t state, and $P_{t+1|t}$ is the one-step prediction covariance matrix of time $t+1$ state. $x_{t+1|T}$ is the smoothed estimation of the state at time $t+1$. $x_{t+1|t}$ is the one-step predicted value of the state at time $t+1$. This formula improves the accuracy of filling missing values in time series by integrating the current filtering result with subsequent smoothing information. This study measures the interpolation quality by comparing errors and backtesting. In terms of spatial interpolation, data collected from peripheral sensors is utilized, and the missing values are comprehensively estimated using the inverse distance weighting method to make the filling results closer to the real situation. The formula is shown in equation (2) [19].

$$z^* = \frac{\sum_{i=1}^{n} \left(z_i \cdot d_i^{-\gamma} \right)}{\sum_{i=1}^{n} d_i^{-\gamma}} \quad (2)$$

In equation (2), z^* is the interpolation result of the target position. z_i is the observation value of the i -th neighboring sensor. d_i is the Euclidean distance between the target position and the i -th sensor. γ is the distance attenuation index, $\gamma > 0$, usually $\gamma = 2$. In inverse distance weighted interpolation, it is necessary to adjust the sensor geometry based on the spatial shape of the target monitoring area to achieve effective coverage, and also adjust the power parameters to ensure stable transmission of data from each sensor. After adjustment, the missing values are estimated comprehensively by calculating the Euclidean distance between the target position and each sensor, using the reciprocal of the distance attenuation index (γ , usually 2) as the weight. The sensor layout needs to evenly cover the monitoring area to reduce sampling bias. If the distance between sensors is too large, it will reduce interpolation accuracy, and if it is too small, it will easily lead to data redundancy. The sensitivity of γ is reflected in the sudden increase of the weight proportion of neighboring sensors when γ increases (easily affected by local data), and the more uniform weight distribution when γ decreases (smoothness is enhanced but local features may be lost). Usually, 2 is taken to balance accuracy and smoothness.

The outlier handling adopts anomaly detection methods based on clustering analysis. Data points that deviate significantly from normal data clustering results are identified as outliers and corrected or removed based on domain knowledge and data context, effectively avoiding the interference of outliers on the analysis results. The calculation formula is shown in equation (3).

$$\text{Outlier}_j \Leftrightarrow \left\| x_j - \mu_c \right\|_2 > \theta \cdot \sigma_c \quad (3)$$

In equation (3), Outlier_j is the j -th data point judged as an outlier. x_j is the j -th data point to be tested. μ_c is the centroid position of cluster c . $\|\cdot\|_2$ is the Euclidean distance. σ_c is the standard deviation of cluster c . θ is the anomaly threshold, usually $\theta \geq 2.5$. The clustering method adopts k-means, which is suitable for clustering environmental parameters. The number of clusters is set to 3-5 categories (corresponding to different

micro environmental feature clusters of farmland), and the pollution rate is taken as 1%-5%. The number of deleted/adjusted points is about 100-300, which can reduce the interference of outliers. Meanwhile, to eliminate the influence of dimensionality, improve the efficiency and accuracy of model training, this study uses a data standardization method based on the wavelet transform. Firstly, wavelet multi-resolution denoising is performed on the agricultural environmental data collected by sensors, such as soil temperature and humidity (with the mother wavelet selected as db4, decomposition level 3, and a soft threshold used for thresholding). Then, the denoised data are standardized instead of directly using wavelet coefficients as features. This method not only converts data to the same scale but also better preserves the detailed features and internal structure of the data, offering a solid foundation for data analysis and modeling.

After data preprocessing, the quality can be improved. AI is widely used in agriculture. Taking farmland irrigation as an example, to provide a scientific basis for agricultural irrigation decision-making, this study uses BP as the basis to predict soil moisture changes. However, BP has shortcomings such as easily falling into local optima and slow convergence speed. To improve the performance of BP in soil moisture prediction, QNN is used to improve BP, forming the QNN-BP model. QNN is a novel algorithm that combines quantum computing and classical neural networks. It utilizes the superposition and entanglement properties of quantum bits to perform global search and optimization more efficiently. Figure 5 shows the QNN-BP's structure.




Figure 5: Structure of QNN-BP model

In Figure 5, the QNN-BP model structure includes an input layer, a quantum layer, a hidden layer, and an output layer. The input layer receives data on factors affecting soil moisture, including air temperature and humidity, soil temperature, etc. The quantum layer is composed of multiple quantum bit units, which utilize the superposition and entanglement properties of quantum bits to perform quantum encoding and processing on input data, converting the data into quantum state representations to enhance data expression capabilities. The quantum state encoding calculation is shown in equation (4).

$$|\psi_{\text{in}}\rangle = \bigotimes_{k=0}^{K-1} R_y(\theta_k)|0\rangle \tag{4}$$

In equation (4), $|\psi_{\text{in}}\rangle$ is the encoded input quantum state. θ_k is the rotation angle corresponding to the k-th feature. $R_y(.)$ is a rotation gate operation around the Y axis (single qubit unitary transformation). $|0\rangle$ is the ground state of quantum bits. $\bigotimes$ is a tensor product that combines states of multiple qubits. The corresponding upper and lower limits are the starting index and ending index. The evolution formula of quantum variational circuits is shown in equation (5).

$$U(\phi) = \prod_{l=1}^{L} H_l(\phi_l) \tag{5}$$

In equation (5), $U(\phi)$ is the global unitary transformation of the quantum layer. $\phi = [\phi_1, \phi_2 ... \phi_l]$ is a variational parameter vector (ϕ_l is the l-th layer parameter). L is the depth of the quantum layer, which controls the complexity of entanglement. H_l is the l-th layer Hamiltonian, and $\prod$ is the interlayer transformation product. The hidden layer adopts the ReLU function of traditional BP for nonlinear transformation. The node output formula is shown in equation (6).

$$h_m = ReLU\left(\sum_{j=1}^{J} W_m^q z_j + b_m\right) \tag{6}$$

In equation (6), h_m is the output of the m-th node in the hidden layer. W_m^q is the connection weight from the quantum layer to the hidden layer, and the superscript q indicates that the quantum is correlated. b_m is the hidden layer bias term. $ReLU(x) = \max(0, x)$ is a modified linear activation function. z_j is the measurement value of the j-th quantum bit, as shown in equation (7).

$$z_j = \langle \psi_{\text{out}} | Z_j | U(\phi) | \psi_{\text{in}} \rangle \tag{7}$$

In equation (7), $\langle \psi_{\text{out}} |$ and $|\psi_{\text{in}}\rangle$ are the output and input state of the quantum layer. Z_j is the Pauli Z operator acting on the j-th quantum bit. The quantum and the hidden layers are connected through a specific weight matrix. Weight initialization combines quantum state randomness and classical methods. The output layer is designed based on the predicted target to predict the soil moisture value, as shown in equation (8).

$$\hat{y} = \sum_{m=1}^{M} W_m^o h_m + b^o \tag{8}$$

In equation (8), $\hat{y}$ is the predicted value of soil moisture. W_m^o is the weight from the hidden to output layer. b^o is the output layer bias. By measuring the observability of quantum bits in quantum circuits (Pauli-Z operator), the expected value is obtained. After normalization preprocessing, it is directly used as the input layer feature of the classical BP network to achieve the connection between quantum output and the classical network. The loss function adopts Mean Squared Error (MSE), and the calculation formula is shown in equation (9).

$$L_{\text{MSE}}(\phi, W, b) = \frac{1}{N}\sum_{i=1}^{N}(\hat{y}_i - y_i)^2 \tag{9}$$

In equation (9), $L_{\text{MSE}}(\phi, W, b)$ represents the MSE loss function. $W = [W_q^m, W_m^o]$ is the classical layer weight matrix. $b = [b_m, b_o]$ is the bias vector. N is the number of samples. $\hat{y}_i$ is the predicted value of the i-th sample and y_i is the true soil moisture value of the i-th sample. The optimization routine of the QNN-BP model is to first optimize the initial weights of the model through quantum annealing, and then fine-tune the parameters using the Adam algorithm.

The training of the model utilizes quantum annealing to optimize the weight matrix, updates the weights through quantum state evolution and measurement, and adjusts the hidden layer parameters using the Adam algorithm to achieve efficient global search and precise local optimization. The trained QNN-BP model can receive new input data, and after quantum layer processing and hidden layer feature extraction, the output layer provides soil moisture prediction results, providing accurate decision support for agricultural irrigation. The QNN-BP model performs 8/16-bit integer quantization, simplifies redundant quantum layer and classical layer parameters to reduce resource consumption, and uses single-precision floating-point numbers to balance prediction accuracy and edge device computing storage costs to ensure numerical accuracy. The rule-based triggering condition is whether the soil moisture predicted by QNN-BP is within the appropriate range. The safety constraint is set to suspend irrigation when sensor data are abnormal, and the fault protection is to cut off the power supply when the solenoid valve fails, achieving irrigation control.


3 Results

A high-performance experimental platform is designed to evaluate the data filtering effect of multiple sensors and analyze the performance of the QNN-BP model. The CPU adopts Intel Core i7-12700K, with a main frequency of 3.6 GHz and a maximum turbo frequency of 5.00 GHz. The GPU adopts NVIDIA GeForce RTX 3060 12 GB, with 16 GB DDR4 3200 Mhz memory and 1 TB SSD hard drive. Qiskit and Cirq are quantum backends used to simulate quantum noise. At the software level, classical quantum mixing training is completed using TensorFlow 2.15.0, and data and computational metrics are processed using Scikit learn 1.3.2. Ansatz is a shallow quantum circuit containing Hadamard, Controlled-NOT, and Ry parameterized gates. The parameter vector corresponds to the rotation angle of the Ry gate, and the cost function takes the prediction error. The optimizer first uses quantum annealing (optimizing initial weights) and then fine-tunes with Adam. The measurement strategy is to read the probability distribution of quantum bits and convert it into classical features. The network weights are transformed into a Quantum Unconstrained Binary Optimization Hamiltonian through linear mapping, and run on the Qiskit Aer simulator. The annealing plan is set to linearly reduce the temperature from 1,000 to 10 and iterate 200 times. Classic features are encoded using angle encoding. Adam has a learning rate of 0.001, batch size of 32, QNN-BP population size of 50, crossover rate of 0.8, mutation rate of 0.02, and termination condition of 200 iterations. QNN-BP has 150-200 trainable parameters and infers FLOP of 1e3-1e4 per inference. BP has 100-150 trainable parameters and FLOP of 800-1200. GA-BPNN has 120-180 trainable parameters and FLOP of 900-1500. The GPU-accelerated version framework is TensorFlow 2.15.0+Qiskit/Cirq. Table 3 shows the QNN-BP's parameters.

Table 3: QNN-BP model parameters

Parameter Category	Parameter Name	Value
BP	Input Layer Neurons	4 (Air Temperature and Humidity, Soil Temperature, Light Intensity)
	Hidden Layer Nodes	10
	Output Layer Nodes	1 (Soil Moisture)
	Activation Function	ReLU
	Training Function	Adam
	Maximum Iterations	200
	Minimum Error Threshold	0.001
QNN	Qubits	4
	Quantum Layer Depth	3
	Quantum Gates Used	Hadamard, CNOT

The experimental data come from multi-sensor detection parameters of cultivated land in a certain village, and are processed using research methods. The processed data are the dataset used to analyze the performance of the QNN-BP model. The ratio of training to testing set is 80%:20%. The dataset includes parameters such as soil temperature and humidity, air temperature and humidity, and light intensity, covering the entire crop growth cycle. During the data preprocessing process, the amount of data and file size before and after each step are shown in Figure 6.



(a) Changes in data volume (b) File size


Figure 6: Data volume and file size before and after data preprocessing

In Figure 6 (a), the data cleaning step removed obvious errors and duplicate data, reducing the data volume from 15,000 to 14,200, a decrease of 800, and improving data quality. After the loss value filling process, the data volume only increased by 100 entries. After handling outliers, the data volume decreased from 14,300 to 13,800, a decrease of 500. After data standardization, the amount of data remained unchanged at 13,800, as standardization only involved scaling and other operations on the data, and did not change the quantity of data. In Figure 6 (b), the file size after data processing decreased from 25.88 MB to 24.15 MB, indicating that the standardization process optimized the data's storage efficiency. The data preprocessing process effectively improved data quality, reasonably reduced redundant and abnormal data, optimized storage space, and laid a solid foundation for subsequent analysis tasks. In terms of performance analysis of the QNN-BP model, this study compared the traditional BP and the Genetic Algorithm-optimized BP Neural Network (GA-BPNN) model [20]. This study compares calculations under the same code path. The experimental results of 5-fold forward cross-validation based on time sequence segmentation are shown in Table 4.

Table 4: Results of 5-fold forward cross-validation experiment based on time sequence segmentation

Method	Cross validation folds	Accuracy (%)	F1 value
BP	1	86.12	0.87
	2	87.56	0.88
	3	88.01	0.89
	4	86.89	0.87
	5	87.42	0.88
	Mean ± standard deviation	87.20±1.25	0.88±0.01
GA-BPNN	1	94.05	0.94
	2	95.32	0.95
	3	95.68	0.96
	4	94.71	0.95
	5	94.74	0.95
	Mean ± standard deviation	94.90±0.85	0.95±0.01
QNN-BP	1	97.02	0.97
	2	97.85	0.98
	3	97.91	0.99
	4	97.33	0.98
	5	97.49	0.98
	Mean ± standard deviation	97.50±0.45	0.98±0.01


As shown in Table 4, this study adopts a time sequential forward validation method, dividing the agricultural data collection time series into 5 continuous intervals. The k-th fold of the training set is the cumulative data of the first k-1 intervals. The test set is the subsequent data of the k-th interval (such as fold 1: training set=1-20% time data, test set=21-25% time data; fold 5: training set=1-80% time data, test set=81-100% time data). The purpose is to avoid future data leaks and meet the time prediction needs of agricultural scenarios. The accuracy of QNN-BP and the standard deviation of F1 values (0.45, 0.01) are both lower than BP (1.25, 0.01) and GA-BPNN (0.85, 0.01), indicating stronger temporal prediction stability. This study uses Qiskit Aer's qasm_Simulator backend with double precision. The simulation cost is calculated by recording the product of CPU/GPU resource usage time and real-time hardware power, while also calculating the proportion of time spent on compiling and measuring quantum circuits. The CPU usage and computation time of each method for predicting data are shown in Figure 7.



(a) Calculate resource consumption (b) Calculation time

Figure 7: CPU usage and computation time when predicting data using various methods

In Figure 7 (a), the average CPU usage of QNN-BP is 23.18%, which is much lower than BP (44.21%) and GA-BPNN (32.92%). This is because QNN-BP quantum encodes the input data, reducing computational complexity. In Figure 7 (b), the average response time of QNN-BP for data prediction is 1.27 seconds, which is 3.22 seconds and 2.48 seconds lower than BP (4.49 seconds) and GA-BPNN (2.51 seconds). This is because the QNN-BP model combines the efficiency of quantum computing with the powerful fitting ability of neural networks, which can process data and optimize parameters more efficiently. QNN-BP exhibits lower CPU usage and shorter computation time in prediction tasks, with overall performance superior to traditional BP and GA-BPNN. QNN-BP relies on shallow quantum layers to simplify the calculation process, and the delay can be controlled within 1.27 seconds when simulating edge deployment to adapt to real-time decision-making in farmland. At the same time, the lightweight design reduces the energy consumption of edge devices by more than 30% compared to BP, achieving a balance between delay and energy consumption. The binary classification framework of "suitable (15% -25%)/unsuitable (<15% or>25%)" for soil moisture has been introduced, and the class threshold is set based on the water demand characteristics of the key growth period of winter wheat summer maize rotation. The accuracy of the model's classification of moisture suitability is measured by the F1 value, which is suitable for agricultural irrigation decision-making scenarios. In the process of predicting soil moisture, the prediction accuracy and F1 value are shown in Figure 8.



(a) Accuracy of soil moisture prediction (b) F1 of soil moisture prediction

Figure 8: Accuracy and F1 value of soil moisture prediction

In Figure 8 (a), the prediction accuracy of the QNN-BP model reaches 97.48%, significantly higher than BP's 87.19% and GA-BPNN's 94.87%. This indicates that QNN-BP has higher accuracy and reliability in predicting soil moisture and can more accurately reflect the actual changes in soil moisture. In Figure 8 (b), the F1 value of QNN-BP is 0.98, which is better than BP's 0.88 and GA-BPNN's 0.95. This indicates that QNN-BP not only has high accuracy in the prediction process but also has a good balance between precision and recall, and can identify positive and negative samples more evenly, effectively capturing subtle features of soil moisture changes. The superposition and entanglement of quantum bits in QNN-BP enable the model to perform more efficient global search when processing complex data, avoiding getting stuck in local optima. The prediction accuracy and F1 value of QNN-BP model are superior to BP and GA-BPNN, demonstrating stronger soil moisture prediction ability and more stable performance. The comparison of soil moisture prediction error indicators between QNN-BP, Long Short-Term Memory (LSTM), and Convolutional Neural Network-Long Short-Term Memory (CNN-LSTM) is shown in Table 5.

Table 5: Comparison table of error indicators for soil moisture prediction between QNN-BP, LSTM, and CNN-LSTM

Method	RMSE (%VWC)	MAE (%VWC)	R^2
LSTM	1.85	1.28	0.92
CNN-LSTM	1.52	1.01	0.95

QNN-BP	1.03	0.72	0.98

As shown in Table 5, the Root Mean Square Error (RMSE) and Mean Absolute Error (MAE) are both measured in units of soil Volumetric Water Content (% VWC), which is in line with the actual scenario of soil moisture monitoring. QNN-BP relies on quantum state feature encoding and hybrid optimization strategy, with RMSE and MAE lower than LSTM and CNN-LSTM, and R^2 closer to 1, reflecting better soil moisture prediction fitting and error control ability. To analyze the interpretability of QNN-BP, additional QNN-BP ablation experiments are conducted, and the results are shown in Table 6.

Table 6: Results of QNN-BP ablation experiment and interpretability analysis

Experimental group	RMSE (%VWC)	MAE (%VWC)	R^2	SHAP Feature Importance Ranking (Top3)
QNN-BP	1.03	0.72	0.98	1. Soil temperature (0.32) 2. Air humidity (0.28) 3. Light intensity (0.21
A. Classic BP control group	1.89	1.35	0.91	1. Soil temperature (0.25) 2. Air humidity (0.21) 3. Light intensity (0.16)
B. Triangle feature mapping group	1.56	1.08	0.94	1. Soil temperature (0.28) 2. Air humidity (0.24) 3. Light intensity (0.18
C. Remove quantum entanglement group	1.32	0.95	0.96	1.Soil temperature (0.30) 2. Air humidity (0.26) 3. Light intensity (0.19)
D1. Quantum depth=1	1.45	1.02	0.95	1. Soil temperature (0.29) 2. Air humidity (0.25) 3. Light intensity (0.18
D2. Quantum depth=3 (original configuration)	1.03	0.72	0.98	1. Soil temperature (0.32) 2. Air humidity (0.28) 3. Light intensity (0.21
D3. Quantum depth=5	1.11	0.78	0.97	1. Soil temperature (0.31) 2. Air humidity (0.27) 3. Light intensity (0.20

In Table 6, the SHAP values show that soil temperature is the core feature driving soil moisture prediction (with the highest SHAP value), and the quantum layer (including entanglement) further strengthens the correlation weights between features (the SHAP values of the top 3 features in the original model are higher than those of the classical control group A). The RMSE of group C (no entanglement) increases by 0.29% VWC compared to the original model, proving the necessity of quantum entanglement for feature correlation encoding. The RMSE of group B (simulated angle encoding) decreases by 0.33% VWC compared to group A (pure classical BP), but still higher than the original model, indicating that quantum encoding is superior to classical feature mapping. When the quantum depth is 3, the model performs the best (with the minimum RMSE and the highest R^2). When the depth increases to 5, there is a slight overfitting (with an increase in RMSE), verifying the rationality of the original model depth configuration.

To verify the practical application capability of QNN-BP, it is applied in the cultivated land of the data collection site, and irrigation strategies are planned based on the predicted soil moisture. 10 sets of Pico W+ESP32-CAM sensors are actually deployed, with soil monitoring depths set at 10-20 cm. The calibration procedure is to compare sensor data with a standard soil temperature and humidity meter every 2 weeks and correct deviations. The plot covers an area of 100-200 m^2, with n=3 repetitions. Random plots are divided according to soil fertility, with soil being loam. Management methods include conventional fertilization and weeding, seasonal coverage throughout the entire growth cycle (120-150 days), and real-time monitoring of weather confounding factors through multiple sensors. Statistical analysis is used to verify the significance of the results through analysis of variance, and the mean is obtained as the result. The protein content is measured using a Kjeldahl nitrogen analyzer (according to GB 5009.5-2016). The vitamin content is measured using a high-performance liquid chromatography (HPLC, according to GB 5009.82-2016). The pesticide residue is measured using a gas chromatography-mass spectrometry (GC-MS, according to GB 23200.113-2018). The sampling frequency is once every 15 days during the critical growth period of crops, and the error bars are set as ± 5%, ± 8%, and ± 10%, respectively. The laboratory standards are based on the corresponding national first-class standard substances. The crop growth and economic benefits before and after the application of the model in the area are shown in Table 7.

Table 7: Crop growth and economic benefits before and after applying the model

Growth Indicator	Unit	Before	After	Percentage Change (%)
Yield	t/ha	15.32	17.85	+16.51%
Protein Content	%	10.20	11.08	+8.63%
Vitamin Content	mg/kg	42.75	46.30	+8.30%

Water Use Efficiency	kg/m³	1.85	2.73	+47.57%
Fertilizer Usage	t/ha	0.0345	0.0278	-19.41%
Pesticide Usage	kg/ha	5.2080	4.1525	-20.28%
Economic Benefit	USD/ha	87.6030	112.4060	+28.30%
Labor Input	h/ha	12	9.8050	-18.29%

Table 7 shows the changes in crop growth and economic benefits before and after applying the QNN-BP model. The yield increased from 15.32 t/ha to 17.85 t/ha, an increase of 16.51%, reflecting the model's effectiveness in improving crop yield. The water resource utilization efficiency has significantly improved, increasing from 1.85 kg/m³ to 2.73 kg/m³ (+47.57%), and highlighting the advantages of the model in optimizing irrigation strategies. At the same time, the use of fertilizers and pesticides has decreased by 19.41% and 20.28%, which not only reduced the environmental burden but also lowered production costs. The economic benefits increased from 87.6030 USD/ha to 112.4060 USD/ha, a significant increase of 28.30%. The labor input decreased by 18.29%, from 12 h/ha to 9.8050 h/ha, further demonstrating the value of the model in improving agricultural efficiency. Overall, QNN-BP has shown excellent performance in improving crop growth indicators and economic benefits, and has good practical application potential. The assumptions of economic analysis (market prices, input costs, labor prices) and sensitivity analysis are shown in Tables 8 and 9.

Table 8: Economic analysis assumptions

Type	Specific content
Market price assumption	Winter wheat 1.8 yuan/kg, summer corn 1.6 yuan/kg; Urea 2.8 yuan/kg, compound fertilizer 3.5 yuan/kg; Pesticide (high efficiency and low toxicity) 25 yuan/100mL; Agricultural labor force 120 yuan/day
Assumption of input cost	Seed cost: 600 yuan/ha for winter wheat and 450 yuan/ha for summer corn; Equipment cost (sensor+controller) is shared at 2000 yuan/ha per year; Irrigation electricity fee of 80 yuan/ha per season
Other Assumptions	The equipment has a service life of 5 years and no residual value; The utilization rate of fertilizers and pesticides has increased by 15% due to precision irrigation; Production loss caused by no extreme weather conditions

Table 9: Sensitivity analysis

Influencing factors	Fluctuation range	Net income (USD/ha)	Net income change rate	Sensitivity level
Comprehensive grain price	-20%	8992.48	-20.00%	High
	-10%	10116.54	-10.00%	High
	Benchmark	11240.6	0.00%	-
	10%	12364.66	10.00%	High
	20%	13488.72	20.00%	High
Cost of fertilizers and pesticides	-20%	11505.41	2.36%	Low
	-10%	11373.01	1.18%	Low
	Benchmark	11240.6	0.00%	-
	10%	11108.2	-1.18%	Low
	20%	10975.8	-2.36%	Low
Agricultural labor prices	-20%	11465.41	2.00%	Medium
	-10%	11353.01	1.00%	Medium
	Benchmark	11240.6	0.00%	-
	10%	11128.2	-1.00%	Medium
	20%	11015.8	-2.00%	Medium

In addition to predicting soil moisture, QNN-BP can also be applied in other agricultural data prediction areas. The accuracy and error of predicting different types of data are shown in Figure 9.




Figure 9: Prediction accuracy and error of different types of data

Figure 9 (a) shows the differences in performance of QNN-BP in predicting different agricultural data. Among them, the accuracy of predicting air temperature and humidity is relatively high, reaching 98.34% (air temperature) and 94.56% (air humidity), which is related to the relatively stable and easy-to-measure temperature and humidity data. The prediction accuracy of pest related data (such as pest infection rate, disease incidence rate) is low, at 82.34% and 81.23%, because the factors affecting pests and diseases are complex, and data acquisition is difficult. In Figure 9 (b), there is a significant difference in the MSE predicted by different data. The predicted MSE of air temperature is the smallest, at 0.0032, indicating that its predicted value has the smallest deviation from the true value. The predicted MSE of the disease incidence rate is the largest, at 0.0081, which means that the prediction error is large. Other data including, soil moisture, air humidity, and light intensity, have relatively moderate MSE values, ranging from 0.0041 to 0.0062. Therefore, QNN-BP performs differently in predicting different agricultural data, and performs better in predicting easily accessible data that is affected by a single factor.

4 Discussion

The proposed QNN-BP model showed significant advantages in soil moisture prediction (accuracy 97.48%, F1 value 0.98). This study solved the problem of conventional BP models easily falling into local optima and slow convergence speed through the superposition and entanglement characteristics of quantum bits. The encoding ability of the quantum layer on input data enhanced the analytical power of the model for nonlinear agricultural environmental relationships, realizing the application of AI in agriculture. Compared with traditional BP, QNN-BP had a prediction accuracy of 97.48%, an improvement of 10.29% compared to BP (87.19%), and an F1 value of 0.98, which was better than BP's 0.88. BP had limitations in nonlinear agricultural data fitting due to issues such as gradient vanishing. The average CPU usage of QNN-BP was only 23.18%, far lower than BP's 44.21%, and the response time was shortened to 1.27 seconds, which was 3.22 seconds less than BP's 4.49 seconds. The soil moisture prediction accuracy of GA-BPNN was 94.87%, lower than QNN-BP's 97.48%, while the irrigation strategy driven by QNN-BP improved water use efficiency by 47.57%. These results indicated that AI technology could promote the development of RSA. This result was consistent with the research conclusions of relevant literature. For example, in reference [11], Ali et al. proposed more agricultural development plans through data analysis, but did not focus on the key indicator of soil moisture. This study focused on soil moisture prediction, which not only made breakthroughs in accuracy but also solved the limitations of traditional models through quantum computing properties. In addition, compared with the unmanned weed control technology proposed by Sharma et al., this study also performed well in reducing manpower input, and further expanded to application scenarios such as precision irrigation, reflecting the diverse value of SA [12].

The quantum entanglement property in QNN can achieve high-dimensional correlation encoding of soil moisture-related features (such as temperature, humidity, and light). Quantum superposition accelerates the model's search for the global optimal solution, effectively avoiding the traditional BP gradient vanishing and local optimal problems, thereby improving convergence speed and prediction accuracy. However, quantum computing requires specialized hardware support, and current edge farmland equipment is difficult to meet deployment requirements. This model is based on single-crop-cultivated land data and has not been optimized for the differences in soil moisture requirements of different crops (such as rice and wheat). Its universality needs to be improved. Future research will optimize classical algorithms to simulate quantum properties, develop multi-

crop adaptation models, reduce hardware costs, and deepen "federated learning+blockchain" data security solutions. Future work will integrate multiple agricultural models into the SA cloud, comprehensively enhancing model deployment and application capabilities.

5 Conclusion

To explore the development path of AI driven RSA and solve the bottlenecks of traditional agricultural prediction models in accuracy, efficiency, and resource consumption, this study combined the parallel optimization capability of quantum computing with the nonlinear mapping capability of traditional BP, and proposed the QNN-BP model. In the task of soil moisture prediction, the accuracy of QNN-BP model reached 97.48%, significantly higher than traditional BP (87.19%) and GA-BPNN (94.87%). Its CPU usage was only 23.18%, with a response time of 1.27 seconds, which was more efficient than traditional BP (44.21%, 4.49 seconds). The irrigation strategy based on QNN-BP prediction increased water use efficiency by 47.57% and reduced fertilizer and pesticide usage by 20.28%. The QNN-BP model confirmed the potential for efficiency enhancement of AI algorithms in SA. The "perception decision execution" closed-loop system driven by it provided a new paradigm for the digital and low-carbon transformation of rural agriculture. However, there are certain shortcomings in current research: (1) The experimental data are limited to a single-cultivated land and need to be expanded to diverse environments such as mountainous and arid areas to validate the model and improve scene scalability; (2) Quantum computing relies on hardware, and in the short term, classical algorithms need to be optimized to simulate quantum characteristics and lower hardware barriers to adapt to edge deployment; (3) The hardware cost of the system is relatively high, which can be reduced through subsidies from the Smart Agriculture Special Fund or equipment sharing models; (4) The privacy risk of farmland data storage rights. In the future, improvements will be made in multiple aspects: (1) The data collection is extended to multiple geographical environments and crop types, and cross-regional validation is conducted to enhance the scalability of the model; (2) Classical algorithms are optimized to simulate quantum properties, and lightweight modules are developed to adapt to edge deployment; (3) Low-cost open-source hardware is selected, combined with special subsidies and regional device sharing to reduce the burden; (4) The decentralized architecture of "federated learning+blockchain" is built to ensure data security.

References

[1] Elbasi E, Mostafa N, AlArnaout Z, Zreikat A I, Cina E, Varghese G, et al. Artificial intelligence technology in the agricultural sector: A systematic literature review. IEEE Access, 2022, 11(1): 171-202. DOI: 10.1109/ACCESS.2022.3232485.

[2] Gebresenbet G, Bosona T, Patterson D, Persson H, Fischer B, Mandaluniz N, et al. A concept for application of integrated digital technologies to enhance future smart agricultural systems. Smart Agricultural Technology, 2023, 5(1): 100255-100256. DOI: 10.1016/j.atech.2023.100255.

[3] Xu J, Gu B, Tian G. Review of agricultural IoT technology. Artificial Intelligence in Agriculture, 2022, 6(1): 10-22. DOI: 10.1016/j.aiia.2022.01.001.

[4] Wei Z, Zhu M, Zhang N, Wang L, Zou Y, Meng Z, et al. UAV-assisted data collection for Internet of Things: A survey. IEEE Internet of Things Journal, 2022, 9(17): 15460-15483. DOI: 10.1109/JIOT.2022.3176903.

[5] Mohammed B. A comprehensive overview of federated learning for next generation smart agriculture: current trends, challenges, and future directions. Informatica, 2025, 49(1), 117-136. DOI: 10.31449/inf.v49i1.6764.

[6] Chen J. Construction and application of an economic intelligent decision-making platform based on artificial intelligence technology. Informatica, 2024, 48(9): 89-106. DOI: 10.31449/inf.v48i9.5705.

[7] Pincheira M, Shamsfakhr F, Hueller J, Vecchio M. Overcoming limitations of iot installations: Active sensing ugv for agricultural digital twins. In 2023 IEEE International Workshop on Metrology for Agriculture and Forestry (MetroAgriFor). Pisa, Italy, 2023, 1(1): 319-324. DOI: 10.1109/MetroAgriFor58484.2023.10424235.

[8] Ahmed A, Parveen I, Abdullah S, Ahmad I, Alturki N, Jamel L. Optimized data fusion with scheduled rest periods for enhanced smart agriculture via blockchain integration. IEEE Access, 2024, 12(1): 15171-15193. DOI: 10.1109/ACCESS.2024.3357538.

[9] Mohapatra H, Rath A K. IoE based framework for smart agriculture: Networking among all agricultural attributes. Journal of ambient intelligence and humanized computing, 2022, 13(1): 407-424. DOI: 10.1007/s12652-021-02908-4.

[10] Akhter R, Sofi S A. Precision agriculture using IoT data analytics and machine learning. Journal of King Saud University-Computer and Information Sciences, 2022, 34(8): 5602-5618. DOI: 10.1016/j.jksuci.2021.05.013.

[11] Ali I, Ahmedy I, Gani A, Munir M U, Anisi M H. Data collection in studies on Internet of things (IoT), wireless sensor networks (WSNs), and sensor cloud (SC): Similarities and differences. IEEE Access, 2022, 10(1): 33909-33931. DOI: 10.1109/ACCESS.2022.3161929.

[12] Sharma S, Verma K, Hardaha P. Implementation of artificial intelligence in agriculture. Journal of Computational and Cognitive Engineering, 2023, 2(2): 155-162. DOI: 10.47852/bonviewJCCE2202174.

[13] McCampbell M, Schumann C, Klerkx L. Good intentions in complex realities: Challenges for designing responsibly in digital agriculture in low-income countries. Sociologia Ruralis, 2022, 62(2): 279-304. DOI: 10.1111/soru.12359.

[14] Feliciano D, Recha J, Ambaw G, MacSween K,

Solomon D, Wollenberg E. Assessment of agricultural emissions, climate change mitigation and adaptation practices in Ethiopia. Climate Policy, 2022, 22(4): 427-444. DOI: 10.1080/14693062.2022.2028597.

[15] Shaikh T A, Mir W A, Rasool T, Sofi S. Machine learning for smart agriculture and precision farming: towards making the fields talk. Archives of Computational Methods in Engineering, 2022, 29(7): 4557-4597. DOI: 10.1007/s11831-022-09761-4.

[16] Shenoy S, Madhushankara M. Seamless connectivity: universal asynchronous receiver and transmitter for implantable medical devices. Analog Integrated Circuits and Signal Processing, 2025, 124(1): 1-13. DOI:10.1007/s10470-025-02423-y.

[17] Rivera J, Salinas P. Low-Cost and accessible scale body maceration control system: integration of internet of things-NodeMCU with Arduino-IDE. International Journal of Morphology, 2024, 42(5): 1239-1247. DOI: 10.4067/S0717-95022024000501239.

[18] Josse J, Chen J M, Prost N, Varoquaux G, Scornet E. On the consistency of supervised learning with missing values. Statistical Papers, 2024, 65(9): 5447-5479. DOI: 10.1007/s00362-024-01550-4.

[19] Liang D, Xu W, Zhu Y, Zhou Y. Focal inverse distance transform maps for crowd localization. IEEE Transactions on Multimedia, 2022, 25(1): 6040-6052. DOI: 10.1109/TMM.2022.3203870.

[20] Jian L, Wang X, Jiang W, Hao H, Xi R, Yang L. Improved tide level prediction model combined GA-BP neural networks and GNSS SNR data. Advances in Space Research, 2024, 74(4): 1595-1608. DOI: 10.1016/j.asr.2024.05.030

A CNN-Enabled Context-Aware Wireless Sensor Network for Smart Banana Cultivation

Shankar Pujari[1*], Jaydeep Patil[2], Sangram Patil[2]
[1]Research Scholar (Computer Science & Engineering) D. Y. Patil Agriculture and Technical University, Talsande, Maharashtra, India
[2]D. Y. Patil Agriculture and Technical University, Talsande, Maharashtra, India
E-mail: shankarpujari77@gmail.com, jaydeeppatil@dyptu.org, sangrampatil@dyp-atu.org
[*]Corresponding author

Keywords: Precision Agriculture, Wireless Sensor Networks (WSN), Context-Aware Systems, Banana Cultivation, Convolutional Neural Network (CNN)

Received: July 31, 2025

Banana cultivation, a critical tropical crop, is highly sensitive to water stress, nutrient imbalance, and disease outbreaks, all exacerbated by climatic variability. Traditional wireless sensor network (WSN) systems rely on static thresholds, limiting their adaptability to dynamic field conditions. This study proposes a context-aware WSN framework integrated with a Convolutional Neural Network (CNN) for real-time field condition classification and intelligent decision support in banana farming. Multimodal data—including soil moisture, temperature, humidity, light intensity, and pH—are captured and normalized using z-score standardization. A 1D CNN architecture (three convolutional layers with ReLU activation, max pooling, and fully connected layers) processes the input feature vector X = [Ms, T, H, L, pH] to classify four agronomic contexts: Water Stress, Nutrient Deficiency, Disease Risk, and Normal Condition.

A dataset of 5,000 samples (3,200 real field records and 1,800 augmented via Gaussian noise and bootstrapping) was used for model training and validation with 5-fold cross-validation. The proposed CNN model achieved an accuracy of 95.3%, precision of 94.5%, recall of 95.2%, and F1-score of 94.8%, outperforming baseline SVM (83.1%) and Decision Tree (80.5%) models. Field deployment demonstrated a 28% improvement in water-use efficiency, a 41% reduction in disease incidence, and a 3.1% false alarm rate, confirming superior adaptability over rule-based systems. The framework provides scalable, real-time decision support, offering a transferable model for sustainable and intelligent precision agriculture.

Povzetek: Raziskava predstavlja pametni senzorski sistem s konvolucijsko nevronsko mrežo za banane, ki omogoča prilagodljivo in natančno odločanje v realnem času ter izboljša rabo vode in zdravje pridelka.

1 Introduction

Precision agriculture represents a transformative approach to modern farming, leveraging wireless sensor networks (WSNs), Internet of Things (IoT) technologies, and artificial intelligence (AI) to enable data-driven, site-specific crop management. By facilitating continuous monitoring of environmental and soil parameters, these systems optimize resource use, reduce operational costs, and enhance sustainability — key priorities in the context of climate change and growing food demand. Among tropical crops, banana (Musa spp.) holds exceptional economic and nutritional importance, serving as both a staple food and a major export commodity across developing regions. However, banana cultivation faces distinct agronomic challenges that differentiate it from other crops such as rice, grapes, or tomatoes. These include:

- High disease susceptibility, particularly to fungal infections such as Panama disease and black Sigatoka, which thrive under humid conditions.
- Soil heterogeneity and pH sensitivity, affecting nutrient uptake and plant health.
- Water management complexity, as bananas are sensitive to both drought and waterlogging.
- Microclimatic variability, which influences plant physiology and increases unpredictability in field conditions.

Conventional WSN-based systems in agriculture typically rely on rule-based decision-making with static thresholds for parameters like soil moisture or temperature. While effective for simple environments, these systems lack adaptability in dynamic field conditions, often leading to false alerts and inefficient interventions. In contrast, machine learning (ML) and

deep learning (DL) models—particularly Convolutional Neural Networks (CNNs)—offer the ability to extract complex patterns and classify contextual states from multi-sensor data, enabling more robust, adaptive decision support. Despite promising results in other crops, existing studies often focus narrowly on disease detection using image data, without integrating environmental sensor fusion or context-aware decision-making. Moreover, few frameworks address real-time field condition classification tailored to banana's unique agronomic profile.

To address these gaps, this paper proposes a CNN-enabled context-aware WSN framework designed specifically for smart banana cultivation. The proposed system:

- Integrates heterogeneous sensor data (soil moisture, temperature, humidity, light, and pH) to capture real-time field conditions.
- Employs a CNN-based classifier to interpret environmental contexts into actionable categories: Water Stress, Nutrient Deficiency, Disease Risk, and Normal Condition.
- Provides real-time alerts and adaptive recommendations for irrigation, fertilization, and disease management.

Field experiments demonstrate the system's capacity to achieve 95.3% classification accuracy, 28% improvement in water-use efficiency, and 41% reduction in disease incidence compared to traditional rule-based methods. Beyond addressing crop-specific challenges, the framework establishes a scalable and transferable model for AI-driven precision agriculture, promoting resilience and sustainability across similar high-value crops. Figure 1 used to show how diseases and pests on banana plants affects [8]. By adopting a context-based approach, tailored to the specific requirements of banana plants, WSNs offer the potential to revolutionize banana cultivation practices and improve yield, quality, and sustainability. This paper begins by providing an overview of precision agriculture and the challenges faced in traditional farming methods. It then introduces wireless sensor networks, discussing their architecture, components, and applications in agriculture. Subsequently, we delve into the context-based approach for banana plantations, addressing the unique requirements of soil, climate, and water management. Through applications and case studies, we illustrate how WSNs have been deployed to monitor and manage banana crops effectively [24].



Figure 1: Visual overview of banana crop diseases and pests

The dynamic nature of challenges in banana cultivation — such as fluctuating climatic conditions, pest infestations, and soil variability — calls for adaptable and intelligent monitoring systems. Traditional or static management approaches fail to capture real-time variability in soil parameters, microclimate, and plant health, leading to delayed interventions and suboptimal resource use. Recent studies underscore the need for climate-resilient agricultural systems that can respond proactively to evolving pathogens and abiotic stressors influenced by climate change [31]. In addition, increasing awareness of beneficial soil microorganisms, such as Plant Growth Promoting Rhizobacteria (PGPR), highlights the potential of holistic management strategies that enhance both nutrient uptake and disease resistance [30].

Wireless Sensor Networks (WSNs) have emerged as transformative enablers in precision agriculture, providing distributed, continuous, and automated monitoring of key parameters like soil moisture,
humidity, pH, and temperature [9, 19]. However, conventional WSN systems typically operate on static threshold-based rules, lacking the adaptability needed to handle dynamic and nonlinear field conditions. This limitation often reduces their effectiveness in complex cultivation environments such as banana plantations, where context-sensitive decision-making is essential. To address these gaps, this paper proposes a context-aware WSN framework specifically tailored for precision banana farming. By integrating heterogeneous environmental, physiological, and agronomic data, the system generates actionable insights for intelligent irrigation, fertilization, and disease management. The framework employs sensor fusion techniques and Convolutional Neural Networks (CNNs) to dynamically classify field conditions and enable adaptive decision-making. This research aims to enhance resilience, productivity, and sustainability in banana cultivation — one of the world's most significant and climate-sensitive fruit crops. Table 1. Used to summarizes Key Challenges and Opportunities in Banana Cultivation.

Table 1: Key Challenges and opportunities in banana cultivation

Challenges	Opportunities
Climate Sensitivity: Highly susceptible to temperature extremes and humidity-induced diseases (e.g., black Sigatoka).	**Technology Adoption**: Precision agriculture tools (e.g., WSNs and AI) enable real-time climate monitoring and early disease detection [3].
Water Management: Sensitive to both drought and over-irrigation; requires balanced water supply.	**Sustainable Practices**: Smart irrigation systems improve water-use efficiency and environmental resilience.
Soil Quality: Erosion, compaction, and nutrient depletion	**Soil Management**: Practices such as mulching, composting,

reduce productivity in many banana-growing regions.	and biofertilizers restore fertility and soil health.
Pests and Diseases: Threatened by nematodes, weevils, thrips, and fungal diseases.	**Research and Breeding**: Development of disease-resistant varieties and use of integrated pest management (IPM) strategies.
Labor Intensity: High manual labor requirements for planting, pruning, and harvesting.	**Mechanization**: Robotics and automation reduce labor dependency and improve operational efficiency.

2 Related work

The advancement of precision agriculture has been significantly accelerated by the integration of Wireless Sensor Networks (WSNs), the Internet of Things (IoT), and Artificial Intelligence (AI). These technologies enable real-time environmental monitoring, data-driven farm management, and automated decision-making across diverse crop systems, including banana cultivation [9, 19, 24].

2.1 WSN-based agricultural monitoring

Numerous studies have explored the use of WSNs in agricultural applications, particularly for environmental sensing and irrigation control. Ojha et al. [9] provided a comprehensive review of WSN applications across crop domains, emphasizing their potential to enhance resource-use efficiency and environmental sustainability. However, most conventional WSN systems employ predefined static thresholds, making them incapable of dynamically adapting to climate fluctuations, disease emergence, or soil variability. To address these shortcomings, context-aware systems have been proposed that adjust sensing and decision-making in response to real-time data. Islam and Dey [24], for instance, implemented a WSN-based smart monitoring system powered by renewable energy and IoT, successfully managing irrigation schedules and basic soil monitoring. However, such systems lack machine learning integration, limiting their ability to derive high-level inferences or predictive insights.

2.2 Deep learning for agricultural diagnostics

Deep learning techniques, particularly Convolutional Neural Networks (CNNs), have shown promise in agricultural diagnostics, especially for disease identification.

- Banerjee et al. [3] developed hybrid deep learning models to classify banana leaf diseases, achieving high prediction accuracy.
- Correa et al. [5] designed a CNN model that significantly improved the accuracy of banana leaf infection detection.
- Kakati and Das [11] employed deep learning to distinguish between healthy and diseased leaves, enabling early diagnosis.

Advanced architectures like YOLOv4 [13] and segmentation-based CNNs [14] further improved real-time detection and precision, while transfer learning approaches [12] enhanced model generalizability across field conditions.

Despite these achievements, most of these image-based approaches focus narrowly on leaf-level disease detection. They do not integrate environmental sensor data, and therefore cannot provide context-aware decision-making (e.g., combining soil moisture, humidity, and pH to infer nutrient stress or irrigation needs).

2.3 Integrative AI-WSN frameworks

Few studies have proposed holistic frameworks that combine multi-sensor environmental monitoring with deep learning for adaptive agricultural decision support. For example, Keerthana et al. [10] demonstrated the link between soil mineral deficiencies and disease susceptibility in bananas, emphasizing the importance of multi-parameter integration. However, such studies lack real-time adaptability and scalable deployment in field conditions. To bridge this gap, the present work introduces a CNN-enabled context-aware WSN that classifies field conditions into actionable contexts — Water Stress, Nutrient Deficiency, Disease Risk, and Normal Condition — using multi-sensor fusion and real-time data processing. This system extends beyond disease detection to enable comprehensive, adaptive farm management shown in table 2.

Table 2: Comparative analysis of ai-based techniques for disease detection in banana plants

Ref. No.	Method / Technique	Key Findings	Limitation
[3]	Hybrid Deep Learning Models	Developed robust classifiers for banana leaf diseases to enhance precision agriculture.	Focused on disease detection only; no context integration
[5]	Convolutional Neural Network (CNN)	Designed a CNN for classifying diseased banana leaves, improving detection accuracy.	Image-only; no multi-sensor data integration
[6]	Comparative Analysis	Assessed multiple methods for leaf disease detection, highlighting strengths and weaknesses.	No unified adaptive framework

[7]	Deep CNN Architecture	Achieved high accuracy in banana disease prediction using deep CNN layers.	No environmental sensing or contextual awareness
[11]	Deep Learning (Healthy vs. Unhealthy Leaves)	Enabled disease classification using leaf health comparison via deep learning.	Limited to visual symptoms
[12]	Transfer Learning for Image-Based Detection	Offered efficient plant disease detection using deep transfer learning techniques.	No real-time adaptability
[13]	Image Segmentation with CNN	Enhanced detection precision using segmentation-based deep learning models.	Focused on leaf-level detection only
[14]	YOLOv4 Object Detection Algorithm	Detected Panama disease in real time using advanced object detection.	Limited interpretability; lacks sensor fusion
[15]	Advanced Convolutional Neural Network	Achieved high classification accuracy in identifying multiple banana leaf diseases.	No field-level integration
[32]	Support Vector Machine (SVM)	Proposed portable Sigatoka spot disease identifier for real-time disease detection.	Lower accuracy; lacks adaptive intelligence

2.4 Research gap and contribution

From the literature, it is evident that:

•Most existing works focus on image-based disease classification;

•Very few integrate multi-sensor environmental data;

•None offer a context-aware WSN that performs real-time classification and adaptive decision-making for banana cultivation.

To fill this gap, our proposed CNN-enabled context-aware WSN provides a multi-modal, real-time, and adaptive decision-support system — marking a novel contribution to precision banana agriculture.

3 Methodology

The proposed framework integrates context-aware sensing with deep learning-based decision support to address the dynamic challenges of banana cultivation. The methodology involves sensor deployment, data preprocessing, wireless communication, and real-time context classification using a Convolutional Neural Network (CNN). The entire process is illustrated in Figure 2.




Figure 2: Proposed Context-Aware WSN framework for banana cultivation

3.1 System overview

The system architecture is composed of four interdependent layers:

- Sensor Layer
- Edge Processing Layer
- Communication Layer
- Cloud/Server Layer (CNN-based Decision Engine)

This modular structure supports adaptability and scalability in diverse field environments, from smallholder farms to commercial banana plantations.

Figure 3 illustrates the architecture of the proposed Context-Aware WSN Framework for Banana Cultivation, comprising four interconnected layers: the Sensor Layer, Edge Processing Layer, Communication Layer, and Cloud/Server Layer. The Sensor Layer collects real-time data from multiple sources—soil moisture, temperature, humidity, light, and pH sensors—forming the foundation for environmental monitoring. The Edge Processing Layer performs noise filtering and normalization, ensuring clean and consistent data. This processed information is transmitted via the Communication Layer (using Wi-Fi or LoRaWAN) to the Cloud/Server Layer, where the CNN-based Decision Engine classifies field conditions into four categories: Water Stress (WS), Nutrient Deficiency (ND),

Disease Risk (DR), and Optimal Growth (OG). This hierarchical design supports adaptive, real-time decision-making for precision banana farming.




Figure 3: Context-aware WSN framework for banana cultivation with CNN decision engine

3.2 Sensor layer: environmental and soil monitoring

To capture critical agricultural parameters, multiple sensor types are deployed throughout the banana field. These include:

- Soil moisture sensors (capacitive)
- Temperature sensors (DS18B20)
- Humidity sensors (DHT22)
- Light sensors (LDR or BH1750)
- pH sensors

Each sensor node continuously samples data at fixed intervals (every 10 minutes), enabling timely detection of agronomic stress conditions. The types and functions of these sensors are summarized in Table 3.

Table 3: Types of sensors used in precision agriculture and their functions

Sensor Type	Function	Examples / Technologies
Soil Moisture Sensors	Measure soil water content to optimize irrigation scheduling.	Capacitive sensors, Resistive probes, TDR (Time Domain Reflectometry) sensors
Temperature Sensors	Monitor air, soil, or water temperature, critical for plant growth and stress.	DS18B20, Thermocouples, Thermistors, RTDs
Humidity Sensors	Assess ambient humidity, aiding in disease prevention and transpiration control.	DHT22, Capacitive and Resistive Humidity Sensors
Light Sensors	Evaluate light intensity and Photosynthetically Active Radiation (PAR).	BH1750, LDR (Light Dependent Resistors), Photodiodes
pH Sensors	Measure soil acidity or alkalinity, influencing nutrient uptake.	Glass Electrode Sensors, ISFET (Ion-Sensitive Field Effect Transistor) pH sensors
Nutrient Sensors	Detect levels of soil nutrients for informed fertilization.	Ion-Selective Electrodes, Optical and Electrochemical Sensors
Weather Sensors	Record external weather conditions such as rainfall, wind, and pressure.	Rain Gauges, Barometers, Anemometers, Weather Stations
Pest & Disease Sensors	Detect early signs of pest infestation or plant disease.	Imaging Sensors, Spectroscopy Devices, Biosensors (DNA-based)

3.3 Edge layer: preprocessing and normalization

Each sensor node is connected to a microcontroller (e.g., ESP32 or Raspberry Pi) that performs local processing. This includes:

- Filtering to eliminate noise
- Normalization using z-score standardization:

$$X_n = \frac{X-\mu}{\partial} \quad \text{----------(1)}$$

Where, X = raw sensor value, μ= mean of historical data, σ= standard deviation

This preprocessing reduces data redundancy and supports real-time analytics without overloading the communication network.

3.4 Communication layer: data transmission

Processed data is transmitted to a central processing unit via either Wi-Fi or LoRaWAN, depending on the plantation size and coverage needs. LoRaWAN is favored for its low-power, long-range capabilities, especially in rural and semi-urban areas with limited infrastructure.

3.5 Cloud/server layer: context inference via CNN

The core of the system is a CNN-based context classifier, trained to interpret sensor data and predict field conditions such as:

- WS – Water Stress
- ND – Nutrient Deficiency
- DR – Disease Risk
- OG – Optimal Growth

The multivariate input vector:

$$X = [Ms, T, H, L, pH]\ X \quad \text{---------- (2)}$$

is fed into a CNN model composed of convolutional and pooling layers, followed by fully connected layers. The model uses ReLU activation functions and is optimized with backpropagation. The CNN model architecture and its performance are illustrated in Figure 3, and the classification results are presented in Table 4.




Figure 4: CNN model performance for context classification

3.6 Alert engine and decision support

Based on the classification probabilities, an alert is generated if the likelihood of a stress condition exceeds a threshold:

$$Alert \begin{Bmatrix} 1 \\ 0 \end{Bmatrix} \frac{if\ P_{CNN}(class) > \tau}{Otherwise}$$

---------- *(3)*

These alerts are communicated to farmers via SMS or a mobile app, enabling timely intervention.

3.7 Data pipeline and workflow summary

The system operates in the following sequence:

- Sensor nodes acquire raw environmental and soil data.
- Microcontrollers perform edge-level preprocessing.
- Wireless modules transmit data to the central server.
- CNN model classifies the field condition in real time.
- Decision engine triggers alerts for irrigation, nutrient correction, or disease mitigation.

This workflow is depicted in Figure 3: Proposed Context-Aware WSN Framework for Banana Cultivation.

3.8 Supporting literature and feature justification

The challenges in banana cultivation—such as water sensitivity, disease prevalence, and soil degradation—were detailed in Table 1, providing context for the parameter selection in this framework. Further, recent advancements in CNN-based disease detection in banana farming are reviewed and synthesized in Table 2, justifying the use of CNNs in the proposed system.

3.9 Advantages of the proposed methodology

- Real-Time Context Recognition: CNNs outperform rule-based systems in adapting to dynamic field conditions.
- Resource Efficiency: Precision alerts reduce water, fertilizer, and pesticide waste.
- Scalability: Modular sensor deployment allows expansion across varied farm sizes.
- Integration of Multimodal Data: Combines visual and environmental inputs for robust decision-making.

4 Results and analysis

The performance of the proposed context-aware wireless sensor network (WSN) framework was evaluated through a series of real-time experiments conducted in banana plantations equipped with multi-sensor nodes and microcontroller-based edge units. This section presents the experimental setup, CNN model evaluation, contextual classification results, and comparative analysis with a conventional rule-based system.

4.1 Experimental setup

To validate the framework, a testbed was deployed in a controlled banana cultivation area. The configuration included

- ***Sensor Devices***
  - DHT11 for temperature and humidity
  - Capacitive soil moisture sensors
  - Photoresistors for light intensity
  - pH sensors for soil analysis
- ***Edge Processing Unit***
  - ESP32 microcontroller with local data normalization and LoRa-based communication
- ***Server-Side Configuration***
  - A CNN model hosted on a cloud server, trained with both real and synthetically augmented datasets
  - Wireless communication over LoRaWAN or Wi-Fi, depending on field coverage

Data was collected over a 30-day period under varying environmental conditions to simulate typical challenges in banana farming.

4.2 CNN model performance

The CNN was trained on a dataset of 5,000 labeled samples, combining real sensor data and synthetically augmented records to simulate various stress conditions. The model was tasked with classifying field conditions into four categories

- Irrigation Needed
- High Disease Risk
- Nutrient Deficiency
- Normal Condition

The model achieved high performance across all metrics as presented in Table 4 and these results, also visualized in Figure 4, demonstrate the CNN's capability to detect early-stage agronomic issues with high reliability.

Table 4: CNN model performance for context classification

Context Class	Accuracy	Precision	Recall	F1-Score
Irrigation Needed	96.2%	95.5%	97.1%	96.3%
High Disease Risk	94.8%	94.1%	93.5%	93.8%
Nutrient Deficiency	92.3%	90.7%	91.8%	91.2%
Normal Condition	98.1%	97.6%	98.3%	97.9%
Average	**95.3%**	**94.5%**	**95.2%**	**94.8%**

4.3 CNN classification results

The proposed CNN model achieved superior performance across all classes, as summarized in Table 5**.**

Table 5: CNN classification results

Class	Precision (%)	Recall (%)	F1-score (%)
Water Stress (WS)	94.8	95.1	94.9
Nutrient Deficiency (ND)	93.7	94.2	93.9
Disease Risk (DR)	95.4	95.8	95.6
Optimal Growth (OG)	95.0	95.6	95.3
Overall	**94.5**	**95.2**	**94.8**

The overall classification accuracy was 95.3%**,** with an average precision of 94.5% and an F1-score of 94.8%**,** demonstrating robust and reliable context recognition.

4.4 Comparative analysis with baseline models

To highlight the advantage of CNNs in resource-constrained WSN environments, the proposed model was compared against **Decision Tree (DT)** and **Support Vector Machine (SVM)** classifiers using the same dataset.

Table 6: Comparative analysis with baseline models

Model	Accuracy (%)	F1-score (%)	False Alarm Rate (%)	Energy Consumption
CNN (Proposed)	**95.3**	**94.8**	**3.1**	Moderate
SVM	83.1	82.5	12.4	Low
Decision Tree	80.5	79.9	14.7	Low

The CNN outperformed traditional models by over 12% in accuracy and reduced false alarms by 9–11%**,** confirming its superior generalization and adaptability for dynamic field conditions**.**

4.5 Confusion matrix analysis

The confusion matrix, shown in Figure 4 highlights the CNN model's strong capability in accurately identifying critical stress conditions, particularly irrigation needs. This high performance is attributed to the distinct patterns in sensor data—such as low soil moisture, elevated temperature, and reduced humidity—which are effectively captured during model training. As a result, the model achieves a high true positive rate in detecting water stress. Similarly, normal field conditions are classified with the highest accuracy among all categories, likely due to their stable and less variable sensor profiles. This leads to excellent precision and recall, and consequently, a low false positive rate in generating alerts. However, some degree of confusion was observed between nutrient deficiency and disease risk, which is understandable given that both can exhibit overlapping sensor patterns—like abnormal humidity or shifts in soil pH—during early stress stages. These occasional misclassifications reflect the complex nature of distinguishing between subtle agronomic stressors using environmental data alone.




Figure 5: Confusion matrix of CNN-based context classification

Despite these overlaps, the model maintained a low false alarm rate of 3.1%, significantly outperforming the 12.4% rate observed in rule-based systems (as shown in Table 7). This affirms the robustness of a learning-based approach that adapts to dynamic field variability rather than relying on rigid thresholds. Beyond evaluating performance, the confusion matrix serves as a diagnostic tool for continuous improvement. It helps identify which classifications are most error-prone and where refinements are needed. For instance, the noted confusion between disease risk and nutrient deficiency suggests potential for enhancement through integration of visual data, such as leaf imagery or spectral sensing. Additionally, the confidence scores produced by the CNN can guide the fine-tuning of alert thresholds (τ), enabling farmers to balance sensitivity and specificity based on crop stage or season. This interpretability not only validates model performance but also supports more strategic, risk-aware decision-making in precision banana cultivation.

4.4 Real-time system adaptability

The context-aware system's performance was evaluated under live field conditions. Key outcomes observed during the deployment phase include:

- Water-Use Efficiency: Improved by 28% due to timely irrigation scheduling.
- Disease Management: Early detection of disease symptoms led to a 41% reduction in leaf spot incidence through timely spraying.
- Nutrient Correction: pH-based alerts enabled deficiency correction within 3 days, reducing crop stress.

These results highlight the framework's real-time adaptability and agronomic impact.

4.5 Comparative evaluation with rule-based system

Metric	CNN-Based	Rule-Based
Context Classification Accuracy	95.3%	78.6%
False Alarm Rate	3.1%	12.4%
Adaptability to New Data	High	Low
Scalability	Good	Limited

For benchmarking, a conventional threshold-based decision system was also deployed. As shown in Table 7 and visualized in Figure 6, the CNN-powered framework significantly outperformed the rule-based model in all key metrics.




Figure 6: Comparison of CNN-based and rule-based approaches

4.6 Interpretation and Implications

The experimental outcomes confirm that the proposed system offers substantial improvements in

- Early Warning Capability: Contextual alerts lead to preventive, rather than reactive, action.
- Resource Efficiency: Water and fertilizer usage were optimized.
- Scalability and Flexibility: The framework adapted well to variable field conditions without reprogramming.

5 Conclusion

This study presented a CNN-enabled context-aware Wireless Sensor Network (WSN) framework for smart banana cultivation, integrating real-time environmental sensing with deep learning-based decision support. The system effectively classified field conditions into Water Stress**,** Nutrient Deficiency**,** Disease Risk**,** and Optimal Growth, achieving an overall accuracy of 95.3% and significantly improving resource-use efficiency. By leveraging multimodal sensor data and CNN-based classification, the framework demonstrated superior adaptability compared to traditional rule-based and machine learning models. Field deployment confirmed a 28% enhancement in water-use efficiency, 41% reduction in disease incidence, and a 3.1% false alarm rate, validating its applicability in real-world agricultural settings. The system's modular architecture supports scalability across various field sizes and adaptability to diverse climatic zones. Its design can be extended to other high-value crops through retraining with crop-specific datasets. Additionally, integrating adaptive control methods—such as fuzzy logic and backstepping control—offers future potential for closed-loop automation in irrigation and nutrient management. In summary, the proposed context-aware WSN framework offers a robust, intelligent, and sustainable solution for precision agriculture. It empowers farmers with actionable insights, reduces resource wastage, and enhances resilience against climatic and biological stressors. Future research will focus on integrating spectral imaging, NDVI-based indices, and self-learning control mechanisms to further improve accuracy, adaptability, and autonomy.

References

[1] Weiwei Zhang."A Fruit Ripeness Detection Method using Adapted Deep Learning-based Approach", International Journal of Advanced Computer Science and Applications, 2023

[2] Bhupinder Singh, Christian Kaunert. "Chapter 11 Harnessing Sustainable Agriculture Through Climate-Smart Technologies", IGI Global, 2023

[3] Banerjee, Deepak, Vinay Kukreja, Shanmugasundaram Hariharan, and Vandana Sharma. "Precision Agriculture: Classifying Banana Leaf Diseases with Hybrid Deep Learning Models." (2023): 1-5. doi: 10.1109/I2CT57861.2023.10126431.

[4] Tuazon, G. L. H., H. M. Duran, and J. F. Villaverde. "Portable Sigatoka Spot Disease Identifier on Banana Leaves Using Support Vector Machine." 2021 IEEE 13th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management (HNICEM), Manila, Philippines, 2021, pp. 1-6. doi: 10.1109/HNICEM54116.2021.9731808.

[5] Correa, E., M. García, G. Grosso, J. Huamantoma, and W. Ipanaqué. "Design and Implementation of a CNN architecture to classify images of banana leaves with diseases." 2021 IEEE International Conference on Automa- tion/XXIV Congress of the Chilean Association of Automatic Control (ICA-ACCA), Valparaíso, Chile, 2021, pp. 1-6. doi: 10.1109/ICAACCA51523.2021.9465178.

[6] Raja, N., and P. Rajendran. "Comparative Analysis of Banana Leaf Disease Detection and Classification Methods." (2022): 1215-1222. doi: 10.1109/ICCMC53470.2022.9753840.

[7] Devi, M. S., B. Vamshikrishna, J. A. Pandian, P. V. Rao, and S. R. Yaseen. "Eight Convolutional

Layered Deep Convolutional Neural Network based Banana Leaf Disease Prediction." 2022 International Conference on Computing, Communication, and Intelligent Systems (ICCCIS), Greater Noida, India, 2022, pp. 313-317. doi: 10.1109/ICC-CIS56430.2022.10037628.

[8] https://wikifarmer.com/banana-plant-protection-major-banana-diseases/

[9] Ojha, T., S. Misra, and N. S. Raghuwanshi. "Wireless sensor networks for agriculture: The state-of-the-art in practice and future challenges." Computers and Electronics in Agriculture, vol. 118, 2015, pp. 66-84. doi: 10.1016/j.com- pag.2015.08.011.

[10] Keerthana, C., P. Tejasree, M. V. Subba Rao, R. S. Sai Pavan Kumar, and P. Yalla. "Developing A Framework for Diseases of Banana Plant Based on the Deficiencies of Minerals in the Soil." International Journal of INTELLIGENT SYSTEMS AND APPLICATIONS IN ENGINEERING, vol. 12, no. 17s, 2024, pp. 571–577.

[11] Kakati, J. B., and T. K. Das. "Classification of healthy and unhealthy banana leaves using deep learning approach: A comparative assessment." 2023 4th International Conference on Computing and Communication Systems (I3CS), Shillong, India, 2023, pp. 1-5. doi: 10.1109/I3CS58314.2023.10127309.

[12] Chen, J., J. Chen, D. Zhang, Y. Sun, and Y. A. Nanehkaran. "Using deep transfer learning for image-based plant disease identification." Computers and Electronics in Agriculture, vol. 173, 2020, p. 105393.

[13] Sharma, P., Y. P. S. Berwal, and W. Ghai. "Performance analysis of deep learning CNN models for disease detection in plants using image segmentation." Information Processing in Agriculture, vol. 7, no. 4, 2020, pp. 566-574. doi: 10.1016/j.inpa.2019.11.001.

[14] Ibarra, N. C., M. P. Rivera, and C. O. Manlises. "Detection of Panama Disease on Banana Leaves Using the YOLOv4 Algorithm." 2023 15th International Conference on Computer and Automation Engineering (ICCAE), Sydney, Australia, 2023, pp. 209-214. doi: 10.1109/ICCAE56788.2023.10111416.

[15] Mohanraj, E., R. Hariharan, S. Keerthana, and K. B. Cavin. "Banana Leaf Disease Detection using Advanced Convolutional Neural Network." 2023 International Conference on Sustainable Computing and Smart Systems (ICSCSS), Coimbatore, India, 2023, pp. 597-603. doi: 10.1109/ICSCSS57650.2023.10169485.

[16] Ibarra, N. C., M. P. Rivera, and C. O. Manlises. "Determination of Leaf Degradation Percentage for Banana leaves with Panama Disease Using Image Segmentation of Color Spaces and OpenCV." 2023 15th International Conference on Computer and Automation Engineering (ICCAE), Sydney, Australia, 2023, pp. 269-275. doi: 10.1109/IC-CAE56788.2023.10111455.

[17] Tapiwa, M. "The greenhouse concept as used in agriculture, its advantages and disadvantages." ACADEMIA, San Francisco, CA, USA. Accessed: Aug. 10, 2022. [Online]. Available: https://www.academia.edu.

[18] Shrivastava, V. K., M. K. Pradhan, S. Minz, and M. P. Thakur. "Rice plant disease classification using transfer learning of deep convolution neural network." ISPRS International Archives of the Photogrammetry Remote Sensing & Spatial Information Sciences, vol. XLII-3/W6, 2019, pp. 631-635.

[19] Pujari, S., and N. Bogiri. "Precision Agriculture for Banana Using Wireless Sensor Network." 2017 International Conference on Computing, Communication, Control and Automation (ICCUBEA), Pune, India, 2017, pp. 1-6. doi: 10.1109/ICCUBEA.2017.8464007.

[20] Sahu, P., A. P. Singh, A. Chug, and D. Singh. "A Systematic Literature Review of Machine Learning Tech- niques Deployed in Agriculture: A Case Study of Banana Crop." IEEE Access, vol. 10, 2022, pp. 87333-87360. doi: 10.1109/ACCESS.2022.3199926.

[21] Singh, Amit, Priyanka Sahu, Anuradha Chug, and Dinesh Singh. "A Systematic Literature Review of Machine Learning Techniques Deployed in Agriculture: A Case Study of Banana Crop." IEEE Access, 2022, pp. 1-1. doi: 10.1109/ACCESS.2022.3199926.

[22] J V, Anchitaalagammai, S. Kavitha, S. Murali, R. Deepalakshmi, R. Janani, R. Dharshini, and B. Wafeqa. "NexGen AgriCare: Advancing Crop Resilience via Real-Time Disease Detection and IoT-Driven Results for Banana Crop." (2024): 1-8. doi: 10.1109/ic-ETITE58242.2024.10493649.

[23] Keerthana, C., M. V. Subba Rao, P. Yalla, P. Tejasree, and R. S. Sai. "Strategic Implementation of Disease Management in Banana Plants Through Soil Mineral Deficiency Correction." International Journal of Electrical and Electronics Engineering, vol. 12, no. 17s, 2024, pp. 254-260. doi: 10.14445/23488379/IJEEE-V11I4P127.

[24] Islam, Mohammad & Dey, Golap Kanti. (2019). Precision Agriculture: Renewable Energy Based Smart Crop Field Monitoring and Management System Using WSN via IoT. 10.1109/STI47673.2019.9068017.

[25] Mariya Vinshon V., A.V. Senthil Kumar, Priyanka Sharma, Sarabjeet Kaur, Omar S. Saleh, H.R. Chennamma, Ankita Chaturvedi. "Chapter 3 AI-Equipped IoT Applications in igh-Tech Agriculture Using Machine Learning", IGI Global, 2023

[26] Retinderdeep Singh, Chander Prabha, Neha Sharma.

”Artificial Internet of Things (AIoT) and its Momentous Impact and Challenges in Modern Agriculture”, 2023 International Conference on Integration of Computational Intelligent System (ICICIS), 2023

Multi-Task Visual Information Extraction in Industrial Environments Using Darknet-19 with Depthwise Separable Convolutions

Leijie Yang
School of Arts, Xichang University, Xichang, 615013, China
E-mail: yleijie2024@126.com

Keywords: visual communication, object detection, image information, darknet-19, deep learning

Received: September 23, 2025

In response to the dual challenges of insufficient generalization of traditional image processing methods and high computational complexity of deep learning models in industrial visual scenes, this study proposes a two-stage solution integrating object detection and a deep learning scheme. The scheme employs a modified Darknet-19 backbone with depthwise separable convolutions and channel rearrangement mechanisms for multi-scale feature fusion, significantly improving computational efficiency while maintaining accuracy. Experiments on a dataset of 4,000 industrial water level images and 10,000 encoding samples showed that the research method achieved 97% pixel-level accuracy and 5 mm positioning error in water level detection, outperforming suboptimal models by 12%. For encoding recognition, it reached a 97% character recognition rate with only 5% false detection rate. In multi-task scenarios, system interference was reduced to 0.12, with 62% increased video memory usage and stable 25 ms edge latency. The multi-scale photometric transformation achieved a lighting invariance index of 0.93 and improved SNR by 8.7 dB. Lightweight deployment yielded a computational density of 1.26 GMACs/mm² and a 72-hour failure rate below 0.1%. This work provides an accuracy-efficiency balanced solution for industrial vision systems, with applications in smart security and intelligent manufacturing. Future work will focus on adaptive calibration and dynamic pruning for enhanced deployment adaptability.

Povzetek:

1 Introduction

Visual communication plays an increasingly important role in modern information society, and images as information carriers have the significant advantage of "one image is worth a thousand words", which can efficiently convey rich information [1-2]. The advancement of computer vision technology has enabled the automatic extraction of key information from images, demonstrating broad application prospects in fields such as smart security and smart cities [3-4]. Water level detection and coding recognition, as typical visual communication tasks, pose an urgent need for Image Information Extraction (IIE) technology [5-6]. For example, in the non-ferrous smelting scene, due to complex environments, uneven lighting, and inaccurate exposure, the panoramic image has obvious seams and brightness differences. In this context, Subramanyam et al. developed a hybrid descriptor method for multi-camera visual inspection in the steel industry, targeting low registration accuracy and slow stitching of low-texture images. By optimizing feature matching and stitching, the method achieved 91% matching accuracy and 49 ms processing time, outperforming traditional algorithms while producing high-quality, seamless images for real-time steel surface inspection [7]. Chang et al. proposed an improved defect detection method for printed circuit boards to address the issues of low detection accuracy and high cost in traditional methods. This method improved the segmentation efficiency of the Otsu algorithm by optimizing the Particle Swarm Optimization (PSO) algorithm, and integrated Fast Library for Approximate Nearest Neighbors (FLANN) and Speeded Up Robust Features (SURF) algorithm to improve feature matching. The experiment showed that the accuracy of this method reached 98.9%, significantly improving detection efficiency and accuracy, meeting industrial needs [8]. Zermane et al. proposed an intelligent control system that integrates Support Vector Machine (SVM) and fuzzy logic to address the challenges of complex processes in industrial regulatory systems. This system could accurately identify equipment status, reduce maintenance costs, and improve production efficiency through real-time control commands, achieving substantial improvements to traditional industrial supervision methods [9]. Hridoy et al. proposed a Deep Learning (DL) framework based on transfer learning to address the issue of high data demand in industrial inspection systems.

Table 1: Comparative analysis of industrial visual information extraction methods.

Research Method	Accuracy(%)	Processing Speed	Application Domain	Limitations
Hybrid Descriptor-based Stitching [7]	91	High	Low-texture Image Stitching	Low robustness to lighting variations; Limited to specific low-texture scenarios
PSO-Otsu+SURF[8]	98.9	Medium	PCB defect detection	Large computational load for feature matching, unstable under
SVM+Fuzzy Logic[9]	Equipment status >95	Real-time	Industrial supervision systems	industrial noise
Xception Transfer Learning[10]	99.72-100	Fast	Industrial defect detection	Relies on manual feature engineering, limited generalization
Weighted Cross-Entropy Loss[11]	Anomaly detection >90	Real-time	Biotechnology industry	High model complexity, difficult edge deployment
U-Net+CNN[12]	99.43-100	30FPS	Toy quality inspection	Background interference suppression needs improvement
Game-theoretic Multimodal Framework [13]	Not Specified	Medium	Human-Robot Collaboration in Assembly	High deployment cost and complexity; Requires strict hardware synchronization; Poor generalization to resource-constrained environments

Comparing the results of various Convolutional Neural Network (CNN) architectures, the optimized Extreme Inception (Xception) model achieved classification accuracy of 100% and 99.72% on nut and casting material datasets, significantly improving the efficiency of industrial defect detection [10].

Fraccaroli et al. proposed a mask-weighted cross-entropy overlap distance loss function training method to address the issue of misjudgment caused by image background interference in Industry 4.0 anomaly detection. This method has been validated in the practical application of anomaly detection projects in the biotechnology industry, maintaining the real-time performance of CNN while significantly improving the accuracy of industrial defect detection [11]. Yang et al. proposed a machine vision detection scheme based on an improved U-shape Convolutional Network (U-Net) and CNN to address poor accuracy in manual quality inspection of toy sets. This method achieved an accuracy rate of 100% and 99.43% for both whole machine and single piece inspections, significantly improving the level of toy automation quality inspection [12]. Chu et al. developed a game-theoretic multimodal framework integrating visual, auditory, and tactile sensing to optimize human-robot collaboration in industrial assembly. The system enhanced task allocation and decision-making, improving conflict resolution efficiency while maintaining security, adaptability, and real-time responsiveness for intelligent manufacturing [13]. Dei et al. developed a multimodal feedback system to address the issues of low efficiency in human-machine collaboration and difficulty in neural differentiation group interaction in industrial environments. This multimodal interaction strategy significantly improved workplace accessibility, enhanced human-machine collaboration efficiency, and improved worker well-being [14]. To systematically outline the strengths and weaknesses of existing technologies and establish a clear benchmark for comparing the method proposed in this paper, Table 1 provides a summary and comparative analysis of the above-related work across four dimensions: accuracy, speed, application domain, and limitations.

Current state-of-the-art (SOTA) methods suffer from three main deficiencies: insufficient robustness to industrial lighting variations and reflections, inadequate real-time performance for high-speed inspection, and a significant trade-off between model complexity and deployment efficiency. This paper addresses these limitations through a novel framework integrating multi-scale feature fusion and Depthwise Separable Convolution (DSC) techniques. Specifically, a multi-scale photometric transformation strategy enhances lighting invariance, while a lightweight Darknet-19 design achieves 25 ms edge inference latency. Additionally, a channel rearrangement mechanism compresses the model to 4.3 MB without sacrificing accuracy.

The proposed unified architecture balances accuracy and efficiency by bridging the gap between traditional image processing methods with high computational efficiency but poor generalization ability and accurate but resource-intensive DL methods. Key innovations include a multi-scale fusion mechanism for robustness, computational density optimization (1.26 GMACs/mm²) for real-time performance, and channel rearrangement for reduced memory footprint. Applied to water level detection and encoding recognition tasks, the incorporation of DSC and architectural modifications maintains high accuracy while drastically improving computational efficiency.

This study systematically addresses three core research questions through targeted technical innovations: (1) Lightweight Darknet-19 with DSCs for SOTA detection under industrial noise; (2) Multi-scale feature fusion to enhance lighting robustness in water level detection; (3) Optimal balance between computational efficiency and accuracy for multi-task edge deployment. Each component, including Darknet-19 modifications, dictionary learning integration, and channel rearrangement, is strategically designed to resolve these challenges through optimized architectural solutions.

2 Methods and materials

2.1 IIE Method integrating object detection and DL

This study formulates a multi-task optimization framework where an input image I is processed for two core tasks: water-level detection as binary classification and encoding recognition as multi-class classification. Training employs an alternating sampling strategy with a 1:1 task ratio per batch. Loss function balancing is achieved through weighted summation: $L_{total} = \lambda \cdot L_{water} + \upsilon \cdot L_{code}$, where L_{water} is MSE loss for water level detection, L_{code} is cross-entropy loss for encoding recognition, and hyperparameters (λ =0.6, υ =0.4) are optimized via grid search. The MTL architecture employs hard parameter sharing, with Darknet-19 backbone extracting shared features and task-specific layers handling regression and classification. The objective function of water level detection aims at minimizing the positioning error and maximizing the accuracy. The specific definition is shown in equation (1).

$$\min L_{water} = \alpha \cdot Error(y, \hat{y}) + \beta \cdot Complexity(M) \quad (1)$$

In equation (1), y is the true water level position. $\hat{y}$ is the predicted value. M represents the model. α and β are regularization parameters. Similarly, for encoding recognition, the task is formulated as a cross-entropy minimization problem. This formalization ensures that each component addresses the research questions through measurable objectives. Industrial visual inspection faces a critical challenge: traditional image processing methods lack generalization for complex conditions, while DL models suffer from high computational complexity, hindering real-time performance [15-16]. To resolve this dilemma, this study proposes a novel two-stage framework that synergistically integrates object detection with DL, enabling end-to-end collaborative optimization of target localization and recognition. Specifically addressing reflection interference in water level detection, the method reformulates water level line positioning as a binary image classification task. A sliding window mechanism scans the image to classify regions as either wall/benchmark or water wave areas. A Dictionary Learning Method (DLM) is then employed to build an efficient and accurate classification model. The overall DLM framework is depicted in Fig.1.

The DLM implementation process in Fig.1 consists of three core steps. Firstly, preprocess the color water level images collected from multiple scenes, and unify the data format through weighted grayscale conversion using equation (2). Subsequently, it trains and generates a feature dictionary based on processed image samples, and ultimately uses this dictionary to drive sliding window classification, determining the vertical axis of the water level line through category transition points.

$$Gray(x, y) = 0.3 \times R(x, y) + 0.59 \times G(x, y) + 0.11 \times B(x, y) \quad (2)$$

In equation (2), $Gray(x, y)$ is the grayscale intensity value of the output image at pixel coordinate (x, y). $R(x, y)$, $G(x, y)$, and $B(x, y)$ correspond to the channel intensity values of the red, green, and blue primary colors of the input color image at position (x, y).




Figure 1: Flowchart of dictionary learning classification.

The image is preprocessed via weighted grayscale conversion, and a 400×700 pixel ROI is extracted to reduce interference. Dense sampling with a 20-pixel sliding window generates an 8000-dimensional feature vector, constructing a 20000×8000-dimensional training matrix Y for dictionary learning. To integrate DLM with DL into a unified framework, sparse encoding vectors from DLM serve as input to Darknet-19. This two-stage process involves DLM performing initial water level detection, followed by Darknet-19 processing its output features for encoding recognition, enabling end-to-end optimization. During training, the DLM objective function (Equation (3)) is combined with the Darknet-19 loss via a weighted sum, allowing DLM to function as both a preprocessing and a supervision module.

$$D = \arg\min_D \left(\min_{\| S\|_0 \le L} \frac{1}{N} \| Y - DS\|_F^2 - \alpha \min_{\| S\|_0 \le L} \frac{1}{\bar{N}} \| \bar{Y} - DS\|_F^2 \right) \tag{3}$$

In equation (3), α is the regularization parameter. L is the sparse constraint level. N and $\bar{N}$ represent the number of positive and negative samples. D is the dictionary matrix. S is a sparse encoding vector. $\bar{Y}$ is a negative sample matrix. This objective function, which balances intra-class reconstruction and inter-class discrimination through parameter tuning, is optimized via the Alternating Direction Method of Multipliers (ADMM). Dictionary atoms are updated using K-SVD to ensure representativeness, while sparse coding satisfying the constraints is solved via the Orthogonal Matching Pursuit (OMP) algorithm[17-18]. For water level calculation, the sparse coding solution is first applied to test sample k as formulated in equation (4).

$$\hat{s} = \arg\min_s \| k - Ds\|_2^2 + \beta \| s\|_1 \tag{4}$$

In equation (4), $\hat{s}$ is the optimal sparse encoding vector that is ultimately solved. s is the candidate encoding vector in the optimization process. β is the regularization coefficient. The water level line is located by scanning the ROI area from top to bottom using a sliding window with a 1-pixel step. The y-axis position where the classification first changes from "benchmark" to "water wave" is recorded, and the actual water level value R is then calculated using preset calibration parameters in equation (5).

$$R = l_r + (y - l_w) \times \frac{w_r}{w_w} \tag{5}$$

In equation (5), l_r and l_w are reference scales. w_r and w_w are the correspondence between actual size and pixel size. To overcome the poor generalization of the computationally efficient yet scenario-specific DLM, this study introduces a multi-scale feature fusion architecture. This architecture employs spatial pyramid pooling for multi-granularity feature extraction, combined with cross-scale upsampling and an adaptive attention weighting mechanism to dynamically optimize the contribution of features at different scales, as formulated in equation (6).

$$F_{used} = \Sigma(w_m \cdot F_m) \tag{6}$$

In equation (6), F_{used} is the final fused feature. w_m is the dynamic weight of the m-th layer feature. F_m is the feature of the m-th level feature pyramid. Fig.2 shows the pyramid feature fusion process, demonstrating the hierarchical relationship between its underlying texture, mid-level fluctuations, and global features.

Building on the multi-scale feature fusion technique developed for water level detection, this study extends it to industrial coding recognition via a two-stage framework. The first stage employs Darknet-19 for real-time encoding block localization, while the second stage utilizes dedicated classifiers for cargo and vehicle codes. This approach effectively addresses challenges like complex backgrounds and character deformation through task decoupling, enhancing recognition accuracy without compromising real-time performance. The Darknet-19 backbone architecture is detailed in Fig.3.




Figure 2: Schematic diagram of pyramid feature fusion process.




Figure 3: Darknet-19 backbone network architecture.

Fig.3 illustrates the Darknet-19 backbone network architecture. The network accepts a 224×224 input image and progressively reduces spatial resolution to 7×7 through a series of convolutional and pooling layers, facilitating multi-scale feature extraction essential for encoding block localization. The model employs an end-to-end regression architecture, bypassing region proposal steps to accelerate detection. In the first stage, a Sigmoid activation function is used for binary classification (encoding block presence detection) to enhance speed. The subsequent recognition stage utilizes dedicated Softmax outputs, 10 classes for cargo codes and 36 for vehicle codes, enabling precise character-level classification within the located regions. In response to the problem of insufficient data in industrial scenarios, this study proposes geometric transformations to enhance perspective adaptability. The image data enhancement strategy is shown in Fig.4.

Fig.4 systematically illustrates the data augmentation strategy, categorized into geometric and color space transformations. Geometric operations, including flipping, rotating, and scaling, expand the diversity of spatial features, but require synchronous adjustment of ground truth coordinates. Color space transformations, such as contrast enhancement and histogram equalization, modify only pixel values to improve lighting robustness without altering target positions. Together, these complementary techniques significantly enhance the model's generalization capability against spatial and photometric variations.

2.2 Optimization scheme based on DSC

After building an IIE framework that integrates object detection and DL, it is found that existing models still face key bottlenecks such as high computational complexity and difficulty in real-time deployment on industrial equipment [19]. To address these issues, the DSC architecture is introduced, which achieves network lightweighting while ensuring feature extraction capability through standard convolution decomposition and reconstruction. This optimization scheme implements a differentiated design for two core tasks, including a water level classification network and coding recognition. Firstly, for the water level classification network, a combination of deep convolution and 1×1 pointwise convolution is used instead of the traditional 3×3 standard convolution. The schematic diagram of standard convolution and DSC is shown in Fig.5.

In Fig.5, the standard convolution uses a 3D convolution kernel ($M \times d \times N$) to simultaneously process spatial features and channel relationships, and its computational complexity increases exponentially with the number of input and output channels. The standard convolution computation is shown in equation (7).

$$Q_{\text{standard}} = d_a \times d_a \times d_b \times d_b \times M \times N \tag{7}$$





Figure 4: Image data enhancement strategy.



(a) Standard convolution (b) Depth separable convolution

Figure 5: Dimension diagram of standard convolution and DSC.

In contrast, DSC decomposes standard convolution into two independent steps: Step 1 is to perform channel by channel deep convolution, using M single channel convolution kernels to process each input channel separately. Step 2 is to achieve channel dimension transformation through 1×1 pointwise convolution. The computational complexity of this method is shown in equation (8). To clearly illustrate the integration of DSC into Darknet-19, Fig.5 (b) provides a standard convolutional layer, and Fig.5 (a) is a comparative block diagram of the improved DSC layer. In the proposed implementation, the standard 3×3 convolutional layers at positions [3, 6, 9, 12, 15] in the original Darknet-19 backbone are replaced with DSC blocks. Each DSC block comprises a depthwise convolution for spatial filtering, followed by a pointwise convolution for channel combination. This strategic substitution significantly reduces computational complexity while preserving feature extraction performance, which is especially advantageous for real-time encoding localization tasks.

$$Q_{\text{depth}} = d_a \times d_a \times d_b \times d_b \times M + M \times N \times d_a \times d_a \quad (8)$$

Secondly, the encoding localization network enhances feature reuse through a channel rearrangement mechanism [20]. This mechanism inserts a feature reconstruction layer between deep convolution and pointwise convolution layers, first dividing the input feature map into four optimized feature groups. Random channel shuffling operation is implemented within each group, and feature recombination and concatenation are achieved through equation (9).

$$F' = Concat\left[Shuffle(F_1), ..., Shuffle(F_g)\right] \quad (9)$$

In equation (9), F_1 is the i-th group of the input feature map. g is the grouping hyperparameter. The channel rearrangement mechanism delivers three principal advantages: cross-group channel replacement overcomes local receptive field constraints by establishing long-range feature dependencies;an asymmetric shuffling strategy applies intensive reorganization to low-level detail features while employing moderate rearrangement for high-level semantic features, enabling layer-adaptive processing; and a dynamic grouping mechanism automatically adjusts the partition count based on feature map resolution, utilizing 4 groups for 112×112 high-resolution maps while reducing to 2 groups for 56×56 lower-resolution inputs. This design ensures optimal feature interaction across scales while maintaining computational efficiency.


This study presents a comprehensive industrial visual information extraction system for two core tasks: water level detection and encoding recognition. For water level detection, a multi-scale feature fusion algorithm effectively integrates DLM and DL. For encoding recognition, a two-stage framework utilizes Darknet-19 for localization, followed by a dedicated classifier. To address real-time deployment challenges, a DSC optimization scheme with channel rearrangement significantly reduces computational complexity. Supported by data augmentation and lightweight techniques, the solution demonstrates strong task adaptability, environmental robustness, and edge efficiency. For reproducibility, the Adam optimizer (β_1=0.9, β_2=0.999) is used with a batch size of 32, initial learning rate of 0.001, and cosine annealing (reduced by 0.1 every 50 epochs) over 300 rounds. Key hyperparameters include weight decay (0.0005), momentum (0.9), and loss weights α=0.6 (water level) and β=0.4 (encoding). All experiments run on a 4×NVIDIA RTX 8000 GPU setup with one-click Docker deployment.

3 Results

3.1 Performance verification experiment

The experiment conducts a comparative study on industrial water level detection tasks in the hardware environment of Intel Xeon Gold 6248R processor and NVIDIA RTX 8000 graphics card. The experimental dataset comprises 4,000 industrial water level images with reflection and wave interference under diverse lighting conditions, partitioned into 3,200 training and 800 test samples (80-20 split). For encoding recognition, 10,000 samples from a hexagonal nut dataset are equally divided between cargo and vehicle codes (5,000 each), following the same 80-20 training-testing ratio. To enhance model robustness, data augmentation strategies are implemented including geometric transformations (horizontal flipping at 0.5 probability, ±15° rotation, 0.8-1.2 scaling) and color space manipulations, all applied synchronously to images and ground truth bounding boxes using coordinate transformation formulas from Equation (6). The datasets are available upon request for research purposes, and focus on comparing the performance differences of five


algorithms: SIFT feature matching, PSO-Otsu Thresholding (PSO-Otsu), SVM classification, traditional edge detection, and an optimized information extraction algorithm. Through a systematic evaluation of four core indicators, namely Pixel-level Accuracy (PA), water level positioning error, Peak Signal-To-Noise Ratio (PSNR), and single frame processing delay, the comparative results are shown in Fig.6.



(a) Comparison between detection accuracy and positioning performance

(b) Comprehensive evaluation of quality and efficiency

Figure 6: Comprehensive evaluation of quality and efficiency.



(a) Character recognition performance comparison

(b) Comprehensive evaluation of efficiency and quality

Figure 7: Multi-dimensional performance comparison of industrial character recognition model.

Fig.6 demonstrates the superior performance of the proposed method across key metrics. In Fig.6(a), it achieves a leading 97% PA with a minimal 5 mm positioning error, significantly outperforming other algorithms. The model excels in both tasks, with high water level detection accuracy (0.95 IoU, 0.98 mAP) and encoding recognition rates (98% for cargo, 96% for vehicle), while a confusion matrix (Table 4) reveals minimal misclassification. Fig.6(b) shows the algorithm maintains a high PSNR of 34 dB and a low latency of 25 ms, confirming its comprehensive advantages in image quality and real-time processing for industrial scenarios.

To rigorously validate industrial coding recognition robustness, the experiment utilized an expanded dataset of 10,000 samples. This dataset incorporated simulated real-world challenges through ±15° rotations and contrast adjustments [0.8, 1.2]. The proposed Darknet-19 scheme was benchmarked against FLANN+SURF, YOLOv5, Faster R-CNN, and Xception using a multi-faceted evaluation system measuring Character Recognition Rate (CRR), False Positive Rate (FPR), Structural Similarity Index (SSIM), and model parameters. The experimental results are shown in Fig.7.

Fig.7 presents a multi-dimensional performance comparison, demonstrating the superiority of the improved Darknet-19 model. As shown in Fig.7(a), the proposed method achieves a leading CRR of 97% while maintaining a low FPR below 5%, outperforming YOLOv5 (95% CRR, 7% FPR). Concurrently, Fig.7(b) highlights the model's efficiency, with a compact parameter size of 12MB and an inference delay of 25ms, while achieving a high SSIM of 0.91. This balance between a lightweight architecture and high recognition accuracy validates the improved Darknet-19 as an optimal solution for industrial-grade character recognition tasks. To quantify the specific contribution of DSC to the overall performance, an ablation study is conducted comparing the proposed DSC-modified Darknet-19 with a baseline version using standard convolutional layers. The experimental results are shown in Table 2.


Table 2 shows that replacing standard convolutions with depthwise separable versions drastically improves efficiency: model size is compressed by 62.9% to 4.3MB, computational load droppes 37.5%, and latency is reduced by 34.2% to 25 ms. Although CRR only decreases slightly by 0.6%, the results confirme the optimal balance between efficiency and maintaining industrial deployment accuracy. An extensive ablation study is conducted to rigorously quantify the individual contributions of the proposed architectural components: multi-scale feature fusion, DSC, and channel rearrangement. The baseline model (Model A) employs standard convolution and single-scale features. Subsequent models incrementally integrate multi-scale fusion (Model B), DSC (Model C), channel shuffling (Model D, and the full proposed model). The evaluation on the water level detection task results are summarized in Table 3.

Table 2: Ablation study: DSC vs standard convolution performance comparison.

Metric	Standard Conv Baseline	DSC-Modified	Improvement
Model Size	11.6MB	4.3 MB	-62.9%
Computational Load	400 GFLOPs	250 GFLOPs	-37.5%
CRR	97.8%	97.2%	-0.6%
Inference Latency	38 ms	25 ms	-34.2%
Memory Usage	520 MB	300 MB	-42.3%

Table 3: Ablation study of key architectural components.

Model	Multi-Scale Fusion	DSC	Channel Shuffling	PA (%)	Positioning Error (mm)	Model Size (MB)	Latency (ms)
A	×	×	×	91.2	8.5	11.6	38
B	√	×	×	94.5	6.8	11.8	41
C	√	√	×	96.1	5.9	5.2	29
D (Proposed)	√	√	√	97.0	5.0	4.3	25



(a) Real-time processing efficiency comparison

(b) Consumption characteristics of video memory resources

(c) edge computing responsiveness

(d) theoretical calculation load analysis

Figure 8: 4D comparison of parameter quantity-performance relationship of DL model.

Table 3 clearly quantifies the incremental benefits of each architectural component. The addition of Model B alone boostes PA by 3.3% and reduces positioning error by 1.7 mm. Replacing standard convolutions with DSC (Model C) drastically improves efficiency, slashing model size by 56% and latency by 29%, while further increasing accuracy. Finally, incorporating channel rearrangement (Model D) yields the optimal model, achieving the best performance (97.0% PA, 5.0 mm error) with the smallest size (4.3MB) and lowest latency (25 ms). This ablation study confirms that multi-scale fusion improves accuracy, DSC improves efficiency, and channel transformation optimizes both, ultimately achieving excellent performance of the complete model. To verify the performance advantages of research networks in terms of computational efficiency, three representative architectures are selected for comparison: MobileNet Version 3 (MobileNetV3), Faster R-CNN, and Raw Darknet-19. The design of the evaluation system covers three key dimensions: throughput, GPU memory usage, edge latency, and computational complexity. The input resolution is fixed at 512×512 to unify the testing conditions, as shown in Fig.8.

Fig.8 presents a 4D performance comparison, demonstrating the superior efficiency of the improved Darknet-19. The model achieves a leading balance of 30 FPS and 250 GFLOPs at 25M parameters, significantly outperforming comparative architectures. Specifically, Fig. 8(a) shows the improved Darknet-19 attains 30 FPS, doubling the speed of MobileNetV3 (15 FPS) and surpassing Faster R-CNN (25 FPS). Fig.8(b) indicates a memory usage of 300MB, a 100MB reduction compared to Faster R-CNN. Fig.8(c) reveals an edge latency of 25 ms, superior to MobileNetV3's 50 ms and Faster R-CNN's 40 ms. Fig.8(d) demonstrates a computational cost of 250 GFLOPs, which is 37.5% lower than Faster R-CNN. This comprehensive advantage across all metrics validates its industrial deployment strengths. To further assess generalization, 5-fold cross-validation on 4,000 water level images yields a consistent accuracy range of 95.2%-97.8% (SD ± 1.1%). External testing on a public dataset with 2,000 images confirms robust cross-scenario stability, maintaining 94.5% pixel-level accuracy and 6 mm positioning error on unseen samples.

3.2 Scene verification experiment


To verify the robustness of the proposed multi-scale photometric transformation strategy in extreme industrial lighting environments, this experiment uses Basler ace acA2000-50gc industrial camera to collect three typical industrial scene data: strong reflective water surface, low illumination coding area, and dynamic shadow interference. The comparative methods cover four classic lighting processing methods: traditional color constancy theory, histogram equalization, Contrast Limited Adaptive Histogram Equalization (CLAHE) algorithm, and Retina Cortex (Retinex) Theory. The validation indicators consider both physical properties and visual quality: Light Invariance Index (LII), Dynamic Range Retention Rate

(DRR), SURF, SNR, and color distortion, as shown in Table 4.

Table 4 demonstrates the superior performance of the multi-scale photometric transformation strategy across all evaluated metrics. The method achieves a leading LII of 0.93, a 14.8% improvement over the Retinex method, and a DRR of 94.3%, surpassing CLAHE by 9.1%. It also attains a 91.7% feature matching rate (8.3% higher than comparative methods), an 8.7 dB SNR improvement for noise suppression, and excellent color fidelity with a ΔE of 3.2. By excelling in all five core indicators, the strategy effectively resolves lighting interference issues in industrial detection scenarios. The term "task decoupling" is defined as separating public feature extraction from task-specific processing via a hard parameter-sharing architecture, mathematically formulated as $F_{shared} = \Phi(I)$ and $Y_{task} = \Psi_{task}(F_{shared})$. Φ is the shared encoder and Ψ_{task} is the task-specific decoder. Resource Sharing Efficiency (RSE) is quantified by the protocol: $RSE = 1 - \frac{\sum_{i=1}^{N} |L_{i,shared} - L_{i,alone}|}{N \cdot L_{\max}}$, where $L_{i,shared}$ and $L_{i,alone}$ denote the loss of task under multi-task and independent training, respectively, and $L_{\max}$ is a normalization factor. The computational efficiency of three multi-task schemes, independently trained models, traditional MTL, and the proposed decoupling architecture, is evaluated on an NVIDIA Jetson AGX Xavier platform using a mixed dataset. Key performance dimensions, including Multi-Task Interference (MTI), RSE, and Memory Growth Rate (MGR), are assessed, with results detailed in Fig.9.

Table 4: Performance comparison of illumination processing algorithms.

Evaluation dimension	Test index	Color constancy	Histogram equalization	CLAHE	Retinex	Multi-scale photometric transformation strategy
Illumination stability	L index (0-1)	0.68	0.72	0.75	0.81	0.93
Detail reservation	DRR/%	82.4	78.6	85.2	88.7	94.3
Characteristic-induced	SURF matching repetition rate /%	71.5	65.8	76.2	83.4	91.7
Noise suppression	SNR/dB	4.2	3.8	5.1	6.3	8.7
Color fidelity	ΔE	6.8	8.2	5.7	4.9	3.2



(a) Evolution trend of multi-task interference degree

(b) Optimization process of resource sharing efficiency

(c) Control characteristics of video memory occupation

(d) Task switching delay evolution

Figure 9: Comparison of dynamic evolution of key indicators in MTL.

Table 5: Comparison of test results of edge deployment in extreme environment.

Evaluation dimension	Test index	Original Darknet-19	TensorRT-optimized edition	Lightweight scheme
Temperature stability	ΔT fluctuation range/℃	±5.1	±3.8	±2.3
Resistance to mechanical vibration	Fault tolerance rate	82.4%	89.7%	95.3%

Electromagnetic compatibility	Immunity (EMI/dB)	5.2	4.1	2.8
Computational efficiency	Calculated density (GMACs/mm²)	0.37	0.89	1.26
Long term stability	72h failure rate	1.7%	0.6%	0.09%
Model compression	Storage volume (MB)	11.6	6.2	4.3

Fig.9 demonstrates the superior performance of the proposed decoupling architecture across all multi-task evaluation metrics. As illustrated, the architecture achieves minimal MTI of 0.12, representing a 76.9% reduction compared to traditional methods. It also attains 89.3% RSE, a 23.2% improvement, while optimizing MGR to +62% (70.5% better than traditional MTL). The architecture achieves 8.4 ms task switching latency, reducing delay by 70.6% while maintaining stable performance under industrial multi-tasking conditions. Subsequently, the edge computing reliability of the lightweight scheme is verified under extreme industrial conditions. Testing is conducted on a Raspberry Pi 4B platform within an environmental chamber (-20°C to 60°C), simulating harsh industrial scenarios including electromagnetic interference and mechanical vibration. The proposed scheme is compared against original Darknet-19, Tensor Runtime, and Tensor RT implementations to assess its robustness in challenging deployment environments. The reliability test is deployed on a Raspberry Pi 4B. It subjects the system to extreme environmental stresses, including temperature cycling (-20 ℃ to 60 ℃), mechanical vibration (10-500 Hz), and electromagnetic interference (10 V/m). Over a 72-hour continuous run, key metrics including CPU utilization, memory usage, inference latency, and system crash counts, are monitored. The system is deemed fault-tolerant if it experiences ≤2 crashes with auto-recovery under 30 seconds. The failure rate is calculated as (crashes / total runtime) × 100%. The benchmark models are Faster R-CNN and Xception. The validation indicators include temperature stability, vibration fault tolerance, electromagnetic immunity, computational density, and 72-hour continuous operation failure rate, as shown in Table 5.

In Table 5, temperature fluctuations are controlled at ± 2.3 ℃, a decrease of 54.9% compared to the original Darknet-19. The vibration fault tolerance rate reaches 95.3%, an increase of 15.6%. The electromagnetic immunity is 2.8 dB, with a decrease of 46.2%. In terms of computational efficiency, DSC achieves a computational density of 1.26 GMACs/mm2, which is 41.6% higher than TensorRT. The model volume is compressed to 4.3 MB, a decrease of 62.9%. Model compression employs a three-step pipeline: channel pruning first eliminates 30% of parameters, INT8 quantization then reduces weight precision from FP32 (75% storage saving), and Huffman coding provides final lossless compression. The overall ratio is calculated as: Final Size = Original Size × (1 - 0.3) × (8/32) × Huffman Ratio. Long-term operation testing shows that the 72-hour failure rate is only 0.09%, a decrease of 94.7% compared to the benchmark. The lightweight solution provides key technical support for industrial edge deployment.

4 Discussion

This study demonstrates that the proposed method achieves significant performance improvements over baseline approaches, with a 12% higher PA (97% vs. 85%) compared to SIFT/PSO-Otsu. These advantages are attributed to three key innovations: (1) DSCs reduce computational complexity by 37.5% while maintaining feature extraction capability; (2) Channel rearrangement compresses the model size to 4.3MB without sacrificing accuracy; (3) Multi-scale photometric transformation enhances lighting robustness, achieving a 0.93 LII versus 0.78–0.85 for traditional methods. The design involves a trade-off of a 62% memory usage increase for substantial gains in accuracy and real-time performance (25 ms latency). However, the method has limitations. It depends on manual reference scale calibration for water level detection, and its performance may degrade under extreme occlusion (>70% surface coverage) or in high-reflectivity environments where water surface features become indistinguishable. These scenarios represent potential failure cases, necessitating supplementary solutions like polarization filters or sensor fusion in practical deployments.

5 Conclusion

This work successfully addresses the trade-off between traditional methods' poor generalization and DL models' high computational complexity in industrial vision tasks. By integrating a modified Darknet-19 backbone with multi-scale feature fusion, DSC, and channel rearrangement, the proposed two-stage framework achieves an optimal balance between accuracy and efficiency. Experimental results validated its effectiveness: 97% PA and 5 mm positioning error in water level detection, 97% CRR with 5% FPR in encoding recognition, and robust multi-task performance with minimal interference (0.12 MTI). The system also exhibited exceptional environmental adaptability (0.93 LII, 94.3% DRR, 8.7 dB SNR improvement) and reliable edge deployment capabilities, achieving a computational density of 1.26 GMACs/mm2, a 72-hour failure rate below 0.1%, and stable temperature fluctuation control within ±2.3 °C.

6 Funding

The research is supported by Strategies for Enhancing Core Competencies of Design Majors Based on Employment Market Demand", the third phase of the Ministry of Education's supply-demand docking employment and education project, project number: 2024032556396, hosted and under research; the Discipline and Professional Construction Climbing Plan Art and Sports Research Special Project of Xichang University was approved, titled "The Impact of Artificial

Intelligence on the Career Path of Design Major and Response Strategies". Project number: PDZX202415 , hosted and under research.

References

[1] Shuhua Zhao, Jianxin Zhu, Jiang Lu, Zhibo Ju, and Dong Wu. Lightweight human behavior recognition method for visual communication AGV based on CNN-LSTM. International Journal of Crowd Science, 9(2):133-183, 2025. https://doi.org/10.26599/IJCS.2024.9100014

[2] Chuqiao Xu, Linchen Xu, Kai Luo, Jitao Zhang, Adilanmu Sitahong, Ming Yang, and Chengjun Zhang. The essence and applications of machine vision inspection for textile industry: A review. The Journal of the Textile Institute, 116(10):2286-2310, 2024. https://doi.org/10.1080/00405000.2024.2426257

[3] Abdelali Taatali, Sif Eddine Sadaoui, Mohamed Abderaouf Louar, and Brahim Mahiddini. On-machine dimensional inspection: machine vision-based approach. The International Journal of Advanced Manufacturing Technology, 131(1):393-407, 2024. https://doi.org/10.1007/s00170-024-13081-1

[4] Hamam Mokayed, Tee Zhen Quan, Lama Alkhaled, and Sivakumar Vengusamy. Real-time human detection and counting system using deep learning computer vision techniques. Artificial Intelligence and Applications. 1(4): 221-229, 2023. https://doi.org/10.47852/bonviewAIA2202391

[5] Attoumane Abi, Julien Walter, Romain Chesnaux, and Ali Saeidi. Groundwater level monitoring using exploited domestic wells: Outlier removal and imputation of missing values. Hydrogeology Journal, 32(3):723-737, 2024. https://doi.org/10.1007/s10040-023-02740-4

[6] Joshua Snell, Matthew Simons, and Leonie Warlo. A test of letter configuration coding in visual word recognition. Language, Cognition and Neuroscience, 38(6):893-901, 2023. https://doi.org/10.1080/23273798.2023.2179083

[7] Vasanth Subramanyam, Jayendra Kumar, and Shiva Nand Singh. A hybrid descriptor for low-textural image stitching in real-time surface inspection systems. Multimedia Tools and Applications, 83(7):20653-20675, 2024. https://doi.org/10.1007/s11042-023-16357-y

[8] Yuanpei Chang, Ying Xue, Yu Zhang, Jingguo Sun, Zhangyuan Ji, Hewei Li, Teng Wang, and Jiancun Zuo. PCB defect detection based on PSO-optimized threshold segmentation and SURF features. Signal, Image and Video Processing, 18(5):4327-4336, 2024. https://doi.org/10.1007/s11760-024-03075-7

[9] Hanane Zermane, Ahcene Ziar, Hassina Madjour, and Djamel Touahar. Transforming industrial supervision systems: A comprehensive approach integrating machine learning techniques and fuzzy logic. The Scientific Bulletin of Electrical Engineering Faculty, 24(2):52-66, 2024. https://doi.org/10.2478/sbeef-2024-0021

[10] Monowar Wadud Hridoy, Mohammad Mizanur Rahman, and Saadman Sakib. A framework for industrial inspection system using deep learning. Annals of Data Science, 11(2):445-478, 2024. https://doi.org/10.1007/s40745-022-00437-1

[11] Michele Fraccaroli, Alice Bizzarri, Paolo Casellati, and Evelina Lamma. Exploiting CNN's visual explanations to drive anomaly detection. Applied Intelligence, 54(1):414-427, 2024. https://doi.org/10.1007/s10489-023-05177-0

[12] Dezhi Yang, Ning Chen, Qiqi Tang, Hang Zhang, and Jian Liu. Research on defect detection of toy sets based on an improved U-Net. The Visual Computer, 40(2):1095-1109, 2024. https://doi.org/10.1007/s00371-023-02834-w

[13] Dongdong Chu, Shulan Yu, Yuhang Ling, Yang Zhao, and Jianhong Zhang. A game-theoretic and multimodal interaction framework for collaborative robots in smart manufacturing. Decision Making: Applications in Management and Engineering, 7(1):735-751, 2024. https://doi.org/10.31181/dmame7120241433

[14] Carla Dei, Matteo Meregalli Falerni, Turgut Cilsal, Davide Felice Redaelli, Matteo Lavit Nicora, Mattia Chiappini, Fabio Alexander Storm, and Matteo Malosio. Design and testing of (A)MICO: a multimodal feedback system to facilitate the interaction between cobot and human operator. Journal on Multimodal User Interfaces, 19(1):21-36, 2025. https://doi.org/10.1007/s12193-024-00444-x

[15] Harshitkumar j Ghelani. AI-Driven quality control in PCB manufacturing: Enhancing production efficiency and precision. Valley International Journal Digital Library, 12(10):1549-1564, 2024. https://doi.org/10.18535/ijsrm/v12i10.ec06

[16] Ibrahim Yousif, Liam Burns, Fadi El Kalach, and Ramy Harik. Leveraging computer vision towards high-efficiency autonomous industrial facilities. Journal of Intelligent Manufacturing, 36(5):2983-3008, 2025. https://doi.org/10.1007/s10845-024-02396-1

[17] Fanghui Bi, Xin Luo, Bo Shen, Hongli Dong, and Zidong Wang. Proximal Alternating-direction-method-of-multipliers-incorporated nonnegative latent factor analysis. IEEE/CAA Journal of Automatica Sinica, 10(6):1388-1406, 2023. https://doi.org/10.1109/JAS.2023.123474

[18] Monowar Wadud Hridoy, Mohammad Mizanur Rahman, and Saadman Sakib. A framework for industrial inspection system using deep learning. Annals of Data Science, 11(2):445-478, 2024. https://doi.org/10.1007/s40745-022-00437-1

[19] Lin Wang, Yu Shen, Hongguo Zhang, Dong Liang, and Dongxing Niu. Automatic road extraction framework based on codec network. Journal of Measurement Science and Instrumentation, 15(3):318-327, 2024. https://doi.org/10.62756/jmsi.1674-8042.2024033

[20] Wei Liu, Cong Wang, and Yongkang Zhang. Industrial surface defect detection by multi-scale Inpainting-GAN. The Visual Computer, 41(8):5643-5660, 2025. https://doi.org/10.1007/s00371-024-03743-2

Spatially-Guided Bi-Model CNN Architecture for Multi-Noise Localization and Soft-Mask Based Active Noise Cancellation in Indoor Environments

Guoqiang Lu[1*], Yanmin Bai[2], Hairong Wang[3]
[1]School of Internet of Things Engineering, Jiangsu Vocational College of Information Technology, Wuxi 214153, Jiangsu, China
[2]School of Microelectronics, Jiangsu Vocational College of Information Technology, Wuxi 214153, Jiangsu, China
[3]School of Education, Soochow University, Suzhou 215123, Jiangsu, China
E-mail: 2024101345@jsit.edu.cn, baiyanminnuaa@163.com, wanghairong0707@outlook.com
*Corresponding author

Keywords: multi-noise localization, active noise cancellation (anc), overlapping sound events, convolutional neural networks (cnn), mfcc, spatially-guided cnn, attention mechanisms (se, cbam)

Recieved: August 11, 2025

Accurate multi-noise localization and real-time active noise cancellation (ANC) are critical for enhancing audio quality and comfort in smart-bedroom environments. This paper presents a novel deep learning framework, Spatially-Guided CNN Filter Modeling (SG-CFM), designed to both localize multiple overlapping noise sources and simulate soft-mask-based ANC. The proposed architecture employs a modular CNN pipeline with bi-modal frequency–temporal feature extraction, channel and spatial attention modules (SE and CBAM), and residual connections for enhanced context preservation. Key components include the Enhanced Bi-Modal Block (EBMB), Residual Temporal Squeeze Block, Dilated Temporal Convolution Block, and Hierarchical Temporal Aggregation Block, which collectively capture both local and long-range acoustic dependencies. The system is trained and evaluated on the TUT Sound Events 2017 dataset, which contains diverse and realistic indoor and environmental sound events. Each input segment is represented as MFCC-based mel-spectrograms, supporting multi-label learning in overlapping noise conditions. The proposed model achieves an average F1-score of 0.81 across all classes, with strong per-class performance (e.g., AUC of 0.93 for the "car" class), demonstrating its ability to generalize to real-world noisy environments. Compared to standard CNN-based sound event localization models, SG-CFM offers significantly improved multi-label detection accuracy with reduced computational complexity, making it suitable for real-time deployment in embedded IoT devices. Experimental results further demonstrate effective ANC simulation by suppressing noise energy in critical temporal segments through a soft binary mask, highlighting its potential for next-generation smart home audio systems targeting sleep quality, acoustic privacy, and ambient intelligence.

Povzetek: Prispevek predstavlja globokoučni model SG-CFM za pametne spalnice, ki v realnem času lokalizira več prekrivajočih se virov hrupa in simulira aktivno odpravljanje šuma ter pri tem dosega dobro natančnost (povp. F1 = 0,81) ob manjši računski zahtevnosti, primerni za vgradne IoT naprave.

1 Introduction

In the modern world, ambient noise pollution has emerged as a persistent challenge, significantly degrading quality of life, particularly in residential and bedroom environments. With increasing urbanization, smart home appliances, and mixed-use infrastructure, sources such as traffic, construction, HVAC systems, digital alarms, and domestic electronics contribute to a complex and dynamic soundscape. These noise sources not only disrupt sleep quality and mental well-being but also impair focus and long-term health outcomes. Traditional sound insulation techniques are either static, costly, or limited in adaptability, necessitating intelligent, adaptive, and environment-aware solutions.Recent advances in deep learning, particularly Convolutional Neural Networks (CNNs), have demonstrated remarkable potential in audio classification and sound event detection. However, existing systems either focus solely on noise detection or aim at signal enhancement using heavy-weight generative models like GANs or recurrent architectures. They only address both localization and active suppression of multiple simultaneous noise sources in a unified and computationally efficient framework. Moreover, most

prior approaches overlook the spatial and temporal dynamics inherent to real-world acoustic patterns, especially in constrained indoor spaces like bedrooms. Motivated by these limitations, this paper introduces a novel dual-purpose system for multi-noise localization and active noise cancellation (ANC) tailored specifically for bedroom environments. The proposed model, Spatially-Guided CNN Filter Modeling, leverages specialized CNN blocks incorporating bi-modal feature fusion, residual attention mechanisms, and frequency-temporal decomposition to model the spatial characteristics of noise more effectively. In addition to identifying multiple overlapping noise classes, the system is capable of generating soft spectrotemporal suppression masks that simulate ANC behavior reducing the energy of nuisance components in the input signal. Unlike traditional monolithic architectures, our model adopts a lightweight, interpretable, and multi-output design, ensuring both real-time feasibility and robustness across diverse noise conditions. By integrating frequency bottlenecks, CBAM (Convolutional Block Attention Modules), and a dedicated ANC head, the system learns to both recognize and attenuate noise in a resource-constrained setup. The primary contributions of this work are a unified CNN architecture that performs multi-label noise localization and soft-mask-based active noise cancellation, Spatially-guided filtering mechanisms, including channel-spatial attention and temporal-frequency blocks, to enhance acoustic feature learning, domain-specific focus on bedroom sound environments, addressing real-life overlapping noise scenarios that are often neglected in generic datasets and demonstration of real-time feasibility through a lightweight implementation using separable convolutions and low-latency pooling operations. This research lays the groundwork for future smart-bedroom applications, such as sleep-aware acoustic regulation, privacy-preserving background noise suppression, and intelligent audio control in ambient computing systems.

This study investigates whether lightweight spatially-guided CNN architectures can jointly perform multi-label noise localization and soft ANC mask generation on single-microphone indoor acoustic scenes by looking for some research questions like, Can spatially-guided convolutional modules (CBAM, SE) enhance feature disentanglement sufficiently to replace recurrent/transformer blocks for overlapping noise events?, Can such a lightweight model (<1M parameters) achieve competitive accuracy (F1 > 90%) compared to SOTA CRNN/AST baselines? And can the model maintain real-time inference capability suitable for embedded ANC deployment? The Quantitative goals would be to Achieve ≥90% F1 score, improving baseline CRNN performance (∼85%) by at least +5%, Reduce parameter count by >80% compared to Transformer-based AST and Maintain inference speed suitable for real-time ANC (<20ms/frame).

2 Related work

The problem of environmental noise management has been studied from multiple perspectives, including sound event detection, source localization, and active noise cancellation. Each of these domains brings complementary strengths, yet few approaches cohesively integrate spatial awareness with adaptive suppression in realistic multi-noise indoor scenarios.

2.1 Multi-noise detection and localization

Traditional sound event detection systems, often based on CNNs or recurrent networks, focus on identifying single or multiple overlapping acoustic events from time–frequency representations. Localization of sound sources, especially in reverberant indoor environments, introduces additional complexity due to spatial mixing and non-stationary characteristics of sources. Methods incorporating spatial cues (e.g., inter-channel phase differences in microphone arrays) have shown improved localization, but they usually assume multiple sensors or do not jointly perform `

The incorporation of attention modules, such as channel and spatial attention, has recently improved the discriminative power of convolutional networks in audio and vision tasks. Convolutional Block Attention Module (CBAM) and squeeze-and-excitation blocks enable the network to re weight salient frequency–temporal features adaptively, leading to better robustness under noisy conditions. However, most prior work leverages attention purely for classification or detection, without explicitly coupling it with downstream cancellation or mask generation for suppression.

2.3 Active noise cancellation (ANC)

Classical ANC systems rely on adaptive filters (e.g., LMS, FxLMS) and require feedback/reference sensors to invert the noise signal. Deep learning approaches for ANC have started to emerge, where neural networks either learn residual noise patterns or directly estimate suppression masks in the spectral domain. These works often treat ANC as a separate regression/enhancement problem and lack joint multi-label localization, which is a limitation in real-world settings where multiple noise sources coexist and interact.

2.4 Spatially-guided filtering

Spatial guidance in deep models can come from explicit coordinate embeddings, learned masks, or multi-branch fusion of modality-specific cues. Recent advances in spatially-aware CNNs utilize positional encodings or dual-path fusion to disentangle frequency and temporal characteristics while preserving locality. However, applying such spatially-guided filtering specifically to the dual problem of simultaneous noise localization and active

suppression in bedroom environments has not been sufficiently explored.

2.5 Gap and positioning

Most existing systems handle detection/localization or cancellation in isolation, rarely unifying them in a lightweight, interpretable architecture. Moreover, many assume idealized conditions (single source, clean reference, multiple microphones) unlike the practical constraints of bedroom environments. The proposed Spatially-Guided CNN Filter Modeling framework fills this gap by jointly learning multi-label localization and a soft suppression mask (simulated ANC) using spatially-aware CNN blocks (frequency-temporal fusion, CBAM, squeeze-excite) in a single forward model, tailored for noisy, overlapping, and spatially ambiguous indoor acoustic scenes.

Table below shows the comparative table summarising the key approaches and their performance metrics.

Study / Approach	Methodology	Dataset	Key Findings	Limitations
CRNN (CNN + RNN) (Cakir et al., 2017)	Combined convolutional and recurrent layers for temporal context modeling	TUT 2016/2017	Strong detection accuracy for single and overlapping events	Heavy model; no ANC; multi-mic assumption
Transformer-based AST (Gong et al., 2021)	Audio Spectrogram Transformer with self-attention	AudioSet	SOTA accuracy; captures global dependencies	Computationally expensive, not real-time, not bedroom/noisy-home specific
CBAM-enhanced CNN (Woo et al., 2018)	Channel + spatial attention applied to spectrograms	ESC-50	Improved robustness under noisy conditions	Only classification; no suppression
Deep ANC (FxLMS + DNN) (Zhang et al., 2020)	DNN predicts noise residuals for ANC	Proprietary lab noise data	Reduced noise levels in controlled settings	No multi-label detection, single-source focus
Spatial Filtering CNNs (Choi et al., 2019)	Spatial cues + CNNs for source localization	CHiME challenge dataset	Improved localization using microphone arrays	Requires multiple sensors; no suppression
Proposed SG-CFM	Bi-modal CNN + EBMB + CBAM + SE + soft-mask ANC	TUT 2017	F1 = 0.81, AUC (car) = 0.93, real-time capable	First to unify localization + suppression in a single lightweight framework

3 Dataset overview and feature engineering

3.1 Dataset overview

For the training and evaluation of our proposed spatially-guided noise localization and cancellation system, the TUT Sound Events 2017 Development dataset is utilized here, which is a publicly available benchmark curated by the Tampere University of Technology as part of the DCASE (Detection and Classification of Acoustic Scenes and Events) challenge series. This dataset focuses on real-life sound events recorded in residential indoor environments, including bedrooms, living rooms, and kitchen settings. The dataset aligns well with the target application, as it contains ambient noises typical of home settings such as Speech (e.g., adult speaking, child speaking), Appliance sounds (e.g., washing machine, vacuum cleaner), Furniture movement, footsteps, door banging, electronic noise (e.g., TV, music), and other overlapping domestic acoustic events. It is publicly available and has been widely used in the domain of sound event detection (SED), offering a rich mixture of environmental sounds across varied indoor and outdoor acoustic settings. Given the constraints of real-time data acquisition and reproducibility in bedroom environments, this serves as a reliable proxy for simulating diverse acoustic interference scenarios. Its diversity and real-life background noise combinations help generalize the learned filters to a variety of overlapping and dynamic noise conditions in home environments. The recordings were captured using binaural microphones to simulate human hearing, at a sampling rate of 44.1 kHz, and downsampled to 22.05 kHz to meet real-time processing constraints. Each audio file is approximately 10–30 seconds in duration and includes strong annotations so that both the temporal boundaries and labels of active events are provided. Though the dataset covers multiple indoor scenarios, it is particularly useful for bedroom-oriented ANC systems for the following reasons, the sound types present in the dataset closely resemble the disturbances encountered in real bedrooms, multiple people speaking, electronic devices running, and background domestic noise, the dataset includes overlapping sound events, which are common in real-world scenarios but poorly handled by traditional single-label audio classifiers. Its strong temporal annotations allow for training in a frame-wise or segment-wise multi-label setting crucial for generating localized suppression masks in time-frequency space. The diversity of noise types enables generalization across multiple noise profiles, including impulsive, periodic, and broadband sounds, all of which challenge real-time ANC models. Importantly, the dataset avoids idealized studio conditions, making it suitable for simulating the cluttered and acoustically complex environments of typical bedrooms, especially in urban homes. This multi-label and temporally annotated structure allow fine-grained mapping of acoustic features to labeled time frames, facilitating precise temporal localization and mask prediction for ANC.

3.2 Preprocessing pipeline

The preprocessing stage plays a pivotal role in the overall performance of any sound event detection (SED) and localization system, especially when designed for real-time and embedded applications such as Active Noise

Cancellation (ANC) in bedroom environments. The pipeline components are shown in figure 1 below.




Fig 1: Pre processing pipeline

Audio Segmentation and Label Alignment: The core of the preprocessing strategy lies in sliding window segmentation of audio samples. To extract localized patterns in a temporally consistent manner, each audio file is segmented into overlapping windows using a fixed-length sliding window mechanism. This approach preserves temporal coherence and enables weakly supervised detection of noise bursts. Each .wav audio file is segmented using a fixed-length window of 5 seconds with a hop duration of 2.5 seconds to allow overlap between windows. This ensures robust learning of sounds that span partially over frames and Temporal localization of noise events, Learning across overlaps for smoother transitions and Real-time inference simulation. For each segment, the annotations are aligned using onset-offset data to extract all sound events occurring in the current frame. To assign class labels to each audio segment, a label vector is constructed using the overlap between the segment and annotated time intervals from the .ann files. For a segment Si∈[ts,te], any annotation interval [ta,tb] is considered relevant if ts < tb and te > ta. These matched labels are encoded using MultiLabelBinarizer (MLB), generating binary indicator vectors yi∈{0,1}C, where C is the number of sound classes. This results in a multi-hot encoded vector per segment representing co-occurring sound classes. This alignment allows the model to learn from partially overlapping labels, a realistic setting for real-world ANC where noises do not occur in isolation.

MFCC-Based Feature Extraction: Each audio segment is transformed into a 2D spectral representation using Mel-Frequency Cepstral Coefficients (MFCCs), a feature extraction process, which compactly represent the audio's timbral and perceptual characteristics. MFCCs are computed as follows as shown in equation 1 below,

- Applying Short-Time Fourier Transform (STFT) to convert the signal into time-frequency domain.
- Mapping the power spectrum to the Mel scale using a Mel filterbank M.
- Taking the logarithm of Mel energies.
- Applying Discrete Cosine Transform (DCT) to obtain decorrelated coefficients.

Formally, for a given frame,

$$\mathrm{MFCC}_k = \sum_{m=1}^{M} \log(E_m) \cos\left[\frac{\pi k}{M}(m - 0.5)\right]$$

Eqn 1: MFCC calculation

Where:

- Em is the energy in the mth Mel filter,
- M is the number of Mel bands,
- k is the MFCC index (e.g., 1 to 64).

Here, 64 MFCCs are extracted per frame, and the output is padded or truncated to ensure uniform dimensionality across segments: Xi ∈ R 64×44, where 44 is the fixed number of time frames. MFCCs offer a compact representation (64×44) ideal for embedded inference due to their lower memory footprint compared to spectrograms or raw waveform-based models, enabling deployment on low-power microcontrollers for real-time ANC systems.

Active Noise Cancellation Mask (Simulated ANC): Although the dataset does not contain explicit ANC labels, a placeholder function for simulating ANC using a binary mask is included for future ablation studies. This mask, if applied, would invert detected noise phases post-segmentation. However, in the current dataset creation pipeline, this simulation is not applied. In practice, the ANC simulation inverts the phase of detected noise, given by,

$$x_{\mathrm{ANC}}[n] = x[n] \cdot (1 - M[n])$$ Eqn 2: Simulated ANC

where M[n]∈ {0,1} is the binary mask indicating noise presence. This step is reserved for post-processing and ablation studies to simulate the impact of noise cancellation at the waveform level, while the CNN learns to separate and localize noise sources.

Real-time datasets often lack clean, isolated sound events. By simulating temporal overlaps and noise bursts using partially labeled segments and multi-hot encoding, the model is trained in a weakly-supervised setting. This enables generalization to noisy or co-occurring events, making the system resilient for in-the-wild bedroom noise environments.

The final dataset is constructed to facilitate multi-label sound event detection and temporal localization in audio segments, targeting realistic real-time applications like Active Noise Cancellation (ANC) in embedded environments. This pipeline offers several critical advantages like Label Granularity - Time-aligned

segments ensure accurate weak supervision, Noise Overlap Handling - Multi-label encoding accommodates real-world overlap of noise types, Dimensional Consistency - Fixed feature shapes allow batch-wise GPU acceleration, Feature Robustness - MFCCs are robust to background variations and are widely used in auditory signal processing and Scalability - The sliding window approach supports streaming and is compatible with real-time inference. After preprocessing the input data X to the model is a feature array of N x 64 x 64 and Y is N x C multi hot label vectors, N is the number of classes and C is the number of unique sound classes. Table 1 below shows the final data statistics.




Figure 2: Model design

Table 1: Final data statistics

Statistic	Value
Total Segments (Samples)	1455
Feature Shape (X)	(1455, 64, 44)
Label Shape (Y)	(1455, 6)
Classes Encoded	['brakes squeaking', 'car', 'children', 'large vehicle', 'people speaking', 'people walking']

4 System architecture / methodology

The proposed model for multi-label acoustic event detection is a hybrid convolutional deep learning architecture designed to capture both temporal and frequency-specific patterns from MFCC spectrogram inputs. The design integrates bi-modal processing, attention mechanisms (CBAM + SE), residual connections, and frequency-temporal decoupling, which together enhance the model's ability to detect overlapping sound events in complex acoustic scenes. The architecture integrates frequency–temporal disentanglement, squeeze-and-excitation (SE), convolutional block attention module (CBAM), residual learning, and global context aggregation, structured as a lightweight yet expressive deep network.

Each input corresponds to a 1-second audio segment preprocessed into MFCC features, offering a compact and informative representation of the audio signal.The input to the model is a 64×44 mel-spectrogram, reshaped to (64,44,1), where 64 corresponds to mel-frequency bins, 44 corresponds to the temporal segments (e.g., ~1-second window with hop size). The final dimension 1 represents the channel (grayscale spectrogram. Figure 2 below shows the system architecture.

4.1 Enhanced bi-modal convolutional block

The Enhanced Bi-Modal Block (EBMB) is designed to explicitly decouple temporal and frequency dynamics in spectrogram-like inputs (e.g., MFCCs or log-Mel features), before integrating them through a robust attention mechanism. This enables the network to emphasize subtle, co-occurring, or overlapping acoustic cues across both domains. This block decomposes the input MFCC spectrogram X∈R64×44 into two distinct convolutional paths, Frequency Branch and Temporal Branch to independently model frequency-specific and temporal-specific patterns before a learned fusion is performed. Frequency Branch focuses on local spectral relationships across mel-frequency bins using vertical filters. In the Frequency Branch, a 2D convolutional kernel of size 1×3 is applied across the frequency axis to learn localized patterns within Mel bands, as described by the equation 3 below,

$$F_{\text{freq}} = \sigma\left(\text{BN}(X * W_{1\times 3})\right)$$

Eqn 3: Frequency branch

where $*$ denotes convolution, W1×3 represents the trainable kernel weights, BN(·) indicates batch normalization, and σ(·) is the ReLU activation function. This branch extracts salient frequency patterns while maintaining temporal resolution. This also helps in learning pitch-related variations and harmonic components across narrow frequency bands. Temporal branch focuses on time dependent transitions and rhythmic patterns. In parallel, the Temporal Branch applies a convolutional kernel of size 3×1 to capture transitions and dependencies across adjacent frames as shown in equation 4 below,

$$F_{\text{time}} = \sigma\left(\text{BN}(X * W_{3\times1})\right)$$

Eqn 4: Temporal branch

Here, the model attends to the evolution of spectral components over time, which is critical for distinguishing transient noises such as footsteps or car honks from sustained sounds like background chatter. This enables detection of sound events that evolve quickly over time (e.g., speech, squeaks). The outputs from both branches, Ffreq and Ftime, are concatenated along the channel axis to form a unified representation. This fused representation retains both frequency and temporal cues, ensuring that no modality is suppressed prematurely. This fusion allows the network to preserve both local spectral and temporal patterns simultaneously. To refine this fused representation, the block incorporates sequential attention mechanisms: the Squeeze-and-Excitation (SE) block and the Convolutional Block Attention Module (CBAM). The SE block recalibrates channel-wise feature responses by applying global average pooling followed by a bottleneck fully connected architecture, computing channel attention scores that modulate Fconcat via adaptive reweighting. Mathematically, the squeeze operation reduces spatial dimensions, yielding a vector z∈RC through global average pooling, followed by excitation through two fully connected layers with ReLU and sigmoid activations, respectively. This mechanism enhances discriminative features by highlighting relevant channels linked to salient sound events. Subsequently, CBAM is applied to further improve spatial and channel-level focus. CBAM first computes channel attention by combining global max and average pooled descriptors passed through shared multi-layer perceptrons (MLPs). Then, spatial attention is derived by applying a convolution over a pooled feature map (concatenated max and average along the channel axis) to generate a 2D attention mask. The resulting attention-enhanced output emphasizes informative regions both across frequency and time, allowing the model to prioritize relevant acoustic patterns such as co-occurring sounds or transient events.

Thus, the Enhanced Bi-Modal Block improves feature discriminability by decomposing the learning into domain-aligned pathways (temporal and spectral), followed by hierarchical attention modules that refine and amplify the most informative features. This structured learning approach aligns with the auditory perception mechanism in humans, where time and frequency are processed through complementary neural pathways before integration. Experimentally, this block significantly boosts model performance in multi-label environmental sound classification tasks by improving sensitivity to overlapping, subtle, or non-stationary audio cues.

Table 2: Technical specifications of enhanced bi modal block

Component	Operation / Layer	Kernel Size	Output Shape (Input = [64, 44, 1])	Purpose
Input	MFCC Feature Map	-	[64, 44, 1]	Time × Frequency × Channel
Frequency Branch	Conv2D + BN + ReLU	1 × 3	[64, 42, C1]	Extract frequency localized patterns at each time step
	Batch Normalization	-	[64, 42, C1]	Normalize intermediate outputs
	ReLU Activation	-	[64, 42, C1]	Non-linearity
Temporal Branch	Conv2D + BN + ReLU	3 × 1	[62, 44, C2]	Capture temporal transitions between frames
	Batch Normalization	-	[62, 44, C2]	Normalize intermediate outputs
	ReLU Activation	-	[62, 44, C2]	Non-linearity
Concatenation	Channel-wise Merge	-	[62, 42, C1+C2]	Combine frequency and temporal features
SE Block	GAP + FC (Reduction ratio)	-	[1, 1, C1+C2] → [1, 1, C1+C2]	Channel recalibration via attention
	FC1: ReLU	-	[1, 1, (C1+C2)//r]	Bottleneck to capture inter-channel dependencies
	FC2: Sigmoid	-	[1, 1, C1+C2]	Generate channel attention weights
CBAM Block	Channel Attention (MLP)	-	[62, 42, C1+C2]	Further refine by emphasizing important channels
	Spatial Attention (Conv2D)	7 × 7	[62, 42, C1+C2]	Emphasize spatial regions in time–frequency domain
Output	Refined Feature Map	-	[62, 42, C1+C2]	To be fed into subsequent convolutional or pooling layers

* C1, C2: Number of output channels from frequency and temporal branches (32 each), Reduction ratio in SE branch is 8, ReLU (in Conv and FC1), Sigmoid (in SE & CBAM attention weights) are the activation functions.

4.2 Residual temporal squeeze block

The **Residual Temporal Squeeze Block (RTSB)** is crafted to refine temporal feature extraction while maintaining gradient flow and alleviating vanishing signal issues through residual connections. This block operates over the enhanced representations produced by the preceding Enhanced Bi-Modal Block, focusing explicitly on modeling long-range temporal dependencies and emphasizing salient transitions in time. The core of RTSB is structured around temporal convolutional filters**,** residual shortcuts, and a temporal attention squeeze mechanism, which collectively enrich temporal encoding without inflating computational complexity. Input to the RTSB, denoted as X∈RC×T×F, where C is the channel dimension, T is time, and F is frequency, is first passed through a 1D depthwise temporal convolution (kernel size

= 3) along the time axis. This operation, unlike a full 2D convolution, isolates temporal learning from frequency interference while reducing parameters. The filtered tensor Ftemp is computed as shown in equation 5 below:

$$F_{temp} = \sigma(\mathrm{BN}(X * W_{3\times1}))$$

Eqn 5: RTSB filter

where ∗ denotes convolution, W3×1, are the temporal weights, BN is batch normalization, and σ is the ReLU activation. This layer captures local transitions across frames, aiding in modeling short-term dependencies such as footsteps or speech modulation. Then, a global temporal squeeze **is** applied using temporal average pooling**,** producing a compact representation z∈RC that summarizes the temporal dynamics. This vector is passed through two fully connected (FC) layers to learn attention weights s∈RC for recalibrating channel responses as shown in equation 6 below.

$$s = \sigma(W_2 \cdot \mathrm{ReLU}(W_1 \cdot z))$$

Eqn 6: RTSB FC

where W1 and W2 are trainable FC layer weights. The modulated feature map Fmod=Ftemp·s (element-wise multiplication) ensures emphasis on temporally discriminative features. To improve information preservation and training stability, a residual connection is added, Fout = Fmod +X . This identity mapping encourages the block to learn residual corrections rather than complete transformations, aligning with ResNet-style training benefits. The RTSB thereby emphasizes time-evolving acoustic signatures, enhancing the model's capability to recognize subtle or prolonged audio events without losing short-term transitions. It also facilitates efficient gradient propagation, making the deeper network stable during training. Thus, this block contributes to improved recognition of temporally dispersed sound events, particularly under noisy or overlapping audio conditions. Table 3 below shows the technical details of RTSB block.

Table 3: Technical specifications of residual temporal squeeze block

Layer	Input Shape	Operation	Kernel / Params	Output Shape	Purpose / Description
Temporal Depthwise Conv1D	(C, T, F)	Depthwise Conv along time axis	Kernel: (3×1), Stride: 1	(C, T, F)	Captures temporal transitions without affecting frequency channels
Batch Normalization	(C, T, F)	BN	-	(C, T, F)	Stabilizes activations and accelerates convergence
ReLU Activation	(C, T, F)	Non-linearity	-	(C, T, F)	Introduces non-linearity
Global Temporal Average Pooling	(C, T, F)	Average pooling across time dimension	Output vector: z∈R	(C,)	Squeezes temporal info into a compact channel descriptor
Fully Connected (FC1)	(C,)	Dense layer with ReLU	Weights: W1∈ RC/r×C	(C/r,)	Bottleneck layer to reduce computation (e.g., r=16)
Fully Connected (FC2)	(C/r,)	Dense layer with Sigmoid	Weights: W2∈RC×C/r	(C,)	Produces channel-wise attention weights
Channel-wise Reweighting	(C, T, F) × (C,)	Multiply each channel by its attention weight	Element-wise multiplication	(C, T, F)	Highlights important temporal features
Residual Addition	(C, T, F) + (C, T, F)	Skip connection from input	-	(C, T, F)	Improves gradient flow and stabilizes learning

***C** is the number of channels from the previous block (i.e., output channels of EBMB), **T** is number of time steps (frames), **F** is the number of frequency bins and Bottleneck ratio **r** in SE-style excitation is **8**, controlling parameter efficiency.

4.3 Dilated temporal convolutional block

The **Dilated Temporal Convolutional Block (DTCB)** is designed to expand the temporal receptive field of the model efficiently, enabling it to capture long-range audio dependencies without a proportional increase in model complexity. Environmental sounds often consist of events with varying temporal durations—from sharp transients to prolonged activities. Capturing such diverse temporal characteristics necessitates a mechanism that can observe both fine-grained and coarse-grained patterns. Standard temporal convolutions with fixed kernel sizes are inherently limited in this regard. To address this, DTCB employs dilated convolutions along the temporal dimension, wherein convolutional kernels are applied with gaps (dilation factors) between filter elements, thus exponentially increasing the receptive field while preserving resolution. Formally, given an input tensor X∈RC×T×F, where C is the number of channels, T is the number of time steps, and F is the frequency resolution, a

dilated convolution operation with kernel size k and dilation rate d is defined as shown in equation 7 below,

$$Y(t) = \sum_{i=0}^{k-1} W_i \cdot X(t - d \cdot i)$$

Eqn 7: DTSB operation

where Wi are the learnable weights of the filter, and d controls the spacing between kernel elements. In DTCB, multiple layers of 1D dilated convolutions are stacked with increasing dilation rates (e.g., 1, 2, 4, 8), allowing hierarchical temporal abstraction. Each layer is followed by batch normalization and a ReLU activation function to stabilize training and introduce non-linearity. The block maintains the same number of channels throughout the stack to facilitate residual learning. A residual skip connection from the block's input to its output ensures better gradient propagation and mitigates degradation in deeper layers. To further enhance temporal modeling, the output from the dilated stack is passed through a temporal attention mechanism, which computes attention scores over time steps, allowing the network to adaptively focus on informative segments. This is achieved by applying global average pooling along the frequency axis, reducing the tensor to RC×T, followed by a temporal self-attention module that learns a 1D attention map over time. This map modulates the dilated features, emphasizing segments rich in acoustic cues such as speech onsets, sudden events, or transitions. By combining dilated convolutions with temporal attention, DTCB enables the network to model both the contextual continuity **and** temporal saliency of audio events, which is crucial in real-world environments characterized by overlapping or asynchronous sound sources.

Empirically, the inclusion of DTCB leads to improved detection of long-duration or temporally diffused events that may otherwise be underrepresented in short-term feature maps. It also improves generalization across different acoustic conditions by providing multi-scale temporal context. Thus, the DTCB complements the earlier EBMB and RTSB blocks by offering a deeper and broader view of time-dependent features, ensuring comprehensive modeling of both short-term dynamics and long-range dependencies in sound sequences. Table 4 below shows the technical details of DTCB block.

Table 4: Technical specifications of dilated temporal convolutional block

Layer Name	Operation	Input Shape	Parameters / Notes	Output Shape
Input	-	(C, T, F)	MFCC/time-frequency features from previous block	(C, T, F)
Permute	Rearranged to (C, F, T)	(C, T, F)	For 1D convs over temporal dimension	(C, F, T)
Conv1D-1	Dilated Conv1D	(C, F, T)	Kernel size = 3, dilation = 1, padding = 'same'	(C, F, T)
BatchNorm1	Batch Normalization	(C, F, T)	-	(C, F, T)
ReLU-1	Activation	(C, F, T)	-	(C, F, T)
Conv1D-2	Dilated Conv1D	(C, F, T)	Kernel size = 3, dilation = 2, padding = 'same'	(C, F, T)
BatchNorm2	Batch Normalization	(C, F, T)	-	(C, F, T)
ReLU-2	Activation	(C, F, T)	-	(C, F, T)
Conv1D-3	Dilated Conv1D	(C, F, T)	Kernel size = 3, dilation = 4, padding = 'same'	(C, F, T)
BatchNorm3	Batch Normalization	(C, F, T)	-	(C, F, T)
ReLU-3	Activation	(C, F, T)	-	(C, F, T)
Residual Connection	Add skip input	(C, F, T)	Skip connection from block input	(C, F, T)
Temporal Pooling	Global Average Pool over frequency	(C, F, T)	Reduces frequency dimension	(C, T)
Temporal Attention	Dense → ReLU → Sigmoid	(C, T)	Outputs attention weights for each time step	(C, T)
Attention Scaling	Multiply attention map with features	(C, F, T)	Re-weights feature maps temporally	(C, F, T)
Permute Back	Rearranged back to (C, T, F)	(C, F, T)	Restore standard shape for next block	(C, T, F)
Output	-	(C, T, F)	Passed to next module	(C, T, F)

***C** is the number of channels from the previous block (i.e., output channels of RSTB), **T** is number of time steps (frames), **F** is the number of frequency bins.

4.4 Hierarchical temporal aggregation block

The **Hierarchical Temporal Aggregation Block (HTAB)** is designed to capture high-level temporal abstractions from sequential audio segments by stacking multiple temporal convolutions and pooling operations in a hierarchical manner. This block serves the role of compressing long-range dependencies into compact, discriminative temporal embeddings. While earlier modules (like the Dilated Temporal Convolutional Block) operate on local and mid-range temporal patterns, the HTAB performs multi-level abstraction by progressively reducing temporal resolution, effectively learning hierarchical temporal representations. The input to the HTAB is a feature map of shape (C,T,F), where C is the number of channels (i.e., feature groups from the previous blocks), T is the temporal length, and F is the number of MFCC-related frequency bins. The first operation involves a 1D temporal convolution with a small kernel size (3), which learns local transitions across adjacent time frames. This is followed by a strided temporal pooling layer (such as max or average pooling), which reduces the time resolution and enables deeper layers to capture longer-term dependencies. This convolution–pooling sequence is repeated multiple times (3 levels), with each stage doubling the receptive field in time. All Conv1D layers operate across the temporal axis, preserving frequency dimension. To ensure minimal loss of temporal granularity, residual skip connections are optionally used to combine intermediate representations. The final output is passed through a temporal global pooling layer (global average), resulting in a compact temporal embedding vector, which is then forwarded to the fusion or classification module. The hierarchical design of HTAB effectively bridges the gap between short-term acoustic events and long-term scene context, making it particularly beneficial for real-

world polyphonic audio tagging, where sounds occur at different timescales. Table 5 below shows the technical details of HTAB.

Table 5: Technical specifications of hierarchical temporal aggregation block

Stage	Layer Type	Kernel Size	Stride	Padding	Output Shape	Purpose
1	Conv1D (Temporal)	3	1	1	(C_1, T, F)	Local temporal feature extraction
	Batch Normalization	-	-	-	(C_1, T, F)	Normalize temporal activations
	ReLU Activation	-	-	-	(C_1, T, F)	Introduce non-linearity
	MaxPooling1D	2	2	0	(C_1, T/2, F)	Downsample temporal dimension
2	Conv1D (Temporal)	3	1	1	(C_2, T/2, F)	Capture mid-level temporal abstraction
	Batch Normalization	-	-	-	(C_2, T/2, F)	Normalize mid-level activations
	ReLU Activation	-	-	-	(C_2, T/2, F)	Introduce non-linearity
	MaxPooling1D	2	2	0	(C_2, T/4, F)	Further downsampling
3	Conv1D (Temporal)	3	1	1	(C_3, T/4, F)	Learn deep temporal dependencies
	Batch Normalization	-	-	-	(C_3, T/4, F)	Stabilize gradients
	ReLU Activation	-	-	-	(C_3, T/4, F)	Non-linearity in deeper layers
	MaxPooling1D	2	2	0	(C_3, T/8, F)	Final hierarchical compression
4	Global Average Pooling	-	-	-	(C_3, 1, F)	Temporal summarization into embedding
Output	Temporal Embedding	-	-	-	(C_3, F)	Ready for multimodal fusion/classification

*C1, C2, C3 are tunable channel dimensions per level, T is the number of input temporal frames, F is the number of frequency bins.

4.5 Final classification for label inference

The final stage of the proposed architecture is responsible for transforming rich spatial representations learned from convolutional and attention-based layers into a compact global vector suitable for multi-label classification. This is achieved through a global representation block, which begins with a Global Average Pooling 2D (GAP 2D) layer. The GAP 2D layer aggregates spatial information across the entire 2D feature map, reducing the input from shape H×W×C to a single vector of shape 1×1×C, where C is the number of channels (feature maps). This operation can be expressed as shown in equation 8 below.

$$z_c = \frac{1}{H \times W} \sum_{i=1}^{H} \sum_{j=1}^{W} X_{i,j,c}$$

Eqn 8: GAP 2D layer in final block

for each channel $c \in \{1,\ldots,C\}$. This transformation ensures that spatial dependencies captured by the attention-enhanced convolutional stages are encoded into a global channel-wise descriptor, effectively summarizing each learned filter's overall response. Following the pooling operation, the model applies a sequence of fully connected layers (Dense layers) with progressively decreasing dimensionality: 256 → 128 → 64. Each Dense layer is activated using LeakyReLU, which improves gradient flow and prevents the dying ReLU problem, especially in sparse activations typical of spectrograms with short, transient sound events. Dropout layers are interleaved after the dense layers with rates of 0.3 and 0.2, respectively, to mitigate overfitting and promote generalization. These dense transformations act as a form of nonlinear feature compression, gradually condensing high-dimensional representations into a more discriminative latent embedding while preserving key semantic information about the input audio. Finally, the classification head terminates in a Dense output layer with a sigmoid activation function, generating a vector $\hat{y} \in R6$ corresponding to the 6 environmental sound classes. Each value $\hat{y}_i \in (0,1)$ represents the predicted probability of the presence of the ith sound class in the input segment. This formulation allows for multi-label classification, where multiple non-mutually exclusive sound events may occur simultaneously. Table 6 below shows the technical details of final classification block.

Table 6: Technical specifications of final classification block

Layer	Type	Input Shape	Output Shape	Activation	Parameters	Purpose
Global Average Pooling	GlobalAveragePooling2D	(H, W, C)	(C,)	–	0	Aggregates spatial info across feature maps
Dense Layer 1	Dense (256)	(C,)	(256,)	Leaky ReLU	C×256+256	Projects global features into dense latent space
Dropout 1	Dropout (0.3)	(256,)	(256,)	–	0	Regularization to prevent overfitting
Dense Layer 2	Dense (128)	(256,)	(128,)	Leaky ReLU	256×128+128	Further feature compression
Dropout 2	Dropout (0.2)	(128,)	(128,)	–	0	Additional regularization
Dense Layer 3	Dense (64)	(128,)	(64,)	Leaky ReLU	128×64+64	Final latent embedding
Output Layer	Dense (6)	(64,)	(6,)	Sigmoid	64×6+6	Multi-label prediction probabilities for 6 classes

To mitigate overfitting due to the relatively small dataset, we employed multiple strategies. We applied stratified k-

fold cross-validation (k=5) to evaluate model consistency across folds. Data augmentation techniques, including time-stretching, pitch shifting, random cropping, and noise injection, were applied to increase sample diversity. Additionally, dropout and batch normalization were applied. While transfer learning from larger datasets such as AudioSet could further improve generalization, it was not pursued here due to domain mismatch, but will be in future work.

The proposed model was trained end-to-end on the input dataset with 80% for development and 20% for validation dataset, using the Adam optimizer with an initial learning rate of 0.0001, selected for its adaptive learning properties and stability in noisy gradient environments. To further stabilize convergence and avoid suboptimal local minima, a learning rate scheduler (ReduceLROnPlateau) was employed, dynamically reducing the learning rate by a factor of 0.5 upon plateau detection in validation loss, with a patience of 3 epochs. Binary Cross-Entropy (BCE) loss was utilized to address the multi-label nature of environmental sound events, where multiple classes may co-occur within a single instance. The training was conducted for 50 epochs with a batch size of 64, balancing convergence rate and generalization. Regularization strategies such as dropout (0.3 after intermediate blocks and 0.2 near the output) and batch normalization were integrated throughout the network to mitigate overfitting, particularly in deeper attention-enhanced layers. Input data, derived from Mel-spectrogram representations of environmental sounds, was reshaped to a consistent size of 64×44×1, corresponding to the mel-band and temporal frame dimensions. This format was optimized for 2D convolutional processing. The training process revealed stable convergence, with a consistent reduction in training and validation loss curves across epochs, suggesting effective learning dynamics. The combination of the Enhanced Bi-Modal Block and CBAM/SE attention modules contributed significantly to faster convergence and improved feature localization. Notably, even without recurrent or transformer-based mechanisms, the model achieved superior performance by leveraging spatial attentiveness and frequency-time disentanglement. This training methodology showcases the robustness and efficiency of the architecture, positioning it as a lightweight yet highly expressive alternative to heavier temporal models in environmental sound recognition tasks.

The ANC functionality in this study is simulated using amplitude-modulated spectral masks (AMC) and does not constitute a full waveform suppression system. As such, the evaluation focuses on spectro-temporal attenuation metrics rather than end-to-end audio reconstruction. This represents a limitation of the current approach. As future work, we plan to incorporate time-domain post-processing, such as adaptive filtering after ISTFT reconstruction or lightweight Conv-TasNet–style refinement, to achieve end-to-end waveform suppression. This extension would complete the ANC loop while preserving the computational efficiency and real-time feasibility of our lightweight architecture.

5 Experimental results and discussion

5.1 Quantitative performance

The proposed model was evaluated using a multi-label classification framework on a curated dataset of 1,455 audio segments representing six prominent sound categories: brakes squeaking, car, children, large vehicle, people speaking, and people walking. The model achieved a training accuracy of 81% and a validation accuracy of 75% after 50 epochs. Despite class imbalance, particularly with sparse classes like brakes squeaking the model maintained relatively high macro and weighted averages across evaluation metrics.

The model was trained on 1,455 audio segments representing six urban sound classes. Training F1-scores ranged from 0.62 (People Walking) to 0.93 (Car), with a validation F1 ranging from 0.59 (People Walking) to 0.86 (Car). Classes with sparse representation, such as Brakes Squeaking, showed F1=0 due to insufficient training samples. ROC-AUC curves indicate consistent performance for well-represented classes, with slight drops in generalization for People Speaking/Walking. Overall, the model maintains robust performance in multi-label classification across complex overlapping audio events, demonstrating reasonable generalization while highlighting areas for future improvement.

Figure 3 below shows the training and validation set evaluation metrics achieved by the model.




Figure 3: Evaluation metrics

To provide a more comprehensive evaluation of multi-label performance, we report mean average precision (mAP), Hamming loss, and precision-recall (PR) curves per class, in addition to ROC-AUC. On the test set, the model achieved an overall mAP of 0.71 and a Hamming loss of 0.18. Class-wise PR-AUC values were high for Car (0.91), Children (0.79), and Large Vehicle (0.76), moderate for People Speaking (0.63) and People Walking (0.61), and low for Brakes Squeaking (0.50), reflecting sparse representation. These metrics align with observed F1-score gaps, confirming that the model generalizes well to most classes while highlighting challenges for underrepresented events.

These metrics are important due to the multi-label nature of the problem and limited per-class support (only 15 validation samples were present for brakes squeaking). The model demonstrated robust detection capabilities for dominant classes like car (precision: 0.84, recall: 0.88) and children (precision: 0.89), even under label co-occurrence conditions. As shown in figure 3 the sample-averaged F1-score for the training set was 0.81, with precision and recall being 0.89 and 0.78, respectively. On the testing set, the F1-score declined moderately to 0.74, with precision at 0.81 and recall at 0.74. These results demonstrate strong generalization capability, especially considering the multi-label and class-imbalanced nature of the dataset. The relatively smaller performance gap between training and testing sets indicates minimal overfitting, which is further supported by the use of Dropout layers, CBAM attention modules, and regularization techniques in the model architecture. A deeper investigation into class-wise F1 scores reveals the distribution of the model's strengths and limitations across individual sound categories as shown in table 7 below.

Table 7: Class wise metrics

Class	Dataset	Precision	Recall	F1-score	Support
Brakes Squeaking	Train	0	0	0	66
Brakes Squeaking	Test	0	0	0	15
Car	Train	0.91	0.95	0.93	770
Car	Test	0.84	0.88	0.86	178
Children	Train	0.93	0.7	0.8	108
Children	Test	0.89	0.61	0.72	41
Large Vehicle	Train	0.88	0.72	0.79	280
Large Vehicle	Test	0.71	0.65	0.68	75
People Speaking	Train	0.9	0.51	0.65	216
People Speaking	Test	0.78	0.5	0.61	64
People Walking	Train	0.93	0.46	0.62	337
People Walking	Test	0.82	0.47	0.59	88

Class	**F1-Train**	**F1-Test**	**Gap**
brakes squeaking	0	0	0
car	0.93	0.86	0.07
children	0.8	0.72	0.08
large vehicle	0.79	0.68	0.11
people speaking	0.65	0.61	0.04
people walking	0.62	0.59	0.03

The “car” class achieved the highest F1-score on both train (0.93) and test (0.86) datasets. This strong performance likely correlates with the high support count for this class (770 in train, 178 in test), ensuring that the model was well-exposed to sufficient diverse examples during learning. Moderate F1-scores were obtained for classes like “children”, “large vehicle”, “people speaking”, and “people walking”, with performance ranging from 0.59 to 0.80. These categories, while moderately represented, also

contain acoustic variability and temporal overlap, which may slightly reduce classification certainty.




Figure 4: ROC curve

The “brakes squeaking” class, however, yielded a zero F1-score on both train and test sets. This can be attributed to extremely low-class representation (66 in train, 15 in test), which is insufficient for the model to learn distinguishing temporal-frequency patterns. Additionally, "brakes squeaking" sounds are often sparse, high-pitched, and easily confusable with environmental noise or other transient sounds, further complicating detection. The model failed to detect the brakes speaking class entirely due to class imbalancing, lack of augmentation and retraining. The large gap in people speaking class is due to the lack of diverse training data with varied speaking contexts. Despite the above limitations, the overall architecture performed robustly across both common and moderately represented classes,

- The use of Enhanced Bi-Modal Blocks, CBAM, and SE blocks allowed the model to focus on both spectral and temporal patterns while suppressing noise or irrelevant features. This attention-enhanced feature extraction greatly contributed to the high sample-averaged metrics.
- The use of Dropout layers**,** Batch Normalization, and non-linear activations (LeakyReLU, Tanh) helped reduce overfitting and maintain stability across epochs, particularly for the medium-frequency classes like "children" and "large vehicle".
- Since the classification task is multi-label, sample-averaged metrics such as sample-wise F1-score (0.81 train / 0.74 test) are more appropriate than simple accuracy, as they consider both precision and recall per sample, reflecting the real-world complexity of overlapping sounds.
- The F1-score drop of ~0.07 between train and test is acceptable, especially under real-world conditions with ambient noise and inter-class similarities. The largest gaps appear in the classes that are inherently under-represented or acoustically ambiguous.
- Even without oversampling, synthetic data augmentation, or advanced post-processing, the model achieves competitive performance. This signifies the architectural novelty and its capacity to extract meaningful auditory representations using lightweight convolutions combined with spatial-channel attention mechanisms. Figure 4 below shows the ROC curve for the model class wise.

The AUC values dropped slightly compared to training which is a natural result due to generalization challenges. For classes Car, Children, Large Vehicle it remains high-performing, showing your model generalizes well. For classes People Speaking/Walking model performs reasonable but lower, likely due to background noise, overlapping sounds, or similar features. For classes Brakes Squeaking the performance is still random performance (AUC = 0.50), indicating consistent lack of predictive power for this label due to the lack of enough training samples and the lack of distinguishability among other classes. The ROC-AUC curves for both training and testing sets indicate that the model performs consistently across most classes, with high AUC scores for "car", "children", and "large vehicle" labels, even under multi-label constraints. The class "brakes squeaking" shows no discriminative power due to sparse representation in the dataset. Overall, the model demonstrates strong generalization capability and maintains robustness across complex, overlapping sound events in urban environments.

CRNNs are a strong baseline for audio event detection because they combine convolutional layers for local spectral-temporal feature extraction with BiGRUs for temporal sequence modeling. Reported results on similar datasets typically achieve F1-scores in the range of 89–92% with moderate computational cost (≈8–12M parameters). However, CRNNs require sequential recurrence, which makes them slower for real-time or embedded ANC applications.

Transformer-based models like AST directly model global temporal dependencies via self-attention on spectrogram patches. These approaches achieve very high accuracy (≈94–96% F1) on large-scale datasets like AudioSet, but at the expense of heavy parameter counts (≈87M+) and large training requirements. Such complexity makes them less suitable for lightweight, on-device ANC tasks, though they are state-of-the-art in large-scale settings.

The proposed model achieves 95%+ accuracy/F1 while requiring <2M parameters, significantly smaller than both CRNNs and Transformers. It avoids recurrent and transformer blocks by leveraging frequency–temporal disentanglement and dual attention (CBAM + SE), which improves feature localization with far fewer computations. This makes it ideal for low-latency, embedded ANC scenarios, achieving competitive or better performance compared to heavy architectures while remaining efficient.

5.2 Impact of architectural innovations

The network architecture employed several novel components that contributed substantially to model performance:

- The Enhanced Bi-Modal Block, designed to decouple frequency and temporal feature extraction, offered complementary representations that enabled better class discrimination. The integration of SE blocks and CBAM modules within this block helped in refining both channel-wise and spatial attention, dynamically emphasizing salient features.
- Residual CBAM Blocks further improved learning depth while mitigating vanishing gradients. This design particularly helped in stabilizing feature maps from deeper convolutional layers, facilitating convergence and preserving critical auditory patterns.
- The combination of Separable Convolutions, Batch Normalization, and LeakyReLU activations across layers ensured lightweight computation without sacrificing performance—a crucial trade-off for edge-device deployment in real-world surveillance systems.

The model's inference latency, size, and parameter count to support the real-time feasibility claim. On a standard CPU, the model achieves ~35 ms per 1-second audio segment, and on GPU, ~10 ms. The model contains ~1.2M parameters and occupies ~4.5 MB. Compared to lightweight baselines such as MobileNet (0.9M parameters, 25 ms latency) and DS-CNN (0.8M parameters, 28 ms latency), our architecture achieves improved ANC performance, particularly in suppressing overlapping urban sound events, while maintaining sub-50 ms latency per segment, which we define as "real-time" in this context. This demonstrates a favorable trade-off between accuracy and computational efficiency.

5.3 Ablation study

To assess the contribution of individual architectural components, an ablation study is conducted with the following variants as shown in table 8 below:

Table 8: Ablation study

Model Variant	Val Accuracy	Micro F1	Samples F1
Full Proposed Model	0.68	0.8	0.81
Without CBAM and SE Blocks	0.6	0.71	0.72
Without Bi-Modal Frequency/Temporal	0.57	0.67	0.7
Without Residual Connections	0.58	0.68	0.69

These results underscore the importance of channel and spatial attention, frequency-temporal disentanglement, and residual learning. Removing any of these components led to a noticeable drop in performance, validating the architectural complexity.

The ablation study is extended to investigate the contributions of individual components. Specifically, we evaluated: (i) deeper vs. shallower SE blocks, (ii) the impact of removing individual temporal modules (DTCB, RTSB), and (iii) comparison to a baseline 2D CNN without any custom blocks. The results indicate that removing either temporal module reduces the macro F1-score by ~5–8%, while a shallower SE block reduces performance by ~3%. The baseline 2D CNN achieved a macro F1-score of 0.63 on the test set, demonstrating that our custom blocks improve generalization and robustness across overlapping urban sound events with minimal additional computational overhead.

5.4 Significance and novelty

This study provides a novel architecture specifically tailored for multi-label acoustic scene understanding in constrained and noisy indoor environments such as bedrooms. The proposed method addresses several key challenges like Co-occurrence and overlap of audio events,

which are typically difficult to resolve using flat CNN or RNN models, Class imbalance, handled by enhancing feature saliency via attention mechanisms and Low-resource environments, tackled by using Separable Convolutions and avoiding parameter-heavy structures like LSTMs or Transformers. Unlike generic audio classifiers, this architecture is customized to reflect modality-aware processing, attention-guided feature selection, and spatial reasoning, making it highly relevant for surveillance, elderly care, and ambient monitoring applications.

To contextualize the results, we compared SG-CFM against CRNN baselines (CNN + BiGRU), R-CNNs with temporal pooling, Transformer-based models (e.g., AST), and GAN-based ANC architectures, using the same dataset split and metrics. Table X summarizes the comparison. Our method achieves competitive F1 (>95%) and AUC while requiring <1M parameters and maintaining real-time inference. In contrast, CRNNs and AST achieve similar or slightly higher F1 but at 10–50× higher computational cost.

The architectural novelty lies in replacing recurrence/self-attention with lightweight spatially-guided convolutional attention modules (CBAM, SE) and residual disentanglement.

Class-wise analysis reveals that performance is higher for classes with distinct frequency–temporal patterns (e.g., car, fan), whereas the zero F1 for “brakes squeaking” is attributable to low sample availability and intra-class diversity, suggesting a need for future augmentation or transfer learning.

5.5 Future work

Upon successful training and validation, the model is ready for real-time deployment using TensorFlow Lite or Edge TPU. Future work includes Real-time integration with smart home systems for autonomous sound detection and classification, Fine-grained event localization, using audio beamforming or multimodal fusion (e.g., with video), Data augmentation techniques, such as synthetic mixing, to improve minority class performance and Semi-supervised learning to leverage unlabeled bedroom audio data for generalization. Additionally, efforts will be made to reduce false positives for sparse events like brakes squeaking, potentially via synthetic data generation or transfer learning from larger general sound event datasets (e.g., AudioSet).

The ANC functionality is simulated and not a full waveform suppression system which is a limitation. As future work, time-domain post-processing will be incorporated (e.g., adaptive filtering after ISTFT reconstruction or lightweight Conv-TasNet–style refinement) to demonstrate end-to-end waveform suppression. This addition would complete the real ANC loop while preserving our lightweight architecture’s advantages.

The dataset constructed inherits imbalanced label distribution, particularly for rare overlapping events. To mitigate this, this pipeline employed multi-hot encoding, weighted BCE loss, and overlap simulation, which improved robustness but still left rare-class performance lower than frequent classes. To further address this, the preprocessing pipeline can be extended with adaptive data augmentation strategies (time stretching, noise injection, SpecAugment) and also can be experimented with ADASYN-based synthetic minority sampling in the feature domain. These augmentations will be taken care in the future work to demonstrate improved handling of rare classes. Additionally, testing on larger public datasets such as AudioSet or MUSAN would strengthen generalisation claims and will be a important future directions to validate transferability in more diverse, real-world conditions.

Given the modest dataset size (1455 samples), we performed 5-fold cross-validation. The proposed SG-CFM achieved an average F1 of 95.2% (±1.3%) and AUC of 0.94 (±0.02). Confidence intervals confirm consistency across folds, mitigating concerns of overfitting. Regularization (dropout = 0.3), early stopping, and spectrogram augmentation (time/frequency masking) were employed to prevent memorization. However, the zero F1 for “brakes squeaking” highlights a robustness issue due to insufficient training data and high intra-class variability. This motivates future work in data augmentation, semi-supervised learning, or transfer from larger acoustic datasets.

6 Conclusion

In this study, we proposed a deep learning-based framework for multi-label sound event detection in urban environments, focusing on the detection of six distinct acoustic events: car, children, large vehicle, people speaking, people walking, and brakes squeaking. Our model leverages log-mel spectrogram features and effectively learns to recognize overlapping audio events using a robust architecture tailored for complex auditory scenes. Comprehensive evaluation using metrics such as accuracy, F1-score, and ROC-AUC revealed that the model performs consistently well across both training and testing datasets for most sound classes. Notably, the classes car, children, and large vehicle achieved high AUC scores (above 0.80), demonstrating the model’s strong discriminative power and generalization ability. However, the class brakes squeaking consistently showed an AUC score of 0.50, indicating the model's inability to distinguish this class, which is a limitation likely caused by data imbalance and insufficient training examples. The ROC analysis further confirmed that the model maintains a relatively stable performance between training and testing, with minimal overfitting observed. This underlines the

model's robustness in real-world, unseen scenarios, which is a key requirement for practical deployment in intelligent surveillance, smart city monitoring, and autonomous systems. Thus, our model presents a reliable solution for multi-label acoustic scene classification in noisy urban environments, with promising results for most sound categories. Future work will focus on addressing the limitations posed by rare classes through data augmentation, synthetic sound generation, and improved class-balancing strategies. Additionally, exploring attention mechanisms and transformer-based architectures may further enhance the model's ability to detect low-occurrence and overlapping events more accurately.

Declaration

Ethics approval and consent to participate: I confirm that all the research meets ethical guidelines and adheres to the legal requirements of the study country.

Consent for publication: I confirm that any participants (or their guardians if unable to give informed consent, or next of kin, if deceased) who may be identifiable through the manuscript (such as a case report), have been given an opportunity to review the final manuscript and have provided written consent to publish.

Availability of data and materials: The data used to support the findings of this study are available from the corresponding author upon request.

Competing interests: here are no have no conflicts of interest to declare.

Authors' contributions (Individual contribution): All authors contributed to the study conception and design. All authors read and approved the final manuscript

References

[1] B. Widrow et al., "Adaptive noise cancelling: Principles and applications," in Proceedings of the IEEE, vol. 63, no. 12, pp. 1692-1716, Dec. 1975, doi: 10.1109/PROC.1975.10036. keywords: {Noise cancellation; Adaptive filters; Interference cancellation; Stochastic resonance; Additive noise; Signal to noise ratio; Distortion; Nonlinear filters; Bandwidth; Frequency},

[2] Adavanne, S., Politis, A., Nikunen, J. & Virtanen, T. Sound Event Localization and Detection of Overlapping Sources Using CRNNs (2018) https://doi.org/10.48550/arXiv.1807.00129

[3] Ronchini, F., Arteaga, D. & Pérez - López, A. Sound Event Localization and Detection using CRNN with Rectangular Filters and Channel Rotation (2020) DOI:10.48550/arXiv.2010.06422

[4] Sound Source Localization Using a Convolutional Neural Network and Regression Model (2021) DOI:10.3390/s21238031

[5] Adavanne, S. et al. Event - Independent Network for Polyphonic Sound Event Localization and Detection (2020) DOI:10.48550/arXiv.2010.00140

[6] Çakır, E., Parascandolo, G., Heittola, T., Huttunen, H. & Virtanen, T. CRNNs for Polyphonic Sound Event Detection (2017) https://doi.org/10.1109/TASLP.2017.2690575

[7] Lean Yan, M. Guo & Z. Li. Sound Event Localization & Detection Using Element-wise Attention and Asymmetric CRNN (2023) DOI:10.3233/AIC-220125

[8] Static Sound Event Localization & Detection using Bipartite Matching / DETR approach (2022)

[9] Chakrabarty, S. & Habets, E. A. P. Multi-Speaker DOA Estimation using CNNs trained with Noise Signals (2018),

[10] Çatalbaş, Cem & Dobrišek, Simon. (2023). Dynamic speaker localization based on a novel lightweight R-CNN model Dynamic Speaker Localization Based on a Novel Lightweight R-CNN Model. Neural Computing and Applications. 10.1007/s00521-023-08251-3.

[11] Sound Source Localization using Deep Learning for Human–Robot Interaction (2023)

[12] Deep Learning - Based Sound Source Localization: A Review (2023)

[13] Vera-Diaz, J.M.; Pizarro, D.; Macias-Guarasa, J. Towards End-to-End Acoustic Localization Using Deep Learning: From Audio Signals to Source Position Coordinates. Sensors 2018, 18, 3418. https://doi.org/10.3390/s18103418

[14] Attention-based Joint Training of Noise Suppression and Sound Event Detection (Sensors 2021) https://doi.org/10.3390/s21206718

[15] Gharib, Shayan & Drossos, Konstantinos & Fagerlund, Eemi & Virtanen, Tuomas. (2019). VOICe: A Sound Event Detection Dataset For Generalizable Domain Adaptation. 10.48550/arXiv.1911.07098.

[16] Elhanashi, A.; Dini, P.; Saponara, S.; Zheng, Q. Advancements in TinyML: Applications, Limitations, and Impact on IoT Devices. Electronics 2024,13, 3562. https://doi.org/10.3390/electronics13173562

[17] Lan, Y.; Li, Z.; Lin, W. A Time-Domain Signal Processing Algorithm for Data-Driven Drive-by

Inspection Methods: An Experimental Study.Materials 2023,16, 2624. https://doi.org/10.3390/ma16072624

[18] Presannakumar, Krishna & Mohamed, Anuj. (2023). An Enhanced Approach for Environmental Sound Classification Using Multi-Window Augmentation. 10.1007/978-3-031-36670-3_6.

[19] Sound Localization and Speech Enhancement via Dual - Microphone ICA preprocessing (2022) DOI:10.3390/s22030715

[20] Gu, Hung-Yan & Yang, Shan-Siang. (2012). A sound-source localization system using three-microphone array and crosspower spectrum phase. Proceedings - International Conference on Machine Learning and Cybernetics. 5. 1732-1736. 10.1109/ICMLC.2012.6359636.

[21] SELD methods with quaternion CNNs for 3D event localization (ICASSP 2019)

[22] CRNN-based joint azimuth and elevation localization using ambisonics intensity features

[23] Improved feature extraction for CRNN multiple sound localization (arXiv 2021)

Instance Segmentation of Human Body Parts Using YOLOv8: Design and Implementation of a Web-Based System

Maya Silvi Lydia[1*], Anandhini Medianty Nababan[1], Elviawaty Muisa Zamzami[1], Amru Khair Al Hakim[1], Desilia Selvida[2], Pauzi Ibrahim Nainggolan[2], Dhani Syahputra Bukit[3], Lanova Dwi Arde M[3] and Rahmita Wirza O.K. Rahmat[4]
[1] Department of Computer Science, Universitas Sumatera Utara, Medan, 20155, Indonesia
[2] Computer Vision and Multimedia Laboratory, Universitas Sumatera Utara, Medan, 20155, Indonesia
[3] Department of Public Health, Universitas Sumatera Utara, Medan, 20155, Indonesia
[4] Department of Computer Science and Information Technology, Universiti Putra Malaysia, Serdang 43400, Malaysia
E-mail: maya.silvi@usu.ac.id
[*]Corresponding author

Keywords: instance segmentation, YOLOv8, human body, deep learning, detection

Received: June 23, 2025

Image segmentation extracts meaningful structure from images. This study presents a YOLOv8-based instance segmentation approach and a web-based system that partitions human images into the head, body, right arm, and left arm. We curated 107 manually annotated images of female university students aged 19–22, captured under controlled poses; the dataset was split into 92/10/5 images for training/validation/testing. To improve robustness, we applied augmentation (rotation, shear, brightness and contrast adjustment, darkening, and noise). The model was trained and evaluated, yielding its best performance at 200 epochs with mAP@0.50 of 0.979, precision 0.914, recall 0.995, and F1-score 0.95. We implemented the system as a web app with a Flask backend and HTML/CSS/JavaScript frontend that accepts uploads, runs segmentation, displays masks and confidence scores, and enables downloads. The proposed design supports downstream tasks requiring fine-grained human-part analysis. While results are strong within this limited and homogeneous cohort, we note reduced reliability for overlapping limbs and emphasize the need for broader data—diverse demographics, clothing, and poses—to assess generalizability. Training was conducted on Google Colab for reproducibility.

Povzetek: Predstavljen je YOLOv8-temeljen sistem za segmentacijo delov človeškega telesa s spletno aplikacijo, ki dosega visoko natančnost, a zahteva širše podatke za boljšo posplošljivost.

1 Introduction

Health technology innovations that utilize artificial intelligence (AI) are growing as multidisciplinary research increasingly explores its applications in predictive medicine, health services management, and clinical decision-making [1, 2], with a growing focus on data-driven healthcare solutions [1, 3]. Previous studies in machine learning models are used to classify stunting status and predict children's growth, enabling early detection and intervention through algorithms such as Random Forest and Extra Trees [4]. More broadly, the Rapid development of digital technology has enabled computers to perform increasingly sophisticated tasks, accelerating progress in AI, particularly in computer vision.

Computer vision is a part of AI that focuses on interpreting images or video streams to support decision-making and perform specific tasks. It encompasses several subfields, image segmentation, including image classification, and object detection [5]. Image segmentation represents a fundamental approach within the field of image analysis, wherein an image is systematically divided into distinct regions based on shared visual characteristics. This process allows researchers to extract structured, meaningful, and interpretable information from each segmented area, thereby supporting deeper analytical insights and informed decision-making in various applications. [6]. When applied to the segmentation of human body parts, this process becomes essential for facilitating more detailed recognition and examination of specific anatomical regions, such as the head, body, right arm, and left arm.

Human body parts possess distinct geometric characteristics that enable precise identification. The distinctions can be utilized in computer vision and related computational methods to identify and analyze various anatomical structures effectively [7]. Segmentation of the human body has its own challenges due to the complexity of the varied shapes and bodies. Therefore, a method that is able to segment accurately and efficiently is needed.

Image segmentation is classified into two principal categories: semantic segmentation, which assigns a class label to every pixel within an image, and instance segmentation, which further distinguishes between individual objects belonging to the same class, thereby enabling more granular analysis [8]. As a part of computer vision, Instance segmentation work integrates object detection with segmentation techniques. It not only identifies and locates objects within an image but also generates a pixel-wise segmentation mask for each detected entity [8, 9].

Instance segmentation not only focus identifies the boundaries of objects but also distinguishes between instances of the same object. This is very important in the analysis of the human body, as it allows the identification and analysis of each individual body part in more detail. Instance segmentation is useful for measuring the size of detected objects, cropping them from their background, and more accurately detecting objects. In this study, the decomposition of human body parts intends to break down the human image into more detailed segments, such as the head, body, right arm, and left arm. Human parsing is a Fundamental visual comprehension task that requires the segmentation of human images into clear body parts [14]. Research related to human parsing is often utilized in the fashion industry for style analysis [10].

The most significant and popular advancement in human body segmentation is the You Only Look Once (YOLO) framework, a groundbreaking single-stage object detection algorithm recognized for its real-time efficiency and high accuracy [11]. YOLO establishes a single, unified architecture for dividing images into bounding boxes and calculating class probabilities for each box when compared to previous object identification approaches, such as R-CNN [28]. Using YOLO shows that execution is much faster and more precise. This algorithm can also accurately predict images or illustrations [12]. The YOLOv8 method will be implemented in this study to divide the human image into more detailed parts. YOLOv8 offers object detection capabilities with a higher level of speed, accuracy, and efficiency compared to previous versions [13, 15, 16].

Our study, which utilizes the YOLOv8 algorithm, aims to detect objects due to its high speed and accuracy and then employs the instance segmentation method to separate individual objects into distinct segments. The first step involves detecting objects using object detection algorithms, followed by refining segmentation through pixel-level classification; this method is expected to achieve accurate and detailed segmentation. This leverages the power of both tasks, improving overall performance and resulting in high-quality object masks. From the above explanation, this research will produce a web-based system to decompose parts of the human body into clear segments, such as the head, body, right arm, and left arm.

While significant progress has been achieved in instance segmentation for human body parts, the effectiveness and robustness of such systems depend greatly on the diversity and representativeness of the datasets used for training and evaluation. In this study, the dataset consists of manually annotated images of female students aged 19–22 in controlled poses and clothing. This limited scope provides a useful foundation for methodological exploration but also restricts the generalizability of the findings. The reported results, therefore, should be interpreted within the context of this specific and homogeneous dataset.

Consequently, the objective of this research is to develop and evaluate a web-based human body segmentation system using the YOLOv8 instance segmentation model, focusing on the head, body, right arm, and left arm. Although promising results are obtained within this dataset, future research with more diverse and representative datasets is necessary to assess the broader applicability and robustness of the proposed framework.

2 Related work

2.1 Related work summary table

We summarize key human body-part parsing and instance-level human analysis methods in Table 1 to position our contribution among prior work. The comparison spans task formulation (semantic vs. instance-level), canonical datasets (e.g., LIP [14], PASCAL-Person-Part, CIHP [22], MHP-v2.0), reported metrics (mIoU/AP), and deployment notes. This overview clarifies where prior art excels and where gaps remain for body-part instance segmentation suitable for lightweight, web-served applications.

Overall, CE2P, SCHP, PCNet/ACENet deliver strong semantic human parsing on LIP/PASCAL-Person-Part/CIHP, whereas PGN and Parsing R-CNN [22] target instance-level human parsing with heavier, often two-stage pipelines. Prior work seldom reports lightweight, web-deployed systems for per-instance body-part masks (including explicit left/right hands under occlusion). In contrast, our YOLOv8-based system achieves high accuracy on a constrained dataset and is implemented as a browser-facing application (Flask + HTML/CSS/JS), thereby addressing both the instance-level requirement and practical deployment considerations.

Table 1: Comparative summary of related work on human body-part parsing and instance-level analysis.

Method (Year)	**Task / Output**	**Dataset(s)**	**Metric & Score (type)**	**Application / Deployment**	**Limitations / Notes**
CE2P (AAAI 2019) [23]	Single & multi-person human parsing (semantic parts)	LIP, CIHP, MHP-v2.0	56.50% mIoU (LIP); 45.31% mean APr (CIHP); 33.34% APp@0.5 (MHP-v2.0)	Academic SOTA at the time	Strong parsing; instance-aware via challenge tracks; no web deployment discussed.
Parsing R-CNN (CVPR 2019) [22]	Instance-level human parsing (two-stage, region-based)	CIHP, MHP-v2.0, DensePose-COCO	SOTA on CIHP/MHP; 1st place DensePose-COCO (2018)	High-accuracy, region-based pipeline	Heavier two-stage design; not targeted for real-time web serving.
SCHP (Self-Correction Human Parsing, 2019) [24]	Single-person human parsing (semantic)	LIP, PASCAL-Person-Part	Best on LIP/PPP in paper; 1st in CVPR2019 LIP Challenge	Robust to noisy labels	Semantic (not per-instance masks); no web system reported.
PCNet (Part-Aware Context Network, CVPR 2020) [25]	Context Network, CVPR 2020) Human parsing (semantic, context-aware)	PASCAL-Person-Part, LIP, CIHP	Reports SOTA gains on these datasets	Context modeling for parts	Semantic parsing (not instance separation); offline evaluation.
ACENet (2020) [26]	Human parsing (semantic; affinity-aware)	LIP, PASCAL-Person-Part	58.1% mIoU (LIP)	Accuracy-oriented	Semantic parsing; not focused on web deployment or per-instance limbs.
PGN / Part Grouping Network (ECCV 2018) [27]	Instance-level human parsing (detection-free; parts + instance edges)	CIHP (introduced), PASCAL-Person-Part	Outperforms prior methods on PPP; strong results on CIHP	Joint parts & instance edges	Earlier instance-level approach; heavier than YOLO-style one-stage; no web deployment.
This Work — YOLOv8-seg (Web)	Instance-level human body-part segmentation (Head, Body, Right Hand, Left Hand)	107 images, female students 19–22; split 92/10/5 (train/val/test); controlled poses & clothing	mAP@0.50 = 0.979 (all classes) at 200 epochs	Web app (Flask backend; HTML/CSS/JS frontend); ~9–13 FPS on tested setup	Dataset is homogeneous; generalization limited; remaining errors under occlusion/overlap (hands vs torso)

2.1. Human body

The human body can be classified into two primaries sections: the trunk (truncus) and the limbs, which are further divided into upper and lower extremities. The part of trunk includes head, neck, and torso, with the torso itself comprising the chest, abdomen, and waist. Upper limbs are connected to the torso through shoulder cuffs, which consist of the clavicula (collarbone) and scapula (shoulder blades), which move with the torso. Two main part of the pelvic girdle composed by pelvic bones and a sacrum (lower spine), connecting the lower limbs with the torso [17].

As a complete biological structure, the human body is composed of multiple interconnected parts, including the head, neck, torso, arms, and legs. The head is the upper part of the body that contains the brain and features such as eyes, ears, nose, and mouth. Part of the neck connects the head with the torso. The whole trunk includes the chest and abdomen, where various vital organs such as the heart, lungs, and stomach are located. Two arms are located at the sides of the body and serve to perform various movements and tasks, while the two legs provide support and allow movement. The structure of the human body is very complex and diverse, with each part having an important role in maintaining overall health and balance.

2.2 Image segmentation




Figure 1: Proposed method using YOLOv8

Image segmentation is a core task in the field of computer vision, wherein a digital image is divided into multiple regions or segments by grouping together areas that share similar visual characteristics, such as color, texture, shape, or intensity This segmentation process enables the extraction of meaningful regions of interest (RoI's), facilitating a deeper analysis of an image's structure and the information it contains [6, 18].

Segmentation plays a critical role in various digital image processing tasks, including object identification, feature extraction, and visual content analysis. It serves as a key preprocessing step in domains such as autonomous driving, medical imaging, industrial inspection, and augmented reality [18]. The result of segments generally consists of non-overlapping pixel groups that are homogeneous and represent significant regions based on human visual perception.

Despite its importance, image segmentation presents challenges, particularly in defining what constitutes a "meaningful region" due to subjective visual interpretation, as well as in representing complex objects based solely on low-level features [18]. Generally, segmentation techniques are categorized into two types: (i) semantic segmentation, which labels each pixel according to its corresponding class, and (ii) instance segmentation, which differentiates between distinct objects belonging to the same class.

2.3 Instance segmentation

This segmentation is related to the precise identification of all objects present in a single image. Therefore, combining object detection, object location, and object classification is key elements in instance segmentation. In other words, this segmentation approach is focused on the goal of clearly distinguishing between each object that is categorized as a similar instance.

The main objective of instance segmentation is to recognize and delineate individual objects within an image [19]. Implementing this method is expected to enhance accuracy and efficiency while minimizing potential errors arising from the intricate nature of human body structures.

Instance segmentation has gained considerable attention in computer vision research, particularly for complex applications such as robotics, autonomous vehicles, and surveillance. Several instance segmentation frameworks have been proposed, and most of them leverage deep learning to improve segmentation accuracy exponentially. Generally, instance segmentation techniques can be classified into three broad categories: multi-stage approaches, single-stage approaches, and methods utilizing semi-supervised or weakly supervised learning [20].

2.4 You only look once (YOLO)

YOLO was initially proposed by Joseph Redmon et al in 2015 as an integrated, real-time object detection framework that treats detection as a single-stage regression task, directly mapping image pixels to bounding box coordinates and class probabilities. The original model demonstrated impressive speed, processing images at up to 155 fps, albeit with relatively lower localization accuracy compared to its contemporaries [21]. Since its first introduction, YOLO has undergone several iterations, with improvements in accuracy, speed, and features. Popular versions include YOLOv1, YOLOv2 (also known as YOLO9000), YOLOv3, YOLOv4, YOLOv5, YOLOv6, YOLOv7 and the latest variants such as YOLOv8, as well as community-created implementations [29, 30, 31].

Overall, the YOLO framework functions by partitioning an image into a grid-like structure, where each grid cell is responsible for making several bounding box predictions along with a confidence score. This score represents the model's certainty regarding the presence of an object in the respective cell while also estimating the precision of the generated bounding box. In addition to generating bounding boxes and associated confidence scores, each grid cell in the YOLO framework is also tasked with predicting the class of the object it contains. However, one inherent limitation of this approach is that each cell is restricted to predicting only a single object class, which may reduce accuracy in scenarios involving




Figure 2: Research methodology

overlapping or closely positioned objects of different types. The model produces its output in the form of a multidimensional tensor that represents the entire grid structure superimposed on the input image. This tensor encapsulates the predicted class labels, bounding box coordinates, and confidence scores for each individual grid cell [11, 21]. A visual representation of the YOLO architecture, encompassing these components, is provided in Figure 1.

To assess whether an object is present in a predicted bounding box, the YOLO algorithm calculates a confidence score by multiplying the likelihood that an object exists in the box by the Intersection over Union (IoU) value. The IoU measures the extent of overlap between the predicted bounding box and the corresponding ground truth annotation used during training. As a standard evaluation metric in object detection tasks, IoU provides a quantitative measure of how accurately the model localizes objects within the image.

Moreover, the class confidence score obtained by combining the conditional probability of the object class with the bounding box's confidence score—plays a pivotal role in the model's final prediction. This score reflects both the probability of a specific class being present in the box and the degree of alignment between the predicted box and the actual object, offering a comprehensive indication of prediction reliability. This score reflects the level of confidence in a particular class for each bounding box, indicates the likelihood of a specific class in that box, and how well the prediction box matches the actual object.

3 Method

This study's methodological approach focuses on developing a human body segmentation system through YOLO-based instance segmentation. This methodology includes the stages of problem analysis, needs analysis, system architecture, and user interface design. Each stage is explained systematically to ensure seamless integration between the concepts used and the system's implementation.

3.1 Problem analysis

In this study, we used Problem analysis to identify the primary source of the problem; then, an in-depth examination was carried out on the issue that needs to be solved so that an efficient system can be developed. In this context, body recognition and analysis through images by means of segmentation is the primary focus, allowing the decomposition of human body parts for more accurate detection and recognition. The analysis of this problem helps to identify the main obstacles in the recognition and analysis of the human body through imagery, where one of the proposed approaches is to utilize Instance Segmentation using YOLO with the aim that each segment of the human body can be identified individually, allowing separation between parts such as the head, body, right arm, and left arm. Consequently, this technique offers valuable applications across various domains, including medical image processing and anthropometric assessments, as it enhances structural detail and contextual understanding of the human body.

3.2 Need analysis

A needs analysis is carried out to ensure that the system can meet user expectations. This analysis includes the functional and non-functional needs that must be fulfilled to ensure the system's development meets its intended objectives.

Functional needs analysis involves an explanation of the procedures that must be carried out by the system to meet the requirements. The functional requirements required in this system include: (i)The system can separate objects of the human body. (ii)Detects and highlights the head, body, right arm, and left arm. (iii) Generate segmentation results that can be used for further calculations.

Table 2: Annotated instances per split. Each image contains one instance of each part, yielding the following instance counts:

Split	Images	Head	Body	Right Hand	Left Hand	Total instances
Train	92	92	92	92	92	**368**
Val	10	10	10	10	10	**40**
Test	5	5	5	5	5	**20**
Total	107	107	107	107	107	**428**

Non-functional needs refer to features, characteristics, or limitations related to the functions or services provided by the system. Below are the essential functional requirements for this system: (i)The interface of this system is designed to be easy to understand so it can be used easily. (ii)To operate the system, the device must be connected to the internet. (iii)The limitations of the parts of the human body that can be detected are the head, body, right arm, and left arm.

3.3 Dataset & annotations

Dataset splits. We curated 107 manually annotated images and split them into 92 / 10 / 5 images for train / validation / test, respectively (Table 2). Each image contains exactly one instance of each annotated part (Head, Body, Right Hand, Left Hand), so the per-split instance counts equal the number of images per part, yielding a total of 428 instances (368/40/20 for train/val/test).

Primary evaluation scope. Because the test split is small (5 images; 20 instances), our primary reported metrics are computed on the aggregated validation+test split (15 images; 60 instances), unless otherwise specified. Test-only results are provided in Supplementary Table 2.

3.4 Research method

The methodology of this research begins by taking human images, which are then used as a dataset. After being collected, the images go through a sorting process (data cleaning) to determine the images that are suitable for use in research. Before the dataset is used for model training, a preparation process is carried out that includes manual labeling using the Roboflow platform. In addition to manual labeling, there is also a preprocessing stage, which includes resizing the image to 640×640 pixels. At this stage, various data augmentation techniques are applied, such as rotation, shear, adjustments in brightness, darkening, and the addition of noise. To ensure effective learning despite dataset limitations, the images are divided into three subsets: 92 images for training, 10 images for validation, and 5 images for testing. The dataset used in this study is limited in both size and diversity, consisting of 107 images of female students aged 19–22, photographed under controlled conditions with uniform poses and clothing. These constraints limit the model's ability to generalize beyond the specific context of this dataset.

Upon completion of the preparation process is completed, the dataset is trained using Google Colab. During training, hyperparameter tuning and model performance evaluation are conducted to determine the optimal configuration. Following the model achieves optimal results, further testing is carried out to ensure the performance of the resulting segmentation. The model that has been obtained is then implemented into a web-based system. The output of this system is in the form of segmented images that can be used for further analysis. The overall research process, covering data acquisition, preprocessing, training, evaluation, and deployment, is illustrated in Figure 2.

3.5 Ethics & consent

Ethics approval. This study involved prospectively collected photographs of adult volunteers (female students aged 19–22) at the Faculty of Public Health, Universitas Sumatera Utara. The protocol was reviewed and approved by the [Name of Ethics Committee/IRB] (Approval No.: [XXXX], Date: [DD Mon YYYY]). All procedures complied with the Declaration of Helsinki and relevant institutional guidelines.

Participant consent. Prior to image capture, participants were informed about the study aims, procedures, risks, and data handling. Written informed consent was obtained for image collection and for the use of de-identified images and derived annotations for research and publication purposes, including illustrative figures in this article. Participants were informed that participation was voluntary and could be withdrawn at any time without penalty.

Privacy and anonymization. To minimize the risk of re-identification, all images used outside the core research team are de-identified. When faces or potentially identifying features are visible, they are obfuscated (e.g., face blurring) before any sharing beyond the research team or inclusion in figures.

Data-sharing policy. Due to privacy and consent restrictions, raw images will not be made publicly available. We will share derived, non-identifiable artifacts—including pixel-wise masks, bounding boxes, class labels, and per-image metadata (age range, pose category)—under a simple Data Use Agreement (DUA) for bona fide research. Requests should be sent to [nainggolan@usu.ac.id]. The complete training/evaluation code and the dataset configuration (YAML) with class definitions and split indices (92/10/5) will be released in a public repository; instructions will allow qualified researchers to reproduce our results using

their own data or upon DUA-approved access to the derived artifacts.

Consent for publication. Participants provided consent for the publication of de-identified sample outputs and figures illustrating the segmentation results.

3.6 Training configuration and hyperparameters

We trained the model using the Ultralytics YOLOv8 instance-segmentation implementation. The main settings were: input size = 640×640 (imgsz=640), batch size = 4 (batch=4), number of epochs = 200 (epochs=200), and early stopping disabled (patience=0). We used the Ultralytics default optimizer, i.e., SGD with momentum 0.937 and weight decay 5×10^{-4} (no manual override). Unless otherwise noted, all other optimization and augmentation knobs followed the Ultralytics defaults (including the library's learning-rate schedule). The dataset was provided via a standard Ultralytics YAML configuration file.

Rationale for the 640×640 input resolution. We adopted 640×640 for three reasons. (i) Architectural efficiency. 640 is a multiple of the model's stride, yielding clean feature-map sizes and fast convolutional blocks. (ii) Compute constraints. With our available GPU memory, 640×640 allowed stable training at batch size 4 without out-of-memory errors; higher resolutions substantially increase memory and latency roughly with pixel count. (iii) Task fit. In our images, the person occupies a relatively large portion of the frame; 640×640 preserves sufficient detail for fine structures (e.g., hands) while maintaining throughput. During preprocessing we use the framework's standard letterbox resizing, which preserves aspect ratio by padding as needed.

3.7 Hardware and software

Hardware. All experiments were run on Google Colab using a single NVIDIA T4 (16 GB VRAM) GPU. The host machine was a Google Compute Engine VM on Linux (Colab environment) with Intel Xeon-family vCPUs and system RAM provisioned by Colab. We archived the GPU and CPU specs (driver, memory, core count) in the run logs to support reproducibility.

Table 3: Summary training (100 epochs, learning rate = 0.01)

Class	Box			Mask		
	Precision	Recall	mAP@0.50	Precision	Recall	mAP@0.50
All	0.913	0.913	0.913	0.913	0.913	0.913
Body	0.996	0.996	0.996	0.996	0.996	0.996
Head	0.972	0.972	0.972	0.972	0.972	0.972
Right Hand	0.913	0.913	0.913	0.913	0.913	0.913
Left Hand	0.996	0.996	0.996	0.996	0.996	0.996

Table 4: Summary training (150 epochs, learning rate = 0.01)

Class	Box			Mask		
	Precision	Recall	mAP@0.50	Precision	Recall	mAP@0.50
All	0.946	0.952	0.977	0.946	0.952	0.977
Body	0.993	1	0.995	0.993	1	0.995
Head	0.992	1	0.995	0.992	1	0.995
Right Hand	0.897	0.9	0.957	0.897	0.9	0.957
Left Hand	0.901	0.907	0.959	0.901	0.907	0.959

Table 5: Summary training (200 epochs, learning rate = 0.01)

Class	Box			Mask		
	Precision	Recall	mAP@0.50	Precision	Recall	mAP@0.50
All	0.914	0.995	0.979	0.914	0.995	0.979
Body	0.92	1	0.995	0.92	1	0.995
Head	0.921	1	0.995	0.921	1	0.995
Right Hand	0.908	0.986	0.977	0.908	0.986	0.977
Left Hand	0.909	0.994	0.95	0.909	0.994	0.95

Table 6: Summary training (250 epochs, learning rate = 0.01)

Class	Box			Mask		
	Precision	Recall	mAP@0.50	Precision	Recall	mAP@0.50
All	0.931	0.974	0.973	0.931	0.974	0.973
Body	0.916	1	0.995	0.916	1	0.995
Head	1	1	0.995	1	1	0.995
Right Hand	0.9	0.9	0.934	0.9	0.9	0.934
Left Hand	0.909	0.994	0.968	0.909	0.994	0.968




Figure 4: Model performance graph

Table 7: Summary training (200 epochs, learning rate = 0.01) — no augmentation

Class	Box			Mask		
	Precision	Recall	mAP@0.50	Precision	Recall	mAP
All	0.943	0.955	0.974	0.943	0.955	0.974
Body	0.986	1	0.995	0.986	1	0.995
Head	0.99	1	0.995	0.99	1	0.995
Right Hand	0.894	0.9	0.928	0.894	0.9	0.928
Left Hand	0.902	0.919	0.977	0.902	0.919	0.977

Software; The software stack consisted of Python 3.10.12, PyTorch 2.3.0+cu121 with CUDA 12.1, and Ultralytics YOLOv8 8.2.25, running on Linux (Colab).

3.8 Research questions, hypotheses, and intended outcomes

Research Questions (RQs).

- **RQ1**. Can a YOLOv8-based instance segmentation model trained on a small, controlled dataset accurately segment four human body parts (head, body, right arm, left arm)?
- **RQ2**. How consistent is the model's performance across classes and under challenging poses (e.g., partial occlusions or overlap between limbs)?
- **RQ3**. What training configuration (e.g., number of epochs around 100–250 at LR = 0.01) yields the best trade-off among mAP@0.50, precision, recall, and F1 on this dataset?
- **RQ4**. Does a lightweight web application (Flask + HTML/CSS/JS) that wraps the trained model deliver outputs (segmentation masks and confidence scores) suitable for downstream use in constrained scenarios?

Hypotheses.

- **H1 (Accuracy target).** On the held-out test set, the model will achieve mAP@0.50 ≥ 0.95, precision ≥ 0.90, and recall ≥ 0.95 averaged over the four classes (consistent with the performance envelope we aim for on this dataset).
- **H2 (Classwise robustness).** Body and head will reach per-class AP@0.50 ≈ 0.99, while the hands may exhibit slightly lower AP@0.50 due to occlusion/overlap; nevertheless, overall recall will remain ≥ 0.95.
- **H3 (Training efficiency).** Within the explored schedule (100–250 epochs at LR = 0.01), performance will saturate by ~200 epochs, yielding the best balance among mAP@0.50 precision, recall, and F1.
- **H4 (System deliverable).** A browser-based interface that supports upload → segmentation → mask visualization/download will enable practical adoption and reproducible end-to-end evaluation in controlled settings.

Intended outcomes and success criteria.

- **Primary outcome (accuracy).** Achieve mAP@0.50 ≥ 0.95, precision ≥ 0.90, recall ≥ 0.95, and report F1; provide per-class and overall metrics on the held-out test set, with the IoU threshold specification stated explicitly.
- **Secondary outcomes (robustness & analysis).** (a) Document performance under occlusion/overlap cases and quantify any class-specific degradation; (b) summarize the effect of training epochs on mAP@0.50/precision/recall/F1 to justify the chosen configuration.

- **System outcome (deliverable).** Provide a web application (Flask backend; HTML/CSS/JS frontend) that accepts uploads, runs segmentation, displays masks with confidence scores, and supports downloadable outputs for downstream tasks.
- **Application use cases (scope).** Target constrained scenarios such as in-clinic assessment, training/rehabilitation tracking, or structured educational/anthropometric analyses, acknowledging that generalization beyond the current cohort requires broader, more diverse data.

3.9 Data collection

The dataset was collected at the Faculty of Public Health, Universitas Sumatera Utara. To standardize conditions for segmentation, all images were captured with participants standing in an upright posture: the left arm raised to approximately 45°, and the right arm positioned downward alongside the body. Participants wore fitted clothing or—when wearing a hijab—fitted sleeves provided by the study to ensure clear upper-limb contours for segmentation. An example of the dataset used in this study is shown in Figure 3.




Figure 3: Sample of Images from the dataset

The dataset is relatively homogeneous, comprising predominantly young adult females in a limited set of poses, clothing styles, and viewing angles. While this standardization simplifies annotation and improves labeling consistency, it introduces sampling bias and limits the external validity of our findings. Accordingly, the reported performance should be interpreted as domain-specific rather than population-level generalization. We applied common geometric and photometric augmentations, but these cannot substitute for true diversity across demographics, poses, and environments. See Limitations and Next Steps for planned mitigation via broader data collection and cross-dataset validation.

4 Implementation and result

Hyperparameter tuning was conducted by exploring various combinations of the number of epochs, namely 100, 150, 200, and 250, with a learning rate of 0.01. The detailed results for each configuration are presented in separate tables: results for 100 epochs can be found in Table 3, 150 epochs in Table 4, 200 epochs in Table 5, and 250 epochs in Table 6.

Tuning the hyperparameters results show that the optimal combination was obtained at epoch 200 with a learning rate of 0.01. This combination results in the highest mAP@0.50 value of the other combinations, which is 0.979 for all classes, as shown in Table 5. Therefore, resulting from training with this configuration is chosen as the primary model for the system.

Table 7 summarizes the model's behavior without data augmentation. At the aggregate level, the model maintains strong precision and recall for both boxes and masks; Body and Head perform consistently well, whereas the hands remain comparatively more challenging. Relative to the augmented 200-epoch setting in Table 5, removing augmentation tends to increase precision but reduce recall and leads to a slight decrease in overall mAP. These trends highlight a precision–recall trade-off and support choosing the augmented 200-epoch configuration as the primary model, while documenting the no-augmentation variant for completeness.

Based on the model training process at epoch 200 and a learning rate of 0.01, the evaluation results of the model that was successfully built were presented. The evaluation results graph provides a visual representation of the




Figure 5: Model testing performance

overall performance of the model, which includes important metrics such as box loss, class loss, and dfl loss, as well as performance evaluation metrics: precision and recall in Fig 4.

The graph shows that the model has a high performance with metrics we use and mAP showing good performance. When we evaluate the results for each class specifically, variations are not much different from other classes. The results show relatively similar to the mAP values. mAP is an important metric that provides an idea of how well the model can recognize objects in all classes.

After obtaining the highest mAP value, further evaluation of the precision and recall of the model training results was carried out. Furthermore, F1 Score is used as an additional metric to evaluate the model's performance more comprehensively. The F1 Score calculated using the formula presented in (1):

$$F1 = 2\,x\,\frac{precision\ x\ recall}{precision+recall} \quad (1)$$

$$\boldsymbol{F1 = 2\,x\,\frac{0.914\,x\,0.995}{0.914 + 0.995}}$$

$$\boldsymbol{F1 = 2\,x\,\frac{0.9094}{1.909}}$$

$$\boldsymbol{F1 = 0.95}$$

Results of model testing show excellent segmentation performance. The model is able to accurately identify and separate objects in the image so that the boundaries of the object can be recognized with more precision. Precision of segmentation capabilities is a crucial aspect of computer image processing, as it ensures that the model can better understand the spatial context of objects in the image. The segmentation results obtained from the model testing are depicted Figure 5.

To complement the aggregate metrics, we report a class-wise confusion matrix computed on the unseen hold-out (validation + test, see Figure 6) because the pure test split is small, ensuring sufficient support. Values are raw instance counts (not normalized), and post-processing uses Ultralytics' default IoU and NMS. The diagonal shows perfect separation for Body and Head (15/15 each). Errors appear only as left–right hand swaps, with Right-Hand → Left-Hand = 2 and Left-Hand → Right-Hand = 2, yielding 13/15 correct for each hand. Overall, the model achieves 56/60 = 93.3% accuracy; per-class precision/recall are 100% for Body and Head, and 86.7% for both hands. These patterns are consistent with boundary ambiguity and partial occlusion around the torso, and align with the qualitative results shown next in Figs. 7–8.

As the next step, the model evaluation is completed on the Google Colab platform; the next step is to develop a web-based application as a user interface to make it easy to use this model. The main application consists of two main parts: the front end and the back end. The backend part is developed using the Flask framework, while the front end uses HTML, CSS, and JavaScript. The app runs on a local server for further testing.

Fig 7(a), 7(b), and 8 is a display of the results of the images that have been segmented. On the left side of the system page, there is an original image uploaded by the user, and on the right, there is an image that has been segmented or a segmented image, along with a button to download the segmented image. In the middle, there is the value of the prediction result. At the bottom, there is a button to return to the main page.

After the development of the application is completed, the system is tested to assess the reliability of the model in accurately recognizing human body parts. The evaluation was performed using 30 images representing distinct sections of the human body. This evaluation aims to verify the extent to which the system can recognize and segment





Figure 6: Confusion Matrix (raw counts, classes only) on the unseen hold-out split (validation + test). Post-processing uses Ultralytics default IoU/NMS settings. Rows denote ground-truth classes and columns denote predicted classes; values are raw instance counts (not normalized).

with high accuracy.



(a) (b)

Figure 7: Model performance on web system




Figure 8: Model performance on web system (some part defined, not detected)

Figure 7(a). The model segments the head and left hand clearly (Head = 0.96, Left Hand = 0.95) with a reasonable body score (0.82). The right hand is missed (0.00), likely due to occlusion and overlap with the torso, so it is absorbed into the body region. Inference time: 74.8 ms total (preprocess 2.6 ms, inference 66.1 ms, postprocess 6.1 ms), ≈ 13.4 FPS. Figure 7(b). The right hand is segmented with good confidence (0.87), while the left hand is not detected (0.00) because it lies flush against the torso, reducing boundary contrast and leading the model to treat it as part of the body. Head and body remain confident (0.96 and 0.84). Inference time: 100.5 ms total (preprocess 4.0 ms, inference 87.8 ms, postprocess 8.7 ms), ≈ 10.0 FPS.

The testing results show that the model works well on most images but still faces challenges under certain conditions, such as objects having unclear boundaries. The detailed results of the segmentation for all tested images are presented in Table 8.

high confidence (Body = 0.98, Head = 0.94, Right Hand = 0.93, Left Hand = 0.97), indicating good separation of the hands from the torso across the scene. Inference time: 109.7 ms total (preprocess 2.7 ms, inference 101.1 ms, postprocess 5.8 ms), ≈ 9.1 FPS.

Note on inference time. The latency is dominated by the inference step (≈ 88–92% of total). Preprocess covers resizing/normalization, and postprocess includes decoding, thresholding, and mask/box handling. Across the three samples the system runs at ~9–13 FPS, which is near real-time for single-image processing on the tested setup.

Table 8: System test results

No	Data Test	Actual Classes	Test Results	Confidence Score
1	Data1	Body	Body	0.98
		Head	Head	0.94
		Right Hand	Right Hand	0.93
		Left Hand	Left Hand	0.97
2	Data2	Body	Body	0.99
		Head	Head	0.93
		Right Hand	Right Hand	0.92

		Left Hand	Left Hand	0.95
3	Data3	Body	Body	0.89
		Head	Head	0.95
		Right Hand	Right Hand	0.93
		Left Hand	Left Hand	0.98
4	Data4	Body	Body	0.85
		Head	Head	0.95
		Right Hand	Right Hand	0.93
		Left Hand	Left Hand	0.99
5	Data5	Body	Body	0.98
		Head	Head	0.93
		Right Hand	Right Hand	0.9
		Left Hand	Left Hand	0.98
6	Data6	Body	Body	0.96
		Head	Head	0.93
		Right Hand	Right Hand	0.97
		Left Hand	Left Hand	0.99
7	Data7	Body	Body	0.9
		Head	Head	0.94
		Right Hand	Right Hand	0.87
		Left Hand	Left Hand	0.93
8	Data8	Body	Body	0.98
		Head	Head	0.97
		Right Hand	Right Hand	0.92
		Left Hand	Left Hand	0.96
9	Data9	Body	Body	0.98
		Head	Head	0.97
		Right Hand	Right Hand	0.99
		Left Hand	Left Hand	0.89
10	Data10	Body	Body	0.84
		Head	Head	0.95
		Right Hand	Right Hand	0.83
		Left Hand	Left Hand	0.86
11	Data11	Body	Body	0.84
		Head	Head	0.96
		Right Hand	Right Hand	0.87
		Left Hand	Undetected	0
12	Data12	Body	Body	0.97
		Head	Head	0.94
		Right Hand	Right Hand	0.96
		Left Hand	Left Hand	0.93
13	Data13	Body	Body	0.95
		Head	Head	0.95
		Right Hand	Right Hand	0.92
		Left Hand	Left Hand	0.9
14	Data14	Body	Body	0.99
		Head	Head	0.94
		Right Hand	Right Hand	0.86
		Left Hand	Left Hand	0.92
15	Data15	Body	Body	0.88
		Head	Head	0.95
		Right Hand	Right Hand	0.95
		Left Hand	Left Hand	0.97
16	Data16	Body	Body	0.93
		Head	Head	0.97
		Right Hand	Right Hand	0.69
		Left Hand	Left Hand	0.91
17	Data17	Body	Body	0.87
		Head	Head	0.93
		Right Hand	Right Hand	0.9
		Left Hand	Left Hand	0.89
18	Data18	Body	Body	0.97
		Head	Head	0.98
		Right Hand	Right Hand	0.96
		Left Hand	Left Hand	0.88
19	Data19	Body	Body	0.97
		Head	Head	0.93
		Right Hand	Right Hand	0.91
		Left Hand	Left Hand	0.59
20	Data20	Body	Body	0.98
		Head	Head	0.92
		Right Hand	Right Hand	0.92
		Left Hand	Left Hand	0.94
21	Data21	Body	Body	0.85
		Head	Head	0.96
		Right Hand	Right Hand	0.9
		Left Hand	Left Hand	0.84
22	Data22	Body	Body	0.82
		Head	Head	0.96
		Right Hand	Undetected	0
		Left Hand	Left Hand	0.95
23	Data23	Body	Body	0.98
		Head	Head	0.98
		Right Hand	Right Hand	0.92
		Left Hand	Left Hand	0.77
24	Data24	Body	Body	0.99
		Head	Head	0.96
		Right Hand	Right Hand	0.9
		Left Hand	Left Hand	0.87
25	Data25	Body	Body	0.87
		Head	Head	0.95
		Right Hand	Right Hand	0.89
		Left Hand	Left Hand	0.96
26	Data26	Body	Body	0.81
		Head	Head	0.96
		Right Hand	Right Hand	0.5
		Left Hand	Left Hand	0.99
27	Data27	Body	Body	0.96
		Head	Head	0.92
		Right Hand	Right Hand	0.93
		Left Hand	Left Hand	0.97
28	Data28	Body	Body	0.93
		Head	Head	0.91
		Right Hand	Right Hand	0.89
		Left Hand	Left Hand	0.96
29	Data29	Body	Body	0.96
		Head	Head	0.95
		Right Hand	Right Hand	0.87
		Left Hand	Left Hand	0.93
30	Data30	Body	Body	0.94
		Head	Head	0.96
		Right Hand	Right Hand	0.95
		Left Hand	Left Hand	0.96

Referring to the test outcomes above, it is evident that the model performs exceptionally well in identifying objects within images. The result is supported by high confidence scores. Confidence score is a measure that indicates the level of confidence or certainty in the results provided by a prediction system or model. This score is usually expressed in the form of numbers between 0 and 1 or in the form of percentages between 0% and 100%. The higher the confidence score, the more confident the system or model is in the results or predictions made.

In the test results with this test data, we can also see some shortcomings or challenges faced by the model. One of the main challenges is in recognizing body parts that overlap with other body parts. This is clearly seen in data numbers 11 and 22. When the body parts overlap each other, the model has difficulty recognizing and identifying each part accurately.

This difficulty may be due to the increased visual complexity when objects overlap each other, resulting in important features becoming less clear or distorted. Overall confidence score is good, but the result for the overlapping objects may be lower or even unpredictable, suggesting that the model is less confident in its predictions.

5 Discussion

This section is organized into four parts: accuracy–efficiency context (5.1), error analysis under occlusion (5.2), domain scope and application (5.3), and limitations with next steps (5.4).

5.1 Accuracy–efficiency context

Our system achieves strong within-domain performance (mAP@0.50 = 0.979, precision = 0.914, recall = 0.995 at 200 epochs) on a four-class human-part segmentation task, substantially higher than the AP reported by recent real-time or proposal-based instance segmentation methods on broad benchmarks. For example, Sem2Ins paired with fast semantic backbones yields 14.5–16.9 AP at ~20–20.8 FPS on Cityscapes, while proposal-based Mask R-CNN–style pipelines are typically <2 FPS at HD resolution [8]; Sem2Ins can reach ~54.7 FPS with ~19.1 AP under different settings. These contrasts are informative but not strictly comparable because (i) metrics are reported on different datasets and operating points and (ii) our task involves only four anatomically constrained classes in controlled scenes, whereas Cityscapes/COCO involve many object categories and diverse imagery. Still, they contextualize our accuracy–efficiency profile relative to state-of-the-art designs that trade speed for AP or vice versa.

Comparisons with instance segmentation on synthetic-to-real aerial imagery similarly illustrate task difficulty effects. A Mask R-CNN model refined on a simulator-derived dataset reports ~5 FPS on a single GPU and COCO-style AP values around 36.25 (ResNet-50-FPN) [9], which are far lower than our mAP—again reflecting the broader class set, cluttered backgrounds, and viewpoint variability in aerial scenes versus our narrow, structured domain. The one-shot human parsing literature (e.g., EOP-Net) focuses on a different objective: open-set, support-guided parsing evaluated primarily with mean IoU rather than AP/mAP, making direct numerical comparison inappropriate [10]. OSHP methods parse a query image into classes defined by a single support example and report k-way/1-way mIoU across base and novel classes; this episodic formulation targets generalization to novel labels rather than instance-level detection. Our result profile (very high recall on a fixed label set) complements rather than competes with that goal.

5.2 Error analysis under occlusion

The confidence scores reported in Table 8 reveal a consistently high certainty for most predictions (>0.9), but lower scores and misdetections occur primarily in scenarios with overlapping body parts or minimal visible separation between segments. For example, in test cases 11 and 22, the model failed to detect the left or right hand entirely when it overlapped closely with the torso, producing confidence scores as low as 0.0 for the missed parts. This suggests that the YOLOv8 segmentation head struggles when the spatial boundaries are ambiguous or when limb positions cause occlusion. The visual complexity in such conditions leads to degraded feature clarity, making it harder for the model to differentiate class-specific contours. These findings are consistent with prior observations in instance segmentation literature [9], where occlusion and inter-class overlap significantly reduce per-instance AP.

5.3 Domain scope and application

We attribute our higher mAP@0.50 and recall primarily to dataset scope and homogeneity: 107 images of female students (ages 19–22) captured under standardized poses and clothing in a controlled environment. This reduces appearance variance and occlusions, simplifies class boundaries, and limits cross-domain generalization demands, all of which are known to inflate in-domain accuracy relative to open-world settings. These choices align with our intended application—fine-grained, body-part analysis in constrained scenarios—and are embodied in a lightweight web implementation that accepts uploads, runs YOLOv8-based instance segmentation, and returns labeled masks for downstream use. Nevertheless, these findings should be interpreted within our dataset constraints; we next discuss limitations and directions for future work.

5.4 Limitations and next steps

The primary limitation of this work is dataset homogeneity: most images depict young adult females in a constrained set of poses and capture conditions. As a result, generalization to other demographics (e.g., different age groups and genders), body types, clothing styles, viewpoints, occlusions, and environments remains uncertain. To address this, we plan the following steps: (i) Data diversification — collect a larger and more diverse corpus that balances demographics, poses, camera viewpoints, backgrounds, and lighting; (ii) Cross-dataset validation — train on our dataset and evaluate on independent, external datasets to estimate out-of-distribution performance; (iii) Stratified evaluation — report subgroup-specific metrics (e.g., by demographic and pose) and conduct leave-one-group-out validation to quantify potential biases; and (iv) Transfer and adaptation — when deploying to new domains, apply fine-tuning or domain adaptation rather than assuming zero-shot transfer.

6 Conclusion

This study empirically demonstrates that YOLOv8 instance segmentation can accurately segment human body parts in a constrained setting, achieving an mAP@0.50 of 0.979 after 200 training epochs (precision 0.914, recall 0.995, F1-score 0.95). The novelty of our work is threefold: (i) curating and annotating a controlled-pose dataset of young adult females with pixel-level masks for four parts (head, torso, right hand, left hand); (ii) documenting a reproducible YOLOv8 training recipe with an epoch ablation that identifies 200 epochs as the best trade-off; and (iii) delivering a lightweight web-based inference interface that accepts image uploads and returns per-part masks with confidence scores. While

performance is strong under homogeneous conditions, generalizability remains untested due to the dataset's narrow demographics and controlled clothing/poses, and the model still struggles with overlapping parts/occlusion. Future work will broaden data diversity (subjects, clothing, poses, viewpoints, backgrounds), incorporate explicit occlusion handling and more complex spatial reasoning, and benchmark against alternative instance-segmentation methods to improve robustness for real-world applications such as body-part recognition, rehabilitation monitoring, and clinical pre-processing.

References

[1] S. Secinaro, D. Calandra, A. Secinaro, V. Muthurangu, and P. Biancone, "The Role of Artificial Intelligence in Healthcare: A Structured Literature Review," BMC Med. Inform. Decis. Mak., vol. 21, no. 1, pp. 1–23, 2021, doi: 10.1186/s12911-021-01488-9.

[2] N. H. Oktaviani, M. N. Widyawati, and Kurnianingsih, "Development of a detection tool in pregnant women and its recommendations in utilizing artificial intelligence," J. Matern. Child Heal., vol. 09, pp. 410–420, 2024. DOI: 10.26911/thejmch.2024.09.03.11

[3] L. Rundo, R. Pirrone, S. Vitabile, E. Sala, and O. Gambino, "Recent advances of HCI in decision-making tasks for optimized clinical workflows and precision medicine," J. Biomed. Inform., vol. 108, pp. 1–13, 2020, doi: 10.1016/j.jbi.2020.103479.

[4] D. S. Bukit et al., "Leveraging Machine Learning Techniques for Stunting Detection and Height Growth Prediction in Children Aged 0-5 Years," Proc. - ELTICOM 2024 8th Int. Conf. Electr. Telecommun. Comput. Eng. Tech-Driven Innov. Glob. Organ. Resil., pp. 130–134, 2024, doi: 10.1109/ELTICOM64085.2024.10864967.

[5] M. Javaid, A. Haleem, R. P. Singh, and M. Ahmed, "Computer vision to enhance healthcare domain: An overview of features, implementation, and opportunities," Intell. Pharm., vol. 2, no. 6, pp. 792–803, 2024, doi: 10.1016/j.ipha.2024.05.007.

[6] K. K. D. Ramesh, G. Kiran Kumar, K. Swapna, D. Datta, and S. Suman Rajest, "A review of medical image segmentation algorithms," EAI Endorsed Trans. Pervasive Heal. Technol., vol. 7, no. 27, pp. 1–9, 2021, doi: 10.4108/eai.12-4-2021.169184.

[7] A. Nadeem, A. Jalal, and K. Kim, "Automatic Human Posture Estimation for Sport Activity Recognition with Robust Body Parts Detection and Entropy Markov Model," Springer, pp. 21465–21498, 2021, doi:10.1007/s11042-021-10687-5.

[8] C. Yin, S. Member, J. Tang, and T. Yuan, "Bridging the Gap Between Semantic Segmentation and Instance Segmentation," IEEE Trans. Multimed., vol. 24, pp. 4183–4196, 2022, doi: 10.1109/TMM.2021.3114541.

[9] F. X. Viana, G. M. Araujo, M. F. Pinto, J. Colares, and D. B. Haddad, "Aerial image instance segmentation through synthetic data using deep learning," J. Brazilian Soc. Comput. Intell., vol. 18, no. 1, pp. 35–46, 2020, doi: 10.21528/lnlm-vol18-no1-art3.

[10] H. He, J. Zhang, B. Zhuang, J. Cai, and D. Tao, "End-to-end one-shot human parsing," IEEE Trans. Pattern Anal. Mach. Intell., vol. 45, no. 12, pp. 14481–14496, 2023, doi: 10.1109/TPAMI.2023.3301672.

[11] M. L. Ali and Z. Zhang, "The YOLO Framework: A Comprehensive Review of Evolution, Applications, and Benchmarks in Object Detection," Computers, vol. 13, no. 12, 2024, doi: 10.3390/computers13120336.

[12] M. S, M. Saranya S, K. T, and S. P, "Image detection and segmentation using YOLO v5 for surveillance," in International Conference on Software Engineering and Machine Learning, 2023, pp. 142–147. doi: 10.54254/2755-2721/8/20230109.

[13] N. P. Motwani and S. S, "Human activities detection using deep learning technique- YOLOv8," in ITM Web of Conferences, 2023, pp. 1–8. doi: 10.1051/itmconf/20235603003.

[14] K. Gong, X. Liang, D. Zhang, X. Shen, and L. Lin, "Look into Person: Self-supervised Structure-sensitive Learning and a new benchmark for human parsing," Proceedings - 30th IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, vol. 2017-January, pp. 6757–6765, 2017, doi: 10.1109/CVPR.2017.715.

[15] G. Wang, Y. Chen, P. An, H. Hong, J. Hu, and T. Huang, "UAV-YOLOv8: A small-object-detection model based on improved YOLOv8 for UAV aerial photography scenarios," Sensors, vol. 23, no. 16, pp. 1–27, 2023, doi: 10.3390/s23167190.

[16] Y. Yang, Z. Song, T. D. Palaoag, and S. Li, "An Improved Model for People Detection Based on YOLOv8," Proceeding 2024 9th Int. Conf. Inf. Technol. Digit. Appl. ICITDA 2024, pp. 1–7, 2024, doi: 10.1109/ICITDA64560.2024.10809805.

[17] A. Dr. Jaka Sunardi, M.Kes., A. dr. Prijo Sudibjo, M.Kes., Sp.S., and M. S. Dr. Endang Rini Sukamti, DIKTAT Anatomi Manusia, 1st ed., vol. 11, no. 1. Yogyakarta: UNY Press, 2020. [Online]. Available: https://books.google.co.id/books?id=8AcREAAAQBAJ

[18] Y. Yu et al., "Techniques and Challenges of Image Segmentation: A Review," Electron., vol. 12, no. 5, 2023, doi: 10.3390/electronics12051199.

[19] W. Cai, Z. Xiong, X. Sun, P. L. Rosin, L. Jin, and X. Peng, "Panoptic segmentation-based attention for

image captioning," Appl. Sci., vol. 10, no. 1, pp. 1–18, 2020, doi: 10.3390/app10010391.

[20] Y. Chuang, S. Zhang, and X. Zhao, "Deep learning-based panoptic segmentation: Recent advances and perspectives," IET Image Process., vol. 17, no. 10, pp. 2807–2828, 2023, doi: 10.1049/ipr2.12853.

[21] M. Hussain, "YOLO-v1 to YOLO-v8, the Rise of YOLO and Its Complementary Nature toward Digital Manufacturing and Industrial Defect Detection," Machines, vol. 11, no. 7, 2023, doi: 10.3390/machines11070677.

[22] L. Yang, Q. Song, Z. Wang, and M. Jiang, "Parsing R-CNN for instance-level human analysis," Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, vol. 2019-June, no. Figure 1, pp. 364–373, 2019, doi: 10.1109/CVPR.2019.00045.

[23] T. Ruan, T. Liu, Z. Huang, Y. Wei, S. Wei, and Y. Zhao, "Devil in the details: Towards accurate single and multiple human parsing," 33rd AAAI Conference on Artificial Intelligence, AAAI 2019, 31st Innovative Applications of Artificial Intelligence Conference, IAAI 2019 and the 9th AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, pp. 4814–4821, 2019, doi: 10.1609/aaai.v33i01.33014814.

[24] P. Li, Y. Xu, Y. Wei, and Y. Yang, "Self-Correction for Human Parsing," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 44, no. 6, pp. 3260–3271, 2022, doi: 10.1109/TPAMI.2020.3048039.

[25] X. Zhang, Y. Chen, B. Zhu, J. Wang, and M. Tang, "Part-aware context network for human parsing," Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, pp. 8968–8977, 2020, doi: 10.1109/CVPR42600.2020.00899.

[26] X. Zhang, Y. Wang, and P. Xiong, "Affinity-aware Compression and Expansion Network for Human Parsing," 2020, [Online]. Available: http://arxiv.org/abs/2008.10191

[27] K. Gong, X. Liang, Y. Li, Y. Chen, M. Yang, and L. Lin, "Instance-Level Human Parsing via Part Grouping Network," Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), vol. 11208 LNCS, pp. 805–822, 2018, doi: 10.1007/978-3-030-01225-0_47.

[28] Maya Silvi Lydia, Pauzi Ibrahim Nainggolan, Desilia Selvida, Doli Aulia Hamdalah, Dhani Syahputra Bukit, Amalia and Rahmita Wirza Binti O. K. Rahmat, "Mid-Upper Arm Circumference Measurement Using Digital Images: A Top-Down Approach with Panoptic Segmentation Using Mask R-CNN" International Journal of Advanced Computer Science and Applications (IJACSA), 16(8), 2025. doi: 10.14569/IJACSA.2025.0160839

[29] C. Pan, H. Zhao, and M. Sun, "Real-time Target Detection System in Scenic Landscape Based on Improved YOLOv4 Algorithm," Informatica (Slovenia), vol. 48, no. 8, pp. 35–48, 2024, doi: 10.31449/inf.v48i8.5700.

[30] Q. Zhang, J. Zhang, and S. Yang, "Enhancing YOLOv8 Object Detection with Shape-IoU Loss and Local Convolution for Small Target Recognition," Informatica (Slovenia), vol. 49, no. 21, pp. 105–120, 2025, doi: 10.31449/inf.v49i21.8287.

[31] M. Xu, "YOLO-Based Framework with Temporal Context and Network Analysis for Real-Time Basketball Video Understanding," Informatica, vol. 49, no. 27, pp. 173–184, 2025, doi: 10.31449/inf.v49i27.8657.

ELRP: A Trust and IDS-Integrated Opportunistic Routing Protocol for MANETs with NS2-Based Evaluation

Jidong Zhang
School of Information Engineering, Zhengzhou College of Finance and Economics, Zhengzhou 450053, China
E-mail: JD36728001@163.com

Keywords: mobile ad-hoc networks, trust-based routing, opportunistic routing, security, reliability

Received: October 5, 2025

Mobile Ad Hoc Networks (MANETs) are widely used in diverse situations where secure communication and reliability are necessary. MANETs without a centralized infrastructure are prone to various security threats. This paper presents an Enhanced Lightweight Trusted Routing Protocol (ELRP) to ensure secure connectivity and reliability in MANETs. The primary goal of ELRP is to prevent the inclusion of malicious hosts in the route and reliably convey data. Trust metrics provide secure communication by leveraging quality of service parameters to optimize trust computation. Opportunistic routing enhances data reliability and consistency. It allows each node to choose an intermediate node dynamically based on trust levels. Depending on the trust factor, ELRP enables nodes to select the forwarder at runtime. ELRP features an Intrusion Detection System (IDS) designed to recognize and mitigate black and grey hole attacks. ELRP is scalable as it uses local information and does not consume computational resources. Simulations conducted in NS2 demonstrate that ELRP improves throughput by approximately 22%, increases packet delivery ratio by 14.4%, and reduces end-to-end delay by 37.1% compared to standard AODV under malicious attack scenarios.

Povzetek: Predlagan je varen in učinkovit usmerjevalni protokol, ki izboljša zanesljivost komunikacije in odpornost na napade v primerjavi s klasičnimi pristopi.

1 Introduction

Mobile Ad Hoc Networks (MANETs) play a significant role in delivering communication in an environment where traditional infrastructure is either impossible or impractical to coexist [1]. These networks are composed of portable nodes that are connected using wireless technology and operate without fixed infrastructure. This renders the networks extremely portable and practical in various situations, such as military operations [2], disaster response [3], and vehicle networks [4]. The basic nature of MANETs, including fluctuating network formations, limited data transmission capabilities, and the absence of a centralized command system, creates significant challenges, particularly in ensuring safe and reliable communication [5]. Comparable context-aware and adaptive decision-making structures have been studied in recent intelligent transportation research, for instance, the traffic-conscious pedestrian intention prediction model that combines spatio-temporal learning with the dynamics of traffic signal states to enhance behavioral reliability in autonomous environments [6].

MANETs are highly susceptible to various threats, highlighting the security importance. Malicious nodes can easily join the network and disrupt communication by performing black and grey hole attacks. Black and grey hole attacks involve the dropping or selective forwarding of packets, which ultimately compromise the integrity and efficiency of the network in the long run [7]. Conventional routing mechanisms, such as the Ad Hoc On-demand Distance Vector (AODV), are ineffective at identifying or mitigating these threats, resulting in network vulnerabilities [8].

To address these security issues, the current study proposes an Enhanced Lightweight Trust-based Routing Protocol (ELRP). ELRP's primary objective is to enhance the security and reliability of the MANET by eliminating the contribution of malicious nodes to the routing process and ensuring end-to-end data transmission. ELRP applies the extracted trust measures from the Quality of Service (QoS) factors to ease the selection of secure and mobile routes. ELRP enables opportunistic routing, allowing nodes to dynamically change intermediate nodes based on the level of trust, resulting in higher dependability and consistency of the transmitted data.

A unique aspect of ELRP lies in its built-in Intrusion Detection System (IDS), developed to identify and neutralize black and grey-hole attacks. It has an IDS to observe network traffic, allowing it to identify unusual activities and quarantine malicious nodes. This ensures network protection against typical security threats. ELRP is also designed to be easily customizable and resource-efficient. It determines routes based on local information, minimizes computation, and makes it applicable in environments where resources are limited.

The performance of ELRP is evaluated by comparing it with the popular AODV protocol with respect to key metrics such as throughput, delay, packet delivery ratio, and packet loss ratio. Simulation results indicate that ELRP significantly improves the safe and reliable routing

of networks, particularly in the MANET case. This work addresses the security issues inherent to networks of this type. It addresses the following two major research questions:

- Can trust metrics derived solely from local and one-hop observations improve routing reliability and security in MANETs under the presence of malicious nodes?
- Can an integrated lightweight IDS effectively detect and mitigate black-hole and grey-hole attacks without imposing significant computational or communication overhead?

2 Related work

Various routing schemes proposed are presented in Table 1 for enhancing the security and reliability of MANETs. The AODV routing protocol is widely utilized due to its efficiency and simplicity. Despite this fact, it is prone to a large number of security threats because it lacks a robust mechanism for detecting and removing malicious nodes. These vulnerabilities have been addressed through trust-based routing protocols. By evaluating trust metrics, these protocols enhance the security of communication between nodes. However, many existing trust-based protocols demand considerable computational power and are not suited to resource-constrained environments.

Srilakshmi, et al. [9] suggested a novel routing algorithm for MANETs that emphasizes trust, security, and energy efficiency. Their method uses the Bacteria Foraging Optimization Algorithm (BFOA) to identify optimal routes for data transmission. The first step is to use a fuzzy clustering algorithm. This algorithm groups nodes based on various trust indicators, namely direct trust, indirect trust, and current trust. Based on these trust values, cluster head nodes are selected to lead their respective clusters. In addition, value nodes that are considered trustworthy for data transfer are identified in each cluster. Cluster heads handle multi-hop routing, where data packets are forwarded across multiple nodes to reach their destination. A prediction protocol is used to select the most suitable routes. This protocol takes into account factors such as latency, throughput, and connection strength within the routing path boundaries. The proposed algorithm shows significant improvements compared to existing methods, even without causing malicious attacks. Additionally, it has an 83% detection rate in identifying malicious activities.

Mahamune and Chandane [10] introduced two novel trust-based routing schemes to enhance security and communication efficiency in MANETs. These schemes, named Trust-based Co-operative Routing (TCOR) and Trust-based Self-Detection Routing (TSDR), are implemented under the AODV routing protocol. The developed systems address multiple security issues. TSDR and TCOR are designed to successfully identify malicious hosts and maintain disruption of network operations. Both schemes define mechanisms for evaluating the trustworthiness of individual network nodes successfully. The promised schemes guarantee the secure passing of screened information between nodes, avoid tampering, and ensure the preservation of data integrity. TSDR and TCOR prefer the saving of screened communication paths and network modifications and adaptation to potential security threats. The effectiveness of the schemes is empirically proven by comparison of the performance of the current routing protocols, such as the average AODV protocol, the Generalized Trust Model (GTM), and the Evolutionary Self-Cooperative Trust (ESCT). An extensive simulation procedure was conducted for three different network scenarios, and the proposed schemes were assessed using eight key performance metrics. The results show that both TSDR and TCOR outperform the existing routing protocols in all eight metrics. In particular, TCOR has a higher degree of scalability, making it suitable for large MANETs. Conversely, TSDR's focus on small networks is better suited to smaller MANET applications.

Saravanan, et al. [11] proposed a new routing protocol for MANETs, named the Optimal Cluster Trust Asymmetric Key Management Protocol (OptCH_TAKMP). This protocol aims to strike a balance between security and energy efficiency by combining a group key management mechanism with a complex, cluster-based architecture. OptCH_TAKMP utilizes the Particle Swarm Optimization (PSO) algorithm to achieve two primary objectives. PSO is employed to identify the optimal nodes that are intended to serve as network cluster heads. Network cluster heads manage the exchange of data and serve as the controlling agents of network performance. The PSO algorithm is also used to identify malicious nodes that may compromise the network's operation. This fosters confidence among valid nodes by enabling secure and reliable communications. OptCH_TAKMP employs a distinct mechanism for key management. Two specially designed components generate secret keys for secure communication between nodes, while verifying the authenticity of these keys to prevent unauthorized access and distributing the keys safely to authorized nodes within the network. OptCH_TAKMP demonstrates considerable advancements in terms of calculating the trust error, communication cost, network lifetime, throughput, and energy efficiency when compared to current methods.

Table 1: Comparison of related works

Method	Key features	Advantages	Limitations
Trust-based Routing with BFOA [9]	Uses bacteria foraging optimization algorithm and fuzzy clustering for trust and energy efficiency	High trust and energy efficiency, 83% malicious activity detection	Computationally intensive
TSDR and TCOR [10]	Trust-based self-detection routing and trust-based co-operative routing with AODV	Effective in detecting malicious nodes	TSDR is better for small networks

OptCH_TAKMP [11]	Optimal cluster-trust asymmetric key management protocol using PSO algorithm	High security and energy efficiency, effective key management	Complex cluster management
TAM [12]	Trust and anonymous model emphasizing security and anonymity	Two-tier security, high anonymity, energy-efficient	Complexity in dual identity management
Trustworthy route discovery [13]	Trust evaluation using RSSI and packet ID analysis, multi-layered cuckoo search for cluster head selection	High security, effective cluster head selection	Potential overhead in trust evaluation
RRCC-DAODV [14]	Artificial immune systems-inspired model, V-detector algorithm for attack detection	High detection rate (94%), superior in various performance metrics	Complexity in integrating AIS and energy-based detection

Lakshmi and Vaishnavi [12] introduced a novel routing protocol called Trusted and Anonymous Mechanism (TAM) for MANETs. TAM emphasizes security and efficiency, addressing existing limitations. TAM protects data transfers through a two-stage security solution. The first stage selects reliable nodes for processing routing control messages. The speed at which a node handles these messages determines its trustworthiness. Nodes with higher energy availability are considered more trustworthy because they are less vulnerable to overload or compromise. The second stage focuses on anonymity. During data transfer, the original node identities are obscured. Trusted nodes selected in the first stage forward data packets using temporary dual identities. An advanced mathematical function produces these identities, rendering it very challenging for malicious observers to identify individual nodes that are part of the routing process. Due to the security-minded nature of TAM's design, several performance enhancements have been achieved over previous protocols, including EMBTR (an element-based secure routing protocol for embedded networks) and the power-efficient model of logical power for trusted routing, known as CEMT.

Sankaran and Hong [13] solved the problem of ensuring data transmission security in the context of MANETs by designing a reliable ad-hoc route discovery protocol. This protocol tries to establish a high level of confidence between network nodes. The reliability of neighbors is assessed by employing a two-stage mechanism. First, Received Signal Strength Indicator (RSSI) values are used to evaluate signal quality. Second, trust rates are estimated by analyzing the order of packet IDs stored in neighbor logs. Afterward, the protocol employs a multi-level Cuckoo Search optimization technique to select the best cluster heads.Cluster leaders play a key role in guiding communications within the network. To further enhance the security of data transmission, the protocol selects nodes that are most trustworthy for this leadership role. The efficiency of the protocol is evaluated using several key factors, including throughput, end-to-end delay, routing overhead, packet delivery rate, and energy dissipation.

Gowtham, et al. [14] proposed a novel security model for MANETs inspired by Artificial Immune Systems (AIS). This model uses AIS concepts to classify the behavior of a node on the basis of the Mature Context Immune Antigen Rate (MCIAR). Building on this classification, a new technique called Reliable History-dependent Resource Conscious Clustered and Defensive AODV (RRCC-DAODV) is presented. This protocol aims to locate selfish hosts and mitigate disruptive attacks. The detection in RRCC-DAODV follows a double-fold mechanism. Firstly, the current behavior and reliability of nodes are considered by using the trust value for that particular node. Secondly, the current residue level of the node's energy is taken into consideration because damaged nodes may experience erroneous energy utilization patterns. For further security defense of the system, the DAODV component also applies the V-detector algorithm. This further algorithm further enhances the detection and defense capabilities of the protocol against potential attacks. Simulation outcomes demonstrate a 94% detection rate, confirming the model's effectiveness in identifying selfish nodes. Simulation also showed the prevalence of the model over existing standard protocols. The prevalence occurs in several performance factors, including end-to-end delay, packet delivery ratio, energy consumption, and throughput.

3 Proposed approach

3.1 Trust framework

The proposed system assigns a trust score ($T_A(B)$) to each neighboring node (B) within a node's (A) communication range. This value reflects A's trust in B. To ensure scalability, the trust levels are determined entirely by local information available to A. Formally, $T_A(B)$ refers to the degree of trust A gives to B, with a value ranging from 0 to 1 (0 indicating no trust, 1 indicating complete trust). This trust value is determined by combining two variables (as depicted in Figure 1 and calculated by Eq. 1).

$$T_A(B) = \alpha T_{A(self)}(B) + \beta T_{A(neighbour)}(B) \qquad (1)$$
$$\alpha, \beta \geq 0, \alpha + \beta = 1$$

The direct component $T_{A(self)}(B)$ is computed over a sliding C_Window using local counters already maintained in the neighbor table:




Figure 1: Trust score calculation

$$T_A(B) = \frac{Forwarded\ [A \to B]}{To_Forwarded\ [A \to B] + \varepsilon} \quad (2)$$

Where $\varepsilon > 0$ avoids division by zero. The indirect component aggregates one-hop recommendations received via periodic TRUST packets:

$$T_{A(neighbour)}(B) = \frac{1}{|\mathcal{N}_A \cap \mathcal{N}_B|} \sum_{k \in \mathcal{N}_A \cap \mathcal{N}_B} T_{k(self)}(B) \quad (3)$$

The first component, $T_{A(self)}(B)$, represents *A*'s trust in *B* derived from *A*'s direct observations of *B*'s behavior. The second component, $T_{A(neighbour)}(B)$, signifies the average trust that *A*'s neighbors have in *B*. Since these neighbors share proximity with both *A* and *B*, their combined assessment contributes to the overall trust evaluation. By adjusting the weights (α and β) in Eq. 1, the model allows for varying the relative influence of *A*'s own observations (self-trust) and the trust evaluations of its neighbors. This mechanism effectively incorporates history into the trust assessment, considering current observations and *B*'s past behavior.

Furthermore, our model extends the trust concept beyond individual nodes to encompass routes. Each established route (*r*) is assigned a trust value to facilitate informed route selection decisions. This value enables nodes to evaluate whether a newly discovered route to a destination offers a higher level of trust (and potentially better performance) than an existing route. Intuitively, the trust value of a route reflects its overall reliability. As a route is essentially a sequence of nodes (represented by a_1, a_2, ..., a_m, in which a_i denotes i^{th} node in the list), its trustworthiness hinges on the reliability of all constituent nodes.

To support decentralized trust propagation, ELRP introduces a lightweight control packet named TRUST. Each node periodically broadcasts a TRUST packet to its one-hop neighbors containing the trust values it maintains for them. The packet uses a compact TLV-based format to minimize bandwidth use. The structure is summarized in Table 2.

Table 2. Structure of the TRUST packet

Field	Description	Data type	Size (bytes)
PacketType	Identifies control packet as TRUST (value = 0x07)	uint8	1
Version	Protocol version identifier	uint8	1
SenderID	Unique address of the sending node	uint16	2
SeqNo	Sequence number for duplicate suppression	uint16	2
Timestamp	Local time of packet generation	uint32	4
NumEntries	Number of neighbor entries included	uint8	1
NeighborID [i]	Address of neighbor *i*	uint16 × *n*	2×n
TrustValue[i]	Encoded trust score (0–1, scaled to 8 bits)	uint8 × *n*	1×n
Variance[i] (opt.)	Optional confidence or variance field	uint8 × *n*	1×n
TTL	Time-to-live (restricted to one hop)	uint8	1

Each node rebroadcasts its TRUST packet every 5 seconds using a TTL of 1, limiting dissemination to local neighborhoods. With an average of 10 neighbors per node, this adds roughly 150 bytes every 5 seconds, corresponding to ~0.24 kbps, or less than 5 % additional control traffic relative to AODV. Because ELRP reuses counters already maintained for trust computation, the additional computational and storage cost is negligible. This lightweight design ensures that trust information remains current while maintaining high scalability and minimal overhead.

3.2 Integration with AODV

While our trust estimation strategy is adaptable to various routing protocols, we have integrated it with the AODV protocol for this implementation. Traditionally, AODV prioritizes the selection of the shortest route during path discovery. Our modification alters this behavior to favor routes with higher trust values, enhancing security against malicious attacks. In cases where multiple paths exhibit equivalent trust values, the selection process reverts to prioritizing the route with the fewest nodes.

As illustrated in Figure 2, the source node determines the most trustworthy path through the following steps. Eq. 2 defines the trust value (*Tr(r)*) for a given route (*r*). The origin ultimately picks the path boasting the most trustworthiness. This emphasis on well-trusted routes fosters secure communication and safeguards from threats like black and gray hole attacks.

$$R_r = T_{a1}(a2)T_{a2}(a3)\dots T_{ai-2}(a_{m-1}) = \prod_{i=m}^{m-2} T_{ai}(ai+1) \quad (4)$$

To accommodate the trust estimation scheme within AODV, specific modifications to the data structures are required. The existing neighbor table entries are augmented with five new fields:

- To forward: Indicates the number of packets forwarded by the neighbor.
- Forwarded: Indicates the number of packets received from the neighbor and successfully forwarded.
- Current window (C_Window): Employs a sliding window mechanism for trust value calculations.
- Source list (Sc_List): Maintains a list of source nodes for received packets.
- Neighbor trust (Nb_Trust): Represents the trust value assigned to the specific neighbor.

The route table entries are similarly expanded with a single additional entry: Route trust (Rt_Trust), which stores the calculated trust value for the corresponding route. Trust value fields are also incorporated into Route Request (RREQ) and Route Reply (RREP) packets to propagate trust information across the network.

3.3 Trust value dissemination

One approach to disseminate trust values maintained by individual nodes involves periodic broadcasts. Each node transmits a TRUST packet to its single-hop neighbors,




Figure 2: Trust-based path selection process in the modified AODV protocol

carrying its trust values. This necessitates introducing a new control packet type: the TRUST packet. The initial two fields within the TRUST packet specify the packet type and the number of neighbors for which trust values are conveyed. Additionally, a node periodically calculates the average trust value contributed by its neighbors alongside broadcasting the TRUST packet.

ELRP incorporates a lightweight IDS to identify black-hole and grey-hole behaviors. Each node continually observes its neighbors within the current C_Window and computes a forwarding ratio as follows:

$$F(B) = \frac{N_{fwd}(B)}{N_{exp}(B) + \varepsilon} \quad (5)$$

Where $N_{fwd}(B)$ is the number of packets successfully forwarded by node B and $N_{exp}(B)$ is the number expected during the observation window. A node is considered suspicious when:

$$F(B) < \tau_{IDS} \quad (6)$$

Where τ_{IDS} is an adaptive threshold defined by Eq. 7:

$$\tau_{IDS} = \mu_F - \kappa\sigma_F \quad (7)$$

With μ_F and σ_F representing the network-wide mean and standard deviation of forwarding ratios estimated locally, and κ controlling sensitivity. If a neighbor remains below this threshold for n consecutive windows, its trust value $T_A(B)$ is exponentially decreased:

$$T_A(B) \leftarrow (1 - \lambda)T_A(B) \quad (8)$$

Where $\lambda \in (0,1)$ is the decay factor. Nodes marked as malicious are excluded from subsequent route discovery and are not considered for opportunistic forwarding. This adaptive IDS design ensures that ELRP can distinguish genuine link errors from intentional packet drops while maintaining minimal overhead, since all metrics are derived from local counters already maintained for trust computation.

4 Performance evaluation

4.1 Simulation setup

The simulation experiments were conducted in NS-2 using 15 mobile nodes randomly distributed in an $800 \times 800\ m^2$ area for 900 seconds. Node mobility followed the Random Waypoint model with speeds uniformly distributed between 0 and 15 m/s and zero pause time. Communication used CBR traffic over UDP, with ten randomly selected source–destination pairs transmitting 512-byte packets at 4 packets/s. The wireless configuration employed IEEE 802.11 DCF at 2 Mb/s, a Two-Ray Ground propagation model, an omni-directional antenna with a 250 m range, and a DropTail/PriQueue of length 50.

Both AODV and the proposed ELRP (AODV + trust) were evaluated under two attack scenarios in which 3 (20%) and 5 (33%) nodes behaved maliciously by dropping 100% (black-hole) or 50% (grey-hole) of data packets. Trust values were updated every 2 s within a sliding observation window (C_Window) of 50 packets, and TRUST packets were broadcast every 5 s. All results were averaged over five independent runs using different random seeds (20241–20245). This configuration mirrors prior lightweight trust-based MANET studies and includes all parameters necessary for reproducibility.

4.2 Performance metrics

The simulations assessed the proposed method (ELRP) using four key indicators: throughput, end-to-end delay, Packet Delivery Rate (PDR), and Packet Loss Rate (PLR).




Figure 3: Throughput comparison

Throughput is measured as the total number of packets successfully delivered to the destination divided by the total simulation time, formally defined as:

$$Throughput = \frac{Total\ packets\ delivered}{Total\ simulation\ time} \quad (9)$$

As depicted in Figure 3, ELRP exhibits superior throughput compared to the traditional AODV protocol. This improvement is primarily due to ELRP's ability to dynamically select routes based on trust levels, which minimizes packet loss caused by malicious nodes and ensures more reliable data transmission. By prioritizing trustworthy routes, ELRP enhances the overall network stability and efficiency, leading to a higher throughput compared to AODV.

End-to-end delay is the average time a data packet takes to travel from the source node to the destination across the network, calculated by Eq. The results in Figure 4 demonstrate that our method achieves lower end-to-end delay than AODV. This improvement is primarily due to the trust-based route selection in our method, which ensures that data packets are routed through more reliable and stable paths, reducing the likelihood of packet retransmissions and detours caused by malicious or unreliable nodes. Consequently, the overall time required for packets to reach their destination is minimized, enhancing the efficiency and performance of the network.

$$End-to-end\ delay = \frac{\sum(Packet\ received\ time - Packet\ sent\ time)}{Total\ packets\ received} \quad (10)$$

PDR, a crucial metric for evaluating system quality, signifies the proportion of data packets successfully delivered to the destination, given by Eq. 11.

$$PDR = \frac{Total\ packets\ received}{Total\ packets\ sent} \times 100\% \quad (11)$$




Figure 4: End-to-end delay comparison




Figure 5: PDR comparison

Conversely, PLR represents the percentage of packets dropped during transmission, calculated as follows:

$$PDR = \frac{Total\ packets\ sent - Total\ packets\ received}{Total\ packets\ sent} \times 100\% \quad (12)$$

As shown in Figures 5 and 6, ELRP achieves a significant improvement in PDR and PLR. This enhancement is primarily due to the trust-based routing mechanism, which prioritizes secure and reliable routes, effectively mitigating the impact of malicious nodes and reducing packet loss. By ensuring that data is transmitted through trusted paths, our scheme increases the likelihood of successful packet delivery and minimizes the number of packets dropped during transmission. This dual improvement highlights the scheme's effectiveness in fostering secure and reliable communication within MANETs.

4.3 Discussion

ELRP enhances the performance of MANET in evaluation metrics like throughput, end-to-end delay, PDR, and PLR. ELRP significantly improves these entities, particularly in terms of prime efficiency and reliability indicators of a network. ELRP distinguishes between malicious and trustworthy nodes by dynamically assessing the entities of trust and integrating opportunistic routing techniques. Opportunistic routing strategies are helpful when the network environment and node characteristics are highly dynamic. ELRP responds to such variations by refining the values of trusts and routing channels accordingly, thereby optimizing the security and resilience of the network.




Figure 6: PLR comparison

The superior performance of ELRP compared with the standard AODV routing protocol, particularly in malicious node-based applications, underscores the strong need to incorporate trust concepts and IDS into routing protocols. Although AODV has garnered considerable interest within the research community owing to its simplicity and improved performance, it still lacks security mechanisms, making it susceptible to various attack types. The proposed ELRP method can address these challenges by using trust values to evaluate node performance and opportunistic routing to identify the most trusted and optimal routes dynamically. The addition of an IDS system further enhances reliability.

Such developments render ELRP a stronger and more dependable communication model for MANETs, ensuring secure and reliable data transmission even in highly unpredictable and possibly hostile environments. The fact that the protocol is efficient in tackling primary security flaws while maintaining high performance in key network parameters makes it a promising candidate for MANET applications in the military, emergency services, and vehicular communications systems. ELRP's flexibility and opportunism are most suitable in environments where the network's topological configuration and node behavior are nondeterministic. This ensures that data transmission remains secure and efficient, regardless of the challenges posed by the network operational context.

The adaptational property of ELRP enables it to maintain stable routing even in highly dynamic network environments where node mobility and topological variations are frequent. Like adaptive control schemes for nonlinear control systems, such as adaptive fuzzy control and robust neural adaptive control, ELRP opportunely recalculates the trust measures and optimally updates the next-hop choices as it adapts to network variations. This property enables the protocol to perform optimally, regardless of the unpredictability of link quality or node movement. ELRP's adaptational property, hence, mirrors the self-tuning property of control systems treated in the adaptive backstepping and the robust synchronization schemes [15-17], for the purpose of guaranteeing stable and efficient communications in time-varying, decentralized, and mobile environments.

To further contextualize ELRP’s performance, it is notable that protocols such as TCOR, TSDR, and OptCH_TAKMP also employ trust-based routing mechanisms. However, while these depend on extensive inter-node communications and optimization algorithms that add to processing complexity, ELRP achieves comparable or better reliability with significantly lower computational overhead. This benefit derives from its localized computation of trust and a light-weighted intrusion detection module. Furthermore, future developments of ELRP may leverage adaptive control mechanisms, such as optimal and backstepping control styles. Such mechanisms would permit a dynamically adjustable set of trust thresholds for each node, depending on network feedback observed and the intensity of the attack, thereby enhancing resilience and response latency in highly variable or malicious environments. Because ELRP relies on the periodic refresh of trust using local information, it remains scalable for larger networks, where the computational expense scales linearly with the number of neighbor nodes, but not with the overall network size.

Besides resolving black-hole and grey-hole behaviors, ELRP also demonstrates resilience to additional typical trust-oriented attacks, such as collusion, Sybil, and bad-mouthing attacks. Since the ELRP's trust estimation procedure is based mainly on locally perceived forwarding activity and one-hop indirect recommendations, malicious nodes have limited control over the global distribution of trust. Under conditions of Sybil or bad-mouthing activity, the requirement for direct observation ensures that only nodes with a verifiable history of packet forwarding can obtain or retain high values for trust. Furthermore, the legitimacy of the TRUST broadcasts is ensured through the use of one-hop exchanges embedded in the current AODV control messaging, which can be supported by the addition of link-layer authentication or lightweight cryptographic tags without compromising scalability. Hence, ELRP remains safe for independent and collaborative attempts to manipulate the trust while retaining its lightweight style.

5 Conclusion

MANETs are highly adaptive, plug-and-play wireless networks that are suitable for military purposes, disaster scenarios, rural regions lacking radio infrastructure, and outdoor environments. With highly changeable and variable network structures, security becomes the most problematic aspect, as it is susceptible to attack through eavesdropping, routing mechanisms, and modifications to applications. We introduced ELRP to enhance the reliability and security of the MANET. With the use of a dynamic trust metric and the incorporation of an IDS, ELRP effectively locates malicious nodes and isolates them, ensuring secure and reliable communication. Our NS2 network simulator simulation demonstrated ELRP's superiority over the conventional AODV protocol in key performance measures, including throughput, end-to-end delay, packet delivery ratio, and packet loss rate. This enhancement is particularly significant in the presence of a large number of malicious nodes, underscoring the effectiveness of ELRP in countering security threats.

The success of ELRP in improving MANET security and performance demonstrates its potential and applicability across domains such as military scenarios, disaster recovery networks, and vehicular communications. Nevertheless, several research avenues may be explored in the future to improve and extend related research. For example, applying machine learning concepts and methodologies to forecast and proactively mitigate potential future threats and malicious activities. The degree of flexibility of the developed protocol and its appropriateness across various network sizes and mobility models may also yield critical new perspectives. In any case, ELRP provides an attractive foundation and a potentially fertile area that may facilitate new research and progress in this important and timely field.

References

[1] B. H. Khudayer *et al.*, "A comparative performance evaluation of routing protocols for mobile ad-hoc networks," *International Journal of Advanced Computer Science and Applications,* vol. 14, no. 4, 2023.

[2] S. Al Ajrawi and B. Tran, "Mobile wireless ad-hoc network routing protocols comparison for real-time military application," *Spatial Information Research,* vol. 32, no. 1, pp. 119–129, 2024.

[3] S. Mangasuli and M. Kaluti, "Efficient multimedia content transmission model for disaster management using delay tolerant mobile adhoc networks," *International Journal of Advanced Computer Science and Applications,* vol. 14, no. 1, 2023.

[4] B. Pourghebleh and N. Jafari Navimipour, "Towards efficient data collection mechanisms in the vehicular ad hoc networks," *International Journal of Communication Systems,* vol. 32, no. 5, p. e3893, 2019.

[5] S. Kaisar, J. Kamruzzaman, G. Karmakar, and M. M. Rashid, "Decentralized content sharing in mobile ad-hoc networks: A survey," *Digital Communications and Networks,* vol. 9, no. 6, pp. 1363–1398, 2023.

[6] F. O. Nia and H. Lin, "Traffic-Aware Pedestrian Intention Prediction," in *2025 American Control Conference (ACC)*, 2025: IEEE, pp. 3455–3460, doi: https://doi.org/10.23919/ACC63710.2025.11107953.

[7] S. Li and B. Gong, "Developing a reliable route protocol for mobile self-organization networks," *High-confidence computing,* vol. 4, no. 3, p. 100194, 2024.

[8] C. Bharanidharan, S. Malathi, and H. Manoharan, "Detection of black hole attacks in vehicle-to-vehicle communications using ad hoc networks and on demand protocols," *International Journal of Intelligent Unmanned Systems,* 2024.

[9] U. Srilakshmi, S. A. Alghamdi, V. A. Vuyyuru, N. Veeraiah, and Y. Alotaibi, "A secure optimization routing algorithm for mobile ad hoc networks," *IEEE Access,* vol. 10, pp. 14260–14269, 2022.

[10] A. A. Mahamune and M. Chandane, "Trust-based co-operative routing for secure communication in mobile ad hoc networks," *Digital Communications and Networks,* 2023.

[11] S. Saravanan, D. Prabakar, and S. Sathya, "Trust aware ad hoc routing protocol with key management based mechanism and optimal energy-efficient cluster head selection in mobile ad hoc networks," *Concurrency and Computation: Practice and Experience,* vol. 35, no. 7, p. e7599, 2023.

[12] G. V. Lakshmi and P. Vaishnavi, "A trusted security approach to detect and isolate routing attacks in mobile ad hoc networks," *Journal of Engineering Research,* 2023.

[13] K. S. Sankaran and S.-P. Hong, "Trust Aware Secured Data Transmission Based Routing Strategy Using Optimal Ch Selection in Mobile Ad-Hoc Network," *Mobile Networks and Applications,* pp. 1–13, 2023.

[14] M. Gowtham, M. Vigenesh, and M. Ramkumar, "An artificial immune system-based algorithm for selfish node detection in Mobile Ad Hoc Networks (MANETs)," *Transactions on Emerging Telecommunications Technologies,* vol. 35, no. 2, p. e4938, 2024.

[15] A. Boulkroune, F. Zouari, and A. Boubellouta, "Adaptive fuzzy control for practical fixed-time synchronization of fractional-order chaotic systems," *Journal of Vibration and Control,* p. 10775463251320258, 2025, doi: https://doi.org/10.1177/10775463251320258.

[16] A. Boulkroune, S. Hamel, F. Zouari, A. Boukabou, and A. Ibeas, "Output-Feedback Controller Based Projective Lag-Synchronization of Uncertain Chaotic Systems in the Presence of Input Nonlinearities," *Mathematical Problems in Engineering,* vol. 2017, no. 1, p. 8045803, 2017, doi: https://doi.org/10.1155/2017/8045803.

[17] G. Rigatos, M. Abbaszadeh, B. Sari, P. Siano, G. Cuccurullo, and F. Zouari, "Nonlinear optimal control for a gas compressor driven by an induction motor," *Results in Control and Optimization,* vol. 11, p. 100226, 2023, doi: https://doi.org/10.1016/j.rico.2023.100226.

Static Malware Detection through Ensemble Feature Selection and Supervised Classification

Isai Moreno-Lara, Alejandra Guadalupe Silva-Trujillo*, Juan C. Cuevas-Tello, Jose Nunez-Varela
Facultad de Ingeniería, Universidad Autónoma de San Luis Potosí, San Luis Potosí, Mexico
E-mail: isai.lara.dev@gmail.com, asilva@uaslp.mx, cuevas@uaslp.mx, jose.nunez@uaslp.mx
*Corresponding author

Keywords: Malware, classification, machine learning, cybersecurity, algorithms

Received: August 7, 2025

In a digital landscape where malicious software evolves faster than traditional defenses, intelligent and proactive detection has become essential. This study presents a machine learning framework for static malware detection based on the analysis of 138,047 Portable Executable samples, including both malware and benign files. The dataset comprises 56 static structural features extracted without code execution. Four supervised classifiers—Backpropagation Neural Network, Decision Tree, Random Forest, and Support Vector Machine—were evaluated following the Knowledge Discovery in Databases process. Ensemble-based feature selection methods (Random Forest and Extra Trees) were applied to identify the most informative attributes, while random undersampling was used to mitigate class imbalance. Experimental results show that the Random Forest classifier achieved the best performance, reaching 99.45% accuracy and a 0.9909 F1-score on imbalanced data, and 99.32% accuracy on the balanced dataset. These findings highlight the reliability and scalability of tree-based models for static malware detection. Overall, the proposed framework demonstrates that careful feature selection and balance adjustment can significantly enhance the performance and interpretability of cybersecurity classification systems.

Povzetek: Študija predstavi statično zaznavanje zlonamerne programske opreme iz 56 značilk PE datotek na velikem naboru vzorcev, kjer z izbiro značilk z ansambli in uravnoteženjem razredov pokaže, da drevesni modeli ponujajo zanesljivo in razložljivo detekcijo.

1 Introduction

In today's hyperconnected world, malware poses a persistent threat to individuals, organizations, and even critical infrastructure. Malware, a contraction of 'malicious software', encompasses any software developed with the intent to harm, exploit, or otherwise compromise computers, networks, or users. The U.S. National Institute of Standards and Technology (NIST) defines malware as a program inserted into a system with the aim of compromising the confidentiality, integrity, or availability of the system's data or operations [1]. This broad category includes viruses, worms, trojans, ransomware, spyware, and more sophisticated threats that constantly evolve to evade traditional security systems.

The increasing digitalization of services and the dependency on connected systems have increased the risks posed by malware attacks. These attacks can result in massive financial losses, data breaches, reputational damage, or even disruptions to critical infrastructure. Global statistics from cybersecurity firms show an upward trend in malware activity across sectors, with new variants being generated using automated tools and code obfuscation techniques, making manual detection approaches increasingly infeasible [2].

To address this growing threat, machine learning (ML) has emerged as a powerful tool for malware detection. Unlike signature-based methods that rely on predefined rules and known patterns, ML algorithms can learn from past data to identify new, previously unseen malware by recognizing subtle structural or behavioral indicators. This data-driven approach allows for improved generalization, early threat detection, and reduced reliance on expert-crafted features.

Malware detection techniques are broadly categorized into three types: **static analysis**, **dynamic analysis**, and **hybrid analysis** [3]. Static analysis involves examining the structure, code, and metadata of a program without executing it. Common static features include Application Programming Interface (API) call sequences, opcode frequency, string patterns, and control flow graphs elements that can be extracted safely and efficiently at scale. In contrast, dynamic analysis executes the malware in a sandbox or controlled environment to observe its runtime behavior, such as system calls, registry changes, or network activity. While dynamic techniques are more resilient to obfuscation and capable of detecting zero-day threats, they are time-consuming and resource-intensive, and can be bypassed by malware that detects virtualized environments. Finally, hybrid analysis combines static and dynamic methods to benefit from both perspectives. However, it inherits the limitations of both and often increases computational cost.

In this study, we have adopted a **static analysis** approach. This decision is driven by the nature of our dataset and practical constraints. Static analysis allows fast, large-scale inspection of software without the overhead or risk of execution. Since our dataset includes pre-extracted structural features from known samples, static analysis is both appropriate and scalable for building machine learning models.

Consequently, we reinforce the notion that the union of machine learning and cybersecurity, when guided by principled data science methodologies, has the potential to produce intelligent, adaptive, and ethically sound tools for modern malware detection. By demonstrating the effectiveness of well-calibrated models under different experimental conditions, this work contributes to the ongoing development of secure, data-driven defense mechanisms capable of facing the challenges of an increasingly hostile digital ecosystem. Moreover, this work investigates how class balance and feature selection strategies influence the performance and interpretability of supervised machine learning models for malware detection. These aspects are critical, as imbalanced datasets can bias classifiers toward the majority class, while inadequate feature selection may introduce redundancy or noise that reduces generalization. The study systematically evaluates these factors within the Knowledge Discovery in Databases (KDD) process, using both balanced and unbalanced datasets, and compares models through metrics such as precision, recall, F1-score and Area Under the Curve (AUC). This approach aims to identify the conditions that yield the most robust and explainable detection results.

This paper is structured as follows. Section 2 introduces the Knowledge Discovery in Databases process and explains its relevance in malware detection. The state of the art is presented in Section 3 to contextualize this study within existing research. Section 4 describes the dataset in detail, including the class distribution and a statistical analysis of the feature values. The preprocessing steps are then outlined in Section 5, with particular emphasis on the class balancing strategy through undersampling, which resulted in two versions of the dataset. Section 6 addresses the transformation stage, detailing the feature selection algorithms applied. The data mining phase is described in Section 7, including the classification models used and the configuration of their respective hyperparameters. Section 8 presents the results of the evaluation metrics and reports the performance of the models under both original and balanced datasets, followed by an interpretation of the outcomes. Finally, Section 10 concludes with a summary of the key findings and suggestions for future research.

2 Knowledge discovery in databases (KDD) Process

To build an effective malware detection system, we follow the KDD process — a systematic methodology for extracting meaningful patterns from large datasets. As defined by Fayyad et al. [4], KDD is "the nontrivial process of identifying valid, novel, potentially useful, and ultimately understandable patterns in data". This methodology is especially important when the volume and complexity of data exceed human capacity for manual analysis.

In cybersecurity contexts such as malware detection, datasets are often high-dimensional and voluminous, making manual exploration of correlations and anomalies infeasible. KDD provides a structured framework that integrates not only data mining algorithms, but also essential steps such as data selection, preprocessing, transformation, and interpretation. Moreover, blindly applying data mining techniques — commonly referred to as *data dredging* — can lead to misleading conclusions. The KDD process mitigates this risk through iterative refinement, incorporation of prior knowledge, and user-guided evaluation. In our study, the KDD process structures the full pipeline, from analyzing static malware attributes and selecting the most informative features, to evaluating classification performance across balanced and imbalanced scenarios. This process includes the following stages:

- **Data Selection:** Involves choosing the subset of data relevant to the problem domain from potentially large and heterogeneous sources.
- **Preprocessing:** Selected data is cleaned and transformed to improve its quality and consistency. Tasks include removing noise, handling missing values, converting data formats, and normalizing features.
- **Feature Selection:** Reduces the number of input variables by selecting only the most relevant features for the task. It helps to improve model performance, reduce overfitting, and enhance interpretability by eliminating redundant or irrelevant attributes.
- **Feature Comparison:** Selected features are analyzed to understand their properties to identify correlations, redundancies, or informative patterns that may influence model outcomes.
- **Data Mining:** Algorithms are applied to extract patterns or models from data. Techniques may include classification, regression, clustering, or association rule mining, depending on the objective of the study.
- **Evaluation:** Assessment of the quality and usefulness of the knowledge discovered using performance metrics or validation techniques.

The core task in this study is formulated as a **binary classification problem**, where each software instance is labeled either as `malware` or `benign`. To solve this, we employ and compare the following machine learning algorithms: Backpropagation Neural Networks, Decision Trees, Random Forests, and Support Vector Machines. Each model is trained and evaluated using the same dataset and preprocessing pipeline. The overall workflow is illustrated in Figure 1, summarizing the steps from data acquisition to classification.




Figure 1: General workflow for malware detection using ML and the KDD process.

3 State of the art

Malware detection remains a core challenge in modern cybersecurity due to the rapid increase in novel attack variants and the evolving sophistication of evasion techniques. Traditional defenses struggle to keep pace with the speed and diversity of malware generation, especially in mobile and Internet of Things (IoT) ecosystems, where constraints on resources and real-time protection demand more intelligent and scalable approaches.

Recent research has focused on leveraging ML techniques to improve malware detection through both static and dynamic analysis. One of the most influential studies in this area is that of Shakib et al. [5], who introduced a benchmark dataset widely adopted for evaluating hybrid models that combine Genetic Artificial Intelligence, deep neural architectures, and Active Learning (AL). Their experiments achieved near-perfect accuracy levels above 99%, demonstrating the effectiveness of deep learning architectures for malware detection. However, their work primarily emphasized performance metrics such as accuracy and F1-score, without addressing potential class imbalance or feature redundancy issues that could affect generalization.

Building on this line of research, Tanuwidjaja and Kim [6] proposed an adaptation of the Deep Feature Extraction and Selection (DFES) method originally designed for intrusion detection. Their approach integrates Stacked Autoencoders (SAE) for deep abstraction, Weighted Feature Selection, and Artificial Neural Networks (ANN), resulting in a lightweight yet highly accurate pipeline. By focusing on dimensionality reduction and feature relevance, this study highlighted the importance of feature selection as a key factor in improving efficiency and performance in malware classification.

Complementing these works, Roy [7] investigated the detection of encrypted malware traffic, comparing Logistic Regression, Convolutional Neural Networks, and Random Forests. Despite the additional challenge of encryption, Random Forest achieved the highest accuracy (98.28%), reinforcing the robustness of tree-based models in constrained and obfuscated environments. Similarly, Baker del Aguila et al. [8] examined lightweight static analysis techniques under limited computational resources. Their findings showed that Artificial Neural Networks reached 94.74% accuracy, followed closely by Support Vector Machines and Gradient Boosting Machines, proving that traditional ML models can remain competitive in memory-restricted scenarios.

Overall, these studies illustrate the progressive refinement of malware detection methods, from complex hybrid architectures to efficient lightweight models. Nevertheless, most prior works—such as those by Shakib et al. [5], Tanuwidjaja and Kim [6] and Roy [7]—focused primarily on achieving high accuracy and F1-scores, while overlooking important aspects like dataset imbalance, feature redundancy, or model interpretability.

Addressing these gaps, the present study systematically evaluates the influence of class balance and feature selection strategies within the Knowledge Discovery in Databases process, aiming to provide more reliable and explainable results.

Table 1 summarizes the classification performance reported in recent malware detection studies. Each study employed different ML models and evaluation strategies, yet most relied primarily on accuracy as the main performance indicator. Although each study refers to the dataset differently, all of them were conducted using the same underlying dataset, which contains both benign and malicious program samples. To provide a more complete comparison, the table includes not only accuracy but also F1-score and loss values when available. Further details comparing these results with those obtained in the present study are discussed in Section 9.

4 Dataset

This study relies on a benchmark dataset comprising 138,047 labeled software samples, including 96,724 identified as malware and 41,323 as legitimate. Each instance is represented by 56 static features that encapsulate structural metadata and header-related attributes, extracted without executing the software binaries. This static approach enables scalable and reproducible analyses, particularly suitable for pre-execution detection pipelines. To ensure methodological consistency, the same dataset used in the studies listed in Table 1 was adopted in this work. This dataset was originally derived from *VirusShare* repository [9], which provides publicly available malware samples used for academic and security research.

Originally distributed in Comma-Separated Values (CSV) format — a widely accepted standard for structured data representation. For analytical processing, the dataset was loaded into a Pandas DataFrame [10], a powerful tabular data structure within the Python ecosystem that provides extensive functionality for data transformation, filtering, and statistical computation.

A preliminary structural inspection revealed that two

Table 1: Comparison of evaluation metrics achieved by different machine learning models in malware detection studies.

Ref.	Model / Approach	Accuracy (%)	F1-score	Loss
[5]	Convolutional Neural Network	99.94	0.9993	0.007
	Recurrent Neural Network	99.55	0.9954	0.026
	Long Short-Term Memory Network	77.66	0.8094	0.483
	Gated Recurrent Unit Network	81.05	0.8050	0.422
	Active Learning with Convolutional Neural Network	99.93	0.9961	0.006
	Active Learning with Recurrent Neural Network	99.89	0.9989	0.001
	Active Learning with Long Short-Term Memory Network	86.59	0.8673	0.325
	Active Learning with Gated Recurrent Unit Network	94.01	0.9402	0.175
	Genetic Artificial Intelligence with Convolutional Neural Network	95.93	0.9589	0.149
	Genetic Artificial Intelligence with Recurrent Neural Network	99.36	0.9935	0.055
	Genetic Artificial Intelligence with Long Short-Term Memory Network	99.27	0.9925	0.037
	Genetic Artificial Intelligence with Gated Recurrent Unit Network	99.77	0.9977	0.019
[6]	Original Deep Abstraction and Weighted Feature Selection with Stacked Autoencoder and Artificial Neural Network	99.917	0.9986	-
	Modified Deep Abstraction and Weighted Feature Selection with Stacked Autoencoder and Artificial Neural Network (reduced feature set)	99.974	0.9996	-
[7]	Random Forest	98.28	-	-
	Logistic Regression	70.15	-	-
	Convolutional Neural Network	97.00	-	-
[8]	Artificial Neural Network	94.74	0.94	0.1488
	Support Vector Machine	91.07	0.92	0.239
	Gradient Boosting Machine	92.47	0.91	0.04

features—`Name` and `md5`—served as unique identifiers and did not contribute meaningful semantic information for classification purposes. Therefore, these fields were excluded from subsequent analyses. After this refinement, the dataset contained a total of 55 columns: 54 informative features and one target class. All variables exhibited a consistent and well-defined schema, with 45 stored as 64-bit integers (`int64`) and 10 as 64-bit floating-point numbers (`float64`). Figure 2 illustrates the distribution of data types across the dataset after discarding the non-informative identifiers.




Figure 2: Distribution of data types in the dataset (excluding Name and md5)

To better understand the behavior and statistical profile of each feature across classes, descriptive metrics were computed independently for the malware and legitimate samples. These metrics include the minimum and maximum observed values, arithmetic mean, standard deviation, and interquartile range boundaries (Q1 and Q3). To enhance the readability and interpretability of the results, a formatting scheme was applied according to the magnitude of the values. Specifically, large numerical values were converted into more compact representations using metric suffixes (e.g., “K” for thousands, “M” for millions) or expressed in scientific notation for extremely large magnitudes. This transformation not only reduces visual clutter in the tables but also enables more efficient cross-feature comparisons across varying scales. Tables 6 and 7 (see Appendix) present these adapted statistics, highlighting relevant distributional characteristics that may differentiate benign and malicious instances. For example, features related to section entropy, import table sizes, or memory allocation regions often show marked discrepancies between classes, revealing potential signals for classification models.

Following the computation of descriptive statistics, the features of the dataset were systematically grouped according to their functional roles within the structure of Portable Executable (PE) files. This categorization serves a dual purpose: it not only enhances interpretability by organizing features into coherent blocks—such as file headers, section properties, import/export statistics, and resource descriptors—but also facilitates the identification of feature types that may be particularly informative for static malware detection. Grouping features in this manner supports the modeling process by allowing the analysis to reflect the underlying structure of PE files, which in turn can capture relevant patterns associated with malicious or benign behavior.

During this process, attributes deemed non-informative for the learning task—specifically `Name`, which serves only as an identifier; `md5`, a cryptographic hash used to reference each sample; and legitimate, the binary classification label—were excluded from the feature grouping to maintain clarity and focus on predictive variables. These excluded elements were nonetheless preserved in the dataset for tracking and evaluation purposes. Table 5 (see Appendix) provides a comprehensive summary of the grouped features retained for modeling, including concise descriptions of their technical significance. This structural organization aids both in the interpretability of the dataset and in the development of models that leverage domain-relevant features.

While static-analysis enables large-scale and reproducible experimentation, it inherently captures only structural characteristics of executables. The dynamic behaviors of malware—such as obfuscation or runtime evasion—remain beyond the scope of this dataset and are discussed further in Section 10.

5 Preprocessing

Following the workflow in Figure 1, the dataset underwent basic integrity checks to ensure its suitability for further processing. A systematic search confirmed the absence of missing (null) values and duplicate entries across all features. Additionally, two attributes—`Name` and `md5`—were removed from the dataset. These fields acted solely as unique identifiers and did not carry any semantic or statistical value relevant to the classification task. Their exclusion prevents potential information leakage and ensures that the model focuses exclusively on meaningful predictive features. These validations, while straightforward, are essential for preventing bias and ensuring that the subsequent modeling process is both reliable and reproducible. According to Sharifnia et al. [11], overlooking issues such as missing or inconsistent data can significantly compromise data quality, resulting in biased parameter estimates and misleading conclusions.

A class distribution analysis was then conducted to assess the balance between legitimate and malicious files. The results revealed a significant imbalance: out of a total of **138,047** samples, **96,724** were labeled as *malware* and only **41,323** as *benign*, corresponding to approximately **70.1%** and **29.9%** of the dataset, respectively. This imbalance poses a risk of biasing classifiers toward the majority class, reducing their ability to detect minority patterns accurately.

To address this, a random undersampling technique was applied to reduce the number of malware samples. After undersampling, both classes contained **41,323** samples, resulting in a balanced dataset of **82,646** instances. Despite this reduction, the dataset remains sufficiently large to support meaningful statistical inference and robust model training. This strategy is supported by recent research, which highlights that undersampling can reduce class overlap and enhance minority class visibility, especially when the majority class includes redundant or less informative samples [12]. Additionally, it improves training efficiency and can lead to more balanced decision boundaries, particularly in domains where minority class detection is critical, such as malware analysis.

To assess the effect of this resampling technique, both the original imbalanced dataset and the balanced version were retained for comparative modeling and evaluation. Figure 3 illustrates the class distributions before and after the undersampling process.




Figure 3: Class distribution before and after applying undersampling

6 Transformation

Dimensionality reduction techniques are essential in machine learning to address the challenges posed by high-dimensional data, often referred to as the "curse of dimensionality" [13, 14]. These techniques aim to reduce the number of input variables while preserving as much relevant information as possible, thereby enhancing model performance and interpretability. Common methods include:

- **Principal Component Analysis (PCA):** A linear technique that transforms the original variables into a new set of uncorrelated variables (principal components), ordered by the amount of variance they capture in the data.
- **Linear Discriminant Analysis (LDA):** A supervised method that seeks linear combinations of features that best separate two or more classes, maximizing class separability.
- **Tree-based methods:** Algorithms like Random Forest and Extra Trees assess feature importance based on their contribution to decision splits, effectively selecting the most informative features for classification tasks. Selecting the most informative features for classification tasks.

These methods not only reduce computational complexity but also help in mitigating overfitting and improving the generalization capability of models.

In this study, two ensemble-based methods were used to evaluate the relevance of each attribute: Random Forest Classifier and Extra Trees Classifier, both configured

with n_estimators=50 and default parameters as per the scikit-learn implementation [15]. These tree-based models compute feature importance based on the contribution of each attribute to the split decisions across trees. While Random Forests use optimized splits, Extra Trees introduce greater randomness by choosing thresholds at random, which can reduce overfitting and variance in high-dimensional contexts. Both models were independently trained on the original (imbalanced) dataset and the balanced version. The goal was to compare the stability and consistency of the selected attributes under varying class distributions. In each case, 14 features were automatically selected using the SelectFromModel method which are presented in Table 2 for comparison.

Table 2: Features selected by extra trees and random forest classifiers

Extra Trees Classifier	Random Forest Classifier
Machine	Characteristics
SizeOfOptionalHeader	BaseOfData
Characteristics	ImageBase
ImageBase	MajorOperatingSystemVersion
MajorOperatingSystemVersion	MinorImageVersion
MajorSubsystemVersion	Subsystem
Subsystem	DllCharacteristics
DllCharacteristics	SizeOfStackReserve
SizeOfStackReserve	SectionsMaxEntropy
SectionsMinEntropy	ExportNb
SectionsMaxEntropy	ResourcesNb
ResourcesMinEntropy	ResourcesMinEntropy
ResourcesMaxEntropy	ResourcesMinSize
VersionInformationSize	VersionInformationSize

A comparison of the selected features reveals that both models share 9 common attributes, including Subsystem, DllCharacteristics, and VersionInformationSize. These overlapping features suggest that both methods consistently identify them as informative for distinguishing between legitimate and malicious files. However, each classifier also selected 5 distinct features. Extra Trees included attributes such as Machine and SizeOfOptionalHeader, which showed strong positive correlations with the target, while Random Forest selected attributes like BaseOfData and ExportNb, which exhibited lower individual correlation but may provide complementary decision information. This divergence highlights how different ensemble strategies can lead to feature sets with varying levels of redundancy, diversity, and interpretability.

To further analyze the relationship between the selected attributes and the target variable, correlation matrices were computed to measure the linear association between each feature and the legitimate label. As shown in Figures 11 and 12, see Appendix, features selected by the Extra Trees Classifier exhibit generally stronger absolute correlations with the target, notably Machine and SizeOfOptionalHeader (both $r = 0.55$), and Subsystem ($r = 0.51$). Additionally, negatively correlated features such as DllCharacteristics ($r = -0.63$) and SectionsMaxEntropy ($r = -0.62$) show clear discriminatory power.

In contrast, features selected by the Random Forest Classifier display weaker overall correlations with the target variable, although some attributes like Subsystem ($r = 0.51$), DllCharacteristics ($r = -0.63$), and VersionInformationSize ($r = 0.38$) still demonstrate meaningful relationships. This suggests that Extra Trees may have prioritized features with higher individual predictive strength, while Random Forest may have selected a more diverse feature set with complementary interactions not solely captured by linear correlation.

Finally, four distinct experimental setups were constructed to evaluate model performance under different conditions:

1. Original dataset + features selected by Extra Trees
2. Original dataset + features selected by Random Forest
3. Balanced dataset + features selected by Extra Trees
4. Balanced dataset + features selected by Random Forest

Each experimental setup was evaluated using two different train-test split configurations: one with 80% of the data used for training and 20% for testing, and another with an equal split of 50% for training and 50% for testing. This dual evaluation strategy enables the assessment of each model's robustness, generalization capability, and sensitivity to the amount of training data available. The inclusion of a 50/50 split allows us to examine model performance under limited training data conditions, which is particularly relevant in real-world scenarios where labeled samples may be scarce. Together, these experimental variations enable a comparative analysis of how feature selection strategies, class distribution, and training size interact to influence classifier performance, interpretability, and computational cost.

7 Data mining

Data mining has emerged as a vital component in malware detection due to its ability to uncover hidden patterns and generalize from labeled examples, going beyond the limitations of traditional signature-based techniques. As highlighted by Souri and Hosseini [16], the integration of data mining with machine learning enables robust classification mechanisms that can detect both known and previously unseen malware threats.

In this study, we apply data mining techniques to perform supervised classification of static malware attributes. The selected algorithms—Backpropagation Neural Network (BPNN), Decision Tree, Random Forest, and Support Vector Machine—are widely established in the literature for their effectiveness in modeling diverse decision boundaries while balancing predictive performance with interpretability.

The following subsections detail the implementation and theoretical background of each algorithm used in this work.

7.1 Backpropagation neural network (BPNN)

BPNN are fundamental due to their ability to model complex, nonlinear relationships by automatically learning hierarchical feature representations from raw data [17]. BPNN is a type of supervised learning model based on artificial neural networks, composed of an input layer, one or more hidden layers, and an output layer [17]. Each neuron in a given layer is fully connected to all neurons in the subsequent layer, and these connections are associated with weights that determine the strength and direction of influence between neurons. Weights and biases are the core trainable parameters of the network and are adjusted during training to reduce prediction error.

The training process in BPNN consists of two main phases: forward propagation and backpropagation. During forward propagation, input data is passed through the network layer by layer to produce an output. The network's error is then calculated by comparing this output to the expected target. In the backward pass, the error is propagated backward through the network to compute gradients for each weight, using the chain rule of calculus. These gradients are then used to update the weights in a way that minimizes the loss function. This process is repeated for several iterations or epochs until convergence is achieved [17].

Figure 4 illustrates the general architecture of the BPNN implemented in this study. While each hidden layer in the actual model consists of 128 neurons, the figure provides a simplified visualization using ellipses to indicate additional units. The network receives an input vector of length n, processes it through two fully connected hidden layers, and produces a single binary output via a sigmoid-activated neuron.




Figure 4: Simplified architecture of the BPNN.

In this study, we implemented a fully connected feed-forward BPNN using the `Keras` API with `TensorFlow` as the backend. The architecture consisted of two hidden layers, each with 128 neurons and ReLU activation functions (`activation="relu"`), and an output layer with a single neuron and a sigmoid activation function (`activation="sigmoid"`) for binary classification. The model was compiled using the Adam optimizer with a learning rate of 10^{-3} (`learning_rate=1e-3`) and the binary cross-entropy loss function (`loss="binary_crossentropy"`). Binary accuracy (`metrics=["BinaryAccuracy"]`) was used as the evaluation metric. All other hyperparameters were kept at their default values.

7.2 Decision tree (DT)

DT are simple, interpretable models that construct tree structures by recursively splitting the dataset based on feature values. While easy to understand and implement, their performance can degrade in high-variance or noisy environments due to overfitting [18]. DT is a supervised learning algorithm that recursively partitions the instance space using a rooted and directed tree structure, where each internal node performs a test on an input attribute, and each leaf node represents a decision outcome or a probability distribution over target classes [19]. This top-down approach, also known as recursive partitioning or "divide and conquer", results in a hierarchical model that is both interpretable and easy to visualize. In each step of the tree construction, the algorithm selects the attribute and corresponding split point that maximize a given splitting criterion—typically the information gain, Gini index, or reduction in variance—depending on the nature of the task (classification or regression).

The algorithm proceeds until a stopping criterion is met, such as reaching a maximum tree depth, a minimum number of samples per node, or the absence of further information gain. Each path from the root to a leaf node can be interpreted as a decision rule, which enables rule-based reasoning and transparent decision-making. In fact, each internal node acts as a conditional `if` statement, and each branch corresponds to a possible outcome (`else`), making the entire path a sequence of nested `if-else` conditions. This logic-based structure is visually illustrated in Figure 5, where each decision node leads to a branch representing a binary condition and eventually a classification output. Each branch reflects a conditional rule, and leaves represent final decisions.




Figure 5: General structure of a binary DT.

In this study, we employed the `scikit-learn` implementation of DTs [15], which is based on the CART algorithm (Classification and Regression Trees), originally introduced by Breiman et al. (as summarized in [19]). Unlike other tree algorithms such as ID3 or C4.5, CART constructs strictly binary trees and supports both classification and regression tasks by using the Gini impurity and mean squared error as default criteria, respectively. In our configuration, the DT was initialized with a maximum depth of 10




Figure 6: Simplified representation of a RF.

(`max_depth=10`) to control model complexity and reduce the risk of overfitting, while the remaining hyperparameters were left at their default values.

7.3 Random forest (RF)

RF address the limitation of DT by aggregating the predictions of multiple decision trees trained on random subsets of the data, leading to improved accuracy, reduced variance, and robustness across diverse data distributions [18]. Therefore, RF is a widely used ensemble learning method designed to improve the performance and robustness of decision tree classifiers by combining the predictions of multiple trees into a single output. RF was proposed by Leo Breiman and Adele Cutler and is considered an extension of the bagging method [20]. The core idea behind RF is to build a large collection of de-correlated decision trees and aggregate their outputs, using majority voting for classification or averaging for regression.

The algorithm constructs each tree using a bootstrap sample of the training data (sampling with replacement), and at each split, it selects the best feature from a randomly chosen subset of features—rather than considering all features as in a traditional decision tree. This dual randomness, in both data and feature selection, introduces diversity among the trees, which reduces overfitting and improves generalization performance. The underlying decision trees are typically trained using the CART algorithm, which employs criteria such as Gini impurity or mean squared error to determine optimal splits [20].

Figure 6 shows a simplified representation of a RF. Each tree in the ensemble produces its own prediction based on different subsets of data and features. Multiple decision trees are trained independently, and their predictions are aggregated through a majority voting mechanism (for classification), illustrated by the green node labeled *Voting*, which determines the final output of the model.

In this study, we used the `scikit-learn` implementation of RF [15], configuring the model with 100 trees (`n_estimators=100`) and a fixed random seed (`random_state=42`) to ensure reproducibility. All other hyperparameters were left at their default values.

7.4 Support vector machine (SVM)

SVM is a supervised learning algorithm that aims to find the optimal hyperplane that separates data points of different classes in an N-dimensional space [21]. This hyperplane is chosen to maximize the margin, defined as the distance between the closest points (support vectors) of opposing classes. The idea is to achieve the most generalizable separation between classes, reducing the risk of overfitting and improving performance on unseen data. Studies have demonstrated their strong discriminative power in educational and cybersecurity datasets, particularly when using sigmoid or radial basis kernels [22].

Figure 7 illustrates a typical linear SVM scenario in a 2D space. The solid line represents the optimal separating hyperplane, while the dashed lines define the margin boundaries. The hyperplane separates the two classes while maximizing the margin between the closest points, known as support vectors, which determine its position and orientation.




Figure 7: Linear SVM classification

Developed in the 1990s by Vladimir Vapnik and colleagues, SVMs support both linear and non-linear classification tasks. When data is linearly separable, a linear SVM fits the widest possible margin between classes. However, for more complex data distributions, SVMs use the kernel trick—a mathematical technique that implicitly maps the input features into a higher-dimensional space where linear separation becomes feasible. Common kernel functions in-

clude the polynomial kernel, sigmoid kernel, and radial basis function (RBF) kernel [21].

In this study, the SVM model was implemented using the `scikit-learn` library [15]. We employed the radial basis function (RBF) as the kernel (`kernel="rbf"`), with the regularization parameter set to `C=1.0` and `gamma=0.7`, which controls the influence of individual training samples. The remaining hyperparameters were kept at their default values.

8 Results

Building on the experimental setups introduced earlier, this section presents a detailed evaluation of the models across all scenarios. The goal is to analyze how the feature selection strategy, class distribution, and training data size affect classification performance.

To quantify the performance of each classifier, we used standard metrics: accuracy, F1-score, mean squared error (MSE), and the Area Under the Receiver Operating Characteristic Curve (AUC–ROC, hereafter AUC). These metrics were computed using `scikit-learn` [15], and are complemented by confusion matrices to visualize prediction outcomes.

8.1 Evaluation metrics

The evaluation metrics were calculated based on the confusion matrix, which summarizes prediction outcomes as illustrated in Figure 8. The formulas follow standard definitions in classification evaluation [23].

- **Accuracy:**

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}$$

- **F1-score:**

$$\text{F1-score} = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}},$$
$$\text{with Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}$$

- **Mean Squared Error (MSE):**

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2$$

- **AUC:**

$$\text{AUC} = \int_0^1 \text{TPR}(x)\, d(\text{FPR}(x))$$

where TPR (True Positive Rate) is defined as $\text{TPR} = \frac{TP}{TP+FN}$ and FPR (False Positive Rate) is defined as $\text{FPR} = \frac{FP}{FP+TN}$.




Figure 8: Structure of a confusion matrix

In this context, **TP** (True Positives) refers to instances correctly predicted as belonging to the positive class, **TN** (True Negatives) to instances correctly predicted as negative, **FP** (False Positives) to negative instances incorrectly classified as positive, and **FN** (False Negatives) to positive instances incorrectly classified as negative.

8.2 Results on the original dataset (unbalanced)

Table 3 summarizes the metrics obtained when training the models with the original imbalanced dataset. Two different feature selectors were evaluated: Extra Trees Classifier and Random Forest Classifier, each under 80/20 and 50/50 train-test splits. In general, the best performance was consistently achieved by the RF model, followed closely by DT, especially in terms of F1-score and MSE. The BPNN model showed the lowest accuracy and F1-score across most configurations, particularly under the Extra Trees 80/20 split.

Confusion matrices corresponding to these results are shown in Figures 9(a) to 9(d).

8.3 Results on the balanced dataset

Table 4 presents the results when the dataset was balanced through undersampling. In this case, BPNN performance improved significantly in both accuracy and F1-score across all settings. While tree-based models such as RF and DT retained their strong performance, the performance gap between them and BPNN/SVM narrowed considerably.

The corresponding confusion matrices are shown in Figures 10(a) to 10(d).

8.4 Interpretation

The evaluation results and confusion matrices across all experimental setups reveal critical insights into how the feature selection strategy, class distribution, and training size affect the behavior of different classifiers.

Table 3: Evaluation results on the original (unbalanced) dataset.

Feature Selector	Train/Test	Model	Accuracy (%)	F1-score	MSE	AUC
Extra Trees Classifier	80/20	BPNN	91.84	0.8458	0.0816	0.9404
		DT	99.11	0.9853	0.0089	0.9943
		RF	**99.43**	**0.9906**	**0.0057**	**0.9995**
		SVM	98.45	0.9749	0.0155	0.9958
	50/50	BPNN	96.04	0.9318	0.0396	0.9392
		DT	99.01	0.9834	0.0099	0.9934
		RF	**99.34**	**0.9890**	**0.0066**	**0.9995**
		SVM	98.06	0.9683	0.0194	0.9945
Random Forest Classifier	80/20	BPNN	96.73	0.9452	0.0327	0.9588
		DT	99.03	0.9840	0.0097	0.9944
		RF	**99.45**	**0.9909**	**0.0055**	**0.9995**
		SVM	95.96	0.9374	0.0404	0.9897
	50/50	BPNN	96.60	0.9422	0.0340	0.9568
		DT	99.06	0.9842	0.0094	0.9929
		RF	**99.37**	**0.9894**	**0.0063**	**0.9995**
		SVM	95.45	0.9290	0.0455	0.9871

Table 4: Evaluation results on the balanced dataset.

Feature Selector	Train/Test	Model	Accuracy (%)	F1-score	MSE	AUC
Extra Trees Classifier	80/20	BPNN	93.07	0.9327	0.0693	0.9572
		DT	98.96	0.9897	0.0104	0.9950
		RF	**99.32**	**0.9932**	**0.0068**	**0.9994**
		SVM	98.28	0.9832	0.0172	0.9954
	50/50	BPNN	94.36	0.9414	0.0564	0.9438
		DT	98.93	0.9894	0.0107	0.9944
		RF	**99.25**	**0.9925**	**0.0075**	**0.9993**
		SVM	97.98	0.9802	0.0202	0.9949
Random Forest Classifier	80/20	BPNN	94.59	0.9456	0.0541	0.9247
		DT	98.86	0.9887	0.0114	0.9952
		RF	**99.27**	**0.9928**	**0.0073**	**0.9993**
		SVM	96.37	0.9652	0.0363	0.9871
	50/50	BPNN	96.34	0.9630	0.0366	0.9353
		DT	98.82	0.9883	0.0118	0.9933
		RF	**99.23**	**0.9923**	**0.0077**	**0.9990**
		SVM	96.20	0.9634	0.0380	0.9846


Under the original (unbalanced) dataset, both the **Extra Trees Classifier** and the **Random Forest Classifier** enabled the tree-based models (DT and RF) to achieve outstanding performance. In particular, RF consistently delivered the best results across nearly all configurations. For instance, when using the Random Forest Classifier with an 80/20 split on the unbalanced dataset, RF achieved an F1-score of 0.9909 and an MSE of 0.0055, with only 57 false negatives and 96 false positives (Figure 9(c)). Similarly, DT obtained 99.03% accuracy with only 134 false negatives and 134 false positives in the same setting.

The performance of BPNN under unbalanced data was comparatively lower, particularly with the Extra Trees Classifier in the 80/20 setting. As shown in Figure 9(a), BPNN misclassified 2179 legitimate samples as false negatives and 74 non-legitimate samples as false positives, resulting in a relatively low F1-score of 0.8458 and the highest MSE among all models (0.0816). Although its accuracy and F1-score improved with more training data (96.04% accuracy and 0.9318 F1-score in the 50/50 split), the gap with tree-based models remained noticeable (Figure 9(b)).


SVM also exhibited sensitivity to class imbalance. Particularly, in the Random Forest Classifier with 50/50 split (Figure 9(d)), SVM produced the highest number of false positives (3115) among all models evaluated and an F1-score of 0.9290, indicating potential overfitting or misclassification of non-legitimate samples.

After applying class balancing through random undersampling, substantial improvements were observed for both BPNN and SVM. The most dramatic gains were evident in the confusion matrices and F1-scores. For example, in the Extra Trees Classifier with 80/20 split, BPNNs number of false negatives decreased sharply from 2179 (Figure 9(a)) to 396 (Figure 10(a)), and its F1-score rose from 0.8458 to 0.9327. A similar trend occurred in the 50/50 split (Figure 10(b)), where BPNN reached an F1-score of 0.9414, rivaling the performance of the DT model.


SVM also benefited from class balancing. Its false posi-




(a) Feature selector = Extra Trees Classifier (80/20 split)



(b) Feature selector = Extra Trees Classifier (50/50 split)



(c) Feature selector = Random Forest Classifier (80/20 split)




(d) Feature selector = Random Forest Classifier (50/50 split)

Figure 9: Confusion matrices derived from unbalanced datasets.


tives dropped from 373 (Figure 9(a)) to 254 (Figure 10(a)) and its F1-score improved to 0.9832. In the Random Forest Classifier 50/50 split (Figure 10(d)), SVM reached an F1-score of 0.9634, which was a significant leap compared to its previous 0.9290 under unbalanced conditions.

The Random Forest Classifier again proved to be the most stable and performant model, maintaining F1-scores above 0.99 in all conditions. Its robustness was evident not only in metrics but also in the confusion matrices (Figures 9(c) and 10(c)), where it consistently minimized both types of errors.


DT also demonstrated solid performance, though it was




(a) Feature selector = Extra Trees Classifier (80/20 split)



(b) Feature selector = Extra Trees Classifier (50/50 split)



(c) Feature selector = Random Forest Classifier (80/20 split)



(d) Feature selector = Random Forest Classifier (50/50 split)

Figure 10: Confusion matrices derived from balanced datasets.

slightly less robust than RF when evaluated across multiple conditions. Nevertheless, DTs simplicity and interpretability, combined with its consistent accuracy above 98.8%, make it a compelling alternative in scenarios where model transparency is essential.

Taken together, class balancing emerged as a critical factor in enhancing the performance of BPNN and SVM. BPNN in particular showed the largest relative improvement, validating its ability to generalize well when trained with balanced data. The change was evident from the patterns observed in the confusion matrices, where the misclassification of legitimate samples drastically declined.

The findings also underline the importance of evaluating model performance not only through scalar metrics like accuracy and F1-score but also through the detailed inspection of confusion matrices, which reveal nuanced differences in behavior under various training conditions.

Ultimately, the RF and DT models consistently outperformed other classifiers, regardless of feature selection method or class balance. However, BPNN proved to be a viable and competitive option when supported with balanced data, highlighting the potential of neural models in binary classification tasks involving skewed class distributions.

In addition to the evaluation results, it is important to note that extensive experimentation was conducted to determine optimal hyperparameter settings for each model. The configurations reported in this study were selected after testing multiple combinations and correspond to those that yielded the best trade-off between accuracy and generalization. Notably, BPNN and SVM models required more careful tuning and exhibited longer training times compared to tree-based models. This difference in computational cost was particularly evident during iterative experimentation, where DT and RF consistently trained faster, making them more suitable for rapid prototyping and scenarios with limited computational resources.

In the case of BPNN, the architectural decision to use two hidden layers with moderate size was guided by empirical testing. Configurations with 128 neurons per layer offered a practical balance between representational capacity and computational efficiency, capturing complex patterns without overfitting or incurring excessive training costs. Although other configurations were considered, larger networks did not show meaningful improvements, reinforcing this choice as an effective trade-off.

9 Discussion

The experimental findings presented in Tables 3 and 4 reveal that the proposed models achieve performance levels comparable to those reported in previous malware detection studies (Table 1). Earlier works based on deep neural networks—such as Convolutional Neural Network, Recurrent Neural Network, or Active Learning architectures—reported accuracies above 99%. In contrast, the RF model in the present study reached a peak accuracy of 99.45% and an F1-score of 0.9909 on the unbalanced dataset, while maintaining similar performance (99.27% accuracy and 0.9928 F1-score) on the balanced dataset. These results position RF on par with advanced deep-learning approaches, despite its substantially lower computational complexity and training time.

It is important to note that although previous studies reported high accuracy values (while some also showed results around 70–80%), this metric alone can be misleading when the dataset is imbalanced. When one class is significantly more frequent than the other, a model can achieve high accuracy without truly learning to distinguish between classes. Therefore, complementary metrics such as Recall, F1-score, and AUC provide a more complete and fair assessment of model performance. In particular, AUC evaluates how well the model separates positive and negative samples—that is, the probability that the model assigns a higher score to a positive instance than to a negative one. As shown in Tables 3 and 4, the RF model achieved an AUC value of 0.9995, which is nearly perfect.

A notable finding is the consistent superiority of tree-based methods—particularly RF and DT—over both neural and kernel-based models. Several factors explain this behavior. First, tree ensembles inherently manage nonlinear feature interactions and handle irrelevant attributes effectively, which is a crucial advantage when using static features extracted from PE files. Second, tree-based algorithms are less sensitive to feature scaling and class imbalance, leading to stable convergence without extensive hyperparameter tuning. Moreover, the feature selection methods (Extra Trees and Random Forest) used in this work synergize naturally with DT and RF models, as they rely on the same impurity-based importance measures. This alignment likely amplified their discriminative power, yielding near-perfect accuracy and minimal MSE.

Although RF achieved near-perfect accuracy, its exceptional performance must be interpreted cautiously. Ensemble models can overfit when trained on high-dimensional data or when feature redundancy is high. Nevertheless, the low MSE and consistent results across training/test splits suggest strong generalization rather than overfitting. RF also offers partial interpretability through feature importance metrics, making it more explainable than most deep-learning approaches that function as black boxes. Runtime efficiency was another advantage: DT and RF required significantly shorter training and inference times than BPNN and SVM, supporting their suitability for real-time or resource-limited malware detection scenarios.

Regarding novelty, this work does not introduce a new algorithmic architecture but rather provides a systematic comparative evaluation of established ML techniques under a new dataset configuration with explicit class balancing and feature selection strategies. This approach bridges a gap left by previous studies that primarily emphasized raw accuracy without addressing imbalance or interpretability. The contribution therefore lies in demonstrating that traditional, interpretable methods—when properly tuned and combined with informed feature selection—can achieve state-of-the-art performance comparable to deep neural networks while remaining computationally efficient and transparent.

In summary, the discussion reinforces three core insights: (1) tree-based models remain a competitive and interpretable choice for static malware detection; (2) data balancing and feature selection significantly enhance neural and kernel-based classifiers; and (3) explainability, runtime efficiency, and model simplicity are decisive factors when

translating research findings into operational cybersecurity systems.

10 Conclusions and future work

This study presented an approach to the detection of malware using supervised machine learning models trained on static features extracted from malware and benign executable samples. The problem was addressed through the lens of binary classification, with a clear experimental structure grounded in the KDD process. By evaluating four well-known classifiers—BPNN, DT, RF, and SVM—across different training sizes, feature selection strategies, and class balance conditions, the work offers an in-depth perspective on the capabilities and limitations of each algorithm in real-world scenarios.

The integration of the KDD process provided a structured and reproducible pipeline, encompassing data selection, preprocessing, transformation, feature selection, and evaluation. This methodology allowed for a disciplined experimentation strategy that ensured consistency across tests while providing room for targeted insights. In particular, the use of tree-based feature selection methods, namely Extra Trees and Random Forest classifiers, was effective in reducing input dimensionality while preserving high predictive performance. These selectors not only improved training efficiency but also helped mitigate potential noise and redundancy in the feature space.

Quantitative results showed that the RF and DT models consistently outperformed other classifiers in nearly all configurations, achieving F1-scores above 0.99 and minimum MSE across both unbalanced and balanced datasets. Their robustness to class imbalance and their ability to produce reliable predictions make them strong candidates for malware detection systems in high-stakes environments. Notably, RF achieved outstanding performance even with fewer training samples, suggesting that it can generalize well with limited labeled data.

BPNN, on the other hand, initially struggled under unbalanced data conditions, presenting higher false negative rates and lower F1-scores. However, after balancing the dataset via undersampling, BPNN showed the most significant performance improvement among all classifiers. Its F1-score increased by nearly 10 percentage points in some scenarios, and its error rates decreased substantially. These results confirm that while neural networks may be more sensitive to class distribution, they also possess strong generalization capabilities when trained under balanced conditions with representative data. Similarly, SVM exhibited sensitivity to class imbalance, with a tendency to produce high false positive rates. Nevertheless, it also benefitted from class balancing, improving its F1-score and reducing misclassification rates.

Beyond model performance, this study highlights the strategic convergence of three core domains: data science, machine learning, and cybersecurity. The use of static malware analysis aligns with practices in ethical hacking, where reverse engineering and behavioral understanding of malicious software support the development of robust defense mechanisms. The incorporation of automated classification models into malware detection workflows represents a step forward toward proactive and intelligent cybersecurity systems capable of adapting to ever-evolving threats. In this context, data-driven approaches not only improve detection accuracy but also enable scalable and interpretable systems that align with ethical standards of cyber defense.

10.1 Limitations

Although the proposed approach demonstrates strong performance in detecting malware through static analysis, certain limitations should be acknowledged. The methodology relies exclusively on static features extracted from PE files, which may not capture behaviors exhibited only during runtime. As a result, malware employing advanced obfuscation or dynamic evasion techniques could remain undetected. Previous studies, such as the ARMED framework by Castro et al. [24], have shown that minor modifications to executable files can drastically reduce the effectiveness of static detectors, underscoring the inherent fragility of static-only approaches. Furthermore, the dataset used—while extensive—may not fully represent the diversity of emerging threats in real-world environments. These factors highlight the need for further research integrating complementary behavioral insights and broader datasets to address evolving malware techniques.

10.2 Future work

Future work should explore several avenues to extend the present findings. One direction involves incorporating dynamic features, such as runtime behavior, system calls, and network activity, which can provide richer contextual information and enhance the model's ability to detect complex or evasive behaviors. Another promising path includes the integration of hybrid or ensemble architectures that combine the strengths of multiple classifiers—e.g., a BPNN-RF stack—to capture both nonlinear patterns and decision-level robustness. Additionally, future research should consider adversarial robustness, particularly the model's resistance to manipulated input data, by exploring adversarial training or applying explainability frameworks such as SHapley Additive exPlanations (SHAP) or Local Interpretable Model-agnostic Explanations (LIME) to promote interpretability and accountability. Finally, applying the methodology to real-time or online detection settings, and generalizing it across platforms and malware families, would enhance the applicability and operational value of the proposed solutions.

References

[1] National Institute of Standards and Technology, "Malware definition." https://csrc.nist.gov/glossary/term/malware, 2023. Accessed: 2025-05-17.

[2] Symantec, "Internet security threat report 2023." https://symantec-enterprise-blogs.security.com, 2023. Accessed: 2025-05-17.

[3] R. Sihwail, K. Omar, and K. A. Z. Ariffin, "A survey on malware analysis techniques: Static, dynamic, hybrid and memory analysis," *International Journal on Advanced Science, Engineering and Information Technology*, vol. 8, no. 4-2, pp. 1662–1671, 2018.

[4] U. Fayyad, G. Piatetsky-Shapiro, and P. Smyth, "The kdd process for extracting useful knowledge from volumes of data," *Communications of the ACM*, vol. 39, no. 11, pp. 27–34, 1996.

[5] M. Shakib, "Android Malware Detection Approach's Based on Genetic Ai, Cnn, Rnn, Lstm, Gru, and Active Learning." Social Science Research Network, 2023.

[6] H. C. Tanuwidjaja and K.-j. Kim, "Enhancing malware detection by modified deep abstraction and weighted feature selection," in *In Proceedings of the 2020 Symposium on Cryptography and Information Security, Seoul, Republic of Korea*, pp. 1–8, 2020.

[7] R. K. ROY, "A few approaches in encrypted malware classifications." Zenodo, 2022.

[8] R. Baker del Aguila, C. D. Contreras Pérez, A. G. Silva-Trujillo, J. C. Cuevas-Tello, and J. Nunez-Varela, "Static malware analysis using low-parameter machine learning models," *Computers*, vol. 13, no. 3, p. 59, 2024.

[9] VirusShare. https://virusshare.com/, Accessed on March 25, 2025.

[10] The pandas development team, "pandas-dev/pandas: Pandas." Zenodo, Sept. 2025.

[11] A. M. Sharifnia, D. E. Kpormegbey, D. K. Thapa, and M. Cleary, "A primer of data cleaning in quantitative research: Handling missing values and outliers," *Journal of Advanced Nursing*, vol. 0, pp. 1–6.

[12] M. Carvalho, A. J. Pinho, and S. Brás, "Resampling approaches to handle class imbalance: a review from a data perspective," *Journal of Big Data*, vol. 12, no. 1, p. 71, 2025.

[13] R. E. Bellman, *Dynamic Programming*. Princeton, NJ: Princeton University Press, 1957.

[14] D. Peng, Z. Gui, and H. Wu, "Interpreting the curse of dimensionality from distance concentration and manifold effect," *arXiv preprint arXiv:2401.00422*, 2023.

[15] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, "Scikit-learn: Machine learning in Python." https://scikit-learn.org/stable/, 2011. Accessed: 2025-05-20.

[16] A. Souri and R. Hosseini, "A state-of-the-art survey of malware detection approaches using data mining techniques," *Human-centric Computing and Information Sciences*, vol. 8, no. 1, p. 3, 2018.

[17] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *nature*, vol. 521, no. 7553, pp. 436–444, 2015.

[18] A. Kinasih, A. Handayani, J. Ardiansah, and N. Damanhuri, "Comparative analysis of decision tree and random forest classifiers for structured data classification in machine learning," *Science in Information Technology Letters*, vol. 5, pp. 13–24, 11 2024.

[19] L. Rokach and O. Maimon, *Decision Trees*, pp. 165–192. Boston, MA: Springer US, 2005.

[20] IBM, "What is random forest?." https://www.ibm.com/think/topics/random-forest, 2021. Accessed: 2025-05-24.

[21] N. Cristianini and E. Ricci, "Support vector machines," in *Encyclopedia of algorithms*, pp. 928–932, Springer, 2008.

[22] T. Admassu, A. Salau, G. Chhabra, K. Kaushik, and S. Braide, "Evaluation of random forest and support vector machine models in educational data mining," 06 2024.

[23] A. Geron, *Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow: Concepts, Tools, and Techniques to Build Intelligent Systems*. O'Reilly Media, Inc., 2nd ed., 2019.

[24] R. Castro, C. Schmitt, and G. Rodosek, "Armed: How automatic malware modifications can evade static detection?," pp. 20–27, 03 2019.

Appendix

In this section we present the grouped features and their descriptions for static malware analysis (Table 5), the descriptive statistics for the features separated by class (Tables 6 and 7), and the correlation matrices (Figures 11 and 12),.

Table 5: Grouped features and descriptions for static malware analysis

Group	Feature	Description
File Header	Machine	Identifies the required architecture for execution and helps determine compatibility with system hardware.
	SizeOfOptionalHeader	Defines the byte size of the optional header that contains execution-specific fields.
	Characteristics	Specifies attributes of the file such as its type and layout via a set of binary flags.
Optional Header	MajorLinkerVersion	Stores the primary version number of the linker used during compilation.
	MinorLinkerVersion	Stores the secondary version number of the linker.
	SizeOfCode	Indicates the combined size in bytes of all executable code sections.
	SizeOfInitializedData	Indicates the total size in bytes of initialized data sections.
	SizeOfUninitializedData	Refers to the size of memory blocks declared but not initialized during compilation.
	AddressOfEntryPoint	Represents the memory offset where execution starts once the binary is loaded.
	BaseOfCode	Marks the beginning memory address of the code section.
	BaseOfData	Marks the beginning memory address of the initialized data section.
	ImageBase	Indicates the default memory location where the file should be loaded by the operating system.
	SectionAlignment	Describes how the sections are aligned in virtual memory during load time.
	FileAlignment	Describes how the sections are aligned on disk.
	MajorOperatingSystemVersion	Declares the major version of the minimum supported operating system.
	MinorOperatingSystemVersion	Declares the minor version of the minimum supported operating system.
	MajorImageVersion	Indicates the major version label assigned to the image by the developer.
	MinorImageVersion	Indicates the minor version label assigned to the image.
	MajorSubsystemVersion	Provides the major version of the subsystem environment required.
	MinorSubsystemVersion	Provides the minor version of the subsystem environment required.
	SizeOfImage	Specifies the full size in memory of the loaded binary including headers and sections.
	SizeOfHeaders	Indicates the total byte size of all headers in the file.
	CheckSum	Used to verify integrity of the file; often unused during execution.
	Subsystem	Determines the expected runtime environment required to execute the binary.
	DllCharacteristics	Contains binary flags that determine runtime features related to memory and execution behavior.
	SizeOfStackReserve	Declares the total memory reserved for the process stack.
	SizeOfStackCommit	Declares the portion of the stack that is initially committed.
	SizeOfHeapReserve	Declares the total memory reserved for the process heap.
	SizeOfHeapCommit	Declares the portion of the heap that is initially committed.
	LoaderFlags	Reserved field used for system-specific loading behaviors.
	NumberOfRvaAndSizes	Number of data directory entries present in the optional header.
Section Entropy	SectionsNb	Counts the number of sections defined within the binary.
	SectionsMeanEntropy	Measures the average entropy across all sections indicating data randomness.
	SectionsMinEntropy	Identifies the lowest entropy score among all sections.
	SectionsMaxEntropy	Identifies the highest entropy score among all sections.
Section Size	SectionsMeanRawsize	Reports the average disk size of all sections.
	SectionsMinRawsize	Records the smallest section size on disk.
	SectionMaxRawsize	Records the largest section size on disk.
	SectionsMeanVirtualsize	Reports the average size of all sections when loaded in memory.
	SectionsMinVirtualsize	Records the smallest memory size among sections.
	SectionMaxVirtualsize	Records the largest memory size among sections.
Imports	ImportsNbDLL	Counts the total number of dynamic link libraries used.
	ImportsNb	Counts all imported functions across all libraries.
	ImportsNbOrdinal	Counts functions imported using ordinal references rather than names.
Exports	ExportNb	Counts the number of functions made accessible to other modules.
Resources	ResourcesNb	Counts the embedded assets included in the binary.
	ResourcesMeanEntropy	Measures the average entropy of the embedded resources.
	ResourcesMinEntropy	Identifies the lowest entropy score across the embedded resources.
	ResourcesMaxEntropy	Identifies the highest entropy score across the embedded resources.
	ResourcesMeanSize	Measures the average size of the embedded resources.
	ResourcesMinSize	Records the smallest embedded resource by size.
	ResourcesMaxSize	Records the largest embedded resource by size.
Configuration	LoadConfigurationSize	Declares the byte size of the load configuration structure.
	VersionInformationSize	Declares the byte size of the file versioning metadata.

Table 6: Descriptive statistics for features (Malware class only)

Feature	Range	Mean	Std	Q1	Q3
Machine	332 – 34404	355.95	903.10	332.00	332.00
SizeOfOptionalHeader	224 – 352	224.01	0.597	224.00	224.00
Characteristics	2 – 49551	3.3K	9.3K	258.00	259.00
MajorLinkerVersion	0 – 255	8.57	4.82	8.00	10.00
MinorLinkerVersion	0 – 255	4.96	13.83	0.000	0.000
SizeOfCode	0 – 1818586738	176.9K	6.8M	37.9K	120.3K
SizeOfInitializedData	0 – 4294966272	518.6K	25.1M	119.8K	385.0K
SizeOfUninitializedData	0 – 4294940713	143.7K	19.5M	0.000	0.000
AddressOfEntryPoint	0 – 1074484297	172.3K	4.1M	14.8K	61.6K
BaseOfCode	0 – 2028711251	80.3K	6.6M	4.1K	4.1K
BaseOfData	0 – 268435456	223.0K	2.5M	45.1K	127.0K
ImageBase	65536.0 – 6442450944.0	13.1M	148.8M	4.2M	4.2M
SectionAlignment	16 – 134217728	8.3K	747.5K	4.1K	4.1K
FileAlignment	16 – 4096	588.85	519.26	512.00	512.00
MajorOperatingSystemVersion	0 – 36868	4.94	118.53	4.00	5.00
MinorOperatingSystemVersion	0 – 17757	1.18	92.65	0.000	1.00
MajorImageVersion	0 – 28619	3.32	190.06	0.000	0.000
MinorImageVersion	0 – 20512	2.86	168.51	0.000	0.000
MajorSubsystemVersion	3 – 6	4.70	0.461	4.00	5.00
MinorSubsystemVersion	0 – 47600	1.59	216.45	0.000	1.00
SizeOfImage	0 – 1410035712	827.1K	7.5M	311.3K	528.4K
SizeOfHeaders	448 – 786432	1.3K	6.5K	1.0K	1.0K
CheckSum	0 – 4294967295	256.1M	699.7M	300.4K	573.7K
Subsystem	1 – 3	2.01	0.076	2.00	2.00
DllCharacteristics	0 – 36864	28.7K	11.3K	32.8K	33.1K
SizeOfStackReserve	0 – 33554432	1.1M	484.2K	1.0M	1.0M
SizeOfStackCommit	0 – 2097152	5.5K	17.8K	4.1K	4.1K
SizeOfHeapReserve	0 – 13631488	1.1M	137.4K	1.0M	1.0M
SizeOfHeapCommit	0 – 2077323491	47.3K	9.4M	4.1K	4.1K
LoaderFlags	0 – 2328297507	51.5K	10.6M	0.000	0.000
NumberOfRvaAndSizes	7 – 3402309701	112.9K	17.5M	16.00	16.00
SectionsNb	1 – 40	5.25	1.81	5.00	5.00
SectionsMeanEntropy	0.0 – 7.98994115645	4.88	1.02	4.26	5.65
SectionsMinEntropy	0.0 – 7.98994115645	2.44	1.92	0.000	4.15
SectionsMaxEntropy	0.0 – 7.99999379205	7.38	0.732	6.59	7.96
SectionsMeanRawsize	64.0 – 1431641941.33	181.2K	9.2M	38.3K	101.1K
SectionsMinRawsize	0 – 2754048	5.8K	11.2K	0.000	9.7K
SectionMaxRawsize	64 – 4294885376	666.2K	35.9M	105.5K	330.8K
SectionsMeanVirtualsize	0.0 – 1431673348.0	183.7K	5.0M	46.3K	102.6K
SectionsMinVirtualsize	0 – 3399680	8.0K	20.1K	1.2K	9.4K
SectionMaxVirtualsize	0 – 4294884876	646.2K	15.3M	161.5K	339.7K
ImportsNbDLL	0 – 280	5.35	3.87	3.00	8.00
ImportsNb	0 – 3046	103.86	75.23	87.00	113.00
ImportsNbOrdinal	0 – 1051	1.43	11.11	0.000	1.00
ExportNb	0 – 8015	1.53	61.04	0.000	0.000
ResourcesNb	0 – 3060	13.99	32.64	6.00	14.00
ResourcesMeanEntropy	0.0 – 7.99972286753	4.15	1.23	3.50	4.45
ResourcesMinEntropy	0.0 – 7.99972286753	2.28	0.686	2.16	2.46
ResourcesMaxEntropy	0.0 – 7.99999295933	5.93	1.48	5.22	7.39
ResourcesMeanSize	0.0 – 2415919166.0	74.9K	9.3M	1.8K	12.7K
ResourcesMinSize	0 – 2415919166	25.7K	7.8M	48.00	48.00
ResourcesMaxSize	0 – 4294902624	323.4K	25.4M	7.3K	28.8K
LoadConfigurationSize	0 – 4294967294	664.6K	31.2M	0.000	72.00
VersionInformationSize	0 – 26	10.68	7.38	0.000	15.00

Table 7: Descriptive statistics for features (Legitimate class only)

Feature	Range	Mean	Std	Q1	Q3
Machine	332 – 34404	13.4K	16.6K	332.00	34.4K
SizeOfOptionalHeader	224 – 240	230.14	7.78	224.00	240.00
Characteristics	2 – 33679	7.2K	3.0K	8.2K	8.4K
MajorLinkerVersion	2 – 48	8.73	1.16	8.00	9.00
MinorLinkerVersion	0 – 60	1.16	3.51	0.000	0.000
SizeOfCode	0 – 51634176	396.5K	1.4M	7.2K	264.2K
SizeOfInitializedData	0 – 322908160	291.1K	2.2M	6.1K	112.6K
SizeOfUninitializedData	0 – 4197376	951.22	51.5K	0.000	0.000
AddressOfEntryPoint	0 – 45251088	171.3K	654.8K	4.6K	97.4K
BaseOfCode	0 – 3014656	5.1K	28.7K	4.1K	4.1K
BaseOfData	0 – 33599488	217.6K	939.5K	0.000	106.5K
ImageBase	65536.0 – 1.844673527761653e+19	1.8e+15	1.8e+17	268.4M	6442.5M
SectionAlignment	16 – 2097152	5.0K	21.1K	4.1K	4.1K
FileAlignment	16 – 65536	941.40	2.2K	512.00	512.00
MajorOperatingSystemVersion	0 – 10	5.46	0.806	5.00	6.00
MinorOperatingSystemVersion	0 – 3	0.891	0.679	1.00	1.00
MajorImageVersion	0 – 21315	221.90	2.1K	1.00	6.00
MinorImageVersion	0 – 20512	209.96	2.1K	0.000	1.00
MajorSubsystemVersion	1 – 10	5.24	0.838	5.00	6.00
MinorSubsystemVersion	0 – 50	1.11	1.77	0.000	1.00
SizeOfImage	3072 – 324210688	790.0K	3.1M	49.2K	540.7K
SizeOfHeaders	512 – 65536	1.4K	2.1K	1.0K	1.0K
CheckSum	0 – 4257612032	1.2M	38.6M	64.0K	488.7K
Subsystem	1 – 16	2.51	0.700	2.00	3.00
DllCharacteristics	0 – 49504	7.4K	13.4K	320.00	1.3K
SizeOfStackReserve	0 – 10000000	487.3K	447.6K	262.1K	1.0M
SizeOfStackCommit	0 – 1048576	5.4K	18.7K	4.1K	4.1K
SizeOfHeapReserve	0 – 4194304	988.5K	252.0K	1.0M	1.0M
SizeOfHeapCommit	0 – 65536	4.0K	1.6K	4.1K	4.1K
LoaderFlags	0 – 0	0.000	0.000	0.000	0.000
NumberOfRvaAndSizes	16 – 16	16.00	0.000	16.00	16.00
SectionsNb	1 – 38	4.39	2.01	3.00	5.00
SectionsMeanEntropy	0.173444442902 – 7.99555757619	4.06	1.05	3.25	4.83
SectionsMinEntropy	0.0 – 7.99555757619	1.83	1.51	0.334	2.96
SectionsMaxEntropy	1.11230271386 – 7.99999271595	5.96	0.984	5.78	6.54
SectionsMeanRawsize	333.714285714 – 92973226.6667	201.1K	1.1M	8.5K	114.7K
SectionsMinRawsize	0 – 29000704	51.7K	645.8K	512.00	4.1K
SectionMaxRawsize	512 – 321623040	614.3K	3.1M	26.6K	401.9K
SectionsMeanVirtualsize	226.0 – 64839490.2	199.5K	952.0K	8.4K	116.8K
SectionsMinVirtualsize	1 – 29000672	51.7K	645.8K	131.00	2.3K
SectionMaxVirtualsize	288 – 321622732	608.8K	2.7M	25.6K	407.9K
ImportsNbDLL	0 – 39	5.72	5.34	1.00	9.00
ImportsNb	0 – 4432	135.16	191.62	1.00	179.00
ImportsNbOrdinal	0 – 3450	11.15	60.70	0.000	4.00
ExportNb	0 – 16596	75.51	446.93	0.000	11.00
ResourcesNb	0 – 7694	40.93	243.39	1.00	8.00
ResourcesMeanEntropy	0.0 – 7.41281622478	3.66	0.648	3.41	3.92
ResourcesMinEntropy	0.0 – 5.14079953855	2.81	0.961	2.47	3.54
ResourcesMaxEntropy	0.0 – 7.99999997868	4.56	1.44	3.54	5.17
ResourcesMeanSize	0.0 – 3907290.66667	9.8K	89.9K	832.00	2.0K
ResourcesMinSize	0 – 7224	528.41	433.61	126.00	928.00
ResourcesMaxSize	0 – 312479744	66.8K	1.7M	928.00	9.6K
LoadConfigurationSize	0 – 160	30.78	40.25	0.000	72.00
VersionInformationSize	0 – 26	16.31	2.15	16.00	17.00




Figure 11: Correlation matrix of features selected by Extra Trees




Figure 12: Correlation matrix of features selected by Random Forest

GAPO-LSTM: A Genetic Algorithm-Optimized Attention-LSTM Framework for Spatiotemporal Power Outage Forecasting in Distribution Networks

Yu Zhang, Hao Sun, Zexiong Wang*, Zhengping Wang, Jialin Liu
State Grid Hebei Electric Power Co., Ltd. Shijiazhuang Power Supply Branch, Shijiazhuang, Hebei, 056000, China
E-mail: zexiong_wang@hotmail.com
*Corresponding author's

Keywords: power outage prediction, genetic algorithm, LSTM, distribution networks, spatiotemporal modeling

Received: September 4, 2025

Accurate prediction of power outages is critical for maintaining grid reliability and enabling proactive operational planning. This paper proposes a genetic algorithm-optimized Pattern-Oriented LSTM (GAPO-LSTM) model to predict outage events based on historical data. The model processes a dataset of 3 years of outage records from the Region, incorporating key features such as weather conditions, equipment type, and load data. Outage patterns are clustered into 5 groups, and the LSTM hyperparameters, including number of layers, hidden units, learning rate, and dropout probability, are optimized using a genetic algorithm with population size 50, 100 generations, crossover probability 0.8, and mutation probability 0.1, employing single-point crossover and Gaussian mutation. GAPO-LSTM is benchmarked against standard LSTM, GRU, and ARIMA models using RMSE, F1-score, and accuracy. Results show that GAPO-LSTM achieves an RMSE of 0.82, F1-score of 0.89, and accuracy of 91.5%, outperforming baseline approaches. The proposed method demonstrates the ability to capture complex outage patterns and provides a foundation for enhanced operational decision-making and system resilience.

Povzetek: Raziskava predstavi model strojnega učenja za napoved izpadov električne energije, ki z optimizacijo parametrov izboljša natančnost napovedi in podpira zanesljivejše načrtovanje delovanja elektroenergetskega omrežja.

1 Introduction

Resilience of infrastructure, public safety, and economic activity all depend on reliable electricity distribution networks [1]. Modern electric distribution networks are more sophisticated, causing more frequent and unpredictable power outages. Urbanization increases energy demand and grid density, but decentralized energy sources like solar and wind increase supply variability and instability [2]. Extreme weather events like storms, wildfires, and heat waves have taxed electrical networks, making forecasting harder [3]. Blackouts disrupt life, inhibit industrial output, and threaten healthcare, transportation, and communication infrastructure. Maintaining energy resilience and security requires robust and intelligent outage prediction systems. [4]. For innovative grid systems to facilitate real-time planning, operational resilience, and customer service reliability, it is crucial to have accurate and proactive outage forecasts [5].

Traditional approaches to outage management frequently use rule-based systems, physics-based simulations, or statistical estimators, none of which are very adaptable to changing patterns of failure or non-linear dependencies [6]. Both the short-term and long-term predictions are inaccurate because these models do not take into consideration the spatiotemporal correlations that are evident in the historical outage data [7]. In addition, generalization attempts are complicated because of the high variety in outage patterns caused by regional Clustering and environmental variation [8]. Therefore, intelligent forecasting algorithms that can understand complex datasets and adjust to infrastructure behavior in real-time are urgently needed [9].




Figure 1:Timely trend of power outages

Time series forecasting, anomaly detection, and predictive maintenance in the energy sector have all benefited from the recent advances in deep learning and machine learning, which have produced more accurate and scalable systems [10], as represented in Figure 1. For example, LSTM networks are highly acclaimed for their ability to capture power consumption or failure logs, two types of sequence data that exhibit temporal relationships [11]. Their real-world application is limited without further optimization due to their performance being susceptible to input feature selection, hyperparameter tuning, and data imbalance concerns [12]. Additionally, complex techniques to prevent overfitting and enhance generalizability are frequently necessary when optimizing LSTM models for grid-scale settings [13].

For feature selection, hyperparameter tuning, and multi-objective optimization, metaheuristic algorithms such as genetic algorithms have been extensively used to make predictive models more resilient and flexible [14]. When combined with deep learning models, genetic algorithms which mimic natural selection are ideal for effectively searching complicated parameter spaces [15].

1.1 Research problem and objectives

In contemporary distribution networks, reliability prediction relies on capturing high-dimensional spatiotemporal connections; nevertheless, current AI-based outage forecasting algorithms are inadequate in this regard. Modern outage data is characterized by spatial diversity, cluster-level anomalies, and non-linear temporal trends; static or non-adaptive algorithms are ill-equipped to deal with this data. Specifically designed for use in power distribution network outage planning, GAPO-LSTM is a hybrid reliability prediction framework that takes advantage of genetic algorithms for optimization and LSTM networks for sequence modeling. This framework aims to mitigate this issue. The objectives are,

- To improve prediction performance and flexibility, we aim to develop a hybrid model using GA to optimize LSTM input characteristics and learning parameters.
- To enhance spatiotemporal pattern learning in specific zones, preprocess and cluster outage data based on geographical commonalities.
- To evaluate the model in a real-world outage and compare its performance to benchmark models using root-mean-squared error and F1-score.

To increase clarity of the research design, two specific research questions have been added at the end of Section 1.1 to align the intent of the study with testable hypotheses, and to strengthen the methodological direction. As written, this revised section concludes with: “The current study is addressed with two main research questions: (1) Does GA-based feature selection significantly improve outage prediction performance both qualitatively and quantitatively compared to a basic LSTM approach? and (2) Does DBSCAN-based spatial clustering improve the accuracy of temporal modeling to capture dependent relationships in outage reporting and forecasting?” These serve as more specific empirical validators and hypothesis-based experimentation.

1.2 Contributions

The research begins with preprocessing a publicly available dataset of timestamped and geotagged Maryland outages. Density-based Clustering based on spatial coordinates organizes the dataset into localized zones with similar grid behavior. Next, a genetic algorithm determines the appropriate sequence lengths, learning rate, batch size, and number of hidden units for the Long Short-Term Memory (LSTM) model and selects the most relevant input features. Next, an attention-enhanced LSTM model is trained on these improved feature sequences to predict cluster outages. Models use attention mechanisms to improve learning efficiency and interpretability. The model can prioritize time steps by predicting the value. Finally, GAPO-LSTM is compared to Random Forests and standard LSTM ensemble learning models on dependability measures and real-world scenarios. In terms of intelligent grid analytics and the control of power outages, this study adds the following:

- To create a new hybrid prediction model (GAPO-LSTM) for proactive outage forecasting by combining deep learning with evolutionary feature optimization.
- To enhance the level of precision in predicting insights by implementing a spatial clustering method for identifying the location of power outage behavior in distribution networks.
- To automate model configuration, sequence creation, and feature selection through the design of an end-to-end optimization pipeline utilizing GA.
- To prove that the suggested strategy is resilient by showing that RMSE is reduced by 18.6% and F1-score is increased by 12.4% compared to baseline models.
- To determine the model's scalability in different operating settings, it is necessary to do a sensitivity analysis to investigate how cluster density and outage volume impact model performance.

GA-based feature selection significantly enhances outage prediction by automatically identifying the most influential temporal, spatial, and environmental variables, reducing redundancy and overfitting. This targeted optimization improves LSTM learning efficiency, achieving lower RMSE and higher F1-scores compared to standard LSTM, which relies on fixed, manually selected feature sets.

This paper's organization follows: Section 2 reviews power outage forecasting, machine learning-based reliability modeling, and GA-based optimization methods. Section 3 describes the GAPO-LSTM framework, including data pretreatment, model construction, and optimization procedure. Experimental setup, dataset features, and assessment measures are in Section 4. Comparative insights and sensitivity testing are presented and analyzed in Section 5. Finally, Section 6 summarizes findings, implications, and future directions.

2 Related work

2.1 Reliability prediction and power outage planning in distribution networks

Saldaña et al. [16] utilize Long Short-Term Memory (LSTM) networks and confidence interval thresholds for long-term scenario forecasting to develop a hybrid distribution network design technique. The system predicts future expansion demands using historical power demand and PV self-consumption data, including non-linear, non-stationary trends ignored by current approaches. The information included operational line restrictions, substation metrics, and economic planning characteristics from a Spanish radial medium-voltage network. Results show that LSTM-based planning is more flexible and cost-effective than static techniques and improves prediction accuracy. However, limited training data in fast-moving energy systems or places with poor sensor coverage may restrict the approach's performance.

Hughes et al [17] Machine learning and physics-based structural fragility curves are used to forecast storm-induced outages in this hybrid mechanistic-data-driven Outage Prediction Model (OPM). Connecticut's distribution system's 2005–2020 meteorological, terrain, vegetation, infrastructure, and historical outage data inform the algorithm. A $600 million investment in tree removal and pole reinforcement might cut outage incidence by 15,000, according to counterfactual scenarios.

Wu et al [18] Using MILP and MIQCP, this study models EVs, FCVs, EVCSs, HFSs, and the transmission and distribution systems. Emission-free station integration is assessed utilizing the IEEE 57-bus transmission network and three 33-bus distribution systems. All distribution systems operated successfully, with renewable production and battery storage increasing EVCS profitability by 475%. The model may not apply because it assumes ideal renewable energy and fixed storage costs.

Wang et al. [19] utilize an Improved-Augmented Epsilon-Constrained (I-AUGMENCON) algorithm for multi-objective optimization (MOO) of EV charging coordination in a modified IEEE 33-bus distribution network dataset. The model's Pareto efficiency reduces power loss, DNO operational costs, and EV charging prices, exceeding NSGA-II. Results show a reduction in power loss from 6% to 2% and better voltage stability. However, static load profiles and assumptions of consistent EV charging behavior may limit adaptability to real-time system dynamics.

Zhou et al. [20] Using simulation and probabilistic modeling of EV load profiles and renewable energy (RE) integration, offer a capacity planning technique that includes reliability evaluation and economic analysis. The modified RBTS BUS6 F4 system is used to evaluate reliability indices like SAIFI and cost. Optimizing energy storage system (ESS) capacity enhances dependability (63.17% SAIFI reduction) and saves money while preserving reliability in Microgrid C. However, the approach may be limited by assumptions on static EV behaviors and ideal RE availability, affecting scalability to diverse real-world scenarios.

2.2 Applications of genetic algorithms in smart grid optimization

Heroual et al [21] Metaheuristic algorithms genetic algorithm (ga), ant colony optimization (aco), and grey wolf optimization (gwo) are used to optimize an energy management system (ems) for a hybrid energy storage system (hess) with batteries and supercapacitors coupled to solar PV. The dataset includes real-time solar and load profiles from MATLAB/Simulink simulations of dynamic irradiance and power demand. Results show the GWO-tuned PI controller improves battery longevity and system stability with fast transient response and low computational load.

Wang et al [22] This study optimizes the economic dispatch model for a microgrid with EVs using wind, solar, micro gas turbine, fuel cell, and battery sources. To reduce operational and pollutant treatment costs, the revised Reference Vector Guided Evolutionary Algorithm (RVEA) uses Chebyshev mapping for population

initialization and an angle-penalized distance (APD) method for convergence-diversity balance. The multi-strategy RVEA outperforms conventional approaches in cost-effectiveness and pollution reduction. EV behavior assumptions limit the model's performance and need physical system validation.

Shejul et al [23] Under dynamic pricing, this study provides an efficient energy scheduling system for a food storage chiller plant to reduce operational cost and peak demand. Grey wolf optimizer (gwo), jaya, and their genetic algorithm-enhanced variants (GA-GWO, GA-JAYA) promote solution diversity for optimization. Simulations using real-time electricity pricing datasets show a 22% cost reduction and 10% energy savings over standard approaches with temperature limits. To set consumer load profiles, the model cannot be validated under different climate or market circumstances.

Došljak et al [24] This study uses a modified genetic algorithm (GA) with novel crossover and mutation operators to optimize electric vehicle charging station placements and capacity in two stages. The graph-based model considers traffic density, grid infrastructure, and user behavior and refines results using simulation-driven metrics like waiting time and usage.

Toughzaoui et al [25] This project develops a solar PV-powered Fuel Cell Combined Heat and Power (FC–CHP) system optimized with a genetic algorithm (GA) to improve hospital energy efficiency. Under penalty restrictions, the GA optimizes PV peak output, electrolyzer size, fuel cell capacity, and hydrogen storage to reduce investment and grid energy prices.

2.3 LSTM and deep learning techniques for time-series-based outage forecasting

Hu et al [26] This study integrates Long Short-Term Memory (LSTM) networks with a self-attention mechanism to improve photovoltaic (PV) power prediction by learning temporal dependencies and inter-variable correlations from past and anticipated weather data. Training and evaluation of the model using Japanese building PV generation data resulted in 15.8% R^2 increases for LSTM and 26.4% for the hybrid model, enhancing short- and long-term forecast accuracy. The model improves prediction reliability, but it relies on accurate weather forecasts and may perform poorly in harsh weather.

Sabyasachi et al. [27] propose a hybrid DCNN-LSTM model for predicting cloud computing workloads and ensuring SLA compliance. This model utilizes deep convolutional layers for spatial feature extraction and LSTM for temporal sequence learning. A real-world cloud workload dataset comprising CPU utilization and SLA parameter time-series data was normalized and window-segmented before training the model. Experimental results show that the proposed model reduces energy-SLA violations by 6.8% to 22.4% compared to ARIMA-LSTM, CNN, LSTM, and ARIMA, demonstrating superior accuracy and SLA adherence. However, scalability and computational complexity limit it for large-scale real-time deployments.

Huang et al. [28] utilize CNN and Bi-LSTM in this study to enhance hourly PV power forecasts with TSF-CGANs. The discriminator verifies forecasts from historical time series data and random noise, allowing adversarial training to increase prediction accuracy. The model outperformed LSTM, RNN, BP, and SVM on a real-world PV power dataset with a 32% reduction in RMSE compared to BP and a forecast skill (FS) of 0.4863 over the Persistence model. GAN-based models' computational expense and training instability are significant drawbacks. This unique adversarial learning framework improves solar power forecasting accuracy.

Xu et al [29] This study presents a two-step fault prediction system using Attention-based LSTM, Random Forest (RF), and Extra Trees (ET) to anticipate device failure modes. The regression model uses wavelet packet-transformed sensor data to forecast time-series trends, while the classification model predicts fault type and severity. Tests on bearing vibration datasets like the IEEE PHM Challenge and IMS bearing dataset revealed excellent forecasting and classification accuracy, proving the model can predict defects. Limited by high-quality sensor data and the computational overhead of a multi-model architecture. This technology makes fault type and intensity predictions early and accurately, improving maintenance planning.

Wang et al [30] This study introduces CL-ROP, a hybrid CNN and LSTM model for online reliability prediction of dynamic web service compositions. Limited by missing or noisy data and the necessity for constant model upgrades. Proactive fault avoidance improves runtime service quality.

Table 1: Comparison of GAPO-LSTM with existing GA–LSTM and hybrid models

Study	Hybrid Technique	Application Area	Optimization Target	Key Results	Limitation in Prior Model	Novelty and Advantage of GAPO-LSTM
Bouktif et al. (2018) *Energies*	GA + LSTM	Electric load forecasting	Feature selection and hyperparameter tuning	Improved load forecast accuracy over basic LSTM	Limited to single-dimensional temporal data, no spatial modeling	GAPO-LSTM integrates spatiotemporal clustering (DBSCAN) with GA-driven feature optimization, handling both geographic and temporal dependencies.

Memarzadeh & Keynia (2023) *J. Energy Storage*	CBSA–GA + MRMI–LSTM	PV–ESS planning	Energy storage optimization	Better PV generation prediction	No attention mechanism, lacks interpretability	GAPO-LSTM includes attention-enhanced LSTM for interpretability and feature weighting across clusters.
Wan et al. (2023) *Energy*	CNN–LSTM + Attention	CHP power load prediction	Sequential load trend learning	8–12% RMSE improvement	No evolutionary optimization; parameters manually tuned	GAPO-LSTM introduces GA-based hyperparameter search, improving adaptability without manual tuning.
Cui et al. (2024) *Energy*	WOA–CNN–LSTM	Heat load prediction	Feature extraction optimization	RMSE ↓ by 18.4%	Focused only on thermal domain; no spatial clustering	GAPO-LSTM generalizes to distribution networks using spatial DBSCAN clustering for localized pattern learning.
Afzal et al. (2023) *Energy*	MLP + GA variants	Building energy prediction	Parameter tuning	Better convergence over BP	No deep sequential modeling	GAPO-LSTM combines deep temporal modeling with GA-driven optimization, improving robustness to non-linear temporal dependencies.
Habib et al. (2024) *SETA*	Hybrid GA + Data-Driven Model	Short-term demand prediction	Demand optimization	Improved short-term demand accuracy	Neglects uncertainty and spatial influence	GAPO-LSTM captures spatial variability and integrates reliability-aware metrics (SOPS, RAFDI).
Xu et al. (2021) *DSP*	Attention-LSTM + RF + ET	Machinery fault prediction	Fault type and severity	High classification accuracy	Requires high-quality sensor data; computationally heavy	GAPO-LSTM achieves similar interpretability using attention with lower complexity via GA-optimized configuration.
Proposed GAPO-LSTM	GA + Attention-LSTM + DBSCAN	Spatiotemporal Power Outage Forecasting	Feature subset selection, hyperparameter tuning, and spatial clustering	RMSE ↓18.6%, F1 ↑12.4%, R^2=0.938	—	Combines GA-based optimization, attention-enhanced interpretability, and spatial clustering, achieving robust, scalable, and interpretable outage forecasting.

Data Sensitivity: GAPO-LSTM was assessed on one dataset which may behave differently when applied to different types of outage events, such as outages caused by storms as opposed to equipment failure events. Additionally, the model's capacity to generalize different outage patterns may require additional training data or specially formulated feature engineering approaches to account for certain characteristics from outage events. Interpretability: While the model achieves good accuracy, LSTM's black-box nature along with GA optimization may make it more difficult for operators to obtain usable insights from their data, demonstrating the need for additional considerations for explainability.

Research on reliability prediction and power outage planning shows tremendous progress, but numerous crucial gaps remain. Many methods [16][17][20] rely on historical data and assume static load behavior, limiting their flexibility in dynamic and real-time contexts. Many models incorporate electric vehicle charging, renewable energy, or microgrid coordination [18][19][22], but omit uncertainty modeling and real-time system feedback. LSTM, CNN, and attention-based architectures [26][29][30] are promising machine learning and deep learning models, but they demand high-quality, noise-free datasets and heavy computational resources. While adversarial networks and hybrid metaheuristics have been introduced

[21] they generally experience training instability or overfitting when generalizing across operational contexts. Most models lack explainability and interpretability, making it difficult for utility operators to embrace. Additionally, algorithms that predict specific fault types [29] or online reliability forecasts [30] are currently being developed and not yet deployed. .

GAPO-LSTM serves this need by utilizing an attention mechanism that emphasizes which spatio-temporal features contribute the most to each prediction, therefore providing interpretable insights, rather than the black-box model output [32]. To more readily provide interpretability of generated outage forecasts, we propose the use of model agnostic interpretability methods such SHAP. This method would provide not only global feature importance rankings to assess relative contribution of models but additionally local explanations for individual outage forecasts.

GAPO-LSTM can provide predictive state estimation inputs to fuzzy controllers, enabling proactive parameter tuning before instability occurs [33]. Its GA-optimized feature selection refines the fuzzy rule base dynamically, ensuring smoother synchronization under uncertain grid dynamics and improving convergence time and system resilience.

By forecasting transient deviations, GAPO-LSTM can supply real-time adaptive references to the output-feedback controller [34]. This predictive augmentation enhances the controller's robustness against unknown disturbances and nonlinearities, reducing synchronization lag and stabilizing distributed network operations during fluctuating load or environmental conditions.

GAPO-LSTM's attention-based temporal modeling can detect evolving nonlinear dependencies and feed them to neural adaptive controllers [35]. Genetic optimization ensures optimal feature selection and hyperparameter balance, reducing overfitting while strengthening multi-variable adaptation for uncertain grid environments and fault-resilient response. Integrating GAPO-LSTM enables predictive estimation of future state trajectories, enhancing backstepping control design by providing dynamic feedback adjustment. Its GA-driven optimization supports parameter adaptation and mitigates modeling errors, thereby achieving faster convergence and greater robustness in nonlinear distribution network operations. GAPO-LSTM can forecast torque fluctuations and pressure dynamics, supplying anticipatory correction signals to nonlinear optimal controllers [36]. Its spatiotemporal learning refines motor drive control loops, minimizes energy loss, and increases compressor reliability under varying grid and load conditions. When combined with GAPO-LSTM, the controller gains predictive awareness of vibration and deflection trends [37]. GA-optimized temporal features allow adaptive compensation for nonlinearities and actuator delays, ensuring smoother motion, reduced oscillations, and improved fault tolerance in electromechanical network applications.

3 Method description

For distribution network reliability planning and power outage prediction, Figure 2 shows the whole architectural workflow of the suggested GAPO-LSTM model. The model starts with the intake of power outage logs, which gather basic data such as the frequency of outages, time stamps, and geolocations $(\mathrm{Lat}, \mathrm{Lon})$. During the preprocessing phase, the data is normalized, outliers are cleaned, and spatial Clustering with DBSCAN is applied to identify and group comparable zones that are prone to outages. By optimizing the chromosomal population, LSTM parameters (such as learning rate and batch size), sequence lengths, and input feature combinations, the Genetic Algorithm (GA) is used to achieve this. By definition, a chromosome is a set $\chi = \{ f, L_s, B, b, \eta \}$ where f is the set of features that have been chosen, L_s The length of the sequence is the size of the batch, and H is the number of LSTM hidden units. To identify the dependencies between the outage sequences over time, an attention-enhanced LSTM model is trained. Minimal forecasting error is guaranteed using RMSE evaluation. After identifying potential danger zones, the model is subjected to sensitivity testing to ensure it can withstand changes in cluster density and data noise. Compared to baseline approaches, GAPO-LSTM achieves better prediction accuracy, with an 18.6% reduction in RMSE and a 12.4% rise in F1-score, as shown in experimental testing on real spatiotemporal datasets (e.g., UID 20904, with 121 outages).

DBSCAN formed eight clusters with epsilon = 0.5 and minimum samples = 5, effectively identifying geographically correlated outage zones for localized spatiotemporal learning and improved model scalability across heterogeneous grid regions.

The Genetic Algorithm used population size = 50, generations = 100, crossover probability = 0.8, and mutation probability = 0.1, ensuring robust exploration-exploitation balance for hyperparameter and feature optimization.

GA-based feature selection improves outage prediction over standard LSTM and whether spatial clustering enhances temporal modeling accuracy. Statistical validation has been incorporated for the results, with paired t-tests and ANOVA used to confirm performance differences.




Figure 2: Workflow of GAPO-LSTM for spatiotemporal outage prediction in distribution networks

3.1 Data preprocessing and geospatial clustering

Noise, missing entries, and unstructured temporal-spatial data are common in raw outage logs, which can make power outage prediction models less accurate. This first module's primary goals are to clean, normalize, and organize the outage dataset; to handle missing values; to standardize geospatial coordinates; and to ensure uniform timestamp formats.

A. Datetime standardization

Time data should be structured consistently for sequential modeling, and dt_stamp standardization accomplishes just that. The LSTM network can now handle outages as ordered time series for this transition. Parsing timestamps into consistent datetime objects, T_i Using Python's datetime. strptime can align documents temporally and eliminate date-time format conflicts. $T_i = \text{datetime. strptime}(dt_{stamp_i}, \text{"\%d} - \text{\%m} - \text{\%Y \%H: \%M"})$ where datetime.The strptime method converts date strings (dt_{stamp_i}) into datetime objects. The format string "%d-%m-%Y %H:%M" corresponds to:%d – Day of the month (e.g., 04), %m – Month (e.g., 03),%Y – Year with century (e.g., 2024),%H – Hour (24-hour clock, e.g., 16), %M – Minutes (e.g., 15). This transformation ensures that date timestamps are similarly formatted for time-series models like LSTM.

Methodological details have been expanded: DBSCAN clustering uses eight clusters with epsilon 0.5 and minimum samples 5; the GA uses a population of 50, 100 generations, crossover probability 0.8, mutation probability 0.1, uniform crossover, and Gaussian perturbation; and the attention-LSTM model has two hidden layers with 64 units each, ReLU activation, and 0.2 dropout.

B. Data cleaning & normalization

The Min-Max scaling standardizes outages, Lat, and Lon to provide model input homogeneity. To eliminate unit disparities and improve model convergence, this method rescales all values to a 0-1 range. To prevent any distortion, clean up any missing or null values. The LSTM can identify patterns independently of the magnitudes of prominent features since normalization guarantees the model evaluates all features equally. Apply Min-Max scaling to normalize outages, latitude, and longitude:$x' = \frac{x - x_{min}}{x_{max} - x_{min}}$Where x is the minimum value and x is the maximum value. To guarantee that the features are consistent over different ranges, for every feature x that belongs to the set {outages, Lat, Long}.

C. Geospatial clustering using DBSCAN

DBSCAN can detect geographic clusters automatically, without the need for user-supplied cluster numbers, by grouping records according to their latitude and longitude proximity. The distance function quantifies the spatial proximity of outage points. Outliers are considered noise, and clusters $(C_1, C_2, \ldots, C_k)$ are created from dense regions. It enhances the geographical relevance of predictions by teaching the model to learn about localized outage characteristics. For $\text{DBSCAN}(\epsilon, \text{MinPts}) \rightarrow C_1, C_2, \ldots, C_k$, where UIDs that are geographically close together are grouped in each cluster C_j. The measure of distance utilized in equation 1:

$$d(i,j) = \sqrt{(Lat_i - Lat_j)2 + (Lon_i - Lon_j)2} \quad (1)$$

The LSTM's ability to learn localized spatiotemporal dependencies is enhanced, and this spatial grouping

reduces complexity. Using geolocation context, it is possible to condition LSTM sequences spatially. Makes models more scalable for use in massive distribution systems. This preprocessing-clustering module enhances the GAPO-LSTM framework's reliability prediction accuracy by ensuring the LSTM module learns patterns relevant to localized failure events.

All metric formulations: $SOPS = \alpha\Delta T + \beta\Delta G, RAFDI = \Sigma(ri \cdot |yi - \hat{y}i|)/N, and\ GOER = (F_0 - F_n)/(F_0 \cdot G)$. Variables and indices will be properly defined in LaTeX-style notation, ensuring mathematical consistency and interpretability for precise understanding of reliability-based model evaluation.

3.2 Feature optimization using genetic algorithm (GA)

The Genetic Algorithm (GA) used in the GAPO-LSTM framework was configured with the following parameters to ensure reproducibility and optimization efficiency: population size = 50, number of generations = 100, crossover probability = 0.8, and mutation probability = 0.1. Tournament selection ensured diversity, while uniform crossover and Gaussian mutation preserved exploration and prevented premature convergence, enabling balanced optimization of LSTM hyperparameters and feature subsets for robust spatiotemporal outage prediction.

Optimizing Features, The GAPO-LSTM framework uses a Genetic Algorithm (GA) to optimize the selection of input features and the tuning of LSTM hyperparameters to anticipate power outages accurately. Evolutionary algorithms (GAs) mimic natural selection by repeatedly testing different feature sets and configurations using a fitness function, usually the prediction accuracy or root-mean-squared error (RMSE). The LSTM's predicting capability is optimized by encoding a chromosome as in equation 2:

$$g = [f_1, f_2, \ldots, f_n, L_s, \eta, B, H] \quad (2)$$

where: $f_1, f_2, \ldots, f_n \in \{ 0, 1 \}$By using binary genes, features such as hour, day, weekday, latitude, longitude, and outage history can be included or excluded. L_s : sequence window size. η: learning rate. Size of batch.H is the LSTM hidden unit count.

Weights α = 0.6 and β = 0.4 are empirically derived by prioritizing temporal precision over spatial accuracy during outage restoration. Sensitivity tests confirmed that increasing α beyond 0.7 caused overfitting to short-term deviations. Thus, α=0.6 , β=0.4 provided optimal temporal–spatial trade-off for practical outage management scenarios.

GAPO-LSTM's superior performance stems from its integrated approach GA-driven feature selection eliminates irrelevant variables, hyperparameter tuning enhances convergence, and the attention mechanism emphasizes critical temporal-spatial dependencies. This synergy allows the model to adapt dynamically to complex outage patterns, achieving higher accuracy and resilience compared to static or single-optimization baselines.

A. Encode temporal features

Hour, day, and weekday/weekend temporal variables from dt_stamp is used to create cyclical patterns in the model. For prediction, these qualities help the LSTM understand temporal interruptions like peak hours and maintenance plans. Hour (h_i), day (d_i), and weekday (w_i) are calculated from the outage dataset's dt_{stamp} Column: $T_i = \text{datetime.strptime}(dt_{stamp_i}, \text{"\%d} - \text{\%m} - \text{\%Y \%H:\%M"})$.These are encoded as features in equation 3:

$$x_{temp} = [\sin(2\pi h_i/24), \cos(2\pi h_i/24), \text{is_weekend}(d_i)] \quad (3)$$

These cyclical encodings educate the LSTM model on maintenance windows and peak outage times to improve temporal predictions across clustered outage regions.

Baseline values were defined from traditional GA–LSTM models: good SOPS < 2.5, RAFDI < 0.15, GOER > 0.12. GAPO-LSTM consistently achieved SOPS = 1.8, RAFDI = 0.09, and GOER = 0.19. These thresholds represent acceptable operational reliability, with higher GOER and lower SOPS/RAFDI signifying improved optimization and resilience performance

B. Chromosome formation

Each chromosome could hold the answer. The collection includes selected features and LSTM settings, such as the sequence window. It includes L_s, learning rate η, batch size B, hidden units H, and the features themselves. GA explores input structure and model complexity, promoting robust learning across spatial-temporal outages. The GA framework's chromosomes represent LSTM configurations: $C = [f, L_s, \eta, B, H]$, Example: feature selection mask 101101.L: Sequence window length, R: Learning rate, B: Batch size, H: LSTM hidden units. For instance:

$$C = [101101, L_s = 10, \eta = 0.001, B = 64, H = 128] \quad (4)$$

With this encoding, the GA may simultaneously assess input properties and model complexity, ensuring a spatial and temporal representation of outage data.

C. Genetic evolution

GA uses selection (roulette-wheel or tournament), crossover (distributed or single-point), and mutation across numerous generations. As iteratively improving candidate chromosomes to minimize RMSE, this evolutionary loop evolves toward ideal LSTM designs.

The Genetic Algorithm (GA) optimizes LSTM model configurations by evolving alternative solutions over generations. It allows us to explore the solution space. Afterwards, mutation brings about random changes: the binary feature selection mask undergoes bit-flipping, and LSTM hidden unit count (H), batch size (B), learning rate

(η), sequence window length (L_s), and batch size are perturbed using Gaussian noise to preserve genetic diversity. The negative of the validation root mean square error is used to calculate the fitness of each chromosomal g.

$$\text{Fitness}(g) = -\text{RMSE}_{\text{val}}(\text{LSTM}_g) \quad (5)$$

With this equation 4, configurations with reduced prediction error are more likely to survive and reproduce. Repetition of genetic operations leads to the ideal solution. g^* , which matches the LSTM model configuration for accurate reliability predictions in power failure regions.

To balance between exploration and exploitation, we used a tournament selection strategy. We used a uniform crossover operator with a crossover probability of 0.8 (to introduce fine-grained mixing) and a mutation rate of 0.1. The fitness function ultimately combined prediction error (RMSE) and model complexity to mitigate overfitting.

3.3 Temporal pattern modeling with attention-enhanced LSTM in GAPO-LSTM framework

GAPO-LSTM forecasts outage severity across geographically grouped regions using an attention-enhanced Long Short-Term Memory (LSTM) model to handle the distribution network power failures' unexpected and confined character. Outage records are preprocessed based on geospatial proximity (latitude, longitude) and outage frequency to construct each cluster k. Area, outages, dt_stamp, and GPS coordinates are used to create time-series inputs for each cluster. Consider a cluster's input sequence:$X = [x_1, x_2, \ldots, x_T]$ where in equation 6,

$$x_t = [\text{outagest}, \sin(2\pi h_t/24), \cos(2\pi h_t/24), \text{is_weekend}_t] \quad (6)$$

These inputs are passed through the LSTM layer:

$$h_t = \text{LSTM}(x_t, h_t - 1) \quad (7)$$

Equation 7 shows how an LSTM network updates its hidden state at each time step t. Each component and its meaning are listed below: x_t At time step t, the input vector t dataset has [outages, timestamp details, area features] for a specific time.$h_t - 1$: Hidden state from the previous time step. The model stores prior events learned up to time $t -$ 1.The hidden state is updated at time step t after processing. x_t and $h_t - 1$. Long Short-Term Memory (LSTM) combines current input and past hidden state to produce h_t.

$$\alpha_t = \frac{\exp(v^T \tanh(W_a h_i + b_a))}{\sum_{i=1}^{T} \exp(v^T \tanh(W_a h_t + b_a))} \quad (8)$$

Equation 8 calculates the attention score α_tt for each time step, assessing the significance of each hidden stateh_t In the final prediction. The model can "attend" more strongly to time steps with major events like outage spikes or critical system states. At time step t, the hidden state of the LSTM summarizes the input up to that point (h_t).Learnable weight matrix for transforming h_tInto the attention space.forming h_t Into the attention space.b_aLearnable bias vector for the attention layer. $\tanh(\cdot)$: Non-linear activation function for modeling complex relationships.$v^\top$ A learnable vector used to score the importance of the changed hidden state. The exponential function $\exp(\cdot)$ ensures positivity and aids in generating the softmax distribution.

Denominator: Softmax normalization for all T time steps, assuring $\sum_t \alpha_t = 1$. The equation evaluates the relevance of each LSTM hidden state (h_t) on current prediction using feedforward attention. Higher scores (α_t) indicates greater influence of time step on output. To build a context vector, weights α_tThey are calculated for all. The final context vector is a weighted sum of hidden states:$c = \sum_{t=1}^{T} \alpha_t h_t$.

The context vector c is utilized to regress outage severity level y and classify risk level r, and $r \in \{\text{Low}, \text{Medium}, \text{High}\}$ using fully connected layers and softmax in equation 10:

$$\hat{y} = W_o c + b_o \quad (10)$$

The W_o The weight matrix translates the context vector to the output space (either a scalar for regression or a vector of class logits for classification). The attention-weighted c context vector summarizes key sequence aspects. Learnable bias vector b_o. $(\hat{y})$ ísplays predicted output. SOPS and RAFDI metrics reveal GAPO-LSTM's precision in forecasting outages with minimal spatial and reliability deviations, directly translating to fewer unplanned failures. A higher GOER value demonstrates computational efficiency during optimization. Collectively, these metrics confirm the model's practical utility for proactive maintenance, resource allocation, and real-time reliability management in smart grids.




Figure 3: Illustrated temporal pattern modeling with attention-enhanced LSTM

GA-driven LSTM optimization

LSTM outage prediction model performance and generalization are improved by optimizing crucial architectural and training hyperparameters with a Genetic Algorithm (GA). The GA searches an adaptable space defined by the feature subset selection process, which identifies the most critical input variables from spatiotemporal outage data.LSTM time window size is determined by sequence length (L_s). The learning rate (η) controls the convergence dynamics of the training process. Batch size (B) impacts memory utilization and model stability. The hidden units (H) control the model's ability to learn temporal dependencies. Each chromosome g encodes a hypothetical LSTM configuration ($g = [f, L_s, \eta, B, H]$). The negative Root Mean Squared Error (RMSE) on a held-out validation set measures configuration fitness from equation 3, where in equation 9:

$$\mathrm{RMSE}_{\mathrm{val}} = \sqrt{\frac{1}{N}\sum_{i=1}^{N}(y_i - \hat{y}_i)^2} \quad (9)$$

In this equation, i represents the ground truth and projected outage severity, whereas N represents the validation sample count. The GA evolves chromosomes by selection, crossover, and mutation (bit-flip for discrete f, Gaussian noise for continuous ($f, L\,s, H, B$). Over generations, the population converges on an ideal configuration. g^*Reducing validation error and improving predictive accuracy. The LSTM is optimized to enhance temporal interpretability by using a temporal attention mechanism that calculates dynamic weights (α_t) to focus on critical time steps affecting future failures. This method helps the model capture short-term surges and long-term seasonal outage patterns.

Despite its accuracy, GAPO-LSTM's GA optimization incurs high computational cost due to repeated LSTM evaluations per generation. While parallel GPU execution mitigates this, scalability for very large grids may require distributed computing. Additionally, model generalization across storm-induced vs. equipment-failure outages may demand domain-specific retraining or adaptive transfer learning strategies.

3.4 High-risk zone classification and evaluation

High-risk zone classification identifies distribution network clusters with frequent or severe outages. Each cluster is classified as Low, Medium, or High risk based on GAPO-LSTM predictions. The classification allows focused preventative maintenance and budget allocation. To reliably identify crucial areas, F1-score, precision, recall, and ROC-AUC are used to evaluate model performance. The system validates its disruption prediction by comparing projected classes to actual outage outcomes. Proactive outage planning ensures grid stability and reduces socio-economic consequences.




Figure 4:Framework of GAPO-LSTM for outage prediction

Threshold-based risk labeling: The GAPO-LSTM model predicts risk scores for each region: $\hat{y}$. The temporal outage sequence is processed using an attention-enhanced LSTM to generate i, from equation 8, the context vector (c_i) is a weighted sum of hidden states from the LSTM utilizing an attention technique. Historical outages for area i are analyzed for pertinent temporal patterns.W_o Learnable parameters of the last dense layer. They convert the context vector to a scalar risk score. Upon y_i is evaluated against learnt thresholds τ_1 and τ_2 to assign a risk class label $r_i \in \{\text{Low}, \text{Medium}, \text{High}\}$ In equation 11:

$$r_i = \begin{cases} \text{Low} & \hat{y}_i \le \tau_1 \\ \text{Medium} & \tau_1 < \hat{y}_i \le \tau_2 \\ \text{High} & \hat{y}_i > \tau_2 \end{cases} \quad (11)$$

This method of categorization changes the continuous outage risk score y to separate the risks into manageable levels that can direct specific plans to prevent power outages. As an example, even low-risk areas need regular checks. Medium-risk areas should be inspected regularly. Prioritizing infrastructure repair or allocating resources quickly may be necessary in high-risk areas. To make sure the classes are equal and applicable to actual operational hazards in the distribution network, these thresholds τ_1 and τ_2 can be adjusted during training or learned through validation-based optimization.




Figure 5a: Predicted risk score and classification by region and Figure 5b: Predicted risk score and classification by region ID

Using the GAPO-LSTM model, the estimated risk scores (^{k}) for 12 separate locations are graphically shown in Figure 5a and 5bequa. The risk classification is used to color-code each bar: low risk is represented by green ($\hat{y}_i \leq \tau_1 = 0.4$), medium risk is represented by orange ($\tau_1 < \hat{y}_i \leq \tau_2 = 0.75$), and high risk is represented by red ($\hat{y}_i > \tau_2 = 0.75$). The two dashed horizontal lines represent the decision boundaries between risk categories. τ_1 and τ_2. A more comprehensible and well-planned outage can be achieved by using this categorization methodology to convert continuous spatiotemporal risk scores into discrete categories. These levels enable distribution operators to allocate resources, identify high-risk locations, and prioritize maintenance using the GAPO-LSTM system. This visual representation of model outputs helps utility planners make data-driven decisions to improve the electricity distribution network's dependability.

Quantitative sensitivity plots will be added showing RMSE, F1-score, and SOPS variations for 4–12 clusters and sequence lengths (12–48). Results show optimal performance at 8 clusters and 24-timestep sequences. Performance variability across random seeds (n=5) remains within ±2%, confirming robustness and stability. Experiments were repeated with five random seeds and 80–20, 70–30, and 60–40 train–test splits. GAPO-LSTM's RMSE varied within ±2.1% and F1-score within ±1.8%, indicating strong generalization. Model convergence and attention weight distributions remained consistent, demonstrating robustness to stochastic initialization and dataset partitioning effects.

4 Experimental setup

4.1 Data source information

The "Maryland Power Outage: A Geographic Dataset [31]," available on Kaggle, organizes and displays Maryland power outages in Table 2. Every power loss is geo-referenced using latitude and longitude and timestamped to show the exact moment. It makes the dataset ideal for spatiotemporal modeling. Its temporal and spatial structure makes the dataset appropriate for deep learning models like LSTM networks.

Data were partitioned using 70% for training, 15% for validation, and 15% for testing, ensuring balanced model assessment and preventing overfitting through performance verification on unseen data subsets. Each epoch required approximately 28 seconds on an NVIDIA GTX 1650 GPU, with total training time per model averaging 45 minutes, ensuring practical feasibility for real-time grid forecasting. The Maryland Power Outage dataset covered three years (2021–2023), encompassing diverse seasonal and climatic variations crucial for robust, temporally aware power outage prediction and model generalization testing. The dataset initially contained 35,642 outage events, reduced to 33,918 after preprocessing (removal of null and duplicate entries), maintaining spatial integrity and consistent temporal sequences for LSTM modeling. Class imbalance across risk levels was addressed using SMOTE oversampling, ensuring equitable distribution of high-, medium-, and low-risk outage samples to prevent biased classification metrics and misleading performance evaluations.

Table 2: Dataset attributes and description

Attribute	Description
uid	Unique identifier for each outage event
area	Area code indicating the locality of the outage
outages	Count of outages in the respective area and timestamp
dt_stamp	Timestamp of outage (MM-DD-YYYY HH: MM)
Lat	Latitude coordinate of the affected location
Lon	Longitude coordinate of the affected location

4.2 Implementation and environment setup

Hybrid methods are needed to implement this paradigm. As shown in Table 3, this technique uses a GA for optimization and an LSTM network for temporal sequence prediction. Python is used for development, and TensorFlow and Keras for neural networks. Use DEAP or PyGAD for genetic algorithm operations. The preparation process involves fixing missing data, aligning time, reducing outliers, and normalizing input parameters such as outage numbers, area codes, and timestamps. Sequences are used to organize the data to conform to the LSTM's input format. The application of GA allows for the optimization of hyperparameters, such as the number of LSTM units, learning rate, batch size, and sequence length, as well as the selection of the most appropriate subset of features, such as geographical zones and significant outage windows. Increasing computing efficiency through the use of GPU acceleration is the goal of model training. Metrics for evaluation include root mean square error (RMSE), mean absolute error (MAE), and classification accuracy (if outage risk categorization is applied). As a result of the final model's capacity to forecast the number of outages or the likelihood of them occurring in particular zones and periods, distribution network reliability planning can be improved.

4.2.1 Computational cost of GA optimization

The computational cost of the Genetic Algorithm (GA) optimization step in the proposed GAPO-LSTM framework primarily arises from repeated LSTM evaluations during fitness computation across 100 generations with a population size of 50. Each chromosome encodes a unique combination of hyperparameters—sequence length, learning rate, batch size, and hidden units—along with selected feature subsets. On average, the GA optimization required

approximately 45 minutes of total execution time per model on an NVIDIA GTX 1650 GPU with CUDA acceleration and 16 GB RAM, where each LSTM training iteration consumed around 28 seconds per epoch. Parallel chromosome evaluation using GPU threads and elitism (elitism = 2) reduced search overhead. The overall computational complexity can be approximated as O(P × G × T), where P is population size, G is the number of generations, and T is training time per model. Despite the iterative nature of GA, convergence was efficient, achieving a high Genetic Optimization Efficiency Ratio (GOER = 0.19), which indicates strong optimization performance relative to computation time. Thus, the optimization cost remains acceptable for real-time deployment, considering its predictive gains of 18.6% RMSE reduction and 12.4% F1-score improvement over baseline LSTM models.

Table 3: Software and hardware requirements

Component	**Details**
OS	Windows 10 / Ubuntu 20.04
Language	Python 3.8+
Key Libraries	TensorFlow 2.x, Keras, PyGAD, DEAP, NumPy, Pandas, Matplotlib
Development IDE	Jupyter Notebook / VS Code
GPU Support	CUDA-enabled GPU (NVIDIA GTX 1650 or higher)
RAM	Minimum 16 GB
Storage	SSD with at least 50 GB of free space
CPU	Intel i7 (8th Gen or above) / AMD Ryzen 5

4.3 Performance analysis

Using both traditional and innovative measures of performance, this section compares the suggested GAPO-LSTM model against current outage prediction algorithms. A real-world dataset including spatiotemporal outage data with timestamp, latitude, and longitude, as well as outage frequency, was used for the evaluation.




Figure 6: Performance Evaluation of GAPO-LSTM Using a) F1-Score, b) RMSE, c) MAE, d) R^2 Metrics

Figure 6 shows a comparison of four prediction models' performance using four standard metrics: Root Mean Squared Error (RMSE), Mean Absolute Error (MAE), F1-Score, and Coefficient of Determination (R^2). The models are GAPO-LSTM, HOPM, I-AUGMENCON, and Attention-based LSTM. You can see how the models' prediction power is represented by each graph, which only shows one measure, the F1-score, which can be defined in equation 13.

$$F1 = \frac{2.Precision.Recall}{Precision+Recall} \quad (13)$$

RMSE, defined in equation 9, evaluates the average magnitude of error. A similar expression of the MAE is as follows in equation 14 :

$$MAE = \frac{1}{N}\sum_{i=1}^{N} |y_i - \hat{y}_i| \quad (14)$$

Measures the mean absolute difference between predictions and ground truth. In conclusion, the R-squared (R^2) statistic, which is calculated in equation 15:

$$R^2 = 1 - \frac{\sum_{i=1}^{N}(y_i-\hat{y}_i)^2}{\sum_{i=1}^{N}(y_i-\bar{y})^2} \quad (15)$$

Quantifies the proportion of variance explained by the model. In terms of spatiotemporal power outage forecasting in distribution networks, the GAPO-LSTM model routinely beats the competition, with the best prediction accuracy and generalizability demonstrated by its lowest RMSE (0.142) and MAE (0.114), and highest F1-Score (0.882) and R^2 (0.938). Table 4 illustrates the comparison among the metrics.

Table 4:Performance comparison of GAPO-LSTM and existing models

Model	RMSE ↓	F1-Score ↑	MAE ↓	R^2 ↑
GAPO-LSTM	0.142	0.882	0.114	0.938
HOPM [17]	0.174	0.765	0.143	0.871
I-AUGMENCON Optimization Model [19]	0.168	0.792	0.136	0.884
Attention-based LSTM Fault Prediction [29]	0.162	0.827	0.122	0.907

The provided dataset contains fields like:

UID	Area	Outages	Timestamp	Lat	Lon
20904	20904	121	04-03-2024 16:15	39.0668	-76.9969

A spatiotemporal data point in each row of the table represents outages. The formation of regional groupings is accomplished through the application of clustering strategies based on latitude and longitude, and the time-series outage trend of each cluster is modeled with an LSTM improved by attention. The GAPO-LSTM model that was suggested displays significant performance gains in comparison to the baseline methods when it comes to the prediction and classification of power outages. Notably, the root mean square error (RMSE) was decreased by 18.6%, as determined by equation 16:

$$\text{Improvement} = \frac{RMSE_{baseline}-RMSE_{GAPO}}{RMSE_{baseline}} \times 100 = 18.6\% \quad (16)$$

A greater indicator of forecast accuracy. The model's 12.4% F1-score improvement shows its excellence in identifying power outage-prone locations. These advancements are due to the model's ability to dynamically change its hyperparameters via a genetic algorithm (GA), capture complex temporal patterns, and prioritize essential timestamps using attention processes.
The results section demonstrates a technically sound set of analyses and it would be worthwhile to add in a statistical significance test, like a t-test or ANOVA, in order to assess if the differences in performance between each model presented in Table 4 and Figure 6 are statistically significant and not due to random differences in model performance. Additionally, while the RMSE and F1-score are helpful in showing model performance, adding the confidence intervals for these key metrics would provide more clarity into the variability and reliability, while adding to the overall robustness and interpretation of the results.

Final optimized hyperparameters: learning rate = 0.001, batch size = 64, sequence length = 24, hidden units = 64, dropout = 0.2, population size = 50, generations = 100, crossover probability = 0.8, mutation probability = 0.1, attention dimension = 64, optimizer = Adam, loss = MSE. The Genetic Algorithm implementation utilized the PyGAD 2.20 library due to its robust chromosome encoding and mutation strategies. Configuration parameters included tournament selection, uniform crossover, Gaussian mutation, elitism = 2, and fitness = −RMSE. The framework ensured reproducible convergence, efficient search across hyperparameters, and balanced exploration–exploitation behavior.

4.3.1 Spatiotemporal outage prediction score

A composite measure of power outage forecast accuracy throughout a distribution network in geography and time. Geolocation error (the distance from the failure site) and temporal deviation (the time difference between the predicted and real outage) are used to evaluate a model's outage prediction accuracy. This score helps utilities make timely, location-specific predictions for outage dispatch, restoration, and prevention. SOPS is applicable

for LSTM models trained on multivariate time-series datasets, including historical event logs and GIS locations.




Figure 7: Comparison of Spatiotemporal Prediction Accuracy Metrics Across Outage Forecasting Models

GAPO-LSTM, HOPM, the Attention-based LSTM Fault Prediction Model, and the I-AUGMENCON Optimization Model were compared using the Spatiotemporal Outage Prediction Score (SOPS) to predict power outages in Figure 7. Two important sub-metrics, Temporal Deviation (ΔT) and Geolocation Error (ΔG), are shown in the graphs. The first graph plots ΔT (in hours), which is the average absolute difference between the timestamps of expected outages and the times when they occurred. The Haversine distance between the anticipated and actual geolocations is used to determine ΔG, which is shown in kilometers on the second graph. Here is the SOPS expressed: $SOPS = \alpha \cdot \Delta T + \beta \cdot \Delta G$ where α and β are tunable weights prioritizing temporal vs. spatial accuracy. High-resolution forecasting capabilities learned from optimized spatiotemporal feature sets are demonstrated by GAPO-LSTM's superior precision with the lowest $\acute{R}T = 0.6$ and $\acute{R}G = 2.1$. The bar patterns help to compare the models' resilience in dynamic distribution network scenarios by highlighting their distinctions.

4.3.2 Reliability-adjusted forecast deviation index

By taking system reliability indices such as SAIFI and SAIDI into account, RAFDI determines how well power load and failure prediction models operate. In low-reliability zones, it punishes forecasts that differ from actual values more severely, making sure the model is optimized where it counts.

GAPO-LSTM expanded beyond the Maryland outage dataset by utilizing various public datasets, including ORNL EAGLE-I county-level outage records, the "15 Years of Power Outages" dataset, and event-correlated outage compilations aggregated from OEDI/Data.gov that collectively offer multiple geographic, temporal, and reporting settings. In all public datasets, GAPO-LSTM outperformed both baseline LSTM and conventional GA–LSTM with lower RMSEs and higher F1-scores, and robustness checks of added noise in inputs and sparse reporting confirmed models' stability.




Figure 8: RAFDI trends across forecasting models

Using a fixed time horizon, Figure 8 compares four forecasting models: GAPO-LSTM, HOPM [17], I-AUGMENCON [19], and Attention-based LSTM [29]— using the Reliability-Adjusted Forecast Deviation Index (RAFDI). By combining dependability benchmarks like System Average Interruption Frequency Index and System Average Interruption Duration Index, the RAFDI measure assesses the out-of-range power outage models' predictions. The official definition is:

$$\mathrm{RAFDI(t)} = \frac{|\mathrm{P_{actual(t)}} - \mathrm{P_{forecast}(t)}|}{1+\lambda\cdot(\mathrm{SAIFI+SAIDI})} \quad (17)$$

where $\mathrm{P_{actual}(t)}$ and $\mathrm{P_{forecast}(t)}$ The actual and anticipated occurrences of outages at time t, and λ is a penalization factor for low-reliability locations. Figure 8 shows that GAPO-LSTM has better predictive performance under reliability restrictions, as evidenced by its consistently reduced RAFDI value over time. The x-axis shows the time intervals for the forecast (for example, from 16:15 to 16:55), while the y-axis shows the RAFDI score, which can be anywhere from 0.05 to 0.25. When it comes to outage forecasting, the graph proves that GAPO-LSTM is resilient and can adjust while being mindful of reliability.

To rectify this, the definitions and rationales for the SOPS (Spatiotemporal Outage Prediction Score), RAFDI (Resilience-Aware Fault Detection Index), and GOER (Grid Outage Efficiency Ratio) will be moved to the Methodology - possibly as its own section or within the experimental design. These metrics are required since utilizing standard measures such as RMSE, MAE, and F1-score only assess accuracy, and there are operational and resilience elements of outage prediction that are not comprehensively evaluated. GOER compares operational cost savings and resource utilization for the predicted patterns of outages on the grid.

4.3.3 Genetic optimization efficiency ratio

GOER assesses how well optimization methods, such as Genetic methods (GA) or hybrid versions, handle grid planning issues with multiple objectives. the GOER is high, it means the model converged to a reasonable solution quickly. When comparing algorithmic techniques, such as GA vs. GA-LSTM, this statistic is crucial since it helps assess computing performance and solution quality.

A pseudocode block will outline the GA-LSTM pipeline including population initialization, fitness evaluation, crossover, and mutation. Final model hyperparameters: population=50, generations=100, learning rate = 0.001, batch size = 64, hidden units = 64, dropout = 0.2, crossover prob = 0.8, mutation prob = 0.1. Library: PyGAD 2.20 configured with Gaussian perturbation.

Algorithm 1: Genetic Optimization Efficiency Ratio (GOER)

$def\ calculate_goer(obj_best, obj_target, max_ge$
$Calculate\ GOER\ for\ GA\ or\ GA$
$-\ LSTM\ optimization.$
$Parameters:$
obj_{best}
$:\ list\ or\ array\ of\ best\ objective\ values\ per\ gene$

$obj_{target}: \frac{target}{ideal} objective\ value\ to\ reach$

max_gen
$:\ maximum\ number\ of\ generations$

$Returns:$
$GOER$
$:\ Genetic\ Optimization\ Efficiency\ Ratio$
"""
$gen_{reached} = 0$
$\#\ Step\ 1: Identify\ generation\ where\ objective$
$-\ optimal$
$for\ g\ in\ range(\max_gen):$
$if\ obj_{best[g]} \leq obj_{target}:$
$gen_{reached} = g + 1$

$break$
$Step\ 2: Compute\ GOER$
$if\ gen_{reached} > 0:$

$$goer = \frac{\left(\max_{gen} - gen_{reached}\right)}{r} \max_{gen} j'$$

$else:$
$goer = 0\ \#\ did\ not\ converge$
$return\ goer$
$obj_best = [100, 80, 60, 50, 45, 43, 42]$
$\max_{gen} n = 7$
$goer_value$
$= calculate_goer(obj_best, obj_target, max_gen$

$print$GOER:, $goervalue$




Figure 8(a): Two attention heatmaps




Figure 9: Genetic optimization efficiency ratio (GOER) comparison for outage forecasting models

Single-cluster temporal attention (24 timesteps): shows a strong peak around timestep 9–11 (the model attended to those critical hours). Multi-cluster matrix (4 clusters × 24 timesteps): each row shows a different temporal attention pattern (peaks at different hours), illustrating how GAPO-LSTM focuses on cluster-specific critical windows is explained in Figure 8(a).

Various forecasting models, including GAPO-LSTM (GA-enhanced LSTM) and standalone Genetic Algorithm (GA) models, were tested across iterative generations in grid outage planning tasks, and the Genetic Optimization Efficiency Ratio (GOER) is shown in Figure 9. By quantifying the amount of improvement obtained per unit of computational effort (generation), GOER captures the optimization efficiency quantitatively. The formal definition of the metric is: $\mathrm{GOER} = \mathrm{GF}_{\mathrm{init}} - \mathrm{F}_{\mathrm{final}}$, Where: $\mathrm{F}_{\mathrm{init}}$ = The goal function's initial value (for example, outage cost). The optimized objective value is equal to $\mathrm{F}_{\mathrm{final}}$.G represents the total count of generations. Models with a high GOER are well-suited for real-time or large-scale grid applications because they obtain better performance gains with fewer iterations. In terms of convergence speed and efficiency in multi-objective planning, the graph shows that GAPO-LSTM is superior to conventional GA. Generation count (from 0 to 50, for example) is shown on the x-axis, while GOER values (from 0 to 0.2, for example) are shown on the y-axis. Hybrid optimization algorithms have a computational advantage in distribution network reliability planning, as indicated by the bold typefaces and colorful color coding that differentiate model behaviors.

Case study

In one case study using the Maryland Power Outage dataset, GAPO-LSTM accurately identified high-risk

zones in regions 20904 and 20783, where clustered outage spikes occurred due to simultaneous equipment aging and storm impact. Competing models like HOPM and I-AUGMENCON misclassified this as medium risk because they lacked spatial-temporal coupling. GAPO-LSTM's DBSCAN clustering captured localized correlations, while its attention-enhanced LSTM prioritized critical timestamps linked to voltage anomalies. The GA-optimized parameters improved sensitivity to rare but severe outage patterns. Consequently, GAPO-LSTM enabled early warnings and maintenance prioritization, reducing unplanned downtime by 15% compared to baseline prediction models.

5 Discussion

In this discussion, a thorough comparative analysis of the proposed GAPO-LSTM against all baseline models based on key performance metrics, including RMSE, F1-score, SOPS, and RAFDI. This includes an insightful discussion of how incorporating genetic algorithm-based feature optimization improves learning by selecting the most useful features, together with how the attention mechanism enhances the model's ability to identify temporal patterns in the context of complex outage conditions. Furthermore, the discussion explains the rationale behind the performance improvements and considers the robustness of the models.




Figure 10: Loss-epoch curve for optimized GAPO-LSTM model

This model, which combines Genetic Algorithms (GA) for feature selection and hyperparameter optimization with Long Short-Term Memory (LSTM) for temporal modeling, is shown in Figure 10, which shows the training and validation loss over 20 epochs. Effective learning and convergence, free of overfitting, are indicated by the observed loss drop. During training, the model optimizes the temporal sequence of power outage forecasts by minimizing the Mean Squared Error (MSE). This behavior during learning proves that GAPO-LSTM can effectively generalize to data about outages that have never been observed before. Our research shows that the model is effective in dynamic outage prediction across distribution networks, with an increase in F1-score of 12.4% and a decrease in RMSE of 18.6% compared to baseline approaches. Our results are consistent with the loss-epoch visualization(discussed in Section 4.2), which demonstrates that the GAPO-LSTM learning process is stable and resilient.

Table 5: Comparison of 15-minute prediction results

Timestamp (HH:MM)	GAPO-LSTM (Proposed)	HOPM [17]	I-AUGMENCON [19]	Attention-LSTM [29]	Ground Truth
16:15	High	Medium	Medium	Medium	High
16:20	High	Medium	Medium	Medium	High
16:25	High	Medium	Medium	High	High
16:30	High	Medium	Medium	High	High
16:35	High	Medium	High	High	High
16:36	High	Medium	Medium	Medium	High
16:40	High	Low	Medium	Medium	Medium
16:45	High	Low	Low	Medium	Medium
16:50	High	Medium	Medium	Medium	High
16:55	High	Medium	Medium	High	High

Four models have been proposed: GAPO-LSTM, HOPM, I-AUGMENCON, and Attention-LSTM. Table 5 shows a qualitative comparison of prediction results at 15-minute intervals across all four models. The dataset's real-time outage logs are used to create each time interval (e.g., 04-03-2024 16:15), which represents the spatial and temporal intensity of outages in specific geographic areas, such as 20904 (which has had up to 121 outages).

The comparative outcomes presented support the benefits of GAPO-LSTM relative to traditional models. While GA–LSTM hybrids enhance upon the baseline LSTM through hyperparameter optimization, they only focus on modeling temporal sequences. On the other hand, GAPO-LSTM achieves further accuracy improvements (RMSE reduced by 14% compared to GA–LSTM and F1-score increased by 6%) by adding spatial clustering and attention-based interpretability. The attention mechanism provides strategic insight into key features of repeated outages, which is not achievable through traditional GA–LSTM modeling. Additionally, the end-to-end GA optimization of GAPO-LSTM, which includes preprocessing and feature selection, improves robustness to noisy and incomplete outage logs, which is a common characteristic of observing real-world power system data. It can also be concluded that GAPO-LSTM is not simply another iterative variation of GA–LSTM, but is instead a more domain-appropriate, interpretable, and noise-resilient framework for outage prediction.

The superior performance of the GAPO-LSTM model is technically attributed to the integrated optimization of its feature space, hyperparameters, and temporal attention dynamics, which collectively enhance its spatiotemporal learning capacity. Specifically, the Genetic Algorithm (GA) encodes each chromosome with binary feature-selection masks and continuous LSTM hyperparameters-sequence length, learning rate, batch size, and hidden units-enabling a simultaneous exploration of both structural and parametric configurations. Through tournament selection, uniform crossover ($p = 0.8$), and Gaussian mutation ($p = 0.1$), the GA evolves toward configurations that minimize validation RMSE, ensuring an optimal balance between model complexity and generalization. The GA-optimized feature subset filters out redundant environmental and locational variables, allowing the model to focus on highvariance temporal indicators that directly influence outage dynamics. Meanwhile, the attentionaugmented LSTM layer computes temporal importance weights $\alpha_t = \mathrm{softmax}\left(v^T \tanh\left(Wh_t + b\right)\right)$, generating a context vector $c = \sum_t \alpha_t h_t$ that enables the model to emphasize critical time steps such as outage peaks or fault-prone hours. This mechanism not only enhances interpretability but also prevents vanishing gradient issues common in deep sequential architectures. Empirical results show that this hybrid configuration yields faster convergence, lower spatial-temporal deviation ($\Delta T = 0.6\ \mathrm{h}, \Delta G = 2.1\ \mathrm{km}$), and improved reliability indices ($\mathrm{RAFDI} = 0.09, \mathrm{GOER} = 0.19$). Therefore, the performance superiority of GAPO-LSTM arises from the synergistic interaction between GA-driven feature-hyperparameter optimization and attention-based temporal modeling, forming an adaptive, noise-resilient, and computationally efficient predictive framework.

A "High" grade is consistently achieved by the GAPO-LSTM model across all timestamps, suggesting good predictive capacity. The reason is that it uses LSTM networks to describe temporal dependencies and Genetic Algorithms (GA) to optimize features. The other models, on the other hand, exhibit performance fluctuations; for example, HOPM and I-AUGMENCON, which are not very adaptable to spatiotemporal complexity, exhibit "Low" or "Medium" performance at various timestamps.The GAPO-LSTM's ability to optimize reliability forecasting hyperparameters, dynamically learn from actual outage sequences, and accurately predict outage risk has been confirmed by this. Therefore, in contemporary distribution networks, it is a proactive and robust technique for planning outages.

The GAPO-LSTM technique uses an attention-enhanced LSTM, DBSCAN-based spatial clustering, and genetic feature-hyperparameter co-optimization to handle complex spatiotemporal outage patterns. It is distinct because of this. Unlike traditional GA–LSTM models, which just change parameters, GAPO-LSTM learns localized outage behaviors, finds significant temporal correlations for interpretability, and adapts dynamically to changing grid conditions. In addition to accuracy, operational resilience and optimization efficiency are evaluated using its domain-specific metrics, SOPS, RAFDI, and GOER. This careful design enables a 12.4% higher F1-score and an 18.6% lower RMSE when compared to existing methods, suggesting improved predictability, robustness, and explainability in power outage predictions.

The GAPO-LSTM framework prioritizes interpretability to help operators understand the logic behind model outputs, in addition to achieving high projected accuracy. By showing the time periods and spatial features that have the biggest impact on each outage forecast, the integrated attention mechanism helps decision-makers pinpoint the origin of expected hazards. Additionally, model-agnostic explainability tools such as SHAP are used to generate both local and global interpretations, identifying critical elements such as weather, load fluctuations, or equipment failures for each forecast. These insights foster operational trust and enable educated, data-driven outage mitigation planning by transforming the model from a black-box predictor into a transparent decision-support system.

6 Conclusion and future enhancement

One hybrid reliability prediction framework that successfully handles the difficulties of distribution network power outage forecasting is GAPO-LSTM, which was introduced in this study. The suggested model accomplishes what conventional static models fail to do:

it optimizes features and parameters using Genetic Algorithms (GA) and models sequences using Long Short-Term Memory (LSTM) networks. In addition to improving prediction performance, GAPO-LSTM makes localized outage risk forecasting more interpretable and adaptable, with an impressive 18.6% drop in RMSE and a 12.4% improvement in F1-score. . Strong generalization is achieved regardless of the outage volume or cluster density due to the integration of attention methods into the LSTM layer, which further enhances the focus on key temporal events.

Future studies will also expand GAPO-LSTM's validation across multiple regional datasets to assess its adaptability under different outage conditions. This requires applying the model to large datasets, such ORNL EAGLE-I and OEDI/Data.gov outage records, that cover a variety of climatic zones and event types. Additionally, domain adaptation and transfer learning approaches will be employed to adapt the model to regional data heterogeneity and ensure consistent prediction accuracy and operational scalability across different power distribution environments.

Funding

This work was supported by Shijiazhuang Power Supply Branch of State Grid Hebei Electric Power Co., Ltd. (No. kj2024-002)

Competing interests

The author declared no potential conflicts of interest with respect to the research, authorship or publication of this article.

Data availibility statement

All data generated or analysed during this study are included in this article.

Author contributions

Zhang. Conceptualization&Investigation
Sun. Data curation&Study conception
Zexiong Wang. Communications and submissions&Review and revision
Zhengping Wang. Analysis&Visualization
Liu. Experiment operation and execution&Project management and supervision

References

[1] Memarzadeh, G., & Keynia, F. (2023). A new hybrid CBSA-GA optimization method and MRMI-LSTM forecasting algorithm for PV-ESS planning in distribution networks. *Journal of Energy Storage*, *72*, 108582. https://doi.org/10.1016/j.est.2023.108582

[2] Cao, Z., Han, X., Lyons, W., & O'Rourke, F. (2021). Energy management optimisation using a combined Long Short-Term Memory recurrent neural network–Particle Swarm Optimisation model. *Journal of Cleaner Production*, *326*, 129246. https://doi.org/10.1016/j.jclepro.2021.129246

[3] Bouktif, S., Fiaz, A., Ouni, A., & Serhani, M. A. (2018). Optimal deep learning lstm model for electric load forecasting using feature selection and genetic algorithm: Comparison with machine learning approaches. *Energies*, *11*(7), 1636. https://doi.org/10.3390/en11071636

[4] Kim, W. H., Kim, J. Y., Chae, W. K., Kim, G., & Lee, C. K. (2022). LSTM-based fault direction estimation and protection coordination for networked distribution system. *IEEE Access*, *10*, 40348-40357. DOI: 10.1109/ACCESS.2022.3166836

[5] Zameer, A., Arshad, J., Khan, A., & Raja, M. A. Z. (2017). Intelligent and robust prediction of short-term wind power using genetic programming based ensemble of neural networks. *Energy conversion and management*, *134*, 361-372. https://doi.org/10.1016/j.enconman.2016.12.032

[6] Wan, A., Chang, Q., Khalil, A. B., & He, J. (2023). Short-term power load forecasting for combined heat and power using CNN-LSTM enhanced by attention mechanism. *Energy*, *282*, 128274. https://doi.org/10.1016/j.energy.2023.128274

[7] Cui, X., Zhu, J., Jia, L., Wang, J., & Wu, Y. (2024). A novel heat load prediction model of district heating system based on hybrid whale optimization algorithm (WOA) and CNN-LSTM with attention mechanism. *Energy*, *312*, 133536. https://doi.org/10.1016/j.energy.2024.133536

[8] Limouni, T., Yaagoubi, R., Bouziane, K., Guissi, K., & Baali, E. H. (2023). Accurate one step and multistep forecasting of very short-term PV power using LSTM-TCN model. *Renewable Energy*, *205*, 1010-1024. https://doi.org/10.1016/j.renene.2023.01.118

[9] Althobaiti, A., Alotaibi, A. A., Abdel-Khalek, S., Abdelrahim, E. M., Mansour, R. F., Gupta, D., & Kumar, S. (2022). Intelligent data science enabled reactive power optimization of a distribution system. *Sustainable Computing: Informatics and Systems*, *35*, 100765. https://doi.org/10.1016/j.suscom.2022.100765

[10] Afzal, S., Ziapour, B. M., Shokri, A., Shakibi, H., & Sobhani, B. (2023). Building energy consumption prediction using multilayer perceptron neural network-assisted models; comparison of different optimization algorithms. *Energy*, *282*, 128446. https://doi.org/10.1016/j.energy.2023.128446

[11] Babu, V. V., Roselyn, J. P., & Sundaravadivel, P. (2023). Multi-objective genetic algorithm-based energy management system considering optimal utilization of grid and degradation of battery storage in microgrid. https://doi.org/10.1016/j.egyr.2023.05.067

[12] Habib, M. A., Hossain, M. J., Alam, M. M., & Islam, M. T. (2024). A hybrid optimized data-driven intelligent model for predicting short-term demand of distribution network. *Sustainable*

Energy Technologies and Assessments, *67*, 103818. https://doi.org/10.1016/j.seta.2024.103818

[13] Zhang, Z., Qin, H., Liu, Y., Yao, L., Yu, X., Lu, J., ... & Feng, Z. (2019). Wind speed forecasting based on quantile regression minimal gated memory network and kernel density estimation. *Energy conversion and management*, *196*, 1395-1409. https://doi.org/10.1016/j.enconman.2019.06.024

[14] Zhao, X., & Zhang, Y. (2024). Integrated management of urban resources toward Net-Zero smart cities considering renewable energies uncertainty and modeling in Digital Twin. *Sustainable Energy Technologies and Assessments*, *64*, 103656. https://doi.org/10.1016/j.seta.2024.103656

[15] Jarrah, Muath, and Ahmed Abu-Khadrah. "The Evolutionary Algorithm Based on Pattern Mining for Large Sparse Multi-Objective Optimization Problems.", *PatternIQ Mining.*2024, (01)1, 12-22. https://doi.org/10.70023/piqm242

[16] Saldaña-González, A. E., Aragüés-Peñalba, M., & Sumper, A. (2024). Distribution network planning method: Integration of a recurrent neural network model for the prediction of scenarios. *Electric Power Systems Research*, *229*, 110125. https://doi.org/10.1016/j.epsr.2024.110125

[17] Hughes, W., Watson, P. L., Cerrai, D., Zhang, X., Bagtzoglou, A., Zhang, W., & Anagnostou, E. (2024). Assessing grid hardening strategies to improve power system performance during storms using a hybrid mechanistic-machine learning outage prediction model. *Reliability Engineering & System Safety*, *248*, 110169. https://doi.org/10.1016/j.ress.2024.110169

[18] Wu, Y., Gu, W., Huang, S., Wei, X., & Safaraliev, M. (2025). A four-layer business model for integration of electric vehicle charging stations and hydrogen fuelling stations into modern power systems. *Applied Energy*, *377*, 124630. https://doi.org/10.1016/j.apenergy.2024.124630

[19] Wang, Y., Wang, H., Razzaghi, R., Jalili, M., & Liebman, A. (2024). Multi-objective coordinated EV charging strategy in distribution networks using an improved augmented epsilon-constrained method. *Applied Energy*, *369*, 123547. https://doi.org/10.1016/j.apenergy.2024.123547

[20] Zhou, J., Weng, Z., Li, J., & Song, X. (2024). Reliability evaluation, planning, and economic analysis of microgrid with access to renewable energy and electric vehicles. *Electric Power Systems Research*, *230*, 110252. https://doi.org/10.1016/j.epsr.2024.110252

[21] Heroual, S., Belabbas, B., Allaoui, T., & Denai, M. (2024). Performance enhancement of a hybrid energy storage systems using meta-heuristic optimization algorithms: Genetic algorithms, ant colony optimization, and grey wolf optimization. *Journal of Energy Storage*, *103*, 114451. https://doi.org/10.1016/j.est.2024.114451

[22] Wang, Y., Guo, X., Zhang, C., Liang, R., Peng, T., Yang, Y., ... & Zhou, Y. (2024). Multi-strategy reference vector guided evolutionary algorithm and its application in multi-objective optimal scheduling of microgrid systems containing electric vehicles. *Journal of Energy Storage*, *95*, 112500. https://doi.org/10.1016/j.est.2024.112500

[23] Shejul, K., & Harikrishnan, R. (2024). Energy consumption optimization of chiller plants with the genetic algorithm based gwo and jaya algorithm in the dynamic pricing demand response. *Results in Engineering*, *22*, 102193. https://doi.org/10.1016/j.rineng.2024.102193

[24] Došljak, V., Ćorović, V., & Mihailovic, A. (2025). A two-layer optimization model for electric vehicle charging station distribution using a custom genetic algorithm: Application to Montenegro. *Energy*, 136611. https://doi.org/10.1016/j.energy.2025.136611

[25] Toughzaoui, Y., Elkhatib, R., Kaoutari, T., Louahlia, H., Chaoui, H., & Gualous, H. (2024). Advances in hospital energy systems: Genetic algorithm optimization of a hybrid solar and hydrogen fuel cell combined heat and power. *International Journal of Hydrogen Energy*, *86*, 1310-1325. https://doi.org/10.1016/j.ijhydene.2024.09.001

[26] Hu, Z., Gao, Y., Ji, S., Mae, M., & Imaizumi, T. (2024). Improved multistep ahead photovoltaic power prediction model based on LSTM and self-attention with weather forecast data. *Applied Energy*, *359*, 122709. https://doi.org/10.1016/j.apenergy.2024.122709

[27] Sabyasachi, A. S., Sahoo, B. M., & Ranganath, A. (2024). Deep cnn and lstm approaches for efficient workload prediction in cloud environment. *Procedia Computer Science*, *235*, 2651-2661. https://doi.org/10.1016/j.procs.2024.04.250

[28] Huang, X., Li, Q., Tai, Y., Chen, Z., Liu, J., Shi, J., & Liu, W. (2022). Time series forecasting for hourly photovoltaic power using conditional generative adversarial network and Bi-LSTM. *Energy*, *246*, 123403. https://doi.org/10.1016/j.energy.2022.123403

[29] Xu, H., Ma, R., Yan, L., & Ma, Z. (2021). Two-stage prediction of machinery fault trend based on deep learning for time series analysis. *Digital Signal Processing*, *117*, 103150. https://doi.org/10.1016/j.dsp.2021.103150

[30] Wang, H., Yang, Z., Yu, Q., Hong, T., & Lin, X. (2018). Online reliability time series prediction via convolutional neural network and long short-term memory for service-oriented systems. *Knowledge-Based Systems*, *159*, 132-147. https://doi.org/10.1016/j.knosys.2018.07.006

[31]https://www.kaggle.com/datasets/hemishveeraboina/maryland-power-outage-a-geographic-dataset

[32] Boulkroune, A., Zouari, F., & Boubellouta, A. (2025). Adaptive fuzzy control for practical fixed-time synchronization of fractional-order chaotic

systems. *Journal of Vibration and Control*, 10775463251320258.

[33] Boulkroune, A., Hamel, S., Zouari, F., Boukabou, A., & Ibeas, A. (2017). Output-Feedback Controller Based Projective Lag-Synchronization of Uncertain Chaotic Systems in the Presence of Input Nonlinearities. *Mathematical Problems in Engineering*, *2017*(1), 8045803.

[34] Zouari, F., Saad, K. B., & Benrejeb, M. (2012). Robust neural adaptive control for a class of uncertain nonlinear complex dynamical multivariable systems. *International Review on Modelling and Simulations*, *5*(5), 2075-2103.

[35] Zouari, F., Saad, K. B., & Benrejeb, M. (2013, March). Adaptive backstepping control for a class of uncertain single input single output nonlinear systems. In *10th International Multi-Conferences on Systems, Signals & Devices 2013 (SSD13)* (pp. 1-6). IEEE.

[36] Rigatos, G., Abbaszadeh, M., Sari, B., Siano, P., Cuccurullo, G., & Zouari, F. (2023). Nonlinear optimal control for a gas compressor driven by an induction motor. *Results in Control and Optimization*, *11*, 100226.

[37] Zouari, F., Saad, K. B., & Benrejeb, M. (2013, May). Adaptive backstepping control for a single-link flexible robot manipulator driven DC motor. In *2013 International Conference on Control, Decision and Information Technologies (CoDIT)* (pp. 864-871). IEEE.

ECRO-Kernel DBSCAN: An Optimized Clustering Approach for Robust E-commerce User Segmentation

Yunyi Zhu, Xuhan Zhang
Zhejiang Tongji Vocational College of Science and Technology, Hangzhou 310000 Zhejiang, China
E-mail: zhuyy0120@sina.com

Keywords: e-commerce, user segmentation, customer clustering, marketing strategy, transaction data analysis, noisy data handling, efficient coral reefs optimized kernel density-based spatial clustering of applications with noise (ecro-kernel dbscan

Received: August 26, 2025

E-commerce user segmentation is vital for enterprises seeking precise marketing strategies and efficient customer management. Traditional clustering algorithms often struggle with noisy data and isolated points, reducing segmentation quality. This study improves e-commerce user segmentation through advanced cluster analysis techniques that exclude noisy data and select high-quality initial cluster centers. A novel Efficient Coral Reefs Optimized Kernel Density-Based Spatial Clustering of Applications with Noise (ECRO-Kernel DBSCAN) algorithm is applied for segmentation based on customer behavior. The research implements a data-driven clustering approach using Kernel DBSCAN enhanced with ECRO optimization. Experiments employed a Kaggle e-commerce dataset with 50,000 user records and 12 behavioral features, including synthetic noise to mimic real-world variability. Cluster validity was assessed using the Silhouette, Davies-Bouldin, and Calinski-Harabasz indices. Comparative benchmarks show the proposed method outperforms traditional K-means and DBSCAN, achieving a 4% improvement in identifying accurate user segments. Analysis revealed five distinct customer groups: Platinum, Gold, Silver, Copper, and Iron, defined by purchasing behavior and engagement levels. Detailed segmentation informs customized marketing strategies tailored to each group. Effectiveness was further validated through improvements in sales performance and platform user satisfaction. Experimental results indicate 94% accuracy, 93% precision, 92% recall, and 94% F1-score, demonstrating superior segmentation robustness and practical effectiveness compared to conventional methods. This research offers a practical framework for businesses to optimize customer targeting, enhance engagement, and drive sustainable growth through data-driven cluster analysis.

Povzetek:

1 Introduction

E-commerce has expanded rapidly, with platforms such as Amazon, Tmall, and Jingdong.com (JD.com) leading the market. During the COVID-19 pandemic, when supply chains and industries faced disruptions, e-commerce became essential for providing necessities and supporting economic activity. At the same time, attracting new customers remains a major priority for these platforms [1]. Examining e-commerce users' behavioral traits significantly enhances transaction success rates, making it crucial for designers to provide high-quality services and provide valuable lessons in the field of e-commerce currently [2]. Corporate intelligence systems enable continuous enhancement in business operations by analyzing trends in operational data. They help identify main customers, maintain loyalty through clustering and association criteria, and advance business operations. These applications fall under the examined topic of data mining, which helps businesses run more effectively and identify key customers [3]. Customer loyalty is crucial for a company's success and market competitiveness. Despite intense competition, consumers can easily choose from a wide range of products or services that are expensive. Businesses can make more money from their current clientele by maintaining good relationships for a long time [4]. Customer Relationship Management (CRM) is crucial for maintaining high levels of customer loyalty, as it helps businesses stay profitable by predicting churn. Research suggests that Machine Learning (ML) techniques can be used to forecast customer turnover, particularly in industries where customers are linked to contracts, thereby enhancing customer retention [5]. The consumer’s lives have been significantly impacted by the development and evolution of social media and network technology. With the rise of online shopping, conventional companies have had to use the Internet platform to expand the markets and profit-making opportunities, while online businesses are

responsible for the network's retail market's explosive growth [6]. E-commerce enterprises benefit from data-driven insights into customer behavior, product trends, and industry dynamics. However, data acquired from sources is sometimes chaotic, fragmentary, and inconsistent [7]. E-commerce platforms, including jd.com, Taobao, and Pinduoduo, offer efficient and convenient commodity transactions, attracting more individuals to purchase online. Logs on the e-commerce platform capture user access, transaction details, address location, and system status. E-commerce stages constantly create large volumes of log data. Identifying emerging patterns in large datasets is crucial for corporate operations and decision-making [8]. Artificial Intelligence (AI) technology has led to fast growth in e-commerce. The e-commerce business is transforming the customer experience. AI technology and deep learning (DL) have transformed the e-commerce sector [9]. An effective register organization system ensures the steady provision of international e-commerce, gives participants in the supply chain a seamless flow of goods, and adapts to changing customer demands [10].

Objective of the research: The research intends to develop an enhanced clustering algorithm to improve e-commerce user segmentation that overcomes the constraints of previous methods by dealing with noisy as well as solitary data points. It uses the ECRO-Kernel DBSCAN algorithms to identify relevant consumer groups through behavioral patterns, allowing firms to develop focused marketing campaigns, increase customer engagement, and improve overall platform performance.

1.1 Research questions

- Can ECRO-Kernel DBSCAN achieve higher segmentation accuracy on noisy e-commerce data compared to K-Means, DBSCAN, and XGBoost-based clustering?
- How robust is ECRO-Kernel DBSCAN to synthetic noise in user behavior data while preserving meaningful customer segments?
- Which kernel type (Uniform, Triangular, Epanechnikov) provides the best clustering performance for e-commerce user segmentation using ECRO-Kernel DBSCAN?
- How do ECRO parameter settings—population size, iterations, crossover, and mutation probabilities—affect the quality and stability of detected customer clusters?

Organization of the remainder of the paper: Section 1 demonstrates the introduction, Section 2 describes the related work, Section 3 presents the methodology, Section 4 illustrates the result, Section 5 discusses the results and previous research, and Section 6 concludes the research.

2 Related work

Customer segmentation was an important tool in marketing since it allowed managers to identify specific clientele and reduce resource waste. The idea was to build relationships with profitable consumers through specialized marketing methods. While a variety of statistical methods have been employed, big data sets could impede efficacy. Clustering seeks to increase similarity within and dissimilarity between groups. This research used the clustering method K-means for segmentation, which resulted in five consumer clusters based on yearly income and spending ratings. The findings indicate that high-income clients with substantial expenditure ratings are suitable targets for marketing efforts [11]. The individual cluster analysis divided users with similar behavior into groups via iterative update clustering, identifying core and larger user groups. This investigation delivered a clustering method that combines connected rules with Multivalued Discrete Features (MDF), building on the KMC algorithm. The research presented a technique for calculating user similarity using Jaccard distance and using connection rules to enhance similarity between users [12]. Customer segmentation was a popular issue, especially in the face of increasing organizational competition. A novel approach model, Recency, Frequency, Monetary, and Tenure (RFMT), used agglomerative segmentation techniques, Density-Based Spatial Clustering of Applications with Noise (DBSCAN), and K-means to evaluate an e-commerce dataset. The model results in three discrete clusters, aiding retailers in improving customer interactions, implementing effective tactics, and optimizing targeted marketing [13]. The research focused on consumer segmentation to better understand customer needs and boost loyalty. Using KMC for behavioral data proved superior to rule-based methods, resulting in accurate segmentation into Platinum, Gold, Silver, Bronze, and Bad groups. However, the study was limited to behavioral data without considering demographic, psychographic, or geographic factors. Effective segmentation facilitated targeted marketing, enhanced product offerings, and fostered greater customer loyalty [14]. Online shopping has become a critical part of modern consumer behavior, with quick growth in digital commerce worldwide. This research presented Length, Relationship, Frequency (LRFS), an enhanced consumer segmentation model that builds on the traditional LRF framework. Designed exclusively for the e-commerce sector, this tool tracks relationships, recent purchases, and frequency of purchase. Using the LRFS model, this investigation enhances e-commerce by helping businesses modify marketing campaigns to coincide with altering online consumer preferences [15]. A framework [16] was proposed, ClusChurn-EC, which combines behavioral clustering with an LSTM network and attention mechanism for churn prediction. This deep learning approach used to identify at-risk customers performed

better than traditional machine learning schemes; however, the produced model's flexibility impacts generalizing to different e-commerce platforms. The experiment aimed to improve customer segmentation in e-marketing by comparing several machines learning clustering methods, specifically DBSCAN and K-Means. Utilizing Kaggle datasets, the unsupervised clustering methods achieved higher segmentation accuracy. The research also explored additional clustering techniques to bolster predictive modeling and validate applications across various industries beyond e-marketing [17]. Location and time factors, which were often overlooked in traditional segmentation, were used to divide up Business-to-Consumer (B2C) retail buyers. Ten categories of customers were created using the Recency, Frequency, Monetary, Tenure (RFMT) model, which was also used to examine product popularity, purchase timing, and geographic distribution. Identified popular product categories, peak buying times, and customer hotspots. To boost engagement, a recommender system was developed. The research's applicability to various retail settings was limited because it was based on a single case dataset [18]. This explored sophisticated clustering algorithms for online client buying behavior in an Omni channel firm. Using a KMC approach with elastic net penalty and extending the Recency, Frequency, Monetary (RFM) model to weekly-level data, the proposed process outperforms conventional k-means by lowering error rates and permitting variable selection across four setups. However, the focus on high-dimensional clustering within a single retail dataset can limit cross-sector generalizability [19]. The use of clickstream data to target e-commerce clients is increasingly popular. A test with real clickstream data from two websites demonstrated that customized advertising campaigns yield better click-through and conversion rates. This indicates that tailored advertising strategies can be effective in enhancing online sales, underscoring the need to understand consumer interest patterns and online buying behavior [20]. Ordered Clustering-based Algorithm (OCA), a suggested clustering approach, offered professional prospects in modern cultures as e-commerce continues to evolve. By addressing data sparsity and cold-start issues, OCA helped companies mitigate the effect of e-commerce on approval systems. A complete analysis of data clustering methods was shown to evaluate the effectiveness in addressing these challenges [21]. E-commerce systems, prevalent across industries, serve as platforms for online product marketing. This exploration focuses on customer behavior, employing the KMC clustering algorithm to analyze buying habits and segment clientele effectively [22].

To use DL and neural network (NN) [23] models to investigate user behavior patterns for e-commerce platforms, underscoring the benefits of AI-based methods for predictive insights. Yet, it rose from a predictive approach instead of unsupervised segmentation, which makes it distinct from the framework, which was based on clustering. The K-means clustering for segmenting clients and a random forest (RF) [24] approach to forecast client retention using transactional data. The research finds four separate client segments based on their purchasing behavior. The RF method identifies payment quantity and region as major influences on churn probabilities. The findings supported the simultaneous use of both strategies as a viable way to give insights into precise marketing.

Table 1 presents a comparative overview of prior research on e-commerce customer segmentation, outlining their objectives, methods, findings, and limitations. It highlights the progression from traditional clustering to advanced models, emphasizing existing research gaps.

Table 1: Summary of related work on customer segmentation in e-commerce

Reference Number	**Objective**	**Methods**	Findings	**Limitations**
Pradana and Ha [11]	Identify specific consumer segments and optimize marketing strategies	K-means clustering based on yearly income and spending ratings	Five clusters: Cluster 1: 22% Cluster 2: 15% Cluster 3: 28% Cluster 4: 20% Cluster 5: 15%	Less effective with large datasets and sensitive to noise and outliers.
Zhang et al. [12]	To improve clustering with categorical data	K-mode clustering with MDF, Jaccard distance, and correlation rules	Improved grouping accuracy: ~87% similarity score	High computation; limited scalability
Ullah et al.[13]	To optimize customer segmentation in marketing	RFMT with Agglomerative, K-Means, DBSCAN	Three clusters: Cluster 1: 35%, Cluster 2: 40%, Cluster 3: 25%	Dataset-specific Lacks external validation
Akande et al.[14]	To segment customers by behavior	K-Means vs. rule-based clustering	Five clusters: Platinum 20%, Gold 22%, Silver 18%, Bronze 25%, Bad 15%	Only behavioral data No demographic/psychographic integration

Khan et al.[15]	To enhance segmentation beyond RFM	LRFS model (Length, Relationship, Frequency, Spending)	Three clusters: Cluster 1: 30%, Cluster 2: 45%, Cluster 3: 25%	Tailored for e-commerce only
Musunuri [16]	To predict and prevent customer churn	ClusChurn-EC (clustering + LSTM + attention)	Churn prediction accuracy: 91%; identified 18% at-risk customers	Limited generalization to other platforms
Ling & Weiling [17]	To compare clustering methods for e-marketing	K-Means, DBSCAN on Kaggle datasets	Segmentation accuracy: 92%	Requires multi-industry validation
Ehsani & Hosseini [18]	To segment B2C buyers by time/location	RFMT model	Ten clusters: largest 15%, smallest 8%; identified peak purchase hours	Single-case dataset Limited generalizability
Zhao et al.[19]	To analyze omnichannel buying behavior	K-Means with elastic net + RFM	Reduced clustering error by 12%; variable selection enabled	Focused on one dataset, Limited cross-sector use
Sakalauskas & Kriksciuniene [20]	To improve targeted advertising	Clickstream data analysis	Click-through rate increased by 8%; conversion rate by 5%	Dependent on site-specific data
Gulzar et al. [21]	To address sparsity and cold-start issues	Ordered Clustering-based Algorithm (OCA)	Recommendation accuracy improved by 10% under sparse data	Not validated on diverse datasets
Tabianan et al.[22]	To identify purchasing patterns	K-Means clustering	Segmented clientele into five groups; cluster sizes 20–25% each	Simple algorithm; lacks complexity handling

3 Methodology

Customer transaction and behavior data is aggregated and analyzed using Kernel DBSCAN to identify dense regions and filter out noise. Clusters are refined through Efficient Coral Reefs Optimization, resulting in segments like Platinum, Gold, Silver, Copper, and Iron. These segments support targeted marketing strategies, validated for accuracy and robustness against traditional methods to enhance business outcomes.This framework model is illustrated in Figure 1.




Figure 1: ECRO–kernel DBSCAN-based e-commerce user segmentation Workflow

3.1 Integrated transactional and behavioral data collection model for e-commerce user segmentation

Customer activity data is gathered by merging transactional records (recency, frequency, monetary value) with behavioral interactions (sessions, browsing, campaigns, wishlist, cart). These features are aggregated per customer to form a unified dataset of 50,000 users collected over 12 months (January-December 2024) (https://www.kaggle.com/datasets/ziya07/e-commerce-user-behavior-and-transaction-dataset/data/data.

Preprocessing steps included data cleaning, normalizing numerical features, encoding categorical data, and adding synthetic noise to assess robustness. Synthetic noise is added to assess robustness, enabling ECRO–Kernel DBSCAN to filter anomalies and generate precise customer segments. Those collective data and their descriptive features are depicted in Table 2.

Table 2: Key e-commerce customer data features

Feature	Description	Feature	Description
Customer ID	Customer unique identifier	Pages Viewed	Pages per session
Recency	Days since purchase	Clicks	Total platform clicks
Frequency	Purchase count frequency	Campaign Response	Campaign response flag
Monetary	Total customer spending	Wishlist Adds	Wishlist items added
Avg Order Value	Average order value	Cart Abandon Rate	Cart abandonment ratio
Session Count	Browsing session count	Returns	Returned product count
Avg Session Duration	Session average duration	Noise Flag	Outlier data indicator

Data cleaning: The e-commerce data underwent a data-cleansing process to yield output in a reliable form.

Actions taken included handling missing data, dropping duplicates, and standardizing data using categorical variables and correcting identified inconsistencies. Outliers were detected and treated. Data processing produced improved data quality with mitigated noise and, therefore, produced reliable clustering capabilities for user segmentation.

Z-Score normalization: To ensure adequate comparison of different user behavior features, a Z-score normalization is performed on the dataset before clustering. This technique standardizes each attribute with the mean (μ_Y) being subtracted and normalizes with the standard deviation (σ_Y) as follows in equation (1).

$$c' = \frac{c-\mu_Y}{\sigma_Y} \quad (1)$$

Normalization prevents any individual trait (e.g., income, browsing time, purchase frequency) from outpacing scaling-up during clustering, which helps improve the accuracy of customer segmentation, as it also eliminates scale-related bias.

3.2 Kernel density-based spatial clustering of applications with noise (Kernel DBSCAN)

The improved Kernel DBSCAN is effective for e-commerce user segmentation, handling noisy datasets like customer transactions and browsing records. Unlike standard DBSCAN, it uses Kernel Density Estimation (KDE) for flexible density estimation, processing transactional attributes such as Recency, Frequency, Monetary, and Avg Order Value, along with behavioral metrics like Session Count and Avg Session Duration. KDE reduces the influence of irregular purchase behaviors and browsing anomalies.

Additionally, the density of a point x, denoted as dens (x, ε), is computed using a kernel function K as in equation (2).

$$\text{dens}(x,\epsilon) = \sum_{y\epsilon x} k\left(\frac{d(x,y)}{\epsilon}\right) \quad (2)$$

where $d(x, y)$ is the distance between users x and y, and ε is the neighborhood radius. In this research, six widely applied kernels are tested on the dataset: uniform, triangular, Epanechnikov, cosine, exponential, and Gaussian kernels. Each provides a different weighting scheme to nearby users, such as

1 **Uniform kernel:** treats all neighbors equally, equivalent to classic DBSCAN.
2 **Triangular / Epanechnikov kernels:** emphasize customers with closer behavioral similarity, e.g., similar Recency and Frequency values.
3 **Cosine kernel:** highlights mid-range density patterns, balancing high-frequency buyers with occasional shoppers.
4 **Exponential / Gaussian kernels:** assign influence even at larger distances, useful for capturing long-tail users with sporadic purchases but consistent browsing.

For example, When Gaussian kernels are applied to features like Frequency, Monetary, and Session Count, they effectively filter out low-activity users as noise and cluster stable customers into segments such as Gold or Platinum. This method enhances segmentation resilience over traditional DBSCAN, which may misclassify loyal but low-frequency customers due to its strict uniform density assumption.

3.3 ECRO-based clustering approach

In ECRO, broadcast spawning mimics an eagle exploring a vast area, creating a number of potential customer clusters to ensure that many different solutions are considered. Depredation acts like selective hunting, and it refines those clusters by removal of the worst-performing points of clutter, which helps the algorithm converge towards the most meaningful user segments. These two operators work together to balance exploration and refinement for clustering purposes.

To further enhance segmentation quality, Efficient Coral Reefs Optimization (ECRO) is incorporated after Kernel DBSCAN extracts the dense regions of the dataset. The process begins by initializing corals (candidate clustering solutions), where each coral corresponds to a set of potential cluster centers in the multi-dimensional feature space. This function flowchart is depicted in Figure 2.




Figure 2: Evolutionary clustering process for user segmentation flowchart

3.3.1 Coral representation and fitness function

In the ECRO model, a coral represents a candidate segmentation of e-commerce customers. Each dimension of the coral corresponds to a cluster center in the feature space. For example, a 5-dimensional coral aligns with five market segments: Platinum, Gold, Silver, Copper, and Iron. Each dimension encodes cluster centers across

transactional (RFM metrics) and behavioral (session and interaction) features. The fitness function evaluates segmentation quality by balancing compactness, separation, and noise-handling in equation (3).

$$\mathrm{fit}_i = \alpha \frac{\mathrm{Comp}_i - \mathrm{Comp}_{min}}{\mathrm{Comp}_{max} - \mathrm{Comp}_{min}} + \beta \frac{\mathrm{Sep}_{max} - \mathrm{Sep}_i}{\mathrm{Sep}_{max} - \mathrm{Sep}_{min}} \quad (3)$$

Where Comp_i denotes an intra-cluster compactness of solution i (lower is better), Sep_i is an inter-cluster separation of solution i(higher is better), and α, β are the weights controlling the importance of compactness vs separation.

Table 3 identifies seven important criteria for the ECRO-Kernel DBSCAN method. Population Size, Iterations, Mutation Rate, and Crossover Probability manage the evolutionary optimization process, whereas Kernel Bandwidth and Minimum Points determine the density of points in a cluster. Fitness Weights (α, β), meanwhile, are used to weigh either compactness or separation of clusters, producing strong and meaningful patterns of e-commerce users as shown in Table 3.

Table 3: Hyperparameter tuning variables

Parameter	Variable	Description
Population Size	***PopSize***	Number of candidate solutions (corals) in each generation of ECRO.
Number of Iterations	***Iter***	Maximum evolutionary cycles allowed for optimization.
Mutation Rate	***MutRate***	Probability of introducing random changes to maintain diversity.
Crossover Probability	***CrossProb***	Probability of combining traits from two parent solutions.
Kernel Bandwidth (ε)	***Eps***	Neighborhood radius controlling kernel density estimation in Kernel DBSCAN.
Minimum Points	***MinPts***	Minimum number of points required to form a dense cluster region.
Fitness Weights (α,β)	***Alpha, Beta***	Control the balance between compactness (α) and separation (β) in the fitness function.

The ECRO–Kernel DBSCAN approach consists of data preprocessing, Kernel Density DBSCAN, and evolutionary optimization. Transactional and behavioral features are cleaned and normalized first. Next, Kernel DBSCAN identifies dense regions and mitigates noise from input data, using adaptive kernels. It uses evolutionary operations within ECRO to not only improve cluster centers, but also to achieve compactness versus separation properties, providing useful and robust customer segments in business terms like Platinum, Gold, Silver, Copper, and Iron as shown in Algorithm 1.

Algorithm 1: ECRO_Kernel_DBSCAN

Input: E-commerce dataset D with transactional + behavioral features
Output: Segments {Platinum, Gold, Silver, Copper, Iron}
1. Data Preprocessing:
  - Handle missing values, drop duplicates
  - Normalize features using Z-score
  - Add synthetic noise flags for robustness
2. Kernel DBSCAN:
  For each user x in D:
    Compute density(x, ε) = Σ K(d(x,y)/ε) for neighbors y
    Select kernel function (Uniform, Triangular, Epanechnikov, Gaussian, etc.)
  Identify core points and form preliminary clusters
  Mark sparse/noisy points as outliers
3. Initialize ECRO:
  - Represent each candidate solution as "coral" = cluster centers
  - Define fitness = α * Compactness + β * Separation
  - Initialize population P with random corals
4. Evolutionary Optimization:
  While (iteration < MaxIter):
    Apply Broadcast Spawning → generate offspring clusters
    Apply Crossover → combine cluster centers
    Apply Mutation → introduce diversity
    Evaluate the fitness of each coral
    Depredation: replace weakest solutions with better ones
  End While
5. Select the best clustering solution with the highest fitness
6. Label clusters as {Platinum, Gold, Silver, Copper, Iron}
Return Segments

4 Result and discussion

The model is implemented using Python-based data science libraries, including scikit-learn for clustering and classification, pandas and NumPy for preprocessing, matplotlib and seaborn for visualization, and TensorFlow/PyTorch for advanced learning tasks. Jupyter Notebook/Google Colab serve as development platforms, while SQL/NoSQL databases manage storage. Hardware implementation relies on multi-core CPUs, optional GPUs (NVIDIA CUDA-enabled) for acceleration, and cloud computing platforms for scalable training and deployment. The dataset was partitioned into training (70%), validation

(15%), and testing (15%) sets, ensuring stratified distribution across segments. Clustering was assessed for 3-7 clusters with Uniform, Triangular, and Epanechnikov kernel functions and Silhouette Scores of 0.58-0.64, and Davies-Bouldin Index of 0.51-0.67. It tuned the ECRO parameters (population size between 30 and 100, iterations of 50 and 250, crossover of 0.6-0.9, and mutation of 0.1-0.3) to be able to extract robust clusters.

Figure 3 (a-b) show that the ECRO–Kernel DBSCAN segmentation effectively identifies e-commerce user groups. A heat map indicates that the Platinum segment exhibits the highest monetary and engagement values, while the Copper and Iron segments show lower activity. The confusion matrix reflects high clustering accuracy with minimal misclassifications. (Figure. 3 d) shows strong positive relationships between frequency, monetary value, browsing depth, and wish list activity, representing customers with high-value or optimal feature behavior. As an alternative, strong negative correlations of recency and returns to engagement features characterize these low-value segments, supporting cluster validity and informing marketing strategy. (Figure 3e) profiles each segment's behavioral footprint, illustrating clear contrasts between high-value Platinum/Gold customers and low-activity Copper/Iron users.




Figure 3: Visualization of E-Commerce User Segmentation and Feature Analysis, (a) Average Feature Values by Segment, (a) Average Feature Values by Segment, (b) Confusion Matrix of Segmentation Performance, (c) RadViz Projection of Customer Clusters, (d) Feature Correlation Heatmap, (e) Radar Chart of Average Customer Profiles

Figure 4 (a-e) demonstrates the validity of the ECRO–Kernel DBSCAN framework for e-commerce customer segmentation. Analysis reveals a high concentration of recent transaction customers and balanced representation across user clusters (Platinum, Gold, Silver, Copper, Iron). High-value users show shorter purchasing intervals in recency density profiles. Pairwise feature relationship matrices effectively delineate segment boundaries, while cluster visualizations illustrate density-based grouping and minimize outliers. Overall, these diagnostics affirm the model's effectiveness in clustering and maintaining the interpretability of consumer behavior for data-driven segmentation.




Figure 4: Multi-Perspective Validation of ECRO–Kernel DBSCAN Customer Segmentation (a) Distribution of Recency (Days as Last Purchase), (b) Customer Segment Distribution, (c) Revenue Density Profiles Across Segments, (d) Pairwise Feature Relationships: Recency, Frequency, and Monetary Value, and (e) Pairwise Feature Relationships: Extended RFM Variables Across Segments.

4.1.Performance evaluation metrics

Accuracy: Accuracy represents the proportion of properly classified users to the overall number of users, calculated by equation (4). It evaluates the complete effectiveness of the segmentation model.

$$\text{Accuracy} = \frac{\text{TP+TN}}{\text{TP+ TN+FP+FN}} \quad (4)$$

Precision: Precision indicates the proportion of correctly identified positive users out of all users predicted as positive, measured using equation (5). It reflects how reliable the model is when it classifies a customer into a specific segment.

$$\text{Precision} = \frac{\text{TP}}{\text{TP+FP}}$$

(5)

Recall: The model's recall quantifies its capacity to accurately identify every real positive user, calculated using equation (6). It is useful to ensure that important customer groups are not missed during segmentation.

$$\text{Recall} = \frac{\text{TP}}{\text{TP+FN}}$$

(6)

F1-Score: The F1-score, defined as the harmonic mean of precision and recall, provides a balanced metric for evaluating performance, especially when customer classes are unevenly distributed and minimizing false positives and false negatives is crucial.

$$\text{F1} - \text{Score} = \frac{2*\text{Precision}*\text{Recall}}{\text{Precision+Recall}}$$

(7)


Performance evaluation compared with existing models

The ECRO–Kernel DBSCAN model outperforms traditional clustering methods, such as K-means [14], Logistic Regression (LR) [23], and Gradient Boosting (XGBoost) [23] and K-means clustering and random forest (KMC-RF) [24], which struggle with assumptions and noise sensitivity. It excels in e-commerce user segmentation across all metrics (Figure 5 and table 4).

Table 4: Performance comparison of different models for e-commerce user segmentation

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
LR [23]	80	78	70	74
RF [23]	85	82	78	80
XGBoost [23]	88	84	81	82
KMC-RF [24]	90	91	90	88
ECRO-Kernal DBSCAN [Proposed]	**94**	**93**	**92**	**94**

Figure 5: Performance Evaluation of Proposed ECRO-Kernel DBSCAN against Benchmark Models



In contrast, the proposed model attains 0.94 accuracy, 0.93 precision, 0.92 recall, and 0.94 F1-score by dynamically adapting density valuation via kernels and refining cluster centers through ECRO. The increase of 4% accuracy over KMC-RF appears small in scale, but it carries significant implications in practical e-commerce applications. Each reduction in misclassification of a customer contributes to more accurate segmentations and targeting of customers for marketing campaigns, which results in increased conversion rates and retention of customers. Ultimately, greater accuracy means greater revenue and competitive advantage.

Table 5 displays that the proposed method ECRO-Kernal DBSCAN holds MSE = 0.0059, MAE = 0.0520, and MAPE = 0.40%, attesting to its powerful forecasting ability. The kernel density estimation design and evolutionary optimization are used in enhancing the clustering errors efficiently, thus adding precision for a business-oriented customer segmentation task.

Table 5: Numerical evaluation of proposed model ECRO-Kernal DBSCAN

Model	MSE	MAE	MAPE (%)
FA-SVM [25]	0.03718	0.23474	0.19482
FA-LSTM [25]	0.02825	0.13597	0.10304
FA-PSO-RNN [25]	0.02425	0.11777	0.8979
FA-PSO-GRU [25]	0.01875	0.10906	0.8443
FA-PSO-LSTM [25]	0.00738	0.06283	0.4887
ECRO-Kernal DBSCAN [Proposed]	0.0059	0.0520	0.40

Table 6 shows the segmentation of customer value by tier (Platinum, Gold, Silver, and Bronze) based on K-Means clustering [14] and the proposed ECRO-Kernel DBSCAN. Three scores for Recency (R), Frequency (F), and Monetary (M) were determined, with score values (1–5) based on each customer ID. The proposed method has better segment differentiation, especially in differentiating mid and low tiers of value, which further demonstrates the method's ability to classify customer behavior more comprehensively. The proposed ECRO-Kernel DBSCAN demonstrates superior scores compared to K-Means clustering, with average improvements of 12-18% across recency, frequency, and monetary scores. Platinum and Gold clusters show consistently elevated loyalty levels, while Silver and Bronze are more sharply differentiated. This segmentation improvement provides targeted marketing guidance, allowing premium offers to the highest tiers of value and retention strategies to the tiers of lower value, providing stability and profitability.

Table 6: Customer value segmentation

Metrics	**Segmentation**							
	Platinum		**Gold**		**Silver**		**Bronze**	
	K-Means clustering [14]	**ECRO-Kernal DBSCAN [Proposed]**	**K-Means clustering [14]**	**ECRO-Kernal DBSCAN [Proposed]**	**K-Means clustering [14]**	**ECRO-Kernal DBSCAN [Proposed]**	**K-Means clustering [14]**	**ECRO-Kernal DBSCAN [Proposed]**
R	**5**	**5**	**5**	**5**	**4**	**4**	**2**	**3**
F	**5**	**5**	**5**	**5**	**3**	**4**	**2**	**2**
M	**5**	**5**	**4**	**5**	**3**	**4**	**1**	**2**

Table 7 provides a comparison of six different kernel functions—namely, Uniform, Triangular, Epanechnikov, Quartic, Tricube, and Gaussian—across important clustering evaluation measures of interest, namely, Silhouette Score, Davies-Bouldin Index (DBI), Calinski-Harabasz Index (CHI), Dunn Index, and Adjusted Rand Index (ARI). The results indicate that the Gaussian kernel function has the highest Silhouette Score (0.71) and ARI (0.88), which shows it has good cohesion, separation, and alignment with true customer segments. The other kernel functions achieve decreasing scores, which is not unexpected.

Table 7: Performance Metrics for Various Kernels in E-commerce User Segmentation

Kernel Function	**Silhouette Score**	**DBI**	**CHI**	**Dunn Index**	**ARI**
Uniform	0.58	0.67	342	0.32	0.72
Triangular	0.61	0.59	376	0.34	0.75
Epanechnikov	0.64	0.51	402	0.36	0.79
Quartic (Biweight)	0.66	0.47	438	0.39	0.81
Tricube	0.68	0.42	465	0.41	0.85
Gaussian *(selected)*	**0.71**	**0.38**	**512**	**0.46**	**0.88**

In Table 8, it is defined that the Gaussian kernel produces the highest Silhouette Score (0.71), lowest Davies-Bouldin Index (0.38), highest Calinski-Harabasz Index (512), highest Dunn Index (0.46), and highest Adjusted Rand Index (0.88). These values show that the Gaussian kernel creates the most compact, best-separated, and most accurate e-commerce user clusters.

Table 8: Comparison of clustering performance across different kernel functions

Kernel Function	**Silhouette Score**	**DBI**	**CHI**	**Dunn Index**	**ARI**
Uniform	0.58	0.67	342	0.32	0.72
Triangular	0.61	0.59	376	0.34	0.75
Epanechnikov	0.64	0.51	402	0.36	0.79
Quartic (Biweight)	0.66	0.47	438	0.39	0.81
Tricube	0.68	0.42	465	0.41	0.85
Gaussian *(selected)*	**0.71**	**0.38**	**512**	**0.46**	**0.88**

Table 9 shows the results of the full ECRO-Kernel DBSCAN model with preprocessing. The model reaches 94% Accuracy, 93% Precision, 92% Recall, and 94% F1-score, clearly indicating that the combination of Kernel DBSCAN with preprocessing and ECRO optimization produces strong, accurate e-commerce user segmentation.

Table 9: Ablation study for the proposed method ECRO-Kernel DBSCAN

Method Variant	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
Full ECRO-Kernel DBSCAN	94	93	92	94
Kernel DBSCAN only (without ECRO)	90	89	88	89
Preprocessed DBSCAN (without KDE)	85	84	82	83

Table 10 displays the computational performance of the ECRO-Kernel DBSCAN proposed for 50 to 250 epochs. Runtime, CPU, and GPU utilization increase as the epochs increase; clustering becomes more stable at higher epochs, but the improvements taper off, with almost all the improvement happening before 200 epochs. This indicates predictable performance scaling and efficient use of resources.

Table 10: ECRO-Kernel DBSCAN model training resource utilization

Epochs	Runtime (s)	CPU Utilization (%)	GPU Utilization (%)
50	48	70	30
100	92	72	35
150	138	75	40
200	185	77	42
250	235	80	45

5 Discussion

A comprehensive ML-based framework, LR, RF, and XGBoost [23], for the examination of e-commerce user behavior, but there are limitations. It can encounter issues of data quality, including missing or noisy interactions, as well as challenges of model interpretability. The high computational burden such as ML-based approaches incurs and their overfitting to past behavior make it difficult for the model to generalize to future scenarios. Further, the model does not fully consider the immediate context of evolving user behavior. The KMC-RF [24] successfully segments customers using the K-means clustering methodology based primarily on income and spending score; however, there are some disadvantages. The research has only relied on two attributes, which omit behavioral, demographic, and psychographic factors. K-means clustering is extremely sensitive to outliers and initial centroid placements that can be influenced by cluster quality. The scalability and market dynamics were not taken into consideration in the research. The proposed ECRO provides an advantage over naive clustering approaches in noisy scenarios by improving initialization of cluster centers and refining estimated core dense regions in order to minimize the effect of outliers, thereby improving segmentation accuracy and overall robustness. Potential trade-offs of ECRO include the additional computational cost from the iterative optimization and sensitivity to the underlying hyper parameters (population size, number of iterations, crossover, mutation) that may require additional tuning to optimize performance. The five customer categories present explicit business actions. Platinum customers require loyalty rewards and preferential treatment, Gold customers are responsive to marketing and packing, Silver customers respond to discounts and personalized recommendations, and Copper customers need engagement nudges such as seasonal offers. Iron customers are a less valuable category, as they do not require an engagement plan beyond the most cost-effective method of reactivation. Each differentiated approach moves customers from a technical cluster to marketing action.

6 Conclusion

The ECRO–Kernel DBSCAN model effectively segments customers by combining transactional and behavioral data while accurately filtering noise. It distinguishes high-value users (Platinum and Gold) from low-engagement groups (Copper and Iron) and enhances the interpretability of results, supporting targeted marketing. Its integration of kernel density estimation and evolutionary optimization yields clear clusters with impressive performance metrics: 94% accuracy, 93% precision, 92% recall, and 94% F1-score, outperforming other models like KMC-RF, LR, RF, and XGBoost. However, its high computational demands and the need for tuning parameters may restrict scalability for very large datasets. Future iterations may incorporate adaptive parameter tuning and hybrid clustering techniques for improved efficiency in e-commerce platforms.

All datasets used in this study, including those sourced from **Kaggle (**https://www.kaggle.com/datasets/ziya07/e-commerce-user-behavior-and-transaction-dataset/data/data**)**, are publicly available and come with licenses that grant permission for research use.

References

[1] Azeroual, O., Nacheva, R., Nikiforova, A., & Störl, U. (2025). A CRISP-DM and Predictive Analytics Framework for Enhanced Decision-Making in Research Information Management Systems. Informatica, 49(18).

[2] Zhao, Q. (2025). Research on Optimal Model Combination of Cross-Border E-Commerce Platform Operation Relying on Robot Hybrid Algorithm. Informatica, 49(7).

[3] Chefrour, A., & Souici-Meslati, L. (2022). Unsupervised deep learning: Taxonomy and algorithms. Informatica, 46(2).

[4] Xiahou, X., & Harada, Y. (2022). B2C e-commerce customer churn prediction based on K-means and SVM. *Journal of Theoretical and Applied Electronic Commerce Research, 17*(2), 458–475. https://doi.org/10.3390/jtaer17020024

[5] Matuszelański, K., & Kopczewska, K. (2022). Customer churn in retail e-commerce business: Spatial and machine learning approach. *Journal of Theoretical and Applied Electronic Commerce Research, 17*(1), 165–198. https://doi.org/10.3390/jtaer17010009

[6] Shobana, J., Gangadhar, C., Arora, R. K., Renjith, P. N., Bamini, J., & Devidas Chincholkar, Y. (2023). E-commerce customer churn prevention using machine learning-based business intelligence strategy. *Measurement: Sensors, 27*, 100728. https://doi.org/10.1016/j.measen.2023.100728

[7] Sharma, C., Kaur, A., Datta, P., & Gulzar, Y. (2025). Optimizing e-commerce data: Effective approaches for data collection, cleansing, and preprocessing. In *Strategic Innovations of AI and ML for E-Commerce Data Security* (pp. 1–30). IGI Global. https://doi.org/10.4018/979-8-3693-5718-7.ch001

[8] Wang, T., Li, N., Wang, H., Xian, J., & Guo, J. (2022). Visual analysis of e-commerce user behavior based on log mining. *Advances in Multimedia, 2022*(1), 4291978. https://doi.org/10.1155/2022/4291978

[9] Li, J. (2022). E-commerce fraud detection model by computer-aided artificial intelligence data mining. *Computational Intelligence and Neuroscience, 2022*(1), 8783783. https://doi.org/10.1155/2022/8783783

[10] Tang, Y. M., Chau, K. Y., Lau, Y. Y., & Zheng, Z. (2023). Data-intensive inventory forecasting with artificial intelligence models for cross-border e-commerce service automation. *Applied Sciences, 13*(5), 3051. https://doi.org/10.3390/app13053051

[11] Pradana, M. G., & Ha, H. T. (2021). Maximizing strategy improvement in mall customer segmentation using K-means clustering. *Journal of Applied Data Sciences, 2*(1), 19–25. https://doi.org/10.47738/jads.v2i1.18

[12] Zhang, B., Wang, L., & Li, Y. (2021). Precision marketing method of e-commerce platform based on clustering algorithm. *Complexity, 2021*(1), 5538677. https://doi.org/10.1155/2021/5538677

[13] Ullah, A., Mohmand, M. I., Hussain, H., Johar, S., Khan, I., Ahmad, S., & Huda, S. (2023). Customer analysis using machine learning-based classification algorithms for effective segmentation using recency, frequency, monetary value, and time. *Sensors, 23*(6), 3180. https://doi.org/10.3390/s23063180

[14] Akande, O. N., Akande, H. B., Asani, E. O., & Dautare, B. T. (2024). Customer segmentation through RFM analysis and K-means clustering: Leveraging data-driven insights for effective marketing strategy. In *2024 International Conference on Science, Engineering and Business for Driving Sustainable Development Goals (SEB4SDG)* (pp. 1–8). IEEE. https://doi.org/10.56134/jst.v3i1.81

[15] Khan, R. H., Dofadar, D. F., Alam, M. G. R., Siraj, M., Hassan, M. R., & Hassan, M. M. (2024). LRFS: Online shoppers' behavior-based efficient customer segmentation model. *IEEE Access, 12*, 96462–96480. https://doi.org/10.1109/ACCESS.2024.3420221

[16] Musunuri, A. (2023). Leveraging AI and deep learning for e-commerce customer segmentation. *International Journal of Innovative Research in Science, Engineering and Technology, 12*(6). https://doi.org/10.15680/IJIRSET.2023.1206165

[17] Ling, L. S., & Weiling, C. T. (2025). Enhancing segmentation: A comparative study of clustering methods. *IEEE Access.* https://doi.org/10.1109/ACCESS.2025.3550339

[18] Ehsani, F., & Hosseini, M. (2025). Consumer segmentation based on location and timing dimensions using big data from business-to-customer retailing marketplaces. *Big Data, 13*(2), 111–126. https://doi.org/10.1089/big.2022.0307

[19] Zhao, H. H., Luo, X. C., Ma, R., & Lu, X. (2021). An extended regularized K-means clustering approach for high-dimensional customer segmentation with correlated variables. *IEEE Access, 9*, 48405–48412. https://doi.org/10.1109/ACCESS.2021.3067499

[20] Sakalauskas, V., & Kriksciuniene, D. (2024). Personalized advertising in e-commerce: Using clickstream data to target high-value customers. *Algorithms, 17*(1), 27. https://doi.org/10.3390/a17010027

[21] Gulzar, Y., Alwan, A. A., Abdullah, R. M., Abualkishik, A. Z., & Oumrani, M. (2023). OCA: Ordered clustering-based algorithm for e-commerce recommendation system. *Sustainability, 15*(4), 2947. https://doi.org/10.3390/su15042947

[22] Tabianan, K., Velu, S., & Ravi, V. (2022). K-means clustering approach for intelligent customer segmentation using customer purchase behavior data.

Sustainability, 14(12), 7243. https://doi.org/10.3390/su14127243

[23] Somavarapu, S., & Gupta, V. (2025). Analyzing and visualizing user behavior in e-commerce: A machine learning approach. *Unpublished manuscript.*

[24] Li, Z. (2025). Customer segmentation and churn prediction based on K-means and random forest: A case study of e-commerce data. *Unpublished manuscript.* https://doi.org/10.61784/ejst3071

[25] Chen, X., & Long, Z. (2023). E-commerce enterprises' financial risk prediction based on FA-PSO-LSTM neural network deep learning model. *Sustainability, 15*(7), 5882. https://doi.org/10.3390/su15075882

Hybrid ANFIS and Random Forest Algorithms Optimized by Prairie Dog Optimization for Predicting Punching Shear Strength in Reinforced Concrete Slab-Column Connections

Yan Li[1, *], Dong Liu[2] and Bin Li[2]
[1]School of Transportation Engineering, Wuhan Technical College of Communications, Wuhan 430065, China;
[2]Changjiang Institute of Survey, Planning, Design and Research Co., Ltd, Wuhan, 430010, China
E-mail: 15926383656@163.com
[*]Corresponding author

Keywords: shear reinforcement, slab-column, punching shear strength, prairie dog, feature importance

Received: August 31, 2025

This study presents a data-driven framework for predicting the punching shear resistance (Vn) associated with failure modes (FMs) in reinforced concrete (RC) slab-column connections with shear reinforcement. A curated database of 327 experimental tests was compiled, incorporating nine critical input parameters related to the punching shear mechanism. The dataset was divided into training (70%), validation (15%), and testing (15%) subsets to construct, tune, and assess the predictive models. Two machine learning approaches—random forests (RF) and adaptive neuro-fuzzy inference system (ANFIS)—were optimized using the Prairie Dog Algorithm (PDA) to enhance hyperparameter selection. Model performance was evaluated using statistical indicators including the coefficient of determination (R^2), root mean square error (RMSE), and mean absolute error (MAE). Results demonstrate that both RF-PDA and ANFIS-PDA achieved high predictive accuracy, with ANFIS-PDA marginally outperforming RF-PDA (R^2 = 0.9893, RMSE = 0.0666 on the test set) compared to RF-PDA (R^2 = 0.9753, RMSE = 0.1057). Comparative analysis against existing baseline models further confirmed the superiority of the proposed hybrid approaches. These findings highlight the potential of metaheuristic-optimized machine learning schemes as reliable tools for evaluating the punching shear resistance of RC slab-column connections.

Povzetek: Študija pokaže, da napredni modeli strojnega učenja omogočajo zelo zanesljivo napoved prebojne strižne nosilnosti armiranobetonskih plošča–steber spojev.

1 Introduction

Smooth slabs are commonly preferred in the design and building of Reinforced Concrete (RC) constructions because of their economic viability and optimal performance [1], [2]. These slabs are positioned immediately above the pillars, obviating the necessity for beams and facilitating a more direct transfer of bars from the slab to the pillars. The absence of beams offers several advantages, including reduced construction height, seamless integration of vertical shafts, improved layout flexibility, optimized improvement placement, accelerated construction timeline, and effective form design [3], [4]. The configuration of a smooth slab is predominantly influenced by the structural response of slabs and foundations to concentrated loads, leading to shear failure near the slab and pillar's junction, resulting from elevated shear powers. The profound incursion of forces causes an entire decrease of shear strength at the intersection between the slab and pillar, resulting in an abrupt and fragile rupture of this connection [5]. This defeat subsequently initiates a redistribution of bars onto adjacent structural elements, potentially resulting in a cascading chain of failures. Assessing the failure mechanism of structural components such as slabs and foundations subjected to shear from concentrated stresses in smooth slabs is a complex endeavor, since it encompasses numerous aspects, including excessive reinforcement bars and inadequate cementitious composite strength [6], insufficient slab width [7], lack of shear enhancement [8], tiny pillar tops, and substandard construction practices. These agents must be thoroughly examined to accurately gauge the smooth slabs' performance and integrity. Several experimental techniques have been utilized to formulate technical specifications [9]. The current experimental methods [10], [11], [12] have been derived from empirical data through forecasting. The efficacy of their function depends on the particular data foundation employed to compute the structural reaction of slabs and foundations to concentrated loads, resulting in shear failure. The experimental methodologies have demonstrated inconsistencies in their results, resulting in either the underestimate or overestimation of the structural response of slabs and foundations to concentrated loads, culminating in shear failure [13]. Numerous methodologies are available for evaluating an FM in structural components, including slabs and foundations, subjected to shear from concentrated loads, as well as the

efficacy of smooth slabs; yet, these methods are constrained to certain scenarios. Machine learning (ML) methodologies can be utilized to address the issues inherent in experimental approaches [14], [15], [16], [17], [18], [19], [20], [21]. Scholars have employed artificial neural networks (ANNs) in forecasting the loading capability of enhanced cement-based composite components [22], elucidating the flexible properties of ordinary also great-resistance cement-based composite [23], examining the constructional characteristics of slabs [13], estimating the maximum power of beams [24], anticipating the grooving function of asphalt combinations with steel slag aggregates [20], and projecting the conduct of shear fasteners in cement-based composite [25]. ANN architectures have shown impressive efficacy in evaluating the operational capabilities of diverse constructional elements. ANNs have been successfully employed to estimate the loading capability of constructional members, such as the resistance estimation of enhanced cement-based composite beams [26], also pillars [27], [28], [29]. Nonetheless, ANNs face difficulties with regional enhancement, which may obstruct comprehensive data collection and analysis, resulting in erroneous estimations. Improving the performance of an artificial neural network can be accomplished by employing heuristic methods. Heuristic processes have substantial advantages over artificial neural networks, including their ability to optimize network weights through refinement and their proficiency in circumventing local minima and managing multivariate challenges [30].

The cohesion of RC beams has been forecasted using a combined technique that mixed Adaptive Neuro Fuzzy Inference System (ANFIS) with a genetic procedure and particle congestion enhancement [31]. The integrated technique shown enhanced accuracy in assessing cohesiveness relative to individual procedures. A separate research study employed a sophisticated Bat ANN to predict the structural response of slabs and foundations to concentrated loads, resulting in shear failure, and the resistance of reinforced concrete smooth slabs devoid of shear improvements [32]. The study examined 30 unique configurations of the model to identify the most precise estimation scheme with reduced faults and the greatest R^2 quantities. Concha et al. [33] utilized a mixture of neural network and particle congestion enhancement to forecast the cohesion of the iron-enhanced agent RC deep beams [34]. The blended technique precisely estimated the resistance of an iron-reinforced cement-based composite deep beam, showcasing a robust correlation coefficient of 0.997. These composite forecasting approaches are reliable for estimating structural performance and have proven valuable in civil engineering applications. Sandeep and colleagues [35] employed ML tactics to forecast the cohesion of RC beams. The scholars utilized the atom search optimizer (ASO) procedure in conjunction with a neural network to make forecasts regarding the cohesion of beams. The outcomes were subsequently compared with the forecasted outcomes of different combined and independent techniques, such as ANN, Genetic Algorithm (GA) and Support Vector Machine (SVM).

A recent study underscores the extensive utilization of machine learning in engineering, encompassing crack identification in concrete via $GCN - GLCM$ models with an accuracy of 98.99%, as well as intrusion detection and economic forecasting [36], [37]. Machine learning-based surrogate models in structural analysis attained R^2 values of 0.996 with a limited number of sensors [38], [39]. These results validate the efficacy of AI in improving accuracy and efficiency while encouraging the implementation of hybrid metaheuristic-optimized models such as PDA-based RF and $ANFIS$ in this research.

The principal objective of this project is to create and validate a hybrid, data-driven framework for precisely forecasting the punched shear strength of reinforced concrete slab-column connections with shear reinforcement. Consequently, two machine learning algorithms, RF and $ANFIS$ are combined with a metaheuristic optimizer, the PDA, to improve hyperparameter tweaking and model efficacy. The present research indicates that metaheuristic optimization (via PDA) markedly enhanced the learning accuracy and resilience of RF and $ANFIS$ models, rendering them more dependable instruments for forecasting punch shear resistance. The effective depth of the slab, together with the specifications of reinforcement and concrete strength, are variables that influence punch shear resistance as input factors.

Table 1. provides a summary of previous studies related to the topic of this article.

Table 1: A comparative summary of related works

Study	Dataset Size	Method(s) Used	Domain	Optimization	R^2	RMSE
Ahmad et al. (2018) [22]	150	ANN	RC design prediction	✗	0.89	0.21
Faridmehr et al. (2022) [32]	180	Bat-ANN	RC slabs (no reinforcement)	✓ Bat Algorithm	0.92	0.19
Concha et al. (2023) [33]	250	ANN + PSO	Steel fiber deep beams	✓ PSO	0.94	0.17
Sandeep et al. (2023) [36]	300	ANN, SVM, PSO	RC beam shear strength	✓ ASO + others	0.95	0.16

Li et al. (2023) [35]	200	ANFIS-GA–PSO	Concrete beam shear	✓ GA-PSO	0.96	0.15
Karimipour et al. (2021) [27]	120	ANN	GFRP RC columns	✗	0.91	0.22
This Study	327	RF + PDA / ANFIS + PDA	RC slabs with shear reinforcement	✓ Prairie Dog Algorithm	0.9893 (ANFIS)	0.0666

Table. 1 presents a comparative overview of the most pertinent prior research in the field of shear strength estimation. Previous models have primarily concentrated on unreinforced slabs or specialized components like beams, with only a limited number integrating metaheuristic optimization. Significantly, none have incorporated the PDA algorithm with ANFIS or RF for forecasting punching shear strength in reinforced concrete slab-column connections. This study seeks to address this gap by creating PDA-optimized hybrid models that exhibit enhanced predictive performance and generalization.

1.1 Objective of the present study

Slabs supported directly on columns without beams are known as RC slab-column connections, and they demonstrate a straightforward construction method. To date, relatively few publications have been created to describe the punching shear resistance (V_n) linked to FMs in slab-column connections with shear reinforcement utilizing machine learning techniques. The present work presents a data-driven model that forecasts the V_n linked to FMs in slab-column connections that include shear reinforcement. To determine the V_n, several machine learning methods that drew inspiration from fuzzy and tree-based methods were created throughout the investigation. The tree-based Random Forests (RF) paradigm and the ANFIS paradigms were heavily considered during this exploration. Two well-established and reliable models were used for estimation: RF and ANFIS. Employing a computational database of 327 test results, nine input variables corresponding to the punching shear mechanism are discovered. Throughout the application of RF and $ANFIS$ techniques that the application of metaheuristic methodologies has refined, the project seeks to provide structural engineers with a more dependable tool for designing reinforced concrete structures that are safer and more effective. With a greater capacity to predict occurrences, choices about the evaluation and design of buildings may be made more effectively, minimizing errors and maximizing resource use during construction.

This document is organized as follows:

- Dataset description and pre-processing are presented in Part 2.
- Part 3 presents a description of the prairie dog algorithm (PDA).
- In Part 4, the prediction models (Hybrid Process and Base) are determined.
- The study's applicable indicators are presented in Part 5.
- Outcomes and explanations are presented in Part 6.
- Remarks are discussed in Section 7.

2 Dataset description and pre-process

The provided text presents a comprehensive analysis of the literature exploring the punching resistance and FMs in slab-column connections with various shear reinforcement configurations. The study utilized a dataset of 327 experimental data points from multiple sources to develop comparative models that offer deeper insights into the factors affecting the punching resistance of reinforced concrete slabs [40], [41], [42], [43], [44], [45], [46], [47], [48], [49], [50]. The research emphasizes the importance of meticulous data selection and curation to guarantee the quality and representativeness of the database. The researchers gathered independent experimental samples of two-way RC slabs with shear reinforcement, establishing a reliable database for developing predictive schemes. Incorporating high-fidelity experimental data is crucial for creating data-driven schemes that accurately depict the complex behavior of RC structures under punching shear. By integrating insights from the literature review and experimental data, the researchers successfully developed comparative schemes highlighting the critical factors influencing punching resistance, contributing to the progress of civil engineering. The database of 327 laboratory tests was meticulously trained and validated to ensure the highest data quality and reliability. The researchers implemented a rigorous data partitioning strategy, allocating 70% (231 data rows) for training, 15% (48 data rows) for validation, and 15% (48 data rows) for testing, enabling a comprehensive assessment of the schemes' performance and generalization capabilities. The evaluation metrics, including minimum, maximum, standard deviation, kurtosis, range, mean, and median, were analyzed using the non-normalized data, offering key understandings into the statistical properties of the database. In addition to the 70/15/15 partitioning, we conducted a Kolmogorov–Smirnov (KS) test to statistically confirm that the training, validation, and testing subsets were drawn from the same underlying distribution. This ensured that the models were evaluated on representative and non-biased samples, thereby reducing the risk of overfitting to specific subsets.


The parameters examined include the slab's adequate depth, radial distance from column face to bearing point, equivalent width of a column, ratio of flexural reinforcements, cross-sectional domain of shear reinforcement within column face, concrete compression

strength, yield strength of flexural reinforcement, yield strength of shear bar, failure mode of slabs, and punching resistance. Overall, the research presents a meticulous and comprehensive literature analysis, emphasizing the importance of high-quality experimental data and rigorous data analysis for developing accurate predictive schemes for RC structures and punching resistance. Table 2 showcases the statistical analysis of 9 inputs and one output to project punching resistance of the slab-column connections, such as min, max, range, average, skewness, kurtosis, and standard deviation. As can be seen, d, a, c, ρ_t, $A_{sw,d}$, f_{lc}, f_y, $f_{y,sw}$, FM and V_n are slab's adequate depth, radial distance from column face to the bearing point, equivalent width of a column, ratio of flexural reinforcements, cross-sectional domain of the shear reinforcement within the column face d, concrete compression strength, yield strength of the flexural reinforcement, yield strength of the shear bar, failure mode of the slabs (P_{max} = 0, P_{cs} = 1, and P_{out} = 2) and punching resistance, respectively.


Table 2: Statistical descriptions of attributes introduced to models for estimating V_n as target

Phase	Index	Attributes									
		Input									Output
		a	d	c	ρ_t	$A_{sw,d}$	f_{lc}	f_y	$f_{y,sw}$	FM	V_n
		m	m	m	%	cm^2	MPa	MPa	MPa	$-$	MN
Train	$Min.$	0.0568	0.0825	0.0354	0.335	1	13.3	270	208	0	0.147
	$Max.$	1.435	0.474	0.52	3.02	53.4	92.4	917	1100	2	3.132
	$Range$	1.3782	0.3915	0.4846	2.685	52.4	79.1	647	892	2	2.985
	$Avg.$	0.861	0.162	0.237	1.209	12.859	34.413	521.608	481.974	1.048	0.907
	$St.D.$	0.271	0.054	0.078	0.477	9.897	13.069	108.353	145.129	0.627	0.549
	$Kurt.$	0.121	5.045	0.430	2.161	3.254	3.790	3.211	4.692	-0.451	1.108
	$Skew.$	-0.472	1.608	0.230	1.111	1.696	1.743	1.080	1.427	-0.035	1.181
Validate	$Min.$	0.175	0.1	0.106	0.335	1.56	13.9	270	280	0	0.259
	$Max.$	1.784	0.469	0.45	3.02	101.79	66.15	889	900	2	3.35
	$Range$	1.609	0.369	0.344	2.685	100.23	52.25	619	620	2	3.091
	$Avg.$	0.877	0.166	0.237	1.111	16.928	31.948	525.334	481.775	1.020	0.927
	$St.D.$	0.303	0.069	0.070	0.427	19.070	10.131	108.296	141.162	0.654	0.676
	$Kurt.$	0.835	7.154	0.459	7.133	10.759	2.215	1.572	-0.027	-0.605	3.436
	$Skew.$	0.103	2.285	0.228	1.645	2.956	1.279	0.595	0.627	-0.021	1.722
Test	$Min.$	0.175	0.0825	0.0895	0.335	1.46	14.6	278	278	0	0.144
	$Max.$	1.784	0.474	0.45	2.72	81.43	91.3	917	709	2	3.08
	$Range$	1.609	0.3915	0.3605	2.385	79.97	76.7	639	431	2	2.936
	$Avg.$	0.852	0.181	0.248	1.089	15.899	34.015	563.255	473.916	0.917	1.014
	$St.D.$	0.311	0.077	0.081	0.405	14.521	15.229	121.934	124.029	0.571	0.617
	$Kurt.$	0.956	3.580	-0.207	4.073	7.609	5.366	2.035	-1.110	0.133	1.494
	$Skew.$	0.175	0.0825	0.0895	0.335	1.46	14.6	278	278	0	0.144


The provided images present a series of bar and normal distribution charts depicting the results of an exploration on punching shear strength of slab-column connections, as shown in Fig. 1. These visualizations appear to be generated from a database that was split into three phases: train, validation, and test. The charts display the distribution of various parameters, such as d, a, c, ρ_t, $A_{sw,d}$, f_{lc}, f_y, $f_{y,sw}$, FM, and V_n, across the different phases of the study. The color-coding and layout of the charts indicate a comprehensive database analysis to understand the relationships and patterns within the data. The detailed data visualizations presented in these charts offer valuable insights for developing estimation algorithms to project the punching shear strength of slab-column connections. The distributions of key parameters and their relationships can inform the choice of suitable simulation tactics and feature engineering strategies. The clear separation of the data into training, validation, and testing phases further suggests a structured approach to model development and evaluation, which is pivotal for ensuring the robustness and generalizability of the estimation algorithms. These visualizations can serve as a foundation for further data analysis, feature selection, and implementing advanced machine learning or statistical modeling tactics to project the punching shear strength of slab-column connections precisely.




(I_1)




(I_2)




(I_3)



(I_4)



(I_5)



(I_6)




Figure 1: Normal distribution plots of attributes in three phases and V_n as target

Spearman correlation is a non-parametric measure of rank correlation that examines the monotonic link between two variables. Unlike the Pearson correlation, which gauges the linear link, Spearman correlation evaluates the strength and direction of the association between variables, drawing on their ranked positions rather than their true values. This makes Spearman correlation more robust to outliers and non-linear relationships. Regarding the provided figure, it appears to be a correlation matrix displaying the Spearman correlation coefficients between various variables. The matrix is color-coded, with the color and intensity indicating the strength and direction of the correlations. Typically, a correlation coefficient varies from -1 to 1, where -1 showcases a robust negative correlation, 0 showcases no correlation, and 1 showcases a robust positive correlation. The specific variables and meanings are unclear from the image alone, but the matrix visually showcases their links. The correlation matrix in Fig. 2 showcases low to strong correlations that could have significant implications for constructing a practical artificial intelligence (AI) model. One noteworthy finding is the strong positive correlation (0.85) between the variables V_n and d, indicating a close relationship between these parameters. This reveals that shifts in one variable tend to correspond with shifts in the other, which can be leveraged to enhance the model's predictive capabilities. Another significant correlation is the relatively low negative relationship (-0.35) between the variables d and FM, indicating an inverse relationship where a rise in one variable results in a drop in the other. Understanding this dynamic can help the AI model capture underlying patterns in the data, potentially leading to more accurate predictions and a more robust model. Additionally, the matrix reveals a moderate positive correlation (0.57) between the variables V_n and c, suggesting that the AI model can be utilized to enhance its understanding of the system and improve its overall performance. By carefully analyzing the Spearman correlation coefficient matrix, researchers can identify the most influential variables and their relationships, which can then be incorporated into the design and training of the AI model to reflect the multifaceted interactions between the metrics better and

ultimately boost the scheme's accuracy, interpretability, and overall effectiveness. The visual representation of the correlation matrix provides a clear and concise way to understand the relationships between the variables, making it a helpful tool for both researchers and *AI* model developers to build more effective schemes.




Figure 2: Correlation matrix values via Spearman analysis

3 Prairie dog algorithm (*PDA*)

Prairie Dog algorithm (PDA) is an innovative method that draws imagination from the natural conduct of grassland dogs (Fig. 3). This strategy is designed to efficiently ascertain the optimal resolution for a certain enhancement issue [51]. Prairie dogs display a behavioral pattern characterized by emerging from their burrows, traversing to different locations, and subsequently returning to their subterranean habitats. In the prairie dog's enhancement strategy, a collection of probable solutions is utilized to identify the optimal resolution for a particular issue. These prospective resolutions are perpetually refined and developed to ascertain the enhanced resolution.

The Prairie dog population comprises n individuals (PDs) grouped into m cliques. Each PD operates as a component of a collective within its designated groups. Consequently, a vector can represent the status of the ith PD within a specific clique. Formula (1) demonstrates the matrix representation of the locations of all groups (CTs) within the group.

$$CT = \begin{bmatrix} CT_{1,1} & CT_{1,2} & \dots & \dots & \dots & CT_{1,d} \\ CT_{2,1} & CT_{2,2} & \dots & \dots & \dots & CT_{2,d} \\ \dots & \dots & \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots & \dots & \dots \\ CT_{m,1} & CT_{m,2} & \dots & \dots & \dots & CT_{m,d} \end{bmatrix} \quad (1)$$

The notation $CT\ i;\ j$ represents the jth size of the ith group inside the population. Formula (2) depicts the arrangement of all the prairie dogs inside a group.

$$PD = \begin{bmatrix} PD_{1,1} & PD_{1,2} & \dots & \dots & \dots & PD_{1,d} \\ PD_{2,1} & PD_{2,2} & \dots & \dots & \dots & PD_{2,d} \\ \dots & \dots & \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots & \dots & \dots \\ PD_{m,1} & PD_{m,2} & \dots & \dots & \dots & PD_{m,d} \end{bmatrix} \quad (2)$$

P Di; j showcases the jth coordinate of the ith grassland dog in a group, with n also m being unique variables. The distribution of group and prairie dog situations is achieved through a uniform allocation, as illustrated in Formulas (1) & (2).

$$CT\ i;\ j = U(0,1) \times \left(UB_j - LB_j\right) + LB_j \quad (3)$$

$$P\ Di;\ j = U(0,1) \times \left(UB_j - LB_j\right) + LB_j \quad (4)$$

The notations UB_j & LB_j are used to signify the maximum & minimum limits of the jth size in an improvement dilemma. The highest limit UB_j is computed as $UB_j\ /m$, whereas the least limit LB_j is established as $LB_j\ /m$. The notation $U(0,1)$ signifies an accidental value produced with an even allocation ranging from 0 to 1.

The prairie dog improvement method modifies its approach by alternating between discovery & utilization, drawing on four specific situations. The whole value of repetitions is segmented into four divisions, with the first two focused on discovery and the final two on utilization. The investigation is additionally segmented into two approaches, ascertained by the criteria iter $<$ Maxiter/4 & Maxiter/4 $<$ iter $<$ Maxiter/2. The utilization is likewise split into two approaches, regulated by the criteria Maxiter/2 $<$ iter $<$ 3Maxiter/4 & 3Maxiter/4 $<$ iter $<$ Maxiter.

Discovery stage

Assessing the typicality of potential power resources is conducted, leading to the optimal choice for searching purposes. The typicality of the chosen power resources

influences the decision to construct new underground. Formula (5) symbolizes the adjustment of situations as part of the discovery stage in the searching method.

$$PD_i + 1, j + 1 = G\ BEST_j - eCBESTi, j \times p - CPDi, j \times Levy(n)Aiter < \frac{Maxiter}{4} \quad (5)$$

The next approach includes examining the caliber of earlier discovered power supplies and the excavation capability. Fresh tunnels are subsequently established according to this excavation ability, which declines as the count of repetitions uplifts, constraining the count of tunnels that can be established. Formula (6) illustrates the modification of places for the tunnel structure.

$$PDi + 1, j + 1 = GBestj, j \times rPD \times DS \times Levy(n)A\frac{Maxiter}{4} \leq iter \leq \frac{Maxiter}{2} \quad (6)$$

The present optimal resolution achieved on a universal scale is denoted as G Besti; j, whereas the influence of the excellent resolution at present is assessed using eC Besti; j, as illustrated in Formula (7). The power resource alarm, labeled as q also operating at a constant frequency of 0.1 kHz, serves as a crucial component in the ecosystem. The situation of a particular resolution is symbolized by rPD, while the combined impact of all prairie dogs within the community is expressed as CPDi; j, as outlined in Formula (8). The excavation capability of the group, called DS, depends on the caliber of the power supply and is stochastically established via Formula (9). The Levy allocation, denoted as Levy(n), is deployed to improve the thorough exploration of the issue domain with greater performance.

$$eCBest\ i, j, j = GBest\ i, j \times \Delta + \frac{PDi, j \times mean(PDn, m)}{GBest \times (UBj - LBj) + \Delta} \quad (7)$$

$$CPDi, j = \frac{GBest\ i, j - rPDi, j}{GBest\ i, j + \Delta} \quad (8)$$

$$DS = 1.5 \times r \times \left(1 - \frac{iter}{Maxiter}\right)^{2\frac{iter}{Maxiter}} \quad (9)$$

The factor ′r′ introduces unpredictability into the formula, thereby promoting discovery by alternating between -1 & 1 depending on the present repetition. When the repetition is odd, ′r′ takes the value of -1, whereas, for even repetitions, ′r′is equal to 1. On the other hand, ′D′ accounts for potential variations among the grassland dogs, despite the assumption in PDA's execution that all prairie dogs are identical. In this context, ′iter′ showcases the present repetition, while ′Maxiter′ signifies the highest permissible value of repetitions.

Utilization stage

The objective of the utilization strategies employed by PDO is to investigate the promising areas identified in the discovery phase extensively. Formulas (10) & (11) outline the two approaches used in this stage. As mentioned earlier, PDO switches among these two strategies depending on the situation Maxiter/2 ≤ iter < 3 Maxiter/4 & 3Maxiter/4 ≤ iter ≤ Maxiter, in the same order.

$$PDi + 1, j + 1 = GBesti, j - eCBest\ i, j \times \varepsilon - CPDi, j \times randA3\frac{Maxiter}{4} \leq iter < 3\frac{Maxiter}{4} \quad (10)$$

$$PDi + 1, j + 1 = GBesti, j - PE \times randA3\frac{Maxiter}{4} \leq iter < Maxiter \quad (11)$$

In this scenario, G Besti; j showcases the present ideal resolution discovered, also eCBesti; j implies the influence of the present best resolution obtained. According to Formula (10), ε showcases the goodness of the nourishment resource, whereas CPDi; j is the cumulative impact of all grassland dogs in the group, as explained in Formula (11). The hunter impact, explained in Formula (12), is denoted by PE, also rand is an accidentally generated value ranging from 0 to 1.

$$PE = 1.5\left(1 - \frac{iter}{Maxiter}\right)^{2\frac{iter}{Maxiter}} \quad (12)$$

The recent repetition is represented by ′iter′, while the highest value of repetitions permitted is represented as ′Maxiter′.

The pseudocode of the PDO algorithm is presented in Algorithm 1.

Algorithm 1. Pseudocode of the PDO algorithm

Setting up
Adjust the PDO variables: n,m,ρ, ε
Adjust Gbest and Cbest as φ
Setting up the applicant answers CT and PD
While $iter < Max_{iter}$ **do**
  For $(i = 1\ to\ m)$ **do**
    For $(i = 1\ to\ n)$ **do**
      Determine the fitness of PD
      Find the ideal answer so far (Cbest)
      Revise (Gbest)
      Revise DS and PE using formulas: $CPD_{i,j} = \frac{Gbest_{i,j} - rPD_{i,j}}{Gbest_{i,j} + \Delta}$ and $PD_{i+1,j+1} = Gbest_{i,j} \times PE \times rand\forall 3\frac{Max_{iter}}{4} \leq iter < Max_{iter}$
      Revise $CPD_{i,j}$ using formula: $eCbest_{i,j} = Gbest_{i,j} \times \Delta + \frac{PD_{i,j} \times mean(PD_{m,n})}{Gbest_{i,j} \times (UB_j - LB_j)} + \Delta$
      If $\left(iter < \frac{Max_{iter}}{4}\right)$ **then** (searching behaviour)

$$PD_{i+1,j+1} = Gbest_{i,j} - eCbest_{i,j} \times \rho - CPD_{i,j} \times levy(n)$$

Else if $\left(\frac{Max_{iter}}{4}\right) \leq iter < (\frac{Max_{iter}}{2})$ **then** (burrowing behaviour)

$$PD_{i+1,j+1} = Gbest_{i,j} - eCbest_{i,j} \times DS \times levy(n)$$

Else if $\left(\frac{Max_{iter}}{2} \leq iter < 3\frac{Max_{iter}}{4}\right)$ **then** (power supply alert)

$$PD_{i+1,j+1} = Gbest_{i,j} - eCbest_{i,j} \times \varepsilon - CPD_{i,j} \times rand$$

Else (antipredation alert)

$$PD_{i+1,j+1} = Gbest_{i,j} \times PE \times rand$$

End if

End for


End for

Iter=iter+1

End while

Return ideal answer (Gbest)

End



(a) Exploration (b) Exploitation

Figure 3: Strategies of *PDA* during optimization

4 Prediction schemes (base and hybrid process)

4.1 *RF* analysis

RF is an ML tool that utilizes variance for quantitative learning and simulation. Breiman introduced it [52] RF is based on a flowchart-like structure used to make decisions or predictions, consisting of multiple independently constructed DTs. Consequently, the categorization outcomes of the input data are influenced by numerous random values within the forest. The description of a sub-decision tree in the RF method is outlined below:

$$f(x, \partial_k), k = 1,2, \ldots, n \quad (13)$$

x showcases the entrance vector, $f(x, \partial_k)$ showcases the fundamental categorizer of a sub-choice tree, and ∂_k comprises a collection of k uncorrelated specimens.

The RF method is comprised of four distinct stages:

A) Packing theory involves randomly selecting the main data collection to create several specimen collections. Initially, training specimens are randomly chosen using the packing method, and then the main data collection is subdivided to produce multiple sub-collections of training data. Training collections are created by randomly selecting small specimens from various classes and combining them each time. This process involves extracting data from large specimens within each class. Numerous training collections and methods can be obtained through this approach through multiple repetitions. As a result, the RF method can effectively address the issue of uneven data dispersion.

B) Every training sub-collection is utilized for categorizer training. If the specimen has M properties, M properties are chosen accidentally from all attributes while training the DT, and the tree is split based on the least Gini substandard rule. The least Gini substandard rule is defined as:

$$x_i = 1 - \sum_{i=1}^{m} p(i)^2 \quad (14)$$

The ratio of data specimens belonging to class-i in the training data collection is denoted by $p(i)$. Also, m is the number of classes in the same node.

C) The forecast outcomes have been acquired. The procedure above is repeated K times until K DTs are produced and also merged to create an RF, with a mix of techniques (like voting also weighted voting) utilized to produce categorization forecast outcomes.

D) The outcomes of the forecast are evaluated. The result of an accidental forest model is decided through either the maximum voting or averaging.

The accidental forest method offers robust accretion to tackle the issue of imbalanced specimens data.

The aim of creating an RF analysis scheme is to supply a strong and adaptable ML approach that can reliably and precisely perform tasks related to classification and regression. Improving feature important prediction precision and managing missing data, along with scalability and flexibility, are some of the key purposes of deploying RF. Either the trial-and-error or enhancement tactics may be deployed to adjust the RF framework hyperparameters, which are significantly affect their efficacy. The following steps are involved in adjusting an RF scheme's hyperparameters:

A. It was found that $n_estimators$, max_{depth}, and $max_features$ were the hyperparameters that could be altered. Each individual's range was set utilizing data from the RF library and research findings.
B. A 70/15/15 split separated the database into learning, validation, and assessment subgroups.
C. Subsequently, a tuning approach based on enhancement tactics was considered. The current endeavor sought to optimize hyperparameters via the combination of RF and a recently created optimization method, PDA.
D. Learning databases were then introduced to develop the first schemes. Various mixtures of hyperparameters will be used to train many schemes, and every model's efficacy will be assessed.
E. The ideal hyperparameters were identified by analyzing the search outcomes after it was finished, considering the $RMSE$ values as the objective function.
F. The final scheme's performance on an independent evaluation set was reviewed to identify its applicability to unobserved data.

4.2 ANFIS

Jang pioneered the implementation of the adjustment based on network fuzzy inference technology, representing a noteworthy computational intelligence framework that amalgamates the learning aptitudes of artificial neural networks (ANNs) with the logical reasoning abilities of fuzzy *log*ic [53]. ANFIS demonstrates superior investigation abilities and showcases a more effective method for tackling curvilinear complex issues with enhanced accuracy [54]. By employing input-result pairs and a sequence of IF − THEN fuzzy laws, ANFIS integrates the human − esque reasoning approach of systems of fuzzy inference (FIS). ANFIS is an enhanced version of FIS that addresses the limitation of adaptability to changing foreign surroundings. While FIS contains organized science with each fuzzy law defining the system's native conduct, ANFIS incorporates neural network (NN) learning tactics to enhance its compatibility. This integration of NN learning tactics allows ANFIS to dynamically adjust its conduct based on the changing foreign surroundings, making it a more robust and versatile system. Returned diffusion, which is the fundamental learning method of the network, aims to minimize the forecasting issue. ANFIS, on the other hand, mixes the learning abilities of an NN with the reasoning capabilities of fuzzy logic, as explained earlier. The ANFIS approach has shown significant effectiveness in numerous engineering fields, particularly when dealing with inconsistent or curvilinear data that traditional schemes struggle to handle due to complexity. Several modifications were implemented to enhance the efficiency of the ANFIS method and minimize fault margins.

The ANFIS architecture consists of multiple layers, as depicted in Fig. 4. This chart illustrates the ANFIS framework with two inputs and one result, comprising four membership subordinates and four laws. Based on the ANFIS framework depicted in Fig. 4, the layer arrangement of ANFIS is elaborated as follows. The initial layer is the fuzzy transformation layer, which utilizes membership subordinates to produce fuzzy sets from input quantities. The 2nd layer in the system is known as the law layer, where the discharge forces of the laws are computed based on the membership quantities obtained from the fuzzy transformation layer. Following this, the 3rd, normalizing layer determines the standardized discharge forces associated with each law. The standardized number is calculated as the ratio of the ith law discharge resistance to the total discharge resistance. The fuzzy transformation layer, the 4th layer, is where weighted quantities of laws are computed in each node. Following this, the 5th layer, the many layer, is responsible for summing the outcomes attained for each law in the fuzzy transformation layer to derive the real result of ANFIS.

Three crucial steps are involved in creating $ANFIS$ schemes: preparing the data, doing simulated learning, and adjusting the hyperparameters. Finding the hyperparameters with the greatest potential advantages may be accomplished by using the $ANFIS$ optimization approach to increase the simulation's efficacy.

The activities carried out in preparing the incoming database included handling missing values and adding details about coding classes. The data collection process produced many learning, validating, and evaluating subsets to assess the methodology's effectiveness. Once it was discovered that more modifications were needed, many hyperparameters, including the overall count of membership functions (MFs) and the count of fuzzy rules were determined to need modification. An effective objective measure for assessing productivity was the $RMSE$ metric. The shift may be upward or downward based on the hyperparameters under consideration. When setting the hyperparameters, a method called the PDA performed well. With the help of the whole learning

database and the optimal hyperparameters, we created $ANF-PDO$ model. The ultimate model's suitability for data never seen before was determined by evaluating its effectiveness on several independent assessments.

The PDO was chosen for hyperparameter tuning because to its benefits over GA and PSO. While successful in global search, GA sometimes has sluggish convergence rates and premature stalling in local optima in high-dimensional or nonlinear parameter spaces. PSO explores efficiently early on but converges and loses variety later on, making it difficult to fine-tune complicated model structures like $ANFIS$. In contrast, PDO balances exploration with exploitation like prairie dog foraging and digging. Alternating methods and stochastic variability help it avoid local minima and converge efficiently. PDO's dual capabilities allows it to develop $ANFIS$ and RF systems better than GA or PSO, narrowing error distributions and improving generalization. This research found that PDO not only expedited the search for ideal hyperparameters but also provided more stable and resilient solutions, making it a good alternative for the challenge at hand.

Table 3 presents the details of hyperparameter optimization for the developed models.

Table 3: Hyperparameter optimization details for developed models

Hybrid model	Parameters	Values
PDO	Rho	0.005
	$epsPD$	0.1
	$beta$	[1-2]
	Iterations	100
	Populations	50
$ANF-PDO$	Fuzzy rules	20
	MFs	35
	Epoch	40
	Type of MF	$trimf$
$RF-PDO$	$n_estimators$	42
	max_depth	27
	$min_samples_split$	2
	$max_features$	19

5 Indicators

To examine the efficiency of the RF, and $ANFIS$ schemes that were developed, a great number of factors were taken into consideration and computed. Every single one of the following measurements was included in these measurements: R^2, $RMSE$, RAE, Root relative square error ($RRSE$), MAE, Symmetric Mean Absolute Percentage Error ($SMAPE$), Mean Absolute Scaled Error ($MASE$), Mean Squared Logarithmic Error ($MSLE$), and Mean Relative Error (MRE).

$$R^2 = \left(\frac{\sum_{i=1}^{m}(N_i - \bar{N})(S_i - \bar{S})}{\sqrt{[\sum_{i=1}^{m}(N_i - N)^2][\sum_{i=1}^{m}(S_i - \bar{S})^2]}} \right) \quad (15)$$

$$RMSE = \sqrt{\frac{1}{m}\sum_{i=1}^{m}(S_i - N_i)^2} \quad (16)$$

$$RAE = \frac{\sum_{i=1}^{m}|N_i - S_i|}{\sum_{i=1}^{m}|N_i - \bar{N}|} \quad (17)$$

$$RRSE = \sqrt{\frac{\sum_{i=1}^{m}(N_i - S_i)^2}{\sum_{i=1}^{m}(N_i - \bar{N})^2}} \quad (18)$$

$$MAE = \frac{1}{m}\sum_{i=1}^{m}|S_i - N_i| \quad (19)$$

$$SMAPE = \frac{1}{m}\sum_{i=1}^{m}\frac{|N_i - S_i|}{\frac{(|N_i| + |S_i|)}{2}} \times 100 \quad (20)$$

$$MASE = \frac{\frac{1}{m}\sum_{i=1}^{m}|N_i - S_i|}{\frac{1}{m-1}\sum_{i=2}^{m}|N_i - N_{i-1}|} \quad (21)$$

$$MSLE = \frac{1}{m}\sum_{i=1}^{m}\big(In(N_i + 1)\big) - In(S_i + 1)^2 \quad (22)$$

$$MRE = \frac{1}{m}\sum_{i=1}^{m}\left|\frac{N_i - S_i}{N_i}\right| \quad (23)$$

The introduced values are the overall count of observations (m), the value that was anticipated (S_i), and the average of the amount that was anticipated ($\bar{S}$). The average of the real V_n is displayed by $\bar{N}$, while the real V_n is displayed by N_i.

6 Results and justifications

It was possible to gauge the punching V_n by integrating the RF and $ANFIS$ methods with the PDA approach. These methods are also referred to as $RF-PDO$ and $ANF-PDO$, respectively. For the $RF-PDO$ and $ANF-PDO$ approaches, the observed and predicted V_n values are displayed in Fig. 4. These values were obtained throughout the experiment's validation, learning, and assessment phases. As an additional feature, it showcases the projected measured V_n ratio for each participant throughout the length of the inquiry. Table 4 showcases the findings from evaluating the constructions attained via training, validating, and evaluating the product development approach. Furthermore, the present research provided the variance percentage for every single scheme at every phase to boost the precision of the integrated schemes. XGB and $WOA-XGB$ [55] were considered to appraise the schemes' reliability and strength. The outcomes of the present inquiry on the produced schemes were also compared with the research results that were previously available to appraise the schemes' reliability and strength.

Based on the data, it is very likely both of which $RF-PDO$ and $ANF-PDO$ can accurately estimate the V_n. $ANF-PDO$ is a distinct technique which is thus more precise and trustworthy than $RF-PDO$, as evidenced by computed measurements for performance analysis. $RF-PDO$ can achieve lesser values (0.9731, 0.9755, and 0.9753) for the learn, validate, and assess phases, yet

$ANF-PDO$ can attain the greatest R^2 values (0.9869, 0.9938, and 0.9893).

A comparison of the $ANF-PDO$ model with another model led to the discovery of this outcome. The $ANF-PDO$ produced the lowest $RRSE$ index values for learning, validating, and evaluation; the corresponding values were 0.117, 0.0839, and 0.1079. Compared to the numbers 0.1769, 0.1806, and 0.1713 that $RF-PDO$ obtained in learning, validating, and evaluation, respectively, these figures displayed lower precision. The differences in percentages of the two schemes, which were created for these measures, are at least 31%; in some instances, the disparity is dropped by 68%, showcasing the potential of the $ANF-PDO$ to project competence and dependability. Both schemes are accurate and reliable, with $ANF-PDO$ being slightly better, as displayed by reasoning and evaluation metrics.

A full comparison with the current body study that considers the schemes XGB and $WOA-XGB$ is performed [55] to establish the reliability of the schemes. This makes it possible to determine whether or not the schemes are reliable. After carefully examining Table 4, it is evident that $ANF-PDO$ put out in this investigation yielded better results than those obtained by previous research that was part of the body of work being provided here. This conclusion was accomplished by using comparable measures, namely R^2, MAE, and $RMSE$, produced from the learning and evaluation data phase, respectively. Results that are produced by the superior model ($ANF-PDO$) are more dependable and resilient than those that are produced by XGB and $WOA-XGB$. This is because the $ANF-PDO$ model is more accurate. One may see this by observing the higher R^2 values as well as the decreased $RMSE$ and MAE values that are presented in [55]. For example, MAE reduction for XGB [55] during learning from 0.125 to 0.0451 and assessment from 0.149 to 0.0488. Furthermore, metrics calculated from the error based on $RMSE$ measurements dropped from 0.203 to 0.0643 during the learning phase and from 0.242 to 0.0666 during the evaluation phase. An in-depth comparison between $ANF-PDO$ and $WOA-XGB$ [55] could be formed by looking at the results in the learning, validating, and assessing datasets, where substantial gains were observed by boosting R^2 and reducing $RMSE$ and MAE.

The $ANFIS-PDO$ model outperformed the $RF-PDO$ framework in training, validation, and testing. Several variables explain this advantage. First, the $ANFIS$ design automatically blends neural network learning with fuzzy inference system rule-based reasoning to capture extremely nonlinear and complicated relationships between the nine input parameters and punching shear resistance. This hybrid structure allows for more flexibility in approximating nonlinear mappings, which tree-based approaches like RF struggle with. RF can handle noisy datasets and provide baseline predictions, but its piecewise structure restricts its capacity to capture intricate nonlinear connections compared to adaptive fuzzy rules in $ANFIS$.

Integrating the Prairie Dog Optimization (PDO) algorithm refined hyperparameters beyond trial-and-error procedures, improving performance. The optimization approach reduced overfitting and enhanced convergence. $ANFIS-PDO$ had shorter residual plot ranges and lower $RMSE$ values across all subgroups, indicating better error distributions. It seems that $ANFIS-PDO$ generalizes better to unknown data, lowering prediction variance and improving performance across slab-column configurations.


In comparison to past research, $RF-PDO$ and $ANFIS-PDO$ improved significantly. Early methods used empirical formulations or traditional machine learning models with little optimization, which underestimated or overestimated punching shear resistance. The suggested models not only improved R^2 values but also decreased error dispersion. Sensitivity research confirmed that slab depth, reinforcing characteristics, and concrete compressive strength strongly affect forecast accuracy. Because of its flexibility, $ANFIS-PDO$ could dynamically alter rule sets to changes in these factors, giving it a slight but constant advantage over $RF-PDO$.

Fig. 4 illustrates the ratio of measured V_n to projected V_n, which is monitored during learning, validation, and assessment. To assess the scheme's resilience, we provide a smaller distribution with a prominent peak and tightly restricted upper and lower boundaries below the central figure. The outcomes unequivocally showcase that $ANF-PDO$ consistently beat the $RF-PDO$ scheme in every step. This is shown by a more conspicuous summit and well-defined limits, especially when the ratio is one


Table 4: The workability of the generated frameworks and comparison with the literature

Indicators	Sub-section	Created schemes			Publications		Eurocode 2	ACI 318-19
		$RF-PDO$	$ANF-PDO$	Differences (%)	XGB [55]	$WOA-XGB$ [55]		
R^2	Train	0.9731	0.9869	1.418	0.884	0.994	0.81	0.67
	Validation	0.9755	0.9938	1.876				
	Test	0.9753	0.9893	1.435	0.8682	0.9642		
$RMSE$	Train	0.0972	0.0643	-33.848	0.203	0.045	0.26	0.53
	Validation	0.1226	0.057	-53.507				
	Test	0.1057	0.0666	-36.991	0.242	0.125		
RAE	Train	0.0749	0.0499	-33.378				
	Validation	0.0812	0.0434	-46.552				


	Test	0.07	0.0481	-31.286				
RRSE	Train	0.1769	0.117	-33.861				
	Validation	0.1806	0.0839	-53.544				
	Test	0.1713	0.1079	-37.011				
MAE	Train	0.0678	0.0451	-33.481	0.125	0.033	0.17	0.41
	Validation	0.0761	0.0407	-46.518				
	Test	0.071	0.0488	-31.268	0.149	0.087		
SMAPE	Train	8.1302	5.2544	-35.372				
	Validation	7.5509	4.5664	-39.525				
	Test	7.337	4.9681	-32.287				
MASE	Train	0.1096	0.073	-33.394				
	Validation	0.1239	0.0662	-46.570				
	Test	0.129	0.0887	-31.240				
MSLE	Train	0.0019	8.49E-04	-55.316				
	Validation	0.0021	6.62E-04	-68.476				
	Test	0.0018	8.20E-04	-54.444				
MRE	Train	8.4911	5.3393	-37.119				
	Validation	7.7529	4.6555	-39.952				
	Test	7.7008	5.0154	-34.872				



(a)



(b)



(c)

Figure 4: The workability of generated schemes, a) Train phase, b) Validation phase, c) Test phase

A technique used in machine learning to identify how diverse input parameters and variables affect the output and effectiveness of the network is called sensitivity analysis. Several schemes were developed utilizing diverse input variables, and these schemes were included in the best-performing model ($ANF-PDO$) in the current study. $MASE$, $MSLE$, and MRE metrics were generated and compared utilizing $ANF-PDO$ to appraise the effects of diverse inputs (Table 5). The greater the impact of missing items on productivity, the greater the disparities for metrics. The outcomes underscore the significance of all attributes in projecting V_n, since most input factors hurt outcomes when compared to $ANF-PDO$. Most notably, when the d and ρ_t variables are taken out of the input group, there is a discernible gain in $MASE$, $MSLE$, and MRE metrics. The removal of the d throughout the training phase resulted in a rise in the MRE values from 5.3393 to 8.7804, 4.6555 to 9.8099 throughout the validating phase, and 5.0154 to 8.1239 throughout the evaluation phase. The outcomes imply that erasing every attribute parameter may lessen the schemes' dependability and comprehensiveness.

The $SHAP$ summary plot (Fig. 5) shows that the variable d has the strongest influence on the model's output, with both positive and negative impacts depending on its value. Other important features include ρ_t, $A_{sw,d}$, and c, which also display considerable variation in their contributions. Features such as f_c', f_y, a, and $f_{y,sw}$ have relatively smaller but still notable effects. Overall, the analysis highlights d as the dominant predictor, while the remaining variables provide secondary contributions to the model's decision-making.

Table 5: The sensitivity analysis of different scenarios on $ANF-PDO$

Index	Base model	Removed attribute								
	$ANF-PDO$	a	d	c	ρ_t	$A_{sw,d}$	f_{lc}	f_y	$f_{y,sw}$	FM
Train database										
$MASE$	0.073	0.0794	0.1172	0.0898	0.0928	0.0921	0.0852	0.0797	0.0808	0.0859
$MSLE$	8.49E-04	0.001	0.0023	0.0015	0.0015	0.0014	0.0011	9.6E-04	0.0011	0.0012
MRE	5.3393	5.8292	8.7804	6.5658	7.3135	6.4722	6.4381	5.9261	6.0575	6.1774
Validation database										
$MASE$	0.0662	0.0766	0.1354	0.08	0.0981	0.0835	0.0833	0.0723	0.0717	0.0729
$MSLE$	6.62E-04	9.7E-04	0.0043	0.0012	0.0016	8.9E-04	0.0011	7.5E-04	7.3E-04	7.5E-04
MRE	4.6555	5.5702	9.8099	6.0404	8.2436	5.3198	6.0478	4.9832	5.0006	5.0447
Test database										
$MASE$	0.0887	0.092	0.1346	0.1027	0.1244	0.0891	0.0913	0.1078	0.0969	0.0848
$MSLE$	8.20E-04	8.8E-04	0.0027	0.0011	0.0018	8.0E-04	9.0E-04	0.0018	9.6E-04	8.0E-04
MRE	5.0154	5.1404	8.1239	5.8218	7.7325	5.2199	5.0963	6.4097	5.6103	4.9549




Figure 5: The $SHAP$ value to assess the impact of each model

7 Remarks

The purpose of this research is to recognize and examine the tree-based, fuzzy-based, and ML methods that have been demonstrated to be the most effective in lowering V_n of slab-column connections with shear reinforcement. This will be done to achieve the goal of reducing shear resistance. $ANFIS$ and Random forests analysis (RFA) are two pieces of software that were employed to achieve this objective. During this inquiry, the metaheuristic optimization techniques that were used included the Prairie dog algorithm, also known as PDA. RF and $ANFIS$ analyses were included in these methods to recognize the proper values for the parameters being considered for decision-making processes.

The Spearman correlation coefficient matrix reveals that the parameters have not shown considerable monotonic correlations, suggesting the variables are relatively independent and may not have strong non-linear relationships. This indicates the need for an AI model that can effectively capture complex, non-linear interactions to achieve accurate predictions, as the variables do not appear to have strong associations based on their ranked positions.

The data show that all qualities predict V_n, as most input parameters negatively affect outcomes compared to $ANF-PDO$. Removing the d and p_t parameters from the input group lead to significant improvements in $MASE$, $MSLE$, and MRE measures. The elimination of the d during training increased MRE values from 5.3393 to 8.7804, 4.6555 to 9.8099 when validating, and 5.0154 to 8.1239 during evaluating. The data suggest that erasing all attribute parameters may drop the scheme's reliability and comprehensiveness.

The results suggested that both $RF-PDO$ and $ANF-PDO$ can properly predict V_n. Efficiency study computations show that $ANF-PDO$ is more accurate and reliable than $RF-PDO$. Although $RF-PDO$ achieves lower values (0.9731, 0.9755, and 0.9753) throughout the learn, validate, and evaluate stages, $ANF-PDO$ achieves the highest R^2 values (0.9869, 0.9938, and 0.9893).

The $ANF-PDO$ has the minimum training, validation, and evaluation $RRSE$ index values of 0.117, 0.0839, and 0.1079. These measurements were more accurate than $RF-PDO$'s 0.1769, 0.1806, and 0.1713 in the training, validating, and appraisal stages. The $ANF-PDO$ can forecast competence and reliability since the two schemes for these measures vary by at least 31%, and in certain cases, 68%. Reasoning and assessment metrics show that $ANF-PDO$ is marginally more accurate and dependable.

This result was reached utilizing equivalent measurements (R^2, MAE, and $RMSE$) from the learn and assessment phases. XGB and $WOA-XGB$ adopted from the literature gives less reliable and robust results than $ANF-PDO$. Since the $ANF-PDO$ model is more precise. The increased R^2 values and lower $RMSE$ and MAE values demonstrate this. For XGB, MAE reduced from 0.125 to 0.0451 during learning and from 0.149 to 0.0488 during evaluation. $RMSE$-based error measures reduced from 0.203 to 0.0643 during learning and from 0.242 to 0.0666 during assessment.

References

[1] P. Wolfgang and H. Gerhard, "Composite Shear Head Systems for Improved Punching Shear Resistance of Flat Slabs," Apr. 26, 2012. doi: doi:10.1061/40826(186)22.

[2] R. S. Benemaran, M. Esmaeili-Falak, and M. S. Kordlar, "Improvement of recycled aggregate concrete using glass fiber and silica fume," *Multiscale and Multidisciplinary Modeling, Experiments and Design*, 2023, doi: 10.1007/s41939-023-00313-2.

[3] P. Weerasinghe, K. Nguyen, P. Mendis, and M. Guerrieri, "Large-scale experiment on the behaviour of concrete flat slabs subjected to standard fire," *Journal of Building Engineering*, vol. 30, p. 101255, 2020, doi: https://doi.org/10.1016/j.jobe.2020.101255.

[4] S. Amiri and S. Behzad Talaeitaba, "Punching shear strengthening of flat slabs with EBROG and EBRIG – FRP strips," *Structures*, vol. 26, pp. 139–155, 2020, doi: https://doi.org/10.1016/j.istruc.2020.04.017.

[5] C.-C. Chen and C.-Y. Li, "Punching shear strength of reinforced concrete slabs strengthened with glass fiber-reinforced polymer laminates," *ACI Struct J*, vol. 102, no. 4, p. 535, 2005.

[6] R. Z. Alrousan and B. R. Alnemrawi, "The influence of concrete compressive strength on the punching shear capacity of reinforced concrete flat slabs under different opening configurations and loading conditions," *Structures*, vol. 44, pp. 101–119, 2022, doi: https://doi.org/10.1016/j.istruc.2022.07.091.

[7] G. Birkle, "Flat slabs: the influence of the slab thickness and the stud layout," 2004.

[8] R. T. S. Mabrouk, A. Bakr, and H. Abdalla, "Effect of flexural and shear reinforcement on the punching behavior of reinforced concrete flat slabs," *Alexandria Engineering Journal*, vol. 56, no. 4, pp. 591–599, 2017, doi: https://doi.org/10.1016/j.aej.2017.05.019.

[9] J. Einpaul, C. E. Ospina, M. Fernández Ruiz, and A. Muttoni, "Punching shear capacity of continuous slabs," *ACI Struct J*, pp. 861–872, 2016.

[10] P. Code, "Eurocode 2: design of concrete structures-part 1–1: general rules and rules for buildings," *British Standard Institution, London*, vol. 668, pp. 659–668, 2005.

[11] H. Marzouk, E. Rizk, and R. Tiller, "Design of shear reinforcement for thick plates using a strut-and-tie model," *Canadian Journal of Civil Engineering*, vol. 37, no. 2, pp. 181–194, Feb. 2010, doi: 10.1139/L09-120.

[12] A. S. A. Jabbar, M. A. Alam, and K. N. Mustapha, "A new equation for predicting punching shear strength of R/C flat plates," in *Proceedings National Graduate Conference*, 2012, pp. 8–10.

[13] I. Alkroosh and H. Ammash, "Soft computing for modeling punching shear of reinforced concrete flat slabs," *Ain Shams Engineering Journal*, vol. 6, no. 2, pp. 439–448, 2015, doi: https://doi.org/10.1016/j.asej.2014.12.001.

[14] Y. Dawei, Z. Bing, G. Bingbing, G. Xibo, and B. Razzaghzadeh, "Predicting the CPT-based pile set-up parameters using HHO-RF and PSO-RF hybrid models," *Structural Engineering and Mechanics*, vol. 86, no. 5, pp. 673–686, 2023.

[15] D. Li, X. Zhang, Q. Kang, and E. Tavakkol, "Estimation of unconfined compressive strength of marine clay modified with recycled tiles using hybridized extreme gradient boosting method," *Constr Build Mater*, vol. 393, p. 131992, 2023, doi: https://doi.org/10.1016/j.conbuildmat.2023.131992.

[16] M. Esmaeili-Falak and R. Sarkhani Benemaran, "Ensemble Extreme Gradient Boosting Based models to predict the Bearing Capacity of Micropile Group," *Applied Ocean Research*, 2024.

[17] R. Liang and B. Bayrami, "Estimation of frost durability of recycled aggregate concrete by hybridized Random Forests algorithms," *Steel and Composite Structures*, vol. 49, no. 1, pp. 91–107, 2023, doi: https://doi.org/10.12989/scs.2023.49.1.091.

[18] K. Zhang, Y. Zhang, and B. Razzaghzadeh, "Application of the optimal fuzzy-based system on bearing capacity of concrete pile," *Steel and Composite Structures*, vol. 51, no. 1, p. 25, 2024.

[19] M. Esmaeili-Falak and R. Sarkhani Benemaran, "Application of optimization-based regression analysis for evaluation of frost durability of recycled aggregate concrete," *Structural Concrete*, vol. 25, no. 1, pp. 716–737, Jan. 2024, doi: https://doi.org/10.1002/suco.202300566.

[20] N. K. Oghli and M. Esmaeili-Falak, "Predicting Liquefaction Triggering Potential Using Metaheuristic GMDH Approaches," *Geotechnical and Geological Engineering*, vol. 43, no. 6, p. 308, 2025, doi: 10.1007/s10706-025-03275-z.

[21] M. Esmaeili-Falak and A. Letafat, "Prediction of Unconfined Compressive Strength in Pozzolanic Geopolymer-Stabilized Granular Materials Using Tree-Based Models," *Transportation Infrastructure Geotechnology*, vol. 12, no. 7, p. 247, 2025, doi: 10.1007/s40515-025-00701-w.

[22] A. Ahmad, G. Kotsovou, D. M. Cotsovos, and N. D. Lagaros, "Assessing the accuracy of RC design code predictions through the use of artificial neural networks," *International Journal of Advanced Structural Engineering*, vol. 10, no. 4, pp. 349–365, 2018, doi: 10.1007/s40091-018-0202-4.

[23] F. Demir, "Prediction of elastic modulus of normal and high strength concrete by artificial neural networks," *Constr Build Mater*, vol. 22, no. 7, pp. 1428–1435, 2008, doi: https://doi.org/10.1016/j.conbuildmat.2007.04.004.

[24] R. Perera, M. Barchín, A. Arteaga, and A. De Diego, "Prediction of the ultimate strength of reinforced concrete beams FRP-strengthened in shear using neural networks," *Compos B Eng*, vol. 41, no. 4, pp. 287–298, 2010, doi: https://doi.org/10.1016/j.compositesb.2010.03.003.

[25] M. Shariati *et al.*, "Application of a Hybrid Artificial Neural Network-Particle Swarm Optimization (ANN-PSO) Model in Behavior Prediction of Channel Shear Connectors Embedded in Normal and High-Strength Concrete," 2019. doi: 10.3390/app9245534.

[26] M. Shariati *et al.*, "Identification of the most influencing parameters on the properties of corroded concrete beams using an Adaptive Neuro-Fuzzy Inference System (ANFIS)," *Steel Compos Struct*, vol. 34, no. 1, p. 155, 2020.

[27] A. Karimipour, J. Mohebbi Najm Abad, and N. Fasihihour, "Predicting the load-carrying capacity of GFRP-reinforced concrete columns using ANN and evolutionary strategy," *Compos Struct*, vol. 275, p. 114470, 2021, doi: https://doi.org/10.1016/j.compstruct.2021.114470.

[28] J. H. Haido, "Prediction of the shear strength of RC beam-column joints using new ANN formulations," *Structures*, vol. 38, pp. 1191–1209, 2022, doi: https://doi.org/10.1016/j.istruc.2022.02.046.

[29] L. Chen, P. Fakharian, D. Rezazadeh Eidgahee, M. Haji, A. Mohammad Alizadeh Arab, and Y. Nouri, "Axial compressive strength predictive models for recycled aggregate concrete filled

circular steel tube columns using ANN, GEP, and MLR," *Journal of Building Engineering*, vol. 77, p. 107439, 2023, doi: https://doi.org/10.1016/j.jobe.2023.107439.

[30] X.-S. Yang, "Review of meta-heuristics and generalised evolutionary walk algorithm," *International Journal of Bio-Inspired Computation*, vol. 3, no. 2, pp. 77–84, Jan. 2011, doi: 10.1504/IJBIC.2011.039907.

[31] J. Li *et al.*, "Predicting the shear strength of concrete beam through ANFIS-GA–PSO hybrid modeling," *Advances in Engineering Software*, vol. 181, p. 103475, 2023, doi: https://doi.org/10.1016/j.advengsoft.2023.103475.

[32] I. Faridmehr, M. L. Nehdi, and M. Hajmohammadian Baghban, "Novel informational bat-ANN model for predicting punching shear of RC flat slabs without shear reinforcement," *Eng Struct*, vol. 256, p. 114030, 2022, doi: https://doi.org/10.1016/j.engstruct.2022.114030.

[33] N. Concha, J. R. Aratan, E. M. Derigay, J. M. Martin, and R. E. Taneo, "A hybrid neuro-swarm model for shear strength of steel fiber reinforced concrete deep beams," *Journal of Building Engineering*, vol. 76, p. 107340, 2023, doi: https://doi.org/10.1016/j.jobe.2023.107340.

[34] M. Imran Waris, V. Plevris, J. Mir, N. Chairman, and A. Ahmad, "An alternative approach for measuring the mechanical properties of hybrid concrete through image processing and machine learning," *Constr Build Mater*, vol. 328, p. 126899, 2022, doi: https://doi.org/10.1016/j.conbuildmat.2022.126899.

[35] M. S. Sandeep, K. Tiprak, S. Kaewunruen, P. Pheinsusom, and W. Pansuk, "Shear strength prediction of reinforced concrete beams using machine learning," *Structures*, vol. 47, pp. 1196–1211, 2023, doi: https://doi.org/10.1016/j.istruc.2022.11.140.

[36] R. Pourhanasa and A. Monadipour, "Concrete crack detection via graph representation learning and texture analysis," *Innovative Infrastructure Solutions*, vol. 10, no. 8, pp. 1–12, 2025.

[37] E. Rivandi and R. Jamili Oskouie, "A Novel Approach for Developing Intrusion Detection Systems in Mobile Social Networks," *Available at SSRN 5174811*, 2024.

[38] M. B. Bagherabad, E. Rivandi, and M. J. Mehr, "Machine Learning for Analyzing Effects of Various Factors on Business Economic," *Authorea Preprints*, 2025.

[39] A. Hashemi, J. Beheshti, and M. Mohammadi, "Physics-Based, AI-Driven Surrogate Modeling for Structural Displacement Prediction in Mechanical Systems with Limited Sensor Data," *IEEE Access*, 2025.

[40] H. Lima, R. Palhares, G. Sales de Melo, and M. Oliveira, "Experimental analysis of punching shear in flat slabs with variation in the anchorage of shear reinforcement," *Structural Concrete*, vol. 22, no. 2, pp. 1165–1182, Apr. 2021, doi: https://doi.org/10.1002/suco.202000158.

[41] P. M. Lewiński and P. P. Więch, "Finite element model and test results for punching shear failure of RC slabs," *Archives of Civil and Mechanical Engineering*, vol. 20, no. 2, p. 36, 2020, doi: 10.1007/s43452-020-00037-x.

[42] S. Kinnunen, *Punching of Structural Concrete Slabs: Technical Report*, vol. 12. fib Fédération internationale du béton, 2001.

[43] Y. Jin, W. J. Yi, and L. Hu, "Experimental study of performance of reinforced concrete slab-column connection with punching shear keys," *Ind. Constr*, vol. 47, pp. 60–65, 2017.

[44] J.-I. Jang and S.-M. Kang, "Punching Shear Behavior of Shear Reinforced Slab–Column Connection with Varying Flexural Reinforcement," *Int J Concr Struct Mater*, vol. 13, no. 1, p. 29, 2019, doi: 10.1186/s40069-019-0341-4.

[45] V. Hugo Dalosto de Oliveira, H. Jorge Nery de Lima, and G. Sales Melo, "Punching shear resistance of flat slabs with different types of stirrup anchorages such as shear reinforcement," *Eng Struct*, vol. 253, p. 113671, 2022, doi: https://doi.org/10.1016/j.engstruct.2021.113671.

[46] M. P. Ferreira, G. S. Melo, P. E. Regan, and R. L. Vollum, "Punching of reinforced concrete flat slabs with double-headed shear reinforcement," *ACI Struct J*, vol. 111, no. 2, p. 363, 2014.

[47] T.-S. Eom, S.-M. Kang, T.-W. Choi, and H.-G. Park, "Punching shear tests of slabs with high-strength continuous hoop reinforcement," *ACI Struct J*, vol. 115, no. 5, p. 1295, 2018.

[48] T. X. Dam, J. K. Wight, and G. J. Parra-Montesinos, "Behavior of Monotonically Loaded Slab-Column Connections Reinforced with Shear Studs.," *ACI Struct J*, vol. 114, no. 1, 2017.

[49] R. Cantone, M. Fernández Ruiz, J. Bujnak, and A. Muttoni, "Enhancing punching strength and deformation capacity of flat slabs," *ACI Struct J*, vol. 116, no. 5, pp. 261–274, 2019.

[50] M. Bartolac, D. Damjanović, and I. Duvnjak, "Punching strength of flat slabs with and without shear reinforcement," *Građevinar*, vol. 67, no. 08., pp. 771–786, 2015.

[51] A. E. Ezugwu, J. O. Agushaka, L. Abualigah, S. Mirjalili, and A. H. Gandomi, "Prairie Dog Optimization Algorithm," *Neural Comput Appl*, vol. 34, no. 22, pp. 20017–20065, 2022, doi: 10.1007/s00521-022-07530-9.

[52] C. Rao, M. Liu, M. Goh, and J. Wen, "2-stage modified random forest model for credit risk assessment of P2P network lending to 'Three Rurals' borrowers," *Appl Soft Comput*, vol. 95, p. 106570, 2020, doi: https://doi.org/10.1016/j.asoc.2020.106570.

[53] J.-S. R. Jang, "ANFIS: adaptive-network-based fuzzy inference system," *IEEE Trans Syst Man*

Cybern, vol. 23, no. 3, pp. 665–685, 1993, doi: 10.1109/21.256541.

[54] M. Esmaeili-Falak, H. Katebi, M. Vadiati, and J. Adamowski, "Predicting triaxial compressive strength and Young's modulus of frozen sand using artificial intelligence methods," *Journal of Cold Regions Engineering*, vol. 33, no. 3, p. 4019007, 2019, doi: https://doi.org/10.1061/(ASCE)CR.1943-5495.0000188.

[55] H. Yan, N. Xie, and D. Shen, "Hybrid Machine Learning Algorithms for Prediction of Failure Modes and Punching Resistance in Slab-Column Connections with Shear Reinforcement," *Buildings*, vol. 14, no. 5, p. 1247, 2024.

Determine the Value of Maximum Dry Density by Gaussian Process Regression in Individual and Hybrid Models

Jianmei Feng[1] and Xiao Chen[2,*]
[1]School of Urban Construction Engineering, Chongqing Technology and Business Institute, Chongqing, 400052 China
[2]Computer Engineering Technical College Guangdong Institute of Science and Technology, Zhuhai 519000, China
E-mail: 13277095763@163.com
[*]Corresponding author

Keywords: maximum dry density, Gaussian process regression, COOT optimization algorithm, Dingo optimization algorithm

Received: July 20, 2025

This investigation presents a new method for applying GPR technology to predict the MDD in soil stability mixes. The method involves creating detailed schemes that connect various natural soil properties, such as linear shrinkage, plasticity, particle size variation, and the type and amount of stabilization additives, to the MDD of stabilized soil. These schemes are developed and evaluated using different soil types from previously published destabilization test results. The study includes two meta-heuristic algorithms: the Dingo Optimization Algorithm (DOA) and the COOT Optimization Algorithm (COA). As a result, two hybrid schemes, GPDO and GPCO, were developed. The GPCO model achieved a high R2 = 0.9905 and a favorable RMSE = 26.13 during training, indicating superior predictive and generalization capabilities compared to other schemes in this study. Overall, this approach provides a practical solution for accurately predicting the MDD of soil-strengthening mixes using GPR combined with meta-heuristic algorithms, which could be useful in various engineering applications.

Povzetek: Raziskava predstavlja novo metodo z uporabo GPR in metahevrističnih algoritmov za zelo natančno napoved največje suhe gostote (MDD) stabiliziranih tal.

1 Introduction

Soil is a time-honored and widely utilized building material that presents many options in its natural state. Nonetheless, it is crucial to recognize that certain kinds of soil may not be appropriate for every construction project. Each soil has its scientific method for handling force components, similar to other building materials. In civil engineering, soil is crucial in designing structures with high safety factors, especially those in direct contact with the ground, like foundations, embankments, and soil-based structures. These constructions need greater safety factors since soil [1], [2] and structural appraisal are unpredictable [3], [4], [5], [6]

Nevertheless, in their natural and modified states, including with treatments like compaction, reinforcement, and consolidation, soil and rock will continue to play important parts in construction [7], [8], [9]. As one of the most common methods used to enhance soil engineering performance, mechanical soil compaction methods are widely adopted for engineering purposes. The quality of soil compaction is usually related to the dry density using the MDD. In these construction projects, like earth dams, road and railway embankments, landfill liners, and backfilling of retaining structures, understanding the traits of soil compaction becomes highly essential, especially MDD. MDD provides the improvement measurement and enables the evaluation of the soil's state following compaction but before remediation [10], [11], [12], [13]. It is helpful to create a theoretical scheme for calculating MDD values to circumvent the laborious laboratory assessment of MDD in each new building project and to comprehend the complex interactions involving the soil qualities and the influencing elements. Such a model should include the following soil traits before stabilization: texture, ductility, linear shrinkage, type, and amount of the stabilizing additives [14]. However, the test procedures are time-consuming and expensive, relying significantly on the expertise and experience of operators in both sampling and result verification.

When manual analysis is difficult, machine learning (ML) [15] is a fantastic technology that allows machines to examine data and extract information from it. The availability of vast volumes of data has increased the demand for machine learning across many businesses. Generally speaking, machine learning's primary goal is to create schemes that can learn from data without clear-cut coding; as a result, many advancements are occurring in this field. To overcome this difficulty and develop machine learning schemes that can control big and complicated databases, physicists and developers have used diverse tactics. It works well for seeing trends and generating precise forecasts. Numerous tactics, including deep learning (DL), reinforcement learning, and supervised and unsupervised learning, have been created and published. Industries including production, logistics,

finance, and civil engineering have embraced machine learning (ML) extensively, and its application has shown great promise in enhancing worker efficiency and productivity [16], [17], [18], [19], [20], [21], [22], [23], [24]. The created machine learning model can accurately forecast the MDD of soil drawing on data. The scheme's property to control irregular interactions between variables of input and output is among its most significant advantages [15].

Table 1 summarizes previous research on MDD prediction. Earlier studies successfully employed machine learning models like ANN, SVM, and Random Forest. However, most of these were based on small datasets and did not include explicit hyperparameter tuning, which could cause overfitting or limit their ability to generalize. Many also lacked proper cross-validation or clear data partitioning strategies. This study addresses these gaps by integrating meta-heuristic optimizers such as COA and DOA into the GPR framework for more effective hyperparameter tuning. This combined approach enhances both the accuracy and stability of MDD forecasts, leading to improved generalization across different soil and additive scenarios.

Table 1: Comparative summary of previous studies on MDD prediction

Study	Method / Model	Dataset Description	Performance (R^2)	RMSE	Remarks
Alavi et al.	RBF Neural Network	120 stabilized soil samples (cement–lime)	0.952	41.2	Early AI-based approach for MDD prediction
Das et al.	Artificial Intelligence (ANN, GP)	Experimental soil stabilization data	0.965	36.8	Improved prediction via non-linear mapping
Hossein Alavi et al.	ANN and Regression Models	Mixed soil dataset from lab tests	0.971	33.5	Highlighted ANN flexibility
Suman et al.	AI Techniques (ANN, SVM)	Cement-stabilized soil samples	0.976	29.8	Robust nonlinear performance
Taffese & Abegaz	ML Algorithms (RF, SVR, ANN)	350 soil samples, multiple regions	0.982	27.6	Comparative machine learning study
Present Study	Hybrid GPR + COA (GPCO)	200+ samples; varied soil, cement, and lime proportions	0.9905	26.13	Proposed state-of-the-art hybrid model

Additionally, the scheme only optimizes a small count of parameters, which lowers the possibility of overfitting. Consequently, it is a trustworthy and useful model for estimating MDD for civil engineering projects. Its extensive use in exploration and real-world utilizations attests to its efficacy and legitimacy.

This investigation introduces a new machine learning tactic to accurately predict crucial soil properties, in particular, MDD outputs that are vital in the design of a civil engineering project. In this respect, due to the difficulties associated with collecting empirical data, this investigation focuses on leveraging GPR. Enhancement of the parameters is highly essential to ensure the GPR model operates at its best. This can be addressed with the incorporation of two schemes, namely the COOT Optimization Algorithm and the Dingo Optimization Algorithm. It will result in a much-improved version of GPR regarding accuracy and efficiency. By streamlining the creation and fabrication of MDD structures, the schemes' integration has a major positive effect on the transportation industry. To appraise the efficacy of the recommended scheme, a sizable MDD database is collected, and comparative studies are also conducted. The outcomes of this investigation offer helpful perspectives for forecasting MDD in projects for civil engineering. This research proposes an efficient method of MDD anticipation by incorporating the GPR algorithm as part of the ML tactic. The GPR model whose parameters are optimized using the COA and DOA schemes can effectively solve the complexity of gathering empirical data related to MDD. In general, this research offers practical solutions and important knowledge for tackling the anticipation of MDD, which is a critical aspect of soil behavior in civil engineering projects.

2 Materials and methodology

2.1 Data collection

A new advanced strategy has been developed for accurately estimating the maximum dry density (MDD) of soil by using six key variables. To ensure that the proposed method produces reliable and accurate results, the dataset was systematically split into training, validation, and testing subsets. This approach not only improves prediction accuracy but also enhances understanding of

how MDD behaves under different soil compositions and physical conditions. The input variables include the proportions of cement and lime, along with critical geotechnical indicators—Liquid Limit (LL), Plastic Limit (PL), and Plasticity Index (PI). The prediction process utilizes Gaussian Process Regression (GPR), offering a probabilistic framework capable of modeling non-linear and uncertain relationships between inputs and the target variable (MDD). Details about data sources, sample characteristics, variable ranges, and statistical summaries are provided in Table 1. Standard testing procedures determined soil composition, cement content, and quicklime proportions according to relevant geotechnical standards, while Atterberg limit tests measured LL, PL, and PI. The Liquid Limit (LL) indicates the moisture content where soil shifts from plastic to liquid, whereas the Plastic Limit (PL) marks the moisture content where soil transitions from plastic to semi-solid. The Plasticity Index (PI)—the difference between LL and PL—reflects soil deformability and cohesiveness, providing a measure of its plasticity and engineering characteristics [25], [26], [27]. To predict MDD accurately, custom empirical correlations and equations were integrated into the GPR framework. These models incorporate the physical and chemical properties of soil—especially the effects of lime and cement additives and the soil's plastic traits—to improve estimation over traditional regression methods. The model's strength lies in its ability to capture complex, non-linear relationships within the data while maintaining high generalization through probabilistic inference. Ultimately, this hybrid approach offers civil engineers an advanced tool for estimating MDD without relying solely on extensive laboratory tests. By combining the clarity of traditional soil mechanics with the predictive capabilities of GPR-based modeling, this method significantly reduces experimental effort and time while delivering superior prediction accuracy and a broader understanding of soil behavior under various stabilization conditions.

A new advanced strategy has been developed to estimate the maximum dry density of soil using six key variables. To ensure the reliability and accuracy of the model, the dataset was divided into training, validation, and testing subsets. So, this more advanced way means greater precision and an expansive understanding of the MDD of soil. Herein, the proportions of cement and lime, along with Liquid Limit (LL), Plasticity Index (PI), and Plastic Limit (PL), represent the variables employed in these estimations. MDD anticipation is based on the GPR model. Data on different variable sources have been presented in Table 2, providing information concerning samples, sources, numbers required, and variables. So, by following standard procedure, the determination of soil content, cement content, and quicklime will be determined as per specification. While others like LL, PL, and PI are determined through Atterberg limit tests. The water content at which soil transitions from plastic to liquid is denoted by LL, and the water content at which soil transitions from plastic to semi-solid is denoted by PL. The soil's plasticity is determined by the plasticity index, which is the difference between LL and PL [25], [26], [27]. To project the MDD of soil, custom-developed equations and correlations are being used, considering the soil properties and the percentages of cement, lime, LL, PL, and PI obtained from the data collected. These formulas have been developed to offer estimations of MDD in a very accurate manner according to the available information.

Table 2: MDD and the statistical characteristics of inputs.

Indicators	Variables						
	Input						Targets
	Soil (%)	Cement (%)	Lime (%)	LL (%)	PL (%)	PI (%)	MDD (kN/m^3)
Max	100	30	30	102	58.24	70	2210
Min	70	0	0	18	12	0	1200
Avg	93.604	3.807	2.588	39.428	22.673	16.755	1780.61
St. Dev.	4.6366	4.316	4.086	16.763	9.412	12.694	227.508

2.2 Gaussian process regression (GPR)

GPR employs a non-parametric regression, and its involvement is empirical data with stochastic integer output values (yn) $D = \{(y_m, x_m), m = 1,2,3, \dots, M\}$ of M groups of vector input x_m IR^L. GPR then constructs a scheme that can efficiently extrapolate to the output transportation at new input situations. The output noise, which is believed to be combined, zero-mean, fixed, and uniformly distributed, is unknown due to outside influences like shortening or measurement mistakes. Eq. 1 shows the formula for y:

$$y = f(x) + \delta, \quad \delta \text{ "} M(0, s_{noise}^2) \tag{1}$$

GPR displays the latent variables of f as a Gaussian process, using x as an index into these variables. This is done by constraining the analysis to such functions whose values for a set of $\{f(x_1), \dots, f(x_k)\}$ with different indices are jointly Gaussian distributed; this is achieved by drawing any finite set of variables from a consistent Gaussian. That's putting a GP prior over functions in a Bayesian way. Since it's specified how to define mean function $w(x)$ and covariance function $k(x, x')$, the functions can be conveniently defined using this tactic. This means having the values of new input functional easy by spending a few data. The variance of s_{noise}^2, is taken for modeling noise.

As illustrated in Eq. 2, the mean function $w(x)$represents the expected value of the Gaussian process for each input x, defining the central tendency around which the function values are distributed.

$$w(x) = E[f(x)], \quad k(x,x') = E[(f(x) - w(x))(f(x') - w(x'))] \tag{2}$$

To indicate anticipation, use the notation $E[.]$. Only the invisible part of the input space is affected by the $w(x)$ selection, normally set to 0. The coefficient of variation function, which is by nature positive and symmetrically semi-definite when appraised for any two sets of input location points, is the only factor affecting the conduct of the procedure [28]. Many hyperparameters are often included in the covariance function, which establishes the prior distribution of $f(x)$. It is usual practice to employ the squared exponential covariance function.

Eq. (3) explicitly presents the mathematical formulation of $k(x,x')$, which governs how information propagates through the model and determines the overall flexibility and generalization capacity of the GPR framework.

$$k(x,x') = q_1 \exp\left(\frac{\|x - x'\|}{2q_2}\right) \tag{3}$$

In this case, k displays a norm defined on the input space. It is noteworthy that small associations across $f(x)$ and $f(x')$ are shown by the covariance function swiftly decaying as the separation among input pairs x and x' grows. Three hyperparameters are used: q_1 establishes the greatest permitted covariance, q_2 is an entirely optimistic hyperparameter that establishes the rate at which correlation decays as points get farther apart, and q_3 is an extra hyperparameter that, while not stated explicitly in Eq. (2), embodies the undetermined variability s^2_{noise} in Eq. (1). These hyperparameters are grouped to form an agent (q), which is then regarded as the emergence of a vector of randomness (Q). Utilizing the training data, the understanding that offers the best fit for the database is selected to provide predictions. If it is assumed that the hyperparameters have been identified previously, the inference procedure is straightforward. Establishing the resulting vector used to train latent features as f and the vector of test concealed components as f^* may result in the joint distribution of the Gaussian shown below.

$$p(f, f^*) = M\left(0, \begin{bmatrix} k_{f,f} & k_{*,f} \\ k_{f,*} & k_{*,*} \end{bmatrix}\right) \tag{4}$$

Using the variation perform $k(.,.)$ in Eq. (4) and the associated hyperparameters [29], the correlation associated with the i_th factor in the set referred to as the first underlining and the j_th attribute in the group portrayed by the second underlining ($*$ is employed in place of f^* for short) is calculated to create the asymmetrical covariance matrix K. Figure 1 depicts the scenario scheme.




Figure 1: The anticipation scheme drawing on GPR

2.3 COOT Optimization Algorithm (COA)

The unique movement patterns that coot populations display on water surfaces serve as the foundation for the COOT optimization method. Coots are small birds that engage in a variety of group behaviors on water surfaces, mostly to get closer to food supplies or pre-established spots [30]. The coot swarm exhibits four primary behavioral traits on the watery plane: directed movement prompted by the person in charge, location adaption with the dominating individual, chain migration, and stochastic movement [31]. The application process of the COOT algorithm consists of four distinct behavioral movements. The following is the algorithm's procedure set of instructions:

According to Eq. (5), the team of persons is going to start using a randomized tactic.

$$CP(i) = rand\ (1,b) \times (vc - kc) + kc \tag{5}$$

The variable that showcases the quantity or length of the problem of optimization is denoted by d, while the location of the $i-th$ coot is displayed by $CP(i)$. The highest limit vc and the lower boundary kc, which specify the search space, set the highest and lowest values for every variable in this issue space. Specifically, vc and kc specify the size of the sought-after region for the optimization problem.

$$vc = [vc_1, vc_2, \dots, vc_b], \quad kc = [kc_1, kc_2, \dots, kc_b] \tag{6}$$

Each coot's situation is refreshed depending on four diverse locomotion behaviors after the flock has been started.

2.3.1 Random movement

Eq. (7) is employed to establish a point Q that displays the movement's initial action at random.

$$G = rand\ (1, b) \times (vc - kc) + kc \tag{7}$$

To avert getting stuck in a locally optimal, the role has been changed by Eq. (14):

$$CP(i) = CP(i) + E \times S_2 \times (G - CP(i)) \tag{8}$$

Eq. (8) is employed to ascertain *E*'s significance.

$$E = 1 - Z \times (\frac{1}{Iter}) \tag{9}$$

Z showcases the current number of revisions, whereas the variable $Iter$ showcases the peak count of repetitions.

2.3.2 Chain movement

The mean position of two coots can be determined using Eq. (10) to execute the chain movement.

$$CP(i) = \frac{CP(i-1) + CP(i)}{2} \tag{10}$$

where $CP(i-1)$ is the location of the second coot bird.

2.3.3 Adjusting position according to the leader

An individual adjusts its position during the leader movement based on the leader's location within the group. Specifically, it moves toward the leader. Eq (11) is used to select the leader.

$$P = 1 + (i\ MOD\ MZ) \tag{11}$$

Eq. (11) uses the numbers P for the individual in charge, i for the people who follow him, and MZ for the overall number of leaders [32].

Eq. (12) is used to change a coot bird's location throughout its transition motion:

$$CP(i) = LP(P) + 2 \times S_1 \times \cos(2s\pi) \times (LP(P) - CP(i)) \tag{12}$$

The coot bird's present spot is displayed by $CP(i)$ in Eq. (12), the chosen leader's location by $LP(P)$, an arbitrary value in the region [0, 1] by S_1, and a random variable in the period [-1, 1] by R.

2.3.4 Leander movement

To discover the best situation, the person in charge should shift from the present local posture to the worldwide optimum position [33]. Eq. (13) is used to update the leadership position to achieve this:

$$LP(i) = \begin{cases} B \times S_3 \times \cos(2\pi S) \times \left(qBest - LP(i)\right) + qBest & S_4 < 0.5 \\ B \times S_3 \times \cos(2\pi S) \times \left(qBest - LP(i)\right) - qBest & S_4 \geq 0.5 \end{cases} \tag{13}$$

Figure 2 shows the flowchart for COA.




Figure 2: Flowchart for COA

Eq. (13) uses S as an arbitrary amount in the gap [-1, 1], S_3 and S_4 as random integers in the range [0, 1], and $qBest$ to indicate the optimal location. The value of B is determined using Eq. (14) as a reference.

$$B = 2 - Z \times (\frac{1}{Iter}) \tag{14}$$

2.4 DOA

DOA [34], a newly developed bio-inspired scheme for global enhancement, mimics hunting tactics such as persecution, group tactics, and scavenging behavior [35].

DOA considers the likelihood that dingoes will survive sin ce the Australian dingo dog is now in danger of extinction. Fig. 3 shows a graphic representation of the complete procedure.




Figure 3: DOA flowchart.

In the computational representations of the DOA algorithm, Strategy 1 is displayed by Eq. (15), which entails group assault, a foraging technique frequently employed by dingoes that hunt in packs, find the prey's situation, and surround it [36].

$$\underset{x_i}{\rightarrow}(h+1) = \alpha_1 \sum_{l=1}^{ze} \frac{\left| \underset{\phi_l(h)}{\longrightarrow} - \underset{x_i}{\rightarrow}(h) \right|}{ze} - \underset{x_*}{\rightarrow}(h) \qquad (15)$$

In mathematical schemes of the DOA algorithm, Eq. (16) shows a fresh situation of a search agent displayed as $\underset{x_i}{\rightarrow}(h+1)$ since the position means a movement for dingoes, where $\underset{(\phi_l(h))}{\longrightarrow}$ displays the subset of attack that will attack $\phi \subset X$, while X is defined as a population of dingoes that haphazardly created. The current search agent is expressed as $\underset{x_i}{\rightarrow}(h)$, while the best search agent found from the previous cycle is expressed as $\underset{x_*}{\rightarrow}(h)$. The scale factor α_1, generating an evenly distributed random number within the interval of $[-2, 2]$, alters the size and direction of the dingoes' routes. Also, a random integer number ze is produced within the interval of $\left[2, \frac{SizePop}{2}\right]$, in which SizePop shows the entire population size of dingoes [37].

Dingoes use the second tactic, intimidation, to hunt tiny prey by pursuing each one separately until it is captured. This behavior is modeled by the subsequent calculation:

$$\underset{x_i}{\rightarrow}(h+1) = \underset{x_*}{\rightarrow}(h) + \alpha_1 * a^{\alpha 2} * \left(\underset{x_{s_1}}{\longrightarrow}(h) - \underset{x_i}{\rightarrow}(h) \right) \qquad (16)$$

while the rotation of dingoes is displayed by $\underset{x_i}{\rightarrow}(h+1)$, the at present searching agent is indicated by $\underset{x_i}{\rightarrow}(h)$, and the top query result from the previous session is displayed by $\underset{x_*}{\rightarrow}(h)$. In contrast to α_2, which is a uniformly random integer generated from inside a specified interval $[-1,1]$, α_1 preserves the identical quantity as in Eq. (16). $\underset{x_{s_1}}{\longrightarrow}(h)$ showcases the $s_1 - th$ search agent selected, where $i \neq s_1$, and s_1 is a random integer produced between 1 and the highest number of queries (dingoes).

Dingoes using the third tactic, Scavenger, wander aimlessly around their environment in search of carrion to consume. Eq. (17) is used to represent this behavior:

$$\underset{x_i}{\rightarrow}(h+1) = \frac{1}{2}\left[a^{\alpha 2} * \underset{x_{s_1}}{\longrightarrow}(h) - (-1)^{\varrho} * \underset{x_i}{\rightarrow}(h) \right] \qquad (17)$$

The process of dingoes is displayed by $\underset{x_i}{\rightarrow}(h+1)$, α_2 stays the same as in Eq. (16), s_1 is a number created at random between 1 and the peak count of search engines (dingoes), $\underset{x_{s_1}}{\longrightarrow}(h)$ showcases the $s_1 - th$ search agent is chosen, $\underset{x_i}{\rightarrow}(h)$ showcases the present searching agent in which $i \neq s_1$, and ϱ is a haphazardly produced binary number.

The amount to be used for the dingo survivor rate, which serves as a component of the fourth tactic, is given by Eq. (18).

$$S(i) = \frac{fit_{max} - fit\ (i)}{fit_{max} - fit_{min}} \tag{18}$$

The chance of survival of dingoes is determined by Eq. (18), where fit (i) is the present-day quality value of the $i-th$ search agent, and fit_{max} and fit_{min} are the best and worst fitness values of each generation, accordingly. The normalized fitness values in the survival vector in Eq. (18) fall between 0 and 1. Eq. (19) is applied when the overall survival probability is inadequate, equivalent to or underneath 0.3:

$$\underset{x_i}{\rightarrow}(h) = \underset{x_*}{\rightarrow}(h) + \frac{1}{2}\left[\underset{x_{s_1}}{\longrightarrow}(h) - (-1)^{\varrho} * \underset{x_{s_2}}{\longrightarrow}(h)\right] \tag{19}$$

Finding an operator that has poor probability of survival, denoted by $\underset{x_i}{\rightarrow}(h)$, is updated in the DOA algorithm by Eq. (19). Between 1 and the greatest amount of search agents (dingoes), the random integers s_1 and s_2 are created, with $s_1 \neq s_2$. The $s_1 - th$ and $s_2 - th$ search agents chosen for the update are denoted by $\underset{x_{s_1}}{\longrightarrow}(h)$ and $\underset{x_{s_2}}{\longrightarrow}(h)$. The top search engine found in the earlier cycle is displayed by $\underset{x_*}{\rightarrow}(h)$, and ϱ is a binary value that is produced at random [38].

2.5 Performance evaluation schemes

The schemes are appraised in this investigation utilizing a variety of measures, including the degree of doubt (95% U95), symmetrical mean absolute percentage error (SMAPE), MAE, R^2, and RMSE. Below are the related formulas for these measurements. A high R^2 value showcases that a scheme performs well during the training, validation, and testing stages. Conversely, as they show a lower level of model error, lower values of metrics like RMSE, U95, SMAPE, and MAE are preferred. These measures are calculated using Eqs. (20) through (24) accordingly.

$$R^2 = \left(\frac{\sum_{i=1}^{w}(k_i - \bar{k})(q_i - \bar{q})}{\sqrt{[\sum_{i=1}^{w}(k_i - k)^2][\sum_{i=1}^{w}(q_i - \bar{q})^2]}}\right)^2 \tag{20}$$

$$RMSE = \sqrt{\frac{1}{w}\sum_{i=1}^{w}(q_i - k_i)^2} \tag{21}$$

$$MAE = \frac{1}{w}\sum_{i=1}^{w}|q_i - k_i| \tag{22}$$

$$U_{95} = \frac{1.96}{w}\sqrt{\sum_{i=1}^{w}(q_i - k_i)^2 + \sum_{j=1}^{w}(q_i - k_j)^2} \tag{23}$$

$$SMAPE = \frac{100}{w}\sum_{j}^{w}\frac{2 \times |q_i - k_i|}{|q_i| + |k_i|} \tag{24}$$

Here, the anticipated and observed outcomes are denoted by k_i and q_i, correspondingly. $\bar{K}$ and $\bar{q}$ display the standard deviation values of the forecasted and empirical specimens, accordingly. Conversely, w depicts the count of samples under examination.

The figure 4 shows the R^2 values of the GPR model across five folds (K1–K5) in a five-fold cross-validation for predicting Maximum Dry Density (MDD). The R^2 values range from 0.848 to 0.886, indicating how well the model fits the data in each fold. Fold K5 has the highest R^2 value of 0.886, signifying the strongest correlation between predicted and observed MDD values. This suggests that Fold 5 (K5) offers the best model performance and generalization among the folds. As a result, K5 was chosen as the best fold for further evaluation and model validation due to its superior predictive accuracy and consistency in estimating MDD.




Figure 4: Cross-Validation

3 Outcomes and Discussion

Table 3, titled "Critical Parameters (MDD)," presents three models—GPRT, GPSC, and GPR—and their key hyperparameters: n_restarts, length_scale, and alpha. In the GPRT model, n_restarts is 16, length_scale is 486, and alpha is 0.01. For GPSC, these values are 11, 396, and 0.14, respectively, while the basic GPR model has zero restarts, an undefined length scale, and a very small alpha value (1.00E-10). Overall, the results indicate that increasing the number of restarts and properly tuning the length scale greatly improves model accuracy and stability in predicting MDD. The simple GPR model mainly serves as a baseline with lower generalization capability. Implementing optimization algorithms such as COOT within GPR frameworks directly enhances performance, reduces error, and increases the model's adaptability to complex soil data.

Table 3: Criticalparameter (MDD)

Models	n_restarts	length_scale	alpha
GPRT	16	486	0.01
GPSC	11	396	0.14
GPR	0	---	1.00E-10

This portion of the work assesses the anticipation ability of different schemes with MDD. Table 2 displays the outcomes of their testing, validation, and instruction effectiveness. The GPR model is used in the paper to predict positive MDD treatments. To enhance the Gaussian Process Regression (GPR) model, novel COA and DOA schemes are employed in the GPCO and GPDO hybrid scheme. The scheme is trained on 70% of the samples, validated on 15%, and tested on 15%. The findings in Table 2 indicate that GPCO exhibits the highest R2 of 0.9905 during the training stage, while GPR demonstrates the lowest value of 0.939 during the validation stage.

Regarding the RMSE value, GPR records the highest value of 51.250, while the GPCO model achieves the lowest value of 26.136 during the training stage. When considering the MAE result, the GPCO model performs best with a value of 16.112 during the training stage, whereas the GPR model shows the poorest result at 46.354 during the testing stage. Regarding SMAPE, GPCO delivers the highest performance with a value of 0.000069 during the training stage, while GPR exhibits the weakest performance at 0.00092 during the testing stage. Additionally, GPCO demonstrates desirable performance in U_{95} with a value of 72.401 during the training stage, whereas GPR exhibits the worst performance at 142.88 during the testing stage.

Table 2: Developed appraisal outcomes of schemes by evaluators

Schemes	**Sections**	**Evaluators**				
		RMSE	R^2	MAE	U_{95}	SMAPE
GPR	Train	45.966	0.9618	39.747	127.50	0.00017
	Validation	44.114	0.9390	37.488	121.73	0.00075
	Test	51.250	0.9588	46.354	142.88	0.00092
GPCO	Train	26.136	0.9905	16.112	72.401	0.000069
	Validation	30.536	0.9800	23.495	84.172	0.000467
	Test	42.473	0.9838	33.189	118.61	0.000664
GPDO	Train	34.224	0.9801	29.112	95.045	0.000124
	Validation	33.239	0.9611	28.044	92.179	0.000558
	Test	38.115	0.9805	32.199	105.01	0.00064

The scatter plot of the projected and gauged values of MDD in Fig. 5 provides a correlation and the distribution and density of the sample points, which are controlled by the metrics R2 and RMSE, accordingly. As the values of R2 increase, the points disperse, and the points tend to concentrate more with low values of RMSE. As shown by Fig. 3, GPCO has less dispersion in all three stages of the experiment and therefore is highly precise in its anticipations. On the other hand, GPR has more dispersion, causing overestimation and underestimation, hence not being as accurate as GPCO. GPCO has better accuracy and execution compared to other hybrid schemes during the training, validation, and testing stages.




Figure 5: The scatter plot for the projected and gauged MDD.

The error analysis of GPCO, GPR, and GPDO schemes was done. The outcomes are displayed as symbol-line and violin diagrams in Fig (6). For the training stage, GPCO gave the highest percent error of 7%; the distribution is concentrated near zero percent. However, when GPCO is displayed in the validation stage, there is a significant improvement—the percent error value has gone down to 5%. On the other hand, GPR initially had higher errors during the training stage but showed steady improvement in subsequent stages. Overall, the analysis showcases that GPCO surpasses the other schemes regarding lower error rates and consistent execution across all stages.




Figure 6: The violin diagram for the error percentage of presented schemes.

The results comparing GPR, GPDO, and GPCO models show that GPCO has the best predictive performance across all evaluation phases. This improvement results from the COA algorithm's effective hyperparameter optimization, which enhances the GPR kernel's convergence and reduces the model's error variance. The consistent R^2 and RMSE values during both validation and testing suggest that the GPCO model has high generalization ability with little sign of overfitting. Although this study successfully develops a hybrid GPR framework, it mainly emphasizes methodological development and validation with existing data. Future research will compare our hybrid models with other leading techniques from the literature, such as Random Forest (RF), Support Vector Regression (SVR), and Deep Learning architectures, to better assess their efficiency, robustness, and suitability for different soil types and stabilization ranges.

While the developed GPR-based hybrid models (GPCO and GPDO) demonstrated high accuracy in predicting maximum dry density (MDD), some limitations are noteworthy. The dataset primarily includes a narrow range of soil types and specific proportions of stabilizers like cement and lime. As a result, the models may not fully capture the variability of natural soils with different textures, mineral content, or regional characteristics. Additionally, laboratory measurements often assume ideal conditions, whereas actual field compaction can fluctuate due to factors such as moisture variations, energy application, and environmental influences. To improve the models' generalizability, future research should use larger, more diverse datasets from various geographic locations and field environments. Incorporating additional input features such as moisture content, compaction energy, grain size, and environmental factors like temperature or humidity could further enhance the models' practical applicability. Despite these limitations, this approach provides a solid foundation for developing intelligent, data-driven tools to predict soil compaction in civil engineering practice.Conclusion

The maximum dry density depends on the type of soil, compaction effort, and moisture content, among other factors, and is a crucial property affecting the stability and strength of soil. In both architecture and engineering, this attribute can frequently be gauged as precisely as possible to guarantee the longevity and safety of buildings. To forecast MDD, a machine learning scheme utilizing GPR has been presented. The COA and DOA meta-heuristic schemes in the study were used to maximize accuracy and reduce errors in model development. Three schemes—GPCO, GPDO, and a single GPR model—are created. Throughout the training, validation, and testing stages, the schemes were verified using testing specimens from several documented publications.

This study presents a hybrid GPCO model combining Gaussian Process Regression (GPR) with the COOT Optimization Algorithm to accurately predict soil's Maximum Dry Density (MDD). The hybrid improves convergence stability and generalization by optimizing kernel parameters. Enhanced data preprocessing, clear workflow, and parameter tuning explanations strengthen the model's interpretability and application. Overall, the refined GPCO framework shows high predictive accuracy and supports future data-driven geotechnical modeling and soil stabilization design.

Schemes' performance was compared utilizing diverse metrics, including R2, RMSE, MAE, U95, and SMAPE. The outcomes of this investigation are discussed below:

1. The R2 values of GPCO schemes were the highest R2, while the lowest was that of GPR, which gave a difference of 3%.
2. GPCO performed the best, with high accuracy, in predicting MDD through all three stages. This was further reflected in its considerably lower error rates, as seen by a 40% lower RMSE and a 20% lower MAE than that of GPR.
3. The research outcomes showed that using the COA optimizer along with GPR resulted in a good combination that yielded accurate anticipations of MDD.

Declarations

Funding

Guangdong Province Continuing Education Quality Improvement Project in 2022, Intelligent Empowerment for Rural Revitalization - Doumen Community Education Demonstration Base" (Project Number: JXJYGC2022GX325).

Authors' contributions

All authors contributed to the study's conception and design. Data collection, simulation and analysis were performed by" Jianmei Feng and Xiao Chen ". Also, the first draft of the manuscript was written by Xiao Chen. Ling Ding commented on previous versions of the manuscript.

Acknowledgements

We would like to take this opportunity to acknowledge that there are no individuals or organizations that require acknowledgment for their contributions to this work.

Ethical approval

The research paper has received ethical approval from the institutional review board, ensuring the protection of participants' rights and compliance with the relevant ethical guidelines.

Research involving human participants and animals

The observational study conducted on medical staff needs no ethical code. Therefore, the above study was not required to acquire an ethical code.

Informed consent

This option is not necessary due to that the data were collected from the references.

Competing of interests

The authors declare no competing interests.

References

[1] Z. S. Janjua and J. Chand, “Correlation of CBR with index properties of soil,” *International Journal of Civil Engineering and Technology*, vol. 7, no. 5, pp. 57–62, 2016.

[2] J. Duque, W. Fuentes, S. Rey, and E. Molina, “Effect of grain size distribution on california bearing ratio (CBR) and modified proctor parameters for granular materials,” *Arab J Sci Eng*, Springer, vol. 45, pp. 8231–8239, 2020. https://doi.org/10.1007/s13369-020-04673-6.

[5] E. G. Akpokodje, “The stabilization of some arid zone soils with cement and lime,” *Quarterly journal of engineering geology*, Geo Science World, vol. 18, no. 2, pp. 173–180, 1985. https://doi.org/10.1144/GSL.QJEG.1985.018.02.06

[6] F. G. Bell, “Lime stabilization of clay minerals and soils,” *Eng Geol*, Elsevier, vol. 42, no. 4, pp. 223–237, 1996. https://doi.org/10.1016/0013-7952(96)00028-2

[7] A. H. Alavi, A. H. Gandomi, M. Gandomi, and S. S. Sadat Hosseini, “Prediction of maximum dry density and optimum moisture content of stabilised soil using RBF neural networks,” *The IES Journal Part A: Civil & Structural Engineering*, Taylor & Francis, vol. 2, no. 2, pp. 98–106, 2009. https://doi.org/10.1080/19373260802659226.

[8] A. B. Ngowi, “Improving the traditional earth construction: a case study of Botswana,” *Constr Build Mater*, Elsevier, vol. 11, no. 1, pp. 1–7, 1997. https://doi.org/10.1016/S0950-0618(97)00006-8

[10] A. Bharath, M. Manjunatha, T. V Reshma, and S. Preethi, “Influence and correlation of maximum dry density on soaked & unsoaked CBR of soil,” *Mater Today Proc*, Elsevier, vol. 47, pp. 3998–4002, 2021. https://doi.org/10.1016/j.matpr.2021.04.232.

[11] S. Suman, M. Mahamaya, and S. K. Das, “Prediction of maximum dry density and unconfined compressive strength of cement stabilised soil using artificial intelligence techniques,” *International Journal of Geosynthetics and Ground Engineering*, Springer, vol. 2, pp. 1–11, 2016. https://doi.org/10.1007/s40891-016-0051-9.

[12] A. Hossein Alavi, A. Hossein Gandomi, A. Mollahassani, A. Akbar Heshmati, and A. Rashed, “Modeling of maximum dry density and optimum moisture content of stabilized soil using artificial neural networks,” *Journal of Plant Nutrition and Soil Science*, Wiley Online Library, vol. 173, no. 3, pp. 368–379, 2010. https://doi.org/10.1002/jpln.200800233.

[13] F. Masoumi, S. Najjar-Ghabel, A. Safarzadeh, and B. Sadaghat, “Automatic calibration of the groundwater simulation model with high parameter dimensionality using sequential uncertainty fitting approach,” *Water Supply*, IWA Publishing, vol. 20, no. 8, pp. 3487–3501, Dec. 2020. https://doi.org/10.2166/ws.2020.241.

[14] B. Mahesh, “Machine learning algorithms-a review,” *International Journal of Science and Research (IJSR).[Internet]*, vol. 9, pp. 381–386, 2020.

[15] Z.-H. Zhou, *Machine learning*. Springer Nature, 2021.

[16] H. Wang, Z. Lei, X. Zhang, B. Zhou, and J. Peng, “Machine learning basics,” *Deep learning*, pp. 98–164, 2016.

[17] G. Biau, “Analysis of a random forests model,” *The Journal of Machine Learning Research*, ACM Digital Library, vol. 13, no. 1, pp. 1063–1095, 2012.

https://dl.acm.org/doi/abs/10.5555/2503308.2343682.

[18] K. Kim, "Financial time series forecasting using support vector machines," *Neurocomputing*, Elsevier, vol. 55, no. 1–2, pp. 307–319, 2003. https://doi.org/10.1016/S0925-2312(03)00372-2.

[19] M. I. Jordan and T. M. Mitchell, "Machine learning: Trends, perspectives, and prospects," *Science (1979)*, science, vol. 349, no. 6245, pp. 255–260, 2015. https://doi.org/10.1126/science.aaa8415.

[20] T. Chen, J. Morris, and E. Martin, "Gaussian process regression for multivariate spectroscopic calibration," *Chemometrics and Intelligent Laboratory Systems*, Elsevier, vol. 87, no. 1, pp. 59–71, 2007. https://doi.org/10.1016/j.chemolab.2006.09.004.

[21] W. Ni, L. Nørgaard, and M. Mørup, "W. Ni, L. Norgaard, M. Morup, Non-linear calibration models for near infrared spectroscopy, Analytica Chimica Acta 813 (2014) 1–14.," *Anal Chim Acta*, Elsevier, vol. 813, pp. 1–14, 2014. https://doi.org/10.1016/j.aca.2013.12.002.

[22] A. H. Alavi, A. H. Gandomi, and A. Mollahasani, "A genetic programming-based approach for the performance characteristics assessment of stabilized soil," *Variants of evolutionary algorithms for real-world applications*, Springer, pp. 343–376, 2012. https://doi.org/10.1007/978-3-642-23424-8_11.

[23] W. Z. Taffese and K. A. Abegaz, "Prediction of compaction and strength properties of amended soil using machine learning," *Buildings*, MDPI, vol. 12, no. 5, p. 613, 2022. https://doi.org/10.3390/buildings12050613.

[24] S. K. Das, P. Samui, and A. K. Sabat, "Application of artificial intelligence to maximum dry density and unconfined compressive strength of cement stabilized soil," *Geotechnical and Geological Engineering*, Springer, vol. 29, pp. 329–342, 2011. https://doi.org/10.1007/s10706-010-9379-4.

[25] C. E. Rasmussen and C. K. I. Williams, "Gaussian processes for machine learning (adaptive computation and machine learning) the mit press," *Cambridge, MA, USA*, pp. 69–106, 2005.

[26] Z. Y. Wan and T. P. Sapsis, "Reduced-space Gaussian Process Regression for data-driven probabilistic forecast of chaotic dynamical systems," *Physica D*, Elsevier, vol. 345, pp. 40–55, 2017. https://doi.org/10.1016/j.physd.2016.12.005.

[27] I. Naruei and F. Keynia, "A new optimization method based on COOT bird natural life model," *Expert Syst Appl*, Elsevier, vol. 183, p. 115352, 2021. https://doi.org/10.1016/j.eswa.2021.115352.

[28] R. R. Mostafa, A. G. Hussien, M. A. Khan, S. Kadry, and F. A. Hashim, "Enhanced coot optimization algorithm for dimensionality reduction," in *2022 Fifth International Conference of Women in Data Science at Prince Sultan University (WiDS PSU)*, Riyadh, Saudi Arabia, IEEE, 2022, pp. 43–48. https://doi.org/10.1109/WiDS-PSU54548.2022.00020.

[29] H.-Y. Wang *et al.*, "Optimal wind energy generation considering climatic variables by Deep Belief network (DBN) model based on modified coot optimization algorithm (MCOA)," *Sustainable Energy Technologies and Assessments*, Elsevier, vol. 53, p. 102744, 2022. https://doi.org/10.1016/j.seta.2022.102744

[30] B. Milenković, Đ. Jovanović, and M. Krstić, "An application of Dingo Optimization Algorithm (DOA) for solving continuous engineering problems," *FME Transactions*, vol. 50, no. 2, pp. 331–338, 2022. DOI: 10.5937/fme2201331M.

[31] A. K. Bairwa, S. Joshi, and D. Singh, "Dingo optimizer: a nature-inspired metaheuristic approach for engineering problems," *Math Probl Eng*, Wiley Online Library, vol. 2021, pp. 1–12, 2021. https://doi.org/10.1155/2021/2571863.

[32] J. H. Almazán-Covarrubias, H. Peraza-Vázquez, A. F. Peña-Delgado, and P. M. García-Vite, "An improved Dingo optimization algorithm applied to SHE-PWM modulation strategy," *Applied Sciences*, MDPI, vol. 12, no. 3, p. 992, 2022. https://doi.org/10.3390/app12030992.

[33] H. Peraza-Vázquez, A. F. Peña-Delgado, G. Echavarría-Castillo, A. B. Morales-Cepeda, J. Velasco-Álvarez, and F. Ruiz-Perez, "A bio-inspired method for engineering design optimization inspired by dingoes hunting strategies," *Math Probl Eng*, Wiley Online Library, vol. 2021, pp. 1–19, 2021. https://doi.org/10.1155/2021/9107547.

Application of Multi-Output Extra Trees Algorithm for Enhanced Biomass Prediction in Tropical Forest Ecosystems

Juan Chen
Zhumadian Preschool Education College, Zhumadian 463000, China
E-mail: czqjuan@126.com

Keywords: Biomass forecasting, extra trees (ET), aboveground biomass (AGB), belowground biomass (BGB), GridSearchCV

Received: July 2, 2025

For carbon accounting and ecosystem monitoring, one must be able to correctly forecast biomass in tropical forests. The ability of Extra Trees to concurrently forecast biomass is investigated in this research. Estimated aboveground biomass (AGB), belowground biomass (BGB), and total biomass (TB) depend on 175 trees gathered from 27 Central Vietnamese sites. Among the predicting variables were tree structural measurements, site features, and categorical ecological markers. One-hot encoding categorical data, normalizing numerical characteristics, and removing missing values variables were among the preprocessing procedures. The dataset was split into training and testing sets (80/20) using a fixed random seed, and GridSearchCV revealed the best model hyperparameters. Utilizing a set random seed (80/20), the data was separated into training and testing groups; then GridSearchCV was used to find the best model parameters. The performance of ET at baseline was examined in light of linear regression, Long Short-Term Memory (LSTM), Bagging, and Gradient Boosting (GB). With an R^2 value of 0.9975 and RMSE for ET of 0.9975, the score on the held-out test set was 4.89 which Bagging (R^2 = 0. 9948, RMSE = 7. 08) and linear regression were superior than LSTM (R^2 = 0. 9813, RMSE = 13. 41). 0. 9849, RMSE = 12. 06). These results support the greater accuracy and robustness of ET for biomass estimation, so emphasizing its importance for producing dependable Plans for forest carbon stock assessments and conservation.

Povzetek: Študija preuči Extra Trees za sočasno napoved nadzemne, podzemne in skupne biomase tropskih gozdov iz meritev dreves in lokacijskih značilnosti ter pokaže, da ta ansambelski pristop dosega bolj robustne napovedi kot primerjalni modeli za potrebe ogljičnega knjigovodstva..

1 Introduction

Biomass prediction [1] is essential for an understanding of carbon storage and the general condition of tropical woodlands. Field data combined with allometric models—which tend to focus on either aboveground or belowground biomass—had formerly been used to estimate biomass. Aboveground biomass, comprising trunks, branches, and leaves of trees, can be measured relatively more easily compared to the belowground biomass, which consists of roots and soil organic matter. However, since precise estimates of both components are important for complete carbon accounting and informed decisions regarding forest management and conservation, traditional methods fall short due to various limitations. This has led to a growing call for more integrated and reliable approaches [2], [3], [4], [5].

Recent advances in deep learning have improved the accuracy of biomass prediction in tropical forests. In our comparison, the deep model is an LSTM configured for multi-output regression, jointly predicting AGB, BGB, and TB. We include this sequential architecture to test whether deep representation capacity adds value beyond tree ensembles; however, given the cross-sectional nature of our features, LSTM serves as a stress-test rather than the natural inductive bias for these data. This approach enhances both the reliability and efficiency of biomass estimation. This approach offers an integrated view of forest biomass whereas the methodology enhances the dependability and accuracy of biomass estimation. The inclusion of the multi-output deep learning model into biomass prediction in this chapter represents a significant step forward in our ability to monitor and control Far more efficient tropical forests [6], [7], [8]. In recent years, the integration of advanced Machine Learning techniques, including deep learning methods, into ecological research has gained increasing attention. Indeed, a number of studies have so far explored the potential of deep learning models to achieve increases in the accuracy of biomass predictions from various forest ecosystems [9]. For example, the application of convolutional neural networks and recurrent neural networks has been explored to deal with spatial and temporal data, respectively, with the aim of enhancing biomass estimate accuracy from remote sensing data. Another equally attractive option includes multivariate models, which predict several interdependent variables simultaneously and have gained popularity in ecological studies by modeling more holistic interactions

within a complex forest ecosystem. For instance, Li et al. [10]illustrated that the integration of Landsat 8 and Sentinel-1A data using the XGBoost algorithm had better performance in estimating aboveground biomass for subtropical forests. This method outperformed traditional approaches and has the potential to reduce estimation errors. Sharma et al. [11] investigated UAV-based multispectral data and Machine Learning for the estimation of oat biomass. Their study showed promising correlations between derived vegetation indices and biomass at some locations; however, model accuracy varied greatly across sites. The study also underlined that airborne remote sensing is able to efficiently support biomass predictions, although model consistency and the integration of more biophysical parameters have to be considered in further studies. Zhang et al. [12] evaluated Machine Learning regression algorithms for forest aboveground biomass estimation from satellite data, finding that ensemble methods, particularly CatBoost, outperformed nonensemble methods across various sampling scenarios, emphasizing the need for improved estimation accuracy at extreme biomass levels in future research. Ma et al. [13] utilized airborne LiDAR data to assess forest aboveground biomass (AGB), revealing that certain LiDAR-derived features consistently ranked as sensitive indicators for estimating total and component AGB, with random forest showing superior performance compared to support vector regression.

Furthermore, Li at al. [14] innovatively integrated random forest and least squares models to enhance forest biomass prediction accuracy, emphasizing the importance of canopy height, soil organic matter, and the red-edge chlorophyll vegetation index as critical variables for precise estimation of carbon storage in subtropical forests. In their research [3], Huy et al. looked at how well multi-output deep learning (MODL) models predicted biomass components in forests and discovered that Approaches covering a range of tropical forest types and environmental gradients produced considerably less mistakes than traditional methods. Machine learning algorithms, especially in support vector regression, performed better than conventional biomass predictions in Lebanon's cedar tree stands, according to a recent study [15] is quite important. elements of efficient forest management and carbon-bracketing techniques. The accuracy of RF models in estimating soil CO2 emissions from different restoration habitats was as Canteral et al. [16] have shown. This shows their ongoing capacity to reduce the doubts about the dynamics of the carbon cycle [17]. Sesnie et al. showed how well ensemble Machine Learning models worked by using data from many satellite sensors that foretold tree biomass. Diversity indexes of seasonally dry tropical woods that provide pertinent data for more comprehensive biodiversity mapping projects. As discussed by Li et al. [18], Machine Learning algorithms have shown significant improvements in biomass prediction accuracy in forest ecosystems.

While this study explores the potential of Multi-Output Deep Learning (MODL) models, such as Long Short-Term Memory (LSTM), for biomass prediction, we focus on the Extra Trees (ET) algorithm for its superior performance in small, noisy datasets typical of ecological research. While LSTM has been shown to be effective for sequential data, we demonstrate that in this non-sequential, cross-sectional scenario, ET outperforms MODL due to its robustness in capturing nonlinear interactions and preventing overfitting.

Building on these considerations, Table 1 provides a comparative overview of prior biomass prediction studies, highlighting the diversity of applied methodologies, ranging from traditional allometric approaches to advanced machine learning frameworks. The table emphasizes the variation in datasets, predictor variables, and evaluation metrics, illustrating the fragmented landscape of biomass modeling. This contextualization underscores the rationale for testing both MODL architectures and ensemble learners in the present work.

Table 1: Summary of prior biomass prediction studies.

Study	Models	Dataset	Metrics	Key findings
Li et al. (2020) [14]	XGBoost, RF	Landsat 8 + Sentinel-1A; subtropical forests	R^2, RMSE	XGBoost outperformed traditional methods, improving AGB estimation accuracy.
Sharma et al. (2022) [15]	ML regressors with UAV multispectral data	Oat biomass, multisite	Correlation, RMSE	Strong correlations found, but performance varied across sites.
Zhang et al. (2020) [16]	8 ML regression algorithms (CatBoost, SVR, RF, etc.)	Satellite-based Forest AGB	R^2, RMSE	Ensemble models (CatBoost) outperformed non-ensemble methods.
Ma et al. (2023) [17]	Random Forest, SVR	Airborne LiDAR, subtropical forests	R^2, feature sensitivity	Random Forest superior; LiDAR-derived features critical predictors.
Huy et al. (2024) [5]	Multi-output Deep Learning (MODL)	175 destructively sampled trees, Vietnam	RMSE, MAE	MODL improved multi-output biomass

				prediction vs traditional WNSUR.
Present study	Extra Trees (ET), GB, Bagging, LSTM	175 trees, 27 plots, Vietnam	R^2, RMSE, MAE, VAF	ET outperforms baselines; robust under small, noisy ecological datasets.

This study will test the ET algorithm's efficiency in enhancing the accuracy and reliability of simultaneous biomass estimates of aboveground, belowground, and total biomass in tropical forests.

Gaps and challenges. Prior biomass-estimation studies have been characterized by (i) limited sample sizes resulting from destructive sampling, (ii) collinearity among structural and site variables, and (iii) heterogeneous protocols that complicate generalization. In addition, many works have compared single-output models or emphasized cost or emissions proxies without jointly estimating AGB, BGB, and TB or reporting cross-validated variability. This study's contribution. Biomass prediction is cast as a multi-output regression problem (AGB, BGB, TB), with ET, GB, Bagging, and LSTM benchmarked under a uniform pipeline with leakage-safe cross-validation. A baseline linear regression model is provided for clarity, and model interpretability is added via feature importance and SHAP analysis to ground ecological plausibility. The results show that ET achieves the strongest test performance for this dataset—an empirical conclusion rather than an a priori assumption. These models were selected to represent complementary methodological families. GB provides strong boosting performance on nonlinear ecological data; ET offers variance reduction and robustness on small, noisy datasets; Bagging improves stability via bootstrap aggregation; and LSTM serves as a deep-learning comparator with sequence-modeling capacity. Together, they cover both ensemble and neural approaches, enabling a balanced evaluation of methodological suitability for tropical biomass prediction.

By incorporating a new optimization approach to couple with the ET algorithm, this study aims to overcome the deficiencies of traditional methods and enhance predictive performance. It does so by introducing, for the first time, the use of ET to predict biomass, comparing it with established Machine Learning techniques such as Gradient Boosting, Bagging, and LSTM networks. Until now, ET has been recently applied in ecological modeling; this study will offer fresh viewpoints on its capacity for more exact and reliable biomass estimation supports environmental monitoring and helps forest management. We benchmark ET against Gradient Boosting (GB), Bagging, and a Long Short-Term Memory (LSTM) network. GB provides a strong boosted-tree baseline that incrementally corrects residuals; Bagging isolates the effect of variance reduction via bootstrap aggregation; and LSTM offers a deep-learning comparator with sequence-model capacity. This panel spans complementary inductive biases for nonlinear tabular data, enabling a fair assessment of whether multi-output ET is preferable for tropical biomass estimation.

1.1 Research questions and hypotheses

This study addresses the following research questions:

- RQ1: Can multi-output ensemble methods (Extra Trees, Gradient Boosting, Bagging) and deep learning models (LSTM) provide accurate simultaneous predictions of AGB, BGB, and TB in small, destructively sampled tropical forest datasets?
- RQ2: How does the ET algorithm perform relative to other machine learning methods in terms of predictive accuracy, variance reduction, and robustness to noisy ecological features?
- RQ3: How do machine learning approaches compare to a traditional linear regression baseline for biomass prediction?

Based on prior literature, we hypothesize that (H1) ET will outperform other methods due to its strong variance-reduction properties; (H2) ensemble methods in general will provide more stable results than LSTM in small cross-sectional datasets; and (H3) all machine learning approaches will outperform linear regression due to their ability to capture nonlinear interactions.

2 Methodology and dataset

A leakage-safe pipeline is implemented, consisting of the following stages: data curation → preprocessing (missing-data handling, encoding, scaling) → train/validation selection with K-fold cross-validation applied within the training set only → model selection and tuning (ET, GB, Bagging, LSTM) → final training on the full training set using the best hyperparameters → held-out test evaluation. All three targets (AGB, BGB, TB) are predicted jointly in a multi-output framework, and robustness is quantified through cross-validation statistics and confidence intervals on the test-set metrics

The contribution is framed around ET (ET)—an ensemble of fully randomized decision trees (a variant of Random Forest) in which randomized split thresholds and feature subsampling are employed to reduce variance and capture nonlinear feature interactions in tabular ecological data. ET is deployed in a multi-output regression setting for AGB, BGB (belowground biomass), and TB (total biomass) in order to exploit cross-target correlations. On the small-to-medium tropical forest dataset, ET is shown to yield the most reliable test-set performance among the compared learners by effectively handling noisy measurements, collinearity, and heterogeneous predictor scales. ET is particularly suitable here because (i) destructive-sampling forest datasets are typically small-n with complex, nonlinear structure; (ii) ET's heavy randomization curbs overfitting better than deep trees

trained deterministically; and (iii) tree ensembles natively support mixed feature types and are robust to monotone transformations, which simplifies preprocessing relative to deep models. A dataset of 175 destructively sampled trees from 27 plots in Vietnam's Central Highlands (tree-level records) was used. Predictors included structural measurements (e.g., DBH, total height, canopy area), site/environmental descriptors (e.g., elevation, slope, soil type/category), and any available remote-sensing proxies collocated to plots. The targets were AGB, BGB, and TB (kg). Rows with missing target values were removed; numeric predictors were standardized; and categorical predictors were one-hot encoded. The data were split 80/20 (train/test) with a fixed random seed, and all cross-validation and scaling were fitted only on the training partition to avoid leakage. In the current simulation, the ET method was used to improve regression accuracy and compare it with several state-of-the-art Machine Learning models, namely Gradient Boosting, Bootstrap Aggregating, and Long Short-Term Memory networks. During testing and training, the models' evaluation indicators were defined and shown via plot fit and plot regression diagrams, hence providing a complete comparative study of their ability to forecast biomass. The dataset employed in this investigation was created for a book [3]. It relies on a destructive sample of 175 trees harvested from 27 specifically chosen plots in Vietnam's Central Highlands ecoregion. This dataset helped construct and cross-validate multi-output Deep Learning (DL) models, which are an alternative to the traditional Weighted Nonlinear Seemingly Unrelated Regression (WNSUR) technique. The input features for model training include tree-level measurements (e.g., diameter at breast height, tree height, canopy area) and environmental variables relevant for biomass prediction, selected based on prior studies and domain knowledge. These features were used to predict aboveground biomass (AGB), belowground biomass (BGB), and total biomass (TB) simultaneously.

Before training, the dataset was preprocessed as follows: rows with missing values were removed to ensure data quality; numeric features were standardized using StandardScaler to have zero mean and unit variance; categorical variables (if any) were encoded using one-hot encoding to make them compatible with all machine learning models.

Hyperparameters for each model were optimized using GridSearch with 5-fold cross-validation. The selected optimal parameters were as follows:

- Gradient Boosting (GB): learning rate = 0.2, max depth = 5, n_estimators = 200
- Extra Trees (ET): max depth = None, min_samples_split = 2, n_estimators = 50
- Bagging: max features = 1, max samples = 1, n_estimators = 100
- Long Short-Term Memory (LSTM): lookback = 10, units = 50, dropout = 0.2.

Though the collection is rather modest—175 trees over 27 plots—this is in line with destructive sampling research in tropical woodlands, where logistical and environmental constraints limit the amount of data available. Earlier works using destructive sampling (e.g., Huy et al. 2024 [5]) depend on comparable scales. Our research therefore provides a useful benchmark dataset and mirrors a fair sample size for field-based biomass forecast.

The main purpose was to forecast aboveground biomass (AGB), belowground biomass (BGB), and total tree biomass (TB) in two major tropical forest types: dipterocarp forest (DF) and evergreen broadleaf forest (EBLF). When compared to standard WNSUR models, multi-output DL models outperformed the latter in terms of simultaneous predictions. These deep learning models effectively incorporated multiple complex ecological factors, considerably improving the reliability and accuracy of forest biomass projections. (Figure 1).

2.1 Algorithm selection and justification

The machine learning algorithms used in this study were selected to capture a wide range of modeling capabilities suitable for ecological biomass prediction:

- Gradient Boosting (GB)

GB incrementally fits new trees to residuals of previous ones, achieving high predictive accuracy on nonlinear data. In our implementation, hyperparameters were tuned via GridSearchCV, yielding learning rate = 0.2, max depth = 5, and n_estimators = 200. This setup balances complexity with generalization.

- Extra Trees (ET)

ET constructs randomized decision trees with split thresholds drawn at random, which reduces variance and limits overfitting on small datasets. Our optimal configuration used n_estimators = 50, max depth = None, and min_samples_split = 2.

- Bagging

Bagging stabilizes predictions by aggregating multiple bootstrap-trained models. Here, we used Decision Trees as base learners with n_estimators = 100, max_features = 1.0, and max_samples = 1.0.

- Long Short-Term Memory (LSTM)

LSTMs are recurrent neural networks designed for sequential data. While our dataset is cross-sectional, we included LSTM as a deep-learning comparator. The model was configured with lookback = 10, hidden units = 50, and dropout = 0.2.

The detailed search space and tuned values for each algorithm are summarized in Table 2, which documents the hyperparameters optimized through GridSearchCV. This table provides transparency in the model selection process and ensures reproducibility, highlighting the balance achieved between predictive performance and computational efficiency across the compared learners.

Table 2: Hyperparameters used for model tuning via GridSearchCV

Model	Parameter	Best Value
Gradient Boosting (GB)	Learning Rate	0.2
	Max Depth	5
	N Estimators	200
Extra Trees (ET)	Max Depth	None
	Min Samples Split	2
	N Estimators	50
Bagging	Max Features	1.0
	Max Samples	1.0
	N Estimators	100
LSTM	Lookback Window	10
	Units	50
	Dropout	0.2

2.2 Preprocessing and model setup

The dataset consisted of 175 destructively sampled trees from 27 plots in Vietnam's Central Highlands, with predictor variables including tree structural measurements (e.g., diameter at breast height, total height, canopy area), site descriptors (e.g., elevation, slope, soil type), and categorical ecological indicators. The target variables were Aboveground Biomass (AGB), Belowground Biomass (BGB), and Total Biomass (TB).

Prior to model training, rows containing missing values were removed. Numerical features were standardized using StandardScaler to zero mean and unit variance, and categorical features were one-hot encoded. The dataset was split into training and testing partitions using an 80/20 ratio (test_size=0.2) with a fixed random seed of 42 to ensure reproducibility.

Hyperparameter tuning was performed using GridSearchCV within the training set for each model. The optimal values obtained were:

- Gradient Boosting (GB): learning rate = 0.2, max depth = 5, n_estimators = 200
- ET: max depth = None, min_samples_split = 2, n_estimators = 50
- Bagging: base estimator = Decision Tree, max_features = 1.0, max_samples = 1.0, n_estimators = 100
- LSTM: lookback window = 10, hidden units = 50, dropout = 0.2

These configurations were selected as they consistently delivered the best cross-validation results for their respective models. Final evaluation was performed on the held-out test set.




Figure 1: The procedure of modelling

The models under study were statistically assessed with a range of often used metrics, as Table 4 shows. The Mean Absolute Dividing the sum of the absolute variation determined by the total count of observations. By the square root of the mean of the squared differences between each prediction and the associated reality, the RMSE is determined. It therefore illuminates the model's forecasts' veracity. The variance explained (VAF) reveals the degree of variance in the actual values predicted by the predictions. Usually described is the Pearson's correlation coefficient, often known as the R-value in the linear relationship between the actual and predicted values. The Max Error shows the largest disparity between the anticipated and actual values, therefore producing a worst-

case forecast scenario. Standard deviation (Std) measures the dispersion of the prediction errors from the mean value, giving an indication of the variability in model performance. These statistical markers give a broad sense of the models' performance, dependability, and accuracy [3].

2.3 Computational environment

All tests were carried out in Google Colab utilizing Python 3.x in order to guarantee repeatability. Key software libraries and versions are presented in Table 3. To keep consistency across runs, a fixed random seed of 42 was used throughout the data splitting, cross-validation, and training operations.

Table 3: Computational environment used in this study.

Component	Details
Platform	Google Colab
Python Version	3.x (Colab runs Python 3 by default)
Libraries	
NumPy	1.21.x or higher
Pandas	1.3.x or higher
scikit-learn	0.24.x or higher
TensorFlow/Keras	TensorFlow 2.x (with Keras as part of it)
OpenPyXL	For Excel file handling

2.4 Statistical analysis

Reporting of R^2, VAF, MAE, RMSE, and MaxError as well as K-fold suggests the study emphasizes model validation and explanatory diagnostics instead of manual feature extraction. For interpretability, permutations importances and SHAP values are calculated to investigate the factors propelling AGB, BGB, and means and standard deviations utilized to measure stability. TB and to evaluate ecological realism.

Table 4: Statistical evaluation indexes.

Criteria	Equation
Mean Absolute Error, MAE	$\frac{\sum_{i=1}^{n}\lvert y_i-\hat{y}_i\rvert}{n}$
Root Mean Square Error, RMSE	$\sqrt{\frac{\sum_{i=1}^{n}(y_i-\hat{y}_i)^2}{n}}$
Variance account factor, VAF	$\left(1-\frac{var(t_n-y_n)}{var(t_n)}\right)*100$
Pearson's correlation coefficient, R	$\frac{\sum_{n=1}^{N}(t_n-\bar{t})(p_n-\bar{p})}{\sqrt{[\sum_{n=1}^{N}(t_n-\bar{p})^2][\sum_{n=1}^{N}(p_n-\bar{p})^2]}}$
Max error, Max	$Max = max\,(abs\,(Y_{real} - Y_N))$
Standard deviation, Std	$Standard\ Deviation = \sqrt{\frac{\sum_{i=1}^{n}(x_i-\bar{x})^2}{n-1}}$

3 Machine learning

Managing and analyzing difficult environmental data more effectively also helps Machine Learning to enhance the precision and efficiency of biomass predictions in tropical forests. From Utilizing sophisticated algorithms, multioutput deep learning models—famer models—can simultaneously forecast a spectrum of related outputs—from aboveground to belowground biomass. In many respects, this combined approach surpasses previous ones. offers a significantly better grasp of forest ecosystems. Among the several data sets machine learning systems can analyze to find patterns are environmental characteristics and remote sensing data. and relationships which traditional techniques often ignore. Better the predictive accuracy of such models, which makes them helpful tools for projects meant to lessen the effects the more data they accumulate over time. on forest management and preservation of climate change.

3.1 Gradient-boosting

As shown in Figure 2, gradient boosting is a machine learning technique whereby multiple models are generated step wise to produce a strong predictive model. An initial model, typically a rough constant prediction, is spawned. Residuals, differences between the actual values and the initial predictions, are computed. New models are trained on predicting these residuals. Each new model's predictions are added to the previous model's predictions, typically scaled by a learning rate to control their contribution and prevent overfitting. This iterative process continues until the model's performance reaches an acceptable level or a predefined number of iterations is reached [19].

The strength of gradient boosting lies in its ability to produce highly accurate models by correcting errors from previous iteration. It is highly flexible and can be applied to various types of loss functions, making it suitable for

both regression and classification tasks. However, gradient boosting can be computationally intensive and prone to overfitting if not properly regularized. These popular implementations, such as XGBoost, LightGBM, and CatBoost, have optimized the algorithm for efficiency and scalability [20].




Figure 2: The structure of gradient boosting

3.2 Bootstrap aggregating

Bootstrap aggregating, often abbreviated as bagging, is an ensemble learning technique designed to improve the stability and accuracy of Machine Learning algorithms. This involves generating multiple subsets of data by random sampling with replacement from the original dataset. It considers each subset for training a different model-mostly of the identical model type. Sampling with replacement ensures that some observations may appear multiple times in one subset, while others may not appear at all. The key objective of bagging is to reduce the model's variance, making it more robust and less prone to overfitting.

All the models are trained, and their predictions are combined to form the final output. For classification tasks, it typically involves majority voting or probability averaging (see Figure 3). It works by taking the predictions of several models and combining them to produce a better prediction than any single model could make alone. The method especially works well with high-variance algorithms such as decision trees. The most famous implementation of bagging is the Random Forest algorithm. It creates an ensemble of decision trees, combines their outputs to improve accuracy, and controls overfitting.




Figure 3: The structure of bootstrap aggregating

3.3 Long short-term memory

Figure 4 displays Long Short-Term Memory (LSTM), an RNN architecture variant suited to modeling sequences of data and time series. Unlike traditional RNNs, which suffer from the vanishing gradient problem that makes learning long-term dependencies difficult, LSTMs are designed to remember information for a long time. They do this by using a series of gates—input gate, forget gate, and output gate—that govern the flow of information into and out of the cell state. These gates enable the network to retain only useful information and discard irrelevant data. Hence, LSTMs perform exceptionally well in tasks such as language modeling, speech recognition, and time series forecasting.




Figure 4: The structure of long short-term memory (LSTM).

Because of these capabilities, LSTMs have been studied and applied in a wide range of domains. Other applications of LSTMs include financial time-series data; in natural language processing, they are employed in machine translation tasks that call for comprehension of context across numerous words. where the time axis is utilized to forecast stock prices. Moreover, LSTMs are among the most flexible and strong Machine Learning instruments. Deep learning jobs are resistant to noise and varied lengths of input series. This is made possible by the design's capacity for data processing and its success in retaining context across long sequences. Because of its adaptability, LSTM has become a crucial building block in developing intelligent systems needing temporal data processing.

3.4 Extra tree

Figure 5 shows that the Extra Tree algorithm (ET), also known as Extremely Randomized Trees, is an ensemble learning technique applied to both regression and classification problems. ET trains an ensemble of fully randomized trees: at each node, a random subset of features is considered and random split thresholds are drawn; the best among these random splits is selected by impurity reduction. Trees are grown to near-purity (or constrained by min samples split/min samples leaf), and predictions are averaged across “n estimators”. This aggressive randomization lowers variance and mitigates overfitting on small-n tabular data. In tuning, we search over n estimators, max depth, min samples split, min samples leaf, and max features, selecting hyperparameters by cross-validated performance on the training set. Unlike traditional decision trees, ET introduces two levels of randomness by selecting split points randomly from a subset of features.




Figure 5: The structure of extra tree algorithm

4 Results and discussion

The performance of Extra Trees (ET) was compared with other machine learning models, including Gradient Boosting (GB), Bagging, and Long Short-Term Memory (LSTM), for predicting aboveground biomass (AGB), belowground biomass (BGB), and total biomass (TB). ET achieved the highest test-set performance with $R^2 = 0.997$ (BGB), 0.997 (AGB), and 0.996 (TB), demonstrating its robustness in capturing complex nonlinear relationships in ecological data. In contrast, GB performed slightly lower on the test set ($R^2 = 0.994$), which aligns with prior findings that ensemble tree methods are more effective for small, heterogeneous datasets.

Although ET showed excellent performance, its results emphasized the difficulty of grabbing belowground biomass (BGB) because of its natural noisiness. To solve these problems, future studies should investigate bigger datasets and add remote sensing capabilities.

The better performance of Extra Trees (ET) in biomass estimation indicates its possible incorporation with remote sensing processes in operational forestry monitoring systems. For near-real-time estimates of aboveground and underground biomass in forested regions, for instance, ET might be combined with LiDAR data or satellite-derived vegetation indices. Combination might allow for more effective forest management wherein quick biomass assessments are needed to guide carbon sequestration calculations or conservation initiatives.

4.1 Benchmark model comparison

To provide a benchmark for comparison, a linear regression model was implemented using the same input features. Performance metrics including VAF, R^2, MAE, MAPE, Max Error, and RMSE were calculated. Linear regression achieved a VAF of 0.976, R^2 of 0.975, and RMSE of 0.157, indicating its limited ability to capture nonlinear relationships in the data. In contrast, all machine learning models, particularly ET, showed significantly improved performance, highlighting the effectiveness of ensemble learning for biomass prediction in tropical forests.

The numerical outcomes of the linear regression benchmark are reported in Table 5, which consolidates all calculated performance metrics. While the results confirm that linear regression provides a reasonable baseline, the relatively higher error measures underscore its inadequacy for modeling complex ecological interactions compared to the nonlinear learners evaluated in this study.

Table 5: Result of linear regression

Model	VAF	R^2	MAE	MAPE	Max Error	RMSE	EV
LR	0.976	0.975	0.097	24.500	0.573	0.157	0.976

4.2 Model comparison and interpretation

Across folds and on the held-out test set, ET exhibits the highest R^2/VAF and the lowest MAE/RMSE, outperforming GB, Bagging, and LSTM. The performance gap is most pronounced for BGB, where tree-ensemble variance reduction appears to help with noisier belowground signals. GB is competitive but slightly less stable (higher fold-to-fold Std), consistent with boosted trees' sensitivity to learning-rate/depth trade-offs. LSTM underperforms in this cross-sectional setting, which aligns with its sequential inductive bias. Error distributions show ET reduces extreme residuals (MaxError) relative to Bagging/LSTM, indicating better handling of outliers. And for the Cross-validation robustness. Table 6 summarizes 5-fold means ± SD: ET (VAF 0.9970±0.0025; R^2 0.9967±0.0028; MAE 0.0295±0.0111) vs GB (0.9958±0.0034; 0.9951±0.0037; 0.0446±0.0193), Bagging (0.9934±0.0047; 0.9928±0.0046; 0.0568±0.0214), LSTM (0.9892±0.0065; 0.9873±0.0075; 0.0751±0.0238). Figure 6 supports ET's stability benefits. These results fit the theoretical basis for model selection: ET's fierce randomization reduces overfitting, while GB and Bagging give competitive ensemble baselines; LSTM is less successful given the lack of temporal structure in the data.

Table 6: Five-fold cross-validation results for all models. Values reported as mean ± standard deviation.

Model	VAF Mean	VAF Std	R^2 Mean	R^2 Std	MAE Mean	MAE Std
GB	0.995	0.003	0.995	0.003	0.044	0.019
ET	0.997	0.002	0.996	0.002	0.029	0.011
Bagging	0.993	0.004	0.992	0.004	0.056	0.021
LSTM	0.989	0.006	0.987	0.007	0.075	0.023

The possibility of overfitting arose from the very high R^2 and VAF numbers seen in training. We performed five-fold cross-validation on the training data to investigate this and include the mean ± standard deviation of important statistics in Table 6. With regularly low variation across folds, ET produced the best average performance (R^2 = 0.996 ± 0.002, MAE = 0.029 ± 0.011). The results verify this. Gradient Boosting was competitive but showed somewhat more volatility (R^2 = 0.995 ± 0.003). Bagging and LSTM exhibited less and more erratic outcomes with LSTM displaying the greatest variability and lowest mean R^2. These results show that even if the R^2 values of training are excellent, the low standard deviations across folds point to consistent generalization instead of overfitting. This raises faith in the stated test results.

The small dataset size poses challenges for generalizability, particularly in heterogeneous tropical forests. To mitigate this, we applied 5-fold cross-validation, reporting mean ± standard deviation values for each model. The low variability observed across folds for ET (R^2 = 0.996 ± 0.002) and GB (0.995 ± 0.003) indicates stable generalization despite limited sample size. Nonetheless, generalizability beyond the Central Highlands is limited, and future studies should validate these models on larger and more geographically diverse datasets.




Figure 6: Comparison of R^2 values for BGB predictions across ET, GB, Bagging, and LSTM models.

Four models—Gradient Boosting (GB), ET (ET), Bagging, and Long-Short-Term Memory (LSTM)—were assessed in this comparative study across a range of performance indicators; shown the best accuracy. Achieving The best performance on The ET as against the training data shows the lowest MAE and RMSE as well as the highest VAF and R^2. Among the test set, the highest VAF and R^2, the lowest MAE and Mean Absolute Percentage Error. Despite these strong results, ET had a higher maximum error compared to Gradient Boosting. LSTM performed poorly in terms of MAE, MAPE, and RMSE, indicating lower accuracy and consistency in predictions. Overall, Gradient Boosting and ET showed the strongest performance, with ET slightly outperforming Gradient Boosting on the test data as shown in Figure 7. Also, the results based on Box plot given in Figure 8 emphasizes on the acceptable performance of ET.




Figure 7: Comparison of model based on value




Figure 8: Comparison of model based on box plot

According to Figure 9, Gradient Boosting exhibited the lowest maximum error on the training set (0.295), indicating minimal extreme deviations. On the test set, its maximum error was 28.645, which was still lower than LSTM but higher than ETs. ET exhibited a higher maximum error of 13.855 on the training set and 12.452 on the test set, indicating larger extreme deviations. Bagging had the highest maximum error, with 195.863 on the training set and 66.329 on the test set. LSTM had the highest maximum error on the test set, 34.364, indicating significant outliers. Gradient Boosting had the perfect R^2 value of 1 on the training set and a very high R^2 of 0.994 on the test set, signifying a model that fits the training data excellently and generalizes well. ETs also demonstrated strong R^2 values (0.999 on training and 0.997 on test), surpassing Bagging and LSTM. Bagging had a slightly lower R^2 than the top performers, while LSTM had the lowest R^2 on both training (0.995) and test sets (0.984), reflecting poorer performance as confirmed in Figure 6.

More details regarding the various metrics are compared in Figure 10.




Figure 9: Comparison of model based on error

According to Figure 11, Gradient Boosting achieved the lowest RMSE on training (0.0845), showing minimal average squared deviation. Its test RMSE was 7.076, still lower than most other models. ETs also had a lower RMSE (4.282 on training and 4.886 on test) compared to Bagging and LSTM. Bagging and LSTM had higher RMSE values, with LSTM showing the highest test RMSE (12.056), indicating larger errors in predictions.




Figure 10: Comparison of model based on metrics




Figure 11: Comparison of model based on root mean square error

Gradient Boosting achieved the highest VAF on both the training and test sets, indicating it explained nearly all of the variance in the data during training (99.999%) and remained robust on the test set (99.522%). ETs also performed well, with high VAF values of 99.903 during training and 99.831 on the test set, suggesting strong generalization. Bagging and LSTM showed lower VAF scores, especially LSTM, which had the lowest VAF values in both sets, indicating a less effective variance explanation as shown in Figure 12. Besides, the results given in Figure 13 emphasizes on the superiority of ET over the rest in terms of three case studies.




Figure 12: Comparison of model based on hybrid




Figure 13: Value of 3 case study according to ET for each case.

According to Figure 14, Gradient Boosting showed the lowest MAE on the training data (0.06), indicating minimal average deviation of predictions from actual values. On the test set, however, Gradient Boosting's MAE increased to 3.385, but it still performed better than other models. ETs had a similar MAE on both training (3.664584) and test (3.863) sets, while Bagging and LSTM exhibited higher MAE values, with LSTM having the highest MAE on the test set (9.451), reflecting larger average prediction errors.




Figure 14: RMSE according to ET for each case

According to hybrid outcome, the performance of ET for each case study is acceptable as given in Figure 15 [5]. Gradient Boosting achieved the lowest MAPE on the training set (0.003), showing minimal average percentage error. It maintained a low MAPE of 0.0331 on the test set, demonstrating effective relative error performance. ETs had slightly higher MAPE values (0.314 on training and 0.065984 on test) but still performed better than Bagging and LSTM. LSTM had the highest MAPE on the test set (0.168), indicating relatively less accurate percentage error. Gradient Boosting achieved a perfect explained variance of 1 on training and a high 0.995 on test, showing

excellent data fit. ETs also performed well, with a high explained variance of 0.998316 on test. Bagging and LSTM had lower explained variance values, with LSTM being the least effective, indicating a less accurate representation of the variance in the data. Gradient Boosting showed the lowest standard deviation of error on training (0.084), reflecting minimal variability in prediction errors. Its test STDError was 6.775, which was still lower than Bagging and LSTM. ETs had a higher standard deviation of error on both training (4.282) and test (4.022), while LSTM had the highest test STDError (8.767), indicating greater variability in errors as demonstrated in Figure 16.




Figure 15: Hybrid according to ET for each case study




Figure 16: The findings of ET for each case study




Figure 17: SHAP summary plot of feature importance for biomass prediction using extra trees.

The performance metrics outlined in Table 7 indicate the following numerical results for the hybrid models. For the training phase, GB achieved a VAF of 99.999 and an R^2 of 1, demonstrating nearly perfect prediction accuracy. Its MAE was notably low at 0.060, while the RMSE was 0.084. In comparison, ET achieved a VAF of 99.903 and an R^2 of 0.999, with an MAE of 3.664 and an RMSE of 4.282. Bagging yielded a VAF of 98.172 and an R^2 of 0.981, with a higher MAE of 3.405 and an RMSE of 18.777. LSTM had a VAF of 99.552 and an R^2 of 0.995, but exhibited the highest MAE of 7.881 and an RMSE of 9.249. For the testing phase, ET stood out with a VAF of 99.831 and an R^2 of 0.997, maintaining a low MAE of 3.863 and an RMSE of 4.886. In contrast, LSTM had a VAF of 99.199, an R^2 of 0.984, with an MAE of 9.451 and an RMSE of 12.056.

The detailed error metrics for the prediction of AGB, BGB, and total biomass are given in Table 8. For its BGB, the ETs system achieved the best training VAF of 99.90391 and for AGB 99.879, respectively, with the R^2 values of 0.999 and 0.998 correspondingly. Since MAE of 3.664 for BGB and of 3.361 for AGB, while the RMSE for BGB was equal to 4.282, and for AGB - 4.129. The VAF for ETs was 99.889 when calculating TB, R^2 stood at 0.998, MAE was 3.738, and RMSE of 4.602. In the testing phase, it was 99.863 for AGB and 99.831 for BGB. The corresponding R^2 values were 0.997 and 0.997 for AGB and BGB, respectively. For MAE, the values were 3.505 for AGB and 3.863 for BGB in reverse order. And finally, their RMSE was 4.546 and for BGB, 4.886. TB-VAF: 99.740, R^2: 0.996, MAE: 3.879, RMSE: 5.956. These reflect a much better performance through the ETs model in predicting biomass with higher accuracy for types and phases variation. MAE quantifies the average deviation from the true biomass values. ET's MAE of 3.86 indicates a high level of precision, making it more suitable for practical applications like carbon accounting and forest management. RMSE penalizes larger errors, capturing the impact of outliers. ET's RMSE (4.89) is lower than Bagging and LSTM, reflecting more consistent predictions even for extreme biomass values. GB has slightly lower MAE than ET, but its higher RMSE suggests that it occasionally produces larger deviations, reducing reliability in field applications. Practical Implication: These metrics demonstrate that ET provides both accurate and robust predictions, which is critical for forest monitoring programs where errors in biomass estimates propagate directly into carbon stock assessments.

Maximum error for ET was 12.452 on the test set, compared with 28.645 for GB and 34.364 for LSTM. STDError for ET was 4.022, lower than Bagging (13.379) and LSTM (8.767). The lower maximum error and standard deviation of ET indicate more reliable predictions across all samples, especially in handling trees with extreme biomass values. This further supports ET's suitability for real-world ecological applications, where some plots or trees may deviate significantly from average conditions.

ETs (ET): Best overall performance, robust to outliers, effectively captures nonlinear relationships, and generalizes well. Gradient Boosting (GB): Excellent on training, slightly lower generalization on test, sensitive to extreme values (higher RMSE). Bagging: Moderate

performance, higher variability, less suitable for small datasets with high feature complexity. LSTM: Poor test performance due to limited dataset size and inability to capture spatial relationships effectively; suitable mainly for sequential or temporal data.

ET's performance demonstrates that Machine Learning can surpass traditional allometric models, providing more reliable biomass estimates for both aboveground and belowground components. Accurate predictions directly inform carbon sequestration calculations, forest management, and conservation planning. The lower variability and robust test performance indicate that ET is suitable for operational forestry applications, where consistency and accuracy are essential.

To further quantify robustness, we computed 95% confidence intervals on the test-set metrics using bootstrap resampling. For ET, R^2 = 0.997 (95% CI: 0.996–0.998) and RMSE = 4.89 (95% CI: 4.32–5.51). GB achieved R^2 = 0.994 (95% CI: 0.993–0.996), RMSE = 7.08 (95% CI: 6.25–7.92). Bagging and LSTM exhibited wider intervals, confirming less stability. These results are consistent with the low standard deviations reported in the cross-validation analysis (Table 6), supporting the reliability of ET's superior performance.

SHAP values for Extra Trees were calculated to evaluate feature contributions and so explain model behavior. Figure 17 shows the SHAP summary chart, in which predictors are ordered by their mean influence on model output amount. The most important parameters discovered were structural measurements, especially diameter at breast height (DBH) and total tree height, then canopy area and altitude. While categorical ecological indicators showed smaller but non-negligible effects, soil type and slope showed modest contributions. SHAP scatter plots further show Consistent with ecological predictions, rising DBH and tree height greatly boosted forecast biomass. These findings validate the model's predictive patterns with established ecological links, therefore bolstering confidence in its utility for estimating forest biomass.

Table 7: Error metrics derived from the application of hybrid models.

Optimizer	GB	ET	Bagging	LSTM
	Train			
VAF	99.999	99.903	98.172	99.552
R^2	0.999	0.999	0.981	0.995
MAE	0.060	3.664	3.405	7.881
MAPE	0.003	0.314	0.022	0.752
MaxError	0.295	13.855	195.863	23.4
RMSE	0.084	4.282	18.777	9.249
ExplainedVariance	1	0.999	0.981	0.995
STDError	0.084	4.282	18.677	9.242
	Test			
VAF	99.522	99.831	98.136	99.199
R^2	0.994	0.997	0.981	0.984
MAE	3.385	3.863	5.289	9.451
MAPE	0.033	0.065	0.032	0.168
MaxError	28.645	12.452	66.329	34.364
RMSE	7.076	4.886	13.411	12.056
ExplainedVariance	0.995	0.998	0.981	0.991
STDError	6.775	4.022	13.379	8.767

Table 8: Error metrics derived from the application of hybrid models.

	AGB	BGB	TB
Optimizer	Train		
VAF	99.879	99.903	99.889
R^2	0.998	0.999	0.998
MAE	3.361	3.664	3.738
MAPE	0.429	0.314	0.337
MaxError	11.585	13.855	13.685
RMSE	4.129	4.282	4.602
ExplainedVariance	0.998	0.999	0.998
STDError	4.129	4.282	4.602
	Test		
VAF	99.863	99.831	99.74
R^2	0.997	0.997	0.996
MAE	3.505	3.863	3.879
MAPE	0.064	0.065	0.058

MaxError	9.755	12.452	23.966
RMSE	4.546	4.886	5.956
ExplainedVariance	0.998	0.998	0.997
STDError	3.199	4.022	4.997

4.3 Discussion

The results demonstrate that ETs (ET) achieved superior performance compared to Gradient Boosting, Bagging, LSTM, and a linear regression baseline. These outcomes are consistent with prior studies reporting the effectiveness of ensemble tree models for ecological prediction tasks. In particular, ET's strength lies in its ability to handle small, destructively sampled datasets by leveraging aggressive randomization in both feature selection and split thresholds, which reduces overfitting and improves generalization. This characteristic is critical in tropical forest applications where datasets are often limited in size and contain noisy, heterogeneous measurements. Compared with state-of-the-art approaches based on remote sensing and deep learning, ET provides competitive or superior accuracy despite relying on smaller field-based datasets. This suggests that ET is well-suited for scenarios where destructive sampling restricts sample size, and where nonlinear relationships between tree structure, site descriptors, and biomass must be captured reliably.

Nonetheless, some performance gaps were observed, particularly in belowground biomass (BGB) estimation, which is inherently noisier and less directly observable. These gaps may be explained by collinearity among predictors, class imbalance between tree size categories, or sparse distribution of extreme values in the dataset. Future research could address these challenges by enlarging sample sizes, integrating additional remote sensing features, or applying hybrid ensemble–deep learning frameworks.

Overall, this study reinforces the value of ET as a robust, variance-reducing ensemble model for ecological prediction, while highlighting areas where ecological data properties still limit predictive performance

4.4 Computational cost comparison

While Extra Trees (ET) outperformed Gradient Boosting (GB), Bagging, and Long Short-Term Memory (LSTM) in accuracy, it comes with a computational cost. As shown in Table 9, ET required 1.142 seconds and 8.42 MB of memory on average, making it more computationally intensive than GB (0.973 s, 0 MB) and Bagging (0.250 s, 2.84 MB). LSTM (0.446 s, 0 MB) was also faster, but less effective in biomass estimation. These findings highlight that ET offers the best performance, albeit at a higher computational cost, which must be considered when deploying in real-time or field-based forestry applications.

Table 9: Computational cost comparison of models.

Model	Time (s)	Memory (MB)
GB	0.973	0
ET	1.142	8.421
Bagging	0.250	2.835
LSTM	0.446	0

5 Conclusion

Indeed, according to the evidence provided, the ET method has yielded promising results regarding biomass estimation in tropical forests compared with other Machine Learning models: GB, Bagging, and LSTM networks. Particularly, the ET got amazing training VAF results of 99. 903 for BGB, 99. 879 for AGB, and 99. 889 for TB. Its R-squared values 0.999 were for as a result, it was the best-fit model with a Mean Absolute Error of 3. 664 for ET, 0. 998 for BGB and 0. 998 for TB. The Root Mean Square Errors of 4. 282, 4. 129, and 4. 602 for the related biomass are given in respectively. Respectively values for BGB, AGB, and TB are 3. 361 and 3. 738. Because the ET model precisely and consistently estimates biomass, as demonstrated by the emphasis of these findings is its capacity as a tool for measuring biomass; a device that could be used to enhance carbon accounting and forest management techniques.

To provide more accurate forecasts, future studies should focus on combining ETs with other sophisticated Machine Learning prediction methods and their hybrid models. Increasing the dataset more would let coverage of a far wider spectrum of forest kinds and environmental conditions, therefore improving the generalizing ability and stability of the model. ET's coupling with remote sensing methods and high-resolution photographs might improve the accuracy of forest biomass distribution and changes in structure. Additionally, creating a real-time ET-based monitoring system would make dynamic woodland management easier so that to preserve the Adopt more Efficient ways to slow down climate change.

Future research should explore the integration of ET with high-resolution remote sensing data, such as satellite imagery (Landsat, Sentinel) or UAV-based LiDAR, to improve biomass prediction accuracy across larger forested regions. By incorporating these technologies, ET can provide spatially explicit, real-time biomass estimates, which could support dynamic forest management systems and help track carbon stock changes over time.

References

[1] W. Chen, X. Li, and L. Wang, *Remote Sensing Intelligent Interpretation for Mine Geological Environment: From Land Use and Land Cover Perspective*. Springer Nature, 2022.

[2] D. B. Gemeda, "mplementation of Machine Learning Models for Transmission Grid Monitoring and Blackout Prevention," *Dissertation, Karlsruhe, Karlsruher Institut für Technologie (KIT)*, 2024.

[3] B. Huy, N. Q. Truong, K. P. Poudel, H. Temesgen, and N. Q. Khiem, "Multi-output deep learning models for enhanced reliability of simultaneous tree above-and below-ground biomass predictions in tropical forests of Vietnam," *Comput Electron Agric*, vol. 222, p. 109080, 2024. https://doi.org/10.1016/j.compag.2024.109080

[4] V. N. Manawat, "Technical Efficiency of Wildfire Detection and Machine Learning Predictions in Alberta, Canada," 2024. https://doi.org/10.7939/r3-y6bq-8a23

[5] M. F. Oliveira *et al.*, "Predicting below and above-ground peanut biomass and maturity using multi-target regression," *Comput Electron Agric*, vol. 218, p. 108647, 2024. https://doi.org/10.1016/j.compag.2024.108647

[6] J. Saini, M. Dutta, G. Marques, J. Saini, M. Dutta, and G. Marques, "Predicting indoor air quality: integrating IoT with artificial intelligence," *Internet of Things for Indoor Air Quality Monitoring*, pp. 51–67, 2021. https://doi.org/10.1007/978-3-030-82216-3_4

[7] M. V. Sebt, Y. Sadati-Keneti, M. Rahbari, Z. Gholipour, and H. Mehri, "Regression Method in Data Mining: A Systematic Literature Review," *Archives of Computational Methods in Engineering*, pp. 1–20, 2024. https://doi.org/10.1007/s11831-024-10088-5

[8] C. Silva-Perez, A. Marino, and I. Cameron, "Monitoring Agricultural Fields Using Sentinel-1 and Temperature Data in Peru: Case Study of Asparagus (Asparagus officinalis L.)," *Remote Sens (Basel)*, vol. 12, no. 12, p. 1993, 2020.

[9] C. Xu, B. Wang, and J. Chen, "Forest carbon sink in China: Linked drivers and long short-term memory network-based prediction," *J Clean Prod*, vol. 359, p. 132085, 2022. https://doi.org/10.1016/j.jclepro.2022.132085

[10] Y. Li, M. Li, C. Li, and Z. Liu, "Forest aboveground biomass estimation using Landsat 8 and Sentinel-1A data with machine learning algorithms," *Sci Rep*, vol. 10, no. 1, p. 9952, 2020. https://doi.org/10.1038/s41598-020-67024-3

[11] P. Sharma, L. Leigh, J. Chang, M. Maimaitijiang, and M. Caffé, "Above-ground biomass estimation in oats using UAV remote sensing and machine learning," *Sensors*, vol. 22, no. 2, p. 601, 2022.

[12] Y. Zhang, J. Ma, S. Liang, X. Li, and M. Li, "An evaluation of eight machine learning regression algorithms for forest aboveground biomass estimation from multiple satellite data products," *Remote Sens (Basel)*, vol. 12, no. 24, p. 4015, 2020.

[13] J. Ma, W. Zhang, Y. Ji, J. Huang, G. Huang, and L. Wang, "Total and component forest aboveground biomass inversion via LiDAR-derived features and machine learning algorithms," *Front Plant Sci*, vol. 14, p. 1258521, 2023. https://doi.org/10.3389/fpls.2023.1258521

[14] G. Li, C. Li, G. Jia, Z. Han, Y. Huang, and W. Hu, "Estimating the Vertical Distribution of Biomass in Subtropical Tree Species Using an Integrated Random Forest and Least Squares Machine Learning Mode," *Forests*, vol. 15, no. 6, p. 992, 2024.

[15] M. J. Diamantopoulou, A. Çömez, R. Özçelik, and S. T. Güner, "Exploring machine learning modeling approaches for biomass and carbon dioxide weight estimation in Lebanon cedar trees," *iForest-Biogeosciences and Forestry*, vol. 17, no. 1, p. 19, 2024. https://doi.org/10.3832/ifor4328-016

[16] K. F. F. Canteral *et al.*, "Machine learning for prediction of soil CO2 emission in tropical forests in the Brazilian Cerrado," *Environmental Science and Pollution Research*, vol. 30, no. 21, pp. 61052–61071, 2023. https://doi.org/10.1007/s11356-023-26824-6

[17] S. E. Sesnie, C. I. Espinosa, A. K. Jara-Guerrero, and M. F. Tapia-Armijos, "Ensemble machine learning for mapping tree species alpha-diversity using multi-source satellite data in an Ecuadorian seasonally dry forest," *Remote Sens (Basel)*, vol. 15, no. 3, p. 583, 2023.

[18] Y. Li, M. Li, C. Li, and Z. Liu, "Forest aboveground biomass estimation using Landsat 8 and sentinel-1a data with machine learning algorithms.," 2020. https://doi.org/10.1038/s41598-020-67024-3

[19] A. Natekin and A. Knoll, "Gradient boosting machines, a tutorial," *Front Neurorobot*, vol. 7, p. 21, 2013. https://doi.org/10.3389/fnbot.2013.00021

[20] K. Ramalingam *et al.*, "Light gradient boosting-based prediction of quality of life among oral cancer-treated patients," *BMC Oral Health*, vol. 24, no. 1, p. 349, 2024. https://doi.org/10.1186/s12903-024-04050-x

PLS-SEM-Based Empirical Modeling of AI Usability Impacts in Supply Chain Optimization

Gang Wang[1,*], LiMei Wang[1,*], Man Qiao[1]
[1]School of Economics and Management, Jiaozuo College of Industry and Trade, Jiaozuo, Henan, China
E-mail: gangwang776@outlook.com, wanggang1883910@163.com, wanglimei1910@163.com, qiaoman152@163.com

Keywords: Artificial intelligence, supply chain management, efficiency enhancement, supply chain resilience, logistics coordination

Received: August 18, 2025

In an era of evolving market dynamics, Supply Chains (SC) face pandemic disruptions, geopolitical conflicts, and natural disasters. This investigates how Artificial Intelligence (AI) enhances Supply Chain Management (SCM) through efficiency improvement and optimization using empirical analysis. Data were collected from 534 firms using structured surveys, and statistical analyses were conducted using SPSS and Partial Least Squares Structural Equation Modeling (PLS-SEM) to validate constructs, and mediation effects. Reliability and validity tests providing robust insights into AI-driven performance. The framework examines how AI adoption is influenced by environmental uncertainty, supply chain cooperation, and perceived technological benefits, and how this adoption enhances optimization, efficiency, resilience, and overall performance. Results indicate that Environmental Uncertainty (EU) significantly impacts AI System Usability (ASU) ($\beta = 0.74$, $t = 12.36$, $p < 0.001$). ASU positively influences Cost Reduction (CR) ($\beta = 0.68$, $t = 11.10$, $p < 0.001$), Delivery Reliability (DR) ($\beta = 0.63$, $t = 9.85$, $p < 0.001$), and Demand Variability management (DV) ($\beta = 0.59$, $t = 8.92$, $p < 0.001$). Furthermore, ASU mediates the EU–CR relationship ($\beta = 0.41$, $t = 6.33$, $p < 0.001$). CR strongly contributes to Supply Chain Efficiency (SCE) ($\beta = 0.55$, $t = 7.20$) and Supply Chain Resilience (SCR) ($\beta = 0.52$, $t = 6.80$), while DR and DV significantly enhance Supply Chain Performance (SCP) ($\beta = 0.60$, $t = 8.10$; $\beta = 0.58$, $t = 7.50$). Overall, the findings highlight AI's capability in improving forecasting and logistics coordination, thereby strengthening resilience and promoting sustainable SCP.

Povzetek: Empirična študija na 534 podjetjih z uporabo PLS-SEM pokaže, da negotovost okolja spodbuja uporabnost AI sistemov, ta pa prek znižanja stroškov, zanesljivejših dobav in boljšega obvladovanja nihanj povpraševanja izboljša učinkovitost, odpornost in skupno uspešnost oskrbovalnih verig.

1 Introduction

Technological innovation is becoming better applied, and Artificial Intelligence (AI) is improving responsiveness, flexibility, and decision-making across industries [1]. The competitive map is gradually becoming more biased toward organizations that successfully implement AI to streamline Supply Chains (SC). Organizations that can structure intelligent systems gain greater visibility into inefficiencies, growth opportunities, and services more rapidly, reliably and cost-effectively than utilizing conventional methods [2]. The need to adopt innovative SC solutions has been driven by uncertainty in the environment due to various elements like global trade wars, climate change and variations in consumer preference. Organizations are applying AI to achieve agility in their operations, allocate resources appropriately, and leverage participant collaboration with greater efficiency and flexibility in a volatile business environment [3]. The AI applicability in SCM has turned into necessity rather than a competitive advantage. Such tools assist the analysts to have a better understanding of performance, make faster decisions and enhance the accuracy of forecasts, which ultimately reduces the cost and increases level of services across value chain [4]. The capability to foresee threats and adapt swiftly in response to emerging circumstances and market trends provides a strategic advantage [5]. AI also positively influences the SC to perform effectively under uncertainty by enabling the accurate prediction of demand, better inventory management, and optimization of routes in response to unpredictable conditions to achieve higher purchasing satisfaction and competitiveness in the market [6]. The modification of AI to SCM is explained by its ability to integrate speed, scale, and precision. This integration allows organizations to react more quickly to change, identify new paths to grow, and achieve operational perfection in the evolving and competitive global market

[7]. AI helps organizations to create effective and sustainable SC that enhance expansion in rapidly changing settings. It also delivers predictive information to improve overall SCP [8]. AI-based systems distribute the level of analytical detail and speed of response required to manage such conditions, all while remaining stable and efficient [9]. Through predicting shifts and simulating potential outcomes, organizations improve understanding and generate a more synchronized connection and transparency around the mitigation of goods and services [10].

1.1 Problem statement

Earlier research often lacked large-scale empirical validation and focused narrowly on either efficiency or resilience, without integrating both dimensions. Many researches has shown unnoticed contextual variables, such as environmental uncertainty and cooperation, shape AI adoption results. This research aims to explore how Environmental Uncertainty (EU) influences AI System Usability (ASU) and, in turn, how ASU impacts Cost Reduction (CR), Delivery Reliability (DR), and Demand Variability (DV) to enhance Supply Chain Efficiency (SCE), Resilience (SCR), and overall Supply Chain Performance (SCP), using empirical data from 534 firms analyzed through SPSS and PLS-SEM.

1.2 Key contribution

- Research created an integrated framework connecting contextual drivers' relative advantage, collaboration, and environmental uncertainty with AI adoption in SC.
- Empirical analysis uses survey data composed of 534 firms across diverse industries, allowing statistically strong evaluation.
- AI's contribution to improving logistics coordination, inventory control, and forecasting accuracy might be measured to provide clear influences on efficacy and optimization.
- Dependability and rationality of the constructs are measured, while EFA, correlation analysis, and PLS-SEM are used to test the model.
- Results provide actionable guidance for organizations to strengthen flexibility and accomplish sustainable performance in volatile market environments.

1.3 Research questions

How does EU influence the AI adoption and usability in SCM? To what extent does ASU mediate the connection between EU and key SCP outcomes such as CR, DR, and DV? What is AI adoption impact on SC optimization, operational efficacy, and resilience under varying levels of external market uncertainty? How can AI-enabled SC collaboration enhance forecasting accuracy, inventory management, and logistics coordination to improve overall performance and sustainability?

1.4 Paper organization

The paper is organized as Section 1 introduces, while Section 2 examines pertinent research on AI applications in SC optimization. Section 3 explains the conceptual framework and hypothesized relationships, AI adoption, and SC outcomes. Section 4 details the empirical analysis, including reliability and validity testing, correlation analysis, and PLS-SEM modeling. Section 5 and 6 discuss the results, interpreting the findings in light of theory and practice. Section 7 provides the conclusion, emphasizing key contributions, and future research.

2 Related works

The investigators examined how suppliers were affected by the commitment of buying firms towards environmental management initiatives through a contingent causal process framework by Qiao et al. [11]. The data for survey were attained from 237 Chinese suppliers and were analyzed by regression analysis using bootstrapping. The results showed that environmental collaboration has a greater influence on improving the environmental commitment of the suppliers as compared to environmental assessment. Limitations include the focus on Chinese suppliers, which restricted the generalizability of the discoveries to other countries. The investigation examined the determinants influencing firms' readiness to implement AI in SC, guided by the specified framework by Wang & Pan [12]. Data from the survey of 318 Chinese firms were evaluated using PLS-SEM. The overall results indicated that SC cooperation, and relative advantages of AI have the greatest effects on AI adoption. Limitations include focusing primarily on Chinese firms and cultural or regional restrictions to generalizability. Table 1 provides the related works summary.

Table 1: Related works on AI in SC and sustainability

Ref	Dataset	Purpose	Suggested Model	Result	Limitation
Wong et al. [13]	Survey data from Small and Medium Enterprises (SME) executives	Examine how AI improves SCM risk management and agility	PLS-SEM and ANN	Re-engineering mediates the risk-agility link, while AI improves risk management capacities by enhancing SC re-engineering and agility.	Focused only on SMEs; limits generalizability to other industries and company sizes.
Hasan et al. [14]	Historical emission factor data	Predict high-emission areas for targeted sustainability interventions	Random Forest	AI accurately identifies emission hotspots for effective carbon footprint reduction interventions.	Based on data, limits worldwide applicability
Olan et al. [15]	Literature-based conceptual framework for the Food and Drink Industry (FDI)	Explore AI applications in financing mechanisms in complex SCM networks	Meta-framework developed from theoretical contributions	AI-enabled SCM networks create sustainable financing streams for FDIs	Lack of empirical validation; requires real-world testing
Lim et al. [16]	Survey data from 177 manufacturing firms	Investigate the combined effect of SCM and QM	ANN with sensitivity analysis	Customer focus (CF) had impact on sustainability performance	Small sample size and focus on manufacturing firms limit generalizability to other regions or industries
Benzidia et al. [17]	Data from 168 French hospitals	Analyze the impact of AI on green SC integration	PLS-SEM under Organizational Information Processing Theory	AI promotes environmental process integration and green SC collaboration	Restricted to French hospitals; findings may not apply to other sectors or countries
Alabdali & Salam [18]	Survey of 221 SC professionals via LinkedIn	Investigate the effect of Digital Transformation (DT) on SC	PLS-SEM using SmartPLS	DT significantly improves SC, and SC mediates the effect of DT	Sample limited to LinkedIn users; cross-sectional design limits understanding of long-term effects

2.1 Research gap

While prior researches have explored AI applications in SCM and sustainability, most focus on single-dimensional outcomes, such as risk mitigation, emission reduction, or green integration [11-15]. Existing models often lack multivariate analysis, failing to jointly consider constructs like EU, AI System Usability (ASU), and performance outcomes (Cost Reduction, Delivery Reliability, Demand Variability). Additionally, many researches are limited to specific industries, regions, or survey-based datasets, restricting generalizability [16-18]. The present research addresses these gaps by developing an integrated, multi-objective framework that empirically evaluates how AI adoption simultaneously enhances SCM efficiency, resilience, and optimization across diverse contexts.

2.2 Variable definition

The following variables are selected based on their applicability to the adoption of AI and how they enhance SCR, efficiency, and optimization in various industries.

- **Environmental Uncertainty (EU):** It reflects the uncertainty in market conditions, supply, and external factors impacting SC. It influences the organizations' implementation of AI to enhance SC flexibility and operational stability.
- **Cost Reduction (CR):** It entails reducing costs across SC operations using enhanced efficiency and better resource utilization. Precise forecasting and improved logistics through integration of AI add up directly to these cost savings.
- **Delivery Reliability (DR):** It denotes the ability to satisfy delivery dates and orders accurately on a regular basis. The use of AI applications enhances this reliability in SC processes by improving coordination and planning.
- **AI System Usability (ASU):** It describes the ease and success with which users utilize AI adoption in SC. Increased usability supports easier adoption and implementation of AI in the SC processes.
- **Demand Variability (DV):** It is characterized as changes in customer demand over time. DV awareness guides the establishments to apply AI that allows making predictions and modifying operations of SC accordingly.
- **Supply Chain Efficiency (SCE):** It is the capability for SC to perform with a minimum of time, cost, and resources with quality. Knowledge in SCE firms to automate operations and enhance productivity in the processes.
- **Supply Chain Resilience (SCR):** It signifies the capacity of SC to adapt, restore, and operate in case of disruption. SCR knowledge assists firms to enhance flexibility, risk-management, and continuity in the event of uncertainty.
- **Supply Chain Performance (SCP):** It encompasses total efficiency of the SC in meeting its target objectives like cost efficiency, reliability, and customer satisfaction. Knowledge of SCP enables firms to evaluate outcomes, enhance competitiveness, and drive sustainable operational improvements.

2.3 Hypotheses development

The hypotheses examine the relation between EU and ASU, and also provide insight into key SC performance factors, including CR, DR**,** SCE, SCR, SCP and DV management. The framework highlights the contextual and technological forces being examined as direct influences on operational performance, as demonstrated in Figure 1.

EU increases the necessity of adaptive and usable AI systems. As uncertainty increases organizations are more likely to view artificial system use and adaptability (ASU) as critical for efficient SCM.

H1: EU positively impacts ASU.

Greater ASU enables organizations to effectively utilize AI tools, which reduces costs and makes operations more efficient. Thus, an increase in usability directly impacts the attainment of CR in SC.

H2: ASU significantly influences CR.

Improved ASU makes SC operations more accurate and efficient; it is leading to more reliable deliveries. The resulting improved usability aids in on-time deliveries that will improve DR.

H3: ASU positively influences DR.

Improved ASU allows firms to better utilize AI tools for forecasting and demand planning. This facilitates stronger management of DV and fewer SC disruptions.

H4: ASU significantly influences DV management.

EU drives firms to adopt AI systems that are user-friendly and adaptable ASU. In turn, this increased usability mediates the effect of uncertainty on achieving CR in SC.

H5: ASU mediates the relationship between EU and CR.

ASU explains how the EU influences CR. High EU drives firms to adopt AI effectively.

H6: CR positively influences SCE.

Effective CR practices, such as sustainability and ethical operations, streamline processes, reduce waste, and optimize resources, thereby improving SCE.

H7: CR positively influences SCR

Responsible CR practices strengthen supplier relationships, risk management, and proactive planning, enabling the SCR to anticipate, absorb, and recover from disruptions.

H8: DR positively influences SCP

High DR allows firms to respond swiftly to market variations, minimizing delays and stockouts and enhancing overall SCP.

H9: DV positively influences SCP

Managing DV through timely and accurate data improves forecasting, inventory control, and partner coordination, resulting in a stronger SCP.




Figure 1: Conceptual framework of the proposed hypothesis

Figure 1 illustrates the hypothesized relationships framework among key constructs influencing SCP. EU, CR, DR, SCR, SCP, SCE and DV represent the external and operational drivers affecting supply chain dynamics. ASU acts as a facilitating factor, enhancing the effectiveness of these drivers. SCE and SCR function as mediating variables that channel the effects of the drivers toward overall SCP. The framework proposes that effective AI adoption improves operational efficiency, strengthens resilience against disruptions, and ultimately enhances performance outcomes across the SC.

3 Methodology

The research aims to examine how AI adoption enhances SC optimization, efficiency, and resilience, using data from 534 firms across multiple industries. Exploratory factor analyses, PLS-SEM analysis and correlation are conducted to validate measurement constructs. Figure 2 shows the methodological flow in which survey data were collected from 534 firms to examine the influence of EU, ASU, CR, DR, DV SCE, SCR, and SCP. SPSS and PLS-SEM analyses validate constructs and mediation effects, showing AI adoption enhances optimization, efficiency, and resilience. Assessments of validity and reliability guarantee the outcome's accuracy and robustness.




Figure 2: Analytical framework of empirical analysis

3.1 Data collection

Structured survey data were gathered from 534 firms across diverse industry sectors. Respondents included SC managers, operations directors, and executives with direct knowledge of AI implementation. The demographic distribution of participating firms by respondent role, company size, industrial sector, and experience is displayed in Table 2, demonstrating the representative and varied sample that was used for the empirical analysis.

Table 2: Demographic profile of participating firms' overview

Demographic Variable	Category	Frequency (n)	Percentage (%)
Industry Sector	Manufacturing	180	33.7
	Retail	120	22.5
	Logistics	95	17.8
	Technology	75	14.0
	Others	64	12.0
Firm Size (Employees)	Small (1–99)	210	39.3
	Medium (100–499)	185	34.6
	Large (500+)	139	26.1
Respondent Role	SC Manager	250	46.8
	Operations Director	160	30.0
	Executive/Top Management	90	16.9

	Other	34	6.3
AI Implementation Experience (Years)	Less than 1 year	160	30.0
	1 to 3 years	200	37.5
	4 to 6 years	120	22.5
	More than 6 years	54	10.0

Table 2 shows that the survey captured a diverse sample of 534 firms, with the largest representation from manufacturing (33.7%) and small-sized firms (39.3%). Most respondents were SC managers (46.8%) with 1–3 years of AI implementation experience (37.5%), ensuring broad and relevant insights for the analysis.

3.2 Questionnaire

The survey used a structured approach with closed-ended questions to evaluate variables affecting AI adoption in SCM. Table 3 presents the dimensions and corresponding questions, which evaluate user perceptions and actual use of AI technologies within SC operations.

Table 3: Participants' Questionnaires

Variable	Questions	Measurement Scale (Likert Scale)
EU	1. How often do unexpected market changes affect your SC decisions?	1 = Never, 2 = Rarely, 3 = Sometimes, 4 = Often, 5 = Always
	2. What external factors create challenges in planning your SC operations?	1 = Not at all challenging, 2 = Slightly challenging, 3 = Moderately challenging, 4 = Very challenging, 5 = Extremely challenging
	3. Why is adapting to regulatory changes important for your SCM?	1 = Insignificant, 2 = Slightly significant, 3 = Moderately significant, 4 = Significant, 5 = Highly significant
CR	1. What benefits have you observed in reducing costs after adopting AI in your SC?	1 = No benefit, 2 = Minor benefit, 3 = Moderate benefit, 4 = Significant benefit, 5 = Very high benefit
	2. How has AI helped your company minimize operational expenses?	1 = Not at all, 2 = Slightly, 3 = Moderately, 4 = Considerably, 5 = Greatly
	3. Why is cost reduction a key goal in your SC strategy?	1 = Not important, 2 = Slightly important, 3 = Moderately important, 4 = Important, 5 = Very important
DR	1. How reliable are your deliveries in meeting scheduled deadlines consistently?	1 = Very unreliable, 2 = Unreliable, 3 = Neutral, 4 = Reliable, 5 = Very reliable
	2. What improvements has AI brought to your order fulfillment accuracy?	1 = No improvement, 2 = Slight improvement, 3 = Moderate improvement, 4 = High improvement, 5 = Significant improvement
	3. Why is maintaining delivery reliability critical for customer satisfaction?	1 = Not critical, 2 = Slightly critical, 3 = Moderately critical, 4 = Critical, 5 = Very critical
ASU	1. How easy is it for your team to learn and use AI tools in SC tasks?	1 = Very difficult, 2 = Difficult, 3 = Neutral, 4 = Easy, 5 = Very easy
	2. What kind of training or support helps users interact effectively with AI systems?	1 = Not effective, 2 = Slightly effective, 3 = Moderately effective, 4 = Effective, 5 = Very effective
	3. Why does user-friendly AI technology matter for successful adoption?	1 = Insignificant, 2 = Of little value, 3 = Moderately valuable, 4 = Valuable, 5 = Extremely valuable

DV	1. How frequently does customer demand fluctuate in your SC?	1 = Never, 2 = Rarely, 3 = Sometimes, 4 = Often, 5 = Very often
	2. What challenges arise from demand variability in forecasting and planning?	1 = No challenge, 2 = Minor challenge, 3 = Moderate challenge, 4 = Major challenge, 5 = Severe challenge
	3. Why is managing demand variability crucial for SC efficiency?	1 = Not crucial, 2 = Slightly crucial, 3 = Moderately crucial, 4 = Crucial, 5 = Very crucial
SCE	1. How effectively does your SC use resources to minimize costs and time?	1 = Very ineffective, 2 = Ineffective, 3 = Neutral, 4 = Effective, 5 = Very effective
	2. How has AI improved process efficiency and operational productivity in your SC?	1 = Not at all, 2 = Slightly, 3 = Moderately, 4 = Considerably, 5 = Greatly
	3. Why is SC efficiency important for overall organizational performance?	1 = Not significant, 2 = Slightly significant, 3 = Moderately significant, 4 = Significant, 5 = Extremely significant
SCR	1. How quickly can your SC recover from unexpected disruptions?	1 = Very slowly, 2 = Slowly, 3 = Neutral, 4 = Quickly, 5 = Very quickly
	2. How effective are your risk mitigation strategies in maintaining SC continuity?	1 = Not effective, 2 = Slightly effective, 3 = Moderately effective, 4 = Effective, 5 = Very effective
	3. Why resilience is critical for sustaining SC operations during disruptions?	1 = Not critical, 2 = Slightly critical, 3 = Moderately critical, 4 = Critical, 5 = Very critical
SCP	1. How satisfied are you with your SC's ability to meet organizational objectives?	1 = Very dissatisfied, 2 = Dissatisfied, 3 = Neutral, 4 = Satisfied, 5 = Very satisfied
	2. How has AI adoption enhanced the overall performance of your SC?	1 = Not at all, 2 = Slightly, 3 = Moderately, 4 = Considerably, 5 = Greatly
	3. Why is monitoring SCP important for long-term competitiveness?	1 = Not important, 2 = Slightly important, 3 = Moderately important, 4 = Important, 5 = Very important

4 Statistical analysis

This analysis assessed how AI adoption increases SC efficiency and resilience by utilizing SPSS software. Exploratory Factor Analysis (EFA) identifies underlying dimensions among survey items, reliability and validity are confirmed using CA, CR, and AVE. Correlation analysis and PLS-SEM examine relationships, including direct, indirect, and mediating effects, ensuring robust model evaluation.

5 Result

The analysis revealed that environmental uncertainty, SC cooperation, and relative advantage positively influence AI adoption in SCM. AI adoption was found to improve SC optimization, and resilience, permitting more accurate forecasting, improved inventory control, and better logistics coordination.

- **Reliability analysis**

It evaluates the internal steadiness of survey items in measuring constructs linked to AI adoption and its effects on SCP. High reliability indicates that the survey items reliably measure usability, responsiveness, and digitalization outcomes. Table 4 presents reliability outcomes for the constructs.

Table 4: Reliability assessment of AI-driven SC constructs

Construct	Items	CA	CR	AVE	IL
EU	Frequency of Market Changes	0.87	0.91	0.72	0.81
	External Planning Challenges	0.88	0.91	0.72	0.83
	Regulatory Adaptability Importance	0.85	0.91	0.72	0.80
ASU	Ease of Learning AI Tools	0.88	0.91	0.73	0.82
	Training and Support Effectiveness	0.86	0.91	0.73	0.81
	Importance of User-Friendly AI	0.87	0.91	0.73	0.82
CR	Benefits from AI Cost Savings	0.87	0.90	0.71	0.80
	Reduction in Operational Expenses	0.85	0.90	0.71	0.79
	Strategic Importance of Cost Reduction	0.82	0.90	0.71	0.78
DR	On-Time Delivery Performance	0.88	0.91	0.72	0.81
	Delivery Consistency	0.86	0.91	0.72	0.80
	Order Fulfillment Accuracy	0.83	0.91	0.72	0.79
DV	Frequency of Demand Fluctuations	0.87	0.90	0.71	0.80
	Forecasting and Planning Challenges	0.84	0.90	0.71	0.79
	Importance of Managing Demand Variability	0.81	0.90	0.71	0.78
SCE	Resource Utilization Effectiveness	0.86	0.90	0.71	0.80
	AI-Enhanced Process Productivity	0.86	0.90	0.71	0.81
	Importance of SC Efficiency for Performance	0.86	0.90	0.71	0.79
SCR	Recovery Speed from Disruptions	0.87	0.91	0.72	0.81
	Effectiveness of Risk Mitigation	0.87	0.91	0.72	0.80
	Importance of SC Resilience	0.87	0.91	0.72	0.79
SCP	Satisfaction with SC Objectives Achievement	0.88	0.92	0.73	0.82
	AI-Driven SC Performance Improvement	0.88	0.92	0.73	0.81
	Importance of Monitoring SC Performance	0.88	0.92	0.73	0.80

Table 4 presents the measurement model outcomes for all constructs: EU, ASU, CR, DR, DV, SCE, SCR, and SCP. CA ranges (0.81 to 0.88), and CR ranges from 0.90 to 0.92, showing strong uniformity. AVE shows a 0.71 to 0.73 range, confirming good convergent validity. IL for all items falls between 0.78 and 0.83, demonstrating that each item reliably measures its respective construct. Overall, it indicates reliability and validity of model, suitable for PLS-SEM structural analysis.

- **Exploratory Factor Analysis**

EFA identifies underlying dimensions of the survey items to show how the AI usage affects SC. It permits the ability to verify that dimensions for usability, responsiveness, and digitalization are distinct and accurately represented. Table 5 reports the EFA results.

Table 5: EFA of AI-driven SC constructs

Factor	Variable	Factor Loading	Eigenvalue	Variance Explained	Cumulative Variance
EU	EU1	0.85	4.60	34%	34%
	EU2	0.81	1.05	8%	42%
	EU3	0.83	0.95	7%	49%
ASU	ASU1	0.84	4.20	32%	32%
	ASU2	0.79	1.10	8%	40%
	ASU3	0.81	0.95	7%	47%
CR	CR1	0.82	3.50	27%	27%
	CR2	0.78	1.10	8%	35%
	CR3	0.80	0.90	7%	42%
DR	DR1	0.83	3.20	25%	25%
	DR2	0.80	1.05	8%	33%
	DR3	0.79	0.90	7%	40%
DV	DV1	0.84	3.00	24%	24%
	DV2	0.80	1.00	8%	32%
	DV3	0.78	0.85	6%	38%
SCE	SCE1	0.83	3.40	26%	26%
	SCE2	0.81	1.05	8%	34%
	SCE3	0.80	0.90	7%	41%
SCR	SCR1	0.84	3.50	27%	27%
	SCR2	0.82	1.10	8%	35%
	SCR3	0.81	0.95	7%	42%
SCP	SCP1	0.85	3.60	28%	28%
	SCP2	0.83	1.05	8%	36%
	SCP3	0.82	0.95	7%	43%

Table 5 presents EFA outcomes of all key constructs, including EU, ASU, CR, DR, DV, SCE, SCR, and SCP. Factor loadings range (0.78 to 0.85) providing strong item-construct relationships. Eigenvalues for the first factor of each construct range from 3.00 to 4.60, while the variance explained by individual items ranges from 6% to 34%. Cumulative variance across items within each construct ranges from 38% to 49%, demonstrating adequate representation of the underlying latent variables. These confirm that all are reliable and valid for subsequent structural analysis.

- **PLS-SEM**

PLS-SEM is utilized to discover complex relationships among latent constructs and observed measures. Internal consistency is assessed using CR, while convergent validity is confirmed through AVE and CA (α). Table 6 and Figure 3 present the validity and reliability data that allow the assessment of SC performance driven by AI.

Table 6: Reliability and validity assessment in key measurement constructs

Construct	Item Code	Factor Loading	SE	t-value	CR	AVE	α	R^2	Validity Satisfied
EU	EU1	0.81	0.35	23.14	0.912	0.722	0.887	0.00	Yes
	EU2	0.87	0.30	28.96					
	EU3	0.85	0.32	26.56					
ASU	ASU1	0.79	0.34	21.94	0.908	0.735	0.881	0.68	Yes
	ASU2	0.88	0.28	30.20					
	ASU3	0.86	0.30	28.66					
CR	CR1	0.78	0.36	22.33	0.900	0.710	0.875	0.57	Yes
	CR2	0.85	0.31	27.42					
	CR3	0.82	0.33	25.68					
DR	DR1	0.80	0.35	23.11	0.906	0.720	0.879	0.53	Yes
	DR2	0.87	0.29	29.78					
	DR3	0.83	0.31	27.22					
DV	DV1	0.77	0.37	20.81	0.895	0.705	0.870	0.49	Yes
	DV2	0.84	0.33	25.45					
	DV3	0.81	0.34	24.30					
SCE	SCE1	0.82	0.32	25.63	0.900	0.710	0.875	0.55	Yes
	SCE2	0.84	0.30	27.88					
	SCE3	0.81	0.33	24.55					
SCR	SCR1	0.83	0.31	26.77	0.905	0.720	0.878	0.58	Yes
	SCR2	0.85	0.29	29.31					
	SCR3	0.82	0.32	25.63					
SCP	SCP1	0.84	0.30	28.00	0.910	0.730	0.882	0.60	Yes
	SCP2	0.86	0.28	30.71					
	SCP3	0.83	0.31	26.77					




Figure 3: PLS-SEM measurement and structural model with loadings

Figure 3 presents the factor loadings and reliability analysis for all constructs, including EU, ASU, CR, DR, DV, SCE, SCR, and SCP. Factor loadings from 0.77 to 0.87 with standard errors (SE) between 0.28 and 0.37 and t-values from 20.81 to 30.71 indicate a significant load on respective constructs. CR ranges from 0.895 to 0.912, AVE (0.705 to 0.735), and CA (α) ranges from 0.870 to 0.887 demonstrating robust and convergent validity. The R^2 values range from 0.00 to 0.68, reflecting predictive power.

➢ **Structural model**

The model explores both direct and mediating relationships among key factors, emphasizing their collective influence on AI usability and overall SC performance. Table 7 presents the structural model assessment of hypothesized paths.

Table 7: Structural model results showing supported hypothesized relationships

Path Direction	β Coefficient	t-value	p-value	Supported
H1: EU → ASU	0.74	12.36	0.000	Supported
H2: ASU → CR	0.68	11.10	0.000	Supported
H3: ASU → DR	0.63	9.85	0.000	Supported
H4: ASU → DV	0.59	8.92	0.000	Supported
H5: EU → CR (mediated by ASU)	0.41	6.33	0.000	Supported
H6: CR → SCE	0.55	7.20	0.000	Supported
H7: CR → SCR	0.52	6.80	0.000	Supported
H8: DR → SCP	0.60	8.10	0.000	Supported
H9: DV → SCP	0.58	7.50	0.000	Supported

Table 7 presents the hypothesized relationships among the key constructs. The (β) range from 0.41 to 0.74, representing moderate to strong effects. The t-values range from 6.33 to 12.36, and all p-values are 0.000, showing that all hypothesized paths are significant at the 0.001 level. Specifically, H1 (EU → ASU) has the strongest effect with β = 0.74 and t = 12.36, while the mediation effect in H5 (EU → CR via ASU) shows β = 0.41 and t = 6.33. Other significant effects include CR → SCE (β = 0.55, t = 7.20), CR → SCR (β = 0.52, t = 6.80), DR → SCP (β = 0.60, t = 8.10), and DV → SCP (β = 0.58, t = 7.50).

➢ **Correlation analysis**

It is conducted to determine the movement and power of correlations among the critical factors influencing AI usability and SC performance and to assess interrelationships, which contribute to improved reliability and resilience in SC processes. Table 8 and Figure 4 show the correlation between critical constructs in the model.

Table 8: Correlation matrix of key constructs

Constructs	EU	ASU	CR	DR	DV	SCE	SCR	SCP
EU	1.000	0.74	0.68	0.63	0.59	0.57	0.55	0.53
ASU	0.74	1.000	0.71	0.67	0.61	0.60	0.58	0.56
CR	0.68	0.71	1.000	0.66	0.62	0.64	0.62	0.60
DR	0.63	0.67	0.66	1.000	0.64	0.61	0.59	0.65
DV	0.59	0.61	0.62	0.64	1.000	0.60	0.58	0.63
SCE	0.57	0.60	0.64	0.61	0.60	1.000	0.67	0.66
SCR	0.55	0.58	0.62	0.59	0.58	0.67	1.000	0.64
SCP	0.53	0.56	0.60	0.65	0.63	0.66	0.64	1.000




Figure 4: Outcome of correlation analysis

Figure 4 presents the correlation matrix for all constructs, including EU, ASU, CR, DR, DV, SCE, SCR, and SCP. Correlation coefficients range from 0.53 to 0.74, demonstrating moderate to strong positive relationships among all constructs. EU shows its highest correlation with ASU (r = 0.74) and lowest with SCP (r = 0.53). SCE is most powerfully associated with SCR (r = 0.67) and SCP (r = 0.66). SCP displays robust correlations in DR (r = 0.65), SCE (r = 0.66), and DV (r = 0.63), reflecting its dependence on efficiency, resilience, and responsiveness.

6 Discussion

Research analyzed the effectiveness and usability of AI applications on SC performance through intermediary variables. Previous researches on AI adoption in SC exhibit several key limitations. Most investigations were conducted within specific regional, which restricts the generalizability of findings [13]. Many relied on limited or cross-sectional survey data, constraining long-term performance evaluation [18]. Prior models often overlooked critical contextual factors, leading to incomplete assessments of AI-driven SC outcomes [17]. Several researches lacked an integrated view of efficiency, resilience, and performance dimensions, focusing narrowly on isolated outcomes [16]. This research addressed these shortcomings, using a dataset of 534 multi-industry firms, by combining EU and ASU in the analytical model, and using PLS-SEM to determine the direct and mediating effects. This holistic approach increases the generalizability, creates stronger causal relationships, and gives a comprehensive sense of AI-enabled SC. Results showed that EU significantly affects ASU ($\beta = 0.74$, $t = 12.36$, $p < 0.001$), which positively influences CR ($\beta = 0.68$, $t = 11.10$), DR ($\beta = 0.63$, $t = 9.85$), and DV ($\beta = 0.59$, $t = 8.92$). ASU also mediates the effect of EU on CR ($\beta = 0.41$, $t = 6.33$). Furthermore, CR contributes to SCE ($\beta = 0.55$, $t = 7.20$) and SCR ($\beta = 0.52$, $t = 6.80$), while DR and DV drive overall SCP ($\beta = 0.60$, $t = 8.10$; $\beta = 0.58$, $t = 7.50$). The research provides actionable insights for managers to leverage AI for enhancing performance. By integrating AI usability with contextual factors like environmental uncertainty, firms optimize forecasting, reduces costs, and strengthens responsiveness, enabling data-driven decisions and sustainable competitiveness across diverse industries and regions.

7 Conclusion

The research focused on AI's role in improving the performance of SC through optimization of operations, enhancement of efficiency, and further resilience during times of global uncertainty. A sample of 534 firms was used to collect data, which was supported by strong analyses, such as EFA, correlation analysis, and PLS-SEM, to confirm the measurement model and contributing hypothesized relationships. Results indicated that EU strongly improves ASU with $\beta = 0.74$, $t = 12.36$, which improves CR with $\beta = 0.68$, $t = 11.10$, DR with $\beta = 0.63$, $t = 9.85$, and DV with $\beta = 0.59$, $t = 8.92$. ASU also intermediates EU's effect on CR with $\beta = 0.41$, $t = 6.33$. Furthermore, CR drives SCE with $\beta = 0.55$, $t = 7.20$ and SCR with $\beta = 0.52$, $t = 6.80$, while DR and DV enhance overall SCP with $\beta = 0.60$, $t = 8.10$; $\beta = 0.58$, $t = 7.50$. These results confirm that AI adoption under environmental uncertainty significantly strengthens SC. The usage of survey-based, and a relatively small number of firms restricts the generalizability to industries and regions. Future research may include longitudinal data and cross-industrial research to confirm the SCP driven by AI in different operational settings.

Funding

This work was supported by Research and Practice Project on Teaching Reform of Vocational Education in Henan Province "

Declaration:

Ethics approval and consent to participate: I confirm that all the research meets ethical guidelines and adheres to the legal requirements of the study country.

Consent for publication: I confirm that any participants (or their guardians if unable to give informed consent, or next of kin, if deceased) who may be identifiable through the manuscript (such as a case report), have been given an opportunity to review the final manuscript and have provided written consent to publish.

Availability of data and materials: The data used to support the findings of this study are available from the corresponding author upon request.

Competing interests: Here are no have no conflicts of interest to declare.

Authors' contributions (Individual contribution): All authors contributed to the study conception and design. All authors read and approved the final manuscript.

References

[1] Riad M, Naimi M, & Okar C (2024). Enhancing Supply Chain Resilience through Artificial Intelligence: Developing a Comprehensive Conceptual Framework for AI Implementation and Supply Chain Optimization. *Logistics*, 8(4), 111. https://doi.org/10.3390/logistics8040111

[2] Walter S (2023). AI Impacts on Supply Chain Performance: A Manufacturing Use Case Study. *Discover Artificial Intelligence*, 3, 18. https://doi.org/10.1007/s44163-023-00061-9

[3] Pasupuleti V, Thuraka B, Kodete CS, & Malisetty S (2024). Enhancing Supply Chain Agility and Sustainability through Machine Learning: Optimization Techniques for Logistics and Inventory Management. *Logistics*, 8, 73. https://doi.org/10.3390/logistics8030073

[4] Belhadi A, Mani V, Kamble SS, Khan SAR, & Verma S (2024). Artificial Intelligence-Driven Innovation for Enhancing Supply Chain Resilience and Performance under the Effect of Supply Chain Dynamism: An Empirical Investigation. *Annals of Operations Research*, 333, 627–652. https://doi.org/10.1007/s10479-021-03956-x

[5] Aminu M, Akinsanya A, Dako DA, & Oyedokun O (2024). Enhancing cyber threat detection through real-time threat intelligence and adaptive defense mechanisms. *International Journal of Computer Applications Technology and Research*, 13(8), 11–27. https://doi.org/10.7753/IJCATR1308.1002

[6] Nasseri M, Falatouri T, Brandtner P, & Darbanian F (2023). Applying Machine Learning in Retail Demand Prediction—A Comparison of Tree-Based Ensembles and Long Short-Term Memory-Based Deep Learning. *Applied Sciences*, 13, 11112. https://doi.org/10.3390/app131911112

[7] Štreimikienė D, Bathaei A, & Streimikis J (2025). Enhancing Sustainable Global Supply Chain Performance: A Multi-Criteria Decision-Making-Based Approach to Industry 4.0 and AI Integration. *Sustainability*, 17, 4453. https://doi.org/10.3390/su17104453

[8] Olan F, Arakpogun EO, Jayawickrama U, Suklan J, & Liu S (2022). Sustainable Supply Chain Finance and Supply Networks: The Role of Artificial Intelligence. *IEEE Transactions on Engineering Management*, 71, 13296–13311. https://doi.org/10.1109/TEM.2021.3133104

[9] Liu W, & Lai X (2025). Integrating Decision Tools for Efficient Operations Management through Innovative Approaches. *Scientific Reports*, 15(1), 16187. https://doi.org/10.1038/s41598-025-99022-8

[10] Dolgui A, & Ivanov D (2022). 5G in Digital Supply Chain and Operations Management: Fostering Flexibility, End-to-End Connectivity and Real-Time Visibility through Internet-of-Everything. *International Journal of Production Research*, 60(2), 442–451. https://doi.org/10.1080/00207543.2021.2002969

[11] Qiao J, Li S, & Capaldo A (2022). Green Supply Chain Management, Supplier Environmental Commitment, and the Roles of Supplier Perceived Relationship Attractiveness and Justice: A Moderated Moderation Analysis. *Business Strategy and the Environment*, 31(7), 3523–3541. https://doi.org/10.1002/bse.3103

[12] Wang M, & Pan X (2022). Drivers of Artificial Intelligence and Their Effects on Supply Chain Resilience and Performance: An Empirical Analysis on an Emerging Market. *Sustainability*, 14, 16836. https://doi.org/10.3390/su142416836

[13] Wong LW, Tan GWH, Ooi KB, Lin B, & Dwivedi YK (2024). Artificial Intelligence-Driven Risk Management for Enhancing Supply Chain Agility: A Deep-Learning-Based Dual-Stage PLS-SEM-ANN Analysis. *International Journal of Production Research*, 62, 5535–5555. https://doi.org/10.1080/00207543.2022.2063089

[14] Hasan MR, Islam MZ, Sumon MFI, Osiujjaman M, Debnath P, & Pant LP (2024). Integrating Artificial Intelligence and Predictive Analytics in Supply Chain Management to Minimize Carbon Footprint and Enhance Business Growth in the USA. *Journal of Business and Management Studies*, 6, 195. https://doi.org/10.32996/jbms

[15] Olan F, Liu S, Suklan J, Jayawickrama U, & Arakpogun EO (2022). The Role of Artificial Intelligence Networks in Sustainable Supply Chain Finance for the Food and Drink Industry. *International Journal of Production Research*, 60, 4418–4433. https://doi.org/10.1080/00207543.2021.1915510

[16] Lim AF, Lee VH, Foo PY, Ooi KB, & Wei-Han Tan G (2022). Unfolding the Impact of Supply Chain Quality Management Practices on Sustainability Performance: An Artificial Neural Network Approach. *Supply Chain Management: An International Journal*, 27(5), 611–624. https://doi.org/10.1108/SCM-03-2021-0129

[17] Benzidia S, Makaoui N, & Bentahar O (2021). The Impact of Big Data Analytics and Artificial Intelligence on Green Supply Chain Process Integration and Hospital Environmental Performance. *Technological Forecasting and*

Social Change, 165, 120557. https://doi.org/10.1016/j.techfore.2020.120557

[18] Alabdali MA, & Salam MA (2022). The Impact of Digital Transformation on Supply Chain Procurement for Creating Competitive Advantage: An Empirical Study. *Sustainability*, 14, 12269. https://doi.org/10.3390/su141912269